



PRELIMINARY, NOT FOR FABRICATION


REV	DESCRIPTION	DATE	BY
P1	Preliminary general arrangement (TRL 3)	2026-09-25	AC




TOP VIEW
Scale 1:20




FRONT VIEW (SIDE ELEVATION)
Scale 1:20




RIGHT VIEW (FROM LOW EDGE)
Scale 1:20



DETAIL B: LOW EDGE, DISTILLATE AND BRINE
Scale 1:2, untilted; wick tails not shown



DETAIL A: STACK SECTION AT A RIB
Scale 2:1, looking up the slope



ISOMETRIC VIEW
Not to scale

KEY DIMENSIONS AND FIGURES (SSK-CAL-001)

Aperture 1.0 x 1.0 m; tilt 20 deg, stand 10 to 35 deg
4 stages; 6 mm vapor gap; 1 mm wicks; 0.5 mm plates
Ribs: 4 per gap at 194 mm pitch; sag 0.5 mm
Dry breaks 10 mm each side of ribs and rails
Air gap 25 mm; 6 mm twin-wall PC glazing
Frame 12 mm plywood + 25 mm PIR; 1,074 mm square outside
Front pivot 350 mm; rear strut 530 to 940 mm
Design day: about 10.6 L/day, GOR about 1.3
Dry stagnation: stage 1 about 140 C
Panel about 16 kg dry, 20 kg wet
Wick tails (0.25 m) and fasteners not shown

STILLSTACK
General arrangement

DRAWING NO. SSK-DWG-002			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:20	UNITS mm	PROJECTION 	DATE 2026-09-25		DRAWN Amish Chadha
MATERIAL / NOTES See bom/bom.csv. Plates 0.5 mm aluminum; rails PC; ribs silicone; frame plywood and PIR					
Licensed CERN-OHL-S-2.0 · Open Hardware Portfolio · amishchadha.com			Generated from cad/src; do not edit by hand		