STUMPRIDER · PRECIS

StumpRider design precis

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	SMR-PRC-001	Version	0.6
Status	Draft	Date	2026-10-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/stumprider		
Source	docs/02-concept.md @ 6afbf98		

REVISION HISTORY

Version	Date	Author	Change
0.6	2026-10-25	Amish Chadha	Amish's decisions of 2026-10-25 (SMR-DEC-001 O6 to O9) written in; O10 back with Amish; bamboo local variant USD 66.90
0.5	2026-10-24	Amish Chadha	Kit 1.9.1 upgrade: this precis describes option A of the concept options SMR-OPT-001 (selection proposed, awaiting Amish); hook head J of 12 mm bar (SMR-DEC-001 F1); dynamic heel item O6; figures from SMR-CAL-001 v0.3; model detailed to D3 (cad/fidelity.json)
0.4	2026-10-03	Amish Chadha	Amish's decisions of 2026-10-03 (SMR-DDR-003); hook head, small-canoe rule, carried kit, bamboo local variant; figures from SMR-CAL-001 v0.2
0.3	2026-10-03	Amish Chadha	TRL 3; constructable design of SMR-DDR-002 and figures from SMR-CAL-001
0.2	2026-10-03	Amish Chadha	TRL 2 precis; how it works, components with BOM numbers, key

			design choices, first-order numbers, safety, open questions
0.1	2026-09-30	Amish Chadha	Initial scaffold

StumpRider design precis

Frees gillnets snagged on submerged trees from the canoe so children are not sent to dive.




Figure 1. The kit (concept render, CONCEPT, NOT FOR FABRICATION).

> **Safety:** StumpRider exists so that nobody enters the water. It must never be presented as a reason to keep children on boats, and it never replaces a life jacket. Working a snag pulls the canoe over; the shear pin breaks before a steady pull can heel the design canoe more than about 4 deg (a sudden jerk about 6.5 deg, so lift steadily), but small dugouts are not covered (see Safety). Stop and cut the net rather than risk a capsize.

This precis describes option A, the rider ring on a shear-pin pole, of the concept options in SMR-OPT-001. It is the design carried since TRL 2; its selection over options B (line-riding knocker weight) and C (grapnel cross-pull) was chosen by Amish on 2026-10-25 (SMR-DDR-005, SMR-DEC-001 O7). Its claims are checked in the STEM check SMR-STM-001.

How it works

The crew pulls the net line up over the gunwale crutch and holds it taut above the snag. The operator, kneeling near the bow, opens the gate of the rider ring, closes the ring round the line and pushes it down the line with the jointed pole until it seats on the branch. The crew then slackens the line and the operator lifts, twists and pushes the ring along the branch until the mesh lifts clear. The pole head grips the ring by a fork on a tang, joined only by a 2 mm soft aluminium shear pin; if the pull or push goes above about 300 N (67 lbf), the pin breaks and the pole comes away. The ring stays on the net line and is recovered on its tether cord, a new pin is fitted, and the operator tries a different angle. For snags beyond the pole's reach, the pole head is taken off, the jigging weight is pinned to the tang in its place, and the ring is run down the line on its tether and jigged, as angling retrievers do.

Components

Table 1. Components (numbers are BOM lines in `bom/bom.csv`).

#	Component	Role	Made or bought
1	Rider ring	Two half rings of 12 mm steel bar, 100 mm inside, with ears at each joint and a tang on the fixed half; closes round the net line and slides down it	Made: bent, welded, galvanised
2	Hinge bolt	M8 bolt with a nyloc nut; the swinging half turns on it	Bought
3	Gate pin	8 mm clevis pin, R-clip and lanyard; the only part removed to open the ring	Bought
4	Pole head	Steel socket on the pole with a fork that straddles the tang	Made: welded, galvanised
5	Shear pins	2.0 mm soft aluminium wire, 30 mm long; the safety link between fork and tang	Made: cut from one calibrated reel
6	Pole sections	Three 1.45 m lengths of 32 x 2 mm aluminium tube	Made: cut and drilled
7	Joint sleeves	200 mm of 38 mm tube riveted on the lower section of each joint	Made
8	Pop rivets	Fix the sleeves	Bought
9	Lock pins	6 mm clevis pins at the two joints, the head and the jigging weight	Bought
10	Grip cap	Rubber cap on the top of the pole	Bought
11	Tether cord	10 m of 6 mm braided polyester, tied to the tang	Bought
12	Float winder	Closed-cell foam winder that floats the ring and cord if dropped	Made
13	Spare pin tube	Keeps eleven spare pins dry	Bought
14	Jigging weight	1.1 kg steel weight pinned to the tang for snags beyond pole reach	Made: welded, galvanised
15	Gunwale crutch frame	Steel saddle clamped on the gunwale, with cheeks for the roller	Made: bent, welded, galvanised
16	Crutch roller and axle	HDPE roller on an M12 bolt; the net line runs over it	Made and bought
17	Crutch clamp screw	M10 screw with a pad; clamps gunwales 30 to 60 mm thick	Made
21	Hook head	12 mm steel J hook (the ring's stock, SMR-DEC-001 F1) butt welded to a flat that pins into the same fork; pulls a wrapped net back round the branch	Made: bent, welded, galvanised
V1, V2	Bamboo local variant pole	Three treated bamboo culms and two steel ferrules in place of lines 6, 7, 8 and 10 (`bom/bom-bamboo-variant.csv`)	Made

Key design choices

Each choice was made under Amish's 2026-10-03 pre-approval and is argued in SMR-DDR-001 (TRL 2 review) and SMR-DDR-002 (design for construction); the register is SMR-DEC-001.

- **A hinged ring, not a spring clip.** Two half rings on a hinge bolt, closed by a pinned gate. Nothing springs or corrodes shut, and the ring opens wide enough for any line from 4 to 16 mm.

- **The shear pin is the only link between pole and ring.** The tang never reaches the end plate (45 mm clear), so push and pull both go through the pin, and twisting goes through the fork cheeks bearing on the tang, not the pin.
- **One pin rating, set by the canoe.** 2.0 mm soft aluminium wire in double shear, 302 N nominal; the band allowed by R3 (256 to 347 N) is checked by breaking ten pins from each reel on CalRig before use.
- **Aluminium pole for the prototype, bamboo for local production.** The aluminium pole is uniform, so the trials measure the tool and not a piece of bamboo. Amish decided on 2026-10-03 (SMR-DDR-003) that a bamboo local variant, with one crutch and jigging weight shared by five canoes, is built alongside it so the two can be compared.
- **A hook head for wrapped nets.** A J hook on a flat like the tang pins into the same fork with the same pin, so it adds a second way to unwind a wrap without adding pull on the canoe (SMR-DDR-003).
- **Only canoes 7 m or longer with three crew.** The rule is kept; heel tests by canoe size class at TRL 4 set a pin for each class before a smaller class is served (SMR-DDR-003).
- **Crutch on the canoe, weight at the landing.** The crutch stays clamped on as a fitting and the jigging weight is taken out only for deep sets, so less is carried (SMR-DDR-003).
- **The jigging weight pins to the tang.** A weight loose on the cord would not move the ring; pinned on, it makes the ring heavy enough to jig on the tether.
- **Clamp-on crutch.** It fits any gunwale from 30 to 60 mm thick without drilling the canoe.

First-order numbers

All from SMR-CAL-001 (`docs/04-calcs/sizing.py` , results in `docs/04-calcs/results.csv`); estimates on stated assumptions, not test results.

Table 2. Key figures.

Quantity	Value	Assumption
Shear pin rating	302 N nominal (256 to 347 N)	Soft aluminium wire, 48 MPa in shear, double shear
Pull to lift a hooked net	81 to 126 N	Half a turn on the branch, friction 0.3 to 0.5, crew slackens to 30 N
Pull to lift a net wrapped once round	368 N to 2.3 kN	Same, one and a half turns: above the pin, so it must be worked round first
The same, worked back half a turn with the hook head	162 to 493 N	One full turn left on the branch
Design canoe heel when the pin breaks	3.4 deg kneeling, 4.4 deg standing	8 m plank canoe, three crew, 550 kg; pin at the top of its band
Small dugout heel when the pin breaks	24 deg kneeling	5.5 m dugout, two crew, 280 kg; why canoes under 7 m are excluded
Top hand to ring	4.18 m	Hands 300 mm below the top of the pole
Ring depth reached with the pole	3.2 m	Pole 20 deg off vertical, operator kneeling
Tether reach, jigging	8 m	10 m cord, 2 m kept above the water
Pole buckling factor	2.2	Euler, 4.35 m, pinned ends, against 347 N
Carried kit	4.34 kg aluminium prototype; 3.95 kg bamboo local variant	Crutch on the canoe, weight at the landing; whole kit 6.83 kg
Peak heel under a sudden jerk	6.5 deg kneeling	Roll period 1.06 s, pull rising in 0.25 s; over the 5 deg static limit; ruled out by the steady-lift rule and measured at TRL 4 (O6, decided 2026-10-25)
Bamboo pole buckling factor	1.5	E 15 GPa; culms chosen by a bend test
Parts cost of one kit	USD 95.50 aluminium prototype; USD 66.90 bamboo local variant	Prototype prices; variant with its own crutch, jigging weight shared by five canoes

Patent design-arounds

From the preliminary patent, trademark and prior-art screen (not legal advice), kept unchanged:

- The sliding-ring release is public prior art (US3464138A, expired); keep to a plain split ring and publish our own shear-pin value rather than copying a retail retriever.
- State the child-labour context factually and with sources, without naming individual boat owners or communities.

Shared blocks

- CalRig proof-load: calibrates each reel of pin wire (ten pins must break within 256 to 347 N).

- LevelHull canoe stability data, where available: replaces the assumed design canoe in the heel check.

Safety

> **Safety:** These hazards apply to every use and every test of the tool.

- **Nobody enters the water.** The tool is never a reason to keep children on boats; it is handed out only with child-protection work (SMR-DDR-001, D9).
- **Capsize.** The pin limits the pull; in the design canoe it breaks at about 4 deg of heel. In a small dugout the same pin would let the canoe heel about 24 deg, so the tool is used only from canoes 7 m or longer with at least three crew. Amish decided on 2026-10-03 to keep this rule and to set a pin per canoe class from heel tests at TRL 4.
- **The hook head** is held by the same calibrated pin as the ring; it is used kneeling, with the crew's line slack, like the ring.
- **Life jackets** are worn by every person on the canoe while a snag is worked.
- **Use the rated pin only.** Never a nail, bolt or steel wire: a stronger pin removes the protection.
- **Sudden release.** When the pin breaks the operator falls back into the canoe; kneel, never stand, and keep the other crew clear of the pole top.
- **Cut, do not risk it.** If the net will not come free, cut it.

This design is published as an open engineering reference. It is not certified equipment.

Open questions

Open questions are kept in the design decisions register (SMR-DEC-001): R1, R3, R7 and R10 were decided by Amish on 2026-10-03 and the aluminium prototype's carried mass on 2026-10-04. O6 to O9 from the kit 1.9.1 upgrade were decided on 2026-10-25 (steady-lift rule with 5 deg as the static limit, option A, a crutch on every canoe, a measured righting-moment criterion). O10, the hook head's tip-leg case, is open again: the approved gusset was found not to reach the straight shank.