

STUMPRIDER · REQUIREMENTS

StumpRider requirements

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	SMR-REQ-001	Version	0.3
Status	Draft	Date	2026-10-03
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/stumprider		
Source	docs/03-requirements.md @ uncommitted		

REVISION HISTORY

Version	Date	Author	Change
0.3	2026-10-03	Amish Chadha	TRL 3 status from SMR-CAL-001 on the constructable design; R1, R3, R7 and R10 not met or at risk, each a decision for Amish
0.2	2026-10-03	Amish Chadha	TRL 2; targets kept, design canoe and snag cases defined, concept status for each requirement
0.1	2026-09-30	Amish Chadha	Initial scaffold

StumpRider requirements

Targets are unchanged from the scaffold. Status is on paper at TRL 3, from the calculation note SMR-CAL-001; tags in brackets point to its results. Where a requirement is not met or at risk, the options and a recommendation are in docs/REVIEW.md (TRL 3, Decisions for Amish) and the design decisions register SMR-DEC-001.

Safety: R3 is a safety requirement: the shear pin is what keeps the pull from rolling the canoe. Nothing here relaxes the rules that nobody enters the water and that every person on the canoe wears a life jacket.

Table 1. Requirements and TRL 3 status.

ID	Requirement	Target	Verification (TRL 3 or later)	TRL 3 status
R1	Free a gillnet snagged on a submerged branch without anyone entering the water	At least 8 of 10 staged snags freed from the canoe	Tank or shallow-lake trials with staged branches at TRL 4	At risk: hooked nets need 81 to 126 N, well inside the pin [F1, F2]; a net wrapped once round needs 368 N to 2.3 kN, above it [F3, F4]
R2	Reach snags at working depth	Pole reach at least 4 m (13 ft); tether-cord method to 6 m (20 ft)	Measured at trial site	Met on paper: 4.18 m from top hand to ring [R1]; tether to 8 m [R3]
R3	Limit side pull on the canoe	Shear pin breaks at a set load within plus or minus 15 % of its rating, below the tested roll load of a typical canoe	Pull tests on CalRig and a canoe heel test	At risk: met for the design canoe (3.4 deg kneeling, 4.4 deg standing at the top of the band) [H5, H6]; a small dugout would heel 24 deg [K5]. The band holds only if each wire reel is calibrated
R4	Protect the net	No more than 5 broken meshes per release on standard 90 to 150 mm mesh	Mesh count after staged releases	Cannot be shown on paper; the pin caps the pull at 347 N [P3]
R5	Fast to use	Median release time under 5 minutes once the snag is found	Timed trials with fisher crews	Cannot be shown on paper
R6	Fit any common net line	Ring clips onto lines and headropes from 4 to 16 mm diameter	Fit check on sample lines	Met on paper: hinged ring, 100 mm inside [R4]
R7	Stows in a canoe	Packed length under 1.6 m (5.2 ft); total mass under 4 kg (8.8 lb)	Measurement	Not met: packed length 1.55 m [M9] meets; the whole kit is 6.5 kg [M8]
R8	Survive wet storage	No functional corrosion or rot after 6 months stored wet in a canoe	Field durability check with partner crews	Met on paper: galvanised steel, 6063 aluminium, stainless pins and rivets, polyester, polyethylene
R9	Locally buildable	Built by a village workshop from the drawings using hand tools and a small welder in under one day	Build trial with a local smith	Met on paper: about 7.7 h for one smith [T1], galvanising sent out
R10	Affordable	Parts cost under USD 40 per kit	Costed bill of materials from local prices	Not met: USD 92.50 at prototype prices [C1]

■ Assumptions

- Most snags are on branches or trunks within a few metres of the surface, as described on Volta Lake.
- The crew can hold tension on the net line above the snag while the ring is run down, and slacken it while the operator lifts.

- Design canoe: 8 m plank canoe, 1.1 m waterline beam, three crew, 550 kg; hard case: 5.5 m dugout, two crew, 280 kg (SMR-CAL-001, section 3). Both are assumptions until measured.
- Boat owners will use a tool if it is faster than sending someone down.