

SUNCLAVE · CALCULATION NOTE

SunClave sizing and first-principles checks

Design Molecule Lab · designmolecule.com

DOCUMENT CONTROL

Document ID	SCL-CAL-001	Version	0.2
Status	Draft	Date	2026-09-25
Author	Amish Chadha	License	CERN-OHL-S-2.0
Project TRL	TRL 3 Proof of concept		
Repository	github.com/BoujeeEnjinia1701/sunclave		
Source	docs/04-calcs/01-sizing.md @ 169e834		

REVISION HISTORY

Version	Date	Author	Change
0.2	2026-09-25	Amish Chadha	Recommendations accepted by Amish (DDR-002)
0.1	2026-09-25	Amish Chadha	First TRL 3 sizing note (steam and altitude, ray-traced optics, heat loss, cycle and day simulation, measurement, relief capacity for both lid options, boil-dry, masses, wind, logger power, cost) against every requirement

SunClave sizing and first-principles checks

On paper SunClave works, but it is slower, heavier and less forgiving to aim than the TRL 2 estimates said. The ray trace puts about 670 W into the cooker at 700 W/m² direct sun (not 710 W), the vessel loses about 395 W at 121 °C (not 200 W), and a cold start reaches the end of a 30 min hold in about 79 min in the central case and about 107 min in the unfavourable one. Version 0.2 applies Amish's acceptance of the recommendations on items 13 to 18 (SCL-DDR-002): retargeting every 12 min (R14 relaxed), a 45 kg total (R16 relaxed), the whole vessel treated as a marked hot zone (R11 restated), four locking castors (R15), a trimming rule with a logger reminder (R10) and a 0 to 300 kPa transducer (R12). Of the 17 requirements, 14 are now met, 2 are at risk (R4 cycle time and R15 stability) and 1 cannot be verified at TRL 3 (R1); no requirement is left not met, although three of the changes (R11, R14, R16) are restated or relaxed targets. The regulator gives 120.95 °C at sea level, so the "121 °C below about 300 m" claim of TRL 2 was optimistic; the decided altitude strategy (option B) extends the hold instead.

Safety: SunClave is a research and educational prototype, not a medical device. Nothing in this note shows that a load is sterile. The design concentrates sunlight to a few hundred times normal intensity at the focus and holds steam at about 121 °C (250 °F) in a pressure vessel. The numbers here are paper estimates and do not replace the maker's rating of the cooker, a certified relief valve or biological indicators.

Every number in this note is printed by `docs/04-calcs/sizing.py` (run from the repo root: `python docs/04-calcs/sizing.py`), which also writes `docs/04-calcs/results.csv`. The script reads the geometry from `PARAMS` in `cad/src/model.py` and the prices from `bom/bom.csv`, so the model, the drawing SCL-DWG-001 and this note agree. Nothing here is measured.

■ 1. Assumptions

Table 1. Inputs. All are assumptions for a paper design unless marked as decided.

Input	Value	Basis
Vessel, dish, aiming, load limits, altitude strategy, budget	As decided	SCL-DDR-001 items 1 to 4 and 6 to 11
Retargeting, mass limit, hot zone, castors, trimming rule, transducer span	As decided	SCL-DDR-002 items 13 to 18
Lid fittings	Shown on the lid; mounting method not decided	SCL-DDR-001 open item 5; section 8 covers both options
Design case	700 W/m ² direct normal irradiance (DNI), sun 60° above the horizon, 25 °C, wind 2 m/s, sea level, 2.0 kg of stainless instruments in a 0.5 kg basket, 1.5 L of water	SCL-REQ-001 v0.4
Dish	1.4 m aperture (1.539 m ²), focal length 500 mm, depth 245 mm, rim angle 70.0°	cad/src/model.py
Reflector	Reflectance 0.85; slope error 10 mrad (one standard deviation per axis)	Polished aluminum sheet bent into gores by hand
Sun	Pillbox sunshape of 4.65 mrad half-angle; apparent motion up to 15° per hour	Solar disc; worst case at low declination
Absorber paint	Absorptance 0.92 up to 60° incidence, falling linearly to half that at 90°	High-temperature matte black; angle fall-off assumed
Cooker	280 mm inside diameter x 200 mm deep (12.3 L), 4 mm wall, 6 mm base, 5 mm lid, aluminum 2,700 kg/m ³	Typical 12 L household cooker; brand to be confirmed
Water and steam	IAPWS-IF97 saturation line; latent heat 2,256 kJ/kg at 100 °C and 2,188 kJ/kg at 125 °C	Steam tables
Ambient pressure	ICAO standard atmosphere	
Regulator and relief	103.4 kPa (15 psi) gauge; relief set at 125 kPa gauge	SCL-REQ-001 R8
Equivalent exposure	z-value 10 °C, reference 121 °C	Common engineering assumption, not validated
Wind convection	$h = 2.8 + 3.0 \sqrt{W/(m^2 K)}$	Watmuff, Charters and Proctor (1977), as used in solar collector texts
Jacket	25 mm mineral wool, $k = 0.040 \text{ W/(m K)}$ at 50 °C rising 0.0002 per K; aluminized skin emissivity 0.3	Supplier data typical
Surfaces	Black base and band emissivity 0.9, 5 K above the water; lid emissivity 0.2; 0.03 m ² of handles and fittings at emissivity 0.5	Assumed
Retargeting	Every 12 min, so the pointing error grows from 0 to 3.0° between retargets	R14 target, relaxed from 15 min (SCL-DDR-002 item 13)
Pressure transducer	0 to 300 kPa absolute, 1 % of span	SCL-DDR-002 item 18 (was 0 to 500 kPa)

Three scenarios bracket the result: **favourable** (reflectance 0.88, slope error 6 mrad, absorptance 0.95, wind 1 m/s), **central** (0.85, 10 mrad, 0.92, 2 m/s) and **unfavourable** (0.78 for a dusty dish, 15 mrad, 0.88, 3 m/s). Central values are quoted unless a range is given.

■ 2. Steam temperature and altitude (R1)

A weighted regulator holds a fixed pressure above ambient. At sea level 103.4 kPa gauge gives **120.95 °C**, just under 121.0 °C, and the steam temperature falls by about 0.19 K per 100 m of altitude. The TRL 2 statement that the cooker reaches 121 °C "below about 300 m" was wrong; it reaches 121.0 °C only at sea level, and only within the tolerance of the weight.

Table 2. Steam temperature and the decided extended hold (option B) with altitude.

Altitude	Ambient	Boiling point	Steam at 103.4 kPa gauge	Gauge needed for 121 °C	Hold for 20 / 30 min at 121 °C (z = 10 °C)
0 m	101.3 kPa	100.0 °C	120.95 °C	103.7 kPa	20 / 30 min
250 m	98.4 kPa	99.1 °C	120.49 °C	106.7 kPa	23 / 34 min
500 m	95.5 kPa	98.3 °C	120.03 °C	109.6 kPa	25 / 37 min
1,000 m	89.9 kPa	96.6 °C	119.13 °C	115.2 kPa	31 / 46 min
1,500 m	84.6 kPa	95.0 °C	118.26 °C	120.5 kPa	38 / 56 min
1,800 m	81.5 kPa	94.0 °C	117.75 °C	123.5 kPa	42 / 63 min
2,400 m	75.6 kPa	92.0 °C	116.74 °C	129.4 kPa	53 / 80 min

Under the decided option B, R1 is restated as an exposure equivalent to 20 or 30 min at 121 °C, with the real temperature recorded. On the calculation the cycle delivers that at every altitude to 2,400 m (116.7 °C, never below the 115 °C floor). Whether the lower-temperature cycle kills as well as the 121 °C one is a microbiological question that only biological indicators can answer, so **R1 is not verifiable at TRL 3**. If the relief valve lifts at 125 kPa gauge, the steam reaches 124.2 °C at sea level, just above the 124 °C cap; that is a fault condition, not a normal cycle.

■ 3. Optics (R4, R9, R14)

A Monte Carlo ray trace (60,000 rays) follows sunlight from the aperture to the reflector and on to the level cooker. It includes the shadow of the vessel, holder ring and holder arms, the pillbox sun, slope errors, pointing error and the true receiver shape: the black base on the focal plane, the 80 mm black band of wall above it, and the jacket, which is aluminized and counted as lost. Because the cooker stays level while the dish tilts, the light arrives at the base from one side, and at low sun a quarter of it lands on the wall band instead.

Table 3. Share of the sun on the aperture absorbed by the cooker, central case, on target.

Sun elevation	Unshaded	Onto the vessel	Onto black surfaces	Absorbed	Absorbed at 700 W/m ²	Share on the base
15°	0.903	0.723	0.601	0.519	559 W	0.75
30°	0.894	0.738	0.674	0.590	636 W	0.73
45°	0.890	0.723	0.720	0.622	671 W	0.79
60°	0.895	0.727	0.727	0.621	669 W	0.92
75°	0.906	0.765	0.765	0.663	714 W	1.00
90°	0.923	0.785	0.785	0.700	755 W	1.00

In the design case (60°) the power flow is: 1,078 W on the aperture, 819 W reflected and not shaded, 784 W onto the vessel, and **669 W absorbed** (optical efficiency 0.62). The favourable and unfavourable scenarios absorb 723 W and 580 W. The TRL 2 estimate of 710 W assumed 95 % unshaded; the vessel, holder ring and arms shade about 10 %.

The mean flux over the base is about 11 kW/m², but the spot is small: the hottest 20 mm cell receives about **270 kW/m²** (270 suns), far above the 30 to 50 kW/m² stated at TRL 2. The base spreads this heat and the water boils it off (section 9), but the focus is more dangerous to skin and eyes than the TRL 2 documents said.

Pointing. The absorbed power falls to 90 % of on-target at a pointing error of about 3.2° (average of elevation and azimuth errors). At the worst-case sun motion of 15° per hour that takes **about 13 min**. The original R14 target of 15 min was not met; Amish accepted the recommendation to relax it to 12 min with a logger reminder (SCL-DDR-002 item 13), so R14 is now **met** with about 1 min of margin. The cycle times below assume 12 min retargeting and include the resulting loss (mean 638 W instead of 669 W). Tilting the dish about 15° off the sun cuts the absorbed power below 5 % (R9).

■ 4. Heat loss from the vessel

Table 4. Heat loss at 2 m/s wind and 25 °C ambient.

Vessel temperature	Total	Black base and band	Lid	Handles and fittings	Jacketed wall	Jacket skin
60 °C	134 W	85 W	35 W	9 W	5 W	28 °C
100 °C	298 W	185 W	77 W	25 W	11 W	33 °C
121 °C	395 W	245 W	101 W	35 W	15 W	36 °C

The base must stay bare and black to absorb the focus, and it radiates and convects about 245 W at 121 °C; the bare aluminum lid loses about 100 W. The jacket works (15 W), but it covers only a small share of the loss. The TRL 2 figure of 200 W at 121 °C was about half the value here. An insulated lid cover would recover up to about 80 W; this is a suggestion in docs/REVIEW.md , not a change to the design.

■ 5. Heat-up, hold and water (R4, R10)

The vessel's heat capacity without water is 5.16 kJ/K (body 3.01 kg, lid 0.95 kg, fittings 0.90 kg, instruments 2.0 kg, basket 0.5 kg). The simulation steps in 5 s: heat with the vent open to the local boiling point, 5 min of free steaming to purge air, fit the regulator and heat to the regulated temperature, then hold with the surplus venting through the regulator.

Table 5. Design cycle at sea level with a 30 min hold (wrapped instruments).

Scenario	Mean absorbed	To boiling	Cold start to 121 °C	Cold start to end of hold	Water left of 1.5 L	Cool-down to zero gauge
Favourable	686 W	25.4 min	40.0 min	70.4 min	1.13 kg	13 min
Central	638 W	30.0 min	48.6 min	79.0 min	1.25 kg	11 min
Unfavourable	555 W	41.1 min	76.2 min	106.6 min	1.41 kg	9 min

R4 (90 min or less in the design case) is met in the central case and **at risk** overall: a dusty dish with a rougher surface misses it by about 17 min, and the only measured precedent (Kaseman et al., 93 to 183 min of heat-up with 14 to 24 L vessels, cited in SCL-PRB-001) is slower still. With a 20 min hold (unwrapped) the central cycle is 68.8 min; at 600 W/m² it is 92.9 min.

Water. In the central case the purge uses 0.045 kg and the hold 0.202 kg, leaving 1.25 kg, well above the 0.5 L of R10. The worst sea-level case, favourable optics at 1,000 W/m² with no trimming, leaves 0.80 kg. Under option B, however, holds grow with altitude and strong sun is common at altitude:

Table 6. Option B cycles at altitude (30 min reference hold).

Altitude	Steam	Hold	Cycle, central	Water left, central	Water left, 1,000 W/m ² favourable, no trimming
0 m	121.0 °C	30 min	79 min	1.25 kg	0.80 kg
1,000 m	119.1 °C	46 min	93 min	1.14 kg	0.48 kg
1,800 m	117.7 °C	63 min	110 min	1.01 kg	0.14 kg
2,400 m	116.7 °C	80 min	125 min	0.88 kg	boils dry before the end of the hold

If the operator trims the dish off the sun so that only about 50 W vents during the hold, 1.31 kg is left at 1,800 m and 1.28 kg at 2,400 m, both at 1,000 W/m². Amish accepted the recommended trimming rule (SCL-DDR-002 item 17): the logger shows a trim reminder whenever the computed hold exceeds 40 min, which covers every site at 1,000 m and above, where an untrimmed hold in strong sun leaves 0.48 kg or less. With the rule, R10 (restated to include it) is **met**; it depends on the operator acting on the reminder, and the 140 °C base alarm stays as the backstop. Cycle time at altitude also exceeds 90 min at 1,000 m and above; R4 is defined at sea level.

■ 6. Cycles in a clear day (R5)

The day simulation starts cold at 09:00 solar time, uses the absorbed power for the sun's elevation at each moment (interpolated from Table 3 with 12 min retargeting), cools to zero gauge, allows 10 min to reload, and restarts warm: the pot and remaining water start at the boiling point, with fresh instruments and top-up water at 25 °C, which gives a restart temperature of about 89 °C. A cycle counts only if its hold ends by 15:00.

Table 7. Complete cycles between 09:00 and 15:00.

Case	Cycles	Hold end times (solar hours)
Equator, equinox, 700 W/m ²	4	10.32, 11.54, 12.74, 13.98
15° N, winter solstice, 700 W/m ²	4	10.34, 11.62, 12.89, 14.17
Equator, equinox, 600 W/m ²	4	10.55, 11.85, 13.14, 14.53

R5 (3 or more) is **met** with one cycle of margin, because warm restarts take only 50 to 60 min. The TRL 2 estimate of 3 cycles assumed a 30 min turnaround; the natural cool-down is 9 to 13 min.

■ 7. Measurement (R7, R12)

At 121 °C a Pt100 reads 146.44 Ω and changes by 0.3769 Ω/K. The class A tolerance is 0.39 K, a 0.1 % reference resistor on the MAX31865 board adds 0.39 K and a 0.05 % resistor 0.19 K; the 15-bit step is 0.035 K. The root sum square is **0.55 K with a 0.1 % reference** (fails R7's 0.5 K) and **0.44 K with 0.05 %**, so the BOM now specifies the 0.05 % part and R7 is **met on datasheets**. The pressure transducer, now 1 % of a 300 kPa span (SCL-DDR-002 item 18) read through a 16-bit ADS1115 converter, gives 3 kPa, inside the 5 kPa R7 target.

The field check against boiling water needs care: near 100 °C the boiling point changes by 0.277 K per kPa, so checking against the logger's own transducer (±3 kPa) carries ±0.8 K of doubt. A reference barometer reading to 0.2 kPa (a phone barometer or the nearest weather station) reduces this to 0.06 K.

For the air-removal check (R12), the saturation temperature changes by 0.155 K per kPa near 205 kPa absolute. With the decided 0 to 300 kPa transducer the pressure error alone is 0.47 K and the combined check uncertainty is **0.64 K** against a 2 K threshold (0.89 K on the earlier 0 to 500 kPa part). That is 32 % of the threshold, inside a 3:1 test uncertainty ratio, so R12 is **met** on calculation, narrowly. A 2 K deficit means about 6.1 % air by volume; allowing for the uncertainty, the logger is sure to flag about 8 % air and may flag from about 2 %. The highest absolute pressure is 205 kPa in normal use and 226 kPa at relief lift, inside the span; the transducer's overpressure rating must exceed the relief set point, and the BOM asks for 600 kPa or more.

■ 8. Pressure safety and the lid options (R8)

The worst steam generation is the favourable optics at 1,000 W/m² with the sun overhead and no heat loss: 1,153 W absorbed, **0.52 g/s** of steam. Choked-flow capacities with a discharge coefficient of 0.6 are:

- the regulator vent (3 mm bore, assumed): 1.36 g/s, 2.6 times the worst generation;
 - the independent relief valve (4 mm seat, assumed) at 125 kPa gauge: 2.66 g/s, 5.1 times the worst generation.
- Any seat of 1.8 mm or more would pass it.

The pressure on the lid is 6.4 kN at 103.4 kPa and 7.7 kN at 125 kPa, over the 280 mm bore. R8 is **met** on capacity; the vessel's own rating can only be confirmed from the maker's data for the model chosen.

How the gauge, relief valve and probe gland are mounted is **open for Amish** (SCL-DDR-001 open item 5). The calculation applies to both options and does not choose between them:

Table 8. Lid options compared on calculable points only.

Point	Option (i): drill the maker's lid	Option (ii): factory ports or an adapter plate on the regulator stem
New holes in the maker's lid	3 (two 11.1 mm tap drills for 1/4 in NPT, one 8.7 mm for 1/8 in NPT)	0
Metal removed	30.9 mm of drilled diameter, 0.41 % of the lid area	None from the lid
Spacing	Smallest ligament between holes 67 mm; smallest distance to the bore 41 mm	Set by the maker or the adapter
Relief and vent capacity	As above (5.1 and 2.6 times)	Same, provided the adapter keeps a vent bore of 3 mm or more (1.36 g/s) and leaves the overpressure plug untouched
What a calculation cannot show	Whether the maker's rating still holds after drilling; the lid is not a flat plate and its design data are not public	Whether a factory-ported 12 L cooker exists in the target market, and the rating of an adapter joint

■ 9. Boil-dry and base temperature (R10)

At 121 °C the surplus is about 243 W. If the operator forgot to turn the dish away after a central hold, the 1.25 kg left would boil dry in about 189 min. While water remains, Rohsenow's nucleate boiling correlation at the peak absorbed flux (252 kW/m²) puts the hottest spot of the base 10.3 K above the water, about 131 °C, which leaves 6.5 K below the 140 °C alarm after a 2.2 K type K tolerance. The thermocouple must sit at the base edge, out of the focal spot, or it will read the sunlight rather than the metal. A dry base in full sun would settle near 229 °C on average and hotter at the spot, where aluminum loses much of its strength; the alarm and the water rule matter.

■ 10. Masses, handling and wind (R15, R16)

Table 9. Mass estimate from the model parameters.

Group	Mass
Dish: reflector (0.5 mm aluminum, 1.71 m ²), ribs, rim, hub, gnomon	10.9 kg
Yoke (two 269 mm arms, collars, lock)	1.7 kg
Timber stand with quadrant, bearing blocks and castors (12.0 kg of timber)	19.4 kg
Pot holder	2.6 kg
Vessel with fittings, jacket and basket	5.6 kg
Logger and power bank	0.9 kg
Empty total	41.0 kg (44.5 kg loaded)

The original 40 kg total was not met: about 41.0 kg. The decided timber stand is heavier than the TRL 2 steel estimate (13 kg). Amish accepted the recommendation to relax the total to 45 kg and keep the 20 kg piece limit (SCL-DDR-002 item 14), so R16 is now **met** with about 4 kg of margin. The handling pieces are all within 20 kg: the stand 19.4 kg, the dish with yoke 12.6 kg, the vessel 5.6 kg and the bolted-on holder and logger 3.5 kg.

The loaded vessel's centre of mass sits about 98 mm above its base, which lies on the tilt axis. A holder free to swing on that axis would be top-heavy, so the model fixes the holder to the uprights and lets only the dish and yoke turn on the stub axles. The dish's own centre of mass is 366 mm from the axis, so the quadrant lock must hold up to 37.9 N·m of gravity torque at 15° elevation.

Wind at 10 m/s (60 Pa): the dish is taken as a plate with a drag coefficient of 1.4 when the wind blows onto the reflector and 1.2 onto the back, acting at the aperture centre, with the vessel and uprights added. The worst case is a low sun (15° elevation) with the wind blowing onto the reflector, because the dish then leans over the lee castor line: 153 N, 134 N·m overturning against 174 N·m restoring, a factor of **1.30**. Every other case is 1.50 or better. R15 (does not tip) is met on this estimate, but with a thin margin it is recorded as **at risk**. The same 153 N exceeded the 109 N of grip from the two locked castors of v0.1 (friction coefficient 0.5), so the stand would have rolled before it tipped. With the decided four locking castors (SCL-DDR-002 item 16) the grip is 218 N, 1.4 times the wind force. The tipping factor is unchanged, so R15 stays **at risk**, and the decided rule is to park the dish face-up in high wind.

■ 11. Logger power and record (R6, R13)

The logger draws about 0.31 W (ESP32, sensors, OLED and microSD), or 2.9 Wh for an 8 h operating day through an 85 % converter. A 10,000 mAh power bank, at 85 % output efficiency and 80 % usable, stores 25.2 Wh: **8.7 days** without recharging, against 3 days in R13. The logger draws only about 72 mA at 5 V, and many power banks switch off below 50 to 100 mA, so the bank must have a low-current (always-on) mode. A record of 16 bytes per 1 s sample for up to 3 h is 173 kB per cycle; a 4 GB card holds about 23,000 cycles (R6 asks for 1,000).

■ 12. Cost (R17)

The priced BOM (`bom/bom.csv`) totals **\$440** for parts (every line except item 18), against the \$450 budget set by Amish's decision (SCL-DDR-001 item 2), a margin of \$10. Version 0.2 adds \$4 for four locking castors (item 4) and \$6 for the keep-out marking (item 21); the 0 to 300 kPa transducer costs about the same as the 0 to 500 kPa part. The decided cuts (timber stand, OLED display, power bank) save about \$29 against the TRL 2 prices, which was short of the \$37 needed to reach \$400; the new safety items (goggles and parking cover, \$22) and the 0.05 % reference and ADS1115 are included. Validation consumables (item 18, \$45) are excluded, as R17 states. All prices are indicative estimates by supplier type, not quotes.

■ 13. Results against every requirement

Table 10. Requirement status at TRL 3 (also in `docs/04-calcs/results.csv`).

ID	Requirement	Value (central unless stated)	Target (SCL-REQ-001 v0.4)	Status
R1	Sterilizing condition (redefined)	120.95 °C and 30.3 min at 0 m; 117.7 °C and 63 min at 1,800 m	Exposure equal to 20 or 30 min at 121 °C (z = 10 °C), 115 to 124 °C, real temperature recorded	Not verifiable at TRL 3
R2	Load capacity	Basket 250 x 150 mm in a 12.3 L cooker, 16 mm above the water	Basket 250 x 150 mm or more; 2.0 kg	Met
R3	Load type	Solid instruments, unwrapped or single-wrapped	No lumened, hollow or textile loads	Met
R4	Cycle time	79 min (70 to 107 min)	90 min or less	At risk
R5	Daily throughput	4 cycles in every case of Table 7	3 or more	Met
R6	Cycle record	173 kB per cycle; about 23,000 cycles on 4 GB	1 s logging; 1,000 cycles	Met
R7	Measurement accuracy	0.44 K (0.05 % reference); 3 kPa (0 to 300 kPa)	0.5 K; 5 kPa	Met
R8	Pressure safety	Relief 5.1 times, vent 2.6 times the worst steam generation	Relief 125 kPa gauge or less; vessel rated by its maker	Met
R9	Heat input control	Below 5 % of power at 15° off the sun; parking cover	Stop within 10 s; dish shaded when parked	Met
R10	Boil-dry protection (restated)	1.25 kg left (design); with the trimming rule 1.31 kg at 1,800 m and 1.28 kg at 2,400 m, 1,000 W/m ² (0.14 kg at 1,800 m untrimmed)	0.5 L left in the design case and, with the trimming rule, at altitude; trim reminder; alarm at 140 °C	Met
R11	Burn and glare protection (restated)	Whole vessel and fittings a marked hot zone, reached only with the dish 15° off the sun; parking cover, goggles and keep-out marking in the BOM	Vessel and fittings a marked hot zone; focus reachable only through the dish; eye protection; keep-out marked	Met (design review)
R12	Air-removal check	Check uncertainty 0.64 K (0 to 300 kPa transducer); sure to flag 8 % air	Flag a hold more than 2 K below saturation	Met
R13	Logger power (redefined)	8.7 days on a 10,000 mAh bank	3 days without charging; USB recharge	Met
R14	Tracking effort (relaxed)	90 % of on-target power held for about 13 min	Retarget no more often than every 12 min; logger reminder	Met
R15	Stability	Tipping factor 1.30 (15° elevation); four locked castors grip 218 N against 153 N of wind	Does not tip at 10 m/s	At risk
R16	Portability and build (relaxed)	41.0 kg empty; largest piece 19.4 kg	45 kg or less; pieces 20 kg or less	Met
R17	Cost (redefined)	\$440	\$450 or less for parts	Met

Summary: 14 met, 2 at risk (R4, R15), 1 not verifiable at TRL 3 (R1) and 0 not met. In v0.1 the count was 9 met, 4 at risk (R4, R10, R12, R15), 1 not verifiable and 3 not met (R11, R14, R16); the change comes from the decisions in SCL-DDR-002, of which R14, R16 and R11 are relaxed or restated targets rather than design improvements.

■ 14. Checks against earlier claims

The TRL 2 documents stated several numbers that this note corrects; SCL-PRC-001 and SCL-REQ-001 v0.4 now carry the values above.

- Steam at sea level: 121.1 °C claimed, **120.95 °C** calculated; 121 °C "below about 300 m" claimed, **sea level only**.
- Absorbed power: about 710 W claimed, **669 W** (ray trace, 60° sun); shading about 10 %, not 5 %.
- Loss at 121 °C: about 200 W claimed, **395 W**.
- Cold start to 121 °C: about 35 min claimed, **48.6 min** central.
- Peak flux on the base: 30 to 50 kW/m² claimed, **about 270 kW/m²** in the hottest 20 mm cell.
- Pointing tolerance: about 8° claimed, **3.2°** to 90 % of on-target power.
- Cycles per day: about 3 claimed, **4** (faster warm restarts).
- Wind: 110 N·m against 180 N·m claimed, **134 N·m against 174 N·m** at the worst tilt.
- Mass: about 32 to 33 kg claimed, **41.0 kg** with the decided timber stand.
- Basket: 270 x 180 mm claimed; it does not fit a 12 L cooker, so it is now **250 x 150 mm**, the R2 minimum.
- Logger autonomy: about 5 days on the panel and cell, now **8.7 days** on the decided power bank.