



CONCEPT, NOT FOR FABRICATION

WaterWalker · github.com/BoujeeEnjinia1701/waterwalker


REV	DESCRIPTION	DATE	BY
P1	Preliminary GA from the parametric model (WWK-CAL-001)	2026-09-25	AC
P2	1.2 mm main wall, thinner cradle, parking lock pin (WWK-DDR-002)	2026-09-25	AC
P3	Design for construction: carrier, brackets, headsets, fixings (WWK-DDR-003)	2026-10-02	AC




TOP VIEW
Scale 1:20; looking down (along -Z)



FRONT VIEW
Scale 1:20; looking at the front (along +Y)



RIGHT VIEW
Scale 1:20; looking at the right side (along -X)



ISOMETRIC VIEW
Not to scale; assist kit shown fitted; seen from the front right and above, about 30 deg elevation

KEY DIMENSIONS (MM) AND NOTES

- Track 770; wheelbase 1530; caster trail 60
- Overall width 898 over axle nuts (R6 900 max)
- Clear walking width 610 between rails (R7 600 min)
- Wheels 26 in, ETRTO 559, 2.1 to 2.4 in tires, 100 mm hubs
- Headsets on all forks; rear pinned, front swivel
- Caster sweep R400; 20 clear of front risers
- Hip bar 850 to 1050 above ground; open rear entry
- Cradle 780 x 430, floor 150 up, on two bearers
- Ground clearance under the bearers 125
- Lift over side rail 364 (R8 450 max)
- Main tube RHS 40 x 30 x 1.2; cross 25 x 25 x 1.5
- Making sketches WWK-DWG-101 to 108 (build plan WWK-BLD-001)
- Parking lock pin, 10 mm, through left rear spokes
- Optional later assist kit: SwapCell v0.3, class V1
- Empty 39.6 kg; loaded 124 kg (WWK-CAL-001 v0.3)
- PRELIMINARY, NOT FOR FABRICATION

WATERWALKER

github.com/BoujeeEnjinia1701/waterwalker

General arrangement, walk-inside water carrier

DRAWING NO. WWK-DWG-001			REV P3	SHEET 1 of 1	SIZE ANSI B
SCALE 1:20	UNITS mm	PROJECTION 	DATE 2026-10-02		DRAWN Amish Chadha
MATERIAL / NOTES Mild steel tube frame; 26 in bicycle wheels and forks; plywood cradle. See bom/bom.csv					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com				Generated from cad/src; do not edit by hand	