


REV	DESCRIPTION	DATE	BY
P1	Making sketch for the prototype build plan	2026-10-03	AC



TOP VIEW

Scale 1:25; looking down (along -Z)



FRONT VIEW

Scale 1:25; looking at the front (along +Y)



RIGHT VIEW

Scale 1:25; looking at the right side (along -X)



WHERE IT GOES

This part in colour, its neighbours in grey

HOW TO MAKE IT AND HOW IT FITS

Make three. Structural tube 76.1 x 3.6 mm, yield at least

310 MPa, cut 4,364 mm long, ends square. Not water pipe.

End caps: 8 mm discs, 76 mm across, welded on both ends.

Tongues: 60 x 90 x 16 mm plate, one welded to the middle of each cap, in line with the tube; the two tongues lie in the same plane. 21 mm pin hole 60 mm from the cap face.

Pin hole to pin hole: 4,500 mm. Set it in a jig.

Leg 1: weld the winch bracket (WSL-DWG-104) before galvanising.

Drill a 10 mm vent hole near each end; galvanise.

Check: pin centres 4,500 mm apart within 3 mm; leg straight within 5 mm; all three legs the same length within 2 mm.

WELLSLING

github.com/BoujeeEnjinia1701/wellsling

WellSling: tripod leg (make 3; leg 1 carries the winch bracket)

DRAWING NO. WSL-DWG-105			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:25	UNITS mm	PROJECTION 	DATE 2026-10-03		DRAWN Amish Chadha
MATERIAL / NOTES Tube 76.1 x 3.6 mm, yield 310 MPa or more; 8 and 16 mm plate					
Licensed CERN-OHL-S-2.0 · Design Molecule Lab · designmolecule.com					Generated from cad/src; do not edit by hand