


CONCEPT, NOT FOR FABRICATION


WellSling · github.com/BoujeeEnjinia1701/wellsling

REV	DESCRIPTION	DATE	BY
P1	Concept sheet	2026-10-03	AC




TOP VIEW

Scale 1:100; looking down (along -Z)




FRONT VIEW

Scale 1:100; looking at the front (along +Y)



RIGHT VIEW

Scale 1:100; looking at the right side (along -X)



ISOMETRIC VIEW

Not to scale; figure is a 1.75 m person; seen from the front right and above, about 30 deg elevation

KEY FIGURES

Tripod: three 76.1 x 3.6 mm legs, 4.5 m pin to pin, feet on a 5 m circle
Head 4.00 m up; spans wells up to 3 m across, pads 0.7 m back from the rim
Safe working load 648 kg at the hook (600 kg animal); rope factor 6.1
Hand winch 1,000 kg, automatic load brake; crank 196 N at most
Two plain webbing bands, 240 mm wide, on an H-frame spreader
Landing bridge: 3 runners, 3 deck panels; never swung over the rim
Kit about 550 kg; heaviest piece 32 kg; about USD 2,780 (estimate)

WELLSLING

github.com/BoujeeEnjinia1701/wellsling

Rim-worked animal lifting kit for open wells

DRAWING NO. WSL - DWG - 010			REV P1	SHEET 1 of 1	SIZE ANSI B
SCALE 1:100	UNITS mm	PROJECTION 	DATE 2026-10-03	DRAWN Amish Chadha	

MATERIAL / NOTES
Massing model for concept communication