

UnitValues

Language Specification

Version 1.0.0

August 14, 2026

1 Introduction

1.1 Purpose

UnitValues is a set of domain-specific typed languages for numerical quantities. The set consists of two languages:

- `.ut` (unit types) for defining units from fundamental dimensions.
- `.uiv` (unit informed values) which import unit types and use dimensional construction to encode numerical quantities.

1.2 Scope

This document defines the syntax, semantics, and usage of all constructs in the `.ut` and `.uiv` domain-specific languages.

2 Language Rules

2.1 Global Section

The `[version]` section is required and defines the format version:

```
[version]  
format: 0.1.0
```

2.2 Unit Frame

The `unit_frame` directive specifies which `.ut` file to import for unit definitions:

```
unit_frame: si_metric.ut
```

2.3 Sections

Sections are denoted by `[section.name]` and can be nested. Common section types include:

- `[standards]` — Defines standard values used across the file.
- `[material.meta]` — Metadata about a material (type, composition, notes).
- `[motor.magnetic]` — Magnetic properties (permeability, hysteresis).
- `[armature.core.slots]` — Armature slot properties (length, material).

2.4 Value Assignments

Values are assigned using the format:

```
key: value prefix(unit)
```

Examples:

- `density: 8930 (kg/m^3)`
- `temperature: 298.15 (K)`

2.5 Unit Prefixes

SI prefixes can be applied to units:

- `(kg/mol)` — kilogram per mole.
- `M(A/m)` — mega-amp per meter.
- `m(m)` — millimeter (i.e., 1/1000 of a meter).
- `m(m^2)` — milli-square-meter (i.e., 1/1000 of a square meter).

2.6 Arrays and Tuples

Arrays are denoted with square brackets:

```
relative_permittivity: [1, 1]
```

Tuples (key-value pairs) use nested arrays:

```
temperature_conductivity: [  
  [273.0, 401.0],  
  [473.0, 389.0]  
] (K), (k)
```

2.7 Strings and Comments

Strings can be used as values:

```
my_spring: "Reduced Order Model | Tubular Ironless Linear Motor"
```

Comments begin with # and extend to the end of the line. Comments may appear on their own line or after a value:

```
# This is a comment
temperature: 298.15 (K) # Operating temperature
```

2.8 Unit Construction

Units are constructed from fundamental dimensions using the following operators:

Operation	Symbols	Description
Multiplication	*, x, ·, •	Multiplies units together
Division	/, ÷	Divides units
Power	^	Raises a unit to a power

Examples:

```
kg*m^2*s^-3*A^-1
m/s^2
kg*m/s^2
```

3 Examples

3.1 .ut File Example

The following example demonstrates how to define custom units derived from fundamental dimensions in a .ut file:

```
# Example Units - Derived from Fundamental Dimensions (kg, m, s, A, etc.)
[version]
format: 0.1.0

[units]
# name: unit
ρ: kg/m^3 # Defines the unit for pressure
V: kg*m^2*s^-3*A^-1 # Defines the unit for voltage
```

Note:

The fundamental unit and prefix semantics (kg, m, s, A, etc.) & (u, m, k, M, etc.) is defined by the runtime environment.

3.2 .uiv File Example

The following example demonstrates how to use unit definitions from a .ut file and assign typed values in a .uiv file:

```
[version]
format: 0.1.0
unit_frame: units.ut

[model]
# name: value prefix(unit)
num_samples: 100                                # Implicitly dimensionless
sample_size: 10                                (Ø)          # Explicitly dimensionless
output_energy: 1.0          (kg*m^2*s^-2)        # Defines unit via construction
output_signal: 5.0          (V)                  # Defined unit `V` for voltage
inlet_pressure: 101         k(ρ)                 # Defined unit `ρ` for pressure with kilo
prefix
```