

# Powershop API

## Developer Documentation

API version 1.0

Documentation version 0.8

Last updated 20 April 2011

## Table of Contents

Getting Access to the API.....	3
Technical Overview.....	3
OAuth Configuration.....	3
API Documentation.....	4
URL Format .....	4
Response Codes.....	4
customer API call.....	5
meter_readings GET API call.....	7
meter_readings POST API call.....	8
products API call.....	9
top_up GET API call.....	10
top_up POST API call.....	11

## Getting Access to the API

Before you can use the Powershop API, you must sign up for an API account for your product. Send an e-mail to [api@powershop.co.nz](mailto:api@powershop.co.nz) asking for access. Please include your product name and the e-mail address you used to sign up to Powershop.

All API accounts have a controlled number of requests per hour that they may submit. If you feel that your application will be submitting many requests, please mention this to the Powershop team.

## Technical Overview

The Powershop API is available over HTTPS. It returns responses in JSON or XML format.

This API uses the OAuth protocol. This allows users to authenticate themselves without entering their password into your application. OAuth libraries are available for all major development platforms, including PHP, Ruby and the iPhone.

For information about OAuth, visit:  
<http://oauth.net/>

It is a condition of using the Powershop API that you are never able to directly capture the user's password. This includes, for example, using a web control on the iPhone inside your application. Please search for "iphone oauth" to see how others have implemented OAuth for iPhone apps.

## OAuth Configuration

Your OAuth library will require several URLs to be configured. For Powershop, these are:

Request Token URL:  
[https://secure.powershop.co.nz/external\\_api/oauth/request\\_token](https://secure.powershop.co.nz/external_api/oauth/request_token)

Authorize URL:  
[https://secure.powershop.co.nz/external\\_api/oauth/authorize](https://secure.powershop.co.nz/external_api/oauth/authorize)

Access Token URL:  
[https://secure.powershop.co.nz/external\\_api/oauth/access\\_token](https://secure.powershop.co.nz/external_api/oauth/access_token)

For the test environment, replace "https://secure.powershop.co.nz" with "https://stable.test.powershop.co.nz".

A callback URL passed to the request token URL is required, as per the OAuth 1.0a specification. Note that your OAuth library may not require this parameter; you must manually specify it in this case or update the library to the latest version.

# API Documentation

## URL Format

Once you have received an access token using OAuth, use your OAuth library to call the API you are interested in. The format of API URLs is:

`https://secure.powershop.co.nz/external_api/v1/apiname.format`

where ***apiname*** is one of **customer**, **meter\_readings**, **products** or **top\_up**  
where ***format*** is one of **js** or **xml**.

If you use format **js**, the response will be a JSON string. If you use format **xml**, the response will be in XML.

Parameters supplied to the calls should be passed URL-encoded. For example, a request to find meter readings for ICP 0123456789 between the 1<sup>st</sup> and 30<sup>th</sup> of September 2009, with a JSON response requested, would look like:

`https://secure.powershop.co.nz/external_api/v1/meter_readings.js?icp_number=0123456789&start_date=2009-09-01&end_date=2009-09-30`

Your OAuth library will add OAuth token information and a signature before passing it to the Powershop server.

See below for details about each of the different API calls. Note that calls that get information require you use an HTTP GET, and calls that update information require you use an HTTP POST.

## Response Codes

A successful call to the API will return an HTTP 200 status code, and either JSON or XML-encoded data.

An unsuccessful call will return HTTP status codes 400, 401 or 503, depending on the error. A single line of text describing the error will also be returned. Error messages common to all API calls are:

- [E900] Invalid OAuth signature or consumer key
- [E901] Unknown OAuth signature method
- [E902] The application has exceeded the request rate limit for this hour
- [E903] Invalid OAuth token
- [E904] OAuth consumer is disabled
- [E905] Expired request token
- [E906] Invalid verifier
- [E907] oauth\_token not found
- [E908] oauth\_callback must be supplied

As the text of error messages may change, please use the [Exxx] error number to detect a particular error message.

## **customer API call**

### **HTTP method:**

GET

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/customer.format](https://secure.powershop.co.nz/external_api/v1/customer.format)

### **Parameters:**

none

### **Description:**

The customer API call returns information about the currently authenticated customer. It does not take any parameters.

### **Returns:**

version = 1.0

result =

properties [Array] =

icp\_number

*the property's ICP number*

status

*see "notes" section below*

status\_detail

*see "notes" section below*

address =

*the address of the property*

property\_name

flat\_number

street\_number

street\_name

suburb

district

region

start\_date

*yyyy-mm-dd; date property went online*

end\_date

*yyyy-mm-dd or nil; date property offline*

unit\_balance

*customer's unit balance; may be negative*

daily\_consumption

*number of kWh currently used per day*

last\_account\_review\_at

*yyyy-mm-dd hh:mm:ss*

registers [Array] =

register\_number

description

*customer-supplied description*

dials

*number of dials that the register has*

hidden

*1 if hidden; 0 otherwise*

last\_reading\_at

*yyyy-mm-dd hh:mm:ss*

last\_reading\_value

last\_reading\_type

*actual, customer, estimated, derived*

estimated\_reading\_value

*estimated reading as of now*

### **Errors:**

No specific errors returned by this method.

(continues next page)

**Notes:**

The status field is one of the following values:

active	<i>the property is currently being supplied by Powershop</i>
inbound	<i>the customer is moving in to switching to Powershop and the property is not ready for supply yet</i>
outbound	<i>the customer is moving out or switching away from Powershop</i>
archived	<i>the property is no longer active with Powershop</i>

A property's lifecycle is inbound → active → outbound → archived.

The status\_detail field contains a text string when the property's status is either inbound or outbound. This text details what stage the inbound or outbound process is currently in, for example, “waiting for switch from other retailer.” This text string can be displayed directly to the user.

Note that you can only use the methods below on ICPs that have a status of active. Trying to use it on other ICPs will return error message E009.

The unit\_balance field shows the current kWh balance of the account. A negative value means that the customer is that many units in arrears and will have to purchase power to make up the deficit at the next account review. A positive value means the customer has purchased more power than they have currently used.

A customer may hide a register if it is a “low use” register. This means you should generally not display it on your user interface.

Note that a customer may have several properties on the same account. Your user interface should allow for this possibility by letting the user select which property they wish to work with, if they have more than one.

## ***meter\_readings GET API call***

### **HTTP method:**

GET

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/meter\\_readings.format](https://secure.powershop.co.nz/external_api/v1/meter_readings.format)

### **Parameters:**

icp_number	<i>the ICP number of the property</i>
start_date	<i>yyyy-mm-dd; retrieve readings from this date</i>
end_date	<i>yyyy-mm-dd; retrieve readings up until this date</i>

### **Description:**

The GET meter\_readings API call returns readings for the given ICP.

They may be “actual” – retrieved from a meter reading company, “customer” – supplied by the customer, “estimated” – estimated by Powershop, normally for account review purposes, or “derived” – calculated using smart meter data.

### **Returns:**

version = 1.0

result **[Array]** =

register_number	<i>reading was taken on this register number</i>
read_at	<i>yyyy-mm-dd hh:mm:ss</i>
reading_type	<i>actual, customer, estimated, derived</i>
reading_value	<i>the reading</i>

### **Errors:**

- [E000] The icp\_number parameter must be specified for this call
- [E000] The start\_date parameter must be specified for this call
- [E000] The end\_date parameter must be specified for this call
- [E001] Dates must be in YYYY-MM-DD format
- [E008] icp\_number specified not found for this customer
- [E009] This property is not active

## ***meter\_readings POST API call***

### **HTTP method:**

POST

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/meter\\_readings.format](https://secure.powershop.co.nz/external_api/v1/meter_readings.format)

### **Parameters:**

icp_number	<i>the ICP number of the property</i>
readings[register_number]	<i>the reading for <b>register_number</b></i>

### **Description:**

The POST meter\_readings API call allows users to enter a reading for the specified ICP.

Note that a full set of readings must be specified, otherwise all readings will be rejected. A full set means that all non-hidden registers must have a valid reading. The reading may not be less than the previous actual reading, and must not exceed the daily usage thresholds that Powershop calculates for the ICP. If it does, an failure message will be returned.

### **Returns:**

version = 1.0

result =

result	<i>“success” or “failure”</i>
message	<i>if result is “failure”, a message describing the failure</i>

### **Errors:**

- [E000] The icp\_number parameter must be specified for this call
- [E002] Readings must be in an array format
- [E003] Register number not found
- [E004] Only numbers may be present in the reading value
- [E005] A reading for each active register must be supplied
- [E008] icp\_number specified not found for this customer
- [E009] This property is not active

### **Notes:**

It is recommended that you use the “dials” number, found in the results of the customer API call against each register, to show how the user many dials the register has and allow entry of exactly that many digits. Note also that under some cases the “dials” number may not be specified, in which case a UI handling up to 8 digits should be provided.



## ***products API call***

### **HTTP method:**

GET

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/products.format](https://secure.powershop.co.nz/external_api/v1/products.format)

### **Parameters:**

icp\_number            *the ICP number of the property*

### **Description:**

The products API call returns the products available for purchase from the specified property, and the per unit price of the products.

### **Returns:**

version = 1.0

result **[Array]** =

name	<i>the name of the product</i>
description	<i>a long HTML-formatted description of the product</i>
type	<i>nominated, special, powerpack</i>
price_per_unit	<i>unit price to 4d.p.</i>
image_url	<i>URL for 130x130 or 165x130 pixel product image</i>

### **Errors:**

[E000] The icp\_number parameter must be specified for this call

[E008] icp\_number specified not found for this customer

[E009] This property is not active

### **Notes:**

Under usual circumstances, a price returned by this call will be valid for purchase through the Powershop web site until midnight.

The image\_url parameter will not be present if there is no image associated with the product. The image URL supports the HTTP If-Modified-Since header, so you may wish to speed up your user's experience by caching the image. Note that the image may change if the product is out of stock.

## ***top\_up GET API call***

### **HTTP method:**

GET

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/top\\_up.format](https://secure.powershop.co.nz/external_api/v1/top_up.format)

### **Parameters:**

icp\_number            *the ICP number of the property*

### **Description:**

The top\_up GET API call returns an offer of how much it will cost the user to top up their account with their default preferred product (or the cheapest product currently on offer if they have not selected a preferred product.)

This call does not make the purchase; it just returns a price. The price must be displayed to the user and their consent granted before the purchase is made. See the top\_up POST API call.

### **Returns:**

version = 1.0

result =

unit_balance	<i>the current unit balance for this property</i>
product_name	<i>the name of the product that will be purchased</i>
price_per_unit	<i>the price per unit</i>
total_price	<i>the total price of the purchase</i>
offer_key	<i>a key that must be passed to the top_up POST API</i>

### **Errors:**

[E000] The icp\_number parameter must be specified for this call

[E008] icp\_number specified not found for this customer

[E009] This property is not active

### **Notes:**

If the customer's unit balance is zero or positive, only the "unit\_balance" key will be returned.

## ***top\_up POST API call***

### **HTTP method:**

POST

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/top\\_up.format](https://secure.powershop.co.nz/external_api/v1/top_up.format)

### **Parameters:**

icp_number	<i>the ICP number of the property</i>
offer_key	<i>the offer key returned by the top_up GET API call</i>

### **Description:**

The top\_up POST API call makes a purchase of power, topping up the customer's unit balance to 0. The top\_up GET API must be called before calling this.

### **Returns:**

version = 1.0

result =

result	<i>"success" or "failure"</i>
message	<i>if result is "failure", a description of the failure</i>

### **Errors:**

- [E000] The icp\_number parameter must be specified for this call
- [E008] icp\_number specified not found for this customer
- [E006] Invalid offer\_key value
- [E009] This property is not active

### **Notes:**

If the result is "failure", the message field may be displayed to the user to inform them why the purchase failed.

## ***contact\_us POST API call***

### **HTTP method:**

POST

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/contact\\_us.format](https://secure.powershop.co.nz/external_api/v1/contact_us.format)

### **Parameters:**

comment                      *text of the comment to be posted to Powershop*

### **Description:**

The contact\_us POST API call posts some feedback to Powershop. The currently authenticated user's name and e-mail address are automatically attached to the feedback so that Powershop can send them a response.

The comment field may be up to 64KB in length.

### **Returns:**

version = 1.0

result =

result                      *"success" or "failure"*

message                    *if result is "failure", a description of the failure*

### **Errors:**

[E000] The comment parameter must be specified for this call

## **usage\_data GET API call**

### **HTTP method:**

GET

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/usage\\_data.format](https://secure.powershop.co.nz/external_api/v1/usage_data.format)

### **Parameters:**

icp_number	<i>the ICP number of the property</i>
start_date	<i>yyyy-mm-dd</i>
end_date	<i>yyyy-mm-dd; not more than a year after start_date</i>

### **Description:**

The usage\_data call returns pre-calculated data about the user's usage, ready to plot on a graph. It is the same data that is shown on the Powershop web site graphs. Powershop suggests you use this data when displaying graphs to give a seamless experience between the web site and your application.

If more than a year's data is requested, the end date will be truncated so that only a year's worth after the start date will be returned.

### **Returns:**

version = 1.0

result =

start_date	<i>the start date of the data returned</i>
end_date	<i>the end date of the data returned</i>
graph_type	<i>optional - see below</i>
registers [Array]	<i>an array of register numbers</i>
data [Array] =	
day_data	<i>number of kWh for this day</i>

### **Errors:**

- [E000] The icp\_number parameter must be specified for this call
- [E008] icp\_number specified not found for this customer
- [E009] This property is not active
- [E010] Invalid graph\_type value

### **Notes:**

The graph\_type variable is optional. If specified, it must be either *smoothed* or *raw*. If not specified, it defaults to *smoothed*. Powershop will be changing these graph types in the future, and it is likely that this field will become unused.

An array of numbers is returned in the data variable. If you requested 60 days, the data array will have 60 elements, where the first element is the usage on the start date and the last element is the usage on the end date. Each element contains the number of kilowatt-hours (kWh) used on that day. This may be a floating point number, and under certain unusual circumstances, may be negative.

## ***promotions GET API call***

### **HTTP method:**

GET

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/promotions.format](https://secure.powershop.co.nz/external_api/v1/promotions.format)

### **Parameters:**

none

### **Description:**

The promotions call returns all active referral promotions. The user can use one of these promotions to refer Powershop to a friend.

### **Returns:**

version = 1.0

result =

promotions [Array] =

promotion_id	<i>a numeric identifier for this promotion</i>
name	<i>the promotion's name</i>
description	<i>a plain text description</i>
image_url	<i>a URL of an image related to this promotion</i>
start_date	<i>the start date of the data returned</i>
end_date	<i>the end date of the data returned</i>
t_and_c_accepted	<i>whether the user has accepted T&amp;C</i>

### **Errors:**

none

### **Notes:**

An empty array of promotions may be returned if there are no active referral promotions. At present, Powershop only runs at most one referral promotion at a time, but this may change in the future.

The promotion description is UTF-8 text. It may contain linefeed characters.

## ***referral POST API call***

### **HTTP method:**

POST

### **API URL:**

[https://secure.powershop.co.nz/external\\_api/v1/referral.format](https://secure.powershop.co.nz/external_api/v1/referral.format)

### **Parameters:**

<code>promotion_id</code>	<i>the numeric identifier of the promotion</i>
<code>name</code>	<i>the name of the referee</i>
<code>email</code>	<i>the e-mail address of the referee</i>
<code>return_url</code>	<i>the URL to return to once the user has accepted the T&amp;C</i>

### **Description:**

This call allows a user to refer a friend to Powershop. The promotion ID can be found from the results of the promotions GET call. A name and valid e-mail address must be specified.

Before a referral can be made, the logged in user must accept the terms and conditions of the promotion. They only need to accept the T&C once per promotion. If the user has not yet accepted the T&C, a result of "redirect" will be returned from the API, and the application must display the specified URL in an embedded browser, or redirect the user to the URL if in a web application. When the user has accepted the T&C, the referral POST request can be resubmitted.

### **Returns:**

version = 1.0

result =

<code>result</code>	<i>"success" or "failure" or "redirect"</i>
<code>message</code>	<i>if result is "failure", a description of the failure</i>
<code>url</code>	<i>if result is "redirect", a URL to display to the user</i>

### **Errors:**

- [E000] The `promotion_id` parameter must be specified for this call
- [E000] The `name` parameter must be specified for this call
- [E000] The `email` parameter must be specified for this call
- [E011] Invalid e-mail address
- [E012] Invalid promotion id

### **Notes:**

If the result is "failure", the message field may be displayed to the user to inform them why the referral failed.