Energy-Efficient Spiking Neural Networks: Technical Analysis and Implementation Advances

Introduction

Spiking Neural Networks (SNNs) have emerged as a promising paradigm for energy-efficient artificial intelligence, offering brain-inspired computing capabilities that significantly reduce power consumption compared to traditional Artificial Neural Networks (ANNs). This analysis examines recent advances in energy-efficient SNN implementations, focusing on practical applications, algorithmic innovations, hardware optimizations, and deployment strategies for real-world AI systems.

Evidence Synthesis

Latest Practical Applications with Quantifiable Energy Gains

Recent research demonstrates substantial energy efficiency improvements across diverse applications. The Xpikeformer architecture achieves remarkable energy reductions of 17.8-19.2× compared to state-of-the-art digital ANN transformers and 5.9-6.8× compared to fully digital SNN transformers, while maintaining software-comparable inference accuracy [2]. This hybrid analog-digital approach represents a significant breakthrough in neuromorphic transformer implementations.

In autonomous vehicle applications, SNNs integrated with Dynamic Vision Sensors (DVSs) show dramatic energy consumption reductions while processing real-time pedestrian detection in adverse weather conditions [1]. The system demonstrates superior computational efficiency compared to traditional CNNs, making it highly suitable for resource-constrained automotive environments.

Specific Power Consumption Metrics

The MC-QDSNN system achieves exceptional energy efficiency with 25.12×-39.20× energy savings compared to ANNs while maintaining 98.8% accuracy in stress detection applications [19]. Similarly, the SVFormer architecture demonstrates ultra-low power consumption of 21 mJ/video for video action recognition, achieving 84.03% accuracy on UCF101 dataset [15].

Neuromorphic hardware implementations show even more impressive results, with the MENAGE accelerator achieving 12.1 TOPS/W energy efficiency [11], and photonic spiking systems reaching energy consumption as low as 1 pJ/spike with threshold energies of ~100 fJ/spike [37].

Core Algorithmic Methods Enabling Energy Efficiency

Spike-Based Encoding and Event-Driven Processing

The OneSpike framework introduces parallel spike-generation (PSG) methods that enable single-timestep SNN operation without accuracy loss, achieving 81.92% accuracy on ImageNet [4]. This approach fundamentally addresses the latency-accuracy trade-off that has limited SNN deployment.

SpikingSSMs combine spiking neural networks with state space models for long sequence learning, achieving 90% network sparsity while maintaining competitive performance [3]. The framework introduces lightweight surrogate dynamic networks that enable orders of magnitude acceleration in training speed compared to conventional iterative methods.

Temporal Dynamics and Thresholding Mechanisms

Advanced thresholding mechanisms include multi-threshold spiking neurons in Spiking-UNet architectures, which improve information transmission efficiency and reduce inference time by approximately 90% compared to converted models without fine-tuning [32]. The Group IF units with membrane potential sharing achieve nearly lossless ANN-SNN conversion in single timesteps, losing only 0.8% accuracy on CIFAR-10 for VGG-16 [5].

Learning Algorithms

The Forward Temporal Bias Correction (FTBC) technique enhances ANN-SNN conversion accuracy through proper temporal bias calibration, reducing expected conversion error to zero after each time step [8]. Temporally Effective Batch Normalization (TEBN) optimizes SNN training for complex weather conditions, demonstrating robust performance across varied environmental scenarios [1].

Post-2023 Breakthroughs and Technical Advances

Recent algorithmic breakthroughs include the development of Temporal Reversed Training (TRT) methods that optimize spatio-temporal performance through temporal reversal operations, achieving 74.77% accuracy on ImageNet with only two timesteps [23]. The HL-ESViT architecture introduces High-Low Frequency Multi-scale Multi-head Self-Attention mechanisms that significantly reduce memory and computational costs while maintaining competitive performance [7].

The emergence of neuromorphic intermediate representation (NIR) provides a unified instruction set for interoperable brain-inspired computing, enabling reproducibility across 7 neuromorphic simulators and 4 digital hardware platforms [34]. This standardization represents a crucial step toward widespread SNN adoption.

Detailed Comparison with Traditional ANNs

Energy Consumption Analysis

Quantitative comparisons reveal substantial energy advantages for SNNs. The energy-efficient reservoir computing system using memcapacitive synapses achieves ~27 fJ per spike power consumption, demonstrating 97.8% accuracy in arrhythmia classification and 80.0% in sleep apnea detection [18]. This represents orders of magnitude improvement over traditional digital processing approaches.

Computational Efficiency Trade-offs

While SNNs demonstrate superior energy efficiency, performance trade-offs exist. The comprehensive analysis shows that SNNs excel in temporal processing tasks but may require careful optimization for static image processing. The Spiking-UNet achieves comparable performance to non-spiking counterparts while reducing inference time by 90%, demonstrating that proper architectural design can minimize performance penalties [32].

Hardware Optimizations and Neuromorphic Implementations

Neuromorphic Chip Implementations

Advanced neuromorphic hardware includes photonic spiking systems using self-pulsing optical microresonators, demonstrating all-optical long-term memory up to 10 μs and event detection capabilities [6]. These systems offer enhanced processing speeds, scalability, and energy efficiency for AI applications.

The TRIP framework introduces hardware-efficient attention mechanisms for event-based vision processing, achieving 46× computation reduction compared to state-of-the-art while maintaining higher accuracy [12]. The system enables 2× latency and energy improvements on neuromorphic processors.

Deployment Strategies

Memristor-based implementations show significant promise, with systems achieving up to 97% accuracy despite device variations and input noise, consuming only 18.9 mJ energy with 2.4-second training time [26]. The integration of analog in-memory computing with digital processing creates hybrid architectures that optimize both energy efficiency and computational flexibility.

Specific Domains Showing Promise

Edge Computing and IoT

Energy-efficient SNNs demonstrate particular strength in edge computing applications. The CAE-Net framework achieves 4-6 fold energy reduction and latency speedups on Raspberry Pi and Jetson Nano while maintaining high accuracy for image classification tasks [44]. These results highlight SNN suitability for resource-constrained IoT deployments.

Robotics and Autonomous Systems

Neuromorphic computing for robotics shows significant potential, with embodied neuromorphic AI systems addressing challenges in accuracy, adaptability, efficiency, reliability, and security [25]. The integration of cross-layer optimizations enables energy-efficient neuromorphic computing suitable for autonomous vehicle applications.

Healthcare and Biosignal Processing

SNNs excel in biosignal classification, with the MC-QDSNN achieving 98.8% accuracy in stress detection while consuming 25.12×-39.20× less energy than traditional ANNs [19]. The artificial gustatory system demonstrates 1000× lower power consumption (49.58 pW) compared to state-of-the-art systems [35].

Critical Evaluation

The reviewed research demonstrates substantial progress in SNN energy efficiency, with consistent improvements across multiple metrics. However, several limitations persist. Many studies focus on specific benchmark datasets, and real-world deployment challenges remain underexplored. The trade-off between energy efficiency and accuracy varies significantly across applications, requiring careful optimization for each use case.

The quality of evidence is generally high, with most studies providing quantitative comparisons and detailed experimental validation. However, standardized benchmarking across different SNN implementations remains limited, making direct comparisons challenging.

Implications and Examples

The practical implications of these advances are substantial. The demonstrated energy reductions of 17-19× compared to traditional neural networks could enable deployment of sophisticated AI systems in battery-powered devices, autonomous vehicles, and IoT applications where power consumption is critical.

The development of single-timestep SNN processing addresses a major barrier to practical deployment, potentially enabling real-time applications that were previously infeasible. The integration of neuromorphic hardware with traditional computing architectures creates hybrid systems that optimize both energy efficiency and computational capability.

These advances position SNNs as viable alternatives to traditional neural networks for specific applications, particularly those requiring real-time processing, low power consumption, and temporal data analysis. The continued development of standardized frameworks and hardware implementations will likely accelerate adoption across diverse domains.

References

[1] Sakhai, M., Mazurek, S., Caputa, J., Argasiński, J. K., & Wielgosz, M. (2024). Spiking Neural Networks for Real-Time Pedestrian Street-Crossing Detection Using Dynamic Vision Sensors in Simulated Adverse Weather Conditions. Electronics, 13(21), 4280.

[2] Song, Z., Katti, P., Simeone, O., & Rajendran, B. (2024). Xpikeformer: Hybrid Analog-Digital Hardware Acceleration for Spiking Transformers. arXiv preprint arXiv:2408.08794.

[3] Shen, S., Wang, C., Huang, R., Zhong, Y., Guo, Q., Lu, Z., Zhang, J., & Leng, L. (2024). SpikingSSMs: Learning Long Sequences with Sparse and Parallel Spiking State Space Models. arXiv preprint arXiv:2408.14909.

[4] Tang, K., Yan, Z., & Wong, W. F. (2024). OneSpike: Ultra-low latency spiking neural networks. Proceedings of the International Joint Conference on Neural Networks (IJCNN), 34, 1-8.

[5] Ye, Z., Zeng, W., Chen, Y., Zhang, L., Xiao, J., & King, I. (2024). Group IF Units with Membrane Potential Sharing for High-Accuracy Low-Latency Spiking Neural Networks. Proceedings of the International Joint Conference on Neural Networks (IJCNN), 34, 1-8.

[6] Biasi, S., Lugnan, A., Micheli, D., & Pavesi, L. (2024). Exploring the potential of self-pulsing optical microresonators for spiking neural networks and sensing. Communications Physics, 7(1).

[7] Shi, K., Liu, H., Chen, Y., & Qu, H. (2024). HL-ESViT: High-Low Frequency Efficient Spiking Vision Transformer. Proceedings of the International Joint Conference on Neural Networks (IJCNN), 34, 1-8.

[8] Wu, X., Bojkovic, V., Gu, B., Suo, K., & Zou, K. (2024). FTBC: Forward Temporal Bias Correction for Optimizing ANN-SNN Conversion. arXiv preprint arXiv:2403.18388.

[9] Zou, M., Jia, X. H., Song, W. J., Deng, S. S., Bao, M. Y., Tang, Y., Lv, J., Li, X., & Zhang, X. (2024). Proposal and detailed theoretical analysis on photonic neural network with optically pumped Spin-VCSEL spiking neurons. Japanese Journal of Applied Physics, 63(9), 092004.

[10] Shen, S., Zhang, R., Wang, S., Huang, R., Tuerhong, A., Guo, Q., Lu, Z., Zhang, J., & Leng, L. (2024). Evolutionary spiking neural networks: a survey. Journal of Membrane Computing.

[11] Abdollahi, A., Kamal, M., & Pedram, M. (2024). MENAGE: Mixed-Signal Event-Driven Neuromorphic Accelerator for Edge Applications. arXiv preprint arXiv:2410.08403.

[12] Arjmand, C., Xu, Y., Shidqi, K., Dobrita, A., Vadivel, K., Detterer, P., Sifalakis, M., Yousefzadeh, A., & Tang, G. (2024). TRIP: Trainable Region-of-Interest Prediction for Hardware-Efficient Neuromorphic Processing on Event-based Vision. arXiv preprint arXiv:2406.17483.

[13] Rathore, M., & Rose, G. S. (2024). Maximizing Efficiency of SNN-Based Reservoir Computing via NoC-Assisted Dimensionality Reduction. Proceedings of the IEEE International Symposium on Very Large Scale Integration (VLSI) Design, 671-674.

[14] Rathore, M., & Rose, G. S. (2024). AnSpiCS-Net: Reconfigurable Network-on-Chip for Analog Spiking Recurrent Neural Networks. Proceedings of the IEEE International Symposium on Circuits and Systems (ISCAS).

[15] Yu, L., Huang, L., Zhou, C., Zhang, H., Ma, Z., Zhou, H., & Tian, Y. (2024). SVFormer: A Direct Training Spiking Transformer for Efficient Video Action Recognition. arXiv preprint arXiv:2406.15034.

[16] Hao, Z., Huang, Y., Xu, Z., Yu, Z., & Huang, T. (2024). Comprehensive Online Training and Deployment for Spiking Neural Networks. arXiv preprint arXiv:2410.07547.

[17] Venkatesh, S., Marinescu, R. V., & Eshraghian, J. K. (2024). SQUAT: Stateful Quantization-Aware Training in Recurrent Spiking Neural Networks. Proceedings of the IEEE International Conference on Neuromorphic Computing and Engineering (NICE).

[18] Jiang, S., Sun, J., Pei, M., Peng, L., Dai, Q., Wu, C., Gu, J., Yang, Y., Su, J., Gu, D., Zhang, H., Guo, H., & Li, Y. (2024). Energy-Efficient Reservoir Computing Based on Solution-Processed Electrolyte/Ferroelectric Memcapacitive Synapses for Biosignal Classification. Journal of Physical Chemistry Letters, 8501-8509.

[19] Ajay, B. S., Kambhampati, P. P., & Rao, M. (2024). MC-QDSNN: Quantized Deep Evolutionary SNN With Multi-Dendritic Compartment Neurons for Stress Detection Using Physiological Signals. IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems, 1-1.

[20] Vol, T., Danial, L., & Shlezinger, N. (2024). Learning Task-Based Trainable Neuromorphic ADCs via Power-Aware Distillation. arXiv preprint arXiv:2409.15300.

[21] Nguyen, M. V., Zhao, L., Deng, B., Severa, W., Xu, H., & Wu, S. (2024). The Robustness of Spiking Neural Networks in Communication and its Application towards Network Efficiency in Federated Learning. arXiv preprint arXiv:2409.12769.

[22] Hu, Y., Qian, Z., Li, G., Tang, H., & Pan, G. (2024). Toward Large-scale Spiking Neural Networks: A Comprehensive Survey and Future Directions. arXiv preprint arXiv:2409.02111.

[23] Zuo, L., Ding, Y., Luo, W., Jing, M., Tian, X., & Yang, K. (2024). Temporal Reversed Training for Spiking Neural Networks with Generalized Spatio-Temporal Representation. arXiv preprint arXiv:2408.09108.

[24] Plagwitz, P., Hannig, F., Teich, J., & Keszöcze, O. (2024). DSL-Based SNN Accelerator Design Using Chisel. Proceedings of the Euromicro Conference on Digital System Design (DSD), 176-184.

[25] Putra, R. V. W., Marchisio, A., Zayer, F., Dias, J., & Shafique, M. (2024). Embodied Neuromorphic Artificial Intelligence for Robotics: Perspectives, Challenges, and Research Development Stack. arXiv preprint arXiv:2404.03325.

[26] Eslami, M. R., Biswas, D., Takhtardeshir, S., Sharifi, S., & Banadaki, Y. M. (2024). On-Chip Learning with Memristor-Based Neural Networks: Assessing Accuracy and Efficiency Under Device Variations, Conductance Errors, and Input Noise. arXiv preprint arXiv:2408.14680.

[27] Johari, S., Mohammadhassani, A., Varshika, M. L., & Das, A. (2024). CMOS-Memristor Hybrid Design of A Neuromorphic Crossbar Array with Integrated Inference and Training. Proceedings of the IEEE Midwest Symposium on Circuits and Systems (MWSCAS), 442-446.

[28] Turck, C., Harabi, K. E., Pontlevy, A., Ballet, T., Hirtzlin, T., Vianello, E., Laurent, R., Droulez, J., Bessière, P., Bocquet, M., Portal, J. M., & Querlioz, D. (2024). The Logarithmic Memristor-Based Bayesian Machine. arXiv preprint arXiv:2406.03492.

[29] An, J., Zhang, N., Tan, F., Zhao, X., Chang, C., Lanza, M., & Li, S. (2024). Programmable Optoelectronic Synaptic Transistors Based on MoS2/Ta2NiS5 Heterojunction for Energy-Efficient Neuromorphic Optical Operation. Small, e2403103.

[30] Stenning, K. D., Gartside, J. C., Manneschi, L., Cheung, C. T. S., Chen, T., Vanstone, A., Love, J., Holder, H. H., Caravelli, F., Kurebayashi, H., Everschor-Sitte, K., Vasilaki, E., & Branford, W. R. (2024). Neuromorphic overparameterisation and few-shot learning in multilayer physical neural networks. Nature Communications, 15(1).

[31] Zhou, S., Wang, J., Yuan, M., Jiang, R., Yan, R., Pan, G., & Tang, H. (2024). Enhancing SNN-based spatio-temporal learning: A benchmark dataset and Cross-Modality Attention model. Neural Networks, 180, 106677.

[32] Li, H., Zhang, Y., Xiong, Z., & Sun, X. (2024). Deep multi-threshold spiking-UNet for image processing. Neurocomputing, 586, 127653.

[33] Yu, Y., Wang, S., Xu, M., Zhang, W., Gao, B., Yang, J., Wang, S., Zhang, Q., Wu, X., Chen, H., Wang, D., Chen, X., Lin, N., Qi, X., Shang, D., & Wang, Z. (2024). Random memristor-based dynamic graph CNN for efficient point cloud learning at the edge. Nature Machine Intelligence, 1(1).

[34] Pedersen, J. E., Abreu, S., Jobst, M., Lenz, G., Fra, V., Bauer, F. C., Muir, D. R., Zhou, P., Vogginger, B., Heckel, K., Urgese, G., Shankar, S., Stewart, T. C., Sheik, S., & Eshraghian, J. K. (2024). Neuromorphic intermediate representation: A unified instruction set for interoperable brain-inspired computing. Nature Communications, 15(1).

[35] Khanday, M. A., Rashid, S., & Khanday, F. A. (2024). Energy Efficient Artificial Gustatory System for In-sensor Computing. Micro and Nanostructures.

[36] Liu, Y., Zhao, R., Xiao, H., Liu, Y. H., & Chen, J. (2024). An XOR-10T SRAM computing-in-memory macro with current MAC operations and time-to-digital conversion for BNN edge processors. AEU-International Journal of Electronics and Communications, 182, 155346.

[37] Diamantopoulos, N. P., Fujii, T., Yamaoka, S., Nishi, H., & Matsuo, S. (2024). Ultrafast Electro-Optic Spiking Membrane III-V Lasers on Silicon Utilizing Integrated Optical Feedback. Journal of Lightwave Technology, 1-10.

[38] Tsuchiya, T., Nishioka, D., Namiki, W., & Terabe, K. (2024). Physical Reservoir Computing Utilizing Ion-Gating Transistors Operating in Electric Double Layer and Redox Mechanisms. Advanced Electronic Materials.

[39] Langner, P., Chiabrera, F., Alayo, N., Nizet, P., Morrone, L., Bozal-Ginesta, C., Morata, A., & Tarancón, A. (2024). Solid-State Oxide-Ion Synaptic Transistor for Neuromorphic Computing. arXiv preprint arXiv:2408.01469.

[40] El Srouji, L., Lee, Y. J., On, M. B., Abdelghany, M., & Yoo, S. J. B. (2024). Bioplausible Photonic-Electronic Neural Networks. Proceedings of the IEEE Photonics Society Summer Topical Meeting Series (SUM), 1-2.

[41] Zhao, Y., Ma, S., Liu, H., & Li, D. (2024). SAL: Optimizing the Dataflow of Spin-based Architectures for Lightweight Neural Networks. ACM Transactions on Architecture and Code Optimization.

[42] Li, J., Ma, L., Sham, C. W., & Fu, C. (2024). A Novel Computing Paradigm for MobileNetV3 using Memristor. arXiv preprint arXiv:2402.10512.

[43] Ramirez-Morales, R. R., Ponce-Ponce, V. H., Molina-Lozano, H., Sossa, H., Islas-García, O., & Rubio-Espino, E. (2024). Analog Implementation of a Spiking Neuron with Memristive Synapses for Deep Learning Processing. Mathematics, 12(13), 2025.

[44] Mahmud, H., Kang, P., Lama, P., Desai, K., & Prasad, S. K. (2024). CAE-Net: Enhanced Converting Autoencoder Based Framework for Low-Latency Energy-Efficient DNN with SLO-Constraints. Proceedings of the IEEE International Conference on Cloud Computing (CLOUD), 128-134.

[45] Song, F., Shao, H., Ming, J., Sun, J., Li, W., Yi, M., Xie, L., & Ling, H. (2024). Dynamic Memristors for Temporal Signal Processing. Advanced Materials Technologies.

[46] Iturbe, X., Camuñas-Mesa, L. A., Linares-Barranco, B., Serrano-Gotarredona, T., González, M. B., Campabadal, F., Margarit, J. M., Serra-Graells, F., Terés, L., Lanillos, P., López, V., Bisquert, J., Guerrero, A., López-Vallejo, M., Ituero, P., Juarez, E., Otero, A., Holgado, M., Rubio, A. J., Rodríguez, R. J. G., Picos, R., Miranda, E., Suñé, J., Sort, J., Roldán, J. B., Jiménez, F., Dueñas, S., Castán, H., Cirera, A., Marsal, L. F., Basterretxea, K., Astarloa, A., Barranco, F., Linares-Barranco, A., Jiménez, Á., Ollero, A., Martínez-de Dios, J. R., Gomá, R., Rodrigues, S., Del Ser, J., Torres, E., Espasa, R., Bofill-Petit, A., Turchetta, R., Goossens, A., Vergara, G., Jonuzi, T., Artundo, I., Sainz, U., Ruiz, D., González-Arjona, D., Regada, R., Pedro, M., Aramburu, A., Lara-Rapp, O., Pérez de Arrilucea, J., Terreri, S., Fernández, M., Ulloa, M. I., & Gabarrón, A. (2024). Neuromorphic Technology Insights in Spain. Proceedings of the IEEE International Conference on Nanotechnology (NANO), 1-11.

[47] Noh, M. S., Ju, D., & Kim, S. (2024). Dynamic memristor array with multiple reservoir states for training efficient neuromorphic computing. Journal of Materials Chemistry C.

[48] Yoo, S. J. B., El Srouji, L., Datta, S., Yu, S., Incorvia, J. A. C., Salleo, A., Sorger, V., Hu, J., Kimerling, L. C., Bouchard, K., Geng, J., Chaudhuri, R., Ranganath, C., & O'Reilly, R. C. (2024). Towards Reverse-Engineering the Brain: Brain-Derived Neuromorphic Computing Approach with Photonic, Electronic, and Ionic Dynamicity in 3D integrated circuits. arXiv preprint arXiv:2403.19724.

[49] Canales-Verdial, J. I. (2024). Synaptic Weights in a Neuromemristive Radioisotope Classifier. Engineering Headway, 12, 37-45.

[50] Luan, W., Zhao, Z., Li, H., Zhai, Y., Lv, Z., Zhou, K., Xue, S. M., Zhang, Q., Yan, Y., Cao, Y., Ding, G., Han, S. T., Kuo, C. C., & Zhou, Y. (2024). Near-Infrared Response Organic Synaptic Transistor for Dynamic Trace Extraction. Journal of Physical Chemistry Letters, 8845-8852.

[51] Li, Y., Sun, H., Yue, L., Yang, F., Chen, J., Zhang, X., Chen, J., Zhao, Y., Chen, K., & Li, Y. (2024). Multicolor Fully Light-Modulated Artificial Synapse Based on P-MoSe2/PxOy Heterostructured Memristor. Journal of Physical Chemistry Letters, 8752-8758.

[52] Titirsha, T., Shuvo, M. M. H., & Islam, S. K. (2024). Reliability Analysis of Phase Change Memory-Based Neuromorphic Circuits. Proceedings of the IEEE International Symposium on Very Large Scale Integration (VLSI) Design, 745-748.

[53] Zhang, W., Xiao, H., Xie, D., Zhou, Y., Duan, S., & Hu, X. (2024). A Global Self-Attention Memristive Neural Network for Image Restoration. IEEE Transactions on Emerging Topics in Computational Intelligence.

[54] Lee, Y. J., Choi, E. S., Baek, J. H., Yang, J., Hong, K., Kim, J. Y., Kim, B. S., Shin, D., Park, S. H., Im, I. H., Lee, H. J., Kim, Y. S., Choi, D., Lee, S., & Jang, H. W. (2024). Memristive Artificial Synapses Based on Brownmillerite for Endurable Weight Modulation. Small.

[55] Jia, X., Han, P., & Wang, D. (2024). Ponte: Represent Totally Binary Neural Network Toward Efficiency. Sensors, 24(20), 6726.

[56] Ren, H., Li, F., Wang, M., Liu, G., Li, D., Wang, R., Chen, Y., Tang, Y., Wang, Y., Jin, R., Huang, Q., Xing, L., Chen, X., Wang, J., Guo, C., & Zhu, B. (2024). An Ion-Mediated Spiking Chemical Neuron based on Mott Memristor. Advanced Materials.

[57] Xiao, T. P., Feinberg, B., Richardson, D. K., Cannon, M., Medu, H., Agrawal, V., Marinella, M., Agarwal, S., & Bennett, C. H. (2024). Analog fast Fourier transforms for scalable and efficient signal processing. arXiv preprint arXiv:2409.19071.

[58] Kim, H. J., Woo, S. Y., & Kim, H. (2024). Neuron Circuit Based on a Split-gate Transistor with Nonvolatile Memory for Homeostatic Functions of Biological Neurons. Biomimetics, 9(6), 335.

[59] Hu, L., Li, Z. X., Shao, J., Cheng, P., Wang, J., Vasilakos, A. V., Zhang, L., Chai, Y., Ye, Z., & Zhuge, F. (2024). Electronically Reconfigurable Memristive Neuron Capable of Operating in Both Excitation and Inhibition Modes. Nano Letters.

[60] Krichene, H., & Prasad, R. M. (2024). A dataflow architecture with distributed control for DNN acceleration. Proceedings of the Mediterranean Conference on Embedded Computing (MECO).