Build an ASP.NET Core MVC App with EF Core One-Day Hands-On Lab

Lab 14

This walks you through creating an area for Make maintenance. Prior to starting this lab, you must have completed Lab 13.

Note: Adjust any directory separators to your OS (e.g. \ for Windows, / for Mac/Linux)

Part 1: Create the Area and MakesController

- □ Create a new folder named Areas in the AutoLot.Mvc project. Right click the folder and select Add -> Area. Select MVC Area, and name it Admin. Delete the Data and Models folders from the scaffolded area. Delete the ScaffoldingReadMe.txt, as we are using attribute routing.
- ☐ Add a new controller named MakesController and update the code to the following:

```
namespace AutoLot.Mvc.Areas.Admin.Controllers;
[Area("Admin")]
[Route("Admin/[controller]/[action]")]
public class MakesController : BaseCrudController<Make, MakesController>
  public MakesController(IAppLogging<MakesController> appLogging, IMakeRepo baseRepo) :
base(appLogging, baseRepo)
  {
  }
  protected override SelectList GetLookupValues()
      return null;
  }
  // GET: Admin/Makes
  [Route("/Admin")]
  [Route("/Admin/[controller]")]
  [Route("/Admin/[controller]/[action]")]
  public override IActionResult Index()
    return base.Index();
}
```

Part 2: Create or Move the _ViewImports and _ViewStart Partials

☐ Either copy the _ViewImports.cshtml and _ViewStart.cshtml files into the Areas\Admin\Views folder or move them to the project root.

Part 3: The Make Views

Step 1: Create the Index view

☐ Add a new view named Index.cshtml to the Areas\Admin\Views\Makes folder and update the markup to the following:

```
@model IEnumerable<Make>
@{ ViewData["Title"] = "Index"; }
<h1>Index</h1>
 <a asp-action="Create">Create New</a>
<thead>
   @Html.DisplayNameFor(model => model.Name) 
     </thead>
 @foreach (var item in Model) {
     @Html.DisplayFor(modelItem => item.Name) 
      <item-edit item-id="@item.Id"></item-edit> |
      <item-details item-id="@item.Id"></item-details> |
      <item-delete item-id="@item.Id"></item-delete>
```

Step 2: Create the Details view

☐ Add a new view named Details.cshtml to the Views\Makes folder and update the markup to the following:

Step 3: Create the Create view

☐ Add a new view named Create.cshtml to the Views\Makes folder and update the markup to the following:

```
@model Make
@{ ViewData["Title"] = "Create"; }
<h1>Create</h1>
<h4>Make</h4>
<hr/>
<form asp-action="Create">
  <div class="row">
    <div class="col-md-4">
      <div asp-validation-summary="ModelOnly" class="text-danger"></div>
        <label asp-for="Name" class="col-form-label"></label>
        <input asp-for="Name" class="form-control"/>
        <span asp-validation-for="Name" class="text-danger"></span>
     </div>
  </div>
  <div class="d-flex flex-row mt-3">
    <input type="submit" value="Create" class="btn btn-primary"/>&nbsp;&nbsp; &nbsp; &nbsp;
    <item-list></item-list>
  </div>
</form>
@section Scripts {
    @{ await Html.RenderPartialAsync("_ValidationScriptsPartial"); }
}
```

Step 4: Create the Edit view

Add a new view named Edit.cshtml to the Views\Makes folder and update the markup to the following: @model Make @{ ViewData["Title"] = "Edit"; } <h1>Edit</h1> <h4>Make</h4> <hr/> <form asp-action="Edit"> <div class="row"> <div class="col-md-4"> <div asp-validation-summary="ModelOnly" class="text-danger"></div> <div> <label asp-for="Name" class="col-form-label"></label> <input asp-for="Name" class="form-control"/> </div> <input type="hidden" asp-for="Id"/> <input type="hidden" asp-for="TimeStamp"/> </div> </div> <div class="d-flex flex-row mt-3"> <input type="submit" value="Save" class="btn btn-primary"/> <item-list></item-list> </div> </form> @section Scripts { @{ await Html.RenderPartialAsync(" ValidationScriptsPartial"); } }

Step 5: Create the Delete view

Add a new view named Delete.cshtml to the Views\Makes folder and update the markup to the following:

```
@model Make
@{ ViewData["Title"] = "Delete"; }
<h1>Delete</h1>
<h3>Are you sure you want to delete this?</h3>
<div>
  <h4>Make</h4>
  <hr />
  <dl class="row">
    <dt class = "col-sm-2">@Html.DisplayNameFor(model => model.Name) </dt>
    <dd class = "col-sm-10">@Html.DisplayFor(model => model.Name)</dd>
  </dl>
  <form asp-action="Delete">
    <input type="hidden" asp-for="Id" />
    <input type="submit" value="Delete" class="btn btn-danger" /> |
    <item-list></item-list>
  </form>
</div>
```

Part 4: Update the _Menu Partial

☐ Add a new menu item to the _Menu.cshtml partial for navigation to the Admin Area:

class="nav-item">
 Makes Admin<i class="fas fa-cog"></i>

Summary

The lab created the area for Make maintenance completed this hands-on lab.

Next Steps

The next lab will add in custom validation attributes.