

Stitcher Capacity Analysis:
Charter Internal Note.
Preliminary Draft Version 1.1.0

Brad Schoenrock
Video Operations Engineering
Charter Communications
Greenwood Village, CO

July. 2019

Contents

1	Introduction	3
2	QAM Bandwidth Availability & Analysis	3
3	Conclusion	4
A	Appendix A Example QRM Configuration	6
B	Appendix B STBs by SGID	7

1 Introduction

Spec-Guide QAM bandwidth was initially a concern brought up as a possible cause of Guide Unavailable, Failure to Tune messages, and a potentially call volume generating problem. Spec-Guide QAM bandwidth is a limited resource, which scales with the number of STBs, so the capacity of the Spec-Guide QAMs is another aspect of this concern to be investigated. The architecture of the platform dictates that each service group gets exactly two Spec-Guide QAMs to serve it, with no more or less. This creates a situation where the RF bandwidth of the QAMs dictate the maximum number of STBs a service group can support. Since the QAMs themselves can't output more bandwidth (They are fixed devices that don't lend themselves to upgrades) and our architecture dictates that we can't add more than two QAMs per service group, this means that the only lever that is available to resolve such issues is managing the size and number of our service groups. We (ISP) does this routinely with service group splits and merges. When service groups get too large they are split into two different service groups, and when small service groups are near each other they are collapsed into one service group.

On a service group by service group level the QAM bandwidth is managed on the CSM by the QAM Resource Manager (QRM). The QRM is set up through configuration files, topology.xml and programs.xml. These config files define the total bandwidth output capability of the QAM for the QRM, the output frequency of the QAM, and the bandwidth expected for each type of stream (SD vs. HD, etc...) in both steady state operations as well as a maximum bandwidth usage. In this way we can monitor estimated QAM usage and ensure there aren't any overruns. As overruns would be approached, the QRM uses smartmuxing in order to serve extra sessions when current sessions are not using up their allotted bandwidth.

2 QAM Bandwidth Availability & Analysis

Each QAM has 38.8MBps of bandwidth, 37.5MBps is usable for delivery of Spec-Guide sessions. With two QAMs per service group this means each service group has 75MBps of bandwidth for delivery of Spec-Guide sessions.

The QRM is configured based on actual session usage, a sample configuration can be seen in Appendix A. The highest definition mpeg streams allocate 2.5MBps steady state, and a peak of 6MBps of RF bandwidth. By monitoring the throughput of the APEX by eye in prime time these settings are matching usage within an acceptable margin of error. Average session bandwidth is between 2-2.5MBps which is below 2.5 since not every session is HD.

In order to define a functional capacity we need to ensure enough bandwidth to serve another session. For this reason 6MBps of bandwidth should be reserved on each QAM. The remaining 63MBps of QAM bandwidth on the service group can then serve 26 HD sessions at the configured 2.5MBps each. Maximum concurrency rate of our customer base was measured to be 5% in stitcher capacity

analysis, and while that would fluctuate more on a service group basis, it still serves as a baseline for system usage. This leads to a capacity calculation of:

$$Capacity = \frac{QAM_{BWT_{total}} - 2 * MAX_{BWS_{ess}}}{SS_{BW} * Concurrency}$$

Where *Capacity* is the number of STBs a service group can handle defined by QAM bandwidth, $QAM_{BWT_{total}}$ is the total usable QAM bandwidth available on the service group, $MAX_{BWS_{ess}}$ is the max bandwidth used for a session (typically during session set up), SS_{BW} is the steady state bandwidth usage for a session, and *Concurrency* is the concurrency rate of users in the service group.

This calculation leads to a capacity of 500 STB per service group. There are several reasons why this is a low estimate.

1. The average usage is lower than an HD stream would dictate. This means more sessions can be allocated to a QAM than if they were all HD streams
2. The allocation of keeping max bandwidth in reserve per QAM is overkill. Not every session will use the max bandwidth on setup, so it is possible that less can be reserved for new sessions.
3. A 5% concurrency rate is on the high end of measured usages. Fluctuations to that value would be possible, but the majority of cases would be lower, and more users could be supported at lower concurrency rates.
4. The QRM uses smartmuxing which “Recycles” unused bandwidth in order to serve out more sessions than this analysis would indicate.

These factors provide significant leeway in capacity concerns. Operating at 500 STBs per service group would be operationally ideal, but these factors would easily allow us to reach 800 STBs per service group without concerns to the customer experience. If we were to reach 1000-1200 STBs per service group then the customer experience would begin to suffer due to Spec-Guide QAM bandwidth.

STBs per service group was measured through the CSM logs and cross checked by referencing the AMS database (but is also tracked in other ways by other groups) in order to determine if any service groups were over the relevant thresholds. Table 1 lists service groups to watch. It is noteworthy that the average number of STB per service group is 100, (which is 5x lower than the first threshold) so overall we have plenty of QAM bandwidth to go around so long as it is properly allocated.

3 Conclusion

If sessions begin to overrun the Spec-Guide QAM bandwidth beyond what smartmuxing could handle, the customer experience would be affected in a few ways. First the QRM will send a few frames of lower quality for sessions in

order to limit the bandwidth usage. Next, users would experience pixelation of the guide interface, delayed frames, and/or dropped frames in order to maintain the integrity of the Spec-Guide QAM. As a last resort the QRM will deny new sessions outright. The QRM will not allow sessions to be sent to a QAM once the bandwidth has been entirely allocated. All of these behaviours would be recorded in CSM logs.

Direct measurements of RF bandwidth in an automated fashion could be performed, but since such a system is not in place that would be time consuming, costly, and ultimately unneeded. The number of STBs per service group serves the same purpose in this case, and requires no further monitoring to be developed.

The best way to ensure we are not overrunning our QAM bandwidth is to limit the number of STBs per service group, since that is what can be controlled, and perform service group collapses and splits as needed. The recommended action is to prepare service groups for splits once they reach 500 STBs, that will leave enough time to continue to grow as those preparations are taking place. By the time a service group has 800 STBs the expectation would be that the service group is ready to split, and that would prevent it from reaching concerning levels.

The tables in Appendix B should be shared with the appropriate ISP groups to determine if service group splits are needed.

A Appendix A Example QRM Configuration

An excerpt of a QRM configuration showing bitrates for different stream types.

```
<resolution height="480">
<mpeg2>
<bitrateProfile name="Default_SD">1000000</bitrateProfile>
<bitrateProfile name="Low_SD">1000000</bitrateProfile>
<bitrateProfile name="MediumLow_SD">1200000</bitrateProfile>
<bitrateProfile name="Medium_SD">1500000</bitrateProfile>
<bitrateProfile name="High_SD">2000000</bitrateProfile>
<bitrate>4000000</bitrate>
<quant>3</quant>
<aquant>4</aquant>
<txtquant>2</txtquant>
</mpeg2>
<h264>
<bitrate>4000000</bitrate>
<quant>14</quant>
<aquant>14</aquant>
</h264>
```

```
<resolution height="720">
<mpeg2>
<bitrateProfile name="Default_HD">1600000</bitrateProfile>
<bitrateProfile name="Low_HD">1600000</bitrateProfile>
<bitrateProfile name="MediumLow_HD">1800000</bitrateProfile>
<bitrateProfile name="Medium_HD">2000000</bitrateProfile>
<bitrateProfile name="High_HD">2500000</bitrateProfile>
<bitrate>6000000</bitrate>
<quant>3</quant>
<aquant>5</aquant>
<txtquant>2</txtquant>
</mpeg2>
<h264>
<bitrate>10000000</bitrate>
<quant>10</quant>
<aquant>14</aquant>
</h264>
```

B Appendix B STBs by SGID

Tables of SGID in a given market with number of STB in that SGID. Analysis was of the QAM markets sldcmo, sldcla, renonv, pldcor, spdcsc, edprmn, mddcwi, and knwdmi.

Market	SGID in PLDCOR	STB Count
renonv	14016	691
renonv	11104	564
baysmi	48075	498
stlomo	16066	496
stlomo	14005	479
madiwi	13029	473
ashenc	22028	472
renonv	14015	465
renonv	10050	464

Table 1: Service groups with over 450 STB.