fancytests

Maths and physics tests in LaTeX

Matteo Bramardi

Version 2.0 — October 2026

Sommario

fancytests is a LaTeX package for writing school tests in mathematics and physics. It replaces the test-related part of fancylessons with a smaller and faster package. Every command takes named options (`key=value`); there are no more round, angle or bar delimiters.

It provides: a test header (full or compact) with the boxes required for students with DSA; exercises and questions with automatic score totals; multiple-choice questions with shuffled options and an exported answer key; reproducible randomisation of variants, numbers, questions and exercises; reduced versions of a test from the same source; teacher copies with solutions; standard styles for function graphs and physics diagrams.

An optional compatibility layer compiles the tests written with fancylessons without changes.

Indice

1 Getting started **3**

1.1 Installation . . . 3

1.2 A minimal test . . . 3

1.3 Package options . . . 3

1.4 Compilation speed . . . 4

2 Global settings: `\testsetup` **4**

3 The header **5**

3.1 Full header . . . 5

3.2 Compact header . . . 6

3.3 DSA boxes, times, resits . . . 6

4 Exercises **6**

4.1 Closing an exercise . . . 7

5 Questions: the `parts` environment **7**

5.1 Options of `parts` . . . 8

5.2 Options of `\itemx` . . . 8

5.3 Graphs and questions side by side . . . 8

5.4 Reduced versions . . . 9

6 Scores and grade **10**

6.1 Score commands . . . 10
6.2 Final score: \finalscore . . . 10

7 Multiple-choice questions **11**
7.1 The choices environment . . . 11
7.2 Options . . . 12
7.3 Answer key and teacher copy . . . 12
7.4 Solutions . . . 13

8 Randomisation **13**
8.1 The seed . . . 13
8.2 Variants and numbers . . . 14
8.3 Shuffling blocks . . . 14
8.4 Shuffling questions and exercises . . . 14
8.5 Several copies . . . 15

9 Graphs **15**

10 Physics diagrams **16**

11 Mathematics, units, text **17**

12 Compatibility with fancylessons **17**

13 A complete test **19**

1 Getting started

1.1 Installation

The package is a single file, `fancytests.sty`. Put it in the same folder as the document and load it in the preamble.

On Overleaf, the simplest way to keep it up to date is to link it from GitHub: *Upload* → *From external URL*, with the address

`https://raw.githubusercontent.com/⟨username⟩/fancytests/main/fancytests.sty`

The *Refresh* button of the linked file downloads the latest version. Replace `main` with a release tag (e.g. `v2.0`) to freeze a project on that version, which is advisable for tests already given.

Note. On Overleaf, use TEX Live 2023 or later (Menu → Settings → TEX Live version). Older versions lack some LATEX3 functions used by the package.

1.2 A minimal test

```
\documentclass[10pt]{article}
\usepackage{fancytests}
\usepackage[T1]{fontenc}
\usepackage{lmodern}
\renewcommand*\familydefault{\sfdefault}
\geometry{a4paper, top=15mm, bottom=15mm, left=17.5mm, right=17.5mm}
\linespread{1.25}

\testsetup{class=4M, subject=math, dsa=rid}

\begin{document}
\testheader[date=20/03/2026, title={Logaritmi}]

\exercise Risolvi le seguenti equazioni.
\begin{parts}[cols=2]
  \itemx[pts=1] $3^x = 9$
  \itemx[pts=1] $\log_2 x = 3$
\end{parts}

\exercise Rispondi.
\begin{parts}
  \itemx[pts=1] Quale funzione è sempre crescente?
    \begin{choices}
      \correct $e^x$
      \choice  $e^{-x}$
      \choice  $\ln(-x)$
      \choice[fixed] Nessuna delle precedenti
    \end{choices}
\end{parts}

\vfill
\finalscore
\end{document}
```

The package already loads babel (Italian), geometry, amsmath, amssymb, mathtools, tabularx, booktabs, enumitem, xcolor, bm, cancel, tikz, and, unless disabled, pgfplots and siunitx. Do not load them again with different options.

1.3 Package options

Options are given when loading the package: `\usepackage[seed=42, answers]{fancytests}`.

Key	Default	Meaning
subject	math	Default subject: math or physics. Sets the colour (blue or green) and the word in the title.
plots	true	Load pgfplots. With false the ftplot environment is not available, but loading is faster.
units	true	Load siunitx (for \qty, \num, ...), set up with the decimal comma.
seed	1	Seed of the random generator (section 8). 0 = a different seed at every compilation.
answers	off	Teacher copy: correct options highlighted, solution boxes printed.
nofigures	off	Fast draft: every TikZ picture and graph is replaced by an empty frame.
cache	off	Store figures and recompile them only when their code changes (package memoize). Needs shell escape, which is enabled on Overleaf.
legacy	off	Load the old fancylessons commands (section 12).

1.4 Compilation speed

On a typical test the package loads in about $0.8\,$s, against $1.9\,$s for fancylessons. Most of the remaining time is spent drawing graphs. To speed things up:

- while writing, use nofigures: pictures become placeholders;
- use cache: each picture is drawn once and reused until its code changes. The first two compilations are slower, the following ones much faster;
- if a test has no graphs, use plots=false.

Note. With cache, a picture whose content depends on randomisation through a macro defined elsewhere (e.g. a shuffled graph stored in a macro) cannot be recognised as changed. After changing such pictures or the seed, use *Recompile from scratch* on Overleaf, which empties the cache.

2 Global settings: \testsetup

\testsetup{⟨*keys*⟩} sets options for everything that follows. In the preamble it sets the defaults of the document; the same keys can be given to \testheader for a single test.

Key	Default	Meaning
subject	math	math / physics (also matematica, fisica); any other text is printed as given.
class	—	Class, e.g. 4M.
date	empty	Date; when empty, a blank __/__/____ is printed.
title	empty	Subtitle of the test (topic).
type	Verifica	Type of test: Verifica, Test, Interrogazione, ...
style	full	Header layout: full or compact.
titlebreak	auto	Compact header only: put the title on its own line when it does not fit next to the subject (auto), always (always) or never, letting it wrap (never).
dsa	none	DSA boxes: none, dsa, rid (section 3).
timing	true	Print start, end and hand-in time fields.
recovery	empty	Date of the original test, for a resit ("recupero del ...").
gradebox	VOTO	Label of the grade box.
showversion	off	Print the copy number next to the class (#1, #2, ...).
reduced	off	Reduced version: questions marked noreduced are left out.
answers	off	Same as the package option, but can be switched on and off inside the document.
labels	box	Labels of multiple-choice options: box (□) or letters (A, B, C, ...).
shuffle	true	Shuffle multiple-choice options.
shuffleparts	false	Shuffle the questions of every parts.
seed	1	Restart the random generator from this seed.
decimal	.	Decimal mark in the score boxes.
opacity	12	Intensity (%) of the coloured score boxes.
grade-min, grade-max	2, 10	Lowest and highest grade in the grade formula.
final	compact	Default style of \finalscore.
autoclose	true	Close automatically an exercise left open (section 4).

The header keys also accept Italian names: materia, classe, data, titolo, tipo, orari, recupero, voto.

3 The header

\testheader[⟨*keys*⟩] starts a new test: it prints the header, resets exercise numbers and scores and increases the copy number. It accepts all the keys of \testsetup; the values given here hold for this test only.

3.1 Full header

Example

```
\testheader[class=4M, date=20/03/2026,
  title={Logaritmo, equazioni esponenziali e logaritmiche}]
```

Nome: . . . . . **Classe 4M**

Cognome: 20/03/2026

Ora inizio: . . . . . → Ora fine: . . . . . Ora consegna: . . . . . .

VOTO

Verifica di Matematica

Logaritmo, equazioni esponenziali e logaritmiche

3.2 Compact header

`style=compact` uses about half the height. The title and the class share the first row, names and times share the second, the DSA boxes and the resit date go on an optional third row. A thin rule closes the header. When the title does not fit on the first row it moves, as a whole, to a row of its own (key `titlebreak`).

Example

```
\testheader[style=compact, class=4M, subject=physics,
  title={Onde e acustica}, dsa=dsa, recovery=12/05/2026]
```

Verifica di Fisica Onde e acustica **Classe 4M** | __/__/_____

VOTO

Nome e cognome: . . . . . | Inizio: . . . . . → Fine: . . . . . | Consegna: . . . . . .

☐ Schemi e calcolatrice ☐ Riduzione es./tempo aggiuntivo ☐ Compensazione . . . . . recupero del 12/05/2026

3.3 DSA boxes, times, resits

- `dsa=dsa`: *Schemi e calcolatrice*, *Riduzione es./tempo aggiuntivo*, *Compensazione*;
- `dsa=rid`: *Uso della calcolatrice*, *Uso di schemi/mappe*, *Riduzione es./tempo aggiuntivo*;
- `dsa=none`: no boxes.

`timing=false` removes the time fields (e.g. for oral tests); `recovery=`⟨*date*⟩ prints "recupero del ⟨*date*⟩".

Example

```
\testheader[class=4G, type=Interrogazione, subject=physics,
  timing=false, date=02/02/2026]
```

Nome: . . . . . **Classe 4G**

Cognome: 02/02/2026

VOTO

Interrogazione di Fisica

4 Exercises

`\exercise[`⟨*keys*⟩`]` prints the heading "Esercizio n" followed by the text of the exercise.

Key	Default	Meaning
`diff`	—	Difficulty from 1 to 3, shown as coloured squares.
`title`	—	A different heading, e.g. `title=Test intermedi`. `\exercise[Test intermedi]` also works.
`bonus`	off	Bonus exercise: heading "Esercizio Bonus*", points go to the bonus, not to the total. `\bonusexercise` is a shortcut.
`fixed`, `follow`	—	Used only when exercises are shuffled (section 8.4).

4.1 Closing an exercise

`\exercisescore[⟨keys⟩]` closes the exercise and prints its score box on the right. Without options the score is the sum of the questions. Options: `pts` imposes the score (`\exercisescore[5]` is the same as `[pts=5]`), `label` changes the label (default E1, E2, ...), `short` makes the box narrower. For bonus exercises use `\bonusexercisescore`; `\bonusexercisenote` prints the explanatory note.

If an exercise is not closed, the next `\exercise` or `\finalscore` closes it (key `autoclose`). Close it explicitly before a `\newpage`, otherwise the score box ends up at the top of the next page.

Example

```
\exercise[diff=2] Un'onda si propaga con velocità $v = \qty{340}{m/s}$.
\begin{parts}
  \itemx[pts=1] Calcola la lunghezza d'onda per $f = \qty{170}{Hz}$.
  \itemx[pts=0.5] Come varia $\lambda$ se $f$ raddoppia?
\end{parts}
\exercisescore

\exercise Spiega la differenza tra scala lineare e logaritmica.
\exercisescore[2]

\bonusexercise Determina il tempo di dimezzamento dello Iodio-131.
\bonusexercisescore[0.5]
\bonusexercisenote
```

Esercizio 1 Un'onda si propaga con velocità $v = 340\,\mathrm{m/s}$.

a. Calcola la lunghezza d'onda per $f = 170\,\mathrm{Hz}$. /1.0

b. Come varia λ se f raddoppia? /0.5

E1: /1.5

Esercizio 2 Spiega la differenza tra scala lineare e logaritmica.

E2: /2.0

Esercizio Bonus* Determina il tempo di dimezzamento dello Iodio-131.

EB: /0.5

* L'esercizio bonus non è obbligatorio e non è necessario svolgerlo per raggiungere il voto massimo.

5 Questions: the `parts` environment

Questions are written inside `parts`, one `\itemx` each. Letters continue across several `parts` of the same exercise and restart at every `\exercise`. The score of each question appears at the right of its first line.

5.1 Options of `parts`

Key	Default	Meaning
`stretch`	`1.5`	Spacing between questions, as a multiple of the line height (`1` = no extra space).
`cols`	`1`	Number of columns; questions fill the rows from left to right.
`start`	—	Letter to start from (`start=3` starts at "c").
`ragged`	off	Ragged-right text instead of justified.
`shuffle`	off	Shuffle the questions (section 8.4).

5.2 Options of `\itemx`

Key	Default	Meaning
`pts`	—	Points of the question; added to the exercise.
`diff`	—	Difficulty 1–3, squares at the left of the letter.
`mark`	off	Highlight the letter.
`upper`	off	Capital letter.
`noreduced`	off	Leave the question out of the reduced version.
`fixed`, `follow`	—	For shuffled questions.

Example

```
\exercise Risolvi.
\begin{parts}[cols=2, stretch=1.3]
  \itemx[pts=1] $3^x - 2^x = 0$
  \itemx[pts=1] $\log_{10}(2x-1) + \log_{10}(x) = 1$
  \itemx[pts=1, diff=2] $e^{2x} - e^{x+1} = 0$
  \itemx[pts=1, mark] $5 \cdot 2^x - 12 = 2^x$
\end{parts}
```

Esercizio 1 Risolvi.

a. $3^x - 2^x = 0$ /1.0

b. $\log_{10}(2x-1) + \log_{10}(x) = 1$ /1.0

c. $e^{2x} - e^{x+1} = 0$ /1.0

d. $5 \cdot 2^x - 12 = 2^x$ /1.0

5.3 Graphs and questions side by side


`parts` works inside a `minipage`; the scores stay at the right edge of the minipage.

Example

```
\exercise Osserva il grafico.

\begin{minipage}[c]{.36\linewidth}
  \centering
  \begin{ftplot}[xmin=-1.9, xmax=8.1, ymin=-3.9, ymax=3.1,
                 width=5.5cm, height=5cm]
    \fplot[domain=0.01:8]{ln(x)/ln(3)}
  \end{ftplot}
\end{minipage}\hfill
\begin{minipage}[c]{.6\linewidth}
  \begin{parts}[ragged]
    \itemx[pts=1] Quale funzione è rappresentata?
    \itemx[pts=1] Determina dominio e immagine.
  \end{parts}
\end{minipage}
```

Esercizio 1 Osserva il grafico.



a. Quale funzione è rappresentata? /1.0

b. Determina dominio e immagine. /1.0

5.4 Reduced versions

Mark with `noreduced` the questions to leave out of the reduced (DSA) version, and compile with `\testsetup{reduced}`. The omitted questions disappear, the following letters move up and their points are not counted. Full and reduced versions come from the same file.

Example

```
\testsetup{reduced}
\exercise Rispondi.
\begin{parts}
  \itemx[pts=1] Primo quesito.
  \itemx[pts=2, noreduced] Quesito omesso nella versione ridotta.
  \itemx[pts=1] Terzo quesito, stampato come b.
\end{parts}
\exercisescore
\testsetup{reduced=false}
```

Esercizio 1 Rispondi.

a. Primo quesito. /1.0

b. Terzo quesito, stampato come b. /1.0

E1: /2.0

6 Scores and grade

6.1 Score commands

Command	Meaning
`\score[⟨short⟩]{⟨n⟩}`	Add n points to the current exercise and print the box. Inside `parts` use `pts` instead.
`\invscore{⟨n⟩}`	Add points without printing anything.
`\scorebox[⟨short⟩]{⟨n⟩}`	Print a box without adding points.
`\emptyscorebox`	An empty box.
`\exercisescore[⟨keys⟩]`	Close the exercise (section 4).
`\currenttotal`	Total of the closed exercises so far.
`\ResetAllScores`	Reset everything (done by `\testheader`).

Scores are computed with exact decimal arithmetic and printed with up to two decimals: $1 \to 1.0$, $0.75 \to 0.75$.

6.2 Final score: `\finalscore`

`\finalscore[⟨keys⟩]` closes the last exercise, prints the summary and resets the scores, ready for the next copy.

Key	Default	Meaning
`style`	`compact`	`table`: table E1, E2, ..., EB, Tot. and formula; `compact`: formula and total on one line; `formula`: formula only; `minimal`: total only; `none`.
`max`	sum	Maximum score shown, if different from the computed total.
`bonus`	`auto`	Bonus column in the table: `auto` (only if there are bonus points), `true`, `false`.
`label`	`Tot:`	Label of the total.

The formula is voto $= \frac{\text{punti ottenuti}}{\text{punti massimi}} \cdot (\text{max} - \text{min}) + \text{min}$ with `grade-min` and `grade-max` of `\testsetup` (default 2 and 10).

Example

```
\exercise Primo. \begin{parts}\itemx[pts=2] a \itemx[pts=1.5] b\end{parts}
\exercise Secondo. \begin{parts}\itemx[pts=3] c\end{parts}
\bonusexercise Bonus. \bonusexercisescore[0.5]
\finalscore[style=table]
```

Esercizio 1 Primo.

a. a /2.0

b. b /1.5

E1: /3.5

Esercizio 2 Secondo.

a. c /3.0

E2: /3.0

Esercizio Bonus * Bonus.

EB: /0.5

E1	E2	EB	Tot.
/3.5	/3.0	/0.5	/6.5

$$\text{voto} = \frac{\text{punti ottenuti}}{\text{punti massimi}} \cdot 8 + 2 = \frac{}{6.5} \cdot 8 + 2 =$$

Example

```
\exercise Unico. \exercisescore[6]
\finalscore
```

Esercizio 1 Unico.

E1: /6.0

$$\text{voto} = \frac{\text{punti ottenuti}}{\text{punti massimi}} \cdot 8 + 2 = \frac{}{6.0} \cdot 8 + 2 =$$

Tot: /6.0

7 Multiple-choice questions

7.1 The `choices` environment

Inside `choices`, `\correct` starts the correct option and `\choice` a wrong one. Options are shuffled; the number of columns is chosen automatically: all on one row if they fit, otherwise two columns, otherwise one. Long options wrap with a hanging indent.

Example

```
\exercise Rispondi.
\begin{parts}
  \itemx[pts=1] Quale funzione ha dominio $x \ge -3$?
    \begin{choices}
      \correct $\sqrt{x+3}$
      \choice  $\log(x+3)$
      \choice  $e^{x+3}$
      \choice  $\frac{1}{x+3}$
    \end{choices}
  \itemx[pts=1] Se $f(x)$ è una decrescita esponenziale, $\ln f(x)$ è
    \begin{choices}
      \correct una retta con pendenza negativa.
      \choice  una retta con pendenza positiva.
      \choice  una curva logaritmica decrescente.
      \choice[fixed] nessuna delle precedenti.
    \end{choices}
\end{parts}
```

Esercizio 1 Rispondi.

a. Quale funzione ha dominio $x \ge -3$? /1.0

☐ $\frac{1}{x+3}$ ☐ $\sqrt{x+3}$ ☐ e^{x+3} ☐ $\log(x+3)$

b. Se $f(x)$ è una decrescita esponenziale, $\ln f(x)$ è /1.0

☐ una retta con pendenza positiva. ☐ una retta con pendenza negativa.
☐ una curva logaritmica decrescente. ☐ nessuna delle precedenti.

7.2 Options

Key	Default	Meaning
cols	auto	auto, or a fixed number of columns.
shuffle	true	Shuffle the options (global default in \testsetup).
labels	box	box or letters.
indent	0pt	Left indent (\itmindent outside parts).
before	2pt	Space above the options.
rowsep	0pt	Extra space between rows of options.
after	.25em	Space below the options.

Options of a single choice: \choice[fixed] keeps the option in its position (typically the last one, "Nessuna delle precedenti"); \correct[if={v=2}] makes the option correct only when the variant v chosen by \pick is the second (section 8).

Options can contain anything, including TikZ pictures.

7.3 Answer key and teacher copy

Every compilation writes the file ⟨*document name*⟩.key.csv, with one line per multiple-choice question:

```
versione;esercizio;quesito;risposta
1;2;b;C
1;2;c;A
2;2;b;B
```

`versione` is the copy number (one per `\testheader`), `esercizio` the exercise number (`B` for the bonus), `quesito` the letter of the question, `risposta` the letter of the correct option in the printed order. On Overleaf the file is in *Logs and output files*.

With the option `answers` (or `\testsetup{answers}`) the correct options are highlighted. Since the seed is the same, the teacher copy matches the student copies exactly.

Example

```
\testsetup{answers, labels=letters}
\exercise Rispondi.
\begin{parts}
  \itemx[pts=1] Capitale d'Italia?
    \begin{choices}
      \correct Roma \choice Milano \choice Torino \choice[fixed] Nessuna
    \end{choices}
\end{parts}
\begin{solution}
Roma è la capitale dal 1871.
\end{solution}
\testsetup{answers=false, labels=box}
```

Esercizio 1 Rispondi.

a. Capitale d'Italia? /1.0

A) Roma **B)** Torino **C)** Milano **D)** Nessuna

Soluzione

Roma è la capitale dal 1871.

7.4 Solutions

The `solution`[⟨*title*⟩] environment is printed only in the teacher copy (`answers`); otherwise it is ignored. The default title is *Soluzione*.

8 Randomisation

8.1 The seed

All random choices (shuffled options, questions and exercises, `\pick`, `\randint`, the old fancylessons commands) come from one generator. Its seed is fixed, so every compilation gives the same copies and the teacher copy and the answer key always match.

Command	Meaning
`\usepackage [seed=42]{fancytests}`	Seed of the whole document (default `1`).
`\testsetup{seed=42}`	Same; inside the document, it restarts the generator from that point.
`\setseed{42}`	Restart the generator from 42 here (e.g. before each class).
`seed=0`	A different seed at every compilation.

Note. Do not use `seed=0` for a real test: the answer key and the teacher copy would only match the student copies of the same compilation. To get new variants, change the number.

8.2 Variants and numbers

Command	Meaning
`\pick[`⟨*name*⟩`]{a \or b \or c}`	One of the variants at random. With a name, the choice is remembered for `\correct[if={name=2}]`.
`\randint[`⟨*name*⟩`]{`⟨*min*⟩`}{`⟨*max*⟩`}`	A random integer between min and max, remembered with the name.
`\useval{`⟨*name*⟩`}`	Print again the number drawn with that name.

Example

```
\exercise
Per quale funzione \pick[d]{$\Dom f = (1, +\infty)$ \or $\Dom f = (-1, +\infty)$}
si ha $\Ima f = \spR$?
\begin{choices}
  \correct[if={d=1}] $f(x) = -\ln(x - 1)$
  \correct[if={d=2}] $f(x) = -\ln(x + 1)$
  \choice $f(x) = -e^{x - 1}$
  \choice $f(x) = e^{x + 1}$
\end{choices}

Calcola $\randint[a]{2}{9} \cdot \randint[b]{2}{9}$.
Il risultato è $\useval{a} \cdot \useval{b} = \inteval{\useval{a}*\useval{b}}$.
```

Esercizio 1 Per quale funzione $\operatorname{dom} f = (1, +\infty)$ si ha $\operatorname{im} f = \mathbb{R}$?

☐ $f(x) = e^{x+1}$ ☐ $f(x) = -e^{x-1}$ ☐ $f(x) = -\ln(x-1)$ ☐ $f(x) = -\ln(x+1)$

Calcola $5 \cdot 4$. Il risultato è $5 \cdot 4 = 20$.

8.3 Shuffling blocks

The `shuffle[`⟨*name*⟩`]` environment shuffles a list of blocks, which are then printed with `\shuffled{`⟨*name*⟩`}{`⟨*position*⟩`}`. Useful for graphs or pictures to be placed in a random order.

Example

```
\begin{shuffle}[g]
  \block{\tikz\draw[thick] (0,0) -- (1,1);}
  \block{\tikz\draw[thick] (0,1) -- (1,0);}
  \block{\tikz\draw[thick] (0,.5) -- (1,.5);}
\end{shuffle}
(a) \shuffled{g}{1} \qquad (b) \shuffled{g}{2} \qquad (c) \shuffled{g}{3}
```

(a)  (b)  (c)

8.4 Shuffling questions and exercises

`parts[shuffle]` shuffles its questions (`\testsetup{shuffleparts}` does it for every `parts`). The environment `exercises` shuffles the exercises it contains. Letters and exercise numbers are assigned after shuffling; scores and the answer key follow.

- `fixed` keeps a question or exercise in its position (counted among the blocks: see below);
- `follow` ties it to the previous one, so they move together.

Example

```
\exercise Rispondi.
\begin{parts}[shuffle]
  \itemx[pts=1] Uno.
  \itemx[pts=1] Due.
  \itemx[pts=1] Tre: osserva il grafico.
  \itemx[pts=1, follow] Quattro: con riferimento al quesito precedente\dots
  \itemx[pts=1, fixed] Cinque (sempre nella quinta posizione tra i blocchi).
\end{parts}
```

Esercizio 1 Rispondi.

a. Uno. /1.0

b. Due. /1.0

c. Tre: osserva il grafico. /1.0

d. Quattro: con riferimento al quesito precedente... /1.0

e. Cinque (sempre nella quinta posizione tra i blocchi). /1.0

```
\begin{exercises}
  \exercise ...            % each exercise runs until the next \exercise
  \exercise[fixed] ...     % stays in its place
  \exercise[follow] ...    % moves together with the previous one
\end{exercises}
```

Limitations:

- a question tied with `follow` forms a block with the previous one; `fixed` keeps the position among blocks, so letters after a block of two move down by one;
- shuffled questions must not refer to each other by letter;
- inside `exercises`, `\exercise` must not be inside a `minipage`; keep the bonus exercise outside the environment;
- `\verb` cannot be used inside `parts`.

8.5 Several copies

`\Repeat{`⟨*n*⟩`}{`⟨*code*⟩`}` repeats a test n times. Each `\testheader` starts a new copy with new random choices; `showversion` prints the copy number, which is also the `versione` column of the answer key.

```
\newcommand{\verifica}{\input{docs/3-logaritmo/base}\newpage}
\Repeat{6}{\verifica}
```


9 Graphs

The `ftplot[`⟨*axis options*⟩`]` environment draws a function graph with the standard style `ft`: centred axes, major and minor grid, thick black curves. Successive curves change style (solid, dashed, grey, dotted) so they can be told apart in black-and-white photocopies.

`\fplot[`⟨*options*⟩`]{`⟨*expression*⟩`}[`⟨*legend*⟩`]` adds a curve; the options are those of `\addplot` (`domain`, `samples`, `dashed`, ...). Any pgfplots option can be passed to `ftplot`.

Example

```
\begin{center}
\begin{ftplot}[xmin=-4.9, xmax=5.1, ymin=-4.9, ymax=5.1, width=7cm, height=7cm]
  \fplot[domain=-5:5]{e^x - 1}[A]
  \fplot[domain=1.001:5]{-ln(x - 1)}[B]
  \fplot[domain=-0.999:5]{ln(x + 1)}[C]
  \fplot[domain=-5:-0.001]{ln(-x)}[D]
\end{ftplot}
\end{center}
```



The style can also be used in an ordinary `axis`: `\begin{axis}[ft, xmode=log]`. The default number of samples is 80; increase it with `samples=150` for curves with sharp bends.


10 Physics diagrams

TikZ styles for physics diagrams:

Key	Default	Meaning
`force`	—	Thick red arrow.
`velocity`	—	Thick blue arrow.
`vector`	—	Generic black arrow.
`axis arrow`	—	Thin arrow for axes.
`dimension`	—	Two-headed arrow for lengths.
`body`	—	Outlined body with light fill (for nodes).
`ground`	—	Grey fill for floors, slopes, walls.
`spring`	—	Spring (coil).
`continue`, `startcontinue`, `endcontinue`	`.75em`	Dotted continuation at both ends, at the start, at the end of a curve.

Example

```
\begin{center}
\begin{tikzpicture}
  \fill[ground] (0,0) -- (4,0) -- (4,2) -- cycle;
  \draw[thick] (0,0) -- (4,0) -- (4,2) -- cycle;
  \node[body, minimum size=6mm, rotate=26.57] (b) at (2.2,1.45) {};
  \draw[force] (b.center) -- ++(0,-1.1) node[right] {$m\vb{g}$};
  \draw[velocity] (b.north) -- ++(-0.9,-0.45) node[above] {$\vb{v}$};
  \draw[dimension] (0,-.3) -- node[below] {$L$} (4,-.3);
  \draw[spring] (5,0) -- (5,2);
  \draw[thick, continue, domain=-1:1, samples=40] plot ({\x+7}, {\x*\x});
\end{tikzpicture}
\end{center}
```



11 Mathematics, units, text

Command	Meaning
\spN, \spZ, \spQ, \spR[⟨*exp*⟩], \spC[⟨*exp*⟩]	$\mathbb{N}, \mathbb{Z}, \mathbb{Q}, \mathbb{R}, \mathbb{R}^2, \mathbb{C}$
\Dom, \Ima, \Sign	$\operatorname{dom} f$, $\operatorname{im} f$, $\operatorname{sgn} x$
\sen, \tg, \arcsen, \arctg	$\operatorname{sen} x$, $\operatorname{tg} x$, $\operatorname{arcsen} x$, $\operatorname{arctg} x$
\abs{⟨*x*⟩}, \norm{⟨*x*⟩}	$\lvert x\rvert$, $\lVert x\rVert$
\eqdef, \eqq	$\overset{\text{def}}{=}$, $\overset{?}{=}$
\lesq, \gesq	$\leqslant$, $\geqslant$
\vb{⟨*F*⟩}, \vect{⟨*AB*⟩}	$\vec{F}$, $\overrightarrow{AB}$
\compacteq, \quitecompacteq, \notsocompacteq	Reduce the space around the next displayed equations (3, 6, 9 pt).
\unm{⟨*u*⟩}, \sunm[⟨*exp*⟩]{⟨*u*⟩}{⟨*v*⟩}	Light units: $3\,\mathrm{kg}$, $9.8\,\mathrm{m/s^2}$. For full units use siunitx: \qty{340}{m/s} gives $340\,\mathrm{m/s}$.
\tbf, \tit, \tbfit, \trm	Bold, italic, bold italic, roman.
\red, \bred, \blue, \bblue	red, **bold red**, blue, **bold blue**.
\hlc[⟨*colour*⟩]{⟨*text*⟩}, \highlight{⟨*text*⟩}	grey background , subject colour .
\dotline{⟨*length*⟩}	A dotted line to fill in: . . . . .

Colours: MathsBlue, PhysicsGreen, SubjectColor (the colour of the current subject) and the colour-blind friendly palette FriendlyRed, FriendlyOrange, FriendlyYellow, FriendlyGreen, FriendlyForest, FriendlyBlue, FriendlyDenim, FriendlyMidnight.

12 Compatibility with fancylessons

With \usepackage[legacy]{fancytests} the tests written with fancylessons compile without changes. The old commands are read only when the option is given, so they do not slow down new tests. In legacy mode

exercises are not closed automatically, as in fancylessons.

fancylessons	**fancytests**
`\mathtestheader[rec]{4M}{date}{title}(dsa)`	`\testheader[class=4M, date=..., title=..., dsa=dsa]`
`\physteстheader`, `\physinttestheader`, ...	`subject=physics`, `type=Interrogazione`, `timing=false`
`\begin {scoredlist}(1.5)<L> ... & \score {1}\\`	`\begin {parts}[ragged] ... \itemx[pts=1]`
`splitlist`, `threesplitlist`	`parts[cols=2]`, `[cols=3]`
`\randomfouroptions{a}{b}{c}{d}(.5)<L>|0pt|`	`\begin {choices} \correct a \choice b ...`
`\randomfouroptionsline`, ...`list`, ...`plusone`...	`choices[cols=4]`, `[cols=1]`, `\choice[fixed]`
`\randOp{a}{b}`, `\randOpThree`, `\randSign`	`\pick{a \or b}`, `\pick{+ \or -}`
`\randIntR{1}{9}`, `\randInt`	`\randint{1}{9}`
`\pgfmathdeclarerandomlist` + `\prunelist`	`shuffle` + `\shuffled`
`\minimalfinalscore` + `\finalscorenotable`	`\finalscore[style=compact]`
`\finalscorenotable`	`\finalscore[style=formula]`
`\overrideAllColors{`⟨*c*⟩`}`	`\colorlet{SubjectColor}{c}`

Also available in legacy mode: `tflist`, `splittflist`, `tflistinv`, `\truefalse`, `\truefalseinv`, `\twooptions`, `\fouroptions`, `\fouroptionslist`, `\fiveoptionslist`, `\randomthreeoptionsline`, `\randomfiveoptions`(`line`, `list`), `\randomfourplusoneoptionslist`, `\mathscore`, `\physscore`, `\intermediatetest`, `\lengthof`, `\nthof`, `notex*`, `\mathsol`, `\physsol` and the unit shortcuts `\unmeter`, `\unmpers`, ...

Note. The old option macros do not know which option is correct, so their questions do not appear in the answer key. To use the key, rewrite them with `choices` and `\correct`.

13 A complete test

```
\documentclass[10pt]{article}
\usepackage[seed=2026]{fancytests}
\usepackage[T1]{fontenc}
\usepackage{lmodern}
\renewcommand*\familydefault{\sfdefault}
\geometry{a4paper, top=15mm, bottom=15mm, left=17.5mm, right=17.5mm}
\linespread{1.25}

\testsetup{class=4M, dsa=none, style=compact, showversion}

\newcommand{\verifica}{%
  \testheader[date=20/03/2026, title={Logaritmi}]

  \exercise Risolvi le seguenti equazioni.
  \begin{parts}[cols=2, shuffle]
    \itemx[pts=1] $3^x - 2^x = 0$
    \itemx[pts=1] $\log_{10}(2x-1) + \log_{10}(x) = 1$
    \itemx[pts=1, noreduced] $2^x + 2 = 0$
    \itemx[pts=1, noreduced] $5 \cdot 2^x - 12 = 2^x$
  \end{parts}

  \exercise Rispondi.
  \begin{parts}
    \itemx[pts=1] Quale funzione è sempre crescente?
      \begin{choices}
        \correct $e^x$ \choice $e^{-x}$ \choice $-\ln x$
        \choice[fixed] Nessuna
      \end{choices}
  \end{parts}
  \begin{solution} $e^x$ è crescente perché la base è maggiore di 1. \end{solution}

  \vfill
  \finalscore
  \newpage}

\begin{document}
\Repeat{4}{\verifica}          % 4 different copies
% \testsetup{reduced}          % reduced (DSA) version
% \usepackage[answers]{...}    % teacher copy: same seed, same copies
\end{document}
```