



C++ Programming

Instructor: Rita Kuo

Office: CS 520E

Phone: Ext. 4405

E-mail: rita.kuo@uvu.edu



Mapping zyBooks Chapters


| Topic | zyBooks Chapter |
|------------------------|-----------------|
| Structures | 8.1, 8.2 |
| Arrays of Structures | 8.2 |
| Structures and vectors | 8.3, 8.4 |



Struct

Review - List in Real Life

- It is often the case in computer science that you will process a list of items



| | Date | Item | In/Out | Balance |
|---|------|-------------------|---------|----------|
| a | 7/1 | Opening deposit | + 16.00 | \$ 16.00 |
| b | 7/2 | Weekly credit | + 3.00 | \$ 19.00 |
| c | 7/3 | Dollar deposit | | |
| d | 7/5 | Gift from Grandma | | |
| e | 7/8 | Shopping - game | | |
| f | 7/8 | Weekly credit | | |
| g | 7/9 | Sunday School | | |
| h | 7/10 | Dollar deposits | | |
| i | 7/11 | Gift for Dad | | |

Course Toolkit

Display: All Academic Units Spring 2006 Go
☐ Show Hidden Courses

Course List - Spring 2006
Click on a course number for additional course info and course tools.
Data current as of Jan 10, 2006 12:00 AM

| Course Number | Course Title | Days | Time | Room | Course Roster | Photo Roster | Class Email | Hide Course |
|--|---------------------------|------|---------------------|-----------|----------------------|--------------|-------------|--------------------------|
| Boulder Main Campus | | | | | | | | |
| CSCI 1200 010 | INTRO TO COMPUTING | TR | 12:30 PM - 1:45 PM | ECCR 1B40 | | | | <input type="checkbox"/> |
| CSCI 6950 931 | MASTER'S THESIS | TBA | | | No Students Enrolled | | | <input type="checkbox"/> |
| TLEN 5440 001 | MULTIMEDIA NETWORKING | TR | 11:00 AM - 12:15 PM | ECCS 1B28 | | | | <input type="checkbox"/> |
| Continuing Education Credit Courses | | | | | | | | |
| CSCI 7000 701 | TPC-MULTIMEDIA NETWORKING | TR | 11:00 AM - 12:15 PM | | | | | <input type="checkbox"/> |

Note: The Course Toolkit database server is updated from 3:00 am to 4:30 am every night. Complete course information may not be available during those times.

3 PC CHICKEN & IND. FRIES \$6.98
Includes 3pcs of chicken, ind. fries.
Limit of one coupon per customer, per visit. Redeemable at participating KFC Restaurants. Not valid with any other offer. Not valid for on-line orders. Premium charge for white meat where available. Please present coupon when ordering. All orders subject to applicable taxes. No Substitutions. Expires Oct 6th, 2013.

3 PC CHICKEN & IND. FRIES \$6.98
Includes 3pcs of chicken, ind. fries.
Limit of one coupon per customer, per visit. Redeemable at participating KFC Restaurants. Not valid with any other offer. Not valid for on-line orders. Premium charge for white meat where available. Please present coupon when ordering. All orders subject to applicable taxes. No Substitutions. Expires Oct 6th, 2013.

4 PC CHICKEN & IND. FRIES \$8.98
Includes 4 pcs of chicken, ind. fries.
Limit of one coupon per customer, per visit. Redeemable at participating KFC Restaurants. Not valid with any other offer. Not valid for on-line orders. Premium charge for white meat where available. Please present coupon when ordering. All orders subject to applicable taxes. No Substitutions. Expires Oct 6th, 2013.

TWO CAN DINE BIG CRUNCH® or ZINGER® \$13.98
Includes 2 Big Crunch® or 2 Zinger® sandwiches, 2 ind. fries and reg. soft drinks.
Limit of one coupon per customer, per visit. Redeemable at participating KFC Restaurants. Not valid with any other offer. Not valid for on-line orders. Premium charge for white meat where available. Please present coupon when ordering. All orders subject to applicable taxes. No Substitutions. Expires Oct 6th, 2013.

14 PC FAMILY SPECIAL \$28.98
Includes 14 pcs of chicken, lg. fries, and 2 med. salads
Limit of one coupon per customer, per visit. Redeemable at participating KFC Restaurants. Not valid with any other offer. Not valid for on-line orders. Premium charge for white meat where available. Please present coupon when ordering. All orders subject to applicable taxes. No Substitutions. Expires Oct 6th, 2013.

Review - Variables

■ Types

- Specify what kind of data it will hold
- Basic data types are **integers** (**short**, **int**, **long**), **real numbers** (**float** or **double**), or **characters** (**char**).
- **int**: hold integer values, i.e., whole numbers such as 7, -11, 0, etc.
 - The largest **int** value is typically 2,147,483,647 but can be as small as 32,767
- **float**: can store numbers with digits after the decimal point, such as 379.125
 - Slower than **int** in arithmetic operation
 - Is often an approximation of the number. E.g., **0.1** in a float variable might be 0.099999999999999987 stored in the system.
- **Variables must be declared before they can be used**

Review - Array

■ Array declaration

- Syntax: `type name[length]`
 - `type` is the data type of the array
 - `name` is the name you use to reference the array
 - `length` is the number of elements in the array, which is always **one more than the last index of the array**
- Example, create an array to hold a 1000 integers
`int a[1000];`
- Another way to initialize array, which makes your code more maintainable, is to use a preprocessor constant
`const int SIZE = 1000;`
`int a[SIZE];`
- Like other variables in C, declaring them does not initialize them



Structures

Structure and Array

■ Array

- All elements of an array have the **same** type
- To select an array element, we specify its **position** (as an **index**)

■ Structure

- The elements (**members**) **aren't** required to have the same data type
- The members of a structure have **names**; to select a particular member, we specify its name, not its position

Structure

- Define a structure

- `struct` *structure_name* {
 member_type1 member_name1;
 member_type2 member_name2;
 ...
};

- Example

- ```
struct point_t {
 double x;
 double y;
};
```

# Structure

- Declaring a structure variable

- `struct` *structure\_name* *variable\_name*;

- Example

- `struct` `point_t` `pt1`;

- `struct` `point_t` `pt2`;

- Initializing Structure Variables

- Prepare a list of values to be stored in the structure and enclose it in braces

- Example:

- `struct` `point_t` `pt1` = {200.0, 200.0};

- The values in the initializer must appear in the same order as the members of the structure.

# Structure

## ■ Accessing Structure Members

- Structure member operator: ., also called the dot operator

- Example:

```
cout << "(" << pt1.x << ", " << pt2.x << ");
```

- Designated Initializers

```
struct point_t pt1 = {.y = 200.0, .x = 100.0};
```

## ■ Where to define structures?

- Generally defined in a **header file** along with **function prototype**
- Can defined them at the top of **.c** file

# Structure

- Create `point.h` with the following codes

```
#ifndef POINT_H
#define POINT_H

struct point_t {
 double x;
 double y;
};

// function prototypes

#endif
```

# Structures as Arguments and Return Values

## ■ Structures as Arguments

- Pass a structure to a function require making a copy of all members in the structure
- Example:

[point.c](#)

```
double distance(struct point_t p, struct point_t q)
{
 return sqrt(pow(p.x - q.x, 2) + pow(p.y - q.y, 2));
}
```

[pts.c](#)

```
int main(void)
{
 struct point_t pt1 = {0.0, 0.0};
 struct point_t pt2 = {3.0, 4.0};
 double d;


 d = distance(pt1, pt2);

 return 0;
}
```

# Review - Memory Layout

## ■ Memory

- Variables correspond to locations in the computer's memory



# Structures as Arguments and Return Values

## ■ Structures as Arguments

- Pass a structure to a function require making a copy of all members in the structure
- Example:

`point.c`


```
double distance(struct point_t p, struct point_t q)
{
 return sqrt(pow(p.x - q.x, 2) + pow(p.y - q.y, 2));
}
```

`pts.c`

```
int main(void)
{
 struct point_t pt1 = {0.0, 0.0};
 struct point_t pt2 = {3.0, 4.0};
 double d;

 d = distance(pt1, pt2);

 return 0;
}
```



# Structures as Arguments and Return Values

- Structures as Arguments
  - Pass the struct parameters by references

point.c


```
double distance(struct point_t &p, struct point_t &q)
{
 return sqrt(pow(p.x - q.x, 2) + pow(p.y - q.y, 2));
}
```

pts.c

```
int main(void)
{
 struct point_t pt1 = {0.0, 0.0};
 struct point_t pt2 = {3.0, 4.0};
 double d;

 d = distance(pt1, pt2);

 return 0;
}
```





# Structures as Arguments and Return Values

## ■ Structures as Arguments

- Pass a structure to a function require making a copy of all members in the structure
- Example:


point.c

```
struct point_t init_point(double x, double y)
{
 struct point_t pt;
 pt.x = x;
 pt.y = y;
 return pt;
}
```

pts.c

```
int main(void)
{
 struct point_t pt1 = init_point(0.0, 0.0);

 return 0;
}
```



# Structures as Arguments and Return Values

## ■ Structures as Arguments

- Another way to solve the problem
- We typically pass structs to functions by **reference**.


point.c

```
void init_point(struct point_t &pt, double x, double y)
{
 pt.x = x;
 pt.y = y;
}
```

pts.c

```
int main()
{
 struct point_t pt1;
 init_point(pt1, 0.0, 0.0);

 return 0;
}
```



# Nested Structure

- Nesting one kind of structure inside another
- Example

```
struct person_name {
 string first;
 char middle_initial;
 string last;
};

struct student {
 struct person_name name;
 int id, age;
 char gender;
};

int main()
{
 struct student std1 = {"John", 'A', "Doe"}, 32, 21};
 cout << "Student's first name is " << std1.name.first << endl;

 return 0;
}
```



# Arrays of Structures

# Review - Array

## ■ Array declaration

- Syntax: `type name[length]`
  - `type` is the data type of the array
  - `name` is the name you use to reference the array
  - `length` is the number of elements in the array, which is always **one more than the last index of the array**
- Example, create an array to hold a 1000 integers  
`int a[1000];`
- Another way to initialize array, which makes your code more maintainable, is to use a preprocessor constant  
`const int SIZE = 1000;`  
`int a[SIZE];`
- Like other variables in C, declaring them does not initialize them

# struct Arrays

- Declaration

- `struct structure_name variable_name[size];`

- Example:

- `struct point_t pts[10];`

- Visit elements in the struct array

- As same as visiting elements in array with primary data types

- Example:

- ```
struct point_t origin = {0.0, 0.0};
for (i = 0; i < 10; i++) {
    cout << "distance to origin: "
        << distance(pts[i], origin) << endl;
}
```

struct Arrays

■ Example

- Find the distance of an array of points to the origin

[pts.c](#)

```
int main()
{
    const int NPOINTS = 5;
    int i;
    double dist[NPOINTS];
    struct point_t pts[NPOINTS] =
        {{3.5, 7.8}, {3.0, 4.0}, {2.0, 8.5},
         {6.3, 8.9}, {5.0, 5.0}};

    distance_to_origin(pts, NPOINTS, dist);

    for (i = 0; i < NPOINTS; i++)
        cout << dist[i] << "\t";
    cout << endl;

    return 0;
}
```

struct Arrays

■ Example

- Find the distance of an array of points to the origin

[point.c](#)

```
void distance_to_origin(struct point_t p[], size_t len, double d[])
{
    int i;
    struct point_t origin = {0.0, 0.0};

    for (i = 0; i < len; i++) {
        d[i] = distance(p[i], origin);
    }
}
```


struct Arrays

■ Example

- Find the distance of an array

```
void distance_to_origin(struct point_t pts, unsigned long len, double* d)
{
    int i;
    struct point_t origin;

    for (i = 0; i < len; i++)
        d[i] = distance_to_origin(&pts[i], &origin);
}
```

main

NPOINTS

int

5

i

int

?

dist

array

| 0 | 1 | 2 | 3 | 4 |
|--------|--------|--------|--------|--------|
| double | double | double | double | double |
| ? | ? | ? | ? | ? |

pts

array

| 0 | 1 | 2 | 3 | 4 |
|----------------|----------------|----------------|----------------|----------------|
| object point_t | object point_t | object point_t | object point_t | object point_t |
| x | x | x | x | x |
| double | double | double | double | double |
| 2.5 | 3 | 2 | 6.3 | 5 |
| y | y | y | y | y |
| double | double | double | double | double |
| 7.8 | 4 | 8.5 | 8.9 | 5 |

distance_to_origin(point_t*, unsigned long, double*)

| | |
|--------|----------------|
| p | pointer |
| len | size_t |
| | 5 |
| d | pointer |
| i | int |
| | ? |
| origin | object point_t |
| | x |
| | double |
| | ? |
| | y |
| | double |
| | ? |



Structures and vectors

struct vectors

■ Example

- Find the distance of an array of points to the origin

[pts.c](#)

```
int main()
{
    const int NPOINTS = 5;
    int i;
    double dist[NPOINTS];
    vector<struct point_t> pts =
        {{3.5, 7.8}, {3.0, 4.0}, {2.0, 8.5},
         {6.3, 8.9}, {5.0, 5.0}};

    distance_to_origin(pts, NPOINTS, dist);

    for (i = 0; i < NPOINTS; i++)
        cout << dist[i] << "\t";
    cout << endl;

    return 0;
}
```

struct vectors

■ Example

- Find the distance of an array of points to the origin

[point.c](#)

```
void distance_to_origin(vector<struct point_t> &p, size_t len,
                        double d[])
{
    int i;
    struct point_t origin = {0.0, 0.0};

    for (i = 0; i < len; i++) {
        d[i] = distance(p.at(i), origin);
    }
}
```

struct vectors

■ Example


- Find the distance of an array of points to the origin

[point.c](#)

```
void distance_to_origin(vector<struct point_t> &p, size_t len,
                        double d[])
{
    int i;
    struct point_t origin = {0.0, 0.0};

    for (i = 0; i < len; i++) {
        d[i] = distance(p.at(i), origin);
    }
}
```

struct vectors



struct vectors

- Example: Seat structure

```
#include <iostream>
#include <vector>
#include <string>
using namespace std;

struct Seat {
    string firstName;
    string lastName;
    int amountPaid;
};
```

struct vectors

- Example:

- Seat structure

```
#include <iostream>
#include <vector>
#include <string>
using namespace std;

struct Seat {
    string firstName;
    string lastName;
    int amountPaid;
};
```


struct vectors

■ Example:

- Seat structure related functions - Seat structure only

```
void SeatMakeEmpty(Seat& seat) {
    seat.firstName   = "empty";
    seat.lastName    = "empty";
    seat.amountPaid  = 0;
}

bool SeatIsEmpty(Seat seat) {
    return(seat.firstName == "empty");
}

void SeatPrint(Seat seat) {
    cout << seat.firstName << " ";
    cout << seat.lastName << ", ";
    cout << "Paid: " << seat.amountPaid << endl;
}
```

struct vectors

■ Example:

- Seat structure related functions - for Seat vector

```
void SeatsMakeEmpty(vector<Seat>& seats) {
    unsigned int i;
    for (i = 0; i < seats.size(); ++i) {
        SeatMakeEmpty(seats.at(i));
    }
}

void SeatsPrint(vector<Seat> seats) {
    unsigned int i;
    for (i = 0; i < seats.size(); ++i) {
        cout << i << ": ";
        SeatPrint(seats.at(i));
    }
}
```