

1. Gig / Jobs Object — Braeden

Internal Logical Files (ILFs)

Internal Logical Files (ILFs) are database tables owned and maintained by our system.

Job table

Item	Complexity	FP
Job table	Average	10

The Job table is average because it has 10+ fields and relationships to four other tables.

Category table

Item	Complexity	FP
Category table	Simple	7

Category is simple because it has only 2–3 fields with no complex relationships.

Skill table

Item	Complexity	FP
------	------------	----

Skill table	Simple	7
--------------------	---------------	----------

Skill is simple because it has only 2–3 fields with no complex relationships.

User Profile table

	Item	Complexity	FP
	User Profile table	Average	10

User Profile is average due to its 12+ fields and references to Skills and MessageThreads.

Review table

	Item	Complexity	FP
	Review table	Average	10

Review is average because it references two UserProfile objects (From and To) plus an associated Job.

External Interface Files (EIFs)

External Interface Files (EIFs) are data sources our system reads but does not own.

Supabase Auth User

Item	Complexity	FP
Supabase Auth User	Simple	5

The Supabase Auth User table is owned and managed entirely by Supabase's authentication infrastructure. We read it only to verify user identity and never write to it directly, making it an EIF rather than an ILF.

External Inputs (EIs)

External Inputs (EIs) are operations that enter the system and modify data.

Create job posting

Item	Complexity	FP
Create job posting (POST /api/jobs/)	Average	4

Creating a job is average because it writes to the Job table while also referencing Category and Skill.

Edit job

Item	Complexity	FP

Edit job (PUT /api/jobs/{jobId})	Simple	3
---	---------------	----------

Simple because it touches only one table with a single, straightforward update.

Delete job

Item	Complexity	FP
Delete job (DELETE /api/jobs/{jobId})	Simple	3

Simple because it touches only one table with a single, straightforward delete.

Mark job complete

Item	Complexity	FP
Mark job complete (PATCH /api/jobs/{jobId}/complete)	Simple	3

Simple because it touches only one table with a single, straightforward update.

Apply to job

Item	Complexity	FP
-------------	-------------------	-----------

Apply to job (POST /api/jobs/{jobId}/request)	Simple	3
--	---------------	----------

Simple because it touches only one table with a single, straightforward update.

Withdraw application

Item	Complexity	FP
Withdraw application (DELETE /api/jobs/{jobId}/request)	Simple	3

Simple because it touches only one table with a single, straightforward delete.

Accept a worker

Item	Complexity	FP
Accept a worker (POST /api/jobs/{jobId}/accept/{userId})	Average	4

Average because it updates AcceptedWorkers and must validate the user against UserProfile.

Remove accepted worker

Item	Complexity	FP
Remove accepted worker (DELETE /api/jobs/{jobId}/accept/{userId})	Simple	3

Simple because it touches only one table with a single, straightforward delete.

External Outputs (EOs)

External Outputs (EOs) are operations that produce computed or derived results. This feature has none — all data returned by the API is retrieved directly from the database with no transformation or calculation applied.

External Inquiries (EQs)

External Inquiries (EQs) are read-only operations that retrieve data without modifying anything.

Filter jobs by category

Item	Complexity	FP
Filter jobs by category	Simple	3

Simple because it applies a single filter condition to one or two tables.

Filter jobs by skills

Item	Complexity	FP
Filter jobs by skills	Simple	3

Simple because it applies a single filter condition to one or two tables.

Filter open/closed jobs

Item	Complexity	FP
Filter open/closed jobs	Simple	3

Simple because it applies a single filter condition to one or two tables.

Jobs by user

Item	Complexity	FP
Jobs by user (GET /api/jobs/user/{userId})	Simple	3

Simple because it applies a single filter condition to one or two tables.

Pending requests for a job

Item	Complexity	FP
Pending requests for a job (GET /api/jobs/{jobId}/requests)	Average	4

Average because it includes a poster-only authorization check and joins Job with UserProfile.

Reviews for a job

Item	Complexity	FP
Reviews for a job (GET /api/jobs/{jobId}/reviews)	Average	4

Average because it joins Review with two separate UserProfile references (the reviewer and the reviewed).

Threads for a job

Item	Complexity	FP
Threads for a job (GET /api/jobs/{jobId}/threads)	Simple	3

Simple because it is a straightforward filter on the MessageThread table by Job foreign key.

Total: 98 Function Points

2. Message Threads / Message Text — Braeden

Internal Logical Files (ILFs)

Internal Logical Files (ILFs) are database tables owned and maintained by our system.

Message Thread table

Item	Complexity	FP
Message Thread table	Average	10

MessageThread is average because it has 7 fields and references Users, Job, and Messages while also tracking archived and name state.

Message table

Item	Complexity	FP
Message table	Simple	7

Message is simple because it has only 4 fields.

User Profile table

Item	Complexity	FP
User Profile table	Average	10

User Profile is average for the same reasons as in the Jobs feature — 12+ fields with multiple relationships.

External Interface Files (EIFs)

External Interface Files (EIFs) are data sources our system reads but does not own.

Supabase Auth User

Item	Complexity	FP
Supabase Auth User	Simple	5

Same reasoning as the Jobs feature — we read this only to verify who the logged-in user is, and Supabase owns and manages it entirely.

External Inputs (EIs)

External Inputs (EIs) are operations that enter the system and modify data.

Create thread

Item	Complexity	FP
Create thread (POST /api/threads/)	Average	4

Average because it creates a MessageThread record while simultaneously linking a Job and setting initial participants from UserProfile.

Archive thread

Item	Complexity	FP
Archive thread (PATCH /api/threads/{threadId}/archive)	Simple	3

Simple because it performs a single, targeted update on one table.

Rename thread

Item	Complexity	FP
Rename thread (PUT /api/threads/{threadId}/name)	Simple	3

Simple because it performs a single, targeted update on one table.

Send message

Item	Complexity	FP
Send message (POST /api/threads/{threadId}/messages)	Simple	3

Simple because it performs a single, targeted update on one table.

Delete message

Item	Complexity	FP
Delete message (DELETE /api/threads/{threadId}/messages/{messageId})	Simple	3

Simple because it performs a single, targeted delete on one table.

Add participant

Item	Complexity	FP
Add participant (POST /api/threads/{threadId}/users/{userId})	Simple	3

Simple because it performs a single, targeted update on one table.

Remove participant

Item	Complexity	FP
Remove participant (DELETE /api/threads/{threadId}/users/{userId})	Simple	3

Simple because it performs a single, targeted delete on one table.

Mark messages as read

Item	Complexity	FP
Mark messages as read (triggered on thread open)	Simple	3

Simple because it performs a single, targeted update on one table.

External Outputs (EOs)

External Outputs (EOs) are operations that produce computed or derived results. This feature has none — all data returned is retrieved directly from the database with no transformation or calculation applied.

External Inquiries (EQs)

External Inquiries (EQs) are read-only operations that retrieve data without modifying anything.

All threads for logged-in user

Item	Complexity	FP
All threads for logged-in user (GET /api/threads/)	Average	4

Average because it joins MessageThread and UserProfile filtered by the current session.

Specific thread + messages

Item	Complexity	FP
Specific thread + messages (GET /api/threads/{threadId})	Average	4

Average because it joins across three tables: MessageThread, Message, and UserProfile.

Messages in thread

Item	Complexity	FP
Messages in thread (GET /api/threads/{threadId}/messages)	Simple	3

Simple because it joins only two tables with a straightforward filter.

Participants in thread

Item	Complexity	FP
Participants in thread (GET /api/threads/{threadId}/users)	Simple	3

Simple because it joins only two tables with a straightforward filter.

Threads for a job

Item	Complexity	FP
Threads for a job (GET /api/threads/job/{jobId})	Simple	3

Simple — a single foreign key filter.

Unread threads

Item	Complexity	FP
Unread threads (GET /api/threads/unread)	Average	4

Average because it joins MessageThread, Message, and UserProfile while filtering by unread status across all three.

Total: 78 Function Points