

Sound Biosynthetic Design over Iterative Grammars: A Realizability Geometry for Fungal Polyketides

Brage Eilertsen
brageei@uio.no
University of Oslo

May 2026

Abstract

Predicting a fungal natural product from its biosynthetic gene cluster (BGC) is usually posed as direct BGC $\rightarrow$ structure regression. It stalls—reported balanced accuracies of 51–68%, barely moved when a thousand bacterial BGCs are pooled with the few hundred fungal ones. We argue the target is wrong. A product is the image $y = \text{Exec}_\Theta(z; G)$ of a latent biosynthetic *program* z executed under an operator library Θ and a domain-derived grammar G , so the field’s ceiling is grammar *identifiability*—how much of z the observables pin down—not data volume.

We build a sound inverse compiler over this program space. *Forward*, a deterministic executor renders a program to a structure. *Inverse*, a beam verifier returns the exact set Z^* of programs consistent with the observables, as a typed verdict: VERIFIED, UNDER-OBSERVED (naming the next observable that collapses Z^*), or OUT-OF-GRAMMAR. Across all 326 fungal PKS in MIBiG 4.0 the beam verifier reaches 9/326; running the executor *forward*—ranking-free, hence complete by construction up to a size bound—lifts this to a **sound reach of 11** (recovering two in-grammar cores the beam’s ranking starved) and converts the *boundary* into a *certified* map: a frontier of 117 cores (83 *provable* structural-gaps and 34 mass-infeasible) with 86 larger cores reported as bounded-inconclusive, never miscounted as gaps. A corpus-wide census places the remainder on a *sound-expressibility* ladder, turning “unsolved” into a located map: which gaps are buildable, which are open research, which need a different grammar.

A cross-taxa probe locates the one hard axis: per-cycle reduction transfers trivially when each cycle’s active domains are given—that 1.00 is the ceiling by construction—but recovering it from the fixed domain set alone collapses to 0.567 across the iteration program; modular and iterative PKS thus instantiate two regimes of catalytic control. *Backward*, the same engine designs, placing a target on a *realizability geometry* of structural versus iteration-program edits, scored by a literature-curated cost that *is* the field’s measured engineering difficulty. A planner ranks the observation that most collapses Z^* per unit cost.

Prediction and design are one quantity read twice—an *identifiability–controllability duality* (Theorem 1, §10): the verifier’s consistent set and the designer’s specification space are a single observability κ_O , so one engine serves both, and the result travels, with a falsifiable prediction on RiPP biosynthesis. The stance is calibrated: the iteration-grammar wall is *established* on the prediction side (cross-taxa transfer, a bacterial control) and *pre-registered* on the design side (the product-neutral degeneracy it predicts is, as yet, beyond coverage), and the design contribution rests on measured difficulty, not on the cost model’s form. Because structure elucidation in this field proceeds by heterologous expression and NMR with mass spectrometry as triage—the route for all seven verified products we curate from primary sources—the verdict doubles as a metabologenomics triage tool naming which clusters triage settles. The observability and verdict layers are family-agnostic, demonstrated unchanged over PKS, a non-ribosomal peptide (NRPS) grammar, and a typed PKS–NRPS hybrid; only the program generator is family-specific. All tools, data, and analyses are open and reproducible from single commands.

1 Introduction

Many fungal drugs—the cholesterol-lowering agent lovastatin, the antifungal griseofulvin—are polyketides: large carbon scaffolds assembled by a multidomain enzymatic factory, the polyketide synthase (PKS), encoded by a contiguous biosynthetic gene cluster (BGC). Genome sequencing has revealed that filamentous fungi carry vast numbers of such clusters, most of them *cryptic*: no metabolite has ever been linked to them. They are widely regarded as one of the most promising untapped reservoirs of new bioactive chemistry.

Turning a cryptic fungal BGC into a candidate molecule requires answering: *what* would the cluster make? Recent machine learning has attacked this with limited success. Riedling et al. (2024) trained classical classifiers to predict the bioactivity class of fungal secondary metabolites from BGC features; trained on 314 fungal BGCs they reached balanced accuracies of 51–68%, and adding 1,003 bacterial BGCs moved this only to 56–68%. That second result is our point of departure: if the bottleneck were a shortage of fungal examples, a fourfold increase in (cross-domain) training data should help substantially. It did not. (The two ceilings measure different quantities—Riedling et al. (2024) classify bioactivity, we reconstruct structure—but we argue both reflect the same grammar mismatch, and we draw no direct numerical comparison.)

The deeper issue is the framing. *Natural-product discovery should not be posed as direct BGC $\rightarrow$ structure regression, but as verifier-grounded inference over—and design upon—latent biosynthetic programs constrained by genome-derived grammars and physical observables.* A BGC is not a molecular blueprint but a constrained program space: the product is the image $y = \text{Exec}_\Theta(z; G)$ of a latent program z under a biochemical operator library Θ and a domain-derived grammar G . We realize this as a **grammar-agnostic biosynthetic inverse compiler** (Figure 1) and run it in three directions on one spine: a grammar-specific executor enumerates legal programs *forward*; a shared observability layer and verifier collapse them against mass and MS/MS *inverse*, returning a three-state verdict; and run *backward*, the same grammar places a desired molecule on a realizability geometry against the natural manifold and ranks the experiments that would confirm it (Section 9). In this sense the framework is *neuro-symbolic*: symbolic execution and verification enforce mass balance, legal reaction structure, and observable consistency, while learned models are reserved for the genuinely high-dimensional pieces—sequence-dependent activity, stereochemistry, and hidden transition policies. More than a predictor, the executor is then a *substrate on which other models compose soundly*: a learned sequence policy can rerank within the legal set Z^* , a bioactivity model can filter it, and wet-lab build outcomes can update the realization cost—each inheriting the executor’s soundness rather than eroding it. This is the middle the field lacks: generative chemistry yields molecules with no construction plan or feasibility guarantee, retrosynthesis searches reactions to commercial reagents but ignores enzyme space, and genome mining asks only what nature already makes. An executable, cost-weighted definition of biosynthetically realizable space—each point carrying a construction program z and a verifying observable—is what a *target-directed* search over makeable chemistry requires. This stance answers a field diagnosis rather than ignoring it: Cox’s review of iterative highly-reducing PKS programming finds it an emergent property and rational engineering “extremely difficult,” naming machine learning as the way forward (Cox, 2023)—which we read as a design *constraint*, not an endorsement, requiring the architecture to stay *sound* precisely where rational reprogramming is intractable. We also scope the contribution honestly: structure elucidation in this field proceeds through heterologous expression and NMR with mass spectrometry as triage, so we build a metabologenomics *triage* tool grounded in those observables that names explicitly the clusters where triage is insufficient and structure elucidation is required. We do *not* claim a complete genome-to-structure predictor or a replacement for structure elucidation; we contribute the architecture, a characterization of the natural manifold that explains the field’s

ceiling, a realizability geometry that turns the same engine into a design tool, and cross-grammar demonstrations. Our contributions are:

1. A **grammar-agnostic inverse compiler** over biosynthetic program grammars: a sound deterministic executor and beam verifier returning the exact consistent program set Z^* behind one observable-constrained interface (Sections 3–4).
2. A **deterministic reconstructibility analysis** of fungal iterative PKS over MIBiG 4.0 (Section 6): exact-match 9/326 (lifted to a sound reach of 11 by a complete forward search, §13), a core-match *sensitivity* showing structural-similarity proxies are unreliable, and a tailoring-latent reformulation (7/107 verified near-uniquely; where a core is producible, tailoring resolves near-uniquely), with a curated literature benchmark (Section 5) and a cross-taxa transfer probe of the iteration-grammar wall (Section 6).
3. A **shared metabolomics observability layer** (Section 7): an adduct-aware, ppm-tolerant approximate verifier Z_ϵ^* , a within-grammar formula-ambiguity report, a tolerance-scored MS/MS matcher, and a minimum-sufficient-observables planner.
4. **Cross-grammar demonstrations** on PKS, NRPS, and a typed PKS–NRPS hybrid bridge (Section 8)—the same observability and verdict layers, only the program generator changing.
5. A **realizability geometry for biosynthetic design** (Section 9): every target molecule scored by its edit distance to the natural manifold on two typed axes—*structural* (domain content, with bacterial modular-PKS precedent) and *control* (the iteration program, the 0.567 frontier)—under a *literature-curated*, *super-additive* cost that encodes the field’s measured engineering difficulty, with a worked design neighbourhood, the control-axis dominance result (69:49), and an **experiment-selection planner** that ranks the next observation by expected collapse of Z^* per unit cost and names the elucidation-required designs.
6. An **identifiability–controllability duality** (Theorem 1, §10): the inference resolution Z^* and the design resolution $D(y; O)$ are the same equivalence class $[z]_O$, so prediction ambiguity and design specification freedom are one quantity κ_O at one observability frontier $\mathcal{F}_O$; instantiated on PKS, NRPS, and hybrid grammars and predicted to survive on RiPP (Corollary 3).
7. A **three-state reconstructibility verdict** (VERIFIED / UNDER-OBSERVED / OUT-OF-GRAMMAR) in which the UNDER-OBSERVED state names the next observable that would collapse Z^* , resting on a failure-mode taxonomy (operator coverage, hidden iterative control, tailoring under-constraint, non-local structure) that replaces a single accuracy score.
8. A **located coverage map and sound-expressibility criterion** (§6.2, §13, Appendix B): a corpus-wide census partitions the 326 into reachable (9), in-scope CHO (205), and heteroatom scope-boundary (112), a cap-lifted re-scan confirming the boundary is genuine (0/91 large cores reachable); a structural-proxy set-cover (an explicit upper bound) shows 178 of 205 (87%) touch a family whose sound expressibility is unproven; and a single criterion—an operator is soundly expressible iff its formula-invariant degree of freedom is a computable function of recoverable cluster features—places each missing operator on a cost ladder (rung 0–4), making the limitations a theory of which gaps are buildable, which are open research, and which are soundly inexpressible.

All numbers in this paper are produced by the open code base by a single documented command and are traceable to a git commit; Appendix A lists the commands.




Figure 1: The grammar-agnostic inverse compiler. Family-specific grammars (blue) compile a cluster’s domain alphabet into candidate programs that a sound executor renders to structures; a shared observability layer (grey) collapses the candidate set with mass and MS/MS, and a shared verifier returns a three-state reconstructibility verdict. Only the grammar and executor are family-specific; the observability and verdict layers are reused across PKS, NRPS, and hybrid grammars.

2 Background and the grammar-mismatch hypothesis

Modular vs. iterative assembly lines. Bacterial type I modular PKS—the archetype being the 6-deoxyerythronolide B synthase—are *colinear*. Each elongation module carries its own ketosynthase (KS) and acyltransferase (AT) for chain extension and an optional reductive cassette of ketoreductase (KR), dehydratase (DH) and enoylreductase (ER). The final product can be read off the linear order of modules. This clean structure-to-function map is why rule-based detectors such as antiSMASH (Blin et al., 2023) and PRISM (Skinnider et al., 2020) and the design database ClusterCAD (Eng et al., 2018; Tao et al., 2023) perform well on bacteria.

Fungal PKS are overwhelmingly *iterative*: a single set of catalytic domains is reused across N cycles, and which reductive steps fire on which cycle is governed by a program that no current tool decodes. The highly-reducing (HR), non-reducing (NR) and partially-reducing (PR) subclasses behave like distinct programming languages. The lovastatin nonaketide synthase LovB runs eight cycles with a different reduction state each time, and its own ER domain is degenerate—ER activity is supplied *in trans* by the standalone partner LovC (Ma et al., 2009). In NR-PKS a dedicated product-template (PT) domain dictates the regioselectivity of aromatic-ring cyclization (Crawford et al., 2009).

The hypothesis, sharpened to reconstructibility. We hypothesize that the 51–68% ceiling reflects a control-flow mismatch rather than a sample-size limit. We state this as a *reconstructibility* (identifiability) property, not undecidability: throughout, “computable” is shorthand for whether the per-step core is recoverable from the BGC-visible domain content under our sound executor grammar. In colinear assembly lines the per-step core *is a function of domain content* and can therefore be tabulated (ClusterCAD); in iterative assembly lines the same domain set must perform different chemistry on different cycles, so the per-step core is *not* a function of domain content and the end-product-to-program map is many-to-one and unobserved. A model trained on colinear data learns a control flow that is not merely uninformative but incorrect for fungi—the near-flat cross-domain result of Riedling et al. (2024) is exactly the prediction this hypothesis makes. The rest of this paper turns the hypothesis into measurements.

3 A verifier-grounded executor

We represent the product of an iterative synthase as the output of a discrete latent *program* executed by a sound, deterministic chemical executor (Figure 2). A program is an ordered list of catalytic




Figure 2: The executor (top) renders a program to a structure; the verifier (bottom) inverts it by beam-searching programs, executing each candidate and pruning any whose partial product cannot reach y , returning the exact consistent set Z^* .

cycles,

$$z = \{(c_t, a_t)\}_{t=1}^N, \quad (1)$$

where c_t marks a chain-elongation event and a_t is an action over the reductive cascade and tailoring chemistry. The cascade is strictly ordered—ER presupposes DH presupposes KR—giving the four reachable β -states (keto, hydroxyl, enoyl, methylene) plus an optional α -methylation (C-MeT) and a terminal chain release. The executor renders a program into a molecule, $\hat{y} = \text{exec}(z)$.

Deterministic core, not weights. Each operator is a fixed reaction encoded as a reaction SMARTS and applied with RDKit (Landrum et al., 2025): a decarboxylative Claisen condensation appends a C_2 ketide unit; KR reduces the β -ketothioester to the β -hydroxy; DH eliminates to the enoyl; ER reduces to the methylene; C-MeT α -methylates; the thioesterase/cyclase releases the chain. The growing chain is modelled as an ACP-tethered thioester whose carrier is a single sentinel atom, so the unique active thioester anchors every operator unambiguously. The core is *validated*, not trained: we confirm each operator by exact mass bookkeeping (extension $+\text{C}_2\text{H}_2\text{O}$, KR $+\text{H}_2$, DH $-\text{H}_2\text{O}$, ER $+\text{H}_2$, C-MeT $+\text{CH}_2$) and by reconstructing known polyketides. Single-mode cyclization—lactonization, the small-aromatic aldol (orsellinic, 6-MSA) and the mellein dihydroisocoumarin—is implemented; the five-class PT-domain regiochemistry of large NR-PKS and the lovastatin Diels–Alder are deliberately scoped out and flagged. The executor is a pure, deterministic function validated within the project’s regression suite (161 tests).

4 The verifier and identifiability

Because the executor is sound and deterministic and the program space is small (N typically 4–10, roughly eight admissible actions per cycle), we recover programs by enumeration rather than amortized inference. Given a target y and an operator set, a beam search emits programs, executes each (partial) program, and prunes any whose partial product cannot reach y . We accept a program into the *verified consistent set*

$$Z^* = \{z : \text{exec}(z) \simeq y\}, \quad (2)$$

where $\simeq$ is graph isomorphism up to canonicalization. Two prunes make the search cheap: a carbon-count bound and an *analytic molecular-formula* prefilter that computes a program’s released-acid formula from validated per-cycle deltas and only executes formula-consistent candidates (e.g. this takes the mellein search from 1,792 to 93 executor calls).

Validation and identifiability. On the curated benchmark the known program is contained in Z^* for all systems, and the search is deterministic and fast (mean 0.28 s/target). Observed

degeneracy on the curated set is $|Z^*| = 1$: programs are identifiable at these chain lengths. Genuine degeneracy *is* detectable when the operator set permits an alternative route—e.g. hexanoic acid is reached as acetyl + $2 \times \text{ER}$ or butyryl + $1 \times \text{ER}$, giving $|Z^*| = 2$ —so identifiability is governed by the operator-set constraints, as the formulation predicts.

4.1 Guarantees

All guarantees are stated relative to the operator library Θ , the (domain-derived) grammar G , the observable set O , and—for the tolerant mass observable (Section 7)—the mass tolerance ϵ and the adduct model. For $Z_\Theta^*(y; G, O) = \{z \in Z_\Theta(G, O) : \text{Exec}_\Theta(z; G) \simeq y\}$ the search is *sound*—every returned z executes to a structure matching y under $\simeq$ —and *relatively complete*: every legal program in the enumerated grammar that matches y is returned, up to the beam bound. That bound is load-bearing and has a realised counterexample: the β -resorcylic-acid lactone zearalenone is in the enumerated grammar—its program renders the deposited connectivity by construction once the resorcylic-macrolactone operator is registered—yet the beam does not surface that program at practical width, because the carbon-closeness ranking lets C-methylation-bearing partials crowd out the long unmethylated highly-reducing prefix; it is recovered only at impractically large widths. Relative completeness thus holds up to the bound, and on large highly-reducing cores the bound is not always practically reachable. It is deliberately *not* biologically complete: if nature uses an operator outside Θ , an empty Z^* is correct relative to Θ even though the molecule is producible *in vivo*. An empty consistent set is therefore a typed *certificate of failure mode*—missing operator, hidden control, tailoring under-constraint, or non-local pathway—not a claim of biological impossibility; the approximate verifier Z_ϵ^* inherits the same relativity, now also to ϵ and the allowed adducts.

A further relativity is *internal* to Θ , and we state it explicitly. Some operators encode characterised regiochemistry by construction: the aromatic releases apply a fixed cyclisation fold—the C2–C7 aldol of the orsellinic/6-MSA type, or the dihydroisocoumarin composite—by pattern-match to the chain, not by reading the fold-selecting product-template (PT) domain from sequence. A poly- β -keto chain generally admits more than one regiochemically valid fold (the orsellinic-type tetraketide admits the attested C2–C7 and C1–C6 PT regiochemistries (Li et al., 2010), of which Θ encodes the characterised one), so the corresponding VERIFIED verdicts are determined *relative to that curated fold* rather than by observation of the register. That fold is the grammar’s encoding of characterised enzymology, justified for the aromatic members of the reachable set—cores whose regiochemistry is experimentally established—and so curation-conditional rather than observation-determined. The one reachable core released without a cyclisation—BAB, a hydrolysis-released linear acid—carries no such condition.

Because the operator library is modular, extending the engine to complex polycyclic cascades, trans-acting tailoring events, or additional release chemistries does not require changing the shared verifier or observability layers; it requires registering new typed operators in the relevant family-specific executor.

5 A curated benchmark of fungal PKS programs

We hand-curate twelve literature-sourced fungal polyketide programs (Table 1), each a machine-readable specification of starter, per-cycle reduction/methylation, and release, with a literature citation, a provenance tag (*independent* ground truth vs. *pending* an authoritative structure), and a confidence flag. Six gate-tier entries with independent ground truth round-trip exactly through the executor; sanity entries cover the reductive extremes; harder systems (the LovB nonaketide; the TenS PKS–NRPS backbone) are retained as trace-level assets.

Table 1: Curated benchmark (excerpt). Reduction states: K keto, H hydroxyl, E enoyl, M methylene. Gate-tier entries round-trip exactly through the executor.

System	Subclass	Program (starter + cycles)	Tier
Triacetic acid lactone	NR	acetyl + K,K $\rightarrow$ lactone	gate (sanity)
Orsellinic acid	NR	acetyl + K,K,K $\rightarrow$ aldol	gate
6-Methylsalicylic acid	PR	acetyl + K,H,K $\rightarrow$ aldol	gate
Mellein	PR	acetyl + H,K,H,K $\rightarrow$ dihydroisocoumarin	gate
6-Hydroxymellein	PR	acetyl + H,K,K,K $\rightarrow$ dihydroisocoumarin	gate
2-Methylbutyric acid (LovF)	HR	acetyl + M _{+Me}	gate
LovB nonaketide	HR	acetyl + 8 cycles (+DA)	hard / Phase-2
Tenellin backbone (TenS)	HR	acetyl + 4 cycles (+NRPS)	Phase-2 trace

A finding from curation is worth stating: the executor caught a mass-balance inconsistency in a literature-pass program for mellein. The single-ketoreduction program reconstructs 6-hydroxymellein ($C_{10}H_{10}O_4$), not mellein ($C_{10}H_{10}O_3$); mellein requires a *second* ketoreduction. The verifier earns its keep by making such errors impossible to overlook.

6 Characterizing the natural manifold

The natural fungal PKS manifold has **nine exactly-reachable cores**, a **0.567 control-axis ceiling with a structural mechanistic explanation**, an **interior whose residual hardness sits on the core, not the tailoring**, and—characterizing the out-of-grammar remainder—a **corpus-wide coverage census** that sorts each gap onto a sound-expressibility ladder (§6.2) — this section characterizes its shape. We read these results not as a catalogue of where prediction fails but as the geometry the design contribution of §9 operates over: the boundary of what nature builds, the axis along which it is hard to read, and the interior, where decorations are near-uniquely recovered once a core is in hand.

6.1 The boundary: nine exactly-reachable cores

The natural manifold has **nine exactly-reachable cores**, defining its boundary: of the 326 fungal PKS entries in MIBiG 4.0, exactly nine are placed exactly by the sound grammar run inverse. That placement is a statement about *structure*; at the finer grain of the *program* the scan pins eight of the nine to a unique route ($|Z^*|=1$, VERIFIED), while the ninth—olivetolic acid—is reached as a structure but admits two sound programs at one formula ($|Z^*|=2$, program-UNDER-OBSERVED). The two routes render the *identical* structure, so no product observable separates them: the degeneracy is resolved by the genome-read starter/loading domain, not by any product measurement (Table 3’s collapse to one is *structure*-level, under a different (Θ, O)). Reach is thus 9 (structures placed) and program-verified 8 (routes pinned)—a structure-versus-program distinction of granularity, not a smaller boundary. This count is a lower bound *in principle*—some missing operators are enumerable, so coverage could move it up—but the census of §6.2 shows that increment is zero for sound, no-new-regiochemistry extension (olivetolic acid, the one such core, is now among the reachable nine), the rest gated on operators whose soundness is unproven (§13); it is a *boundary condition*, not an accuracy: the set of cores the current sound grammar places exactly, the edge from which §9 measures design distance. “Only 9” is the wrong frame; “the manifold’s boundary is here, and it is sharp” is the right one.

6.2 The coverage census: the boundary is genuine, and the remainder is mostly entangled

The nine is a *boundary* only if the unreached remainder is genuinely out of grammar rather than merely unscanned, and a *useful* boundary only if we can say what *kind* of operator each gap needs. Both are settled over the full 326 (tables in Appendix B). **The partition:** nine cores are reachable; 205 are CHO chemistry a polyketide grammar could in principle reach (the *in-scope* gap); 112 carry non-CHO atoms (N, halogen, S) and belong to a different grammar (NRPS-hybrid / halogenase — a *scope boundary*, not a coverage failure), nitrogen dominating (98 of 112). **The boundary is not a scan artifact:** the reachability search caps at $C \leq 20$ for tractability, so re-scanning all 94 larger cores with the cap lifted to $C80$ reached *zero* of the 91 conclusively tested (three exhausted the reduced budget, held inconclusive). The size cap was concealing no reachable core, so 9/326 is a real boundary of the grammar’s reach, not a tractability limit — which forecloses the most immediate objection to “only nine.” **The in-scope remainder is mostly entangled:** a structural-proxy set-cover — an explicit *upper bound* on recovery, since a core counts as proxy-recovered when all its tagged operator classes are present (necessary, not sufficient) — is concentrated into a few coarse families but dominated by non-aromatic-ring/macrolactonization (176/205), not aromatic cyclization, and overwhelmingly entangled: 178 of the 205 in-scope cores (87%) touch a family whose sound expressibility is unproven (§13), and sound extension with *no* new regiochemistry adds no further buildable core beyond the nine: the one clean single-class aromatic an already-encoded closure reaches — olivetolic acid, whose β -resorcylic core the generalized $C2 \rightarrow C7$ closure builds (now among the reachable nine, the VERIFIED cross-grammar build of Table 3) — is already inside the boundary, and the other clean aromatics need PT closures not yet encoded (new regiochemistry). So “coverage moves the nine up” is true in principle yet empty in practice today for sound, no-new-regiochemistry extension: the gain is zero, and the rest is the located research problem of §13, not scheduled engineering.

6.3 Similarity is not a reconstructibility metric

A natural temptation is to soften the boundary with a structural-similarity proxy — count a core “reconstructed” if a predicted skeleton embeds in the product. We show this proxy is *unreliable*: it swings from 9 to 160 reconstructed cores as a single nuisance parameter (the allowed ring-closure slack) is varied, and it admits non-PKS false positives (a de-heteroatomed alkaloid skeleton can embed in a polyketide chain). Similarity is therefore not a reconstructibility metric; we keep exact match as the airtight signal and use the tailoring-latent reformulation below as the principled relaxation, not a tunable proxy.

6.4 The interior: bounded by core reachability

Most MIBiG products are a PKS core plus post-PKS tailoring, so exact core-match understates reconstructibility. Moving tailoring into the latent — $z = (z_{\text{PKS}}, z_{\text{tail}})$ with a gene- and formula-budgeted edit applier — the joint search exactly reconstructs **7/107** annotated clusters (whole products including tailoring; a different target and denominator from the *nine* exact cores over all 326, §6.1). Two reproducible facts shape the interior: only 9/326 cores are built exactly (§6.1), and wherever a core is producible the tailoring search verifies near-uniquely (small $|Z^*|$). The residual hardness therefore sits on core cyclization, with tailoring near-unique once a core is in hand.

6.5 The hard axis: the iteration-grammar wall, structurally explained

The manifold’s one genuinely hard axis is per-cycle control. A cross-taxa transfer probe makes it quantitative: the per-step reduction chemistry is learnable from abundant bacterial modular data and transfers to fungal cycles *perfectly* when each cycle’s active reductive domains are given (1.00), but collapses to **0.567** when only the synthase’s fixed domain set is given — the iteration-grammar wall. The wall decomposes into a narrow highly-reducing per-cycle-reduction control wall ($\sim 9\%$ of products) and a broad, coverage-addressable aromatic-cyclization wall ($\sim 61\%$).

Why the wall is structural, not a data gap. A fungal iterative synthase reuses one set of catalytic domains across every cycle; the per-cycle outcome is fixed by the chain-length and substrate context the enzyme sees on that pass, not by any per-cycle change in the (constant) machinery. This is the precise form of Cox’s observation that highly-reducing PKS programming is an emergent property that “will remain extremely difficult” to predict rationally (Cox, 2023): it is emergent from the interaction between the constant catalytic machinery and the changing substrate context across cycles. The 0.567 is therefore not a placeholder for missing work; it is a structural ceiling for any predictor whose input is the synthase’s fixed domain content. A positive/negative control on the same predictor isolates this. Over 141 colinear bacterial clusters, predicting each module’s reduction from its *own* per-module domains reaches **0.78**; predicting it from the synthase’s single *pooled* domain set—the condition a fungal iterative synthase is in by construction—collapses to **0.50** (the modal baseline), and the fungal 0.567 sits in that pooled column. One predictor nearly doubles when given a per-step signal and falls to the wall when denied it: the deficit is the missing per-step *input*, not the model. (Whole-program exact recovery is only 0.17 even on bacteria, as per-module errors compound across the assembly line—which is why a per-step *sequence* signal helps precisely where one exists, and cannot where it does not.)

A sequence-level probe separates two questions. The cross-taxa probe folded together two questions the sequence head now lets us separate: *(i)* does protein *sequence* carry the per-step chemistry signal the domain abstraction discards, and *(ii)* would that signal, even if real, close the *fungal* wall? *(i)* Yes, on bacterial *modular* PKS, where each module carries its own ketoreductase (KR) sequence: a frozen ESM-2 head reads inactive-domain signal gene content cannot. The domain cartoon can only predict that a present KR fired, so it recovers *none* of the silent-KR clusters, while the sequence head recovers them from sequence alone (§11, leave-cluster-out). Beating the “every present KR fired” null is sub-homology signal by construction — distinguishing an active from a silent KR, both present, turns on local catalytic-motif differences, not fold identity — so no homology-clean partition is needed (and, in a single conserved Rossmann fold with a $\sim 35\%$ identity floor, none is well-defined). *(ii)* No, *structurally*: a fungal iterative synthase reuses *one* KR sequence across all its cycles, so a per-domain sequence head emits a single prediction per synthase—exactly the fixed-domain condition that yields 0.567. Sequence carries per-step chemistry where there *is* a per-step sequence (bacterial, modular) and cannot where there is not (fungal, iterative); the wall is structural, not a data gap.

This manifold — bounded by nine reachable cores, structured by the iteration-grammar wall, with an interior bounded by core reachability (tailoring near-unique where a core is in hand) — is the object the design contribution of §9 operates over. Its hard axis is exactly the axis along which the interesting designs live (§9.7), which is why the same measurement reads as a prediction ceiling here and a design frontier there.

7 Mining: genome and metabolome

The same sound executor, run *forward* as a generator rather than inverted against a known product, is an operational genome-mining tool. Because the executor is a *sound generator*, a cluster’s catalytic alphabet bounds a small enumerable set of producible cores—tiny when reduction is architecturally fixed, combinatorial for highly-reducing programs (a $\sim 13\times$ candidate-set ratio in our curated test)—which can be ranked and matched against metabolomics, recasting the reconstructibility ceiling as a constrained hypothesis generator. Genome mining is then inference over the latent program z from whatever observables are in hand, and the residual candidate set—which we measure operationally by its size, not by a calibrated entropy—falls as orthogonal observables are added (Table 2).

Table 2: The engine’s input/output contract: each observable and what it constrains. Rows distinguish retrospective verification (known product) from prospective mining (unknown product).

Observable	Constrains	If absent / noisy
domain alphabet	legal operators (grammar)	broad candidate set
domain order / subclass	macro-grammar, release mode	wrong grammar
accurate mass (formula)	reduction / edit budget	formula-isomer ambiguity
MS/MS fragments	skeleton / isomer identity	residual isomers unresolved
co-clustered tailoring genes	admissible edit families	over/under-constrained tailoring
known product (benchmark only)	retrospective verification	prospective mining mode

The observable ladder. The genome alone leaves the program highly uncertain (the 0.567 per-cycle transfer); the domain alphabet bounds the legal operators; the MS-measured molecular formula pins the reduction *count*. Conditioning the generator on the two observables a metabologenomics pipeline actually supplies—domain alphabet and mass—collapses our curated reachable set to a median of *one* candidate core (top-3 recall 9/10), so the per-cycle reduction combinatorics, and with them the 0.567 grammar wall, largely dissolve once alphabet and mass are combined. Mass alone is not always sufficient: for small cores within executor reach alphabet+mass is near-deterministic, but larger cores under a rich grammar retain formula-isomers, and these are *fragmentation*-distinguishable (a crude single-bond-cleavage fingerprint already gives all 112 formula-isomers of one C_{12} core distinct fragment sets), so predicted MS/MS resolves the residual to a single core—a domain→mass→fragmentation pipeline grounded throughout in the sound verifier. The binding constraint is then cyclization *coverage*, not computability.

A grammar-relative identifiability benchmark. A controlled benchmark over 30 sampled cores bears the ladder out: the median verified set collapses $1672 \rightarrow 219 \rightarrow 1$ across grammar $\rightarrow$ +mass $\rightarrow$ +MS/MS, and the true core is recovered 30/30 under the correct grammar and true mass but 0/30 under a deliberately wrong, non-reducing grammar—so the grammar and the mass each do real work, and the small sets are not an artefact of a tiny search space. The intermediate 219 is the complex-core regime in which mass narrows sharply but not uniquely and MS/MS supplies the uniqueness; the median-1 collapse above is the tight-alphabet small-aromatic regime. We release a reference implementation, `lpi.engine`: a single interface mapping a cluster’s domain set and observables (accurate mass, MS/MS) to ranked candidate cores and a per-cluster reconstructibility verdict.

A first real-cluster case study. To test the engine against the outside world rather than only curated or simulated targets, we ran it *blind* on a real MIBiG cluster—the 6-methylsalicylic acid synthase (BGC0001275, producer *Glarea lozoyensis*). MIBiG annotates the cluster only as class “PKS” with no per-module domains—the very gap this paper documents—so the grammar input is the canonical 6-MSAS architecture (KS-AT-DH-KR-ACP), and the sole observable is the real monoisotopic mass (152.0473, PubChem CID 11279) supplied as the $[M - H]^-$ ion at 5 ppm; the product structure is withheld from inference. The domain alphabet alone admits 1,121 producible cores, the accurate mass collapses these to a single candidate, and the engine returns VERIFIED. Only on reveal do we score it: the unique candidate is exactly 6-methylsalicylic acid (rank 1). A real EI-MS spectrum (MassBank MSBNK-Fac_Eng_Univ_Tokyo-JP008039) corroborates the molecular ion at m/z 152; being EI rather than LC-MS/MS it serves as a mass sanity reference, not a fragmentation rung, and since the mass alone is already decisive we report the MS/MS rung as not applied rather than simulate it. This is one clean real-cluster case, not a benchmark.

8 Generality across grammars

This section is an architectural proof of concept: the NRPS and hybrid candidate sets below are small *by construction* (a minimal monomer set), and the claim is generality of the shared inference-and-verdict *interface*, not biochemical coverage. The program-synthesis view of Section 1—a BGC is not a molecular blueprint but a constrained program space, $y = \text{Exec}_\Theta(z; G)$ —predicts that the engine should not be specific to polyketides: biosynthetic families differ in their program grammars and operator libraries Θ , but the *observability* layer (accurate mass, MS/MS) and the reconstructibility verdict are physical, not family-specific. We test this directly. Behind the same `infer_cluster( $G, O$ )  $\rightarrow$  ( $Z^*$ , state, next observable)` interface we implement a minimal non-ribosomal peptide (NRPS) grammar: a pure, deterministic peptide executor (amide condensation of a small monomer set; linear and head-to-tail macrocyclic release) with an exact residue-formula prefilter, presented through the identical **Grammar** protocol as the PKS generator (Table 3).

Table 3: One inference interface, two grammars. Verified candidate-set size after each observable rung, and the three-state verdict; the same mass / MS/MS / verdict machinery serves both families.

Cluster / product	Grammar	alphabet	+mass	+MS/MS	Verdict
orsellinic acid	PKS	2	1	1	verified
olivetic acid	PKS	5012	87	1	verified
cyclo(Gly–Gly)	NRPS	100	1	1	verified
glycylglycine	NRPS	576	1	1	verified
cyclo(Phe–Tyr)	NRPS	100	1	1	verified
NRPS, mass withheld	NRPS	788	—	—	under-observed

Because the observability layer consumes only executed candidate structures, the same ppm-tolerant mass recovery, adduct model, MS/MS scorer, observable ladder, and three-state verdict operate unchanged across PKS and NRPS grammars; only the program generator is family-specific. The withheld-mass row is the engine in its operative mode: from the genome alone the peptide is *under-observed*, and the verdict names the observable—accurate mass—that would collapse the candidate set.

Scope. This is a proof of *framework* generality, not NRPS biochemical coverage (the v0 grammar’s conservative scope is stated once in Section 13): the point is that a second grammar plugs into the

same inference and verdict stack, the architecture being grammar-agnostic because the shared layer reads only candidate structures.

8.1 Compositional grammars and hybrid biosynthesis

Biosynthetic families also *compose*. A PKS–NRPS hybrid is modelled as a typed composition of the two grammars,

$$z_{\text{hybrid}} = z_{\text{PKS}} \circ h_{\text{handoff}} \circ z_{\text{NRPS}} \circ r_{\text{release}}, \quad (3)$$

where h_{handoff} is an explicit amide-condensation operator joining the polyketide *linear-acid checkpoint* (Section 3) to the peptide N-terminus. The hybrid grammar does not re-implement either family: it composes the PKS generator with the NRPS monomer set, and the same adduct/ppm-tolerant mass recovery, MS/MS scorer, observable ladder, and three-state verdict run over the composed candidates unchanged (a minimal hybrid, acetoacetyl-glycine, collapses genome→mass to a single *verified* core through the identical stack). Crucially, the fungal tetramic-acid Dieckmann release—the step that converts the TenS polyketide–tyrosine intermediate into pretenellin A—is declared as a *typed but unimplemented* operator: requesting it returns an explicit out-of-grammar verdict naming the missing release operator, rather than a silent failure or a wrong structure. The scope boundary the rest of this paper describes in prose is thus made machine-checkable. The framework now spans **PKS, NRPS, and a minimal PKS–NRPS hybrid bridge** behind one inference-and-verdict interface; grammars are family-specific and composable, while observability and the reconstructibility verdict are shared.

9 Sound biosynthetic design over the iteration grammar

Running the executor forward turns a program into a structure; running the verifier inverse turns a structure into the set Z^* of programs that could have produced it. Here we run the grammar *backward*: given a desired, possibly non-natural target, we place it on a *realizability geometry* relative to the natural manifold, and we rank the experiments that would confirm it. Two results make this more than a restatement of the diagnostic half. First, the design space decomposes onto two axes that map to fundamentally different wet-lab capabilities. Second—and this is what keeps the contribution honest—the cost on those axes is the field’s *measured* difficulty of fungal PKS engineering, curated from primary literature, not an assumption we supply.

9.1 The realizability geometry: two axes

A design target is a program z_d ; its product is $y_d = \text{Exec}_\Theta(z_d; G)$. We score z_d by its edit distance to the nearest natural cluster on the manifold, decomposed into two typed axes:

- **Structural** edits change the *domain content*: add a reductive domain (`add_reductive`), swap the starter or extender (`starter`, `extender`), reprogram the release cyclase (`release`), or insert a methyltransferase de novo (`add_cmt`). These map onto bacterial modular-PKS engineering.
- **Control** edits change the *iteration program* with the domain set fixed: which cycle a present domain fires on (`reduction`, `c_methyl`) or the iteration count (`cycle_add`, `cycle_remove`). This is the iteration-grammar frontier—precisely the 1.00→0.567 wall of the cross-taxa transfer probe (§6), now read as a design dimension rather than a prediction limit.

A design at coordinate (2, 1) (two structural, one control edit) is a different proposition from one at (3, 0): the first requires reprogramming the iteration itself, the second is documented domain

engineering. Each target’s most-realizable route is the minimum-cost edit path to a natural cluster, and its *verdict*—NATURAL, ENGINEERABLE, FRONTIER, or SPECULATIVE—is read off that path. Crucially, the control axis *only exists as a design dimension* for a machine that distinguishes per-cycle firing within a fixed domain set; a tool without the iteration grammar cannot represent the edit “reprogram the ketoreductase at cycle 3,” let alone cost it (§9.7).

9.2 A literature-grounded, super-additive cost

The design enumeration bounds the cost model to the nine edit kinds that actually appear in the 1-edit neighbourhood, and we curated each from primary sources rather than scraping abstracts (two tier rulings turned on facts a search snippet stated incorrectly). The structural edits inherit the mature combinatorial-biosynthesis canon: acyltransferase/extender swaps and loading-module/starter swaps are documented (Musiol-Kroll & Wohlleben, 2018; Jacobsen et al., 1997), as are reductive-loop transplants (Kellenberger et al., 2008); de novo C-methyltransferase insertion has no precedent (the methylation literature reprograms a *present* C-MeT, never inserts one) and is scored SPECULATIVE.

The control edits are the unsolved frontier. Cox’s review of iterative highly-reducing PKS programming (Cox, 2023) states plainly that rational efforts “will remain extremely difficult” because the programme is “an emergent property... highly unpredictable.” Yet a *single* edit beside a closely related cluster is achievable: domain swaps between the tenellin and desmethylbassianin synthases mapped methylation-pattern and chain-length changes cleanly (Fisch et al., 2011). We encode exactly this shape. Structural edits sum linearly by tier; control edits are **super-additive**, growing quadratically in the number k_{ctrl} of control edits in a design:

$$\text{cost}(z_d) = \underbrace{\sum_{e \in \text{struct}} \tau(e)}_{\text{linear}} + \underbrace{\left(\sum_{e \in \text{ctrl}} \tau(e) \right) \cdot k_{\text{ctrl}}}_{\sim k_{\text{ctrl}}^2, \text{ super-additive}}, \quad (4)$$

where τ is the curated per-edit tier. The control term multiplies a sum *already* taken over the k_{ctrl} control edits by k_{ctrl} again, so it scales as k_{ctrl}^2 : one tier-2 control edit costs 2, whereas two tier-2 control edits cost $(2+2) \cdot 2 = 8$, not 4. Equation (4) thus reduces to the linear tier cost at $k_{\text{ctrl}} = 1$ (the Fisch–Cox single-edit regime) and grows quadratically as control edits stack (the Cox emergent regime). The cost model is therefore not asserted: it is the published difficulty landscape of fungal PKS engineering, written into the objective. This is the difference between “we built a design engine” and “we built a design engine whose cost model is the measured difficulty of the field.”

9.3 The worked neighbourhood of 6-MSA

Figure 3 walks one clean template—the 6-methylsalicylic acid synthase, the cluster with a verified blind real-mass match (§7)—end to end. Each row of its 1-edit neighbourhood is a build proposal carrying its (structural, control) coordinate, realizability verdict, predicted monoisotopic mass, and the observable that would confirm it. The neighbourhood separates cleanly into an **engineerable** block (single structural edits—starter swaps such as acetyl→hexanoyl at mass 244.13, release reprograms—all confirmable by accurate mass) and a **frontier** block (single control edits such as reprogramming the cycle-3 reduction), with coverage-limited out-of-grammar designs sunk below the headline. One row reads, “one documented edit (acetyl→hexanoyl) from the 6-MSA synthase, mass 244.13, verifiable by accurate mass”; another, “one iteration-program edit (reprogram cycle-3 reduction), mass 172.07, needs MS/MS.” Design distance, the predicted observable, and a verdict on whether triage suffices or structure elucidation is required—on the same line.

(S, C)	1-edit design from the 6-MSA synthase	mass (Da)	verified by
ENGINEERABLE — structural-only, documented domain engineering (9 designs)			
(1, 0)	starter swap acetyl→hexanoyl	244.13	accurate mass
(1, 0)	starter swap acetyl→butyryl	216.10	accurate mass
(1, 0)	starter swap acetyl→propionyl	202.08	accurate mass
(1, 0)	release reprogram (aromatic→lactone)	188.07	accurate mass
FRONTIER — ≥ 1 control edit, iteration-program editing (12 designs)			
(0, 1)	reprogram cycle-3 reduction (keto→DH)	172.07	+ MS/MS
(0, 1)	cycle-2 reduction KR→DH	170.06	accurate mass
(0, 1)	cycle-1 reduction keto→KR	190.08	accurate mass
(0, 1)	add a fourth cycle (+cyc4)	230.08	accurate mass

Figure 3: The worked 6-MSA design neighbourhood (`scripts/worked_design_6msa.py`): each row is a build proposal carrying its (structural, control) edit coordinate, predicted monoisotopic mass, and the observable that would confirm it. The two blocks are different *kinds* of proposal at comparable cost: a (1, 0) starter swap (acetyl→hexanoyl) is documented domain engineering a wet-lab builds today; a (0, 1) cycle-3 reduction reprogram is the iteration-grammar frontier—the axis only a sound per-cycle executor can express. Of the full neighbourhood, 9 are engineerable, 12 frontier, and 4 speculative (de-novo C-MeT, shortened chain). Design distance and verification plan on one line.

9.4 Control-axis dominance

Across the 1-edit neighbourhood of the natural manifold the control axis dominates: **69** designs lie on the frontier (involve a control edit) against **49** engineerable (structural-only), with 24 speculative. That ratio is itself a product of the literature curation—the raw, uncured count was a starker 93:34, and grounding the edit costs (demoting release to a structural domain swap, raising de novo C-MeT and iteration-count edits) softened it to a defensible margin. Fungal biosynthetic *design* is mostly iteration-program editing: the axis only a sound per-cycle executor can express.

The split is not a cost-model artifact (make design-sensitivity). That curation *softened* the ratio (93:34 → 69:49) rather than sharpening it is the reassuring direction: the tiers track the measured difficulty (Cox 2023; Fisch & Cox 2011), they were not reverse-engineered from 69:49. Three checks close the tuning objection. (i) The split is independent of the cost *form*—no design in the 1-edit neighbourhood carries ≥ 2 control edits, so the super-additive term of Eq. (4) never activates and a linear control cost returns the identical 69:49; the k^2 assumption bears on stacked edits, not this partition. (ii) Leave-one-core-out over the nine cores holds the dominance (1.32–1.50 $\times$, no flip). (iii) The ordering inverts only under a re-tiering that contradicts the record—raising a per-cycle reduction edit to SPECULATIVE, or reclassifying it structural (the latter inflates the engineerable column to 96). That 96 is a *counterfactual* count, not the committed one: reclassifying per-cycle reduction as structural is exactly the move that breaks the 0/192 feature–axis agreement (§9.5), so it shifts the cost boundary while leaving the feature-determined modality cells (49 genome / 69 trajectory) untouched—the cost boundary moves, the modality does not. This *defends* the split against a tuning objection; it does not *establish* the wall—the prediction side (§6.5) does that.

9.5 The design axes are modalities; the decisive cell is empty

Every design edit changes a feature in one of two latent modalities: *genome* (domain content, loading/AT, release cyclase—read from $\phi(B)$) or *trajectory* (which cycle a present domain fires

on, under a fixed domain set). The control axis of §9.1 *is* this modality: tagging each of the 192 edits across the 142 one-edit-neighbour designs by its feature’s modality, independently of the structural/control label, the two agree in **0** of 192 (**make design-tag**)—a proven assignment of which modality controls each edit. It is separate from how costly the edit is: the cost model *then* assigns genome edits a linear cost and trajectory edits a super-additive one (Eq. (4))—a difficulty assumption grounded in Cox 2023, one the 69:49 split is independent of (§9.4), not a consequence the modality assignment derives.

The $(m_{\text{ctrl}}, m_{\text{conf}})$ occupancy, over the 118 engineerable+frontier designs (the 24 speculative excluded from the cells), is (genome, product)=46, (genome, latent)=3, (trajectory, product)=69, and (trajectory, trajectory)=**0**—that is, 49 genome (46+3) and 69 trajectory (69+0), the same 49:69 as the dominance above. The empty cell is the framework’s sharpest honesty: the genuine product-neutral iteration-grammar degeneracy—the residual the construction points at—is un-witnessed in the reachable neighbourhood, because the chemistry that would populate it (macrolactonising highly-reducing cores) lies beyond current executor coverage. It is empty *by construction*, not by measurement; its first occupant—a same-product, same-starter, different-cycle fibre—is pre-registered against a sound macrolactonisation operator, the located research problem of §13.

9.6 The experiment-selection planner

Given a design, which experiment should one run next? The planner ranks each modelled observation o by expected information gain per unit cost, weighted by realizability:

$$\text{score}(o) = \mathbb{E}[\Delta|Z^*|] \cdot w_{\text{real}}/c_{\text{obs}}(o), \quad w_{\text{real}} = 1/\text{cost}(\text{unresolved edits}), \quad (5)$$

with speculative designs hard-excluded ($w_{\text{real}} = 0$). The two cost terms sit on different sides: observation cost c_{obs} (accurate mass 1, MS/MS 3, in committed relative units) in the denominator, and the super-additive realizability cost of Eq. (4) as the design-side weight. Because that weight is super-additive, resolving one of two stacked control edits drops the residual penalty non-linearly—so the planner reasons about the *joint resolution state* of a design, not merely the most-uncertain edge. The planner’s output is a decision tree over observation outcomes in which both children of every node are first-class: the refuted branch (the observation is inconsistent with the predicted product) carries as much information as the confirmed one.

The planner returns a typed triage verdict. VERIFIED-BY-TRIAGE: the modelled observables collapse $|Z^*|$ to near-unique. ELUCIDATION-REQUIRED: the modelled observables are exhausted and $|Z^*|$ is still large—the design must go to structure elucidation. OUT-OF-GRAMMAR: a mass observation refutes every legal program. *Naming the elucidation-required case is the contribution*: a triage tool that knows its own limits, and whose limits are typed and machine-checkable. Figure 4 contrasts two trees: 6-MSA collapses at accurate mass (a shallow tree—the planner doing its job), while the highly-reducing C₁₂ core BAB stays under-determined through mass and MS/MS (4050 → 25 → 23 candidates) and is routed to expression + NMR (the planner naming its limit).

This scoping is forced by the data, not chosen for modesty. All seven verified products in our corpus had their genome→structure link established by heterologous expression (with knockout or native expression) and NMR, with accurate mass and MS/MS serving as triage and detection—never as the sole structure-determining observable. The planner is therefore a metabologenomics *triage* tool: it answers “which observation collapses $|Z^*|$ given the genome,” not “how is this structure proven.” Evaluated retrospectively against this curated corpus it routes correctly—the small aromatics (orsellinic acid, 6-MSA, mellein, 6-hydroxymellein) verify by accurate mass, while the highly-reducing core is flagged elucidation-required—and on the design neighbourhood it steers attention to engineerable and frontier designs over speculative ones.




Figure 4: The triage planner doing its job (6-MSA, left: accurate mass collapses $|Z^*|$ to a unique core $\Rightarrow$ VERIFIED-BY-TRIAGE) and naming its own limit (BAB, right: mass then MS/MS leave $|Z^*|$ at 23 $\Rightarrow$ ELUCIDATION-REQUIRED, routed to expression+NMR). Refuted branches (OUT-OF-GRAMMAR) are rendered first-class at every node, not collapsed. Source: `scripts/planner_tree_figure.py`.

9.7 The architectural moat

The contribution is architectural, not a capability we happen to have: the control axis exists as a design dimension only for a sound executor that distinguishes per-cycle firing within a fixed domain set. “Reprogram the ketoreductase at cycle 3” is not a hard edit to a retrosynthesis tool (which works in chemical space), an enzyme-design tool (which works per protein), or a pathway tool (which ignores assembly-line grammar)—it is a sentence about an object none of them can represent. We are the missing layer between generative chemistry and protein design, and the cost on the axis is the field’s measured difficulty (Eq. (4)). That the same iteration-grammar wall is a prediction ceiling read one way (§6) and a design frontier read the other is no coincidence but a duality, stated and proved in §10: prediction ambiguity and design freedom are one observability quantity κ_O .

10 Identifiability–controllability duality

Section 6 read the iteration-grammar wall as a ceiling on *inference*; §9 read the same wall as the *design* frontier. That one measurement carries two valences (§9.7) is not a rhetorical observation but a property of the program-grammar setup itself. Stated cleanly it is a duality between identifiability and controllability that survives generalisation beyond fungal PKS, and we use it to predict where the architecture should reproduce its results on families we have not implemented.

One distinction first, and it holds for the whole paper. The duality’s *controllability* is design *specification freedom*—the number κ_O of programs an observable specification leaves open—not engineering *difficulty*, the effort of building any one of them. The word invites fusion because the design geometry (§9.7) speaks of a *control axis* and *control edits*; there “control” marks the difficulty-driving dimension—the edits the cost model (§9.2) makes expensive—not the freedom. So there are two quantities, held apart throughout: controllability (κ_O), a cardinality the duality proves; and the control axis, a difficulty the cost model assumes. They meet at exactly one place—the *modality* of the missing feature (the Remark below)—and nowhere else.

Setup. Fix a grammar G with program space $\mathcal{Z}(G)$, an operator library Θ , a sound executor $\text{Exec}_\Theta(\cdot; G) : \mathcal{Z}(G) \rightarrow \mathcal{Y}$ into a structure space $\mathcal{Y}$, and an observable set O with a projection $\text{obs}_O :$

$\mathcal{Y} \rightarrow \mathcal{S}$ onto a signature space $\mathcal{S}$ (mass, MS/MS fragmentation, domain alphabet). Composition gives the observable map of a program, $\phi_O = \text{obs}_O \circ \text{Exec}_\Theta : \mathcal{Z}(G) \rightarrow \mathcal{S}$. Two programs are *O-equivalent*, $z_1 \sim_O z_2$, iff $\phi_O(z_1) = \phi_O(z_2)$; the class $[z]_O \subseteq \mathcal{Z}(G)$ is the set of programs the chosen observables cannot tell apart from z . Two operational quantities use this directly. The *inference resolution* at a true program z under O is the verifier’s consistent set of §4,

$$Z^*(z; O) = \{ z' \in \mathcal{Z}(G) : \phi_O(z') = \phi_O(z) \} = [z]_O,$$

and the *design resolution* at a target structure y specified through O —the programs an engineer may pick from when only the observable signature of y is fixed—is $D(y; O) = \phi_O^{-1}(\text{obs}_O(y))$.

Theorem 1 (identifiability–controllability duality). For every program $z \in \mathcal{Z}(G)$ with structural image $y = \text{Exec}_\Theta(z; G)$,

$$\boxed{Z^*(z; O) = [z]_O = D(y; O).}$$

The verifier’s consistent set when y is the true product, the observable equivalence class of z , and the set of programs an observable specification of y admits as build candidates are one set. Its cardinality $\kappa_O(z) = |[z]_O|$ is simultaneously the inference ambiguity floor at z and the design specification freedom at y : no inference scheme can return fewer than κ_O candidates under O , and no design specification limited to O can rule among them without further observation.

Proof. The three sets are equal as preimages of $\phi_O(z)$ under ϕ_O ; the content is in the identifications. (i) $Z^*(z; O)$ of §4 is the verifier’s algorithmic output: by soundness of the executor (§3) every returned z' satisfies $\text{Exec}(z') \simeq y$, and by relative completeness (§4.1) every legal program with that property is returned, up to the (here saturating) beam bound. Together these state that $Z^*(z; O)$ is exactly the preimage $[z]_O$ as a set, not merely up to notation. (ii) $D(y; O)$ is the set of programs an engineer working from an observable specification of y can propose: any $z' \in [z]_O$ produces the same signature as z and is therefore indistinguishable from it under the specification, while any $z' \notin [z]_O$ violates it, so $D(y; O) = [z]_O$ in the operational sense of “candidates O alone cannot rule out.” The verifier’s algorithmic output and the designer’s specification space are thus identical as sets; the non-triviality is the identification of two operationally distinct objects with one equivalence class. $\square$

A count, not a cost. κ_O measures how many programs the observables leave open—the inference ambiguity, equal to the designer’s specification freedom. That ambiguity is not a cost. To predict is to resolve the ambiguity, and κ_O is its size, so prediction sits on this ledger—the proven one. Only how hard any one program is to *build* is the cost model’s separate, assumed concern (§9.2); the theorem licenses the equality of the two *freedoms* only.

Notation. We write $\kappa_O(y) := \kappa_O(z)$ for any $z \in \text{Exec}^{-1}(y)$; the theorem makes this well-defined, since two programs with the same structure share a signature and hence a class.

Definition 1 (observability frontier). For (G, Θ, O) the *observability frontier* is

$$\mathcal{F}_O(G, \Theta) = \{ y \in \mathcal{Y} : \kappa_O(y) > 1 \}, \tag{6}$$

the structures the observables cannot uniquely program. Theorem 1 reads at the level of $\mathcal{F}_O$: it is at once the under-observed set for inference and the multiply-routable set for design, so the triage planner of §9.6 and a design-specification planner are one query on this object, parameterised by O .

Corollary 1 (the planner is already a design planner). The triage planner of §9.6, *unmodified*, ranks experiments for design specification and for inference identification at once. By the duality the ranking $\mathbb{E}[\Delta|Z^*|]/c_{\text{obs}}(o)$ of Eq. (5) is identical to the ranking of observations by expected reduction in *design* ambiguity per unit cost; the framework needs no design-side analogue, and the routing verdicts (VERIFIED-BY-TRIAGE / ELUCIDATION-REQUIRED) carry across to design with no machinery change.

Corollary 2 (the iteration-grammar wall, both ways). Under $O = \{\text{domain alphabet}\}$, externalised per-module state in bacterial modular PKS gives $\kappa_O \approx 1$ (the 1.00 cross-taxa transfer of §6.5): inference returns single programs, and a structural specification maps to a unique build route. Compressed, state-dependent control in fungal iterative PKS gives $\kappa_O > 1$ at the same observable (the 0.567 collapse): inference is under-observed, and design admits multiple compositionally degenerate routes—the *existence* of the control axis as a design dimension (§9.1) is the duality read backward, available only to a representation that preserves the equivalence class rather than collapsing it. On the inference/design-*freedom* axis, the modular-iterative asymmetry is one quantity κ_O at one observable read in opposite directions; the engineering-*difficulty* asymmetry those literatures (Yuzawa et al., 2018; Tao et al., 2023; Cox, 2023) report tracks it only through the modality—externalised, genome-readable per-module state versus compressed, trajectory-latent state—not through κ_O directly.

Corollary 3 (cross-family prediction). The proof uses only the executor’s soundness and the verifier’s relative completeness, stated for an abstract (G, Θ, O) in §4.1, so the duality transfers to any family the framework can express. In ribosomal peptide (RiPP) biosynthesis the precursor peptide is genome-readable (small κ_O on core composition) while post-translational modification order is iteration-grammar-like (large κ_O on modification topology); the duality predicts core-residue substitutions are *both* highly identifiable and straightforward to engineer, while modification-topology edits are *both* prediction-limited and design-limited at the same frontier $\mathcal{F}_O$. This is the pattern in the lanthipeptide (Repka et al., 2017) and cyanobactin (Donia et al., 2008) engineering literatures—routine core-residue swaps, a barrier at modification-pattern reprogramming—and the duality’s content is that the two barriers are not coincidental but one quantity κ_O on one frontier. It is falsifiable on the NRPS/RiPP chassis of §8: instantiate a RiPP grammar and compute κ_O before and after modification observables.

Remark (what the duality does, and does not, unify). The duality unifies two *freedoms*, not two *difficulties*. By Theorem 1 the inference *ambiguity* at z and the design *specification freedom* at y are one cardinality κ_O : a structure under-observed for prediction is, by the same count, multiply-routable for design. A feature the genome does not fix is, by that same gap, multiply-routable: high κ_O —the proven prediction ambiguity, equal to the design freedom. It is also expensive to build, because the edits that would reach it are control edits (the difficulty axis of §9.7): high cost, the assumed engineering difficulty. The two surface hardnesses—“hard to predict” and “hard to engineer”—share a cause but are not one quantity: the first is κ_O , a cardinality the duality proves; the second is the cost (§9.2, Eq. (4)), a quantity the model assumes; and the trajectory modality of the missing feature is the common cause upstream of both, not a third quantity equal to either. Stated precisely: fungal biosynthesis is observability-limited—one κ_O , two freedoms; its prediction ambiguity is that κ_O , its engineering difficulty is the cost model’s, and the two co-vary because the modality of the missing feature drives both. The v1 programme follows—characterise $\mathcal{F}_O(G, \Theta)$ as a function of O for each grammar; the shared layer of §7 implements the query for $O \in \{\text{mass, MS/MS}\}$, and widening O until $\mathcal{F}_O$ shrinks to where one wishes to operate is then a finite programme on a defined object. We instantiate the duality on the three grammars implemented here (PKS, NRPS,

hybrid)—machine-checked exhaustively, $Z^*=D(y;O)$ on 460/460 distinct product formulas (**make duality**)—and predict its survival on RiPP via Corollary 3; we claim no theorem over an abstract category of program grammars, only that the proof covers any (G, Θ, O) meeting the soundness and relative-completeness conditions of §4.1.

10.1 The coverage–identifiability structure the duality sits in

Read over the corpus, the verdict partitions into R ($\kappa_O=1$, verified), U ($\kappa_O \geq 2$, under-observed), X ($\kappa_O=0$, out-of-grammar) under two knobs of opposite monotonicity: enriching the operator library Θ cannot decrease κ_O (it only adds programs: $X \rightarrow R \cup U$, and by route-overlap $R \rightarrow U$), while enriching the observables O cannot increase it ($U \rightarrow R$, never exiting X). Since $|R|$ is therefore non-monotone, the honest progress metric is not the raw verified count but R^{term} —cores verified under the *full* operator universe, monotone non-decreasing in Θ . This settles the reach-versus-verified reading of the boundary (§6.1): olivetolic has $\kappa_O \geq 2$ under the full universe (genome-distinct, starter-determined routes) and so is never terminal, giving $|R^{\text{term}}|=8$. Three counts of one boundary must not be read as drift: the beam *places* 9 cores, the complete forward search (§13) *reaches* 11—the two beam-starved cores recovered—and $|R^{\text{term}}|=8$ is the finer *verified-terminal* count, below both because olivetolic admits $\kappa_O \geq 2$. Forward sound indexing (§13) makes this growth a reproducible, runnable result: the recovered set only grows with Θ —sound reach 11 at Θ_0 rising to 14 once the encoded PT closure is registered (Θ_1), zero demotions—delivering the projected PT lift at the broader *reach* resolution.

The enumeration certifies its own completeness. The beam can only under-count ($\kappa_\beta \leq \kappa$) and κ is monotone in Θ , so a *reported decrease* of κ_β across a nested enrichment is impossible for a complete search—it proves the larger beam silently pruned a valid program. This fired: adding a methylmalonyl extender at $\beta=8000$ dropped reported κ for olivetolic ($3 \rightarrow 2$) and BAB ($1 \rightarrow 0$)—a flag, not a result—and widening to 5×10^4 restored monotonicity and recovered the pruned programs (**make kappa-certificate**). The relative-completeness caveat of §4.1 thus becomes a runnable per-core check for the *decrease* class—a program found at a smaller Θ and silently pruned at a larger one. A complementary failure escapes it: a core in-grammar yet never surfaced at practical width (zearalenone, §4.1) holds $\kappa_\beta=0$ across the enrichment that should raise it—non-decreasing, so it passes the monotonicity test. That *failure-to-increase* class is caught instead by a generability check (the program is enumerable once its rank-competitors are removed), so the relative-completeness story is stratified across two checks rather than covered by one.

11 Empirical degeneracy resolution: a dual-engine policy over the candidate set

The Outlook (§15) predicts that the fungal per-cycle policy is $a_t \sim P(a_t \mid G, s_t)$: the static enzyme G and an evolving substrate state s_t jointly determine the action. We take a first empirical step toward that injection, and the result is sharper than a single “joint necessity” claim: the same loss decomposes into *two complementary resolution engines*, each precisely applicable to a different chemical regime of the candidate set. The fungal evidence here is preliminary—three detailed assets over an $n=62$ conformational sub-corpus—and is the directional complement to the statistically solid bacterial cross-taxa control of §11.1, not a co-equal validation: the substrate-prefix engine *recovers* the authentic program for two of them (isoterrein, asperlin), while citrinin is a symmetry-breaking demonstration, not a recovery—its authentic product is out of grammar at this formula.

The corpus. We extend the curated 30-cycle HR/PR set (§5) by mining MIBiG fungal PKS clusters whose engine-derived $|Z^*|$ at the metabologenomics observable set (alphabet + molecular formula) lands in the constrained mode, $|Z^*| \leq 10$. An RDKit-driven SMILES-to-formula recovery pass rescues the 112 MIBiG entries without a registered formula; the tractable inventory fixes at 74 clusters and the $|Z^*|$ histogram is bi-modal with an empty middle at $|Z^*| \in [11, 24]$ across all 74—a structural cliff in the natural manifold (§6) that survives the recovery and is not a data-hygiene artifact. These $|Z^*|$ are at the 20,000-program enumeration cap; the exhaustion-certified, uncapped per-cluster values for the producible cores—a few of which land inside the nominal $[11, 24]$ gap once the cap is lifted—are reported in §15. Of the 74, 7 land at $|Z^*| = 1$ (joining the curated 30) and 9 at $2 \leq |Z^*| \leq 10$ contribute the silver tier. A verifier-constrained marginal-likelihood loss $\mathcal{L}(\theta) = -\sum_B \log \sum_{z \in Z^*(B)} \pi_\theta(z | B)$ collapses to standard cross-entropy on the gold and decomposes weight over candidate trajectories on silver.

Structural conditioning. For each cluster with a real synthase we predict the KR+ACP didomain (or full-length protein for divergent PR-PKS the canonical PF08659 HMM does not detect—e.g. citrinin’s CitS, whose KR is silent to the conventional profile even at relaxed thresholds; we fold the 2593 aa CitS in full and rescue the anchor by motif scan). For every *(cluster, candidate, cycle)* we execute the cycle prefix deterministically, 3D-embed the ACP-tethered intermediate, anchor its phosphopantetheine sentinel at the ACP-Ser:OG oxygen, rotate the growing chain along the local ACP-Ser→protein-centroid axis, and extract a five-dimensional pose descriptor: 5 Å contact count partitioned into polar (N/O/S) and hydrophobic (C) subsets, ligand buried fraction, and pocket void volume. These run alongside the substrate-prefix features (cycle index, fractional position, subclass indicator, running chain length and oxidation counts, previous cycle’s reduction rank).

Two engines, one policy. Three feature regimes on the same $n = 62$ conformational sub-corpus reveal a precise partition (Table 4, Fig. 5A). The partition is governed not by cluster identity but by the *symmetry of the reduction-label sequence across the candidates in $Z^*(B)$* .

Substrate-Prefix Engine (label-distinguishable candidates). When the candidates in $Z^*(B)$ differ in their per-cycle reduction labels—e.g., isoterrein’s three candidates (dh, dh, keto), (dh, keto, dh), (keto, dh, dh) that differ in the cycle index of each DH event, or asperlin’s 5 candidates that differ similarly—substrate-prefix features alone concentrate posterior mass: held-out entropy drops to 0.05 for isoterrein and 0.38 for asperlin (against $\log 3 = 1.10$ and $\log 5 = 1.61$ ceilings), each placing its dominant mass on the biologically authentic pathway. The pose channel adds geometric noise to an architecture the substrate counter has already decoded.

Geometric Resolution Engine (label-symmetric candidates). When the candidates share an *identical* reduction-label sequence and differ only in the cycle index of a mass-budget-neutral event—e.g., citrinin’s two candidates both reduce to (dh, keto, keto, keto, keto) and differ only in which of cycle 1 or cycle 2 carries the single C-MeT firing—the marginal-likelihood gradient is symmetric under $(\text{cand}_1 \leftrightarrow \text{cand}_2)$ and *cannot* distinguish them from any function of substrate prefix alone. Citrinin’s held-out entropy under the substrate channel locks at $0.69 = \log 2$ to numerical precision. The pose channel alone barely moves it (0.64); the static cavity geometry without temporal context cannot localize which cycle’s geometry it is measuring. The two channels *jointly* drop the entropy to 0.01, the model committing $\sim 99.9\%$ of its mass to one of the two candidates. The structural channel supplies the only signal that can break this label-symmetry—the substrate channel provably cannot—but both candidates lie outside the grammar’s reach at this formula (the in-vivo citrinin program requires two C-MeT events; see below), so this is disambiguation *within Z^** , not recovery of the authentic product.

Silver asset	Held-out candidate entropy H_{held} (nats)		
	Substrate-prefix	Pose only	Substrate + pose
isoterrein ($ Z^* =3$, $\log 3=1.10$)	0.05	1.07	0.50
asperlin ($ Z^* =5$, $\log 5=1.61$)	0.38	1.26	0.45
citrinin ($ Z^* =2$, $\log 2=0.69$)	0.69*	0.64	0.01

Table 4: The dual-engine partition. Bold = the resolving regime for each asset. *Citrinin’s substrate-prefix entropy locks at exactly $\log 2$ because its two candidates share an identical reduction-label sequence and differ only in C-MeT cycle index; the marginal-likelihood gradient is symmetric under candidate exchange. The pose channel supplies the only signal that resolves this symmetry wall (the substrate channel provably cannot)—a disambiguation among in-grammar candidates, not recovery of the out-of-grammar authentic product.

Directional gating: when the in-vivo program is in $Z^*(B)$. The two engines establish that the policy commits within $Z^*(B)$; whether the committed candidate matches in-vivo biology depends on whether the in-vivo program is in $Z^*(B)$ at all—a question of executor coverage (§13), not of the resolution mechanism. The corpus contains both regimes.

For *isoterrein*, whose biosynthesis proceeds through a linear partially-reducing polyketide before the post-PKS metalloenzyme TerB contracts the chain to the cyclopentenone, the substrate channel routes posterior 0.801 to (dh, dh, keto) hydrolysis—reductions concentrated at the early cycles, matching the canonical HR-PKS architecture—and posterior 0.0001 to the late-reduction (keto, dh, dh) parsimony-best. For *asperlin*, a hexaketide-derived lactone, the substrate channel selects (dh, keto, keto, keto) hydrolysis at posterior 0.845 and crucially *rejects* the parsimony-best aromatic-release candidate at posterior ~ 0 : asperlin is a lactone, not an aromatic, and the substrate-prefix weighting under marginal-likelihood training correctly disfavours the wrong ring topology. Both are directional positives.

For *citrinin*, where the geometric resolution engine commits with posterior 0.999 to a specific candidate, the literature establishes a different fact: heterologous-expression studies of CitS yield a *trimethylated* pentaketide aldehyde requiring *two* C-MeT events (one triketide, one pentaketide) (Storm and Townsend, 2017). Neither of the two candidates in Z^* at $\text{C}_{13}\text{H}_{14}\text{O}_5$ contains two C-MeT events—the grammar cannot synthesize the in-vivo program at this formula. The entropy collapse demonstrates that the structural channel carries per-cluster discriminating information, confirming that the directional assignment remains strictly bounded by symbolic coverage limits rather than neural capacity—an architectural constraint formally mapped to the executor grammar roadmap in §13. The neural head resolves spatial physics within the universe the symbolic core supplies; expanding that universe is the work of operator coverage, not of the resolution mechanism.

11.1 Cross-taxa validation: bacterial control flow encodes s_t in the sequence text

The dual-engine partition makes a sharp prediction about bacterial modular polyketide synthases. Where fungal iterative synthases compress per-cycle control into one reusable catalytic manifold—so G is constant and s_t must be decoded from the substrate prefix or the static pocket—bacterial type I modular PKS encode each catalytic step into its own physical module with its own primary sequence: the temporal index is built into the sequence text. The dual-engine framework predicts that the substrate channel alone should suffice on bacterial systems (there are no label-symmetric walls to break), and adding a structural channel should be largely redundant.




Figure 5: **The dual mechanisms of neuro-symbolic resolution.** (A) Held-out candidate distribution entropy (H_{held}) across three feature regimes. The substrate-prefix channel resolves assets with label-distinguishable reduction sequences (isoterrein to 0.05, asperlin to 0.38). For label-symmetric candidates sharing identical reduction trajectories (citrinin), the sequence channel encounters a permanent symmetry wall ($\log 2$) that only 3D pose cavity descriptors resolve ($H_{\text{held}} \rightarrow 0.01$)—disambiguating the two in-grammar candidates, not recovering the authentic product, which is out-of-grammar at this formula. (B) Joint posterior probability distributions for isoterrein and asperlin. The multi-channel framework consistently routes mass to the biologically authentic pathway: isoterrein’s (dh, dh, keto) early-reduction TerA polyene precursor at posterior 0.801, asperlin’s (dh, keto, keto, keto) non-aromatic linear lactone precursor at 0.845. The parsimony-best alternatives—(keto, dh, dh) for isoterrein, the aromatic-release candidate for asperlin—are actively rejected at ≤ 0.001 .

We test the prediction on the ClusterCAD bacterial type I corpus: 1039 KR-bearing modules across 118 clusters, with per-module reduction state (active KR $\rightarrow$ reduced, silent KR $\rightarrow$ KETO) as the prediction target. The substrate channel here is the standard “domain cartoon” (a present KR fires); the role of the per-cycle G channel is played by a frozen ESM-2 (Lin et al., 2023) per-module sequence embedding fed to a linear head—bacterial modular architecture means per-module sequence varies natively, so the sequence text *is* the temporal index. Three conditions under leave-cluster-out evaluation (Table 5):

The ESM channel alone passes the substrate channel’s ceiling by +10 on whole-program recovery, and it does so without any AlphaFold conditioning. The bacterial control flow is decodable from the per-module sequence because that sequence *is* the temporal index that the fungal architecture compresses away. This recovery is of the *authentic* program: the true per-module reduction pattern lies within the candidate set, so here resolution *is* recovery—the directional-positive regime of isoterrein and asperlin above—whereas citrinin is the contrasting case, its authentic product out-of-grammar, where the same machinery can only disambiguate candidates none of which is biological.

The cross-taxa contrast is precise. **Bacterial modular PKS encode per-cycle control flow in the sequence text** (one module per step, per-module sequence variation $\rightarrow$ ESM does the temporal indexing). **Fungal iterative PKS encode per-cycle control flow in the pocket geometry** (one sequence reused across cycles $\rightarrow$ the structural channel does the temporal indexing that the bacterial sequence channel does natively). Both follow the same $a_t \sim P(a_t | G, s_t)$ policy

Condition (bacterial, $n=118$ clusters / 1039 KRs)	Per-module acc	Whole-program recovery
Domain cartoon (KR present $\rightarrow$ fired)	0.926	60/118 = 0.508
ESM per-module sequence head (the G channel)	0.934	70/118 = 0.593
ESM + oracle active count (headroom)	0.975	107/118 = 0.907

Table 5: Bacterial type I modular PKS: ESM-conditioned sequence policy on its own lifts whole-program recovery by +10 (60 $\rightarrow$ 70/118) over the domain cartoon, recovering 31/58 silent-KR clusters where the cartoon scores 0/58. The oracle active count (row 3) uses the true count—which accurate mass constrains in total but cannot uniquely pin per module—so it is a headroom indicator, not an achieved result. The substrate-only channel (cartoon) reaches its bacterial ceiling because silent KRs are not predictable from gene content alone; the ESM channel passes that ceiling because per-module sequence variation natively encodes which KRs fire.

with the channel partition determined by the architectural locus of the temporal index. The two taxa are dual: bacteria solve the iteration problem by writing the program into text layout (modular sequence variation); fungi solve it by writing the hardware into one sequence and using pocket conformation to route the iteration. The dual-engine framework empirically corroborates both.

Reading. The per-cycle policy is empirically a joint function of G and s_t , in the form the Outlook predicted, but the decomposition reveals that each channel does specific work and the architectural locus of s_t determines which channel does it. For fungal label-symmetric candidates (citrinin), s_t lives in the pocket conformation around the static synthase, and the structural channel is the only way in. For fungal label-distinguishable candidates (isoterrein, asperlin) and for bacterial modular cycles, s_t lives in a channel the substrate/sequence side can read directly. The neuro-symbolic architecture compounds across both regimes: the sound executor bounds $Z^*(B)$ so a learned policy rules within a verified set rather than over an open structure space, and the appropriate channel routes within that set per the chemistry of the candidates the verifier returns. The result is a policy whose neural component would have nothing principled to commit to absent the executor, and whose symbolic core would not distinguish label-symmetric candidates absent the structural channel—two complementary halves of one neuro-symbolic loop, with the empirical partition between them traced precisely to where each taxon places its per-cycle state variable.

12 Related work

Riedling et al. (2024) establishes the 51–68% ceiling and the near-flat cross-domain result that motivates this work. Rule-based detectors and product predictors—antiSMASH/fungiSMASH (Blin et al., 2023), PRISM (Skinnider et al., 2020), DeepBGC (Hannigan et al., 2019), GECCO (Carroll et al., 2021), CLOCI (Konkel et al., 2024)—detect clusters and, for bacteria, read off colinear products; none induce an iterative program. ClusterCAD (Eng et al., 2018; Tao et al., 2023) is the modular-PKS intermediate database we both consume (for the cross-taxa transfer probe) and cite as the bacterial existence proof that colinear assembly lines are tabulable (the conceptual result of Section 6). MIBiG (Zdouc et al., 2025) is our pair source; BGC family methods such as BiG-SLiCE (Kautsar et al., 2021) define the within-family neighbourhoods the cross-taxa transfer probe uses. Property/arrangement predictors such as CHAMOIS (Larralde et al., 2025) infer ontology-level chemistry, not exact iterative programs. Methodologically we draw on execution-guided, neurosymbolic program synthesis (Ellis et al., 2021) and on protein language models (Lin et al., 2023); chemistry is handled with RDKit (Landrum et al., 2025). Our distinguishing stance is to

measure exact reconstructibility and to ground every claim in a sound deterministic verifier.

13 Limitations and outlook

What this does *not* claim. We do not claim complete fungal structure prediction, complete NRPS or hybrid coverage, or validation on real untargeted-metabolomics spectra. *Nor a replacement for structure elucidation:* the engine is a metabologenomics *triage* tool—it selects experiments and names the designs where mass/MS-MS triage is insufficient and expression+NMR is required (the path by which all seven verified products in our corpus were pinned)—not a structure-determination method. We claim a grammar-agnostic, verifier-grounded inference *and design* architecture—an inverse compiler with a shared observability and three-state-verdict layer—and demonstrate it on PKS, NRPS, and a typed PKS–NRPS hybrid grammar. The NRPS and hybrid grammars are v0 demonstrations of architecture generality, not full family coverage. Its natural v1 extension is *observation-updated probabilistic realizability*—turning the curated edit tiers into success distributions fit to wet-lab build outcomes, closing the design–build–test loop the planner opens. With that scope fixed once, the specific limitations are:

- **Partial executor coverage.** Single-mode cyclization plus a tetraketide-aromatic and a PT-naphthalene class (*witness-exact*: it round-trips the deposited 1,3,6,8-tetrahydroxynaphthalene—correcting an earlier “skeleton-correct, regiochemistry-flagged” status the deposited witness refutes), and a macrolactonization are implemented; the remaining PT-aromatic classes and the Diels–Alder are not. Forward sound indexing (below) sorts the 205 in-scope cores the base grammar does not reach (§6.2) from a tally into a certified frontier—which are beam-starved (in grammar), which are provable structural-gaps, and which are out of formula-reach.
- **Additive-only tailoring.** The ~ 12 edit types are additive and the joint verifier is “exact-by-budget” (skeleton embedding + Δ -formula + gene/parsimony budget), threshold-free but not yet full atom-by-atom positional reconstruction (positions affect $|Z^*|$ multiplicity, not existence).
- **Gene budget over-counts** when a locus accession is a whole contig (non-cluster genes included); HMMER on cluster-scoped sequences would tighten it.
- **Subclass unknown for 304/326;** stereochemistry is not modelled (the executor is achiral by design); numbers are over MIBiG-deposited entries, biased toward well-studied (often heavily tailored) compounds.
- **The mining pipeline has one real-cluster case study, not yet a benchmark.** A blind real-cluster, real-mass run (6-MSA, Section 7) verifies the known product at rank 1; beyond it the alphabet+mass+MS/MS chain is shown as near-unique recovery on reachable cores and as fragment-fingerprint *separability* under a crude in-silico fragmenter. A multi-cluster benchmark, real LC-MS/MS validation (e.g. CFM-ID / GNPS), per-cluster domain alphabets from antiSMASH/fungiSMASH, and a learned candidate-ranking prior (data-limited at present) are the natural next steps. In clean form mass and MS/MS act as hard masks; in real metabolomics (adducts, isotopes, noisy or partial spectra) they become high-confidence constraints with explicit uncertainty; we *implement* a matching approximate verifier $Z_\epsilon^* = \{z : \text{mass}(\text{Exec}(z)) \in [m - \epsilon, m + \epsilon], \text{MS/MS}(z) \geq \tau\}$ as an adduct-aware, ppm-tolerant, tolerance-scored layer shared across grammars (built via a mass-window formula prefilter so the tolerance is genuine, not an exact verifier with a cosmetic window) alongside the exact one—validation against real spectra (above) being the open step.

A theory of where the hardness lives: sound expressibility on a cost ladder. The roadmap below is not a TODO list but a placement of each missing operator on one criterion: **an operator is soundly expressible from φ iff the formula-invariant degree of freedom it must resolve is a computable function of the recoverable cluster features $\varphi(B)$.** Soundness (mass) is free by construction; $\simeq$ -correctness is the bite; the DOF is exactly where the two diverge—ring-oxygen position for aromatics, ring size for macrolactones. Fixing φ as the cluster (the stated problem is $\text{BGC} \rightarrow \text{product}$) places each class on a cost ladder beneath a scope prior: **rung 0**, the determinant is *trans*-acting and so outside cluster- φ —a scope failure no per-cluster operator repairs; **rung 1**, fixed by the linear precursor (free); **rung 2**, a sequence-keyed rule (the PT-clade regiochemistry, classified and prospectively verified from sequence (Li et al., 2010)); **rung 3**, recoverable only through fold/dynamics ($\text{AF2} \rightarrow \text{MD/QM}$) at escalating, possibly ruinous cost (the label-symmetric Gate-3 frontier of §15 is the measured rung-3 instance); **rung 4**, *soundly inexpressible*—no function of any cluster feature exists, reached only by an intrinsic product *mixture* (a within-enzyme collision: one sequence, one substrate, ≥ 2 products) or an *extra-genomic* determinant. The impossibility bar is thus high and narrow: a *trans* enzyme encoded elsewhere in the genome is rung 0, and kinetic/dynamic selection is a costly rung 3, so the honest ceiling is “expressible at escalating cost almost everywhere,” with a small, characterized floor. (Citrinin’s two-C-methylation program, by contrast, is a *coverage* gap—out-of-grammar at its formula, §15—not a within-grammar rung-4 mixture; the two must not blur.) This is what makes the census of §6.2 a map rather than a tally: aromatic cyclization is a *resolved* rung-2 class (the predictive PT map places orsellinic and 6-MSA among the reachable nine); macrolactonization—the dominant in-scope family (176/205)—is *located* but not resolved (rung 0 passes for the *cis* resorcylic-acid-lactone thioesterases, and the rung-4 mixture route is closed by the regiospecific zearalenone TE, with the rung-2 resorcylic-macrolactone closure now registered (§4.1): the *beam* does not surface its highly-reducing program at practical width, but *forward sound indexing* (below) does, so the closure’s true increment is the beam-starved set (+2 cores: the beam’s reach of 9 lifts to a sound reach of 11), not zero, and only the fold-gated rung-3 closures stay open above the size bound); and the 178 of 205 (87%) that touch a hard family are exactly the rung-2/3-and-open operators, while the rung-2 closures generalize cleanly—the orsellinic $\text{C2} \rightarrow \text{C7}$ closure extends to a pentyl starter, building olivetolic acid’s β -resorcylic core (now among the reachable nine; Table 3)—so sound, no-new-regiochemistry extension adds no further core beyond the nine. The discriminators that assign a rung—*cis*-vs-*trans* annotation (rung 0), the within-enzyme collision (rung 4), and a structure-vs-sequence experiment with the chain regressed out (rung 2-vs-3)—each carry catalogued false-read failure modes (deposition bias, phylogenetic confounding, static-fold blindness), so a rung is a verdict to be earned per class, not read off structure (Appendix B).

Forward sound indexing turns the boundary into a certified map. The beam verifier is sound but not search-complete ($\kappa_\beta \leq \kappa$), so $\kappa_\beta=0$ cannot distinguish a coverage gap from an in-grammar program the carbon-closeness ranking starves. Running the executor *forward*—enumerating Θ_0 to a size bound ($N=9$ cycles, $C \leq 20$) and rendering every program—is ranking-free and hence complete by construction up to that bound, so an empty structure bucket is a *provable* absence certificate, the one verdict the beam cannot issue. Over the 214 in-scope CHO cores this converts the heuristic 9/326 boundary into a sound map (**make forward-index**): **sound reach 11** as an exact reproducible result—the 9 beam-reachable cores plus the 2 beam-starved in-grammar cores the resorcylic closure enables (including zearalenone, recovered where the beam gave $\kappa_\beta=0$ through $\beta=2 \times 10^5$); a **certified frontier of 117 cores**—83 *provable structural-gaps* (formula-feasible but exhaustively unbuilt up to the bound, each needing a new operator) and 34 mass-infeasible (each

needing new formula-budget chemistry); and 86 *inconclusive* cores ($C > 20$, beyond the size bound, reported as such and never as gaps). The boundary’s search-incompleteness was thus *exactly two cores*, removed by the forward path; what remains is the genuine coverage frontier, now certifiable, and the only residual limit is a size cap on the map’s completeness, not on the executor.

A monotone build-loop over the certified frontier. Restricting the structural-proxy set-cover to soundly-expressible (rung-2) classes turns the 117 into a *build-queue* (**make rung2-cover**): 19 rung-2 (buildable now), 62 rung-3-open (fold-gated regiochemistry), 34 rung-3-mass (formula-changing tailoring). Because registering a sound operator can only move cores $\text{gap} \rightarrow \text{reachable}$, R_{term} is non-decreasing in Θ —which we make a *runnable* check (**make forward-index-monotone**, asserting zero demotions across Θ levels). The loop’s first step delivers it—and with it the reach lift projected in §10.1 for the PT closures: registering the witness-exact PT pentaketide $\rightarrow$ naphthalene closure recovers the three deposited tetrahydroxynaphthalenes (sound reach $11 \rightarrow 14$), zero demotions, *witness-first*—the operator round-trips its deposited structure, no regiochemistry fabricated. The remaining rung-2 family is then mechanism, not open question.

Table 6: Executor-coverage roadmap, placed on the sound-expressibility ladder (§13, Appendix B): each operator extension carries the *kind* of hardness (its rung), not a vague difficulty label—turning “partial coverage” from a limitation into a prioritised programme with a theory of which gaps are buildable, which are open research, and which belong to a different grammar.

Operator extension	Unlocks	Sound-expressibility rung
more small-aromatic closures	many NR/PR aromatics	rung 2 (resolved; sequence-keyed)
PT-domain regiochemistry	larger aromatic folds	rung 2 (PT-clade; naphthalene closure delivered, +3)
macrolactonization	resorcylic-acid lactones, macrocycles	rung 2 registered (+2 via forward index); rung 3 open above the size bound
oxidative skeletal rearrangement	aflatoxin / sterigmatocystin	rung 3 / open (soundness unproven)
PKS–NRPS handoff	hybrid cores	scope boundary (different grammar)
checkpoint		
dimerization / depside coupling	non-local products	non-local scope (off the per-program ladder; unassessed)

14 Conclusion

A fungal BGC is a constrained *program space*, not a molecular blueprint, and a single sound inverse compiler over that space serves three jobs on one spine $y = \text{Exec}_{\Theta}(z; G)$: run *forward* it renders programs to structures; run *inverse* it reconstructs known products and assigns them to metabolome peaks, returning a typed verdict rather than a single accuracy score; run *backward* it designs. The diagnostic half characterizes the natural manifold the engine operates over—exact reconstruction at 9/326 by the beam, lifted to a sound reach of 11 by complete forward search (§13), is its *boundary*—the sharp edge of the current grammar’s reach, not a low score—the $1.00 \rightarrow 0.567$ cross-taxa collapse its one hard axis, and structural-similarity proxies are shown *not* to be reconstructibility metrics. The contribution is what the backward direction buys: a *realizability geometry* that scores any target molecule by its edit distance to that manifold along two axes—structural (documented domain engineering) and control (the iteration-program frontier)—under a cost model that *is* the field’s

measured difficulty, curated from primary sources rather than asserted; across the manifold’s 1-edit neighbourhood fungal design is mostly iteration-program editing (69 frontier to 49 engineerable), the axis only a sound per-cycle executor can express. An experiment-selection planner then ranks the observation that most collapses the candidate set per unit cost and, crucially, *names its own limit*—the designs where mass and MS/MS triage suffice versus those that must go to expression+NMR. The same iteration-grammar wall is therefore a prediction ceiling read one way and a design frontier read the other: one measurement, a limitation and the contribution at once. Formally these are projections of one observability quantity κ_O on one frontier $\mathcal{F}_O$ (Theorem 1), so the same engine, the same planner, and the same experiments serve both directions—and the same theorem predicts the architecture reproduces its results on any family meeting the soundness conditions of §4.1. We do not replace structure elucidation; we build the missing middle—the sound, cost-weighted layer between target-blind generative chemistry, enzyme-blind retrosynthesis, and undirected genome mining—on which other models compose without eroding soundness: a sequence policy reranking Z^* and, as the natural next composition, a bioactivity predictor filtering it, yielding *target-directed* natural-product discovery—a search for the cheapest cluster-plus-edits route to a desired activity, each proposal arriving with a construction plan and a confirming experiment. *We do not claim that pipeline here*; we claim the substrate on which it becomes possible. The tools, benchmark, and analyses are open and reproducible.

Near-term extensions. The architecture is grammar-agnostic—observability and the three-state verdict are shared across PKS, NRPS, and a typed hybrid—so deepening the family grammars (NRPS substrate specificity, the tetramic-acid release) and extending executor coverage widen the manifold without touching the shared layers. A learned, sequence-aware *policy* fits the engine naturally as a soundness-preserving *reranker* over the legal program set, and the controlled per-step/pooled comparison of §6.5 predicts where it pays off: on *bacterial modular* PKS, where each module carries its own sequence (a companion demonstration), not on the fungal iterative wall, which is structural by construction—for fungi the policy ranks within Z^* , it does not break the wall. Two further steps close the loop the planner opens: validating the observability layer on real LC-MS/MS spectra (e.g. CFM-ID / GNPS), and turning the curated edit tiers into *observation-updated probabilistic realizability*—success distributions fit to wet-lab build outcomes—so the design–build–test cycle, not only experiment selection, runs on the same spine. The reference implementation (`lpi.engine`) is released alongside.

The wall, stated once. Collected across the three readings, the iteration-grammar wall is *proven on the prediction side and pre-registered on the design side*, and on neither an artifact of the cost model. **Proven (prediction):** per-cycle reduction transfers across taxa at a fixed-domain ceiling of 0.567, with a bacterial control (0.78 per-module $\rightarrow$ 0.50 pooled, §6.5) isolating the deficit as the missing per-step input, not model capacity; and the genome–trajectory modality assignment and the cost-axis label agree on every edit tested—0 of 192 cross it (§9.5). **Pre-registered $\rightarrow$ resolved (design):** the (trajectory, trajectory) cell—the product-neutral iteration-grammar degeneracy the duality points at—is empty in the reachable neighbourhood. Its first occupant was pre-registered as a macrolactonised highly-reducing core, gated on a curated resorcylic aromatisation fold together with the macrolactonisation release; both are now registered (§4.1). Building the fold resolves the pre-registration to its *informative-negative* branch—the predicted occupant does not appear, for a structural reason. A product-neutral same-product/different-cycle fibre requires the cyclisation to *erase* a reduction-state distinction; the resorcylic fold closes an all- β -keto aromatic ring, which carries no reduction landmark to erase, so distinct reduction trajectories yield distinct products and

no trajectory edit is product-neutral. The occupant the cell awaits would need an aromatic core with a *reduced* ring position the fold flattens—which the curated single-mode folds do not provide—so the cell stays empty by a rendered mechanism, not by missing coverage. (The lactone itself, zearalenone, is in-grammar by construction yet outside the *beam*-reachable set; *forward sound indexing* now recovers it (§13), confirming the $\kappa_\beta=0$ at practical width was a search artifact, not missing coverage, §4.1.) The pre-registration does its job either way: the framework names where its own predicted degeneracy does and does not arise (§9.5, §13). **Not a cost artifact:** the engineerable–frontier split is independent of the cost functional form and survives leave-one-core-out (§9.4), resting on tier assignments calibrated to the biochemistry—so the wall rests on κ_O (proven) and a pre-registration, not on the cost shape.

15 Outlook: the iteration program as a partially observed dynamical control problem

These results invite a reframing of the fungal problem itself. The per-cycle action may not be a function of the synthase alone— $a_t \sim P(a_t \mid G)$ —but of the synthase *and* an evolving substrate state, $a_t \sim P(a_t \mid G, s_t)$, where s_t is the chain length, oxidation state, carrier-protein pose, and transient conformation the constant catalytic machinery presents to itself on cycle t . Bacterial modular PKS *externalize* this state into architecture—one module per step—whereas the fungal iterative synthase *compresses* the entire policy into one reusable catalytic manifold with state-dependent routing: a non-equilibrium, trajectory-dependent object closer to a substrate-conditioned automaton than to a static sequence→structure map. Crucially this is an *architectural* claim, not a statistical null: an iterative synthase exposes no per-step observable by construction, and where one *does* exist—bacterial modular PKS—the same predictor under the same executor nearly doubles ($0.50 \rightarrow 0.78$, §6.5), so the model class is not the limit. The fungal probes then *corroborate* the boundary by elimination: the policy is recovered neither from chain position nor from the computable running substrate state, so the identifying signal lies in the conformational component of s_t that a synthase-local view cannot, by construction, supply. This casts the problem as a partially-observed control problem in which three of the four objects are already known exactly. The state-evolution model $s_{t+1} = F(s_t, a_t)$ *is the executor*: applying an operator to the ACP-tethered intermediate is literally F , symbolic and exact, not a dynamics model to be supplied later. The emission $y = \text{readout}(s_N)$ is known, and the consistent set Z^* is computable by the verifier. The lone unknown in the entire system is one function, the per-cycle policy $\pi_\theta(a \mid s, \phi(G))$ —so *the dynamics is the contribution, and only the policy is open*.

Over the producible-core subset (§6)—the cores the current grammar reaches exactly—we can size and locate where that open policy is hardest. Walking the consistent set Z^* as a prefix trie sorts every branch-resolving decision into three kinds: a *clean trunk*, where the cycle’s action is fixed given the prefix and the executor manufactures a free label; *Gate-2* branches, where candidates differ in reduction state and a running substrate count resolves them; and *Gate-3* branches, where candidates share a reduction trajectory and differ only in the mass-neutral position of a C-methylation—the label-symmetric directions no synthase-local static view can break. Across 24 distinct inference problems (distinct formula and cycle-range—three same-formula natural products the formula-level model cannot separate are necessarily one problem), each enumerated to completion, Gate-3 is not a uniform tax but a localized one, threefold. Over the non-methylating aromatic interior it is *exactly zero*—no Gate-3 among the 87 decisions—because without a C-MeT firing label-symmetry is structurally impossible. Within the methylating, highly-reducing subclass it is single-digit: the mean methylating chemistry routes 7.0% of its clean-or-Gate-3 decisions through Gate-3 (median

6.1%, range 2.6–17.5% across the 15 distinct chemistries; the Z^* -pooled figure is 5.0%, weighted toward the single large enumeration and reported only for comparability). And within that subclass Gate-3 concentrates in the *low-combinatorial* clusters: Gate-2 grows with enumeration size while Gate-3 stays chemistry-bounded, so the ratio falls as the absolute count rises (Spearman -0.61 and $+0.80$ over the 15 methylating chemistries)—the within-corpus echo of the asymmetry by which Gate-2 is combinatorial in the oxidation grammar and Gate-3 is an invariant of the chemistry. The frontier thus has a mapped structure—absent over aromatics, single-digit over HR, sharpest in the small methylation-ambiguous clusters—and citrinin, at 11.1%, sits above that subclass’s median: the modal sharp case, not a convenient one, which is why §11 stages the entire label-symmetric resolution on it.

What structural-dynamics observables (MD ensembles, cryo-EM states, chain-length-conditioned docking) would supply is not F but a coordinate of the policy’s *input* $\phi(G)$: the active-site conformation that breaks the label-symmetric directions a synthase-local static view cannot. The requirement this hands such an effort is sharp: those label-symmetric decisions cannot be learned from synthase-local static observables, so closing them needs either a larger corpus read at per-cycle resolution—and because the marginal-likelihood loss (§11) factorizes over the common prefix of Z^* , the executor manufactures clean per-cycle labels from terminal-only observations, so the training signal scales with total branch-resolved cycles, not with cluster count—or direct partial observables of the conformational coordinate. The first measurable breakthrough need not be complete product prediction—it would be a single per-cycle decision becoming predictable above 0.567 once cycle-distinguishing state is injected, which the executor would then propagate, soundly, through the rest of the program. We take a first empirical step along this axis in §11: AlphaFold2-conditioned pocket descriptors injected alongside the substrate-prefix index resolve the label-symmetric C-methylation degeneracy in citrinin from $H = \log 2$ to $H = 0.01$ on held-out evaluation, with a complementary substrate channel resolving the label-distinguishable cases (isoterrein to 0.05, asperlin to 0.38) on the same corpus. The two engines do specific work: the substrate counter localizes which cycle is being asked about, the structural channel routes within that cycle’s pocket-substrate geometry, and the executor bounds the set within which either can rule.

The coverage tail and the policy frontier are one missing observable. Forward sound indexing (§13) sharpens this convergence. The $C > 20$ cores it cannot resolve above the size bound are not a brute-force limit: pinning a target formula collapses the carbon-cap combinatorics and leaves exactly the *ordering* of the formula-fixed cycle multiset—which cycle does what—as the residual, and for the large highly-reducing cores that ordering count is astronomical. But that ordering *is* the per-cycle policy π of this section: the directed search must enumerate every ordering precisely because, lacking s_t , it cannot tell which one the synthase realised. The same conformational coordinate that collapses Gate-3 for citrinin (§11, demonstrated at $n=1$) is what *would*, if it generalises, prune the ordering space toward nature’s single trajectory—so we read the $C > 20$ coverage tail and the label-symmetric identifiability frontier as one missing observable, met from two directions. We state this as a *pre-registration*, not a *result*: the pocket collapse is shown at $n=1$ only, and that a pocket lever *would* do double duty—complete the map and break the wall at once—is the conjecture the identification motivates, not a delivered claim.

This measurement holds within boundaries that must stay sharp, because it has the same shape as the coverage boundary one level up: exact over what is reachable, silent about what is not. The figures are exact rather than cap-limited—every producible Z^* enumerated to completion—so the smallness is measured, not assumed. But it is measured only over the cores the grammar can build: out-of-grammar chemistry does not surface as Gate-3, it is absent from the producible set

entirely, so were the genuinely pocket-hard cases to fall disproportionately outside the coverage boundary (§13), the in-grammar frontier would look exactly this thin while a larger one stayed hidden. Citrinin is the tell: its full two-methylation biology is out-of-grammar, yet its in-grammar shadow already yields one of the sharpest Gate-3 ratios in the corpus (11.1%, above the methylating median)—so the pocket-hardest chemistries may be precisely those displaced past the coverage boundary, where their Gate-3 is invisible. And a small, located, in-grammar frontier is still not a solved one: whether those label-symmetric decisions are recoverable from a *simulated* pocket (AF2/MD) or only a *measured* one (cryo-EM) is the citrinin hinge of §11, and it is unsettled. The conformational frontier over reachable cores is sized, placed, and thin; that does not deliver the biology, nor does it yet bound the frontier of the cores the grammar cannot build.

A Reproducibility

Python 3.12, RDKit 2025.9.6; optional `torch/transformers` for the cross-taxa transfer and ESM-2 components. Each result maps to one command: `make data` (the 326 pairs), `make roundtrip` (executor gate), `make search` (the verifier and Z^*), `make reachability` (exact-match 9/326), `make forward-index` (the complete forward map: sound reach 11, certified frontier 117=83+34, tag `lpi-v0.24-forward-index`), `make census` (the §6.2/Appendix B census: partition, set-cover, MECE, and the cap-lifted 0-of-91 re-scan), `make two-walls` (the §6.5 ~9%/61% subclass wall split), `make corematch` (the core-match sensitivity), `make phase0c` (tailoring-latent 7/107), `make seqhead` (the bacterial sequence-head table of §11; read-only over the committed ESM-2 embedding cache—regenerating embeddings needs the pinned `esm2_t6_8M` and may differ at the last digit), `make structural-rescue` (the §11 dual-engine Table 4/Fig. 5), `make gate-frontier` (the §15 Gate-3 frontier: 24 distinct keys, $|Z^*|$ Spearman), `make clustercad` and `make differential` (the cross-taxa transfer probe), `make crossgrammar`, `make observability`, and `make realdemo` (the cross-grammar PKS/NRPS/hybrid demo, the candidate-collapse observability benchmark, and the blind real-cluster 6-MSA mining demo), `make figures`, and `make test` (161 tests); the realizability geometry and experiment-selection planner are reproduced by `scripts/worked_design_6msa.py` and `scripts/planner_tree_figure.py` (Figures 3–4); the per-step vs. pooled control behind the structural-wall claim (§6.5) by `scripts/explorations/bacterial_control.py`.

The results-producing targets fall into two reproduction tiers. The structural results regenerate end-to-end from a clean clone (`reachability`, `census`, `two-walls`, `corematch`, `phase0c`, `crossgrammar`, `observability`, `realdemo`); the sequence- and pose-conditioned results instead reproduce from *committed* model intermediates—`seqhead` over the ESM-2 embedding cache, `structural-rescue` over the AlphaFold2 pose descriptors, and `gate-frontier` over the inference inventory—shipped so the expensive fold/embedding step need not rerun; the learned heads (`seqhead`, `structural-rescue`) matched to the last digit on the reference build, and a different `torch/BLAS` build may differ in the final digit. (`data`, `figures`, and `test` are infrastructure, not results-bearing.)

The tagged milestones (`lpi-v0.2-cross-grammar` through the submission tag `lpi-v0.23-journal`, including `v0.14-curated-cost-basis`, `v0.15-planner`, and `v0.16-sequence-head`), per-result numbers, scripts, and commits are available in the public repository: <https://github.com/BrageEilertsen/lpi-fungal>.

Software development. The implementation and the experiments reported here were developed with an AI coding assistant (Claude Code). The paper’s guarantees are properties of the artifact, not of how it was written: the executor is sound by construction (§3) and the verifier returns the exact consistent set Z^* (§4), so every reported number reproduces from the single documented commands above. Experimental design and scientific interpretation are the author’s.

B The coverage census (full 326)

These tables support §6.2: the partition (Table 7), the set-cover concentration (Table 8), and the mutually-exclusive entanglement decomposition (Table 9). Three caveats govern every count. Counts are *exact over the executor’s reach*—a boundary of the current sound grammar’s reach, never a biological limit on the manifold. The corpus is the *MIBiG-deposited* manifold, biased toward well-studied (often heavily tailored) compounds. And the set-cover and operator-class views are structural-feature *proxies* and explicit *upper bounds* on recovery (a core counts as proxy-recovered when all its tagged operator classes are present—necessary, not sufficient), not measured recovery; the steepness measures how few chemical *families* the demand falls into, not how few operators a solution needs. The operator-class tagger counts heterocyclic (lactone) rings, not only all-carbon rings: an all-carbon-only tagger miscounts the resorcylic-acid-lactone family as clean-aromatic rather than aromatic-plus-macrolactonization (entangled), inflating the clean single-class count, so the heterocycle-aware tagger used throughout is the conservative choice (fewer clean, more entangled). It counts 22 clean single-class aromatic cores and 97/205 (47%) entangled.

class	cores	kind of hardness
reachable (exact)	9	built today
CHO, in-scope	205	add a polyketide tailoring operator (§13)
confirmed unreachable	202	
inconclusive (budget)	3	reachability not exhaustively confirmed
heteroatom, scope boundary	112	a different grammar (NRPS-hybrid / halogenase)
total	326	MIBiG-deposited, study-biased

Table 7: The coverage partition (certified). Counts are exact over the executor’s reach; the corpus is the MIBiG-deposited manifold.

#operator classes	+ class added	cumulative proxy-recovered (of 205)
1	non_aromatic_ring/rearrangement	83 (40%)
2	aromatic_cyclization	158 (77%)
3	oxidative_tailoring	186 (91%)
4	prenylation	196 (96%)
5	other_formula	202 (99%)
6	other_topology	205 (100%)

Table 8: In-scope recovery, greedy set-cover. **Structural-proxy upper bound**, not measured recovery: concentration into a few coarse families is the signal; the per-step counts are not a count of buildable operators. The dominant family is non-aromatic ring / macrolactonization, not aromatic cyclization.

Acknowledgments

This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors. Open access publication was supported by the University of Oslo through the Norwegian (Sikt) agreement with Elsevier.

Declaration of interests

The author declares no competing interests.

operator-class set	cores	% of 205
clean aromatic (aromatic cyclization only)	22	11
single hard (rearrangement / oxidation / formula only)	83	40
single soft (topology / prenylation only)	3	1
aromatic + hard (entangled)	85	41
other entangled (two classes)	12	6
total	205	100

Table 9: Canonical mutually-exclusive decomposition of the 205 in-scope cores by operator-class set (structural-proxy tags). Hard = {rearrangement, oxidation, formula change}. The 11/87/47% views in the text are overlapping projections of this one partition: clean single-class aromatic 22; touch-a-hard-family $178 = 83 + 85 + 10$; entangled across ≥ 2 classes $97 = 85 + 12$.

References

- O. Riedling, A. K. Walker, et al. Predicting fungal secondary metabolite activity from biosynthetic gene cluster data using machine learning. *Microbiology Spectrum*, 2024.
- K. Blin et al. antiSMASH 7.0. *Nucleic Acids Research*, 2023.
- M. A. Skinnider et al. Comprehensive prediction of secondary metabolite structure and biological activity (PRISM 4). *Nature Communications*, 2020.
- C. H. Eng, T. W. H. Backman, et al. ClusterCAD: a computational platform for type I modular polyketide synthase design. *Nucleic Acids Research*, 46(D1):D509–D515, 2018.
- X. B. Tao, S. LaFrance, Y. Xing, A. A. Nava, H. Garcia Martin, J. D. Keasling, and T. W. H. Backman. ClusterCAD 2.0: an updated computational platform for chimeric type I polyketide synthase and nonribosomal peptide synthetase design. *Nucleic Acids Research*, 51(D1):D532–D538, 2023.
- G. D. Hannigan et al. A deep learning genome-mining strategy for biosynthetic gene cluster prediction (DeepBGC). *Nucleic Acids Research*, 47(18):e110, 2019.
- L. M. Carroll et al. Accurate de novo identification of biosynthetic gene clusters with GECCO. *bioRxiv*, 2021.
- Z. Konkel, L. Kubatko, and J. C. Slot. CLOCI: unveiling cryptic fungal gene clusters with generalized detection. *Nucleic Acids Research*, 52(16):e75, 2024.
- M. M. Zdouc, K. Blin, et al. MIBiG 4.0: advancing biosynthetic gene cluster curation through global collaboration. *Nucleic Acids Research*, 53(D1):D678–D690, 2025.
- S. A. Kautsar, J. J. J. van der Hooft, D. de Ridder, and M. H. Medema. BiG-SLiCE: a highly scalable tool maps the diversity of 1.2 million biosynthetic gene clusters. *GigaScience*, 10(1):giaa154, 2021.
- M. Larralde et al. Machine learning inference of natural product chemistry across biosynthetic gene cluster types (CHAMOIS). *bioRxiv*, 2025. <https://doi.org/10.1101/2025.03.13.642868>.
- S. M. Ma, J. W.-H. Li, J. C. Vederas, Y. Tang, et al. Complete reconstitution of a highly reducing iterative PKS (lovastatin nonaketide synthase LovB/LovC). *Science*, 326(5952):589–592, 2009.
- J. M. Crawford et al. Structural basis for biosynthetic programming of fungal aromatic polyketide cyclization (the product-template domain). *Nature*, 461:1139–1143, 2009.
- Y. Li, W. Xu, and Y. Tang. Classification, prediction, and verification of the regioselectivity of fungal polyketide synthase product template domains. *J. Biol. Chem.*, 285(30):22764–22773, 2010. doi:10.1074/jbc.M110.128504.

- K. Ellis et al. DreamCoder: bootstrapping inductive program synthesis with wake-sleep library learning. *PLDI*, 2021.
- Z. Lin et al. Evolutionary-scale prediction of atomic-level protein structure with a language model (ESM-2/ESMFold). *Science*, 379(6637):1123–1130, 2023.
- G. Landrum et al. RDKit: open-source cheminformatics (version 2025.09.6), 2025. <https://www.rdkit.org>.
- R. J. Cox. Curiouser and curiouser: progress in understanding the programming of iterative highly-reducing polyketide synthases. *Nat. Prod. Rep.*, 40:9–27, 2023. doi:10.1039/D2NP00007E.
- K. M. Fisch, W. Bakeer, A. A. Yakasai, Z. Song, J. Pedrick, Z. Wasil, A. M. Bailey, C. M. Lazarus, T. J. Simpson, R. J. Cox. Rational domain swaps decipher programming in fungal highly-reducing polyketide synthases and resurrect an extinct metabolite. *J. Am. Chem. Soc.*, 133:16635–16641, 2011. doi:10.1021/ja206914q.
- E. M. Musiol-Kroll and W. Wohlleben. Acyltransferases as tools for polyketide synthase engineering. *Antibiotics (Basel)*, 7(3):62, 2018. doi:10.3390/antibiotics7030062.
- J. R. Jacobsen, C. R. Hutchinson, D. E. Cane, and C. Khosla. Precursor-directed biosynthesis of erythromycin analogs by an engineered polyketide synthase. *Science*, 277(5324):367–369, 1997. doi:10.1126/science.277.5324.367.
- L. Kellenberger, I. S. Galloway, G. Sauter, G. Böhm, U. Hanefeld, J. Cortés, J. Staunton, and P. F. Leadlay. A polylinker approach to reductive loop swaps in modular polyketide synthases. *ChemBioChem*, 9(16):2740–2749, 2008. doi:10.1002/cbic.200800332.
- S. Yuzawa, T. W. H. Backman, J. D. Keasling, and L. Katz. Synthetic biology of polyketide synthases. *J. Ind. Microbiol. Biotechnol.*, 45(7), 2018.
- L. M. Repka, J. R. Chekan, S. K. Nair, and W. A. van der Donk. Mechanistic understanding of lanthipeptide biosynthetic enzymes. *Chem. Rev.*, 117(8):5457–5520, 2017. doi:10.1021/acs.chemrev.6b00591.
- M. S. Donia, J. Ravel, and E. W. Schmidt. A global assembly line for cyanobactins. *Nat. Chem. Biol.*, 4:341–343, 2008. doi:10.1038/nchembio.84.
- P. M. Storm and C. A. Townsend. Functional and structural analysis of programmed C-methylation in the biosynthesis of the fungal polyketide citrinin. *Cell Chemical Biology*, 24(3):316–325, 2017. doi:10.1016/j.chembiol.2017.02.005.