

# Breeding Scheme Language

**Shiori Yabe, Hiroyoshi Iwata, and Jean-Luc Jannink**

**June 8, 2016**

## INDEX

Description.....	2
Introduction.....	3
Required environment.....	4
Install BreedingSchemeLanguage.....	5
Describe breeding scheme.....	6
Example 1.....	8

## Description

Package: BreedingSchemeLanguage

Type: Package

Title: Describe and simulate breeding schemes

Version: 1.0

Date: 2016-03-08

Author: Shiori Yabe, Hiroyoshi Iwata, and Jean-Luc Jannink

Maintainer: Shiori Yabe <syabe@affrc.go.jp>

Description: Users can simulate their planned breeding schemes by using functions that imitate events in breeding.

License: GPL-3

Depends: R ( $\geq 3.0.0$ ), Rcpp ( $\geq 0.11.0$ ), snowfall

Imports:

ggplot2,

rrBLUP

LinkingTo: Rcpp

LazyLoad: yes

NeedsCompilation: yes

RoxygenNote: 5.0.1

## Introduction

This documentation describes how to start and use the R package “BreedingSchemeLanguage”. BreedingSchemeLanguage (BSL) was developed for breeders to conduct breeding simulations in a simple and flexible system. Users can use BSL under the R environment.

The BSL utilizes the coalescent-based whole genome simulator “GENOME” (Liang et al., 2006) to simulate a founder population for simulation.

If you use the program, the appropriate citation is:

---

Reference for GENOME:

Liang L., Zöllner S., Abecasis G.R. (2006) GENOME: a rapid coalescent-based whole genome simulator

## Required environment

Downloading and installing R is necessary to use the package. Users can download R on the web page:

The Comprehensive R Archive Network (CRAN) <https://cran.r-project.org>

The BSL package needs Rtools or Xcode for windows and Mac PC, respectively. These tools are used to install the BSL package from GitHub(<https://github.com>) and to compile C++ code on your PC. Compiling C++ code is automatically done when you install the BSL package.

Rtools: <https://cran.r-project.org/bin/windows/Rtools/>

Xcode: Mac App Store (You need your “Apple ID”.)

## Install BreedingSchemeLanguage

On your R screen, you can write the code as below:

```
install.packages("devtools")          # only at the first time  
library(devtools)  
install_github("syabe/BreedingSchemeLanguage")      # only at the first time  
library(BreedingSchemeLanguage)
```

Once you install the package, the first and second sentences can be removed.

If you asked the mirror cite when you conduct the code, please chose one place you prefer.

Now, you can use “Breeding Scheme Language” on your PC!

## Describe breeding scheme

### Help

You can call help page by two types of code:

?FUNCTION

help(FUNCTION)

FUNCTION should be replaced with the name of function you hope to ask.

### Functions

- `defineSpecies(loadData = NULL, saveDataFileName = "previousData",  
nSim = 1, nCore = 1, nChr = 7, lengthChr = 150, effPopSize = 100,  
nMarkers = 1000, nQTL = 50, propDomi = 0, nEpiLoci = 0)`
- `initializePopulation(nPop = 100, gVariance = 1)`
- `phenotype(errorVar = 1, popID = NULL)`
- `genotype()`
- `predictBreedVal(popID = NULL, trainingPopID = NULL)`
- `select(nSelect = 40, random = F, popID = NULL)`
- `cross(nProgeny = 100, equalContribution = F, popID = NULL)`
- `selfFertilize(nProgenyPerInd = 1, popID = NULL)`
- `doubledHaploid(nProgeny = 100, popID = NULL)`
- `plotData(ymax = NULL, add = F, addDataFileName = "plotData")`
- `outputResults(summarize = T, directory = NULL, saveDataFileName =  
"BSLoutput")`

**We are preparing this section now.**

### Population ID

Initial population ID = 0

Population ID will be incremented by these functions:

1. select
2. cross

3. selfFertilize

4. doubledHaploid

Be careful that:

select() creates a new population that is a subset of the candidate population

## Example 1

### “Phenotypic selection & genomic selection”

#### Code:

1. phenotypic selection (Fig. a)

```
defineSpecies(nSim = 5)
initializePopulation()
phenotype()
select()
cross()
phenotype()
select()
cross()
phenotype()
select()
cross()
plotData()
```

2. genomic selection (Fig. b)


```
defineSpecies(loadData="previousData")
initializePopulation()
phenotype()
genotype()
predictBreedVal()
select()
cross()
phenotype()
genotype()
predictBreedVal()
select()
cross()
phenotype()
genotype()
```



```

predictBreedVal()
select()
cross()
plotData(add=T)


```



### Simulation result:

Scheme 1 is phenotypic selection, and Scheme 2 is genomic selection.

Bold lines represent the mean values of simulation trials (in this case, 5 times of simulations), and each thin line is the result of a simulation trial.



**Now, we are preparing this manual...**