


Deterministic Pattern Formation in Swarms of Robots

Franck Petit


Problem



Definition (Arbitrary Pattern Formation)

Given a swarm of n robots scattered on the plan, designing a **deterministic** algorithm so that, the robots eventually form a pattern \mathcal{P} made of n positions and known by each of them in advance.


Problem



Definition (Arbitrary Pattern Formation)

Given a swarm of n robots scattered on the plan, designing a **deterministic** algorithm so that, the robots eventually form a pattern \mathcal{P} made of n positions and known by each of them in advance.

Problem



Definition (Arbitrary Pattern Formation)

Given a swarm of n robots scattered on the plan, designing a **deterministic** algorithm so that, the robots eventually form a pattern \mathcal{P} made of n positions and known by each of them in advance.

In other words, at the end of the computation, the positions of the robots coincide, with the positions of \mathcal{P} , where \mathcal{P} can be translated, rotated, and scaled in each local coordinate system.

Previous Works

SoD and Chirality

[Flocchini et al., 1999]

A solution exists for **any** n and any \mathcal{P} .

SoD and No Chirality


[Flocchini et al., 2002]

Previous Works

SoD and Chirality

[Flocchini et al., 1999]

A solution exists for **any** n and any \mathcal{P} .



SoD and No Chirality


[Flocchini et al., 2002]

Previous Works

SoD and Chirality

[Flocchini et al., 1999]

A solution exists for **any** n and any \mathcal{P} .



SoD and No Chirality


[Flocchini et al., 2002]

Previous Works

SoD and Chirality

[Flocchini et al., 1999]


A solution exists for **any** n and any \mathcal{P} .



SoD and No Chirality

[Flocchini et al., 2002]

If n is **odd**, a solution exists for any \mathcal{P} .




Previous Works

SoD and Chirality

[Flocchini et al., 1999]


A solution exists for **any** n and any \mathcal{P} .




SoD and No Chirality

[Flocchini et al., 2002]

If n is **odd**, a solution exists for any \mathcal{P} .



If n is **even**, a solution exists provided that \mathcal{P} is **symmetric**.



Pattern Formation With No Sense of Direction

Question

Assuming no sense of direction (with or without chirality), which kind of patterns can be formed in a **deterministic** way?

Pattern Formation With No Sense of Direction

Theorem

[Flocchini et al., 2001]


*If the robots share **no Sense of Direction**, then they cannot solve the Arbitrary Pattern Formation problem **deterministically**, even having the ability of chirality.*

Pattern Formation With No Sense of Direction

Theorem

[Flocchini et al., 2001]

If the robots share **no Sense of Direction**, then they cannot solve the Arbitrary Pattern Formation problem **deterministically**, even having the ability of chirality.



Pattern Formation With No Sense of Direction

Theorem

[Flocchini et al., 2001]

*If the robots share **no Sense of Direction**, then they cannot solve the Arbitrary Pattern Formation problem **deterministically**, even having the ability of chirality.*

Let Θ be the class of patterns that can be solved **deterministically** assuming robots devoid of sense of direction.

Corollary

Either Θ is equal to the set of regular polygons (n -gons)
or $\Theta = \emptyset$.

Circle Formation

Question

Assuming no sense of direction, is it possible to eventually form a regular n -gon (circle)?

Circle Formation

Previous work

[Défago and Konagaya, 2002] [Chatzigiannakis et al., 2004] [Défago and Souissi, 2008]

Asymptotic convergence toward the n -gon.

Circle Formation

Previous work

[Défago and Konagaya, 2002] [Chatzigiannakis et al., 2004] [Défago and Souissi, 2008]

Asymptotic convergence toward the n -gon.

Circle Formation

Previous work

[Défago and Konagaya, 2002] [Chatzigiannakis et al., 2004] [Défago and Souissi, 2008]

Asymptotic convergence toward the n -gon.

[Dieudonné and Petit, 2007]

Prime number of robots.

Circle Formation

Previous work

[Défago and Konagaya, 2002] [Chatzigiannakis et al., 2004] [Défago and Souissi, 2008]

Asymptotic convergence toward the n -gon.

[Dieudonné and Petit, 2007]

Prime number of robots.

Circle Formation

Previous work

[Défago and Konagaya, 2002] [Chatzigiannakis et al., 2004] [Défago and Souissi, 2008]

Asymptotic convergence toward the n -gon.

[Dieudonné and Petit, 2007]

Prime number of robots.

[Katreniak, 2005]

Any n (in ASYNC), but the n -gon is not systematically achieved.

Circle Formation

Previous work

[Défago and Konagaya, 2002] [Chatzigiannakis et al., 2004] [Défago and Souissi, 2008]

Asymptotic convergence toward the n -gon.

[Dieudonné and Petit, 2007]

Prime number of robots.

[Katreniak, 2005]

Any n (in ASYNC), but the n -gon is not systematically achieved.

Circle Formation

All previous protocols are based on the two following steps:


- 1 Move the robots on (the boundary of) a circle \mathcal{C} .
- 2 Without leaving \mathcal{C} , arrange them evenly along \mathcal{C} .

See also: Flocchini et al. « Distributed Computing by Mobile Robots:
Uniform Circle Formation » 2016

Circle Formation

All previous protocols are based on the two following steps:

- 1 Move the robots on (the boundary of) a circle \mathcal{C} .




- 2 Without leaving \mathcal{C} , arrange them evenly along \mathcal{C} .


Circle Formation

All previous protocols are based on the two following steps:

- 1 Move the robots on (the boundary of) a circle \mathcal{C} .




- 2 Without leaving \mathcal{C} , arrange them evenly along \mathcal{C} .



Circle Formation


All previous protocols are based on the two following steps:

- 1 Move the robots on (the boundary of) a circle \mathcal{C} .



EASY PART


- 2 Without leaving \mathcal{C} , arrange them evenly along \mathcal{C} .



Circle Formation


All previous protocols are based on the two following steps:

- 1 Move the robots on (the boundary of) a circle \mathcal{C} .



EASY PART

- 2 Without leaving \mathcal{C} , arrange them evenly along \mathcal{C} .



HARD PART

Circle Formation

Theorem

[Flocchini et al, 2006]


*There exists **no deterministic** algorithm that eventually arrange n robots evenly along a circle \mathcal{C} without leaving \mathcal{C} .*

Circle Formation

Theorem

[Flocchini et al, 2006]

There exists **no deterministic** algorithm that eventually arrange n robots evenly along a circle \mathcal{C} without leaving \mathcal{C} .




Circle Formation

Theorem

[Flocchini et al, 2006]

There exists **no deterministic** algorithm that eventually arrange n robots evenly along a circle \mathcal{C} without leaving \mathcal{C} .



Question


Are we done, i.e., $\Theta = \emptyset$?

Circle Formation

Theorem

[Flocchini et al, 2006]

There exists **no deterministic** algorithm that eventually arrange n robots evenly along a circle \mathcal{C} without leaving \mathcal{C} .




Question

Are we done, i.e., $\Theta = \emptyset$?

Fortunately, not!

An almost n -gon algorithm




[Katreniak, 2005]

Starting from a biangular circle

Theorem


[Flocchini et al, 2006]

There exists *no deterministic* algorithm that eventually arrange n robots evenly along a circle \mathcal{C} *without leaving \mathcal{C}* .




Starting from a biangular circle

Let us leave \mathcal{C}




Starting from a biangular circle

Let us leave \mathcal{C}




Starting from a biangular circle

Let us leave \mathcal{C}



Starting from a biangular circle


Let us leave \mathcal{C}



Starting from a biangular circle

Let us leave \mathcal{C}

Every robot is active




Regular Polygon

Starting from a biangular circle


Let us leave \mathcal{C}

Every robot is active



Regular Polygon


Some robots are active



Ideal Polygon

Starting from a biangular circle

Ideal Polygon




Property 1

- Either $d_0 \geq d_1 \leq \dots \geq d_{n-1} \leq d_0$
- or $d_0 \leq d_1 \geq \dots \leq d_{n-1} \geq d_0$

Starting from a biangular circle

Ideal Polygon




Property 2


A regular n -gon can be associated to an Ideal Polygon.

Starting from a biangular circle


Ideal Polygon



Circle Formation




Circle Formation




It works if $n \geq 5$ only

- 1 [Katreniak 2005] works if $n \geq 5$ only
- 2 Difficulty to find an invariant



$$n \leq 4$$

Arbitrary Pattern Formation



Theorem

$\forall n$, the class of patterns that can be solved *deterministically* assuming robots devoid of sense of direction (Θ) is equal to the set of regular polygons (n -gons).