

OSPF exercise

In this lab you will have to configure a basic two area OSPF setup on 3 routers. All basic configuration of the devices has been completed and does not have to be done.

1. On R0:
 - a. Enable OSPF on the router with the proccess number '10'.
 - b. Manually set the router ID to 9.9.9.9.
 - c. Check the IP address of the G0/1 interface. Advertise this network in the backbone area (area 0).
2. On R1:
 - a. Enable OSPF on the router with the proccess number '10'.
 - b. Manually set the router ID to 8.8.8.8.
 - c. Check the IP address of the G0/1 interface. Advertise this network in the backbone area.
 - d. Check the IP address of the G0/0 interface. Advertise this network in area 1.
3. On R2:
 - a. Configure a loopback interface with an IP address of 7.7.7.7. Remember what subnet masks loopback interfaces have.
 - b. Enable OSPF on the router with the proccess number '10'.
 - c. Check the IP address of the G0/0 interface. Advertise this network in area 1.
 - d. Check the IP address of the G0/1 interface. Advertise this network in area 1.
4. Try to ping R0's G0/1 interface from PC0. Does it work? Do a traceroute from PC0 to R0's G0/1 interface.
5. Check the OSPF routes on R0.
6. Check the OSPF neighbors on R1. What do you expect to see?