

PropertyMax.ai REST API — Required Endpoints

Prepared for: PropertyMax.ai Development Team

Prepared by: Apartment Corp

Date: June 18, 2026

Background

The Apartment Corp Vacancy Report dashboard currently retrieves all data by scraping the internal ColdFusion API (`vacancy.cfc`) using session-based username/password authentication. This approach is fragile — it breaks whenever PropertyMax.ai updates the login flow or HTML structure (which has occurred twice in recent months).

Adding the following REST endpoints, secured by the existing API token system already in place at `https://propertymax.ai/rest/max/`, would allow the dashboard to migrate to a stable, token-authenticated integration.

Existing REST Infrastructure

The current REST API base URL is:

```
https://propertymax.ai/rest/max/
```

Authentication is via a token passed in the URL path, e.g.:

```
https://propertymax.ai/rest/max/users/{token}
```

The `USERS (GET)` endpoint is already live and working. All new endpoints should follow the same pattern.

Required Endpoints

1. Vacancy Summary

Field	Value
Endpoint	<code>GET /rest/max/vacancy/summary/{token}</code>
Description	Returns current per-building vacancy statistics for all buildings
Current Source	<code>vacancy.cfc?method=getVacancyStats</code>

Example Response:

```
{
  "success": true,
  "asOf": "2026-06-18T18:00:00Z",
  "buildings": [
    {
      "id": "marrero",
      "name": "Marrero",
      "region": 3,
      "totalUnits": 173,
      "occupied": 168,
      "vacant": 5,
      "percentOccupied": 97.1,
      "moveIns": 2,
      "moveOuts": 1
    }
  ]
}
```

2. Daily Vacancy Changes

Field	Value
Endpoint	GET /rest/max/vacancy/daily/{token}
Description	Returns day-over-day changes showing which buildings gained or lost occupied units
Current Source	vacancy.cfc?method=getDailyChange

Example Response:

```
{
  "success": true,
  "date": "2026-06-18",
  "changes": [
    {
      "building": "Arbor Crest",
      "region": 1,
      "previousOccupied": 142,
      "currentOccupied": 144,
      "delta": 2
    }
  ]
}
```

3. Monthly Payment Snapshot (Net Rent Collected)

Field	Value
Endpoint	GET /rest/max/payments/snapshot/{token}?month=YYYY-MM®ion={1-4}
Description	Returns per-building Net Rent Collected for a given month and region
Query Params	month (required, format YYYY-MM), region (required, integer 1-4)
Current Source	vacancy.cfc?method=getPaymentsFromDatabase (Net Rent Collected row)

Example Response:

```
{
  "success": true,
  "month": "2026-05",
  "region": 3,
  "buildings": [
    {
      "name": "Marrero",
      "netRentCollected": 84037.32
    },
    {
      "name": "Gates",
      "netRentCollected": 67302.15
    }
  ]
}
```

4. Monthly Net Cash Flow

Field	Value
Endpoint	GET /rest/max/cashflow/monthly/{token}?month=YYYY-MM®ion={1-4}
Description	Returns per-building Net Cash Flow for a given month and region
Query Params	month (required, format YYYY-MM), region (required, integer 1–4)
Current Source	vacancy.cfc?method=getPaymentsFromDatabase (Net Cash Flow row)

Example Response:

```
{
  "success": true,
  "month": "2026-05",
  "region": 3,
  "buildings": [
    {
      "name": "Marrero",
      "netCashFlow": 103544.90
    }
  ]
}
```

5. Historical Vacancy Snapshots

Field	Value
Endpoint	GET /rest/max/vacancy/historical/{token}?month=YYYY-MM
Description	Returns monthly vacancy snapshot data for trend charts and historical analysis
Query Params	month (required, format YYYY-MM)
Current Source	vacancy.cfc?method=getHistoricalVacancy

Example Response:

```
{
  "success": true,
  "month": "2026-05",
  "buildings": [
    {
      "name": "Marrero",
      "region": 3,
      "totalUnits": 173,
      "occupied": 168,
      "vacant": 5,
      "percentOccupied": 97.1
    }
  ]
}
```

6. Building Directory

Field	Value
Endpoint	GET /rest/max/buildings/{token}
Description	Returns the full list of buildings with region assignment, unit count, and building identifier
Current Source	Hardcoded in the Apartment Corp dashboard application

Example Response:

```
{
  "success": true,
  "buildings": [
    {
      "id": "marrero",
      "name": "Marrero",
      "region": 3,
      "totalUnits": 173
    }
  ]
}
```

Summary Table

#	Endpoint	Method	Priority
1	/rest/max/vacancy/summary/{token}	GET	High
2	/rest/max/vacancy/daily/{token}	GET	High
3	/rest/max/payments/snapshot/{token}?month=YYYY-MM®ion={1-4}	GET	High
4	/rest/max/cashflow/monthly/{token}?month=YYYY-MM®ion={1-4}	GET	Medium
5	/rest/max/vacancy/historical/{token}?month=YYYY-MM	GET	Medium
6	/rest/max/buildings/{token}	GET	Low

Notes

- All endpoints should follow the existing token-in-path pattern already used by `USERS (GET)` .
 - All monetary values should be returned as floating-point numbers (not strings).
 - All dates should use ISO 8601 format (`YYYY-MM-DD` or `YYYY-MM-DDTHH:MM:SSZ`).
 - Regions are numbered 1–4 corresponding to the existing PropertyMax.ai region groupings.
 - A standard error response format is recommended: `{ "success": false, "error": "message" }` .
-

For questions, contact the Apartment Corp technical team.