Stage 11. Third-party integrations

Identity, provisioning, message broker, mail, ENERGY STAR, EnergyAI, the public API

PREPARED BY Energy Hippo implementation team

STATUS Research only; no recipe files, no checks and nothing to enter yet

> **Status: research only. Nothing in this stage can be entered yet.** There are no YAML files, no `checks.sql` and no build to follow: the folder holds this chapter and ADR-002c (the Stage 3 source-bundle research). The eight files the proposal at the end names (`01-services-bundle.yaml` to `08-acceptance.yaml`) do not exist, and no integration is built, configured or checked. Stages 1 to 10 and Stage 12 do not depend on it; the Stage 10 backup is complete without it, and what it cannot carry is exactly what this chapter lists. Read it to decide the stage, not to enter it.

Stage 10 ends with a database that is complete in itself: restore it anywhere and every report, rate, bill and allocation is there. Stage 11 is everything Northlake does with a system that is not inside that database: signing in through the university's identity provider, receiving users and groups from its provisioning system, publishing interval data to a message broker, sending mail, talking to ENERGY STAR Portfolio Manager and EnergyAI, and being called by other systems through the public API. These are the product's biggest customer-facing capabilities and the ones a restored database alone cannot demonstrate.

This chapter is research. It records what the product integrates with, where each integration's configuration actually lives, what outside service it needs, and what breaks when the database is restored on a different server. It ends with a proposal for the stage and the decisions that shape it. No YAML files or checks exist yet.

The three places configuration lives

The portability question turns on one distinction. An integration's settings sit in one of three places, and only the first travels with the backup.

Place	Examples	Travels with the backup
Database rows entered through a screen	Identity realms and providers, SCIM connections, ENERGY STAR property links, event-bus event types	Yes, including any URL or host name they contain
Configuration keys per installation	Message broker provider and RabbitMQ connection, SMTP host and credentials, task credentials for ENERGY STAR and EnergyAI, SCIM and SAML security limits	No; they live in the instance's configuration store and are re-entered per server
State inside the outside service	The Keycloak realm with its users, groups, signing keys and client secrets; RabbitMQ queues; the mail inbox; the Portfolio Manager sandbox account	No; the service is brought along or rebuilt beside the application

Database-resident settings that contain host names are the tricky class: they restore correctly but point at wherever the outside service was when they were typed.

Inventory

Identity: OpenID Connect and SAML

What the product has. A full third-party identity console on the web at Security Administration, Third-Party Identity, with sections for realms, OIDC providers, SAML providers, behavior, SCIM and group authority. Providers, realms, secrets, SAML metadata snapshots and trust anchors, token sessions and correlation bindings are all database rows in the IdentityProvider and Identity schemas. Seven legacy fixed providers (Windows, Microsoft, Facebook, Google, Twitter, Azure, OpenID Connect) are seeded disabled; no realm and no Northlake provider exist on the instance yet. SAML clock skew, issue age and replay lifetimes, and metadata fetch limits, are configuration keys, not rows.

Outside service. The synthetic identity provider in `identity/`: a Keycloak 26.7 realm named `northlake` generated from the security manifest (23 users, 29 groups, stable identifiers), behind Caddy at `https://localhost:8443`, with PostgreSQL for realm state and keys. It offers two OIDC client profiles (Modern code plus PKCE, and a Historical Legacy implicit profile), two SAML service-provider registrations (Standard and Saml2Int), two disposable lab realms for issuer and subject scenarios, a separate customer-site origin for cross-site session evidence, a launchpad, and verifiers for both protocols. Its README carries the ready-to-copy EEM values: discovery endpoint `https://localhost:8443/realms/northlake/.well-known/openid-configuration`, client `eemsuite-web`, scopes `openid profile email northlake`; SAML entity ID `urn:energyhippo:eemsuite-web:saml:standard` with metadata at `.../protocol/saml/descriptor`.

Portability. Three things bind the database rows to a place.

- The issuer and metadata URLs. Because the lab publishes itself at `localhost:8443`, a second server that runs the same compose bundle has the same issuer, and the restored provider rows keep working. A shared identity server on another host would need a stable DNS name instead.
- The registered callbacks. Keycloak allows exact redirect, post-logout and assertion consumer URLs; the lab registers `https://localdev.energyhippo.com/Hippo/...` and `https://localhost/Hippo/...`. A server that serves the site under another host name must add its callbacks through the lab's `/configure/oidc` and `/configure/saml` pages, or the site's host name must be a convention every server follows.
- Trust. The lab's private CA must be trusted on each server (`Trust-IdentityCertificate.ps1`), and the SAML metadata trust anchor the product snapshots is that CA's chain.

Client secrets are stored on the EEM side in the provider secret table, so they restore; the same secret must exist in the realm on the other server, which is true when the realm is generated deterministically from the manifest and the same `.env`.

Provisioning: SCIM 2.0

What the product has. EEM is the SCIM service provider at `/Public/scim/v2`. Connections, credentials, company scopes, templates, authority families and the provisioned user and group resources are rows in the Provisioning schema, created on the console's SCIM section. Rate limits, page sizes, credential lifetime (90 days) and rollover overlap are configuration keys.

Outside service. The lab's SCIM client harness (`identity/SCIM-2.0-TESTING.md`) plays the customer's provisioning system in the same role as Microsoft Entra: deterministic user and group lifecycles against a connection named `eem-local` with the template "Northlake external-only users" and group bindings keyed by external ID. Earlier interop work found Entra's exact requirements (mandatory If-Match on mutations, boolean `active`, member removal form), and those cases are in the harness.

Portability. The connection row restores, but its credential has a 90-day lifetime and is a secret the harness must hold too. Stage 11 should plan on re-issuing the SCIM credential on each server from the console and feeding it to the harness, rather than carrying it in the backup.

Message broker: RabbitMQ

What the product has. A broker abstraction with four providers: in-memory, SQLite (the default), file drop and RabbitMQ. Everything is configuration keys under `MessageBroker`: provider, queue providers, the RabbitMQ URI or host, port, virtual host, user name, password, queue kind (classic or quorum), exchange `eemsuite.broker`, publisher confirms, prefetch, heartbeat, recovery, queue length, single active consumer and retry delays. Nothing about the broker is in the database. Publishers today are the interval-data publish component (gateway output to broker queues), the handheld events publisher, brokered email delivery and one customer task. Hippo Tools has a Message Broker workbench for inspecting queues.

Outside service. The product repository already ships a development RabbitMQ (`BuildScripts/Local/Docker`, image `eemsuite-rabbitmq-dev`, ports 5672 and 15672, user `eemsuite`) inside a local-services compose file that also runs Mailpit, an SFTP server and an HTTP fixture server.

Portability. None needed. Switching Northlake to RabbitMQ is a per-server configuration change plus the container. The baseline database is unaffected, which is why the broker does not belong in Stage 10. What Stage 11 adds is the decision to run Northlake on RabbitMQ so the interval publish path and the handheld event path are exercised on a real broker, and the queue names and expected messages to check.

Mail: SMTP

What the product has. An SMTP section of configuration keys (host, port, SSL or STARTTLS, credentials, from address and name, timeout, retries) and a queued email delivery pipeline with its own queue and lease settings. Flows that send: password reset and invitations, email changes, the AP upload emailer, scheduled report delivery, instant report email, alarm notifications and job failure alerts. Hippo Tools has an Email Test Tool. Templates live under the content folder, some flows still send raw text.

Outside service. Mailpit from the same local-services compose file, with an inbox UI and an HTML-check API the templates were tuned against.

Portability. Configuration keys per server; the inbox is disposable. Stage 9's delivery to 100+ recipients needs this to be in place, so the mail sink is a prerequisite Stage 11 provides rather than a capability of its own.

ENERGY STAR Portfolio Manager

What the product has. Property setup and rating requests on the web (Stage 8), a sync task whose parameters are the root URL, customer prefix, Portfolio Manager user name and account password, and a client with timeout and retry settings. Scores arrive only from Portfolio Manager. Property links (the Portfolio Manager property IDs) are database rows once linked.

Outside service. A Portfolio Manager sandbox account. Nothing in either repository provides one; it is an account Energy Hippo holds.

Portability. The credentials are task parameters per server. The property IDs restore with the database and stay valid as long as the same sandbox account is used everywhere.

EnergyAI

What the product has. A client task with user name, password, upload URL and download URL parameters. Enrollment of loads, weather sites and periods is database-only with no screen (finding 12).

Outside service. The EnergyAI service. Lowest priority; Stage 9 carries it as a proposed capability pending the enrollment screen.

Weather and file sources

NOAA and Aeris Weather gateways call public HTTP services; Aeris needs a client id and secret entered as gateway task parameters (Stage 3). The ODBC historian and any SFTP-delivered formats use the SFTP and HTTP fixture containers from the product's local-services compose. These are Stage 3 capabilities with a Stage 11 dependency.

The public API and the event bus

What the product has. The `/Public` API with Swagger locked to administrators, service principals (principal type Service, authentication policy WorkloadOnly) with API keys issued from Users and Groups, and an event bus whose 37 event types include 24 that outside systems may publish through the API (bill import events, task and workflow run events, email requests, report delivery events, client invalidation, configuration materialized). Security notices can be raised toward specific applications. SignalR pushes to browsers and desktop apps are internal.

Outside service. None today. A small Northlake integration client (publishing a bill-import event, reading interval data, creating a user through SCIM) would be the way to exercise this end to end.

Portability. Service principals and their key hashes are database rows; the plain key is issued once and held by the caller, so it is re-issued per server like the SCIM credential.

What would break on a second server

Restoring the Stage 10 database on another machine and starting the application, with nothing else done:

- Local sign-in, every report, rate and bill: works.
- Sign-in through Northlake: fails until the identity bundle runs beside the application with the same issuer, the CA is trusted, and the site's host name matches a registered callback.
- SCIM: the connection exists, its credential must be re-issued.
- Broker: falls back to the SQLite provider unless the RabbitMQ keys are set.
- Mail: nothing sends until SMTP keys point at a sink.
- ENERGY STAR and EnergyAI: the tasks fail validation until their parameters are entered.
- Passkeys and any WebAuthn credential: bound to the site's origin, so a new host name invalidates them; MFA policies restore.

Proposal

Make Stage 11 the "Northlake external services" stage with three parts.

1. **One services bundle.** A compose project that brings the identity lab (Keycloak, PostgreSQL, Caddy, the configuration and customer sites) together with RabbitMQ, Mailpit and the SFTP and HTTP fixture containers from the product's development stack, under one `.env` per server and one start script. The identity lab already does the hard part; the bundle adds the other four services and a host-name convention.
2. **A per-server configuration set.** The configuration keys Northlake needs for the broker, SMTP, ENERGY STAR and EnergyAI, written as one JSON document per manifest for Assembly Configuration or the instance configuration files, with the secrets left as placeholders the server fills. This is what makes the second server behave like the first.
3. **The database-resident integration setup, entered through the console.** The Northlake realm, the Modern and Legacy OIDC providers, the Standard and Saml2Int SAML providers with their correlation bindings, the SCIM connection with its template and group bindings, and the service principals for the API client. These are the rows that belong in the baseline, on the condition below.

The condition is a host-name convention. If every Northlake server serves the site as `https://localdev.energyhippo.com/Hippo` (a hosts-file entry) and runs the identity bundle at `https://localhost:8443`, the identity rows in the baseline are valid everywhere and Stage 11's database work can be done once. Without that convention the identity rows are re-entered per server, and the baseline should carry none of them.

When it is built, the stage folder would hold:

```
stage-11-third-party/
  01-services-bundle.yaml        what runs, on which host names and ports, from which .env
  02-configuration-keys.yaml     MessageBroker, Smtp, EnergyStar, EnergyAI keys per server
  03-identity-realm.yaml         Security Administration > Third-Party Identity > Realms
  04-oidc-providers.yaml         the Modern and Historical Legacy providers
  05-saml-providers.yaml         the Standard and Saml2Int providers, correlation bindings
  06-scim-connection.yaml        connection, credential rollover, template, group bindings
  07-api-service-principals.yaml Users & Groups > service principals and API keys
  08-acceptance.yaml             sign-in per protocol, SCIM lifecycle, a brokered publish,
                                 a delivered mail, an ENERGY STAR sync, an API publish
  checks.sql
```

Decisions needed

- **Host names.** Adopt the convention above, or accept per-server identity setup. This decides whether identity rows go into the baseline.
- **Broker for the baseline build.** Run Northlake on RabbitMQ from Stage 3 onward so the publish paths are exercised while data loads, or keep SQLite until Stage 11. Running RabbitMQ early costs one container and no database change.
- **Portfolio Manager sandbox.** Which account, and who holds it. Stage 8 cannot show scores without it.
- **EnergyAI.** Whether to pursue the service connection at all before the enrollment screen exists.
- **An integration client.** Whether Northlake gets a small client program that publishes to the API and drives SCIM, or whether the identity lab's harness is extended to cover both.

Findings so far

- The SCIM credential lifetime (90 days by default) means a baseline that carried a credential would expire; re-issue per server is the right model, and the console supports rollover.
- The seven legacy fixed providers are seeded disabled on every install; a customer that never uses them sees them in the console. Worth a review of whether they should be hidden until enabled.
- Nothing in either repository provides ENERGY STAR or EnergyAI test services; both stay external accounts.