Class: Player

int: health
string: playerName
string: inventory
string: nenType

getName()
getHealth()
getInventory()
getSaveData()
takeDamage()

Class: Controller

struct Input
class Controller { Input
readAction())

readAction()

Enum Class: Player Request

None
Map
Inventory
Stats

Class: Game State(enum classtype)

TitleScreen
MainMenu
CharacterCreation
LoadsavedState
Settings
Roaming
Battle
Inventory
Narrating
Stats
Death
Exit

Enum Class: Action

North
East
South
West
Inventory
Menu
Exit
Number
Map
Enter
Back
None

readAction()

Enum Class: Roaming

Whale Island
Heaven's Arena
Greed Island

struct AreaState {
Roaming currentArea
PlayerRequest
void roam(Playe& player)
}

Class: TitleScreen

No members

displayTitle(std::<vector> string& title)
titleScreen(int userNum)

Class: Location

std::string: locationName
Location* north
Location* east
Location*south
Location* west
Area* area
Coordinates* position
struct Coordinates
bool isBorder

getName()
getArea()
setNorth(Location*)
setEast(Location*)
setSouth(Location*)
setWest(Location*)
getNorth()
getEast()
getSouth()
getWest()
setArea(Area*)
setCoordinates(Coordinates)
getCoordinates()
isBorder()

Class: Area

std::string areaName
std::vector<Locations>
Area* next
Area* previous

getLocations()
getName()
getNext()
getPrevious()

Class: Whale Island

void movement(Player& player, Input& input)

std::string locationName(Playre& player)

WhaleIsland(Area* whaleIslandArea)

Class: Content Node

std::string textContent private*
contentNode* parent
std::vector<contentNode>
children

setTextContent(string* textContent)
setParent(contentNode*)
addChild(contentNode*)
getTextContent()
getParent()
getChildren()

Class: TypeWrite

No members

\void TypeWrrite(std::string&)
void clearScreen()

Class: savedStates

std:: string playerName
int currentHealth

loadSavedStates()
chooseSAvedGames(std::vector <savedStates>)

