

EXO SLIM Tag

Wafer-thin UHF or HF/UHF asset tags for containers or metallic equipment



HID EXO Slim Tag transponders are the ideal solution for tagging shipping containers or other metallic assets. Some models being less than two-tenths of an inch (2.7 mm) thick, these tags mount flush to any surface. The high impact polycarbonate housings shield internal components from the environmental extremes and rugged treatment of industrial freight operations.

This versatile range of tags provides more ruggedization than standard on-metal labels and includes both global and regional options. The EXO Slim range provides cost effective solutions for volume applications in manufacturing and industry – especially for tracking and managing IT office assets, portals and returnable transport items (RTI's). There is a wide choice in terms of label size, read range, printing options and encasement alternatives.

Standard grey EXO Slim InLine Plate Tags provide excellent contrast for imprinting. The large surface accommodates embossing, laser-engraving or adhesive labels for a logo, barcode, serial number or text message.

Tough and versatile, EXO Slim Tag transponders are available for mounting on metal, plastic or wood using standard nails, screws or industrial adhesives.

The tags are lightweight, dust tight, waterproof and protected against close-range high pressure, high temperature spray downs (IP69K) for some models.

EXO Slim Tag UHF improve data collection speed and accuracy for logistics applications, while making tracking more cost-effective. The plates can be read from distances of up to a 49 ft (15 m), and are compliant with EPC global-certified UHF Class 1 Gen 2 readers and modules.

EXO Slim SHELL low-profile RFID tags are ideal for light duty indoor assets tracking. SHELL+ tags are ultrasonic sealed with a plastic back side to screw, while SHELL tags come with a sticker instead of the plastic cover on the back for easy application. Their transparent housing protects the barcode inside from scratches and allows tags to be applied to metallic and non-metallic surfaces.

In short, EXO Slim tags provide the durability of an encased RFID tag in a small footprint for harsh environments with some of the options in the range being the most rugged tags on the market, even withstanding a "sledgehammer test".



KEY BENEFITS:

- **Durability** – Resistant to outdoor elements as well as blunt and sharp impact.
- **Versatility** – Thin plates mount flush with glue or screws to any material.
- **Visibility** – Large surface may be printed or laser-engraved with logo, barcode, serial number or text.

TECHNOLOGY HIGHLIGHTS:

- RAIN UHF Worldwide operating frequencies from 860 to 960 MHz (off-metal) or specialized (on-metal)
- Fully interoperable; standards-compliant
- Reliable performance on both metal and non-metal surfaces
- Waterproof under high pressure and temperature; chemical and impact resistant
- Mount with glue, nails, or screws
- Versatile print/encasement options including clear rugged covers allowing visibility of human readable print or barcode on the label itself

APPLICATION AREAS:

Outdoor Asset Tracking and Logistics

- Postal and road toll management: truck, wagon and train tracking
- Supply chain management: pallet and goods tracking

Automation and Manufacturing

- Materials and inventory and tracking

Returnable Transport Items

- Shipping container tracking
- Tracking and monitoring plastic trays used in manufacturing conveyor systems

Waste Management

- Commercial and industrial bin identification

Indoor Asset Tracking

- Transparent SHELL+ and SHELL tags are ideal for light duty indoor assets tracking

	EXO Slim							
	InLine Plate	500 Lite	750P	800P	800P Lite	1200P	600 SHELL+	1200 SHELL+
								
Base Model Number	6C698A (EU) 6C698B (US)	CP20643 (EU) CP20494 (US)	CP16374	CP15940	CP20602	CP19038	CP14519 (EU) CP14522 (US)	CP14543
	ELECTRONIC							
Operating Frequency	(EU) - 865-868 MHz (ETSI) (US) - 902-928 MHz (FCC)	865-928 MHz (Global)					(EU) - 865-868 MHz (ETSI) / (US) - 902-928 MHz (FCC)	865-928 MHz (Global)
Chip Type	Monza 4E	M730					Monza R6-P	M730
Memory	496 bit EPC + 96 bit TID + 128 bit user	128 bit EPC 48 bit TID					28/96 bit EPC, 32/64 bit UM	128 bit EPC 48 bit TID
Anti-Collision	Yes							
Reading Distance (2W reader ERP, free space)	Up to 26 ft (8 m) off-metal; 20 ft (6 m) on-metal	Up to 33.8 ft (10.3m)	Up to 36 ft (11 m)	Up to 49 ft (15 m)	Up to 26 ft (8 m)	Up to 41.9 ft (12.8 m)	Up to 25.2 ft (7.7 m)	Up to 34.7 ft (10.6 m)
	PHYSICAL							
Dimensions	4.7 x 2.7 x 0.14 in (120 x 68 x 3.7 mm)	2.95 x 1.54 x 0.11 in (75 x 39 x 2.9 mm)	3.38 x 0.94 x 0.12 in (86 x 24 x 3 mm)	4.1 x 1.4 x 0.14 in (105 x 36 x 3.5 mm)	3.94 x 0.63 x 0.11 in (100 x 16 x 2.7 mm)	5.99 x 0.58 x 0.17 in (152.3 x 14.8 x 4.4 mm)	3.38 x 0.78 x 0.28 in (86 x 20 x 7.3 mm)	4.84 x 1.29 x 0.26 in (123 x 33 x 6.8 mm)
Mounting Method	Glue, nail or screw	Glue, Adhesive	Glue, nail or screw		Glue, Adhesive	Adhesive, Glue, nail or screw		Glue, nail or screw
Screw Fixation Hole	Ø 0.16 in (4.2 mm)		Ø 0.12 in (3.2mm)	Ø 0.17 in (4.4 mm)		Ø 0.13 in (3.5mm)	Ø 0.12 in (3.2 mm)	
Affixes To	All surfaces, including metal, plastic, wood		Off Metal, plastic, wood				All surfaces, including metal, plastic, wood	
Housing Material	PC/ABS high impact	PC		ABS	PC			
Color	Pantone warm gray 2U	Transparent		Gray	Transparent	White	Transparent	
Weight	1.0 oz (27 g)	0.2 oz (5.7 g)	0.24 oz (6.7 g)	0.4 oz (11.6 g)	0.13 oz (3.8g)	0.24 oz (7 g)	0.32 oz (9 g)	0.7 oz (20 g)
	CHEMICAL AND MECHANICAL RESISTANCE							
Water	IP69K, 176° F (80° C), 100 bar, 30 sek. 16 l/min	IP68, 6.6 ft. (2 m) x 24 h						
Withstands Exposure To	Mineral oil, petroleum, salt mist, vegetable oil	168 hr: 10% salt water, vegetable oil up to 80% humidity at 158° F (70° C), motor oil, 24 hr: acetone	5% caustic soda, 10% salt water, vegetable oil, Motor oil 68° F (20° C), 168hr		168 hr: 10% salt water, vegetable oil up to 80% humidity at 158° F (70° C), motor oil, 24 hr: acetone		5% caustic soda, 10% salt water, vegetable oil, Motor oil 68° F (20° C), 168hr	
Vibration & Shock	IEC 68.2.6 / IEC 68.2.29	MIL-STD-810 G						
Impact	IEC 62262-1K06	1.2 m drop on concrete	1 kg Steel, 1 m		1.2 m drop on concrete		1 kg Steel, 1 m	
Axial/Radial Force	500 N, 10 sec							
	THERMAL							
Storage	-40° to +185° F (-40° to +85° C), 1 x 1000 h	-40° to +185° F (-40° to +85° C)	-22° to +149° F (-30° to +65° C)	-4° to +185° F (-20° to +85° C)	-40° to +185° F (-40° to +85° C)		-22° to +149° F (-30° to +65° C)	
Operating	-40° to +185° F (-40° to +85° C)		-22° to +149° F (-30° to +65° C)	-4° to +185° F (-20° to +85° C)	-40° to +185° F (-40° to +85° C)		-22° to +149° F (-30° to +65° C)	
Shock/Fatigue	-40° to +185° F (-40° to +85° C), 100 x 5 min with 30 sec transition							
	OTHER							
Standards	UHF EPC Class 1 Gen 2, ISO 18000-6C, ISO 17364	UHF EPC Class 1 Gen 2, ISO 18000-6C, ISO 17364						
Options	Embossing or laser-engraving of logo, barcode or text. (Standard tags have no laser-engraving.)	Printing, encoding					Also available as SHELL with adhesive liner instead of hard back cover. See spec sheet for details	
Box Size	60 pcs.	1000 pcs.	1300 pcs.	720 pcs.	1000 pcs.	280 pcs.	936 pcs.	448 pcs.
Warranty	2 Years							



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +353 (91) 414060

Asia Pacific: +852 3160 9800 | Latin America: +52 55 9171 1108

For more global phone numbers click here

© 2026 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2026-02-11-1dt-rfid-il-exo-slim-taq-ds-en PLT-01889

Part of ASSA ABLOY

For more information, contact tagsales@hidglobal.com