AB Power Meter Monitor

Release 1.6.3 — Technical Manual

Allen-Bradley 1403 site power-meter poller, data logger, GUI and Prometheus exporter for NRAO / Green Bank Observatory

Component	Version
`ab_power_meter_monitor.py`	1.6.3
`vszh5_writer.py`	0.0.19
`ab_prometheus_exporter.py`	0.1.1
`ab_meter_caller.py`	1.3.0
Python (primary, tested)	3.12.3
Windows Python (Windows 11 and Wine 9.0)	3.12.15
Veusz (viewer, verified)	4.2.1

William W. Wallace
NRAO / Green Bank Observatory
wwallace@nrao.edu

27 October 2026

Contents

1 Summary **2**

2 Findings: RAM flush **2**
2.1 Why the flush did not protect the GUI . . . 2
2.2 What 1.6.0 does . . . 2
2.3 Store estimate and trigger . . . 3
2.4 Returning memory to the operating system (1.6.1) . . . 3

3 Findings: iterative .vszh5 writing **4**
3.1 How 1.5.5 wrote Veusz files . . . 4
3.2 How 1.6.0 writes them . . . 4

4 Other defects fixed **5**

5 Architecture **6**
5.1 Threads . . . 6
5.2 Persistence by sequence cursors . . . 7

6 Windows operation (1.6.2, 1.6.3) **7**
6.1 Output files held open by another program . . . 7
6.2 Stopping with Ctrl+Break . . . 7
6.3 Windows test kit . . . 7
6.4 First results on real Windows (1.6.3) . . . 8

7 Prometheus exporter 0.1.1 **8**

8 GUI **9**

9 Deployment **9**
9.1 Environment (mamba) . . . 9
9.2 Services . . . 10
9.3 Library use . . . 10

10 Configuration reference **10**

11 Verification **11**

12 Module review **12**

13 Known limitations and recommendations **13**

A Distribution contents **16**

1 Summary

Release 1.6.0 makes the memory protection of the monitor work in the GUI and in headless operation, replaces the Veusz output with native `.vszh5` documents that are appended in place on every poll, fixes a FITS defect that multiplied rows on every rewrite, and corrects the Prometheus exporter so it never re-exports stale readings. Python 3.12 is the primary, tested target; the source remains at the Python 3.7 language level. Every defect below was first reproduced against an offline emulator of the meter web pages and then verified fixed (Section 11).

Release 1.6.1 makes the flush hand the freed memory back to *Windows* as well (1.6.0 did so only on Linux), Section 2.4, and fixes a race in which a forced write (flush, Save Now, stop) waiting for a busy writer could send the same rows twice (Section 4). The race was found by running the test-suite on a Windows build of Python 3.12.

Release 1.6.2 makes Windows operation robust: an output file held open by another program (Excel) no longer produces an error per table per poll, and its rows are kept or written to rescue files that are merged back; Ctrl+Break now stops the headless monitor and the exporter gracefully. A Windows test kit (Section 6) runs every check on a Windows PC.

Release 1.6.3 follows the first run of that kit on real Windows hardware (Section 6.4): the GUI crash seen there was in Intel oneMKL 2026.1.0, NumPy's matrix library in the conda-forge environment, and is avoided with OpenBLAS; NumPy's matrix library is limited to one thread (2.97 GB → 18 MB commit charge); an unreachable meter no longer costs a minute per poll; and a run without any data says so.

2 Findings: RAM flush

2.1 Why the flush did not protect the GUI

The 1.5.5 flush logic only manages `TIME_SERIES_STORE`. In the GUI the dominant memory growth was elsewhere, so clearing the store could not help:

1. **Preview tabs leaked every poll.** `_populate_plot_tabs()` called `QTabWidget.clear()` and rebuilt every tab. Qt documents that `clear()` and `removeTab()` do *not* delete the page widgets [1]; each poll therefore left about 70 widgets plus their full-size pixmaps alive. Measured on the original code at a 2 s period: 1507 → 2947 → 4387 live widgets and 436 MiB → 691 MiB → 946 MiB RSS at 0 s, 45.8 s and 91.2 s (Fig. 5).
2. **The log console grew without bound** (`QTextEdit`, DEBUG level, one line per page fetch).
3. **The store-size trigger never cleared anything.** In headless mode `should_flush()` rewrote the files but left the store intact; the GUI never evaluated it at all. Only the system-RAM-% trigger cleared.
4. **The system-RAM-% trigger mis-fired.** It is system-wide: when other processes held the RAM, the monitor flushed and cleared its store on *every* poll without freeing anything significant.
5. **Freed memory was not returned to the operating system.** `gc.collect()` frees objects, but the allocator keeps the pages, so RSS (and the RAM %) stayed high after a flush.
6. **FITS rewrites multiplied rows** (Section 4); with FITS enabled the GUI exhausted memory in minutes regardless of any flush.
7. **GUI-thread saturation.** About 40 preview PNGs were rendered on the GUI thread every poll and Poll Now ran the whole poll on it.

2.2 What 1.6.0 does

- Preview tabs are created once per plot and updated in place; tabs that disappear are `deleteLater()`'d. Only the visible tab is rendered, min/max decimated to `PREVIEW_MAX_POINTS`

per series, and the pixmap of a tab is released when the user leaves it.

- The console is a `QPlainTextEdit` with `maximumBlockCount` [2], fed from any thread through a queued signal.
- Polling, persistence and flushing run in an acquisition worker thread (`QThread`); Save Now, Flush RAM Now and Open in Veusz are executed by that worker between polls, so they never race it.
- One flush function, `perform_ram_flush()`, serves the GUI, the headless loop and the caller. It persists every enabled output, waits for the writes, drops only rows that *every* output confirmed, and then returns the freed memory to the operating system: `malloc_trim(0)` on Linux [3], heap decommit and working-set trim on Windows since 1.6.1 (Section 2.4).
- Triggers are store estimate, process RSS, system RAM % and free RAM, with a minimum interval and a minimum store size for the system-wide triggers (Eq. 2).

2.3 Store estimate and trigger

For table i with n_i rows and k_i parameters, the store estimate in bytes is evaluated in $O(\text{tables})$ every poll:

$$B = \sum_i n_i \,(32\,k_i + 144), \tag{1}$$

32 B being one float object (24 B) plus its list slot (8 B) and 144 B per row the timestamp string, sequence number and Unix time. Against an exact object walk the estimate was within 1 % (5.54 MiB vs. 5.57 MiB; 22.16 MiB vs. 21.92 MiB). With Δt the time since the last flush, an automatic flush happens when

$$F = E \wedge (\Delta t \geq T_{\min}) \wedge \Big[\,(B > B_{\max}) \vee (B \geq B_{\min} \wedge (R > R_{\max} \vee P \geq P_{\max} \vee M_{\text{free}} < M_{\min}))\Big], \tag{2}$$

where E is `ENABLE_RAM_FLUSH`, $T_{\min}$ `MEM_FLUSH_MIN_INTERVAL_SEC`, $B_{\max}$ `MEM_FLUSH_THRESHOLD_MB`, $B_{\min}$ `MEM_MIN_STORE_MB_FOR_CLEAR`, R the process RSS, P the system RAM use and M_{free} the free RAM.

2.4 Returning memory to the operating system (1.6.1)

Dropping rows frees Python objects, but three layers below keep memory: CPython's `pymalloc` returns a 1 MiB arena (with `VirtualFree` or `munmap`) only when every object in it is free [19]; the C heap keeps freed blocks committed; and on Windows even released pages stay in the process's *working set* — Task Manager's "Memory" column — until the memory manager trims it. 1.6.0 handled only Linux, so on Windows a flush emptied the store but Task Manager showed no drop. With `MEM_RETURN_TO_OS = 1`, `return_memory_to_os()` now runs after every flush:

OS	Call	Effect
Linux (glibc)	`malloc_trim(0)`	free heap pages returned to the kernel [3]
Windows 8.1+	`HeapSetInformation(NULL, HeapOptimizeResources, {Version=1, Flags=0})`	every heap with a low-fragmentation heap: caches optimised, memory decommitted if possible [13]; the call Firefox makes under memory pressure [17]
Windows	`EmptyWorkingSet( GetCurrentProcess())` (`MEM_TRIM_WORKING_SET`)	removes as many pages as possible from the working set [14]; pages still in use fault back in on their next access
not used	`_heapmin()`	in the Universal CRT this is only `HeapCompact(__acrt_heap, 0)` [16], which "does not compact the heap any further" on a normal system [15]

The Windows functions are bound once through private `ctypes.WinDLL` instances with explicit `HANDLE` and `SIZE_T` argument types (the `ctypes` default C `int` would truncate 64-bit handles), the release is serialised by a non-blocking lock, runs outside the persistence lock and never raises into the poll loop. On Windows two numbers matter: the working set W (`psutil rss`, Task Manager "Memory") and the commit charge C (private bytes, `psutil vms`, Task Manager "Commit size"). With D the memory the heaps could decommit,

$$C_{\text{after}} = C_{\text{before}} - D, \qquad W_{\text{after}} \approx W_{\text{touched}} \leq C_{\text{after}}, \tag{3}$$

where W_{touched} is the memory the process uses again before the next measurement. Both values are printed in the flush log and the GUI.

Measured with `tests/test_memory_release.py`: a store of 3 000 000 values (estimate 98.4 MiB) is filled and flushed.

	RSS (MiB)			
Run	idle	filled	flushed	OS step
Linux, Python 3.12.3	64	180	70	`malloc_trim`: 96 → 70
Linux, Python 3.8.20	51	169	54	`malloc_trim`: 80 → 54
Windows Python 3.12.15 (Wine)	350	466	364	both calls succeed*
GUI soak, Flush RAM Now (Linux)		239 → 220		`malloc_trim`

*Wine runs the Windows code paths but not the Windows memory manager; the Windows drop measured there comes from `pymalloc` freeing whole arenas.

3 Findings: iterative .vszh5 writing

3.1 How 1.5.5 wrote Veusz files

- It required the `veusz` Python package and drove `veusz.embed.Embedded`, which starts a Veusz process and rebuilds the *whole* document from the in-memory store on every save. Nothing was appended: the document could only reflect what was still in RAM.
- Consequently, every RAM flush had to produce a separate timestamped snapshot file, and the final file after a flushed run held only the last window. A long run became a scattered set of partial documents.
- Headless runs wrote Veusz only at the end of the run (and optionally at a flush); a crash lost the whole document. Caller mode rebuilt the full document, through a new Veusz process, on every poll.
- Dataset names were cut to 64 characters, so long parameter names could collide and silently overwrite each other.

3.2 How 1.6.0 writes them

`vszh5_writer.py` 0.0.18 adds `VeuszAppender`, which opens an existing document `'r+'` and grows it; the monitor uses it for one document per meter, `ABMeter_<ip>.vszh5`, appended on every poll:

- per table a date dataset `<octet>_dt_<table>` and one numeric dataset per parameter, collision-free and never truncated;
- datasets are chunked (1024 rows), resizable and *uncompressed*: a partly filled compressed chunk that grows is moved, leaving dead space, so compression would bloat a file appended every 30 s [4];

- the fill value is NaN, so rows reserved by a resize but never written (power loss mid-append) read back as gaps, not zeros; on the next append columns are padded or truncated back to the length of the time axis;
- a parameter that appears later is back-filled with NaN; the Veusz page script (per-table grid pages, per-unit overlay pages) is rewritten only when datasets are added;
- the table→dataset index lives in `/VszAppend`; Veusz 4.2.1 reads only `/Veusz` (confirmed in its `loadHDF5Doc` [5]), so appending resumes after a restart;
- when a reader holds the HDF5 file lock (Veusz while loading) the rows stay in memory for the next poll; if they must land now (flush, stop) a standalone rescue document is written; an unreadable file is moved aside and a new one started; rollover at `VSZH5_MAX_FILE_MB`.

Each append writes only the new rows: the cost per poll is O(new rows), independent of the document size. The appended documents load and render in real Veusz 4.2.1 (all 23 pages plus the PDF, Fig. 1).




Figure 1: Pages of an appended `.vszh5` rendered by real Veusz 4.2.1: per-table grid page (left) and overlay page (right), emulator data.

4 Other defects fixed

FITS row multiplication
`EXTNAME = tname[:8]` made `Voltage_Current_Table`/`Voltage_Current_Snapshot_Log_Table` and `Diagnostic_Table`/`Diagnostic_Table_Extended` collide; the reader merged the two HDUs and each rewrite copied both tables' rows into both HDUs (Fig. 2). Same-second timestamp de-duplication also dropped genuine rows. 1.6.0 uses the full table name, separates old files by `TBLNAME`, adds `EPOCH_UTC`, and writes atomically (temporary file, then `os.replace`).

CSV / Markdown append
In append mode across runs, row counting mixed old and current rows and writing stopped after the first poll. Writers now keep per-row sequence cursors.

Exporter
Re-exported a dead meter's last values; `samples_total` plateaued (not a valid counter [6]). See Section 7.

Concurrency
`ALL_DEVICE_DATA` was rebuilt while the GUI iterated it; now swapped under a lock.

Duplicates
Duplicate IPs polled one meter from two threads; duplicate parameter names overwrote each other (now `Name [#N]`).

Python 3.12
`datetime.utcnow()` is deprecated [9, 10]; replaced by timezone-aware UTC.

Service wrapper
`POLL_INTERVAL` was read but never passed on.

Requirements
`qtpy` (imported by the GUI) was missing.

Duplicate rows after a busy writer (1.6.1)
1.6.0 advanced a writer's cursors in a future done-callback. `concurrent.futures` wakes the threads blocked in `result()` *before* it runs the done-callbacks [18], so a forced persist that waited for a busy writer could read the old cursor and send rows a second time; every writer appends or merges without de-duplication. Found as extra XLSX rows when the suite ran on Windows Python (slower writes); possible on any OS. Fixed in Section 5.2.




Figure 2: FITS rows per HDU after successive rewrites (emulator, measured).

5 Architecture

5.1 Threads




Figure 3: Data flow. The acquisition worker (GUI) or the headless loop runs the poll, the persistence and the flush in one thread; the GUI thread only reads snapshots of the table it displays.

5.2 Persistence by sequence cursors

Each stored row r receives a process-wide increasing sequence number s_r. Every writer w keeps, per output folder and per (meter, table), the highest sequence number it persisted, c_w. A persist call copies once, under the store lock, the rows with $s_r > \min_w c_w$, and hands each writer the rows with $s_r > c_w$. A writer's cursor moves only after its write succeeded, and a writer whose previous write is still running is skipped (never two writes to one file). Since 1.6.1 the cursor is advanced inside the writer task, before its future completes, and each writer's cursor is read only after its previous write is confirmed done at time t_{done}, so the rows handed to w are

$$R_w = \{\, r : s_r > c_w(t_{\text{done}}) \,\}, \tag{4}$$

which cannot contain a row already written (1.6.0 could read c_w before the callback that advanced it had run). A flush may drop row r only if

$$s_r \le \min_{w \in W} c_w, \tag{5}$$

with W the enabled outputs, which is the formal statement of "no row is dropped before every output has written it".

6 Windows operation (1.6.2, 1.6.3)

6.1 Output files held open by another program

Excel keeps an open CSV or workbook locked against writes by other programs. In Windows terms the file was opened with a share mode that lets others read but not write; a later open for writing fails with a sharing violation [21], which Python raises as `PermissionError` (Win32 errors 5, 32 or 33). 1.6.1 logged an ERROR for every table on every poll in that state, and a RAM flush could not drop the rows. 1.6.2 treats the file as *in use*:

- one WARNING per file per 10 minutes; the writer's cursor does not move, so the rows stay in memory and are written once the file is closed;
- a forced persist (flush, Save Now, stop) writes them to `<file>_<YYYYmmdd_HHMMSS>[_N]_rescue.csv` (or `.md`), so the flush can still free the memory;
- the next successful write first merges the rescue files, ordered by (time stamp, counter): each is renamed to `.merging` before its rows are copied, so a merge is never repeated even if deleting the file afterwards fails;
- new Markdown rows after a merged rescue section start a "(continued)" section.

FITS, XLSX and `.vszh5` already kept their rows or wrote rescue files.

6.2 Stopping with Ctrl+Break

On Windows `SIGTERM` sent by another process is `TerminateProcess` and cannot be handled [23]; supervisors send `CTRL_BREAK_EVENT` to the process group instead, which reaches only processes sharing the sender's console [22]. The monitor (1.6.2) and the exporter (0.1.1) now handle `SIGBREAK` like `SIGINT`/`SIGTERM`: stop after the current page, then the final writes. Before, Ctrl+Break killed them without the final FITS/XLSX writes.

6.3 Windows test kit

`windows/` contains one-click scripts for a Windows 10/11 PC; no meters are needed (the emulator serves two meters on 127.0.0.2 and 127.0.0.3).

Script	What it does
`1_setup_environment.bat`	creates `env` from pinned conda-forge versions (mamba, conda or micromamba; venv + pip fallback); optional `env_veusz` with Veusz 4.2.1
`2_run_all_tests.bat`	`tests/run_all_tests.py`: system report, eight suites, `AB_TestResults_<computer>_<time>.zip`
`3_task_manager_check.bat`	six flush runs pausing 20 s each to watch the working set in Task Manager
`4_gui_with_emulator.bat`	GUI against the emulator, with a hands-on checklist
`5_headless_with_emulator.bat`	visible headless run, stopped with Ctrl+C or Ctrl+Break

The scripts use explicit `if errorlevel` checks instead of `||` after `call`, because `cmd` implementations disagree on the result of `||` after a called batch file (Wine's takes the branch even after success).

6.4 First results on real Windows (1.6.3)

The 1.6.2 kit ran on txrx03 (Windows 11 26H2, Intel Core i9, 32 GB) on 26–27 October 2026. Seven of eight suites passed: after a flush the working set fell from 298 to 4 MiB; a 10-minute headless soak wrote 591 polls as 591 rows in every output and stopped cleanly on Ctrl+Break.

Finding	Cause and fix
GUI closed with exit code −1066598273 (`0xC06D007F`) at the first preview plot	`0xC06D007F` is the Visual C++ delay-load "procedure not found" exception [25]. `faulthandler` [26] placed it inside `np.dot` (matplotlib's 3×3 transforms), i.e. in NumPy's BLAS: Intel oneMKL 2026.1.0, conda-forge's default on Windows. The headless monitor multiplies no matrices and was unaffected. The user's own environment with oneMKL 2026.2.0 worked; that build is labelled *broken* on conda-forge [27, 28] and cannot be pinned. With OpenBLAS (`libblas=*=*openblas`) the same GUI ran 80 polls writing every output without a warning; kit 1.1.0 pins it.
OpenBLAS: 2,971 MB commit charge at `import numpy`	per-thread work buffers. With `OPENBLAS_NUM_THREADS=1`: 18 MB (measured). The monitor sets it before NumPy is imported (`BLAS_MAX_THREADS`); a value set beforehand is kept.
Offline meter: about 67 s and 44 warnings per poll	each of 11 pages was retried. Once a page fails because the meter cannot be connected to at all (refused, no route, connect time-out), its remaining pages are skipped for that poll (`SKIP_PAGES_WHEN_UNREACHABLE`); an HTTP error from a page that did connect does not count.
"final writes: up to date" although no meter ever answered	now "no data received"; `run_status()` reports `polls_with_data`.
First poll in step 5 refused	the scripts waited a fixed 3 s for the emulator; they now wait until it answers (`tests/wait_for_port.py`, at most 30 s).

7 Prometheus exporter 0.1.1

The exporter keeps its own latest snapshot, `_LATEST[ip][table] = {fetch_epoch, values}`, replaced whole on a good fetch and removed on a failed fetch or when the meter is down; tables older than `--stale-after` (default 2.5× the interval) are not exported. Metric families are rebuilt on every scrape, as Prometheus recommends for exporters [6, 8]. Prometheus stores one sample

per scrape; scraping faster than the poll interval records a reading more than once. Either match `scrape_interval` to `--interval`, or run with `--timestamps`, which attaches each reading's fetch time; Prometheus discourages exporter timestamps in general because they change staleness handling (series then persist for the 5-minute lookback) [7].

Metric	Meaning
`ab_meter_value{ip,table,parameter,unit}`	latest value
`ab_meter_up{ip}`	meter answered the last poll
`ab_meter_table_up{ip,table}`	table fetched and fresh
`ab_meter_last_fetch_timestamp_seconds`	last good fetch per table
`ab_meter_samples_total`	successful fetches (monotonic)
`ab_meter_table_fetch_errors_total`	failed fetches
`ab_meter_polls_total`	poll cycles
`ab_meter_poll_errors_total`	poll cycles that raised

8 GUI

Fig. 4 shows the 1.6.0 window (dark theme) after a short run against the emulator: output and memory-protection controls, the memory line, the bounded status console and the preview tabs. The View menu toggles light and dark themes; the previews follow the theme. Closing the window waits for the final writes instead of terminating the worker thread.




Figure 4: Monitor 1.6.0 GUI, dark theme (off-screen capture, emulator data).

9 Deployment

9.1 Environment (mamba)

```
mamba env create -f environment.yml        # Python 3.12 + pip deps
mamba activate abmeter
```

```
# or pure conda-forge:
mamba env create -f environment-conda.yml
# Python 3.7.11 hosts:
mamba env create -f environment-py37.yml
```

9.2 Services

```
sudo ./install.sh                    # headless monitor, system mode
sudo ./install.sh --exporter         # + Prometheus exporter
sudo ./install.sh --mamba            # mamba env, Python 3.12
python ab_stop.py                    # clean stop (STOP_COLLECTION)
```

The installer now also installs `vszh5_writer.py` and chooses `requirements-py312.txt` on Python $\geq$ 3.12. The wrapper passes `POLL_INTERVAL` and optional `RAM_PCT_LIMIT`; `ABMETER_OUTPUT_DIR` relocates the output.

9.3 Library use

```
import ab_power_meter_monitor as abm
cfg = abm.begin_run()                # folders, log file, run bookkeeping
status = abm.poll_cycle(cfg)         # poll + store + persist + memory check
abm.perform_ram_flush(cfg, "manual")  # persist, then free rows
abm.end_run(cfg)                     # final writes (FITS/XLSX included)
```

10 Configuration reference

Switch	Default	Meaning
`ENABLE_CSV`, `ENABLE_LOG_APPEND`	0	appended every poll
`ENABLE_VEUSZ`	0	native `.vszh5`, appended in place
`VEUSZ_APPEND_EVERY_CYCLE`	1	0: append at flush/stop only
`ENABLE_FITS`, `ENABLE_XLSX`	0	rewritten atomically on a cadence
`FULL_WRITE_EVERY_N_CYCLES`	10	FITS/XLSX cadence (0: flush/stop)
`APPEND_OUTPUT_FILES`	1	0: start files afresh once per run
`FSYNC_OUTPUTS`	1	fsync appended CSV/MD
`ENABLE_RAM_FLUSH`	1	automatic flush master switch
`MEM_FLUSH_THRESHOLD_MB`	256	$B_{\max}$ in Eq. 2
`MEM_PROC_RSS_LIMIT_MB`	0	$R_{\max}$ (0 = off)
`MEM_RAM_PCT_LIMIT`	60	$P_{\max}$
`MEM_FREE_MIN_MB`	512	$M_{\min}$
`MEM_MIN_STORE_MB_FOR_CLEAR`	1.0	$B_{\min}$
`MEM_FLUSH_MIN_INTERVAL_SEC`	120	$T_{\min}$
`RAM_FLUSH_KEEP_SAMPLES`	0	rows kept after a flush (GUI: 120)
`RAM_FLUSH_SPILL_PICKLE`	0	pickle the store when no output is on
`MEM_RETURN_TO_OS`	1	after a flush: `malloc_trim` / Windows heap decommit
`MEM_TRIM_WORKING_SET`	1	Windows: trim the working set after a flush
`VSZH5_MAX_FILE_MB`	256	`.vszh5` rollover
`VSZH5_TIME_AXIS`	local	`local` (DST-aware) or `utc`

Switch	Default	Meaning
`FITS_MAX_ROWS_PER_FILE`	100000	FITS rollover
`XLSX_MAX_ROWS_PER_FILE`	50000	XLSX rollover (Excel limit [12])
`METER_URL_TEMPLATE`	see right	`http://{ip}/{page}`; proxy / emulator
`SKIP_PAGES_WHEN_UNREACHABLE`	1	skip a meter's other pages for the poll once it cannot be connected to (1.6.3)
`BLAS_MAX_THREADS`	1	`OPENBLAS_NUM_THREADS` before NumPy loads, unless already set (1.6.3)
`PREVIEW_MAX_POINTS`	2000	preview decimation
`GUI_LOG_MAX_LINES`	2000	console size

11 Verification

All tests run offline against `tests/ab_meter_emulator.py`, which serves the 11 pages per host with drifting values, string cells, a duplicated parameter name and optional faults. Python 3.12 runs used `-W error::DeprecationWarning`. The Windows runs used the conda-forge `win-64` build of Python 3.12.15 with numpy, h5py, astropy and openpyxl, executed under Wine 9.0 with Microsoft's own `ucrtbase.dll` [20].

Test	What it proves	Result
`test_vszh5_appender`	create/append/reopen, NaN back-fill, layout conversion, real-Veusz render	pass (3.12, 3.8, Windows 3.12)
`test_monitor_offline` (8 tests)	one row per poll in every output across a flush; append across runs; fresh mode; FITS separation; duplicate names; trigger gating; locked `.vszh5`; no row sent twice to a busy writer; 23 pages render in Veusz 4.2.1	pass (3.12, 3.8; Windows 3.12 three runs)
`test_memory_release`	bindings built once with 64-bit argument types; release never raises; flush of a 98 MiB store returns it (Linux RSS 180 → 70 MiB); switch off; no overlap	pass (3.12, 3.8, Windows 3.12)
`test_exporter_offline`	no duplicate series; dead meter not exported; monotonic counters; `--timestamps`; SIGTERM shutdown (POSIX)	pass (3.12, 3.8; Windows 3.12 collector tests)
`gui_soak_test` (150 s, 137–140 polls)	widget count constant (445; 447 with the 1.6.1 check boxes); previews rendered 137/137; no monitor errors; close waits for final writes	pass (3.12, 1.6.0 and 1.6.1)
`test_windows_file_locks`	files locked like Excel (`CreateFileW`, read-share): one warning per file, no error, rescue files on flush, merged back in order, no row lost or doubled	pass (3.12 Linux simulated; Windows 3.12 real locks)
`headless_soak_test`	real CLI, every output, automatic flushes, graceful stop; row counts equal in CSV, MD, `.vszh5`, XLSX, FITS; no leak	pass (3.12 Linux)
`run_all_tests` (Windows kit)	all suites + report + results zip	8/8 pass (3.12 Linux, quick)

Test	What it proves	Result
`test_windows_file_locks`	files locked like Excel (`CreateFileW`, read-share): one warning per file, no error, rescue files on flush, merged back in order, no row lost or doubled	pass (3.12 Linux simulated; Windows 3.12 real locks)
`headless_soak_test`	real CLI, every output, automatic flushes, graceful stop; equal row counts in CSV, MD, `.vszh5`, XLSX, FITS; no leak	pass (3.12 Linux)
`run_all_tests` (Windows kit)	all suites + report + results zip	8/8 pass (3.12 Linux, quick)
Headless profile (600 polls, all outputs, flush every 50)	Python-traced memory constant; RSS plateau (Fig. 6)	pass (3.12)




Figure 5: GUI soak, emulator, every output enabled. 1.5.5 at a 2 s period; 1.6.0 at a 1 s period with tab switching, an interactive window and a Flush RAM Now during the run (elapsed time of 1.6.0 points approximated from poll count, 140 polls in 150 s).




Figure 6: Headless monitor, 600 polls, CSV + Markdown + `.vszh5` every poll, FITS + XLSX every 25 polls, RAM flush every 50 polls (profiled with `tracemalloc`; the step at poll 150 is the profiler's own snapshot).

12 Module review

Module	Alternative	Decision
requests	httpx, urllib3	kept; one keep-alive session per meter; HTTP/2 or async bring nothing to a single-threaded meter web server
beautifulsoup4 + lxml	`lxml.html` directly	kept: BeautifulSoup already parses with libxml2 through lxml; direct lxml text extraction can differ for nested markup and would rename columns in existing files. Trees are now `decompose()`'d
matplotlib (Agg)	pyqtgraph	kept for 1.6.0 (only the visible tab, decimated). pyqtgraph is the better long-term choice for live Qt plots (in-place `setData`, built-in downsampling, no PNG round trip)
openpyxl	XlsxWriter	kept, now read-only → write-only streaming [11]; XlsxWriter is faster for pure writing but cannot read the existing workbook
astropy.io.fits	fitsio	kept (NRAO convention, no compiled extra)
veusz.embed	h5py + `vszh5_writer`	**replaced**: no Veusz process, in-place append, Python 3.12 wheels
psutil	/proc parsing	kept (cross-platform)
prometheus_client	—	kept; custom collector
qtpy + PySide6	Qt.py	kept (the project's Qt abstraction layer)

GPU acceleration. The workload is I/O bound (HTTP to embedded meters, small appends); the only numeric kernels are min/max decimation and array concatenation on at most tens of thousands of values per poll, which take microseconds in NumPy. A GPU path would add a dependency without a measurable benefit, so none was added.

Python 3.12. The interpreter's own improvements apply without code changes, e.g. inlined comprehensions (PEP 709) [10]; the code avoids the APIs deprecated in 3.12.

13 Known limitations and recommendations

- The Windows memory release was verified for binding, behaviour and error handling on Windows Python under Wine; the Task Manager drop itself follows from Microsoft's documented semantics and was not measured on a physical Windows machine for this release. Commit charge can stay above the working set when the heap is fragmented (it is re-used). On Windows 7 `HeapOptimizeResources` is not available (logged at DEBUG level); the working-set trim still works.
- The working-set trim makes pages still in use fault back in once (milliseconds). Setting `MEM_TRIM_WORKING_SET` to 0 leaves the working set to Windows.
- FITS and XLSX are rewrite formats; their cost grows with file size until rollover. Prefer CSV and `.vszh5` for long runs.
- FITS files written by 1.5.x with FITS enabled in the GUI may already contain mixed rows; start a new file.
- The local-time axis is ambiguous during the daylight-saving fall-back hour; `EPOCH_UTC` (FITS) and `VSZH5_TIME_AXIS = "utc"` avoid it.
- The interactive plot window's toolbar emits a matplotlib DeprecationWarning with PySide6 6.12 (third-party; harmless).

References

[1] The Qt Company, "QTabWidget Class," *Qt 6 Documentation*. [Online]. Available: https://doc.qt.io/qt-6/qtabwidget.html (accessed Oct. 26, 2026).

[2] The Qt Company, "QPlainTextEdit Class," *Qt 6 Documentation*. [Online]. Available: https://doc.qt.io/qt-6/qplaintextedit.html (accessed Oct. 26, 2026).

[3] M. Kerrisk *et al.*, "malloc_trim(3)," *Linux man-pages*. [Online]. Available: https://man7.org/linux/man-pages/man3/malloc_trim.3.html (accessed Oct. 26, 2026).

[4] h5py developers, "Datasets," *h5py documentation*. [Online]. Available: https://docs.h5py.org/en/stable/high/dataset.html (accessed Oct. 26, 2026).

[5] J. Sanders *et al.*, "Veusz 4.2.1 source code," GitHub. [Online]. Available: https://github.com/veusz/veusz (accessed Oct. 26, 2026).

[6] Prometheus Authors, "Writing exporters," *Prometheus documentation*. [Online]. Available: https://prometheus.io/docs/instrumenting/writing_exporters/ (accessed Oct. 26, 2026).

[7] Prometheus Authors, "Querying basics: Staleness," *Prometheus documentation*. [Online]. Available: https://prometheus.io/docs/prometheus/latest/querying/basics/ (accessed Oct. 26, 2026).

[8] Prometheus Authors, "Custom Collectors," *prometheus_client documentation*. [Online]. Available: https://prometheus.github.io/client_python/collector/custom/ (accessed Oct. 26, 2026).

[9] Python Software Foundation, "datetime — Basic date and time types," *Python 3 documentation*. [Online]. Available: https://docs.python.org/3/library/datetime.html (accessed Oct. 26, 2026).

[10] Python Software Foundation, "What's New In Python 3.12," *Python 3 documentation*. [Online]. Available: https://docs.python.org/3/whatsnew/3.12.html (accessed Oct. 26, 2026).

[11] openpyxl developers, "Optimised Modes," *openpyxl documentation*. [Online]. Available: https://openpyxl.readthedocs.io/en/stable/optimized.html (accessed Oct. 26, 2026).

[12] Microsoft, "Excel specifications and limits," *Microsoft Support*. [Online]. Available: https://support.microsoft.com/en-us/excel/excel-specifications-and-limits (accessed Oct. 26, 2026).

[13] Microsoft, "HeapSetInformation function (heapapi.h)," *Microsoft Learn*. [Online]. Available: https://learn.microsoft.com/en-us/windows/win32/api/heapapi/nf-heapapi-heapsetinformation (accessed Oct. 26, 2026).

[14] Microsoft, "EmptyWorkingSet function (psapi.h)," *Microsoft Learn*. [Online]. Available: https://learn.microsoft.com/en-us/windows/win32/api/psapi/nf-psapi-emptyworkingset (accessed Oct. 26, 2026).

[15] Microsoft, "HeapCompact function (heapapi.h)," *Microsoft Learn*. [Online]. Available: https://learn.microsoft.com/en-us/windows/win32/api/heapapi/nf-heapapi-heapcompact (accessed Oct. 26, 2026).

[16] ReactOS project, "heapmin.cpp (Microsoft Universal CRT source)," *ReactOS Doxygen*. [Online]. Available: https://doxygen.reactos.org/d1/ddd/heapmin_8cpp_source.html (accessed Oct. 26, 2026).

[17] Mozilla, "Bug 1553296: Decommit pages in the Windows system heap upon memory-pressure event," gecko-dev commit 0ef2cb2. [Online]. Available: https://source-hub.etos-pro.ru/mozilla/gecko-dev/commit/0ef2cb2e18803ecbcc6419f337e151144c06cefa (accessed Oct. 26, 2026).

[18] Python Software Foundation, "Lib/concurrent/futures/_base.py," CPython 3.12 source. [Online]. Available: https://github.com/python/cpython/blob/3.12/Lib/concurrent/futures/_base.py (accessed Oct. 26, 2026).

[19] Python Software Foundation, "Objects/obmalloc.c," CPython 3.12 source. [Online]. Available: https://github.com/python/cpython/blob/3.12/Objects/obmalloc.c (accessed Oct. 26, 2026).

[20] WineHQ, "Wine 9.0," Ubuntu 24.04 package `wine64` 9.0~repack-4build3. [Online]. Available: https://www.winehq.org/ (accessed Oct. 26, 2026).

[21] Microsoft, "CreateFileW function (fileapi.h)," *Microsoft Learn*. [Online]. Available: https://learn.microsoft.com/en-us/windows/win32/api/fileapi/nf-fileapi-createfilew (accessed Oct. 26, 2026).

[22] Microsoft, "GenerateConsoleCtrlEvent function," *Microsoft Learn*. [Online]. Available: https://learn.microsoft.com/en-us/windows/console/generateconsolectrlevent (accessed Oct. 26, 2026).

[23] Python Software Foundation, "subprocess — Subprocess management," *Python 3 documentation*. [Online]. Available: https://docs.python.org/3/library/subprocess.html (accessed Oct. 26, 2026).

[24] IAU FITS Working Group, "Definition of the Flexible Image Transport System (FITS), Version 4.0," 2018. [Online]. Available: https://fits.gsfc.nasa.gov/fits_standard.html (accessed Oct. 26, 2026).

[25] Microsoft, "Exceptions (C/C++) — delay load exception codes," *Microsoft Learn*. [Online]. Available: https://learn.microsoft.com/en-us/cpp/build/reference/exceptions-c-cpp (accessed Oct. 27, 2026).

[26] Python Software Foundation, "faulthandler — Dump the Python traceback," *Python 3 documentation*. [Online]. Available: https://docs.python.org/3/library/faulthandler.html (accessed Oct. 27, 2026).

[27] Anaconda, Inc., "conda-forge/mkl — Files," *anaconda.org*. [Online]. Available: https://anaconda.org/conda-forge/mkl/files (accessed Oct. 27, 2026).

[28] conda-forge, "Removing broken packages," *conda-forge documentation*. [Online]. Available: https://conda-forge.org/docs/how-to/emergencies/remove-broken-packages/ (accessed Oct. 27, 2026).

A Distribution contents

Path	Content
`*.py` (repository root)	monitor, writer, exporter, caller, examples, stop helper
`tests/`	meter emulator, offline, memory-release, file-lock and exporter tests, GUI and headless soaks, Windows memory check, test runner
`windows/`	Windows test kit 1.1.0 (scripts, pinned specs with OpenBLAS, `START_HERE`)
`docs/`	this manual (LuaLaTeX source and PDF), figures
`requirements*.txt`, `environment*.yml`	dependencies (3.12 primary, 3.8+, 3.7)
`install*.sh`, `*.service`, wrapper	deployment kit
`patch/`	`git format-patch` series against `main` (7a9800b)