Deployment Document — LavaRápido Vehicular

> Vehicle wash management system · ADSO training project (SENA) Software implementation procedure on the production server.

Table of Contents

1. General Information and Version Control
2. Scope, Topology and Architecture
3. Prerequisites and Preparation (Pre-deployment)
4. Step-by-Step Deployment Procedure (Runbook)
5. Verification, Testing and Evidence Plan (Smoke Tests)

---

1. General Information and Version Control

1.1 Deployment Fact Sheet

1.1.1 System identification and version (Release Tag)

Field	Value
System	LavaRápido Vehicular — bookings, payments and operations management for a car wash
Components	6 backend microservices, API Gateway, web application, Android mobile app
Version (Release Tag)	`v1.0.0` *(pending: create the tag when `develop` is merged into `main`)*
Deployed branch	`develop` (in every repository)
Mobile app version	versionCode **2** (APK) + OTA update "Tapping the new-version notice opens the download"
Repositories	`lavarapido-infra`, `lavarapido-api-gateway`, `lavarapido-security-service`, `lavarapido-customer-service`, `lavarapido-booking-service`, `lavarapido-operation-service`, `lavarapido-notification-service`, `lavarapido-payment-service`, `Front-end-proyecto-web`, `LavadoVehicular-Movil`
Public address	https://lavarapidovehicular.northcentralus.cloudapp.azure.com

1.1.2 Scheduled date, time and maintenance window

Field	Value
Initial deployment date	October 16, 2026
Maintenance window	02:30 – 05:30 (Colombia time, UTC-5)
Actual duration	~2 h 30 min (provisioning, image builds, HTTPS setup and testing)
User downtime	Not applicable: first deployment (no users in production yet)

Field	Value
Window for future updates	Outside the car wash's business hours (before 07:00 or after 18:00)

1.1.3 Target environment (VPS / Staging / Production)

Field	Value
Environment	**Academic production** (also used as staging for the team's tests)
Provider	Microsoft Azure (*Azure for Students* subscription)
Type	Linux virtual machine (IaaS), equivalent to a VPS
Region	North Central US
Alternate environment	Hostinger KVM 2 VPS (purchased, pending payment activation)

1.1.4 Roles and responsibilities matrix (DevOps, Tech Lead, QA, DBA)

> Responsibilities according to the services each member maintains on GitHub. **To be confirmed with the team.**

Role	Owner	Deployment responsibilities
DevOps	Brayan Cabrera	Server, Docker Compose, Caddy/HTTPS, deployment and update scripts
Tech Lead	Brayan Cabrera	Release approval, change review, team coordination
QA	*(to be assigned)*	Smoke tests and functional validation per role (client, operator, administrator)
DBA	*(to be assigned)*	Migrations, backups and database verification
booking-service and customer-service owner	Camilo Guilombo	Changes and verification of their services
payment-service and mobile app owner	Merari Urbano Quintero	Changes and verification of payments and the app

1.2 Document Version History

Version	Date	Author	Description
1.0	2026-10-16	Brayan Cabrera	Initial version: deployment on Azure
1.1	2026-10-16	Brayan Cabrera	Portainer CE installed, real evidence (5.4) and correction of Liquibase schemas and tables

1.3 Change Summary (Release Notes)

1.3.1 New features

Platform and deployment

- Full deployment with Docker Compose and a production file (`docker-compose.prod.yml`).
- Automatic HTTPS with Caddy and a Let's Encrypt certificate (automatic renewal).
- Creation of the first administrator when installing on an empty database (`ADMIN_EMAIL` / `ADMIN_PASSWORD`).

- Server installation script (`setup-server.sh`) and one-step update script (`update-server.sh`).
- Android app download from the web (button and QR code) at the fixed address `/app/LavaRapidoVehicular.apk`.

Notifications

- Push notifications in the mobile app (Expo + Firebase) implemented with the Command pattern.
- Delivery through channels (push and email) with failure isolation.
- Notices in the account's language (Spanish, English, French and Portuguese).
- Notice to administrators about upcoming bookings without an operator.
- New app version notice by push and in the inbox.
- The web bell refreshes by itself and shows a floating notice with new notifications.

Bookings and operations

- Automatic operator assignment when a booking is confirmed (RF-008).
- The client can choose the operator among the available ones (RF-010).
- The operator can only start the service from 15 minutes before the booking.
- Vehicle inspection report with phases, findings and photos, shared with the client.
- Daily summary and operator team metrics for the administrator.

Payments and accounts

- Payment history sorted and filterable by date and service (RF-015/016).
- Account lockout for 15 minutes after 5 failed login attempts (RF-004b).
- Business data editable by the administrator and profile address stored in the backend.

Mobile app

- New version notice and over-the-internet updates (EAS Update) without reinstalling.
- Icon with the project logo and the name "LavaRapidoVehicular".

1.3.2 Bug fixes

- An approved payment was shown as "under verification" on the payments screen (web and mobile).
- The deployed web received 403 on every call because of the services' CORS configuration.
- security-service did not start when an administrator already existed (query outside a transaction).
- The app's operator list did not show a newly created operator until logging out.
- A late 401 after logging out showed the "session expired" notice.
- The new APK announcement could not read the inter-service key because of file permissions.
- Pending reminders kept being sent after the service was started or finished.
- No operator is assigned to bookings whose time has already passed, and cancelled bookings are no longer listed as pending.
- The web requested a non-existent `favicon.ico` (404 error in the console) and used deprecated translation options (console warning).

1.3.3 Infrastructure and dependency changes

Change	Detail
Docker images	Java: `eclipse-temurin:21-jdk` (build) and `21-jre` (runtime) · .NET: `dotnet/sdk:8.0` and `aspnet:8.0` · Web: `node:22-alpine` and `nginx:1.27-alpine`

Change	Detail
Infrastructure services	`mcr.microsoft.com/mssql/server:2022-latest` (Express), `rabbitmq:4-management`, `caddy:2-alpine`, `liquibase/liquibase:4.29`
New migrations	032 (business data), 033 (inspection report), 034 (login lockout), 035 (address), 036 (registration date), 037 (operator profile), 038 (new-version notice type)
Web dependencies	`qrcode` 1.5.4
Mobile dependencies	`expo-notifications`, `expo-device`, `expo-build-properties`, `expo-updates`, `expo-application`
External services	Expo Push + Firebase Cloud Messaging (push), Gmail SMTP (email), EAS (app builds and updates)

1.3.4 Breaking changes

- **New mandatory variables** on the server. Without them, Docker Compose does not start:
  - `INTERNAL_API_KEY`, `PUBLIC_URL`, `RABBITMQ_USERNAME` and `RABBITMQ_PASSWORD`;
  - `RABBITMQ_*` cannot be `guest/guest`.
- **First administrator:** the demo accounts (`admin@gmail.com`, etc.) **only exist in development**. In production the administrator is created with `ADMIN_EMAIL` / `ADMIN_PASSWORD`.
- **Mobile app:** the Android package changed to `com.vehiclecarwash.app`. Previous versions must be uninstalled once; later ones install on top.
- **CORS:** each service only accepts the origin defined in `PUBLIC_URL`.

---

2. Scope, Topology and Architecture

2.1 Components and Artifacts in Scope

2.1.1 Administration panel (Portainer CE)

> **Status: installed on 2026-10-16.** Panel to view the containers' status, logs and resource usage and restart them. Deployment and updates are still done with the scripts (section 4.3).

Artifact	Image	Access
Portainer CE	`portainer/portainer-ce:2.21.5` (~11 MB of RAM)	Only through an SSH tunnel (`https://localhost:9443`); listens on `127.0.0.1`, not exposed to the internet
Environment	`local` (socket `/var/run/docker.sock`)	Stack `lavarapido` visible as *Compose · Limited* (created outside Portainer)

2.1.2 Web Frontend Layer (SPA / Nginx Web Server)

Artifact	Technology	Image / container
Web application	**Angular 21** (SPA), i18n in 4 languages	`lavarapido/web:local` → `lavarapido-web`
Web server	nginx 1.27: serves the build and forwards `/api` to the gateway	inside `lavarapido-web`

Artifact	Technology	Image / container
Reverse proxy and HTTPS	Caddy 2 (Let's Encrypt)	`lavarapido-caddy`
Android mobile app	Expo / React Native, APK built with EAS	Served at `/app/LavaRapidoVehicular.apk`

2.1.3 Backend API Layer (Java Spring Boot / C# .NET Core)


Service	Technology	Internal port	Responsibility
api-gateway	Spring Cloud Gateway (Java 21)	8080	Single entry point for `/api/v1`
security-service	Spring Boot (Java 21)	3001	Accounts, login, JWT, roles, preferences
customer-service	Spring Boot (Java 21)	3002	Clients and vehicles
booking-service	Spring Boot (Java 21)	3003	Catalog, schedule, bookings
operations-service	Spring Boot (Java 21)	3004	Operators, assignment, execution, ratings, inspection
payment-service	ASP.NET Core 8 (C#)	3005	Payments, receipts, loyalty and promotions
notification-service	Spring Boot (Java 21)	3006	Inbox, email, push, reminders
rabbitmq	RabbitMQ 4	5672	Events between services (exchange `carwash.events`)

2.1.4 Persistence Layer (SQL Server)

Artifact	Detail
Engine	**Microsoft SQL Server 2022, Express edition** (container `lavarapido-sqlserver`)
Database	`LavaRapido`: 9 schemas and 59 tables — `security` (11), `customer` (3), `booking` (10), `catalog` (3), `execution` (11), `notification` (6), `payment` (7), `promotion` (5), `audit` (1)
Migrations	**Liquibase**: the Java services apply them on startup; payment-service applies them with the `payment-migrate` container. Each service keeps its history in `dbo.DATABASECHANGELOG_<SERVICE>`
Persistent volumes	`sqlserver-data` (database), `rabbitmq-data` (queues), `caddy-data` (certificates)

2.2 Network and Infrastructure Architecture Diagram

2.2.1 VPS server topology



2.2.2 Internal container network (Docker Bridge Network)

- All containers are on the bridge network **`lavarapido_default`**, created by Docker Compose.
- They call each other by **service name**: `sqlserver`, `rabbitmq`, `security-service`, `api-gateway`, `web`, etc. Docker's internal DNS is `127.0.0.11`.
- The `/internal/**` routes (calls between services) are protected with the `X-Internal-Key` header (`INTERNAL_API_KEY`). **The gateway does not publish them.**
- No port of the internal network is published on the machine, except Caddy's.

2.2.3 Routing and Reverse Proxy with TLS/HTTPS certificates

Public route	Destination	Notes
`https://<domain>/api/*`	`api-gateway:8080`	REST API v1 for the web and the app
`https://<domain>/app/*`	`deploy/downloads` folder	APK and `version.json` (no cache)
`https://<domain>/*`	`web:80`	Angular SPA (routes → `index.html`)
`http://<domain>/*`	308 redirect to HTTPS	Automatic (Caddy)

- **Certificate:** Let's Encrypt, issued and renewed automatically by Caddy (expires on 2027-01-14 and is renewed before). It is stored in the `caddy-data` volume.
- **Domain:** Azure DNS label on the public IP: `lavarapidovehicular.northcentralus.cloudapp.azure.com`.
- **Configuration:** `lavarapido-infra/deploy/Caddyfile`.

2.3 Environments, IP Addressing and Ports Matrix

Environment	Host	IP / URL	Use
Development	Each member's PC	`localhost` (web 4200, mobile 8081, gateway 8080)	Programming and local testing (Mailpit catches the emails)
Academic production	Azure VM `vehiclecarwash-vm`	Static IP `64.236.160.129` · https://lavarapidovehicular.northcentralus.cloudapp.azure.com	Presentation, team testing, installed app
Alternate production (pending)	Hostinger KVM 2 VPS	To be assigned	Migration once the payment is activated

Port	Service	Exposed to the internet?
22	SSH (key only)	Yes (administration)
80 / 443	Caddy	Yes
8080	api-gateway	No (internal network only)
3001–3006	Microservices	No
1433	SQL Server	No
5672 / 15672	RabbitMQ / panel	No
9443	Portainer CE	No (only `127.0.0.1`, through an SSH tunnel)

---

3. Prerequisites and Preparation (Pre-deployment)

3.1 Operating System and VPS Prerequisites Checklist

3.1.1 Available hardware resources (CPU, RAM, disk)

Resource	Minimum required	Available (Azure B2as_v2)	Measured in operation	✓
CPU	2 x86-64 vCPU (SQL Server does not run on ARM)	2 AMD x64 vCPU	Peaks only while building images	✅
RAM	8 GB	7.7 GB + 4 GB of swap	**3.3 GB** used with the 11 containers	✅
Disk	30 GB	64 GB standard SSD	~8 GB (system, images and data)	✅
Operating system	Ubuntu 24.04 or 26.04 LTS	Ubuntu 24.04.4 LTS	—	✅
Network	Ports 22, 80 and 443 open	Azure security group	Verified from the internet	✅

3.1.2 Docker engine status and local socket

```
docker --version            # Docker version 29.x
docker compose version      # Docker Compose v5.x
sudo systemctl is-enabled docker   # enabled  → starts with the machine
sudo systemctl is-active docker    # active
ls -l /var/run/docker.sock         # local engine socket
```

`deploy/setup-server.sh` installs Docker (official `get.docker.com` script) if missing, enables it on boot and creates 4 GB of swap.

3.2 Backup Strategy and Execution

> **Status:** procedure defined; **periodic automation is pending**. It is run manually before every deployment that includes migrations.

3.2.1 Logical database backup (Dump / Snapshot)

```
cd ~/lavarapido/lavarapido-infra
P=$(grep '^DB_PASSWORD=' .env.production | cut -d= -f2-)
sudo docker exec -e SQLCMDPASSWORD="$P" lavarapido-sqlserver /opt/mssql-tools18/bin/sqlcmd \
  -S localhost -U sa -C -Q "BACKUP DATABASE [LavaRapido] TO DISK = N'/var/opt/mssql/backup/LavaRapido_$(date
+%F).bak' WITH COMPRESSION, INIT"
sudo docker cp lavarapido-sqlserver:/var/opt/mssql/backup/LavaRapido_$(date +%F).bak ~/backups/
```

Infrastructure-level complement: **disk snapshot** of the VM from the Azure portal (Disks → Create snapshot).

3.2.2 Backup of Docker persistent volumes

```
mkdir -p ~/backups
for v in lavarapido_sqlserver-data lavarapido_rabbitmq-data lavarapido_caddy-data; do
  sudo docker run --rm -v "$v":/data:ro -v ~/backups:/backup alpine \
    tar czf "/backup/${v}_$(date +%F).tar.gz" -C /data .
done
```

> For a consistent backup of `sqlserver-data`, the `BACKUP DATABASE` from 3.2.1 is preferred, because it can be done while the database is running.

3.2.3 Backup of Stack configurations and previous variables

```
cd ~/lavarapido/lavarapido-infra
cp .env.production ~/backups/env.production_$(date +%F)       # contains secrets: chmod 600
chmod 600 ~/backups/env.production_*
git -C ~/lavarapido/lavarapido-infra rev-parse HEAD > ~/backups/infra-commit_$(date +%F).txt
```

The stack configuration (`docker-compose.yml`, `docker-compose.prod.yml`, `deploy/Caddyfile`) is versioned on GitHub (`lavarapido-infra`). To go back, a `git checkout <commit>` and a new `up -d` are enough.

3.3 Environment Variables and Secrets Management

- Secrets live **only** in `~/lavarapido/lavarapido-infra/.env.production` (permissions `600`), which is in `.gitignore`.
- The template without values is `.env.production.example`.
- **Key generation:** the keys were generated **on the server** with `openssl rand -base64 48` and were never copied or displayed.
- **First administrator:** the owner typed its password directly on the server (`set-admin-password.sh`).

3.3.1 Database connection parameters

Variable	Description
`DB_PASSWORD`	`sa` password (8+ characters, uppercase, lowercase, number and symbol)
`DB_NAME`	`LavaRapido`
`DB_USERNAME`	`sa` *(pending improvement: a user with limited permissions)*
`DB_URL` (compose)	`jdbc:sqlserver://sqlserver:1433;databaseName=LavaRapido;encrypt=true;trustServerCertificate=true`

3.3.2 Token signing keys (JWT Secret Keys)

Variable	Description
`JWT_SECRET`	HS256 key shared by the services that validate tokens (≥ 32 bytes). Tokens last **1 hour**
`INTERNAL_API_KEY`	Key for the `/internal/**` routes between services (`X-Internal-Key` header)
`RABBITMQ_USERNAME` / `RABBITMQ_PASSWORD`	Dedicated RabbitMQ user (not `guest`)
`MAIL_USERNAME` / `MAIL_PASSWORD` / `MAIL_FROM`	Gmail account with an app password
`ADMIN_EMAIL` / `ADMIN_PASSWORD`	First administrator (only used if the database has none)
`PUBLIC_URL` / `SITE_ADDRESS`	Public address (CORS, email links) and Caddy domain
`PUSH_ENABLED` / `MESSAGING_ENABLED`	`true`: push with Expo and events with RabbitMQ

3.3.3 Memory and runtime limits (JVM -Xmx, ASPNETCORE_ENVIRONMENT)

Container	Limit (`mem_limit`)	Runtime
5 Java services + gateway	512 MB each	`java -XX:MaxRAMPercentage=75` → maximum heap ≈ 384 MB · `prod` profile (no Swagger)
payment-service	384 MB	`ASPNETCORE_ENVIRONMENT=Production`
SQL Server	`MSSQL_MEMORY_LIMIT_MB=1536`	`MSSQL_PID=Express`
web / caddy	64 MB each	nginx / Caddy
All	`restart: unless-stopped`	They restart by themselves on failure and when the machine boots

3.4 Communication Protocol and Maintenance Window

1. **Advance notice (24 h):** the DevOps informs the team through the project group about the date, the window and the changes (release notes).
2. **Freeze:** no changes are pushed to the branch being deployed during the window.
3. **Start:** "deployment started" is announced and the backup is taken (section 3.2).

4. **Execution:** runbook in section 4.
5. **Verification:** smoke tests in section 5. QA confirms each role.
6. **Closing:** "deployment finished" is announced with the version and the evidence. If it fails, **rollback**: `git checkout` of the previous commit in `lavarapido-infra` and in the services, `update-server.sh`, and if the migration damaged data, restore the `.bak`.
7. **Standard window:** outside the car wash's business hours (before 07:00 or after 18:00, Colombia time).

---

4. Step-by-Step Deployment Procedure (Runbook)

4.1 Verification and Access to the Base Platform (Portainer CE)

Server access:

```
ssh -i ~/.ssh/lavarapido_azure azureuser@64.236.160.129
```

Portainer CE installation *(done on 2026-10-16; listens only inside the server)*:

```
sudo docker volume create portainer_data
sudo docker run -d --name portainer --restart unless-stopped \
  -p 127.0.0.1:9443:9443 \
  -v /var/run/docker.sock:/var/run/docker.sock \
  -v portainer_data:/data portainer/portainer-ce:2.21.5
```

Access from the administrator's PC (SSH tunnel, without opening ports):

```
ssh -i ~/.ssh/lavarapido_azure -L 9443:localhost:9443 azureuser@64.236.160.129
# then open https://localhost:9443 → user "admin"
```

- **Password of the `admin` user:** it was generated during installation and is on the server, in `~/portainer-admin-password` (permissions `600`). It is read with `cat ~/portainer-admin-password` and can be changed from Portainer (*My account*).
- **`local` environment:** registered on the Docker socket. `lavarapido` appears under *Containers* and *Stacks*.

4.2 Database Deployment and Migration

4.2.1 Running DDL/DML scripts or migration tools (Liquibase)

Migrations are **automatic**:

1. The `db-init` container creates the `LavaRapido` database if it does not exist.
2. The `payment-migrate` container (Liquibase 4.29) applies the payment-service changelogs (`db/changelog/db.changelog-master.yaml`) and exits.
3. Each Java service applies its own changelogs on startup. Numbering is global: 001–038 plus the 1xx catalog seeds.
4. Hibernate only validates that the model matches the tables (`ddl-auto: validate`); it never alters tables.

Production **does not load test data**: only catalogs (roles, services, statuses, schedule and business data).

4.2.2 Verification of schema, index and user integrity

```
P=$(grep '^DB_PASSWORD=' .env.production | cut -d= -f2-)
q(){ sudo docker exec -e SQLCMDPASSWORD="$P" lavarapido-sqlserver /opt/mssql-tools18/bin/sqlcmd \
     -S localhost -U sa -C -d LavaRapido -Q "SET NOCOUNT ON; $1"; }
q "SELECT s.name AS esquema, COUNT(t.name) AS tablas FROM sys.schemas s JOIN sys.tables t ON t.schema_id=s.s
chema_id GROUP BY s.name"
for s in SECURITY CUSTOMER BOOKING OPERATIONS NOTIFICATION PAYMENT; do
  q "SELECT '$s' AS servicio, COUNT(*) AS changesets, SUM(CASE WHEN EXECTYPE IN ('EXECUTED','MARK_RAN') THEN
1 ELSE 0 END) AS ok FROM DATABASECHANGELOG_$s"
done
q "SELECT COUNT(*) AS indices FROM sys.indexes WHERE object_id IN (SELECT object_id FROM sys.tables)"
q "SELECT u.username, r.code FROM security.app_user u JOIN security.user_role ur ON ur.user_id=u.user_id JOI
N security.role r ON r.role_id=ur.role_id WHERE r.code='ADMIN'"
```

Expected result:

- the 9 schemas with their tables;
- in each service, `ok` equal to `changesets` (2026-10-16: 143 of 143);
- the initial administrator created (security log: `First administrator created`).

4.3 Application Stack Deployment and Orchestration

4.3.1 Loading the docker-compose.yml file in Portainer

The stack is defined with two files versioned in `lavarapido-infra`:

- **`docker-compose.yml`:** the base, the same as in development.
- **`docker-compose.prod.yml`:** overrides the production settings: no internal ports, `prod` profile, memory limits, Caddy, web and CORS.

Current deployment (CLI):

```
# 1. Download the 9 repositories (and prepare Docker and swap the first time)
curl -fsSL https://raw.githubusercontent.com/BrayanCABRERA123/lavarapido-infra/develop/deploy/setup-server.s
h -o setup-server.sh
bash setup-server.sh
```

With Portainer: Stacks → Add stack → *Repository*. The images are built from 9 sibling repositories, so the recommended flow is:

1. build the images with the CLI (step 4.3.3);
2. use Portainer to **view, restart, check logs and resource usage** of the containers of the `lavarapido` stack, which appears as a "limited" stack because it was created outside Portainer.

4.3.2 Injecting the Stack's environment variables

```
cd ~/lavarapido/lavarapido-infra
cp .env.production.example .env.production
chmod 600 .env.production
nano .env.production        # fill in the values from section 3.3 (keys generated with openssl)
```

In Portainer, the same variables are loaded in *Environment variables → Load variables from .env file*.

4.3.3 Service deployment and container image updates

First deployment:

```
cd ~/lavarapido/lavarapido-infra
sudo docker compose -f docker-compose.yml -f docker-compose.prod.yml \
  --env-file .env.production --profile app up -d --build
```

Later updates: first push the changes to GitHub and then:

```
bash ~/lavarapido/lavarapido-infra/deploy/update-server.sh                # everything
bash ~/lavarapido/lavarapido-infra/deploy/update-server.sh web            # only the web
bash ~/lavarapido/lavarapido-infra/deploy/update-server.sh security-service notification-service
```

Publishing the mobile app, from the PC, in the app folder:

```
eas build -p android --profile preview          # new APK (native changes)
npm run publish:apk -- "what changed"           # publishes it in /app/ and notifies by push
npm run publish:update -- "what changed"        # screen-only changes: over-the-internet update
```

4.4 Routing, Domain and SSL/TLS Certificate Configuration

1. **Domain:** Azure → public IP `vehiclecarwash-vm-ip` → Configuration → *DNS name label* = `lavarapidovehicular`. The result is `lavarapidovehicular.northcentralus.cloudapp.azure.com`.
2. **Variables:** `.env.production`:

   ```
   SITE_ADDRESS=lavarapidovehicular.northcentralus.cloudapp.azure.com
   PUBLIC_URL=https://lavarapidovehicular.northcentralus.cloudapp.azure.com
   ```

3. **Apply:** `update-server.sh caddy security-service notification-service api-gateway`. Caddy requests the certificate from Let's Encrypt through HTTP-01; port 80 must be open.
4. **Verify the certificate:**

   ```
   echo | openssl s_client -connect lavarapidovehicular.northcentralus.cloudapp.azure.com:443 \
     -servername lavarapidovehicular.northcentralus.cloudapp.azure.com 2>/dev/null | openssl x509 -noout
   -issuer -enddate
   # issuer=C=US, O=Let's Encrypt · notAfter=Jan 14 2027
   ```

5. **Mobile app:** `EXPO_PUBLIC_API_URL` in `eas.json` = `https://lavarapidovehicular.northcentralus.cloudapp.azure.com/api/v1`, and the APK is built.

---

5. Verification, Testing and Evidence Plan (Smoke Tests)

5.1 Service Verification Links and Endpoints Matrix

5.1.1 Access to the administration panel (Portainer)

Link	Expected	Status
`https://localhost:9443` (through SSH tunnel)	Stack `lavarapido`: 11 containers *running/healthy* and 2 init containers in *exited (0)*	✅ (see 5.4.1)
`https://64.236.160.129:9443` (from the internet)	No connection	✅ closed

5.1.2 Public web interface (Angular SPA)

Link	Expected	Result (2026-10-16)
`https://<domain>/`	Home page with the "Download app" section	✅ 200
`https://<domain>/client`, `/admin`	Angular routes (load `index.html`)	✅ 200
`http://<domain>/`	Redirect to HTTPS	✅ 308
`https://<domain>/app/version.json`	Published app version	✅ 200 (`versionCode 2`)
`https://<domain>/app/LavaRapidoVehicular.apk`	APK download (`application/vnd.android.package-archive`)	✅ 200

5.1.3 Backend health endpoints (/actuator/health)

The health endpoints **are not published to the internet**: `/actuator` is not under `/api`. They are checked inside the server:

```
for s in security-service:3001 customer-service:3002 booking-service:3003 operations-service:3004 notificati
on-service:3006 api-gateway:8080; do
  sudo docker run --rm --network lavarapido_default curlimages/curl:8.10.1 -s "http://$s/actuator/health"; e
cho "  ← $s"
done
sudo docker compose -f docker-compose.yml -f docker-compose.prod.yml --env-file .env.production --profile ap
p ps
```

Expected: `{"status":"UP"}` in each Java service, and every container `Up`. `db-init` and `payment-migrate` must end in `Exited (0)`.

5.1.4 Interactive API documentation (Swagger UI / OpenAPI)

- **In production it is disabled on purpose** (`prod` profile): the API structure is not exposed.
- It is consulted in **development**, with each service in the `dev` profile: `http://localhost:3001/swagger-ui.html`, and likewise for each port.
- The OpenAPI specification is versioned in `vehicle-w-docs`.

5.1.5 Direct TCP connectivity to the database engine

SQL Server **does not have port 1433 published**. Connectivity is tested from the internal network:

```
P=$(grep '^DB_PASSWORD=' .env.production | cut -d= -f2-)
sudo docker exec -e SQLCMDPASSWORD="$P" lavarapido-sqlserver /opt/mssql-tools18/bin/sqlcmd \
  -S localhost -U sa -C -Q "SELECT @@VERSION, DB_NAME(DB_ID('LavaRapido'))"
nc -zv 64.236.160.129 1433    # from outside: must FAIL (port closed)
```

5.2 Functional Smoke Tests

5.2.1 Authentication flow and token issuance

Test	Expected	Result
`POST /api/v1/auth/login` with an empty body	400 (validation)	✅ 400
Login with invalid credentials	401 `INVALID_CREDENTIALS`	✅ 401
Login of the initial administrator from the web	JWT token with the `ADMIN` role and access to `/admin`	✅
Request from a foreign origin (CORS)	403	✅ 403
Internal route without key (`/internal/...`)	401; unreachable from the internet	✅ 401 / 405

5.2.2 Data read and query tests

Test	Result
`GET /api/v1/catalog/services` (public catalog)	✅ 200 with the services
`GET /api/v1/schedule/business-hours`	✅ 200
`GET /api/v1/establishment`	✅ 200

5.2.3 Write and transactional persistence tests

Automated end-to-end test: `lavarapido-infra/e2e/full-flow.test.js` (`npm run flow`). It goes through the three roles via the gateway:

#	Step	Result
1	The client books choosing an operator → automatic assignment → notices	✅
2	The client reports the payment with a receipt → it stays under review	✅
3	The administrator approves the payment → the client sees it approved and earns points	✅
4	The operator starts and finishes the service → notices to the client	✅
5	The client rates → the operator sees the rating	✅

- **When it ends:** the test deletes everything it created and restores the client's points.
- **Also verified in production:**
  - real email delivery (recovery code through Gmail);
  - real push to the phone;
  - the push switch (off → inbox only; on → push).

5.3 Log Inspection and Resource Monitoring

5.3.1 Review of startup traces without critical exceptions

```
C="sudo docker compose -f docker-compose.yml -f docker-compose.prod.yml --env-file .env.production --profile
app"
$C logs --since 10m | grep -iE "ERROR|Exception|APPLICATION FAILED" | head
for s in security-service customer-service booking-service operations-service notification-service api-gatew
ay; do
  sudo docker logs lavarapido-$s 2>&1 | grep -oE "Started [A-Za-z]+ in [0-9.]+ seconds" | tail -1
done
sudo docker logs lavarapido-payment-service 2>&1 | grep "Now listening"
```

Expected:

- each service with its `Started ... in N seconds`;
- payment with `Now listening on: http://0.0.0.0:3005`;
- no `APPLICATION FAILED TO START`.

5.3.2 CPU and RAM usage monitoring in containers

```
sudo docker stats --no-stream --format "table {{.Name}}\t{{.CPUPerc}}\t{{.MemUsage}}"
free -h
```


Measurement on 2026-10-16, with the system idle:

Container	Memory
security-service	341 MB / 512 MB
notification-service	319 MB / 512 MB
operations-service	313 MB / 512 MB
booking-service	304 MB / 512 MB
customer-service	300 MB / 512 MB
api-gateway	157 MB / 512 MB
payment-service	62 MB / 384 MB
sqlserver	644 MB
rabbitmq	124 MB
web / caddy	6 MB / 12 MB
Machine total	**3.3 GB of 7.7 GB · swap unused**


5.4 Visual Evidence Record (Screenshots)

> Screenshots taken on 2026-10-16 on the production server, after updating it to the latest version of `develop`. The terminal ones show the real output of the commands. The screenshots keep the original interface language (Spanish).


5.4.1 Screenshot of the Portainer panel with containers in Running state



The 11 services in running */* healthy*; `db-init` and `payment-migrate` end in* exited - code 0 *because they run only once (create the database and apply the payment migrations).*




5.4.2 Screenshot of the Backend services log viewer




Each Java service shows Started … in N seconds *, payment* Now listening on :3005 *, and security confirms that the administrator already exists. There are 0 error traces in the last 15 minutes.*

5.4.3 Screenshot of the HTTP 200 response of the Health Checks




`/actuator/health` responds `UP` (HTTP 200) in the 6 Java services from the internal network; the web, the API and `/app/version.json` respond 200 from the internet.

5.4.4 Screenshot of the web interface with a clean DevTools console



Home page in production over HTTPS. Console: 0 errors and 0 warnings on load.

5.4.5 Screenshot of the successful migration record in the database



Latest migrations (up to 038), 143 changesets `EXECUTED` in the 6 histories and the tables per schema.

Related documents:

- `lavarapido-infra/DEPLOY.md`: short deployment and update guide.
- `lavarapido-infra/e2e/README.md`: tests between services.
- `vehicle-w-docs`: architecture (ADR), OpenAPI and events.