Software Design — Vehicle Washing Management System

Cover Page

Table 1

Document identification data

Field	Value
Project	Vehicle Washing Management System (Vehicle Washing / LavaRápido)
Deliverable	Software design documentation (section 2.5.4)
Program	Software Analysis and Development Technologist (ADSO)
Group (ficha)	3145556
Apprentices	Brayan Estiven Patiño Cabrera (project lead), Juan Camilo Guilombo Osorio (frontend lead), Merari Urbano (backend lead)
Instructor	Karol Daniela Correa
Training center	Industria
Date	October 15, 2026
Version	1.1

> *Note.* Cover data was taken from the project's Technical Manual v2.0. All design content was derived from the source code in the `Sistema Lavado Vehicular` repository (Backend, Web, and LavadoVehicular-Movil) and must be validated with the instructor.

1. Introduction and Scope

The system consists of seven backend services behind an API Gateway, a web application in Angular 21, and a mobile application in React Native (Expo 57); both clients serve three roles: customer, operator, and administrator.

This document describes the design as built: user interfaces, architectural model, design patterns, data model, and main classes. Every statement cites the file where it can be verified. Diagrams are written in Mermaid (Mermaid, n.d.) using UML notation. File paths are relative to the `Sistema Lavado Vehicular/` folder.

Table 2

System components and technology

Component	Technology	Port	Folder
API Gateway	Spring Boot 4.0.8, Spring Cloud Gateway (WebMVC), Java 21	8080	`Backend/lavarapido-api-gateway`
security-service	Spring Boot 4.0.8, Spring Security, JWT, Java 21	3001	`Backend/security-service`
customer-service	Spring Boot 4.0.8, JPA, Java 21	3002	`Backend/lavarapido-customer-service`
booking-service	Spring Boot 4.0.8, JPA, Java 21	3003	`Backend/lavarapido-booking-service`

Component	Technology	Port	Folder
operations-service	Spring Boot 4.0.8, JPA, Java 21	3004	`Backend/lavarapido-operations-service`
payment-service	ASP.NET Core 8, Entity Framework Core 8	3005	`Backend/lavarapido-payment-service`
notification-service	Spring Boot 4.0.8, Spring Mail, Java 21	3006	`Backend/lavarapido-notification-service`
Database	SQL Server 2022 (one database, one schema per service)	1433	`Backend/lavarapido-infra/docker-compose.yml`
Messaging	RabbitMQ 4 (exchange `carwash.events`)	5672	`Backend/lavarapido-infra/docker-compose.yml`
Web application	Angular 21.2.25, Angular Material, ngx-translate, Chart.js	4200	`Web`
Mobile application	React Native 0.86.3, Expo ~57, React Navigation 7, i18next	8081 (Expo)	`LavadoVehicular-Movil`

> *Note.* Versions taken from `pom.xml`, `Directory.Build.props`, and `package.json`. Official documentation: Spring (n.d.), Microsoft (n.d.-a, n.d.-b), RabbitMQ (n.d.), Liquibase (n.d.), Angular (n.d.), React Native (n.d.), and Expo (n.d.).

Out of scope: requirements (see SRS v7, `lavarapido-docs/01_INFORME_DE_ESPECIFICACION_DE_REQUISITOS`), dynamic diagrams (analysis deliverable), and costs.

2. User Interfaces

The web client has 34 routed screens and the mobile app has 30; both split the areas by role and only let each user into their own. On the web this is done by `authGuard` with `data.roles` (`Web/src/app/app.routes.ts:19-49`). On mobile, `RootNavigator` registers only the screens of the logged-in role (`LavadoVehicular-Movil/src/core/navigation/RootNavigator.tsx:63-110`).

2.1 Web Application Screen Inventory

Table 3

Web application screens (Angular)

Route	Screen	Role	Purpose	Services / endpoints consumed
`/`	Landing	Public	Presents the car wash, its services, and contact info	`GET /establishment` (business email and phone)
`/auth`	Login	Public	Authenticate with email and password	`POST /auth/login`

Route	Screen	Role	Purpose	Services / endpoints consumed
`/auth/register`	Sign-up	Public	Create a customer account	`POST /auth/register`
`/auth/forgot-password`	Password recovery (3 steps)	Public	Email → code → new password	`POST /auth/password/forgot`, `/verify`, `/reset`
`/report/:token`	Inspection report	Public	View the report shared by the admin	`GET /public/inspections/{token}` and its photos
`/client`	Customer home	CLIENT	Summary, next booking with its operator, and points	`GET /bookings/me`, `/vehicles`, `/loyalty/balance`, `/operators/my-bookings`
`/client/reserve`	Book	CLIENT	Choose vehicle, service, date, and time	`GET /catalog/services`, `/bookings/availability`, `/operators/available`; `POST /bookings`
`/client/payment`	Payments	CLIENT	Pay for a booking and upload a receipt	`GET /payment-accounts`, `/payments/me/bookings`; `POST /payments`; `/loyalty/*`
`/client/history`	History	CLIENT	Past bookings, payments, and rating	`/bookings/me`, `/payments/me`, `POST /ratings/{bookingId}`
`/client/vehicles`	My vehicles	CLIENT	Vehicle CRUD	`GET/POST/PUT/DELETE /vehicles`, `GET /vehicle-types`
`/client/notifications`	Notifications	CLIENT	Notification inbox	`/notifications/*`
`/client/profile`	Profile	CLIENT	Personal data, address, email, and password	`/users/me`, `/users/me/address`, `/users/me/password`, `/users/me/email`
`/client/configuration`	Settings	CLIENT	Theme, language, and notification channels	`/users/me/preferences`
`/admin`	Dashboard	ADMIN	Daily indicators and alerts	`GET /admin/bookings/day-summary` and booking, payment, operator, and schedule stores

Route	Screen	Role	Purpose	Services / endpoints consumed
`/admin/reservations`	Bookings	ADMIN	Create, reschedule, change status, and assign an operator	`/admin/bookings/*`, `/admin/assignments/*`
`/admin/reservations/:id/inspection`	Inspection	ADMIN	Go through the phases, record findings with photos, publish and share	`/admin/inspections/{bookingId}/**`
`/admin/payments`	Payments	ADMIN	Review, approve, reject, and refund	`/admin/payments/*`
`/admin/management`	Management	ADMIN	Users, roles and permissions, services, promotions	`/admin/users`, `/admin/roles-permissions`, `/admin/catalog/services`, `/admin/promotions`
`/admin/schedule`	Schedule and bays	ADMIN	Weekly hours, exceptions, and bays	`/admin/schedule/*`, `/admin/bays/*`
`/admin/operators`	Operators	ADMIN	Operator list, team summary, and creation	`/admin/operators`, `/admin/operators/summary`, `POST /admin/users`
`/admin/operators/:id`	Operator detail	ADMIN	Availability, absences, profile, and weekly metrics	`/admin/operators/{id}/availability`, `/absences`, `/metrics`, `/admin/operators/profiles`, `PUT /admin/operators/{id}/profile`
`/admin/operators/:id/calendar`	Operator calendar	ADMIN	Operator agenda	`/admin/assignments`
`/admin/reports`	Reports	ADMIN	Revenue and services; export PDF/Excel	Payment and booking stores (jsPDF, xlsx)
`/admin/notifications`	Notifications	ADMIN	Inbox and sending notices	`/notifications/*`, `POST /admin/notifications`
`/admin/profile`	Profile	ADMIN	Account data	`/users/me`
`/admin/settings`	Settings	ADMIN	Business data and payment methods	`/admin/payment-accounts`, `GET/PUT /admin/establishment`

Route	Screen	Role	Purpose	Services / endpoints consumed
`/operator`	Operator home	OPERATOR	Pending services and statistics	`/operator/services`, `/notifications`
`/operator/assigned-services`	Assigned services	OPERATOR	Start and finish services	`POST /operator/services/{id}/start`, `/finish`
`/operator/schedule`	Agenda	OPERATOR	Service calendar	`GET /operator/services`
`/operator/service-history`	History	OPERATOR	Completed services	`GET /operator/services`
`/operator/qualifications`	Ratings	OPERATOR	Scores and comments received	`GET /operator/ratings`
`/operator/notifications`, `/profile`, `/settings`	Shared	OPERATOR	Notices, profile, and preferences	`/notifications/*`, `/users/me/*`

> *Note.* Every API route has the `/api/v1` prefix and goes through the gateway (`Web/proxy.conf.json`). Source: `Web/src/app/core/services/*.ts` and routes in `features/*/*-routing-module.ts`.

2.2 Mobile Application Screen Inventory

The mobile app mirrors the web areas with its own React Native screens. It has no landing page, inspection, or public report.

Table 4

Mobile application screens (React Native / Expo)


Role	Screens (`src/modules/<role>/screens`)	Web equivalent
Logged out	`LoginScreen`, `RegisterScreen`, `ForgotPasswordScreen`	`/auth/*`
CLIENT	`ClientHome`, `ClientReserve`, `ClientPayment`, `ClientHistory`, `ClientVehicles`, `ClientNotifications`, `ClientProfile`, `ClientSettings`	`/client/*`
OPERATOR	`OperatorHome`, `OperatorAssigned`, `OperatorSchedule`, `OperatorHistory`, `OperatorRatings`, `OperatorNotifications`, `OperatorProfile`, `OperatorSettings`	`/operator/*`
ADMIN	`AdminDashboard`, `AdminReservations`, `AdminPayments`, `AdminManagement`, `AdminSchedule`, `AdminOperators`, `AdminOperatorCalendar`, `AdminReports`, `AdminNotifications`, `AdminProfile`, `AdminSettings`	`/admin/*`

> *Note.* If a user has several roles, the mobile app opens the most privileged one: ADMIN, then OPERATOR, then CLIENT (`RootNavigator.tsx:42-46`). The session is stored in the system keychain with `expo-secure-store` (`src/core/storage/sessionStorage.ts:15-20`).

2.3 Navigation Diagram

Figure 1

Web application navigation by role



The diagram shows web navigation; the mobile app follows the same path per role, without the landing page or inspection.

2.4 Screenshots

Screenshots were taken on October 9, 2026, with the full system running: the web client in Chrome at 1366 × 768 and the mobile app in its web build (Expo) at phone size (390 × 844). The data shown comes from the development database and the functional tests.

Figure 2

Public landing page (web)




Figure 3

Login (web)





Figure 4

Login (mobile app)


Iniciar Sesión
Ingresa a tu cuenta para reservar
Correo Electrónico
usuario@gmail.com
Contraseña
****
¿Olvidaste tu contraseña?




Figure 5

Book a wash — customer (web)




Figure 6

Payments with QR and receipt — customer (web)




Figure 7

Customer home (mobile app)


¡Hola, Prueba!
Este es tu módulo de información como cliente de AquaWash
3
Mis reservas activas
6
Mis vehículos
1
Lavados realizados
Ver
Notificaciones
Tu próximo servicio
Confirmado
Básico — Mazda CX-5 · FPW-653
10/10/2026 · 08:00 - 08:45
Express Car Wash · Calle 127 #19A-48, Bogotá,




Figure 8

Assigned services — operator (web)




Figure 9

Operator home (mobile app)


¡Hola, Operario! 👋
¡Bienvenido!
Tienes 0 servicios pendientes para hoy
Ver servicios asignados
1
Reservas Asignadas
0
En progreso
3
3
Notificaciones
5
Calificación
Servicios completados hoy



Figure 10

Dashboard — administrator (web)



Figure 11

Booking management — administrator (web)





Figure 12

User, role, service, and promotion management — administrator (web)



> *Note.* Original screenshots taken with headless Chrome. The mobile app screenshots come from its web build; on Android the UI is the same, rendered with native components.


3. Architectural Model

The system follows a microservices architecture (Newman, 2021): an API Gateway as the single entry point, six domain services with hexagonal architecture, a SQL Server database split by schema, and RabbitMQ for asynchronous events.

3.1 Container Diagram (C4 Level 2)

Figure 13

System container diagram (C4, level 2)



> *Note.* Notation based on the C4 model (Brown, n.d.). Clients talk only to the gateway; each service validates the JWT and stores data in its own schema.

The web and mobile clients only call port 8080. The gateway forwards the `Authorization` header without validating it; each service validates the JWT on its own (`Backend/lavarapido-api-gateway/src/main/resources/application.yml`, route comments, ADR-006). The service-to-service `/internal/**` routes have no gateway route and return 404 from outside.

3.2 Responsibility of Each Container

Table 5

Containers, responsibility, and owned data

Container	Responsibility	Owned schemas	Public routes (gateway)
security-service	Sign-up, JWT login with lockout after failed attempts, password recovery, profile and address, preferences, users, roles, and permissions	`security`, `audit`	`/auth/**`, `/users/**`, `/admin/users/**`, `/admin/roles-permissions/**`
customer-service	Customers, vehicles, and vehicle types	`customer`	`/vehicles/**`, `/vehicle-types/**`, `/admin/vehicles/**`
booking-service	Catalog and prices, business hours, bays, availability, bookings, day summary, and business data	`catalog`, `booking`	`/catalog/**`, `/schedule/**`, `/establishment`, `/bookings/**`, `/admin/bookings/**`, `/admin/catalog/**`, `/admin/schedule/**`, `/admin/bays/**`, `/admin/establishment`, `/operator/bookings/**`
operations-service	Operators and their profile, availability, absences, automatic and manual assignment, execution, ratings, metrics, and inspection report	`execution`	`/admin/operators/**`, `/operators/**`, `/admin/inspections/**`, `/public/inspections/**`, `/admin/assignments/**`, `/operator/services/**`, `/operator/ratings`, `/ratings/**`
payment-service (.NET)	Payments with receipts, payment accounts, promotions, and loyalty points	`payment`, `promotion`	`/payments/**`, `/payment-accounts`, `/admin/payments/**`, `/admin/payment-accounts/**`, `/admin/payment-methods`, `/admin/promotions/**`, `/loyalty/**`
notification-service	Notification inbox, email, push (Expo), scheduled reminders, and alerts for bookings without an operator, in each account's language	`notification`	`/notifications/**`, `/admin/notifications/**`

> *Note.* Source: routes in `Backend/lavarapido-api-gateway/src/main/resources/application.yml` and each service's Liquibase changelogs.

3.3 Service-to-Service Communication

There are two styles. Queries that need an immediate answer use synchronous REST; notices that something happened travel as events through RabbitMQ.

Table 6

Synchronous REST calls between services

Source	Target	Purpose	Environment variable
booking	customer	Check that the vehicle belongs to the customer	`CUSTOMER_SERVICE_URL`
customer	security	Get the `person_id` if the sign-up event did not arrive	`SECURITY_SERVICE_URL`
operations	booking	Read, start, and finish bookings with the user's token; read bookings without a user for automatic assignment and free operators (`/internal/v1/bookings`)	`BOOKING_SERVICE_URL`, `BOOKING_INTERNAL_URL`, `INTERNAL_API_KEY`
operations	security	Operator and customer names, and whether the account is still active (internal route with a shared key)	`SECURITY_SERVICE_URL`, `SECURITY_INTERNAL_URL`, `INTERNAL_API_KEY`

Source	Target	Purpose	Environment variable
payment	booking	Look up the booking and the amount due	`BOOKING_SERVICE_URL`
notification	security	Email and language of each account and administrator list (`/internal/v1/users`)	`SECURITY_SERVICE_URL`, `INTERNAL_API_KEY`

Note. Source: `Backend/lavarapido-infra/docker-compose.yml`.

Table 7

Events published on the `carwash.events` exchange

Routing key	Publisher	Consumer
`security.user_registered`	security	customer (creates the customer profile), notification (welcome)
`customer.provisioned`	customer (only written to the log)	None
`booking.confirmed`	booking	notification (notice and reminders), operations (automatic assignment, with the operator the customer chose)
`booking.cancelled`	booking	notification
`execution.operator_assigned`, `execution.service_started`, `execution.service_completed`, `execution.inspection_shared`	operations	notification
`payment.confirmed`, `payment.rejected`, `payment.refunded`, `payment.promotion_redeemed`, `payment.loyalty_points_earned`	payment	notification


Note. Source: `BookingEvent.java:17-18`, `ExecutionEvent.java:14-16`, `InspectionSharedEvent.java:15`, `PaymentIntegrationEvents.cs`, `CustomerProvisioned.java:15`, and the `ROUTING_KEYS` list in `notification-service/.../RabbitMessagingConfig.java`. notification also listens to `booking.created`, but no service publishes that key.

The notification and customer queues have their own dead-letter queue. The operations queue (`operations-service.events`, only `booking.confirmed`) does not: if automatic assignment fails, it is logged and the booking is left for the unassigned-booking alert and manual assignment (`BookingConfirmedListener.java`). notification stores the `event_id` of each event in `notification.processed_event` to ignore duplicates, because delivery is "at least once" (`DomainEventConsumerService.java:61-72`). Messaging is enabled with `MESSAGING_ENABLED`; when it is off, the Java services use a publisher that only writes to the log (`LoggingDomainEventPublisher.java:16`).

3.4 Internal Layers of Each Service (Hexagonal)

Figure 14

Layers of a service with hexagonal architecture




Hexagonal architecture separates the domain core from infrastructure through ports and adapters (Cockburn, 2005); domain modeling follows Evans (2004). The Java services use the `domain`, `application`, and `infrastructure` packages (for example, `security-service/src/main/java/com/lavarapido/security/`). payment-service applies the same idea with four .NET projects: `PaymentService.Domain`, `.Application` (with `Ports/In` and `Ports/Out`), `.Infrastructure`, and `.Api`.

3.5 Deployment

Figure 15

Deployment diagram with Docker Compose



`docker compose up -d` starts only SQL Server, Mailpit, and RabbitMQ, and the services run from the IDE. `docker compose --profile app up -d --build` also starts the seven services in containers (`Backend/lavarapido-infra/docker-compose.yml:1-6`). The Java services create their tables with Liquibase on startup; payment-service creates them with the `payment-migrate` container.

4. Design Patterns

The code applies 17 verifiable patterns: 5 architectural, 8 backend design patterns, and 4 in the clients. The code itself names some of them in its comments (Strategy, Factory, Unit of Work). Pattern names follow the catalogs of Gamma et al. (1994), Fowler (2002), and Hohpe and Woolf (2003).

Table 8

Design patterns identified

#	Pattern	Where it is used	Problem it solves
1	Microservices + API Gateway	`Backend/lavarapido-api-gateway/.../application.yml`	A single entry point for web and mobile; each domain is deployed separately
2	Hexagonal architecture (ports and adapters)	`domain/port/in`, `domain/port/out`, `infrastructure/adapter` packages in each Java service; `Ports/In`, `Ports/Out` in payment	The domain does not depend on Spring, JPA, or RabbitMQ; infrastructure can change without touching the rules
3	Database per service (schema per service)	Liquibase changelogs per service; no FKs across schemas	No service reads another's tables; cross references are validated through the API
4	Publish / subscribe (distributed Observer)	`RabbitDomainEventPublisher.java`, `DomainEventListener.java:38`, `UserRegisteredListener.java:38`	Notify other services without coupling them or waiting for a reply
5	Idempotent consumer	`DomainEventConsumerService.java:61-72` + table `notification.processed_event`	RabbitMQ delivers "at least once"; a repeated event does not create two notifications
6	Repository	`UserAccountRepository` (port) → `UserAccountPersistenceAdapter.java:33` → `AppUserJpaRepository.java:12`	Hide data access behind a domain interface
7	Adapter	`BCryptPasswordHasher.java:10` implements `PasswordHasher`; `HttpAuthService` implements `IAuthService` on mobile	Adapt an external library (BCrypt, fetch) to the contract the domain expects
8	Strategy	`IDiscountStrategy.cs`, `PercentageDiscountStrategy.cs`, `FixedAmountDiscountStrategy.cs`	Each discount type computes in its own way, with no `switch` inside `Promotion`
9	Factory	`DiscountStrategyFactory.cs:9-21`	A single place decides which strategy matches each `DiscountType`
10	Unit of Work	`IUnitOfWork.cs:8-15`, `EfUnitOfWork.cs`	Approving a payment and crediting points are saved together or not at all
11	Value Object	`EmailAddress.java:12` (record validated on construction), `DocumentNumber`, `PersonName`, `HashedPassword`	Invalid data cannot exist inside the domain

#	Pattern	Where it is used	Problem it solves
12	Aggregate Root + domain events	`AggregateRoot.cs:24-39` (payment), `domain/event/*` (Java)	The root entity protects its rules and records what happened
13	DTO	`LoginRequest.java:6-8` (record with validation), `dto/*` in each service; `Contracts/*` in payment	Separate the HTTP contract from the domain model
14	Dependency injection	`DomainConfig.java` (`@Bean`), `DependencyInjection.cs` (.NET), `inject()` in Angular, `AuthServiceProvider` on mobile	Objects receive their dependencies; tests pass in doubles
15	Null Object / alternate implementation by configuration	`LoggingDomainEventPublisher.java:16` and `NullIntegrationEventPublisher.cs`	With `MESSAGING_ENABLED=false` the system works without RabbitMQ
16	Guard + Interceptor (chain of responsibility)	`Web/src/app/core/guards/auth-guard.ts:10-34`, `core/interceptors/auth-interceptor.ts:14-38`	Control access by role and attach the token only to the system's own API
17	Domain policy (Specification)	`AssignmentPolicy.java`, `AutoAssignmentPolicy.java`, `StartPolicy.java` (operations); `LoginLockout.java` (security)	Each business rule (who can take a booking, who gets it automatically, when it can start, when an account is locked) lives in a pure domain class that is tested without a database

> *Note.* Other mechanisms present: the `X-Correlation-Id` correlation filter (`CorrelationIdFilter.java:23-39`), Angular signal-based stores for admin state (`features/admin/services/*-store.ts`), and lazy loading of modules per role (`loadChildren` in `app.routes.ts`).

4.1 Representative Snippets

Strategy + Factory (`Backend/lavarapido-payment-service/src/PaymentService.Domain/Promotions/Discounts/DiscountStrategyFactory.cs:9-21`):

```
public static class DiscountStrategyFactory
{
    private static readonly IDiscountStrategy Percentage = new PercentageDiscountStrategy();
    private static readonly IDiscountStrategy FixedAmount = new FixedAmountDiscountStrategy();

    public static IDiscountStrategy For(DiscountType type) => type switch
    {
        DiscountType.Percentage => Percentage,
        DiscountType.FixedAmount => FixedAmount,
        _ => throw new DomainException(DomainErrorCodes.PromotionDiscountUnsupported, "...")
    };
}
```

Outbound port + Adapter (`security-service/.../domain/port/out/PasswordHasher.java` and `BCryptPasswordHasher.java`):

```
public interface PasswordHasher {
    HashedPassword hash(String raw);
    boolean matches(String raw, HashedPassword hash);
}

class BCryptPasswordHasher implements PasswordHasher {
    private final PasswordEncoder encoder;
    public boolean matches(String raw, HashedPassword hash) {
        return raw != null && encoder.matches(raw, hash.value());
    }
}
```

Alternate implementation by configuration (`LoggingDomainEventPublisher.java:16-17`):

```
@ConditionalOnProperty(prefix = "app.messaging", name = "enabled", havingValue = "false",
matchIfMissing = true)
class LoggingDomainEventPublisher implements DomainEventPublisher { ... }
```

HTTP interceptor (`Web/src/app/core/interceptors/auth-interceptor.ts:14-25`):

```
export const authInterceptor: HttpInterceptorFn = (req, next) => {
  if (!req.url.startsWith(API_BASE_URL)) {
    return next(req);
  }
  const token = inject(AuthService).accessToken();
  const request = token
    ? req.clone({ setHeaders: { Authorization: `Bearer ${token}` } })
    : req;
  ...
};
```

5. Data Model

The `LavaRapido` database (SQL Server 2022) has 57 tables in 9 schemas, created by each service's Liquibase changelogs. Foreign keys only exist within a single schema; references to another service are indexed columns without an FK, validated through the API.

Table 9

Schemas, owner, and number of tables

Schema	Owning service	Tables	Changelog
`security`	security-service	11	`001`–`036` in `security-service/src/main/resources/db/changelog`
`audit`	security-service	1	`002-create-security-and-audit-core.sql`
`customer`	customer-service	3	`004`, `014`, `015`
`catalog`	booking-service	3	`005`, `022`
`booking`	booking-service	10	`005`, `018`, `021`, `024`, `032`
`execution`	operations-service	11	`007`, `033`, `037`
`payment`	payment-service	7	`lavarapido-payment-service/db/changelog/changes/008`–`020`

Schema	Owning service	Tables	Changelog
promotion	payment-service	5	003–007, 017, 018
notification	notification-service	6	010–031

> *Note.* The security.custom_role table was created in 023 and dropped in 026; it is not counted. Earlier documents (MODELO-DE-DATOS.md) mention 43 tables: the changelogs later added bay_status, schedule_history, device_token, processed_event, booking_reminder, and booking_tracking.

5.1 Common Conventions

- **Audit block.** Almost every domain table ends with created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, and row_version. It is absent from the base security tables (person, app_user, role, permission, role_permission, user_role, user_session, password_reset_token), audit.audit_log, booking.schedule_history, and notification.booking_tracking. The tables added in October (security.login_lockout, security.person_address, execution.operator_profile, execution.operator_skill, and the four inspection report tables) do not have the full block either: they only keep the date and author columns they use.
- **Soft delete.** A non-null deleted_at marks a deleted row; several unique indexes are filtered with WHERE deleted_at IS NULL.
- **Optimistic concurrency.** A tr_touch_<table> trigger updates updated_at and adds 1 to row_version on every UPDATE.
- **UTC dates.** All default values use SYSUTCDATETIME().
- **Coded catalogs.** States and types are tables with a unique code (booking_status, payment_status, execution_status, etc.) loaded by seed changelogs.

5.2 Entity-Relationship Model

Solid lines are real FKs; dashed lines are logical references to another service (no FK). Only key attributes are shown; full detail is in the data dictionary (5.4).

Figure 16

Security and customers (security, audit, customer)





Figure 17


Catalog and bookings (`catalog`, `booking`)



Standalone tables in the `booking` schema (no relationships): `establishment` (single row, `singleton = 1`), `business_hour` (one row per day), `business_hour_exception` (one per date), and `schedule_history`.

Figure 18


Execution and notifications (`execution`, `notification`)



`notification.processed_event` has no relationships: it stores the `event_id` of each event already handled.

Figure 19

Payments, promotions, and loyalty (`payment`, `promotion`)



5.3 Relational Model

Notation: PK = primary key, UK = unique value, → = foreign key, ⇢ = logical reference to another service (no FK). The audit block is omitted.

- `security.person(person_id PK, document_number UK, first_name, last_name, phone, email)`
- `security.app_user(user_id PK, person_id → person UK, username UK, password_hash, is_active, last_login, created_at)`

- security.login_lockout(user_id PK → app_user, failed_count, first_failed_at, locked_until, updated_at) · security.person_address(person_id PK → person, address, updated_at)
- security.role(role_id PK, code UK, name) · security.permission(permission_id PK, code UK, name, resource, action)
- security.role_permission(role_permission_id PK, role_id → role, permission_id → permission) · security.user_role(user_role_id PK, user_id → app_user, role_id → role)
- security.user_session(user_session_id PK, user_id → app_user, refresh_token_hash, started_at, expires_at, revoked_at, ip_address, user_agent)
- security.password_reset_token(password_reset_token_id PK, user_id → app_user, token_hash UK, requested_at, expires_at, used_at, ip_address)
- security.user_preference(user_preference_id PK, user_id → app_user UK, theme, language, notifications_enabled, email_reminders_enabled, promotions_enabled)
- audit.audit_log(audit_log_id PK, entity, entity_id, action, previous_data, new_data, changed_by, changed_at)
- customer.vehicle_type(vehicle_type_id PK, code UK, name, size_factor, display_order, is_active)
- customer.customer(customer_id PK, person_id ⇢ security.person UK, user_id ⇢ security.app_user, loyalty_points, customer_since)
- customer.customer_vehicle(customer_vehicle_id PK, customer_id → customer, license_plate, vehicle_type_id → vehicle_type, brand, model, color)
- catalog.service_category(service_category_id PK, code UK, name, description, display_order, is_active)
- catalog.service(service_id PK, code UK, name, description, service_category_id → service_category, loyalty_points, is_active)
- catalog.service_price(service_price_id PK, service_id → service, vehicle_type_id ⇢ customer.vehicle_type, price, estimated_minutes, valid_from, valid_to)
- booking.establishment(establishment_id PK, legal_name, trade_name, tax_id, address, phone, email, logo_url, singleton UK, business_type, founded_on,

legal_representative, legal_representative_document, website, tax_regime, ciiu_activity, dian_resolution, invoice_prefix, invoice_range, instagram, facebook, support_line, service_hours_note)

- booking.business_hour(business_hour_id PK, day_of_week UK, opens_at, closes_at, break_starts_at, break_ends_at, is_active)
- booking.business_hour_exception(business_hour_exception_id PK, exception_date UK, is_closed, opens_at, closes_at, reason)
- booking.bay_status(bay_status_id PK, code UK, name, accepts_bookings, display_order) · booking.service_bay(service_bay_id PK, code UK, name, bay_status_id → bay_status)
- booking.booking_status(booking_status_id PK, code UK, name, is_final, display_order, is_active) · booking.cancellation_reason(cancellation_reason_id PK, code UK, name, is_customer_fault, display_order, is_active)
- booking.booking(booking_id PK, customer_vehicle_id ⇢ customer.customer_vehicle, service_bay_id → service_bay, scheduled_start, scheduled_end, booking_status_id → booking_status, booked_by ⇢ security.app_user, cancellation_reason_id → cancellation_reason, points_redeemed, points_discount_amount, notes)
- booking.booking_service(booking_service_id PK, booking_id → booking, service_price_id → catalog.service_price, quantity)
- booking.schedule_history(schedule_history_id PK, entity_type, title, detail, changed_at, changed_by)
- execution.execution_status(execution_status_id PK, code UK, name, is_final, display_order, is_active)
- execution.operator(operator_id PK, user_id ⇢ security.app_user UK, hired_on, is_active)
- execution.operator_availability(operator_availability_id PK, operator_id → operator, day_of_week, starts_at, ends_at, is_active)
- execution.operator_absence(operator_absence_id PK, operator_id → operator, starts_at, ends_at, reason)

- execution.service_execution(service_execution_id PK, booking_service_id ⇢ booking.booking_service UK, operator_id → operator, execution_status_id → execution_status, started_at, finished_at, quality_rating, quality_comment, rated_at, is_comment_visible)
- execution.operator_profile(operator_id PK → operator, specialty, updated_at, updated_by) · execution.operator_skill(operator_skill_id PK, operator_id → operator, name, skill_level, display_order)
- execution.inspection_report(inspection_report_id PK, booking_id ⇢ booking.booking UK, booking_code, vehicle, plate, services, booking_date, booking_time, duration_minutes, public_token UK, is_published, published_at)
- execution.inspection_phase(inspection_phase_id PK, inspection_report_id → inspection_report, phase, status, started_at, finished_at) · execution.inspection_finding(inspection_finding_id PK, inspection_report_id → inspection_report, phase, area, severity, note) · execution.inspection_photo(inspection_photo_id PK, inspection_finding_id → inspection_finding, content_type, content, size_bytes)
- payment.payment_method_type(payment_method_type_id PK, code UK, name, requires_account, requires_receipt, display_order, is_active)
- payment.payment_account(payment_account_id PK, payment_method_type_id → payment_method_type, account_holder, account_number, qr_image_url, instructions, is_active)
- payment.payment_status(payment_status_id PK, code UK, name, is_final, display_order, is_active)
- payment.payment(payment_id PK, booking_id ⇢ booking.booking, payment_account_id → payment_account, payment_status_id → payment_status, amount, processed_at, approved_by, rejection_reason)
- payment.payment_receipt(payment_receipt_id PK, payment_id → payment, file_url, transaction_reference, reported_amount, uploaded_at, uploaded_by, reviewed_at, reviewed_by, review_comment)

- payment.loyalty_movement_type(loyalty_movement_type_id PK, code UK, name, sign, display_order, is_active)
- payment.loyalty_transaction(loyalty_transaction_id PK, customer_id ⇢ customer.customer, loyalty_movement_type_id → loyalty_movement_type, booking_id ⇢ booking.booking, points, balance_after, sequence_no, expires_on, description)
- promotion.discount_type(discount_type_id PK, code UK, name, display_order, is_active)
- promotion.promotion(promotion_id PK, code UK, name, description, discount_type_id → discount_type, discount_value, max_discount_amount, min_purchase_amount, is_public, min_completed_booking, valid_from, valid_to, max_redemptions, max_redemptions_per_customer, is_active, price, duration_minutes, icon, featured, benefits, required_points)
- promotion.promotion_service(promotion_service_id PK, promotion_id → promotion, service_id ⇢ catalog.service)
- promotion.promotion_customer(promotion_customer_id PK, promotion_id → promotion, customer_id ⇢ customer.customer, assigned_at, assigned_by)
- promotion.booking_promotion(booking_promotion_id PK, booking_id ⇢ booking.booking, promotion_id → promotion, applied_amount)
- notification.notification_type(notification_type_id PK, code UK, name, display_order, is_active)
- notification.notification(notification_id PK, user_id ⇢ security.app_user, notification_type_id → notification_type, title, message, reference_entity, reference_id, is_read, read_at, sent_at)
- notification.device_token(device_token_id PK, user_id ⇢ security.app_user, token UK, platform, is_active, last_seen_at)
- notification.processed_event(processed_event_id PK, event_id UK, event_type, processed_at)
- notification.booking_reminder(booking_reminder_id PK, booking_id ⇢ booking.booking, user_id ⇢ security.app_user, booking_code, scheduled_start, lead_minutes, remind_at, sent_at)

- `notification.booking_tracking(booking_id PK ⇢ booking.booking, booking_code, customer_user_id, operator_user_id, scheduled_start, is_cancelled, unassigned_alert_at, updated_at)`

5.4 Data Dictionary

There is one dictionary for each of the 57 tables, grouped by schema. The "Null" column shows whether the field accepts NULL; PK = primary key, FK = foreign key, UK = unique value, and ⇢ = logical reference to another service (no FK). Tables that carry the audit block (section 5.1) show it as a single row at the end.

Schema `security`

Accounts, roles, permissions, sessions, and preferences. Owner: security-service.

Table 10

Data dictionary of `security.person` — personal data

Field	Type	Null	Key	Description
person_id	BIGINT IDENTITY	No	PK	Person identifier
document_number	NVARCHAR(20)	No	UK	ID document number
first_name	NVARCHAR(60)	No		First names
last_name	NVARCHAR(60)	No		Last names
phone	NVARCHAR(20)	Yes		Phone
email	NVARCHAR(120)	Yes		Contact email

Table 11

Data dictionary of `security.app_user` — login account

Field	Type	Null	Key	Description
user_id	BIGINT IDENTITY	No	PK	User identifier
person_id	BIGINT	No	FK → person, UK	Person who owns the account (1 to 1)
username	NVARCHAR(60)	No	UK	Email used to log in
password_hash	NVARCHAR(255)	No		BCrypt password hash
is_active	BIT	No		Account enabled (default 1)
last_login	DATETIME2(3)	Yes		Last login
created_at	DATETIME2(3)	No		Account registration date (migration `036`)

Table 12

Data dictionary of `security.role` — system roles

Field	Type	Null	Key	Description
role_id	SMALLINT IDENTITY	No	PK	Role identifier
code	NVARCHAR(30)	No	UK	`ADMIN`, `OPERATOR`, or `CLIENT` (seed `101`)
name	NVARCHAR(60)	No		Display name

Table 13

Data dictionary of `security.permission` — permissions

Field	Type	Null	Key	Description
permission_id	SMALLINT IDENTITY	No	PK	Permission identifier
code	NVARCHAR(60)	No	UK	`VIEW_PANELS`, `CREATE_RECORDS`, `EDIT_DATA`, or `DELETE` (changelog `026`)
name	NVARCHAR(80)	No		Display name
resource	NVARCHAR(60)	No		Resource it applies to
action	NVARCHAR(30)	No		Allowed action

Table 14

Data dictionary of `security.role_permission` — permissions of each role

Field	Type	Null	Key	Description
role_permission_id	BIGINT IDENTITY	No	PK	Assignment identifier
role_id	SMALLINT	No	FK → role; UK con permission_id	Role
permission_id	SMALLINT	No	FK → permission	Granted permission

Table 15

Data dictionary of `security.user_role` — roles of each user

Field	Type	Null	Key	Description
user_role_id	BIGINT IDENTITY	No	PK	Assignment identifier
user_id	BIGINT	No	FK → app_user; UK con role_id	User
role_id	SMALLINT	No	FK → role	Assigned role

Table 16

Data dictionary of `security.user_session` — open sessions

Field	Type	Null	Key	Description
user_session_id	BIGINT IDENTITY	No	PK	Session identifier
user_id	BIGINT	No	FK → app_user	User
refresh_token_hash	NVARCHAR(255)	Yes		Refresh token hash
started_at	DATETIME2(3)	No		Session start (UTC)
expires_at	DATETIME2(3)	No		Expiry
revoked_at	DATETIME2(3)	Yes		Logout time
ip_address	NVARCHAR(45)	Yes		Source IP

Field	Type	Null	Key	Description
user_agent	NVARCHAR(300)	Yes		Source browser or app

Table 17

Data dictionary of `security.password_reset_token` — password recovery codes

Field	Type	Null	Key	Description
password_reset_token_id	BIGINT IDENTITY	No	PK	Request identifier
user_id	BIGINT	No	FK → app_user	User who requested the code
token_hash	NVARCHAR(255)	No	UK	Hash of the 6-digit code
requested_at	DATETIME2(3)	No		Request date
expires_at	DATETIME2(3)	No		Expiry; CHECK `expires_at > requested_at`
used_at	DATETIME2(3)	Yes		When it was used
ip_address	NVARCHAR(45)	Yes		Request IP

Table 18

Data dictionary of `security.user_preference` — UI and notification preferences

Field	Type	Null	Key	Description
user_preference_id	BIGINT IDENTITY	No	PK	Preference identifier
user_id	BIGINT	No	FK → app_user, UK	User (one row per user)
theme	NVARCHAR(20)	No		`green-light`, `green-dark`, `pink`, or `pink-dark`
language	NVARCHAR(5)	No		`es`, `en`, `fr`, or `pt`
notifications_enabled	BIT	No		In-app notifications
email_reminders_enabled	BIT	No		Email reminders
promotions_enabled	BIT	No		Promotion notices
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 19

Data dictionary for `security.login_lockout` — lockout after failed attempts

Field	Type	Null	Key	Description
user_id	BIGINT	No	PK, FK → app_user	Account with recent failures or locked
failed_count	INT	No		Failures within the current window, 0 to 4 (default 0)
first_failed_at	DATETIME2(3)	Yes		Start of the 15-minute window
locked_until	DATETIME2(3)	Yes		Locked until this time; NULL if not locked
updated_at	DATETIME2(3)	No		Last change

Table 20

Data dictionary for `security.person_address` — contact address

Field	Type	Null	Key	Description
person_id	BIGINT	No	PK, FK → person	Person who owns the address
address	NVARCHAR(200)	No		Profile contact address; cannot be blank
updated_at	DATETIME2(3)	No		Last change

Schema `audit`

Change log. Owner: security-service.

Table 21

Data dictionary of `audit.audit_log` — change log

Field	Type	Null	Key	Description
audit_log_id	BIGINT IDENTITY	No	PK	Record identifier
entity	NVARCHAR(60)	No		Affected entity
entity_id	BIGINT	No		Affected row
action	NVARCHAR(20)	No		Action performed
previous_data	NVARCHAR(MAX)	Yes		Previous state
new_data	NVARCHAR(MAX)	Yes		New state
changed_by	BIGINT	Yes		User who made the change
changed_at	DATETIME2(3)	No		Change date (UTC)

Schema `customer`

Customers and vehicles. Owner: customer-service.

Table 22

Data dictionary of `customer.vehicle_type` — vehicle types

Field	Type	Null	Key	Description
vehicle_type_id	SMALLINT IDENTITY	No	PK	Type identifier
code	NVARCHAR(30)	No	UK	`CAR`, `SEDAN`, `SUV`, `PICKUP`, `TRUCK`, or `MOTO`
name	NVARCHAR(60)	No		Display name
size_factor	DECIMAL(4,2)	No		Size factor (> 0)
display_order	SMALLINT	No		Display order
is_active	BIT	No		Type in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 23

Data dictionary of `customer.customer` — customers

Field	Type	Null	Key	Description
customer_id	BIGINT IDENTITY	No	PK	Customer identifier
person_id	BIGINT	No	UK, ⇢ security.person	Customer's person
user_id	BIGINT	Yes	UK filtrada, ⇢ security.app_user	Customer's account
loyalty_points	INT	No		Display copy of the points balance (≥ 0)
customer_since	DATE	No		Sign-up date
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 24

Data dictionary of `customer.customer_vehicle` — customers' vehicles

Field	Type	Null	Key	Description
customer_vehicle_id	BIGINT IDENTITY	No	PK	Vehicle identifier
customer_id	BIGINT	No	FK → customer	Owner
license_plate	NVARCHAR(10)	No	UK filtrada (activos)	License plate
vehicle_type_id	SMALLINT	No	FK → vehicle_type	Vehicle type
brand	NVARCHAR(50)	Yes		Make
model	NVARCHAR(50)	Yes		Model
color	NVARCHAR(30)	Yes		Color
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Schema `catalog`

Service catalog and prices. Owner: booking-service.

Table 25

Data dictionary of `catalog.service_category` — service categories

Field	Type	Null	Key	Description
service_category_id	SMALLINT IDENTITY	No	PK	Category identifier
code	NVARCHAR(30)	No	UK	`LAVADO`, `POLICHADO`, `DETALLADO`, `INTERIOR`, or `PAQUETES`
name	NVARCHAR(60)	No		Display name
description	NVARCHAR(200)	Yes		Description
display_order	SMALLINT	No		Display order

Field	Type	Null	Key	Description
is_active	BIT	No		Category in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 26

Data dictionary of `catalog.service` — wash services

Field	Type	Null	Key	Description
service_id	INT IDENTITY	No	PK	Service identifier
code	NVARCHAR(30)	No	UK	Code (`BASIC`, `PREMIUM`, `FULL` in the seed)
name	NVARCHAR(100)	No		Display name
description	NVARCHAR(MAX)	Yes		Description
service_category_id	SMALLINT	No	FK → service_category	Category
is_active	BIT	No		Available for booking
loyalty_points	INT	No		Points awarded on completion (changelog `022`)
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 27

Data dictionary of `catalog.service_price` — prices per vehicle type

Field	Type	Null	Key	Description
service_price_id	BIGINT IDENTITY	No	PK	Price identifier
service_id	INT	No	FK → service	Service
vehicle_type_id	SMALLINT	No	⇢ customer.vehicle_type	Vehicle type
price	DECIMAL(12,2)	No		Price (≥ 0)
estimated_minutes	SMALLINT	No		Estimated duration (> 0)
valid_from	DATE	No		Valid from
valid_to	DATE	Yes		Valid to; only one open price per service and type (filtered index); rows are immutable by trigger
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Schema `booking`

Establishment, business hours, bays, and bookings. Owner: booking-service.

Table 28

Data dictionary of `booking.establishment` — car wash data

Field	Type	Null	Key	Description
establishment_id	SMALLINT IDENTITY	No	PK	Identifier
legal_name	NVARCHAR(150)	No		Legal name
trade_name	NVARCHAR(150)	No		Trade name
tax_id	NVARCHAR(30)	No		Tax ID (NIT)
address	NVARCHAR(200)	No		Address
phone	NVARCHAR(20)	Yes		Phone
email	NVARCHAR(120)	Yes		Email
logo_url	NVARCHAR(500)	Yes		Logo
business_type	NVARCHAR(100)	Yes		Business type (migration `032`)
founded_on	DATE	Yes		Foundation date; cannot be in the future (migration `032`)
legal_representative	NVARCHAR(150)	Yes		Legal representative (migration `032`)
legal_representative_document	NVARCHAR(30)	Yes		Legal representative ID (migration `032`)
website	NVARCHAR(200)	Yes		Website (migration `032`)
tax_regime	NVARCHAR(150)	Yes		Tax regime (migration `032`)
ciiu_activity	NVARCHAR(150)	Yes		CIIU economic activity (migration `032`)
dian_resolution	NVARCHAR(60)	Yes		DIAN invoicing resolution (migration `032`)
invoice_prefix	NVARCHAR(10)	Yes		Invoice prefix (migration `032`)
invoice_range	NVARCHAR(30)	Yes		Invoice range (migration `032`)
instagram	NVARCHAR(100)	Yes		Instagram (migration `032`)
facebook	NVARCHAR(150)	Yes		Facebook (migration `032`)
support_line	NVARCHAR(30)	Yes		Support line (migration `032`)
service_hours_note	NVARCHAR(150)	Yes		Service hours shown to the customer (migration `032`)
singleton	BIT	No	UK	Always 1: prevents a second row
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 29

Data dictionary of `booking.business_hour` — weekly hours

Field	Type	Null	Key	Description
business_hour_id	SMALLINT IDENTITY	No	PK	Identifier

Field	Type	Null	Key	Description
day_of_week	SMALLINT	No	UK	Day of week (1 to 7)
opens_at	TIME(0)	No		Opening time
closes_at	TIME(0)	No		Closing time (after opening)
is_active	BIT	No		Working day
break_starts_at	TIME(0)	Yes		Break start (changelog `018`)
break_ends_at	TIME(0)	Yes		Break end
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 30

Data dictionary of `booking.business_hour_exception` — schedule exceptions

Field	Type	Null	Key	Description
business_hour_exception_id	INT IDENTITY	No	PK	Identifier
exception_date	DATE	No	UK	Special date
is_closed	BIT	No		Closed all day
opens_at	TIME(0)	Yes		Special opening (if open)
closes_at	TIME(0)	Yes		Special closing (if open)
reason	NVARCHAR(120)	No		Reason
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 31

Data dictionary of `booking.bay_status` — bay statuses

Field	Type	Null	Key	Description
bay_status_id	SMALLINT IDENTITY	No	PK	Identifier
code	NVARCHAR(30)	No	UK	`ACTIVE`, `MAINTENANCE`, or `INACTIVE`
name	NVARCHAR(60)	No		Display name
accepts_bookings	BIT	No		Whether it accepts bookings
display_order	SMALLINT	No		Display order
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 32

Data dictionary of `booking.service_bay` — wash bays

Field	Type	Null	Key	Description
service_bay_id	SMALLINT IDENTITY	No	PK	Bay identifier
code	NVARCHAR(20)	No	UK	Code (`BAY-01`…)
name	NVARCHAR(60)	No		Display name
bay_status_id	SMALLINT	No	FK → bay_status	Status (default 1, active)
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 33

Data dictionary of `booking.booking_status` — booking statuses

Field	Type	Null	Key	Description
booking_status_id	SMALLINT IDENTITY	No	PK	1 `SCHEDULED`, 2 `CONFIRMED`, 3 `IN_PROGRESS`, 4 `COMPLETED`, 5 `CANCELLED`, 6 `NO_SHOW`
code	NVARCHAR(30)	No	UK	Status code
name	NVARCHAR(60)	No		Display name
is_final	BIT	No		Whether the status is final
display_order	SMALLINT	No		Display order
is_active	BIT	No		Status in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 34

Data dictionary of `booking.cancellation_reason` — cancellation reasons

Field	Type	Null	Key	Description
cancellation_reason_id	SMALLINT IDENTITY	No	PK	Identifier
code	NVARCHAR(30)	No	UK	Code (six seed reasons)
name	NVARCHAR(60)	No		Display name
is_customer_fault	BIT	No		Whether the customer is at fault
display_order	SMALLINT	No		Display order
is_active	BIT	No		Reason in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 35

Data dictionary of `booking.booking` — bookings

Field	Type	Null	Key	Description
booking_id	BIGINT IDENTITY	No	PK	Booking identifier
customer_vehicle_id	BIGINT	No	⇢ customer.customer_vehicle	Vehicle to wash
service_bay_id	SMALLINT	Yes	FK → service_bay	Assigned bay; a trigger prevents overlapping times
scheduled_start	DATETIME2(3)	No		Scheduled start
scheduled_end	DATETIME2(3)	No		Scheduled end (after start)
booking_status_id	SMALLINT	No	FK → booking_status	Status
booked_by	BIGINT	No	⇢ security.app_user	User who created the booking
cancellation_reason_id	SMALLINT	Yes	FK → cancellation_reason	Only when the status is `CANCELLED`
points_redeemed	INT	No		Points redeemed
points_discount_amount	DECIMAL(12,2)	No		Points discount (both 0 or both > 0)
notes	NVARCHAR(300)	Yes		Notes
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 36

Data dictionary of `booking.booking_service` — service lines of each booking

Field	Type	Null	Key	Description
booking_service_id	BIGINT IDENTITY	No	PK	Line identifier
booking_id	BIGINT	No	FK → booking; UK con service_price_id	Booking
service_price_id	BIGINT	No	FK → catalog.service_price	Price applied when booking
quantity	SMALLINT	No		Quantity (> 0)
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 37

Data dictionary of `booking.schedule_history` — schedule change history

Field	Type	Null	Key	Description
schedule_history_id	BIGINT IDENTITY	No	PK	Identifier
entity_type	NVARCHAR(20)	No		`WEEK`, `EXCEPTION`, or `BAY`
title	NVARCHAR(200)	No		Change summary

Field	Type	Null	Key	Description
detail	NVARCHAR(300)	Yes		Change detail
changed_at	DATETIME2(3)	No		Change date (UTC)
changed_by	BIGINT	Yes		User who made the change

Schema `execution`

Operators and service execution. Owner: operations-service.

Table 38

Data dictionary of `execution.execution_status` — execution statuses

Field	Type	Null	Key	Description
execution_status_id	SMALLINT IDENTITY	No	PK	1 `PENDING`, 2 `IN_PROGRESS`, 3 `PAUSED`, 4 `COMPLETED`, 5 `WITH_ISSUE`
code	NVARCHAR(30)	No	UK	Status code
name	NVARCHAR(60)	No		Display name
is_final	BIT	No		Whether the status is final
display_order	SMALLINT	No		Display order
is_active	BIT	No		Status in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 39

Data dictionary of `execution.operator` — operators

Field	Type	Null	Key	Description
operator_id	INT IDENTITY	No	PK	Operator identifier
user_id	BIGINT	No	UK, ⇢ security.app_user	Operator's account
hired_on	DATE	No		Hire date
is_active	BIT	No		Eligible for assignments
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 40

Data dictionary of `execution.operator_availability` — operator weekly shift

Field	Type	Null	Key	Description
operator_availability_id	INT IDENTITY	No	PK	Identifier
operator_id	INT	No	FK → operator; UK con day_of_week	Operator

Field	Type	Null	Key	Description
day_of_week	SMALLINT	No		Day of week (1 to 7)
starts_at	TIME(0)	No		Shift start
ends_at	TIME(0)	No		Shift end (after start)
is_active	BIT	No		Shift in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 41

Data dictionary of `execution.operator_absence` — operator absences

Field	Type	Null	Key	Description
operator_absence_id	INT IDENTITY	No	PK	Identifier
operator_id	INT	No	FK → operator	Operator
starts_at	DATETIME2(3)	No		Absence start
ends_at	DATETIME2(3)	No		Absence end; a trigger prevents overlapping absences
reason	NVARCHAR(120)	No		Reason
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 42

Data dictionary of `execution.service_execution` — execution of each service line

Field	Type	Null	Key	Description
service_execution_id	BIGINT IDENTITY	No	PK	Execution identifier
booking_service_id	BIGINT	No	UK, ⇢ booking.booking_service	Booking line
operator_id	INT	No	FK → operator	Assigned operator
execution_status_id	SMALLINT	No	FK → execution_status	Execution status
started_at	DATETIME2(3)	Yes		Actual start
finished_at	DATETIME2(3)	Yes		Actual finish
quality_rating	SMALLINT	Yes		Rating from 1 to 5
quality_comment	NVARCHAR(500)	Yes		Comment; only with a rating
rated_at	DATETIME2(3)	Yes		Rating date
is_comment_visible	BIT	No		Whether the comment is shown
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 43

Data dictionary for `execution.operator_profile` — operator specialty

Field	Type	Null	Key	Description
operator_id	INT	No	PK, FK → operator	Operator
specialty	NVARCHAR(80)	Yes		Specialty
updated_at	DATETIME2(3)	No		Last change
updated_by	BIGINT	Yes		Administrator who changed it ⇢ security.app_user

Table 44

Data dictionary for `execution.operator_skill` — operator skills

Field	Type	Null	Key	Description
operator_skill_id	INT IDENTITY	No	PK	Identifier
operator_id	INT	No	FK → operator	Operator
name	NVARCHAR(60)	No	UK with operator_id	Skill name
skill_level	NVARCHAR(12)	No		`CERTIFIED`, `EXPERT` or `ADVANCED`
display_order	SMALLINT	No		Order in the profile

Table 45

Data dictionary for `execution.inspection_report` — vehicle inspection report

Field	Type	Null	Key	Description
inspection_report_id	BIGINT IDENTITY	No	PK	Identifier
booking_id	BIGINT	No	UK, ⇢ booking.booking	Inspected booking (one report per booking)
booking_code, vehicle, plate, services	NVARCHAR	Yes		Copy of the booking data when the report is created
booking_date, booking_time, duration_minutes	DATE, TIME(0), INT	No		Booking date, time, and duration
public_token	NVARCHAR(64)	No	UK	Random code of the public link
is_published	BIT	No		The link shows the report (default 0)
published_at	DATETIME2(3)	Yes		Publication date; required when published
created_at, created_by, updated_at, updated_by, row_version	—	—		Audit

Table 46

Data dictionary for `execution.inspection_phase` — report phases

Field	Type	Null	Key	Description
inspection_phase_id	BIGINT IDENTITY	No	PK	Identifier
inspection_report_id	BIGINT	No	FK → inspection_report; UK with phase	Report
phase	NVARCHAR(20)	No		`RECEPTION`, `EXTERIOR`, `INTERIOR`, `ENGINE` or `DELIVERY`
status	NVARCHAR(20)	No		`PENDING`, `IN_PROGRESS` or `DONE`
started_at, finished_at	DATETIME2(3)	Yes		Phase start and end

Table 47

Data dictionary for `execution.inspection_finding` — report findings

Field	Type	Null	Key	Description
inspection_finding_id	BIGINT IDENTITY	No	PK	Identifier
inspection_report_id	BIGINT	No	FK → inspection_report	Report
phase	NVARCHAR(20)	No		Phase where it was found
area	NVARCHAR(120)	No		Vehicle area
severity	NVARCHAR(10)	No		`INFO`, `MINOR` or `MAJOR`
note	NVARCHAR(500)	Yes		Note
created_at, created_by, deleted_at, deleted_by	—	—		Creation and soft delete

Table 48

Data dictionary for `execution.inspection_photo` — finding photos

Field	Type	Null	Key	Description
inspection_photo_id	BIGINT IDENTITY	No	PK	Identifier
inspection_finding_id	BIGINT	No	FK → inspection_finding	Finding (up to 5 photos each)
content_type	NVARCHAR(30)	No		`image/jpeg` or `image/png`
content	VARBINARY(MAX)	No		Image
size_bytes	INT	No		Size, up to 2 MB
created_at, created_by	—	—		Creation

Schema `payment`

Payments, payment accounts, and points. Owner: payment-service.

Table 49

Data dictionary of `payment.payment_method_type` — payment methods

Field	Type	Null	Key	Description
payment_method_type_id	SMALLINT IDENTITY	No	PK	Identifier
code	NVARCHAR(30)	No	UK	`EFECTIVO`, `NEQUI`, `DAVIPLATA`, or `TRANSFERENCIA`
name	NVARCHAR(60)	No		Display name
requires_account	BIT	No		Whether it requires an account
requires_receipt	BIT	No		Whether it requires a receipt
display_order	SMALLINT	No		Display order
is_active	BIT	No		Method in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 50

Data dictionary of `payment.payment_account` — car wash receiving accounts

Field	Type	Null	Key	Description
payment_account_id	SMALLINT IDENTITY	No	PK	Account identifier
payment_method_type_id	SMALLINT	No	FK → payment_method_type	Payment method
account_holder	NVARCHAR(120)	No		Holder
account_number	NVARCHAR(50)	Yes		Number or key
qr_image_url	NVARCHAR(MAX)	Yes		QR image stored as data (changelog `016`)
instructions	NVARCHAR(300)	Yes		Instructions for the customer
is_active	BIT	No		Account visible to the customer
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 51

Data dictionary of `payment.payment_status` — payment statuses

Field	Type	Null	Key	Description
payment_status_id	SMALLINT IDENTITY	No	PK	Identifier
code	NVARCHAR(30)	No	UK	`PENDING`, `IN_REVIEW`, `APPROVED`, `REJECTED`, or `REFUNDED`
name	NVARCHAR(60)	No		Display name
is_final	BIT	No		Whether the status is final
display_order	SMALLINT	No		Display order
is_active	BIT	No		Status in use

Field	Type	Null	Key	Description
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 52

Data dictionary of `payment.payment` — payments

Field	Type	Null	Key	Description
payment_id	BIGINT IDENTITY	No	PK	Payment identifier
booking_id	BIGINT	No	⇢ booking.booking	Booking paid; one approved payment per booking (filtered index)
payment_account_id	SMALLINT	No	FK → payment_account	Account paid into
payment_status_id	SMALLINT	No	FK → payment_status	Status
amount	DECIMAL(12,2)	No		Amount (> 0)
processed_at	DATETIME2(3)	Yes		Review date
approved_by	BIGINT	Yes		Approving administrator
rejection_reason	NVARCHAR(200)	Yes		Rejection reason
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 53

Data dictionary of `payment.payment_receipt` — payment receipts

Field	Type	Null	Key	Description
payment_receipt_id	BIGINT IDENTITY	No	PK	Receipt identifier
payment_id	BIGINT	No	FK → payment	Payment
file_url	NVARCHAR(MAX)	No		Receipt image
transaction_reference	NVARCHAR(100)	Yes		Transaction reference
reported_amount	DECIMAL(12,2)	Yes		Amount declared by the customer (> 0)
uploaded_at	DATETIME2(3)	No		Upload date
uploaded_by	BIGINT	No		User who uploaded it
reviewed_at	DATETIME2(3)	Yes		Review date
reviewed_by	BIGINT	Yes		Reviewer (together with reviewed_at)
review_comment	NVARCHAR(300)	Yes		Review comment
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 54

Data dictionary of `payment.loyalty_movement_type` — points movement types

Field	Type	Null	Key	Description
loyalty_movement_type_id	SMALLINT IDENTITY	No	PK	Identifier
code	NVARCHAR(30)	No	UK	`EARNED`, `REDEEMED`, `EXPIRED`, `ADJUSTED`, or `REVERSED`
name	NVARCHAR(60)	No		Display name
sign	SMALLINT	No		+1 or -1
display_order	SMALLINT	No		Display order
is_active	BIT	No		Type in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 55

Data dictionary of `payment.loyalty_transaction` — points ledger

Field	Type	Null	Key	Description
loyalty_transaction_id	BIGINT IDENTITY	No	PK	Movement identifier
customer_id	BIGINT	No	⇢ customer.customer; UK con sequence_no	Customer
loyalty_movement_type_id	SMALLINT	No	FK → loyalty_movement_type	Movement type
booking_id	BIGINT	Yes	⇢ booking.booking	Booking that caused the movement
points	INT	No		Movement points (≠ 0)
balance_after	INT	No		Resulting balance (≥ 0); source of truth for the balance
expires_on	DATE	Yes		Points expiry
description	NVARCHAR(200)	Yes		Detail
sequence_no	INT	No		Per-customer sequence number (changelog `020`)
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Schema `promotion`

Promotions and coupons. Owner: payment-service.

Table 56

Data dictionary of `promotion.discount_type` — discount types

Field	Type	Null	Key	Description
discount_type_id	SMALLINT IDENTITY	No	PK	Identifier
code	NVARCHAR(30)	No	UK	`PERCENT`, `FIXED`, or `PACKAGE`
name	NVARCHAR(60)	No		Display name
display_order	SMALLINT	No		Display order
is_active	BIT	No		Type in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 57

Data dictionary of `promotion.promotion` — promotions

Field	Type	Null	Key	Description
promotion_id	INT IDENTITY	No	PK	Promotion identifier
code	NVARCHAR(30)	No	UK	Coupon code
name	NVARCHAR(100)	No		Display name
description	NVARCHAR(300)	Yes		Description
discount_type_id	SMALLINT	No	FK → discount_type	Discount type
discount_value	DECIMAL(12,2)	No		Discount value (> 0)
max_discount_amount	DECIMAL(12,2)	Yes		Discount cap
min_purchase_amount	DECIMAL(12,2)	No		Minimum purchase
is_public	BIT	No		Visible to all customers
min_completed_booking	INT	No		Completed bookings required (≥ 0)
valid_from	DATE	No		Valid from
valid_to	DATE	No		Valid to
max_redemptions	INT	Yes		Total redemption limit
max_redemptions_per_customer	INT	Yes		Per-customer limit (≤ total)
is_active	BIT	No		Promotion active
price	DECIMAL(12,2)	Yes		Package price (changelog `017`)
duration_minutes	INT	Yes		Package duration
icon	NVARCHAR(40)	Yes		Icon
featured	BIT	No		Featured
benefits	NVARCHAR(600)	Yes		Package benefits
required_points	INT	No		Points needed to redeem (≥ 0; changelog `018`)
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 58

Data dictionary of `promotion.promotion_service` — services each promotion applies to

Field	Type	Null	Key	Description
promotion_service_id	INT IDENTITY	No	PK	Identifier
promotion_id	INT	No	FK → promotion; UK con service_id	Promotion
service_id	INT	No	⇢ catalog.service	Service
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 59

Data dictionary of `promotion.promotion_customer` — target customers of each promotion

Field	Type	Null	Key	Description
promotion_customer_id	BIGINT IDENTITY	No	PK	Identifier
promotion_id	INT	No	FK → promotion; UK con customer_id	Promotion
customer_id	BIGINT	No	⇢ customer.customer	Target customer
assigned_at	DATETIME2(3)	No		Assignment date
assigned_by	BIGINT	Yes		Assigning user
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 60

Data dictionary of `promotion.booking_promotion` — promotion redemptions on bookings

Field	Type	Null	Key	Description
booking_promotion_id	BIGINT IDENTITY	No	PK	Redemption identifier
booking_id	BIGINT	No	⇢ booking.booking; UK con promotion_id	Booking
promotion_id	INT	No	FK → promotion	Redeemed promotion
applied_amount	DECIMAL(12,2)	No		Discount applied (> 0)
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Schema `notification`

Notifications, devices, and reminders. Owner: notification-service.

Table 61

Data dictionary of `notification.notification_type` — notification types

Field	Type	Null	Key	Description
notification_type_id	SMALLINT IDENTITY	No	PK	Identifier
code	NVARCHAR(40)	No	UK	One of the 23 codes, from `USER_WELCOME` to `ADMIN_BOOKING_UNASSIGNED`
name	NVARCHAR(80)	No		Display name
display_order	SMALLINT	No		Display order
is_active	BIT	No		Type in use
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 62

Data dictionary of `notification.notification` — notifications

Field	Type	Null	Key	Description
notification_id	BIGINT IDENTITY	No	PK	Notification identifier
user_id	BIGINT	No	⇢ security.app_user	Recipient
notification_type_id	SMALLINT	No	FK → notification_type	Type
title	NVARCHAR(120)	No		Title
message	NVARCHAR(500)	No		Message
reference_entity	NVARCHAR(40)	Yes		Related entity (for example, booking)
reference_id	BIGINT	Yes		Related entity identifier
is_read	BIT	No		Read (kept consistent with read_at by a CHECK)
read_at	DATETIME2(3)	Yes		Read date
sent_at	DATETIME2(3)	No		Send date
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 63

Data dictionary of `notification.device_token` — push notification devices

Field	Type	Null	Key	Description
device_token_id	BIGINT IDENTITY	No	PK	Device identifier
user_id	BIGINT	No	⇢ security.app_user	Owner

Field	Type	Null	Key	Description
token	NVARCHAR(200)	No	UK	Expo Push token
platform	NVARCHAR(10)	No		Platform; the CHECK accepts `ANDROID` or `IOS`
is_active	BIT	No		Device in use
last_seen_at	DATETIME2(3)	No		Last device registration
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 64

Data dictionary of `notification.processed_event` — already handled events

Field	Type	Null	Key	Description
processed_event_id	BIGINT IDENTITY	No	PK	Identifier
event_id	NVARCHAR(64)	No	UK	RabbitMQ event ID
event_type	NVARCHAR(60)	No		Event type
processed_at	DATETIME2(3)	No		Processing date
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 65

Data dictionary of `notification.booking_reminder` — booking reminders

Field	Type	Null	Key	Description
booking_reminder_id	BIGINT IDENTITY	No	PK	Reminder identifier
booking_id	BIGINT	No	⇢ booking.booking; UK con lead_minutes	Booking
user_id	BIGINT	No	⇢ security.app_user	Customer
booking_code	NVARCHAR(20)	Yes		Booking code
scheduled_start	DATETIME2(3)	No		Appointment time
lead_minutes	INT	No		Minutes of notice (`REMINDER_LEADS`, default 24 h and 1 h)
remind_at	DATETIME2(3)	No		When to notify
sent_at	DATETIME2(3)	Yes		When it was sent
created_at, created_by, updated_at, updated_by, deleted_at, deleted_by, row_version	—	—		Audit block (section 5.1)

Table 66

Data dictionary of `notification.booking_tracking` — local copy of booking state

Field	Type	Null	Key	Description
booking_id	BIGINT	No	PK, ⇢ booking.booking	Booking
booking_code	NVARCHAR(20)	Yes		Booking code
customer_user_id	BIGINT	Yes		Customer user
operator_user_id	BIGINT	Yes		Assigned operator user
scheduled_start	DATETIME2(3)	Yes		Appointment time
is_cancelled	BIT	No		Booking cancelled
updated_at	DATETIME2(3)	No		Last update
unassigned_alert_at	DATETIME2(3)	Yes		When the "no operator" alert was sent (changelog `031`)

> *Note.* Source of types and constraints: `.sql` files in `*/src/main/resources/db/changelog/` (Java services) and `lavarapido-payment-service/db/changelog/changes/`, including the `ALTER` statements made after each table was created.

6. Class Diagrams

There is at least one class diagram for each of the six services; the four largest have two: one for the domain model and one for the application layer with its ports. Business rules live in the domain entities, not in the controllers: for example, `Booking.moveTo()` decides which status changes are valid, and `ServiceExecution.rate()` allows rating only once and only for a completed service.

Diagram conventions:

- UML stereotypes: `aggregate root`, `entity`, `value object`, `enumeration`, `domain service`, `application service`, `interface` (outbound port), `event`, `factory`, and `abstract`.
- The `implements …` line in an application service lists the inbound ports (use cases) it implements.
- A solid arrow (`-->`) is a constructor-injected dependency; a dashed arrow (`..>`) is a usage or a reference by ID.
- Getters, constructors, exceptions, response DTOs (`*View`, `*Dto`), and input commands (`*Command`, `*Request`) are omitted.

6.1 security-service

Figure 20

security-service domain model






Figure 21

security-service application services and ports


«application service»
AccountDeactivationService
implements DeactivateOwnAccountUseCase
+deactivateOwnAccount(command)
«interface»
UserSessionRepository
+open(userId, startedAt, expiresAt, ipAddress, userAgent) : long
+revoke(sessionId, userId, revokedAt)
+revokeAll(userId, revokedAt)
«application service»
UserAdministrationService
implements ListUserAccountsUseCase, ChangeAccountStatusUseCase
+listAccounts(query) : PageResult<UserAccountView>
+changeStatus(targetUserId, active, actingUserId) : UserAccountView
«interface»
TokenIssuer
+issue(account, sessionId, issuedAt) : IssuedToken
+timeToLive() : Duration
«application service»
AuthenticationService
implements AuthenticateUserUseCase, LogoutUseCase
+login(command) : AuthenticationResult
+logout(userId, sessionId)
«interface»
UserAccountRepository
+findById(userId) : Optional<UserAccount>
+findByUsername(username) : Optional<UserAccount>
+existsByUsername(username) : boolean
+findPersonByDocument(documentNumber) : Optional<Person>
+save(account) : UserAccount
+findAll(role, page, size) : PageResult<UserAccount>
«application service»
UserProfileService
implements GetUserProfileUseCase, UpdateUserProfileUseCase, ChangePasswordUseCase
+getProfile(userId) : UserAccountView
+updateProfile(command) : UserAccountView
+changePassword(command)
«interface»
LoginLockoutRepository
+findByUserId(userId) : Optional<LoginLockout>
+save(lockout)
+clear(userId)
«application service»
AccountRegistrationService
implements RegisterUserUseCase, CreateUserAccountUseCase
+register(command) : UserAccountView
+createAccount(command) : UserAccountView
«interface»
PasswordHasher
+hash(raw) : HashedPassword
+matches(raw, hash) : boolean
«application service»
EmailChangeService
implements ChangeEmailUseCase
+changeEmail(command) : UserAccountView
«application service»
PersonAddressService
implements PersonAddressUseCase
+getAddress(userId) : String
+updateAddress(userId, address) : String
«interface»
DomainEventPublisher
+publish(event)
«interface»
PersonAddressRepository
+findByPersonId(personId) : Optional<String>
+save(personId, address)
+delete(personId)
«application service»
PasswordRecoveryService
implements RequestPasswordResetUseCase, VerifyPasswordResetCodeUseCase, ResetPasswordUseCase
+requestReset(command)
«interface»




Note. Outbound adapters: `UserAccountPersistenceAdapter`, `UserSessionPersistenceAdapter`, `PasswordResetTokenPersistenceAdapter`, `UserPreferencePersistenceAdapter`, `RolePermissionPersistenceAdapter`, `LoginLockoutPersistenceAdapter`, and `PersonAddressPersistenceAdapter` (JPA); `BCryptPasswordHasher`; `JwtTokenIssuer`; `SecureRandomResetCodeGenerator`; `EmailResetCodeNotifier`, `LoggingResetCodeNotifier`, and `UndeliveredResetCodeNotifier`; `InMemoryResetAttemptCounter`; `RabbitDomainEventPublisher` and `LoggingDomainEventPublisher`. Inbound adapters: `AuthController`, `UserProfileController`, `UserAdministrationController`, `RolePermissionController`, `UserAddressController`, and `InternalUserController`. Source: `security-service/src/main/java/com/lavarapido/security/`.

6.2 customer-service

Figure 22

customer-service classes



> *Note.* `Register/Update/Remove/List/GetCustomerVehicleUseCase` abbreviates the five vehicle inbound ports. Outbound adapters: `CustomerAccountPersistenceAdapter`, `CustomerVehiclePersistenceAdapter`, and `VehicleTypePersistenceAdapter` (JPA); `SecurityServiceIdentityDirectory` (REST to security-service); `LoggingDomainEventPublisher`, which only writes events to the log. Inbound adapters: `CustomerVehicleController`, `AdminVehicleController`, `VehicleTypeController`, and `UserRegisteredListener` (RabbitMQ). Source: `lavarapido-customer-service/src/main/java/com/lavarapido/customer/`.

6.3 booking-service

Figure 23

booking-service domain model






Figure 24

booking-service application services and ports


«application service»
ScheduleService
implements ScheduleUseCase
+businessHours() : List<BusinessHour>
+updateBusinessHours(hours, actor) : List<BusinessHour>
+exceptions(from) : List<HoursException>
+createException(exception, actor) : HoursException
+bays() : List<ServiceBay>
+createBay(name, status, actor) : ServiceBay
+deleteBay(bayId, actor)
+establishment() : Establishment
+updateEstablishment(establishment, actor) : Establishment
+history() : List<ScheduleHistoryEntry>
«interface»
BookingRepository
+lockSchedule()
+findOccupying(from, to) : List<Booking>
+save(booking, actor) : Booking
+findById(bookingId) : Optional<Booking>
+findForCustomer(userId, vehicleIds) : List<Booking>
+findStartingBetween(from, to, status) : List<Booking>
+findCancellationReason(code) : Optional<CancellationReason>
«interface»
ScheduleRepository
+findBusinessHours() : List<BusinessHour>
+saveBusinessHours(hours, actor)
+findExceptionByDate(date) : Optional<HoursException>
+recordHistory(entityType, title, detail, actor)
«interface»
BayRepository
+findAll() : List<ServiceBay>
+insert(name, status, actor) : ServiceBay
+softDelete(bayId, actor, now)
«application service»
BookingService
implements BookingUseCase
+availability(date, vehicleTypeId, serviceIds, excludeBookingId) : DayAvailability
+create(request, caller) : BookingView
+reschedule(bookingId, request, caller) : BookingView
+cancel(bookingId, reasonCode, caller) : BookingView
+changeStatus(bookingId, status, reasonCode, caller) : BookingView
+mine(caller) : List<BookingView>
+list(from, to, status, caller) : List<BookingView>
+operatorDay(date, to, caller) : List<BookingView>
+operatorAdvance(bookingId, status, caller) : BookingView
+cancellationReasons() : List<CancellationReason>
+daySummary(date, caller) : DaySummary
+getForService(bookingId) : BookingView
+listForService(from, to) : List<BookingView>
«interface»
CustomerDirectory
+ownVehicle(vehicleId) : Optional<VehicleSnapshot>
+ownVehicles() : List<VehicleSnapshot>
+vehiclesByIds(vehicleIds) : Map
«interface»
CatalogRepository
+findServices(includeInactive) : List<CatalogItem>
+findServicesByIds(serviceIds) : List<CatalogItem>
+insertService(code, name, description, categoryId, loyaltyPoints, actor) : int
+replacePrices(serviceId, prices, today, actor, now)
«application service»
CatalogService
implements CatalogUseCase
+categories() : List<ServiceCategory>
+services(includeInactive, vehicleTypeId) : List<CatalogItem>
+create(command, actor) : CatalogItem
+update(serviceId, command, actor) : CatalogItem
+setActive(serviceId, active, actor) : CatalogItem
+delete(serviceId, actor)
«interface»
DomainEventPublisher
+publish(event)
«domain service»
AvailabilityPolicy
«value object»
BookingSettings
+ZoneId zone
+int slotMinutes
+int maxDaysAhead




> *Note.* Outbound adapters: `BookingPersistenceAdapter`, `CatalogPersistenceAdapter`, `SchedulePersistenceAdapter`, and `BayPersistenceAdapter` (JPA); `CustomerServiceDirectory` (REST to customer-service); `RabbitDomainEventPublisher` and `LoggingDomainEventPublisher`. Inbound adapters: `BookingController`, `AdminBookingController`, `OperatorBookingController`, `CatalogController`, `ScheduleController`, and `InternalBookingController` (`/internal/v1/bookings`, with `X-Internal-Key`). Source: `lavarapido-booking-service/src/main/java/com/lavarapido/booking/`.

6.4 operations-service

Figure 25


operations-service classes


«aggregate root»
ServiceExecution
-Long id
-long bookingServiceId
-int operatorId
-ExecutionStatus status
-Instant startedAt
-Instant finishedAt
-Short rating
-String comment
-Instant ratedAt
-boolean commentVisible
+assign(bookingServiceId, operatorId) : ServiceExecution
+reassign(newOperatorId)
+start(now)
+finish(now)
+rate(stars, text, now)
«enumeration»
ExecutionStatus
PENDING
IN_PROGRESS
PAUSED
COMPLETED
WITH_ISSUE
operatorId
«interface»
ExecutionRepository
+findByLineIds(bookingServiceIds) : List<ServiceExecution>
+findByOperator(operatorId) : List<ServiceExecution>
+findRated(operatorId) : List<ServiceExecution>
+saveAll(executions, actor) : List<ServiceExecution>
«interface»
BookingDirectory
+forAdmin(bookingId) : Optional<BookingSnapshot>
+forOperator(from, to) : List<BookingSnapshot>
+forCustomer(bookingId) : Optional<BookingSnapshot>
+forService(bookingId) : Optional<BookingSnapshot>
+forService(from, to) : List<BookingSnapshot>
+advance(bookingId, status)
«aggregate root»
Operator
-Integer id
-long userId
-LocalDate hiredOn
-boolean active
+provision(userId, today) : Operator
+setActive(value)
«value object»
WeeklyAvailability
+short dayOfWeek
+LocalTime startsAt
+LocalTime endsAt
+covers(start, end) : boolean
0..
1
«value object»
Absence
+Integer id
+Instant startsAt
+Instant endsAt
+String reason
+overlaps(start, end) : boolean
0..
1
«interface»
UserDirectory
+operators() : List<UserSnapshot>
+firstNameOf(userId) : String
+contactOf(userId) : Optional<ContactSnapshot>
«interface»
DomainEventPublisher
+publish(event)
«application service»
OperationsService
implements OperationsUseCase
+operators() : List<OperatorView>
+setActive(operatorId, active, adminId) : OperatorView
+setAvailability(operatorId, week, adminId) : OperatorView
+addAbsence(operatorId, startsAt, endsAt, reason, adminId) : Absence
+removeAbsence(operatorId, absenceId, adminId)
+assign(bookingId, operatorId, adminId) : AssignmentView
+candidates(bookingId) : List<CandidateView>
+myServices(from, to, operatorUserId) : List<OperatorServiceView>
+start(bookingId, operatorUserId) : OperatorServiceView
+finish(bookingId, operatorUserId) : OperatorServiceView
+rate(bookingId, rating, comment, customerUserId) : RatingView
+myRatings(operatorUserId) : List<RatingView>
+autoAssign(bookingId, customerUserId, preferredOperatorId) : Optional<AssignmentView>
+availableOperators(date, time, minutes) : List<AvailableOperatorView>
+metrics(operatorId, weekOf) : OperatorWeekMetrics
+teamSummary(weekOf) : TeamSummary
+myBookingOperators() : List<BookingOperatorView>
«domain service»
AssignmentPolicy
+check(operator, week, absences, booking, busyWith)
+blockingReason(operator, week, absences, booking, busyWith) : String
«interface»
OperatorRepository
+findAll() : List<Operator>
+findByUserId(userId) : Optional<Operator>
+save(operator, actor) : Operator
+availability(operatorId) : List<WeeklyAvailability>
+replaceAvailability(operatorId, week, actor)
+absences(operatorId, from, to) : List<Absence>
+addAbsence(operatorId, absence, actor) : Absence
«value object»
BookingSnapshot
+long id
+String code
+String status
+Instant scheduledStart
+Instant scheduledEnd
+Long ownerUserId
+lineIds() : List<Long>
+overlaps(other) : boolean
«domain service»
StartPolicy
+startableAt(booking) : Instant
+check(booking, now)
«application service»
OperatorProfileService
implements OperatorProfileUseCase
+profiles() : List<OperatorProfileView>
+updateProfile(operatorId, specialty, skills, adminId) : OperatorProfileView
«domain service»
AutoAssignmentPolicy
+choose(available, preferredOperatorId) : Optional<Integer>
«event»
ExecutionEvent
+Type type
+long bookingId
+Long operatorUserId
«interface»
OperatorProfileRepository
+findAll() : Map<Integer, OperatorProfile>
+replace(operatorId, profile, actor)
«value object»
OperatorProfile
+String specialty
+List<Skill> skills
+of(specialty, skills) : OperatorProfile

> *Note.* Outbound adapters: `OperatorPersistenceAdapter`, `ExecutionPersistenceAdapter`, `OperatorProfilePersistenceAdapter`, and `InspectionPersistenceAdapter` (JPA); `BookingServiceDirectory` (REST to booking-service, with the user's token or the internal key); `SecurityUserDirectory` (REST to security-service); `RabbitDomainEventPublisher` and `LoggingDomainEventPublisher`. Inbound adapters: `OperationsControllers` (administrator, operator, and rating routes), `AvailableOperatorsController`, `OperatorProfileController`, `InspectionControllers`, and `BookingConfirmedListener` (RabbitMQ, automatic assignment). Source: `lavarapido-operations-service/src/main/java/com/lavarapido/operations/`.

Figure 26

Inspection report in operations-service



> *Note.* The report only exists for bookings of 180 minutes or more, can be edited while the booking is Confirmed or In progress, and can only be shared once published; the public link uses `publicToken` and shows a masked license plate. Adapters: `InspectionPersistenceAdapter` (JPA) and `InspectionControllers` (`/admin/inspections/**` and `/public/inspections/**` routes).

6.5 payment-service (.NET)

Figure 27

payment-service domain model





Figure 28

payment-service application services and ports


«interface»
IPaymentRepository
+GetByIdAsync(id, ct)
+HasApprovedPaymentAsync(bookingId, ct)
+IsTransactionReferenceUsedElsewhereAsync(reference, bookingId, ct)
+ListAsync(status, ct)
«application service»
BookingPaymentGuard
+EnsureBookingIsUnpaidAsync(booking, allowOpenPayment, ct)
+EnsureNoApprovedPaymentAsync(bookingId, ct)
+EnsureReferenceNotReusedAsync(transactionReference, bookingId, ct)
«application service»
PaymentAccountService
implements IPaymentAccountUseCases
+ListForCustomersAsync(ct)
+ListAllAsync(ct)
+ListMethodsAsync(ct)
+CreateAsync(command, ct)
+UpdateAsync(id, command, ct)
«interface»
IUnitOfWork
+CommitAsync(ct)
«application service»
PaymentCommandService
implements IPaymentCommandUseCases
+ReportAsync(command, caller, ct) : PaymentDto
+RegisterInPersonAsync(command, admin, ct) : PaymentDto
+ApproveAsync(paymentId, admin, ct) : PaymentDto
+RejectAsync(paymentId, reason, admin, ct) : PaymentDto
+RefundAsync(paymentId, admin, ct) : PaymentDto
«interface»
IBookingDirectory
+GetForCustomerAsync(bookingId, ct) : BookingInfo
+GetForAdminAsync(bookingId, ct) : BookingInfo
+MineAsync(ct)
«application service»
PaymentQueryService
implements IPaymentQueryUseCases
+MineAsync(ct)
+MyBookingsAsync(ct)
+ListAsync(status, ct)
+GetAsync(paymentId, ct)
+AmountDueAsync(bookingId, ct)
«interface»
IPaymentAccountRepository
+ListAsync(ct)
+GetByIdAsync(id, ct)
+ListMethodTypesAsync(ct)
«interface»
IIntegrationEventPublisher
+PublishAsync(integrationEvent, ct)
«application service»
PromotionAdminService
implements IPromotionAdminUseCases
+ListAsync(ct)
+MetricsAsync(ct)
+CreateAsync(command, ct)
+UpdateAsync(id, command, ct)
+SetActiveAsync(id, active, ct)
+DeleteAsync(id, admin, ct)
«interface»
IPromotionRedemptionRepository
+ExistsAsync(bookingId, promotionId, ct)
+CountByCustomerAsync(promotionId, customerUserId, ct)
+AppliedDiscountTotalAsync(bookingId, ct)
«application service»
CustomerPromotionService
implements ICustomerPromotionUseCases
+ListAvailableAsync(caller, ct)
+RedeemAsync(command, caller, ct) : RedeemPromotionResultDto
«application service»
AmountDueCalculator
+ForAsync(booking, ct) : decimal
+BreakdownAsync(booking, ct) : AmountDueDto
«application service»
LoyaltyService
implements ILoyaltyUseCases
+BalanceAsync(caller, ct) : LoyaltyBalanceDto
«interface»
ILoyaltyLedgerRepository
+CurrentBalanceAsync(customerId, ct) : LoyaltyBalance
+NetPointsByCustomerForBookingAsync(bookingId, ct)
«application service»
LoyaltyRewardService
+CreditForBookingAsync(booking, actor, nowUtc, ct)
+RevokeForBookingAsync(bookingId, actor, nowUtc, ct)
«interface»
IPromotionRepository
+ListAsync(ct)
+GetByCodeAsync(code, ct)
+ExistsCodeAsync(code, ct)

> *Note.* In .NET, attributes are public read-only properties and application methods are asynchronous (`Async`) and take a `CancellationToken ct`. Outbound adapters: `PaymentRepository`, `PaymentAccountRepository`, `PromotionRepository`, `PromotionRedemptionRepository`, `LoyaltyLedgerRepository`, and `EfUnitOfWork` (Entity Framework Core); `BookingServiceDirectory` (REST to booking-service); `RabbitMqIntegrationEventPublisher` and `NullIntegrationEventPublisher`. Inbound adapters: `PaymentsController`, `AdminPaymentsController`, `AdminPaymentAccountsController`, `PromotionsController`, and `LoyaltyController`. Source: `lavarapido-payment-service/src/PaymentService.Domain` and `PaymentService.Application`.

6.6 notification-service


Figure 29

notification-service domain model



Figure 30

notification-service application services and ports



Note. Between application services the real dependency is the inbound port: for example, `DomainEventConsumerService` receives a `SendNotificationUseCase`, implemented by `NotificationSendingService`. `NotificationTypeCode` has 23 codes; the diagram shows only some. Outbound adapters: `NotificationPersistenceAdapter`, `DeviceTokenPersistenceAdapter`, `BookingReminderPersistenceAdapter`, `BookingTrackingPersistenceAdapter`, and `ProcessedEventPersistenceAdapter` (JPA); `SmtpEmailSender` and `LoggingEmailSender`; `ExpoPushSender` and `LoggingPushSender`; `SecurityServiceUserContactDirectory` (internal REST to security-service). Inbound adapters: `NotificationController`, `AdminNotificationController`, `DeviceController`, `DomainEventListener` (RabbitMQ), and `ReminderScheduler` (scheduled job). Source: `lavarapido-notification-service/src/main/java/com/lavarapido/notification/`.

6.7 States of the Main Entities

Table 67

State transitions allowed by the domain

Entity	Transition	Condition (code)
Booking	SCHEDULED → CONFIRMED	Has a bay assigned (`Booking.java:110`)
Booking	CONFIRMED → IN_PROGRESS or NO_SHOW	`Booking.java:111`
Booking	IN_PROGRESS → COMPLETED	`Booking.java:112`
Booking	→ CANCELLED	Only through `cancel(reason)`, not `moveTo` (`Booking.java:95, 113`)
Execution	PENDING → IN_PROGRESS → COMPLETED	`start()` and `finish()` (`ServiceExecution.java:65-80`)
Execution	Rating	Only when COMPLETED and only once (`ServiceExecution.java:82-90`)
Payment	Created → in review → approved, rejected, or refunded	Methods `SubmitForReview`, `Approve`, `Reject`, `Refund` (`Payment.cs:116-157`)
Execution	Start	Only from 15 minutes before the booking time (`StartPolicy.java`)
Account	Locked for 15 minutes	On the fifth failure within 15 minutes; a correct sign-in or a password reset clears it (`LoginLockout.java`)
Inspection report	Draft → published	`publish()`; only a published report can be shared (`InspectionReport.java`)
Inspection phase	PENDING ↔ IN_PROGRESS ↔ DONE	`setPhaseStatus()`; a finding in a pending phase moves it to IN_PROGRESS (`InspectionReport.java`)

7. Design Findings and Open Items

Table 68

Inconsistencies found when comparing the code with earlier documentation

#	Finding	Evidence
1	Technical Manual v2.0 says all six microservices are in Java 21; payment-service is in .NET 8	`lavarapido-payment-service/Directory.Build.props` (`net8.0`)
2	`MODELO-DE-DATOS.md` documented 43 tables and SRS v4 (Table 6) said 47; the changelogs create 57 as of October 15, 2026	Table 9 of this document
3	notification subscribes to `booking.created`, but booking only publishes `booking.confirmed` and `booking.cancelled`	`BookingEvent.java:17-18` and notification's `ROUTING_KEYS`

#	Finding	Evidence
4	customer defines the `customer.provisioned`, `VehicleRegistered`, `VehicleUpdated`, `VehicleRemoved`, and `LoyaltyPointsChanged` events, but its only publisher writes them to the log: they never reach RabbitMQ and have no consumer	`CustomerProvisioned.java:15`, `customer/.../adapter/out/messaging/LoggingDomainEventPublisher.java`
5	Vehicle inspection, its public report, and the business data in Settings are simulated: they are stored in the browser, not in the backend	`Web/src/app/core/services/inspection-store.ts:20`, `features/admin/services/business-store.ts:52`; on mobile `scheduleMock.ts`, `settingsMock.ts`
6	In `docker-compose.yml`, the security and operations builds point to `../lavarapido-security-service` and `../lavarapido-operation-service`, which are the real repository names. In this local copy the folders are named `security-service` and `lavarapido-operations-service`, so `--profile app` fails unless they are cloned with their original names.	`Backend/lavarapido-infra/docker-compose.yml` (security-service and operations-service)
7	booking-service contains a `bin/src/main/java` folder in addition to `src/main/java` (an IDE-generated copy)	`Backend/lavarapido-booking-service/bin`
8	The cash account is not returned by `GET /payment-accounts` (only accounts that require a receipt); the web and mobile clients add it themselves. It is intentional, but the contract does not document it	`PaymentAccountService.cs:24-25`, `Web/.../client/pages/payment/payment.ts:44-57`
9	Hard-coded test text in the UI: "¡Hola, Laura!" on the administrator dashboard and "Laura Méndez" in payment review	`admin/pages/dashboard/dashboard.ts:73`, `payment-review-modal.html:167`
10	In the operator's "Assigned services" (web), the Customer column shows the license plate	`operator/pages/assigned-services/assigned-services.ts:141`
11	The brand name is inconsistent across clients ("AquaWash", "Car Wash", "Lavado Vehicular", "Express Car Wash") and the landing page advertises a "mobile service… wherever you are", although SRS v4 defines a single location	Figures 2 and 7

Note. Code review of October 15, 2026: finding 5 is fixed (the inspection report, its public link, and the business data are stored in operations-service and booking-service; on mobile, `settingsMock.ts`

> only keeps the initial notification preferences) and so is finding 7 (`bin/` is now in booking-service's `.gitignore`). Findings 3, 4, 8, 9, 10, and 11 are still in the code.

References

Angular. (n.d.). *Angular documentation*. Google. Retrieved October 9, 2026, from https://angular.dev/

Brown, S. (n.d.). *The C4 model for visualising software architecture*. Retrieved October 9, 2026, from https://c4model.com/

Cockburn, A. (2005). *Hexagonal architecture*. https://alistair.cockburn.us/hexagonal-architecture/

Evans, E. (2004). *Domain-driven design: Tackling complexity in the heart of software*. Addison-Wesley.

Expo. (n.d.). *Expo documentation*. Retrieved October 9, 2026, from https://docs.expo.dev/

Fowler, M. (2002). *Patterns of enterprise application architecture*. Addison-Wesley.

Gamma, E., Helm, R., Johnson, R., & Vlissides, J. (1994). *Design patterns: Elements of reusable object-oriented software*. Addison-Wesley.

Hohpe, G., & Woolf, B. (2003). *Enterprise integration patterns: Designing, building, and deploying messaging solutions*. Addison-Wesley.

Liquibase. (n.d.). *Liquibase documentation*. Retrieved October 9, 2026, from https://docs.liquibase.com/

Mermaid. (n.d.). *Mermaid: Diagramming and charting tool*. Retrieved October 9, 2026, from https://mermaid.js.org/

Microsoft. (n.d.-a). *.NET documentation*. Retrieved October 9, 2026, from https://learn.microsoft.com/dotnet/

Microsoft. (n.d.-b). *SQL Server technical documentation*. Retrieved October 9, 2026, from https://learn.microsoft.com/sql/sql-server/

Newman, S. (2021). *Building microservices: Designing fine-grained systems* (2nd ed.). O'Reilly Media.

RabbitMQ. (n.d.). *RabbitMQ documentation*. Broadcom. Retrieved October 9, 2026, from https://www.rabbitmq.com/docs

React Native. (n.d.). *React Native documentation*. Meta Platforms. Retrieved October 9, 2026, from https://reactnative.dev/docs/getting-started

Spring. (n.d.). *Spring Boot reference documentation*. Broadcom. Retrieved October 9, 2026, from https://docs.spring.io/spring-boot/