

Package ‘BIGr’

June 12, 2024

Title (B)reeding (I)nsight (G)enomics Functions for Polyploid and Diploid Species

Version 0.2.0

Description This package contains the functions developed to analyze polyploid and diploid species within Breeding Insight.

License `use_apache_license()`

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Depends R (>= 4.0.0)

Imports doParallel,
dplyr,
foreach,
Rdpack (>= 0.7),
readr (>= 2.1.5),
reshape2 (>= 1.4.4),
tidyr (>= 1.3.1)

RdMacros Rdpack

R topics documented:

calculate_Het	2
calculate_MAF	2
capture_diversity.Gmat	3
check_ped	4
dosage2vcf	5
dosage_ratios	6
flip_dosage	6
get_countsMADC	7
updog2vcf	7
Index	9

`calculate_Het`*Calculate Observed Heterozygosity from a Genotype Matrix*

Description

This function calculates the observed heterozygosity from a genotype matrix. It assumes that the samples are the columns, and the genomic markers are in rows. Missing data should be set as NA, which will then be ignored for the calculations. All samples must have the same ploidy.

Usage

```
calculate_Het(geno, ploidy)
```

Arguments

<code>geno</code>	Genotype matrix or data.frame
<code>ploidy</code>	The ploidy of the species being analyzed

Value

A dataframe of observed heterozygosity values for each sample

`calculate_MAF`*Calculate Minor Allele Frequency from a Genotype Matrix*

Description

This function calculates the allele frequency and minor allele frequency from a genotype matrix. It assumes that the Samples are the columns, and the genomic markers are in rows. Missing data should be set as NA, which will then be ignored for the calculations. All samples must have the same ploidy.

Usage

```
calculate_MAF(df, ploidy)
```

Arguments

<code>df</code>	Genotype matrix or data.frame
<code>ploidy</code>	The ploidy of the species being analyzed

Value

A dataframe of AF and MAF values for each marker

capture_diversity.Gmat

Estimate Minimum Number of Individuals to Sample to Capture Population Genomic Diversity (Genotype Matrix)

Description

This function can be used to estimate the number of individuals to sample from a population in order to capture a desired percentage of the genomic diversity. It assumes that the samples are the columns, and the genomic markers are in rows. Missing data should be set as NA, which will then be ignored for the calculations. All samples must have the same ploidy. This function was adapted from a previously developed Python method (Sandercock et al., 2023) (https://github.com/alex-sandercock/Capturing_genomic_diversity/)

Usage

```
capture_diversity.Gmat(
  df,
  ploidy,
  r2_threshold = 0.9,
  iterations = 10,
  sample_list = NULL,
  parallel = FALSE,
  batch = 1,
  save.result = TRUE
)
```

Arguments

df	Genotype matrix or data.frame with the count of alternate alleles (0=homozygous reference, 1 = heterozygous, 2 = homozygous alternate)
ploidy	The ploidy of the species being analyzed
r2_threshold	The ratio of diversity to capture (default = 0.9)
iterations	The number of iterations to perform to estimate the average result (default = 10)
sample_list	The list of samples to subset from the dataset (optional)
parallel	Run the analysis in parallel (True/False) (default = FALSE)
save.result	Save the results to a .txt file? (default = TRUE)

Value

A data.frame with minimum number of samples required to match or exceed the input ratio

References

Sandercock, A. M., Westbrook, J. W., Zhang, Q., & Holliday, J. A. (2023). The road to restoration: Identifying and conserving the adaptive legacy of American chestnut. bioRxiv, 2023-05.

check_ped

*Evaluate Pedigree File for Accuracy***Description**

Check a pedigree file for accuracy and output suspected errors

Usage

```
check_ped(ped.file)
```

Arguments

ped.file path to pedigree text file. The pedigree file is a 3-column pedigree tab separated file with columns labeled as id sire dam in any order

Details

check_ped takes a 3-column pedigree tab separated file with columns labeled as id sire dam in any order and checks for:

- Ids that appear more than once in the id column
- Ids that appear in both sire and dam columns
- Direct (e.g. parent is a offspring of his own daughter) and indirect (e.g. a great grandparent is son of its granchild) dependencies within the pedigree.
- Individuals included in the pedigree as sire or dam but not on the id column and reports them back with unknown parents (0).

When using check_ped, do a first run to check for repeated ids and parents that appear as sire and dam. Once these errors are cleaned run the function again to check for dependencies as this will provide the most accurate report.

Note: This function does not change the input file but prints any errors found in the console.

Value

A list of dataframes of error types, and the output printed to the console

Examples

```
##Get list with a dataframe for each error type
ped_errors <- check_ped(ped.file = "example_ped.txt")

##Access the "messy parents" dataframe result
ped_errors$messy_parents

##Get list of sample IDs with messy parents error
messy_parent_ids <- ped_errors$messy_parents$id
print(messy_parent_ids)
```

`dosage2vcf`*Convert DArTag Dosage and Counts to VCF*

Description

This function will convert the DArT Dosage Report and Counts files to VCF format

Usage

```
dosage2vcf(dart.report, dart.counts, ploidy, output.file)
```

Arguments

<code>dart.report</code>	Path to the DArT dosage report .csv file. Typically contains "Dosage Report" in the file name.
<code>dart.counts</code>	Path to the DArT counts .csv file. Typically contains "Counts" in the file name.
<code>ploidy</code>	The ploidy of the species being analyzed
<code>output.file</code>	output file name and path

Details

This function will convert the Dosage Report and Counts files from DArT into a VCF file. These two files are received directly from DArT for a given sequencing project. The output file will be saved to the location and with the name that is specified. The VCF format is v4.3

Value

A vcf file

Examples

```
## Use file paths for each file on the local system

#The files are directly from DArT for a given sequencing project. The are labeled with Dosage_Report or Counts in

dosage2vcf(dart.report = "example_dart_Dosage_Report.csv",
           dart.counts = "example_dart_Counts.csv",
           ploidy = 2,
           output.file = "name_for_vcf")

##The function will output the converted VCF using information from the DArT files
```

dosage_ratios	<i>Calculate the Percentage of Each Dosage Value</i>
---------------	--

Description

This function calculates the percentage of each dosage value within a genotype matrix. It assumes that the samples are the columns, and the genomic markers are in rows. Missing data should be set as NA, which will then be ignored for the calculations. All samples must have the same ploidy.

Usage

```
dosage_ratios(matrix_data, ploidy)
```

Arguments

ploidy	The ploidy of the species being analyzed
df	Genotype matrix or data.frame

Value

A data.frame with percentages of dosage values in the genotype matrix

flip_dosage	<i>Switch Dosage Values from a Genotype Matrix</i>
-------------	--

Description

This function converts the dosage count values to the opposite value. This is primarily used when converting dosage values from reference based (0 = homozygous reference) to alternate count based (0 = homozygous alternate). It assumes that the Samples are the columns, and the genomic markers are in rows. Missing data should be set as NA, which will then be ignored for the calculations. All samples must have the same ploidy.

Usage

```
flip_dosage(df, ploidy, is_reference = TRUE)
```

Arguments

df	Genotype matrix or data.frame
ploidy	The ploidy of the species being analyzed

Value

A genotype matrix

get_countsMADC	<i>Obtain Read Counts from MADC File</i>
----------------	--

Description

This function takes the MADC file as input and retrieves the ref and alt counts for each sample, and converts them to ref, alt, and size(total count) matrices for dosage calling tools. At the moment, only the read counts for the Ref and Alt target loci are obtained while the additional loci are ignored.

Usage

```
get_countsMADC(madc_file)
```

Arguments

madc_file	Path to MADC file
-----------	-------------------

Value

A list of read count matrices for reference, alternate, and total read count values

updog2vcf	<i>Export Updog Results as VCF</i>
-----------	------------------------------------

Description

This function will convert an Updog output to a VCF file

Usage

```
updog2vcf(multidog.object, ploidy, output.file)
```

Arguments

multidog.object	updog output object with class "multidog" from dosage calling
ploidy	The ploidy of the species being analyzed
output.file	output file name and path

Details

When performing dosage calling for multiple SNPs using Updog, the output file contains information for all loci and all samples. This function will convert the updog output file to a VCF file, while retaining the information for the values that are commonly used to filter low quality and low confident dosage calls.

Value

A vcf file

References

Updog R package

Index

`calculate_Het`, [2](#)
`calculate_MAF`, [2](#)
`capture_diversity.Gmat`, [3](#)
`check_ped`, [4](#)

`dosage2vcf`, [5](#)
`dosage_ratios`, [6](#)

`flip_dosage`, [6](#)

`get_countsMADC`, [7](#)

`updog2vcf`, [7](#)