





User Authentication within Groups

Britta Hale

Based on joint work with Benjamin Dowling


*The views expressed are those of the author and do not reflect the official policy or position of the Department of Defense or the U.S. Government.






Note that the long-term identity keys used by the protocol MUST be distributed by an "honest" authentication service for clients to authenticate their legitimate peers.

[[OPEN ISSUE: Signatures under the identity keys, while simple, have the side-effect of preclude deniability. We may wish to allow other options, such as (ii) a key chained off of the identity key, or (iii) some other key obtained through a different manner, such as a pairwise channel that provides deniability for the message contents.]]



```
init_secret_[n-1] (or 0)
|
V
update_secret -> HKDF-Extract = epoch_secret
|
+--> Derive-Secret(., "sender data", GroupContext_[n])
|    = sender_data_secret
|
+--> Derive-Secret(., "handshake", GroupContext_[n])
|    = handshake_secret
|
+--> Derive-Secret(., "app", GroupContext_[n])
|    = application_secret
|
+--> Derive-Secret(., "confirm", GroupContext_[n])
|    = confirmation_key
|
V
Derive-Secret(., "init", GroupContext_[n])
|
V
init_secret_[n]
```

Lessons from Signal Authentication






Epoch-Level Authentication



Modified Device-to-User Signal Authentication





New QR-code computation:

$$\text{fprint}^{i-1} = \text{HMAC}(ak^{i-1}, H^{i-1} || \text{fvers} || \text{role})$$
$$\text{fprint}^i = \text{HMAC}(ak^i, H^i || \text{fvers} || \text{role})$$

*Session specific

*Asynchronicity in computation





Achievable Guarantees

Auth. Initiator I	Auth. Responder I'	CD Without E.	CD with E.	CU Without E.	CU With E.
Display match	Display match	✓	✓	✓	X
Display match	Scan match	✓	✓	X	X
Scan match	Display match	✓	✓	✓	X
Scan match	Scan match	✓	✓	✓	X
Display non-match	Scan non-match	✓	✓	X	X
Scan non-match	Display non-match	✓	✓	✓	✓
Scan non-match	Scan non-match	✓	✓	✓	✓

CD: Compromised Device

CU: Compromised User

E: Eavesdropper





```
init_secret_[n-1] (or 0)
|
V
update_secret -> HKDF-Extract = epoch_secret
|
+--> Derive-Secret(., "sender data", GroupContext_[n])
|    = sender_data_secret
|
+--> Derive-Secret(., "handshake", GroupContext_[n])
|    = handshake_secret
|
+--> Derive-Secret(., "app", GroupContext_[n])
|    = application_secret
|
+--> Derive-Secret(., "confirm", GroupContext_[n])
|    = confirmation_key
|
V
Derive-Secret(., "init", GroupContext_[n])
|
V
init_secret_[n]
```



Epoch-Level Authentication
Group-Level Authentication


For Group
Membership Auth

Group Auth
Key



For Group
Membership Auth

Group Auth
Key



For Entity Auth? ← SigKeyA

Entity Auth breaks under static long-term SigKey