Term Project #1(part 1).py | Term Project #1(part 2).py

```python
from LinkedStack import LinkedStack


1 usage  new *
class Deque:

    new *
    def __init__(self):
        """Create an empty deque."""
        self._left_stack = LinkedStack()
        self._right_stack = LinkedStack()

    new *
    def is_empty(self):
        """Return True if the deque is empty."""
        return self._left_stack.is_empty() and self._right_stack.is_empty()

    new *
    def __len__(self):
        """Return the number of elements in the deque."""
        return len(self._left_stack) + len(self._right_stack)

    2 usages  new *
    def add_first(self, e):
        """Add an element to the front of the deque."""
        self._left_stack.push(e)

    2 usages  new *
    def add_last(self, e):
        """Add an element to the back of the deque."""
        self._right_stack.push(e)

    2 usages  new *
    def remove_first(self):
        """Remove and return the element at the front of the deque."""
        if self._left_stack.is_empty():
            while not self._right_stack.is_empty():
                self._left_stack.push(self._right_stack.pop())
        if self._left_stack.is_empty():
            raise Exception('Deque is empty')
        return self._left_stack.pop()
```

Term Project #1(part 1).py × Term Project #1(part 2).py

```
35          def remove_last(self):
36              """Remove and return the element at the back of the deque."""
37              if self._right_stack.is_empty():
38                  while not self._left_stack.is_empty():
39                      self._right_stack.push(self._left_stack.pop())
40              if self._right_stack.is_empty():
41                  raise Exception('Deque is empty')
42              return self._right_stack.pop()
43
            new *
44          def first(self):
45              """Return but do not remove the element at the front of the deque."""
46              if self._left_stack.is_empty():
47                  while not self._right_stack.is_empty():
48                      self._left_stack.push(self._right_stack.pop())
49              if self._left_stack.is_empty():
50                  raise Exception('Deque is empty')
51              return self._left_stack.top()
52
            new *
53          def last(self):
54              """Return but do not remove the element at the back of the deque."""
55              if self._right_stack.is_empty():
56                  while not self._left_stack.is_empty():
57                      self._right_stack.push(self._left_stack.pop())
58              if self._right_stack.is_empty():
59                  raise Exception('Deque is empty')
60              return self._right_stack.top()
61
        1 usage  new *
62      def test_deque():
63          deque = Deque()
64          print("Is deque empty?", deque.is_empty())
65          print("Length of deque:", len(deque))
66          deque.add_first(10)
67          deque.add_last(20)
68          deque.add_first(5)
69          deque.add_last(30)
70          print("After adding elements:")
71          print("First element:", deque.first())
72          print("Last element:", deque.last())
```

```
1 usage  new *
def test_deque():
    deque = Deque()
    print("Is deque empty?", deque.is_empty())
    print("Length of deque:", len(deque))
    deque.add_first(10)
    deque.add_last(20)
    deque.add_first(5)
    deque.add_last(30)
    print("After adding elements:")
    print("First element:", deque.first())
    print("Last element:", deque.last())
    print("Length of deque:", len(deque))

    print("Removed first element:", deque.remove_first())
    print("Removed last element:", deque.remove_last())

    print("After removing elements:")
    print("First element:", deque.first())
    print("Last element:", deque.last())
    print("Length of deque:", len(deque))

    # Remove remaining elements
    print("Removed first element:", deque.remove_first())
    print("Removed last element:", deque.remove_last())

    print("Is deque empty?", deque.is_empty())
    print("Length of deque:", len(deque))

if __name__ == "__main__":
    test_deque()
```

Term Project #1(part 1).py Term Project #1(part 2).py

```python
from LinkedStack import LinkedStack
from LinkedQueue import LinkedQueue

1 usage  new *
class Deque:
    """Double-ended queue implementation using a stack and a queue."""

    new *
    def __init__(self):
        """Create an empty deque."""
        self._stack = LinkedStack()
        self._queue = LinkedQueue()

    new *
    def is_empty(self):
        """Return True if the deque is empty."""
        return self._stack.is_empty() and self._queue.is_empty()

    new *
    def __len__(self):
        """Return the number of elements in the deque."""
        return len(self._stack) + len(self._queue)

    2 usages  new *
    def add_first(self, e):
        """Add an element to the front of the deque."""
        self._stack.push(e)

    2 usages  new *
    def add_last(self, e):
        """Add an element to the back of the deque."""
        self._queue.enqueue(e)

    2 usages  new *
    def remove_first(self):
        """Remove and return the element at the front of the deque."""
        if self._stack.is_empty():
            if self._queue.is_empty():
                raise Exception('Deque is empty')
            while not self._queue.is_empty():
```

Term Project #1(part 1).py Term Project #1(part 2).py

```
            while not self._queue.is_empty():
                self._stack.push(self._queue.dequeue())
        return self._stack.pop()

    2 usages  new *
    def remove_last(self):
        """Remove and return the element at the back of the deque."""
        if self._queue.is_empty():
            if self._stack.is_empty():
                raise Exception('Deque is empty')
            while not self._stack.is_empty():
                self._queue.enqueue(self._stack.pop())
        return self._queue.dequeue()

    new *
    def first(self):
        """Return but do not remove the element at the front of the deque."""
        if self._stack.is_empty():
            if self._queue.is_empty():
                raise Exception('Deque is empty')
            while not self._queue.is_empty():
                self._stack.push(self._queue.dequeue())
        return self._stack.top()

    new *
    def last(self):
        """Return but do not remove the element at the back of the deque."""
        if self._queue.is_empty():
            if self._stack.is_empty():
                raise Exception('Deque is empty')
            while not self._stack.is_empty():
                self._queue.enqueue(self._stack.pop())
        return self._queue.first()

1 usage  new *
def test_deque():
    deque = Deque()

    print(deque.is_empty())
    print(len(deque))
```

Deque › is_empty()

```
1 usage  new *
def test_deque():
    deque = Deque()

    print(deque.is_empty())
    print(len(deque))

    deque.add_first(10)
    deque.add_last(20)
    deque.add_first(5)
    deque.add_last(30)

    print("After adding elements:")
    print(deque.first())
    print(deque.last())
    print(len(deque))
    print(deque.remove_first())
    print(deque.remove_last())

    print("After removing elements:")
    print(deque.first())
    print(deque.last())
    print(len(deque))

    print(deque.remove_first())
    print(deque.remove_last())

    print(deque.is_empty())
    print(len(deque))
if __name__ == "__main__":
    test_deque()
```

```
Z:\DSALG01-1DB2\venv\Scripts\python.exe "Z:\DSALG01-1DB2\FINALS\Activities\Term Project #1(part 1).py"
Is deque empty? True
Length of deque: 0
After adding elements:
First element: 5
Last element: 30
Length of deque: 4
Removed first element: 5
Removed last element: 30
After removing elements:
First element: 10
Last element: 20
Length of deque: 2
Removed first element: 10
Removed last element: 20
Is deque empty? True
Length of deque: 0

Process finished with exit code 0
```

```
Z:\DSALG01-1DB2\venv\Scripts\python.exe "Z:\DSALG01-1DB2\FINALS\Activities\Term Project #1(part 2).p
True
0
After adding elements:
5
20
4
5
20
After removing elements:
10
30
2
10
30
True
0

Process finished with exit code 0
```