

What is D³NS

Distributed Decentralized Domain Name Service

- The goal is to create a secure, distributed DNS
- Requirements:
 - Decentralization
 - Authentication
 - Backwards Compatible

Motivation

- Recent events have demonstrated that centralized authorities are not as secure as previously hoped
 - There is little cryptographic protection against the subpoena
 - Poorly constructed laws targeting DNS
 - SOPA and PIPA would have resulted in DNS blocking and compromised security
- A distributed approach for authentication is much less vulnerable



Related Work


Cox *et al.*¹ developed DDNS:

- Motivated by problem of expertise
- Fault tolerant, load-balancing, and scalable
- Easier to administer
- Found higher latencies in a P2P-based DNS
- Incentive problem – why store records for others?

¹Cox *et al.*, “Serving DNS using a Peer-to-Peer Lookup Service” in *Peer-to-Peer Systems*, pp. 155-165, Springer, 2002

Current DNS

- ICANN is the final arbiter on who owns what domain
- ICANN maintains and organizes the TLD authoritative name servers
- Third party verifiers act to authenticate DNS records




Source: ICANN

P2P-Based DNS

- The shared block chain is the final arbiter of who owns what
- The DHT organizes and maintains the authoritative TLD servers
- The block chain acts to authenticate DNS records


Components

- Domain Name Blockchain.
- Distributed Hash Table (UrDHT).
- DNS server frontend (PowerDNS)




Distributed Hash Tables

- Means of organizing communication and responsibility in a P2P network
- Each peer is responsible for a verifiable span of hash values
- Facilitates one-to-one communication and one-to-many communication



UrDHT

- Uses Voronoi regions on an n -dimensional torus to assign responsibility.
- Can define how to compute the regions to emulate almost any DHT topology.
- Node responsibility:
 - Node is responsible for its space, defined by its neighbors.
 - If a node leaves/fails, each neighbors assumes that it is responsible until corrected by maintenance.



Fault Tolerance


- Churn creates a period where I/O can fail.
- With UrDHT:
 - Reads of backed up data are successful.
 - Writes to the region are successful.
 - Reads of **new** data are vulnerable until it is backed up.
 - This means a much smaller window of vulnerability. Writes never fail.

Cool Things UrDHT Can Do

- Embed problem spaces into DHT topology
- Minimal latency based routing
- Basically turns routing into best-search first

DNS Blockchain

- Using a technique similar to Bitcoin, we can assign domain names as reward for mining new blocks and transfer domains between owners
- An 'owner' in this context is a public key
- These public keys can be used to verify stored DNS records by their signature records




Example Record

```
DATA → CNAME.CHRONUS.TLD → IN → A → 3600 → -1 → 131.96.49.89
DATA → CHRONUS.TLD → IN → A → 3600 → -1 → 131.96.49.89
DATA → CHRONUS.TLD → IN → TXT → 3600 → -1 → Hi mom!
DATA → CHRONUS.TLD → IN → CNAME → 3600 → -1 → CNAME.CHRONUS.TLD
DATA → CHRONUS.TLD → IN → NS → 3600 → -1 → CNAME.CHRONUS.TLD
DATA → CHRONUS.TLD → IN → SOA → 3600 → -1 → CNAME.CHRONUS.TLD
ADMIN.CHRONUS.TLD 2013111900 172800 900 1209600 3600
```

```
APC5"RS[EOT?ò~BELDC4~9SS2BrenÜxçi*
@ûUNBHÊ¿L/pACKjÛYDC1UýcãIU@úÉPLUNBHámS SGC1
úDC1ãeöãSPAêöNAKT
```

PowerDNS

- Well established authoritative DNS server software.
- Provides easy interface for custom applications.
- Serves the DNS requests for DHT client.



Man in the Middle In a DHT

- Need to have a distributed, reliable way to authenticate
- Given:
 - An existing network where nodes have exchanged keys securely
 - A new peer who wishes to join the network and share their public key

Prevention

- At least 2 members of the network interrogate the new peer for its public key
- Those interrogators compare their results
- If those results match:
 - The new peer creates an authentication record
 - The interrogators sign that record
 - The new record is distributed across the network
- If the results do not match:
 - An attack is detected and reported to the new peer by all authenticating servers.
 - A member of the network may make a ban of the compromised peer
 - Otherwise the joining process can be repeated.

Conclusions

- Deployable prototype of a decentralized and distributed top-level DNS
- Stronger robustness
- Fully reverse compatible
- Offers greater security
- Any organization can create their own secure verification server

Future Work

- Optimize caching
- Backup Comorbidity
- Further security measures