

Secure Computing Week Three

Functions and Arrays in PHP

Code Blocks

- Executed Server Side
- Can have HTML tags before, after or you can print HTML output from the PHP code
- Denoted by `<?php ?>`
- TO use `<? ?>` for code or `<?= ?>` for substituting the value of an expression, the `short_open_tag` option must be turned on in the `php.ini` configuration file

String Concatenation

•Java

```
•string3 = string1 + string2;
```

•PHP

- The dot (.) is the concatenation operator for strings.
- `$string3 = $string1 . $string2;`
- `$string3 .= $string4;`

<http://php.net/manual/en/language.variables.scope.php>

Calling Built In Functions

```
•$var = 6.54;  
•print ceil($var);    //7  
•print floor($var);   // 6  
•print round($var);   // 7  
•print round($var,3); // 6.543  
  
•print ord('A');      // 65  
•print strtoupper("a"); // "A"  
•print strtolower("A"); // "a"
```

Defining A function

```
function function_name ($argument1, $argument2)
{
    // function code here
    return $something;
}
```

Using include files to import functions, variables, code. The include() function works as though you were copying and pasting the outside code into you PHP block

```
include()
include_once()
require() // if file doesn't exist, the execution will stop
require_once()
```

Arrays

Declare an array in PHP

Declare a multi-dimensional Array

Use Indexed and associative arrays

Traverse arrays

An index to an array element can be a number or a string (associative array)

- Using a number as an index:

```
$users[5] = 'Oscar'; // rest are undefined
```

- Example of an associative array:

```
$users['Canada'] = 'red';
$users['Bird'] = 'yellow';
$users['America'] = '?';
```

- **Note: Unlike other languages, we didn't have to declare the array first!**