

# Undecidability

## CSCI 338

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_1$  on input  $\langle x \rangle$  :  
    └ 1. accept.
2. Construct TM  $M_2$  on input  $\langle y \rangle$  :  
    └ 1. Run  $N$  on  $\omega$  and accept if  $N$  does.
3. Run  $H$  on  $\langle M_1, M_2 \rangle$ .
4. If  $H$  accepts, accept. If  $H$  rejects, reject.

$N$  accepts  $\omega$   
 $\Updownarrow$   
 $L(M_2) = \Sigma^*$

If  $N$  accepts  $\omega$ , then  $M_1$  and  $M_2$  have the same language ( $\Sigma^*$ ). If  $N$  does not accept  $\omega$ , then they have different languages. Thus  $S$  decides  $A_{TM}$ . (bad!)

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1.

To show  $EQ_{TM}$  is undecidable,  
use it to decide  $E_{TM}$ .

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1.

We have a way ( $H$ ) to test if two TMs have the same language.

How could we use that to test if a TM's language is empty?

Plan: ?

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1.

We have a way ( $H$ ) to test if two TMs have the same language.

How could we use that to test if a TM's language is empty?

Plan: Make a TM with an empty language and use  $H$  to compare it to input to  $E_{TM}$ .

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

└ 1. reject.


# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :   $L(M_2) = ?$

1. reject.


# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :   $L(M_2) = \emptyset$   
1. reject.



# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

- 1. reject.
- 2. ?

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

1. reject.

2. Run  $H$  on  $\langle P, M_2 \rangle$ .

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

1. reject.

2. Run  $H$  on  $\langle P, M_2 \rangle$ .

3. If  $H$  accepts, \_\_\_\_\_. If  $H$  rejects, \_\_\_\_\_.

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :  
    └ 1. reject.
2. Run  $H$  on  $\langle P, M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :  
    └ 1. reject.
2. Run  $H$  on  $\langle P, M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If...?

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

    1. reject.

2. Run  $H$  on  $\langle P, M_2 \rangle$ .

3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $L(P) = \emptyset$ , ...?

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :  
    1. reject.
2. Run  $H$  on  $\langle P, M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $L(P) = \emptyset$ ,  $M_2$  and  $P$  will have the same language (since  $L(M_2) = \emptyset$ ) and...?

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :  
     $\downarrow$   
    1. reject.
2. Run  $H$  on  $\langle P, M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $L(P) = \emptyset$ ,  $M_2$  and  $P$  will have the same language (since  $L(M_2) = \emptyset$ ) and  $S$  will accept.



# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :  
    1. reject.
2. Run  $H$  on  $\langle P, M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $L(P) = \emptyset$ ,  $M_2$  and  $P$  will have the same language (since  $L(M_2) = \emptyset$ ) and  $S$  will accept. If  $L(P) \neq \emptyset$ , ...?

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :  
    1. reject.
2. Run  $H$  on  $\langle P, M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $L(P) = \emptyset$ ,  $M_2$  and  $P$  will have the same language (since  $L(M_2) = \emptyset$ ) and  $S$  will accept. If  $L(P) \neq \emptyset$ ,  $M_2$  and  $P$  will not have the same language and...?

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :  
    1. reject.
2. Run  $H$  on  $\langle P, M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $L(P) = \emptyset$ ,  $M_2$  and  $P$  will have the same language (since  $L(M_2) = \emptyset$ ) and  $S$  will accept. If  $L(P) \neq \emptyset$ ,  $M_2$  and  $P$  will not have the same language and  $S$  will reject.

# $EQ_{TM}$

Claim:  $EQ_{TM} = \{\langle M, N \rangle : M, N \text{ are TMs and } L(M) = L(N)\}$  is undecidable.

Proof: Suppose  $EQ_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $E_{TM}$ :

$S$  = on input  $\langle P \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :  
    1. reject.
2. Run  $H$  on  $\langle P, M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $L(P) = \emptyset$ ,  $M_2$  and  $P$  will have the same language (since  $L(M_2) = \emptyset$ ) and  $S$  will accept. If  $L(P) \neq \emptyset$ ,  $M_2$  and  $P$  will not have the same language and  $S$  will reject. Therefore,  $S$  is a decider for  $E_{TM}$ , which is a contradiction, so  $EQ_{TM}$  is undecidable.

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof:

?

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1.

To show  $REGULAR_{TM}$  is undecidable,  
use it to decide  $A_{TM}$ .

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1.

Plan: Build a TM whose language is regular if  $N$  accepts  $\omega$  and not regular if  $N$  does not accept  $\omega$ .



# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

$\lfloor$  ?

$L(M_2)$  is regular  
 $\Updownarrow$   
 $N$  accepts  $\omega$

Plan: Build a TM whose language is regular if  $N$  accepts  $\omega$  and not regular if  $N$  does not accept  $\omega$ .

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

- 1. If  $x \in \{ \quad ??? \quad \}$ , accept.
- 2. If  $x \notin \{ \quad ??? \quad \}$ , run  $N$  on  $\omega$  and accept if  $N$  does.

$L(M_2)$  is regular  
 $\Updownarrow$   
 $N$  accepts  $\omega$

Plan: Build a TM whose language is regular if  $N$  accepts  $\omega$  and not regular if  $N$  does not accept  $\omega$ .

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

- 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
- 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.

$L(M_2) \text{ is regular}$   
 $\Updownarrow$   
 $N \text{ accepts } \omega$

Plan: Build a TM whose language is regular if  $N$  accepts  $\omega$  and not regular if  $N$  does not accept  $\omega$ .

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

- 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
- 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.

$L(M_2) = ?$



Plan: Build a TM whose language is regular if  $N$  accepts  $\omega$  and not regular if  $N$  does not accept  $\omega$ .

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$ :

- 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
- 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.

$L(M_2) = 0^n 1^n \text{ or } \Sigma^*$



Plan: Build a TM whose language is regular if  $N$  accepts  $\omega$  and not regular if  $N$  does not accept  $\omega$ .

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

- 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
- 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.

2. ?

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

- 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
- 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.

2. Run  $H$  on  $\langle M_2 \rangle$ .

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :
  - 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
  - 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.
2. Run  $H$  on  $\langle M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.



# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

- 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
- 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.

2. Run  $H$  on  $\langle M_2 \rangle$ .

3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $N$  accepts  $\omega$ ,  $L(M_2) = \Sigma^*$  (regular).

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

- 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
- 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.

2. Run  $H$  on  $\langle M_2 \rangle$ .

3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $N$  accepts  $\omega$ ,  $L(M_2) = \Sigma^*$  (regular). If  $N$  does not accept  $\omega$ ,  $L(M_2) = \{0^n 1^n : n \geq 0\}$  (not regular).

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :

- 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
- 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.

2. Run  $H$  on  $\langle M_2 \rangle$ .

3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $N$  accepts  $\omega$ ,  $L(M_2) = \Sigma^*$  (regular). If  $N$  does not accept  $\omega$ ,  $L(M_2) = \{0^n 1^n : n \geq 0\}$  (not regular). So, deciding if  $L(M_2)$  is regular will determine if  $N$  accepts  $\omega$ .

# $REGULAR_{TM}$

Claim:  $REGULAR_{TM} = \{\langle M \rangle : M \text{ is a TM and } L(M) \text{ is regular}\}$  is undecidable.

Proof: Suppose  $REGULAR_{TM}$  is decidable and let TM  $H$  be its decider.

Build a TM  $S$  that decides  $A_{TM}$ :

$S$  = on input  $\langle N, \omega \rangle$

1. Construct TM  $M_2$  on input  $\langle x \rangle$  :
  - 1. If  $x \in \{0^n 1^n : n \geq 0\}$ , accept.
  - 2. If  $x \notin \{0^n 1^n : n \geq 0\}$ , run  $N$  on  $\omega$  and accept if  $N$  does.
2. Run  $H$  on  $\langle M_2 \rangle$ .
3. If  $H$  accepts, accept. If  $H$  rejects, reject.

If  $N$  accepts  $\omega$ ,  $L(M_2) = \Sigma^*$  (regular). If  $N$  does not accept  $\omega$ ,  $L(M_2) = \{0^n 1^n : n \geq 0\}$  (not regular). So, deciding if  $L(M_2)$  is regular will determine if  $N$  accepts  $\omega$ . Therefore,  $S$  is a decider for  $A_{TM}$ , so  $REGULAR_{TM}$  is undecidable.

When in doubt use  $A_{TM}!!!$

# Unrecognizable Language

Claim: A language is decidable  $\Leftrightarrow$  it and its complement are Turing-recognizable.

Proof:

# Unrecognizable Language

Claim: A language is decidable  $\Leftrightarrow$  it and its complement are Turing-recognizable.

Proof:  $\Rightarrow$  If a language is decidable, its complement is also decidable (just reverse accept/reject conditions) and decidable languages are recognizable.

Given decider  $T$  for  $A$ , make decider for  $\bar{A}$ :

M = on input  $\omega$

1. Run  $T$  on  $\omega$ .
2. If  $T$  accepts, reject. If  $T$  rejects, accept.

# Unrecognizable Language

Claim: A language is decidable  $\Leftrightarrow$  it and its complement are Turing-recognizable.

Proof:  $\Rightarrow$  If a language is decidable, its complement is also decidable (just reverse accept/reject conditions) and decidable languages are recognizable.

$\Leftarrow$  If  $A$  and  $\bar{A}$  are both Turing-recognizable, let  $M_1$  and  $M_2$  be recognizers for  $A$  and  $\bar{A}$ .



# Unrecognizable Language

Claim: A language is decidable  $\Leftrightarrow$  it and its complement are Turing-recognizable.

Proof:  $\Rightarrow$  If a language is decidable, its complement is also decidable (just reverse accept/reject conditions) and decidable languages are recognizable.

$\Leftarrow$  If  $A$  and  $\bar{A}$  are both Turing-recognizable, let  $M_1$  and  $M_2$  be recognizers for  $A$  and  $\bar{A}$ . Consider the following TM:

$M$  = on input  $\omega$

1. Run both  $M_1$  and  $M_2$  on  $\omega$  in parallel (alternate instructions).
2. If  $M_1$  accepts, accept. If  $M_2$  accepts, reject.

# Unrecognizable Language

Claim: A language is decidable  $\Leftrightarrow$  it and its complement are Turing-recognizable.

Proof:  $\Rightarrow$  If a language is decidable, its complement is also decidable (just reverse accept/reject conditions) and decidable languages are recognizable.

$\Leftarrow$  If  $A$  and  $\bar{A}$  are both Turing-recognizable, let  $M_1$  and  $M_2$  be recognizers for  $A$  and  $\bar{A}$ . Consider the following TM:

$M$  = on input  $\omega$

1. Run both  $M_1$  and  $M_2$  on  $\omega$  in parallel (alternate instructions).
2. If  $M_1$  accepts, accept. If  $M_2$  accepts, reject.

Since  $\omega \in A$  or  $\bar{A}$ ,  $M_1$  or  $M_2$  must accept (halts on input). Thus,  $M$  is a decider for  $A$ .

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof:

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e., ????).

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does **not** halt on some input).

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does **not** halt on some input).

Consider  $S$  on  $\langle M, \omega \rangle$ :

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does **not** halt on some input).

Consider  $S$  on  $\langle N, \omega \rangle$ :

1. Run  $N$  on  $\omega$ .
2. accept.


# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does **not** halt on some input).

Consider  $S$  on  $\langle N, \omega \rangle$ :

1. Run  $N$  on  $\omega$ .
2. accept.





# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does not halt on some input).

Consider  $S$  on  $\langle N, \omega \rangle$ :

1. Run  $N$  on  $\omega$ .
2. accept.

}  **$HALT_{TM}$  recognizer!**

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does not halt on some input).

Consider  $S$  on  $\langle N, \omega \rangle$ :

1. Run  $N$  on  $\omega$ .
2. accept.

}  **$HALT_{TM}$  recognizer!**

Consider  $V$  on  $\langle N, \omega \rangle$ :

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does not halt on some input).

Consider  $S$  on  $\langle N, \omega \rangle$ :

1. Run  $N$  on  $\omega$ .
2. accept.

}  **$HALT_{TM}$  recognizer!**

Consider  $V$  on  $\langle N, \omega \rangle$ :

1. Run  $T$  on  $\langle N, \omega \rangle$  and run  $S$  on  $\langle N, \omega \rangle$  in parallel.

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does not halt on some input).

Consider  $S$  on  $\langle N, \omega \rangle$ :

1. Run  $N$  on  $\omega$ .
2. accept.

}  **$HALT_{TM}$  recognizer!**

Consider  $V$  on  $\langle N, \omega \rangle$ :

1. Run  $T$  on  $\langle N, \omega \rangle$  and run  $S$  on  $\langle N, \omega \rangle$  in parallel.
2. If  $T$  accepts, reject. If  $S$  accepts, accept.

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does not halt on some input).

Consider  $S$  on  $\langle N, \omega \rangle$ :

1. Run  $N$  on  $\omega$ .
2. accept.

}  **$HALT_{TM}$  recognizer!**

Consider  $V$  on  $\langle N, \omega \rangle$ :

1. Run  $T$  on  $\langle N, \omega \rangle$  and run  $S$  on  $\langle N, \omega \rangle$  in parallel.
2. If  $T$  accepts, reject. If  $S$  accepts, accept.

} ???

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof: Suppose  $\overline{HALT_{TM}}$  was Turing-recognizable. Let  $T$  be its recognizer (i.e.,  $T$  will accept if a TM does not halt on some input).

Consider  $S$  on  $\langle N, \omega \rangle$ :

1. Run  $N$  on  $\omega$ .
2. accept.

}  **$HALT_{TM}$  recognizer!**

Consider  $V$  on  $\langle N, \omega \rangle$ :

1. Run  $T$  on  $\langle N, \omega \rangle$  and run  $S$  on  $\langle N, \omega \rangle$  in parallel.
2. If  $T$  accepts, reject. If  $S$  accepts, accept.

}  **$HALT_{TM}$  decider!**

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof:

A language is decidable  $\iff$  it and its complement are Turing-recognizable.

# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof:  $HALT_{TM}$  is not decidable

A language is decidable  $\iff$  it and its complement are Turing-recognizable.



# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof:  $HALT_{TM}$  is not decidable  $\Rightarrow HALT_{TM}$  and  $\overline{HALT_{TM}}$  cannot both be Turing-recognizable (otherwise  $HALT_{TM}$  would be decidable).

A language is decidable  $\Leftrightarrow$  it and its complement are Turing-recognizable.


# Unrecognizable Language

Claim:  $\overline{HALT_{TM}} = \{\langle M, \omega \rangle : M \text{ is a TM and } M \text{ does not halt on } \omega\}$  is not Turing-recognizable.

Proof:  $HALT_{TM}$  is not decidable  $\Rightarrow HALT_{TM}$  and  $\overline{HALT_{TM}}$  cannot both be Turing-recognizable (otherwise  $HALT_{TM}$  would be decidable). Since  $HALT_{TM}$  is Turing-recognizable,  $\overline{HALT_{TM}}$  cannot be Turing-recognizable.

A language is decidable  $\Leftrightarrow$  it and its complement are Turing-recognizable.

# Computability Hierarchy



# Beyond Decidability

What if  $HALT_{TM}$  were “decidable”?

# Beyond Decidability

What if  $HALT_{TM}$  were “decidable”?

Goldbach’s Conjecture:

- 280-year-old open problem.
- Every integer  $\geq 2$  is sum of two primes.

# Beyond Decidability

What if  $HALT_{TM}$  were “decidable”?

Goldbach’s Conjecture:

- 280-year-old open problem.
- Every integer  $\geq 2$  is sum of two primes.

Consider  $G$  on  $\langle x \rangle$ :

1. For  $n = 2$ , check each pair of prime number  $< n$ .
2. If no pair sums to  $n$ , reject.
3. Increment  $n$  and loop to step 1.

# Beyond Decidability

```
public boolean G() {  
    int i = 2;  
    while (true) {  
        boolean found = false;  
        for (int n = 1; n < i; n++) {  
            for (int m = 1; m < i; m++) {  
                if (isPrime(n) && isPrime(m) && m + n = i) {  
                    found = true;  
                }  
            }  
        }  
        if (!found) {  
            return false;  
        }  
        i++;  
    }  
}
```

# Beyond Decidability

What if  $HALT_{TM}$  were “decidable”?

Goldbach’s Conjecture:

- 280-year-old open problem.
- Every integer  $\geq 2$  is sum of two primes.

Consider  $G$  on  $\langle x \rangle$ :

1. For  $n = 2$ , check each pair of prime number  $< n$ .
2. If no pair sums to  $n$ , reject.
3. Increment  $n$  and loop to step 1.

What does it mean if  $G$  halts?

What does it mean if  $G$  does not halt?



# Beyond Decidability

What if  $HALT_{TM}$  were “decidable”?

Goldbach’s Conjecture:

- 280-year-old open problem.
- Every integer  $\geq 2$  is sum of two primes.

Consider  $G$  on  $\langle x \rangle$ :

1. For  $n = 2$ , check each pair of prime number  $< n$ .
2. If no pair sums to  $n$ , reject.
3. Increment  $n$  and loop to step 1.

What does it mean if  $G$  halts? **Goldbach’s conjecture is false!**

What does it mean if  $G$  does not halt? **Goldbach’s conjecture is true!**

# Beyond Decidability

What if  $HALT_{TM}$  were “decidable”?

Goldbach’s Conjecture:

- 280-year-old open problem.
- Every integer  $\geq 2$  is sum of two primes.

Consider  $G$  on  $\langle x \rangle$ :

1. For  $n = 2$ , check each pair of prime number  $< n$ .
2. If no pair sums to  $n$ , reject.
3. Increment  $n$  and loop to step 1.

What does it mean if  $G$  halts? **Goldbach’s conjecture is false!**

What does it mean if  $G$  does not halt? **Goldbach’s conjecture is true!**

Turns out you can do this for lots of open problems over natural numbers (twin prime conjecture,...)