## **Brenda Schecher Week 12 Homework: Web Development**

Before you work through the questions below, please create a new file and record your answers there. This will be your homework deliverable.

#### **HTTP Requests and Responses**

Answer the following questions about the HTTP request and response process.

- What type of architecture does the HTTP request and response process occur in?
   Client/Server Architect
- 2. What are the different parts of an HTTP request? Request Line, Headers, Whitespace and Request body (optional)
- 3. Which part of an HTTP request is optional? Request body
- 4. What are the three parts of an HTTP response? **Status line, Headers, and Response body.**
- 5. Which number class of status codes represents errors? 400s represents client errors and 500s indicates server errors.
- 6. What are the two most common request methods that a security professional will encounter? **GET and POST requests.**
- 7. Which type of HTTP request method is used for sending data? **POST**
- 8. Which part of an HTTP request contains the data being sent to the server? **Request** body
- 9. In which part of an HTTP response does the browser receive the web code to generate and style a web page? **Response body**

## **Using curl**

Answer the following questions about curl:

- 10. What are the advantages of using curl over the browser? The advantage to using curl over a browser is that curl through the command line will always be visible, whereas sometimes the browser is not able to send and receive http requests. Curl through the command line is also more efficient. They are able to quickly make adjustments and test.
- 11. Which curl option is used to change the request method? **-X**
- 12. Which curl option is used to set request headers? -H
- 13. Which curl option is used to view the response header? -I
- 14. Which request method might an attacker use to figure out which HTTP requests an HTTP server will accept? **Options**

#### **Sessions and Cookies**

Recall that HTTP servers need to be able to recognize clients from one another. They do this through sessions and cookies.

Answer the following questions about sessions and cookies:

Which response header sends a cookie to the client?

HTTP/1.1 200 OK Content-type: text/html 15. Set-Cookies

Which request header will continue the client's session?

GET /cart HTTP/1.1 Host: www.example.org

16. Connection: Keep-Alive

#### **Example HTTP Requests and Responses**

Look through the following example HTTP request and response and answer the following questions:

## **HTTP Request**

POST /login.php HTTP/1.1

Host: example.com

Accept-Encoding: gzip, deflate, br

Connection: keep-alive

Content-Type: application/x-www-form-urlencoded

Content-Length: 34

Upgrade-Insecure-Requests: 1

User-Agent: Mozilla/5.0 (Linux; Android 6.0; Nexus 5 Build/MRA58N) AppleWebKit/537.36

(KHTML, like Gecko) Chrome/80.0.3987.132 Mobile Safari/537.36

username=Barbara&password=password

- 17. What is the request method? **POST**
- 18. Which header expresses the client's preference for an encrypted response?

  Upgrade-Insecure-Requests: 1
- 19. Does the request have a user session associated with it? No, it says "1" so not yet.
- 20. What kind of data is being sent from this request body? log in credentials.

# **HTTP Response**

HTTP/1.1 200 OK

Date: Mon, 16 Mar 2020 17:05:43 GMT

Last-Modified: Sat, 01 Feb 2020 00:00:00 GMT

Content-Encoding: gzip

Expires: Fri, 01 May 2020 00:00:00 GMT

Server: Apache

Set-Cookie: SessionID=5

Content-Type: text/html; charset=UTF-8

Strict-Transport-Security: max-age=31536000; includeSubDomains

X-Content-Type: NoSniff X-Frame-Options: DENY

X-XSS-Protection: 1; mode=block

#### [page content]

21. What is the response status code? 200

- 22. What web server is handling this HTTP response? Apache webserver
- 23. Does this response have a user session associated to it? **Yes Set-Cookie**: **SessionID=5**
- 24. What kind of content is likely to be in the [page content] response body? not sure
- 25. If your class covered security headers, what security request headers have been included? Strict-Transport-Security: max-age=31536000; includeSubDomains

#### **Monoliths and Microservices**

Answer the following questions about monoliths and microservices:

- 26. What are the individual components of microservices called? Front End, Back end and Database Services
- 27. What is a service that writes to a database and communicates to other services? APIs
- 28. What type of underlying technology allows for microservices to become scalable and have redundancy? **Containers**

## **Deploying and Testing a Container Set**

Answer the following questions about multi-container deployment:

- 29. What tool can be used to deploy multiple containers at once? **Docker**
- 30. What kind of file format is required for us to deploy a container set? .yml files using ansible-playbook command

#### **Databases**

- 31. Which type of SQL query would we use to see all of the information within a table called customers? **SELECT \* FROM customers:**
- 32. Which type of SQL query would we use to enter new data into a table? (You don't need a full query, just the first part of the statement.) **INSERT INTO table\_name**

33. Why would we never run DELETE FROM <table-name>; by itself? It will delete the entire table.

# **Bonus Challenge Overview: The Cookie Jar**

For this challenge, you'll once again be using curl, but this time to manage and swap sessions.

⚠ **Heads Up**: You'll need to have WordPress set up from the Swapping Sessions activity from Day 1 of this unit. If you have not done it or it is improperly set up, please refer to the Day 1 student guide and the Swapping Sessions activity file.

If you recall, on Day 1 of this unit you used Google Chrome's Cookie-Editor extension to swap sessions and cookies. For this homework challenge, we'll be using the command-line tool curl to practice swapping cookie and sessions within the WordPress app.

It is important for cybersecurity professionals to know how to manage cookies with curl:

- Web application security engineers need to regularly ensure cookies are both functional and safe from tampering.
  - For example, you might need to request a cookie from a webpage and then test various HTTP responses using that cookie. Doing this over and over through the browser is tedious, but can be automated with scripts.
- The same concept applies for penetration testers and hackers: curl is used to quickly save a cookie in order to test various exploits.
  - For example, an HTTP server may be configured so that, in order to POST data to specific pages, clients need to have cookies or authentication information set in their request headers, which the server will verify.

#### Revisiting curl

Recall that you used curl to craft different kinds of requests for your curl activity, and that you saw how to use the Chrome extension Cookie-Editor to export and import cookies and swap sessions.

There will be many systems in which you will need to test requests and cookies that will not connect to a browser or browser extension.

curl not only allows users to look through headers, send data, and authenticate to servers, but also to save and send cookies through two curl options: --cookie-jar and --cookie.

These two options work exactly like Cookie-Editor, but on the command line.

• --cookie-jar allows a curl user to save the cookies set within a response header into a text file.

 --cookie allows a user to specify a text file where a cookie is saved, in order to send a request with the cookies embedded in the request header.

Let's look at how we can create a curl command that will log into a web page with a supplied username and password, and also save the server's response that should contain a cookie.

#### Logging In and Saving Cookies with Curl

If we want to use the curl command to log into an account, Amanda, with the password password, we use the following curl options:

- curl --cookie-jar ./amandacookies.txt --form "log=Amanda" --form "pwd=password" http://localhost:8080/wp-login.php --verbose
- curl: The tool that we are using.
- --cookie-jar: Specifies where we will save the cookies.
- ,/amandacookies,txt: Location and file where the cookies will be saved.
- --form: Lets us pick the login username and password forms that we set in our user info earlier. In this case it's our username.
- log=Amanda: How WordPress understands and accepts usernames.
- --form: Lets us pick the login username and password forms that we set in our user info earlier. In this case it's our password.
- pwd=password: How WordPress understands and accepts passwords.
- http://localhost:8080/wp-login.php: Our WordPress login page.
- --verbose: Outputs more specific description about the actions the command is taking.

Run the command: curl --cookie-jar ./amandacookies.txt --form "log=Amanda" --form "pwd=password" http://localhost:8080/wp-login.php --verbose

If the site confirms our credentials, it will give us a cookie in return, which curl will save in the cookie jar file ./amandacookies.txt.

Now let's look at how to use that saved cookie on a page that requires us to be logged in.

#### **Using a Saved Cookie**

To use a saved cookie, we use the following curl syntax:

- curl --cookie ./amandacookies.txt http://localhost:8080/wp-admin/users.php
  - o curl: The tool that we are using.
  - o --cookie: Precedes the location of our saved cookie that we want to use.
  - o ./amandacookies.txt: Location and file where the cookies are saved.
  - http://localhost:8080/wp-admin/users.php: A page that requires authentication to see properly. Note that we are not going to the login page, because supplying a cookie in this instance assumes that we are already logged in.

Now that we know how to use the curl cookie jar, let's look at what we need to do for this challenge.

# **Bonus Challenge Instructions: The Cookie Jar**

First, using Docker Compose, navigate to the Day 1 WordPress activity directory and bring up the container set:

/home/sysadmin/Documents/docker files

Using curl, you will do the following for the Ryan user:

- Log into WordPress and save the user's cookies to a cookie jar.
- Test a WordPress page by using a cookie from the cookie jar.
- Pipe the output from the cookie with grep to check for authenticated page access.
- Attempt to access a privileged WordPress admin page.

#### Step 1: Set Up

Create two new users: Amanda and Ryan.

- 1. Navigate to localhost:8080/wp-admin/
- 2. On the left-hand toolbar, hover over **Users** and click **Add New**.
- 3. Enter the following information to create the new user named Amanda.
  - Username: Amanda
  - Email: amanda@email.com
- 4. Skip down to password:
  - o Password: password
  - o Confirm Password: Check the box to confirm use of weak password.
  - o Role: Administrator
- 5. Create another user named Ryan.
  - Username: Ryan
  - Email: ryan@email.com
- 6. Skip down to password:
  - o Password: 123456
  - o Confirm Password: Check the box to confirm use of weak password.
  - o Role: Editor
- 7. Log out and log in with the following credentials:
  - o Username: Amanda
  - o Password: password

#### Step 2: Baselining

For these "baselining" steps, you'll want to log into two different types of accounts to see how the WordPress site looks at the localhost:8080/wp-admin/users.php page. We want to see how the Users page looks from the perspective of an administrator, vs. a regular user.

- 1. Using your browser, log into your WordPress site as your sysadmin account and navigate to localhost:8080/wp-admin/users.php, where we previously created the user Ryan. Examine this page briefly. Log out.
- 2. Using your browser, log into your Ryan account and attempt to navigate to localhost:8080/wp-admin/index.php. Note the wording on your Dashboard.
- 3. Attempt to navigate to localhost:8080/wp-admin/users.php. Note what you see now.

Log out in the browser.

#### Step 3: Using Forms and a Cookie Jar

Navigate to ~/Documents in a terminal to save your cookies.

- 1. Construct a curl request that enters two forms: "log={username}" and "pwd={password}" and goes to http://localhost:8080/wp-login.php. Enter Ryan's credentials where there are placeholders.
  - Question: Did you see any obvious confirmation of a login? (Y/N) yes, see attached screen shot.
  - sysadmin@UbuntuDesktop:~/Documents\$ curl --cookie-jar ./ryancookies.txt
     --form "log=Ryan" --form "pwd=123456" http://localhost:8080/wp-login.php
     --verbose
  - o \* Trying 127.0.0.1...
  - \* TCP NODELAY set
  - \* Connected to localhost (127.0.0.1) port 8080 (#0)
  - > POST /wp-login.php HTTP/1.1
  - > Host: localhost:8080
  - > User-Agent: curl/7.58.0
  - > Accept: \*/\*
  - > Content-Length: 240
  - > Content-Type: multipart/form-data;
    - boundary=-----0085959aa0459dbc
  - o >
  - < HTTP/1.1 302 Found</li>
  - < Date: Thu, 02 Mar 2023 16:29:09 GMT</li>
  - < Server: Apache/2.4.54 (Debian)</li>
  - < X-Powered-By: PHP/8.0.28</p>
  - < Expires: Wed, 11 Jan 1984 05:00:00 GMT</li>
  - < Cache-Control: no-cache, must-revalidate, max-age=0</li>
  - \* cookie size: name/val 21 + 19 bytes
  - \* cookie size: name/val 4 + 1 bytes

- \* Added cookie wordpress\_test\_cookie="WP%20Cookie%20check" for domain localhost, path /, expire 0
- Set-Cookie: wordpress\_test\_cookie=WP%20Cookie%20check; path=/
- < X-Frame-Options: SAMEORIGIN</li>
- \* cookie size: name/val 42 + 130 bytes
- \* cookie size: name/val 4 + 19 bytes
- \* cookie size: name/val 8 + 0 bytes
- \* Added cookie

wordpress\_37d007a56d816107ce5b52c10342db37="Ryan%7C1677947349%7 CdhCVhjdcKdPnpBODimU6HZAD4JH9Y59MrrZuBlavWrR%7C3f06133dfa6a56e aba73ddda9ef0844b13d765076d8a3148a950fb64c546363f" for domain localhost, path /wp-content/plugins, expire 0

< Set-Cookie:</p>

wordpress\_37d007a56d816107ce5b52c10342db37=Ryan%7C1677947349%7C dhCVhjdcKdPnpBODimU6HZAD4JH9Y59MrrZuBlavWrR%7C3f06133dfa6a56ea ba73ddda9ef0844b13d765076d8a3148a950fb64c546363f; path=/wp-content/plugins; HttpOnly

- \* cookie size: name/val 42 + 130 bytes
- \* cookie size: name/val 4 + 9 bytes
- \* cookie size: name/val 8 + 0 bytes
- \* Added cookie

wordpress\_37d007a56d816107ce5b52c10342db37="Ryan%7C1677947349%7 CdhCVhjdcKdPnpBODimU6HZAD4JH9Y59MrrZuBlavWrR%7C3f06133dfa6a56e aba73ddda9ef0844b13d765076d8a3148a950fb64c546363f" for domain localhost, path /wp-admin, expire 0

< Set-Cookie:</p>

wordpress\_37d007a56d816107ce5b52c10342db37=Ryan%7C1677947349%7C dhCVhjdcKdPnpBODimU6HZAD4JH9Y59MrrZuBlavWrR%7C3f06133dfa6a56ea ba73ddda9ef0844b13d765076d8a3148a950fb64c546363f; path=/wp-admin; HttpOnly

- \* cookie size: name/val 52 + 130 bytes
- \* cookie size: name/val 4 + 1 bytes
- \* cookie size: name/val 8 + 0 bytes
- \* Added cookie

wordpress\_logged\_in\_37d007a56d816107ce5b52c10342db37="Ryan%7C1677947349%7CdhCVhjdcKdPnpBODimU6HZAD4JH9Y59MrrZuBlavWrR%7C26426f52b70b06b57e2c36afd2e45b3e9cef3161ac2143f8a9179b4a1607e0a0" for domain localhost, path /, expire 0

< Set-Cookie:</p>

wordpress\_logged\_in\_37d007a56d816107ce5b52c10342db37=Ryan%7C16779 47349%7CdhCVhjdcKdPnpBODimU6HZAD4JH9Y59MrrZuBlavWrR%7C26426f5 2b70b06b57e2c36afd2e45b3e9cef3161ac2143f8a9179b4a1607e0a0; path=/; HttpOnly

< X-Redirect-By: WordPress</li>

- < Location: http://localhost:8080/wp-admin/</li>
- < Content-Length: 0</p>
- < Content-Type: text/html; charset=UTF-8</li>
- \* HTTP error before end of send, stop sending
- **<**
- 2. Construct the same curl request, but this time add the option and path to save your cookie: --cookie-jar ./ryancookies.txt. This option tells curl to save the cookies to the ryancookies.txt text file.
- 3. curl --cookie ./ryancookies.txt http://localhost:8080/wp-admin/users.php
- 4. Read the contents of the ryancookies.txt file.
  - Question: How many items exist in this file? looks like 2 items with a cookie of WP%20Cookie%20check
  - localhost FALSE / FALSE 0 wordpress\_test\_cookie WP
     Cookie check
  - #HttpOnly\_localhost FALSE/wp-content/plugins FALSE 0
    wordpress\_37d007a56d816107ce5b52c10342db37
    Ryan|1677947349|dhCVhjdcKdPnpBODimU6HZAD4JH9Y59MrrZuBlavWrR|3f06
    133dfa6a56eaba73ddda9ef0844b13d765076d8a3148a950fb64c546363f
  - #HttpOnly\_localhost FALSE/wp-admin FALSE 0
    wordpress\_37d007a56d816107ce5b52c10342db37
    Ryan|1677947349|dhCVhjdcKdPnpBODimU6HZAD4JH9Y59MrrZuBlavWrR|3f06
    133dfa6a56eaba73ddda9ef0844b13d765076d8a3148a950fb64c546363f
  - #HttpOnly\_localhost FALSE / FALSE 0
     wordpress\_logged\_in\_37d007a56d816107ce5b52c10342db37
     Ryan|1677947349|dhCVhjdcKdPnpBODimU6HZAD4JH9Y59MrrZuBlavWrR|264
     26f52b70b06b57e2c36afd2e45b3e9cef3161ac2143f8a9179b4a1607e0a0

0

Note that each one of these is a cookie that was granted to Ryan after logging in.

## **Step 4: Log in Using Cookies**

- 1. Craft a new curl command that now uses the --cookie option, followed by the path to your cookies file. For the URL, use http://localhost:8080/wp-admin/index.php.
- 2.
- Question: Is it obvious that we can access the Dashboard? (Y/N) y curl --cookie ./ryancookies.txt <a href="http://localhost:8080/wp-admin/users.php">http://localhost:8080/wp-admin/users.php</a>
- yes see screen shot below.
- <head>
- <meta http-equiv="Content-Type" content="text/html; charset=UTF-8" />
- <title>Dashboard &lsaquo; &#8212; WordPress</title>
- <script type="text/javascript">
- addLoadEvent = function(func){if(typeof
   ¡Query!=='undefined')¡Query(function(){func();});else if(typeof

```
wpOnload!=='function'){wpOnload=func;}else{var
oldonload=wpOnload;wpOnload=function(){oldonload();func();}}};
o var ajaxurl = '/wp-admin/admin-ajax.php',
o pagenow = 'dashboard',
o typenow = ",
o adminpage = 'index-php',
o thousandsSeparator = ',',
o decimalPoint = '.',
o isRtl = 0:
```

3. Press the up arrow on your keyboard to run the same command, but this time, pipe | grep Dashboard to the end of your command to return all instances of the word Dashboard on the page.

0

- Question: Look through the output where the Dashboard is highlighted. Does any of the wording on this page seem familiar? (Y/N) Yes it does.
- curl --cookie ./ryancookies.txt http://localhost:8080/wp-admin/index.php |grep Dashboard

<a href='index.php' class="wp-first-item current menu-top menu-top-first menu-icon-dashboard menu-top-last" aria-current="page"><div class="wp-menu-arrow"><div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></div></di>

Welcome to your WordPress Dashboard!The Dashboard is the first place you will come to every time you log into your site. It is where you will find all your WordPress tools. If you need help, just click the "Help" tab above the screen title.

following controls to arrange your Dashboard screen to suit your workflow. This is true on most other administration screens as well.<strong>ScreenOptions</strong> &mdash; Use the Screen Options tab to choose which

You can use the

Dashboard boxes to show.cstrong>Drag and Drop</strong> &mdash; To rearrange the boxes, drag and drop by clicking on the title bar of the selected box and releasing when you see a gray dotted-line rectangle appear in the location you want to place the box.<strong>Box Controls</strong> &mdash; Click the title bar of the box to expand or collapse it. Some boxes added by plugins may have configurable content, and will show a &#8220;Configure&#8221; link in the title bar if you hover over it.

## Step 5: Test the Users.php Page

- 1. Finally, write a curl command using the same --cookie ryancookies.txt option, but attempt to access http://localhost:8080/wp-admin/users.php.
  - Question: What happens this time? I wasnt able to log in. It says I have to have higher level of permissions?
  - curl --cookie ./ryancookies.txt http://localhost:8080/wp-admin/users.php
  - </head>
  - <body id="error-page">
  - <div class="wp-die-message"><h1>You need a higher level of permission.</h1>Sorry, you are not allowed to list users.</div></body>

# **Submission Guidelines**

0

 Save the file where you documented your solutions and submit it as your homework deliverable.