

4K60 Tri-Combo input card



- Full quality 4K@60p 4:4:4 on a single cable
- Rugged modular design
- One DisplayPort 1.2 connector
- Supports up to 4K60p
- HDCP 1.4 Compliant
- EDID support for VESA/CEA, and custom timings
- Automatic input acquisition and configuration
- One HDMI 2.0 Connector
- Supports up to 4K60p
- HDCP 2.2 compliant
- EDID support for VESA/CEA, and custom timings
- Automatic input acquisition and configuration
- Four 12G-SDI (BNC) Connectors
- Supports up to 4x 1200p@60, or 2x 4K@60p/ UHD per card (single cable)

Product specifications**4K60 TRI-COMBO INPUT CARD**

General specifications	
Connectors	1x DP 1.2; 1x HDMI 2.0; 4x 12G-SDI (BNC)
Resolution	Up to 2x 4096x2160@60p in '8L' slot
Color depth	8-bit; 10-bit; 12-bit (DL or lower)
Color sampling	HDMI 2.0: up to UHD@60p 4:4:4 8-bit DP1.2: up to UHD@60p 4:4:4 10-bit 12G-SDI: up to UHD@60p 4:2:2 10-bit
HDCP	HDCP 2.2 compliant on HDMI HDCP 1.x compliant on DisplayPort
Signal capacity	HDMI: 600 MHz DisplayPort: 660 MHz

Last updated: 04 Dec 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.