



LITEBARPRO 15QX IP

LEDBAR015

Pixel mappable IP65-rated LED batten produces deep, saturated, perfectly-mixed colors for wall grazing and dynamic linear washes and effects:

- 15 x 10W RGBW LEDs
- Mounting brackets allow fixture to be flown or floor-mounted
- Rugged diecast body and touring-grade construction
- Color and white presets available via onboard menu or DMX
- Silent operation with advanced fanless thermal management
- Onboard library of 14 dynamic preprogrammed light shows
- Custom color mixing and adjustable white balance
- Menu display backlight auto blackout
- Power linking (IP65 PowerKon In/Out)
- DMX or W-DMX control (W-DMX onboard)





Specifications

Product	LITEBARPRO 15QX 1P		
Code	LEDBAR015		
Lamp Source	15 x 10W RGBW LEDs		
Power Supply	100-240V AC, 50/60Hz		
Power Consumption	162W		
Ingress Protection Rating	IP65		
DMX Connection	IP65 5-pin XLR In/Out		
DMX Channels	4/6/10/60/65		
Beam Angle	16°		
Field Angle	28°		
Dimensions	992(L) x 205(W) x 160(H)mm		
Weight	8.2 kg		

SYDNEY +61 2 9748 1122

MELBOURNE +61 3 9681 7511 BRISBANE +61 7 3267 3177

PERTH AU +61 8 9248 8119 +64

AUCKLAND +64 0 860 3203



Channel Allocation

	4-CH	6-CH	10-CH
1	Red	Master Dimmer	Master Dimmer
2	Green	Red	Red
3	Blue	Green	Green
4	White	Blue	Blue
5		White	White
6		Strobe	Strobe
7			Color Macros
8			Auto Programs
9			Auto Program Speed
10			Dimmer Curve Select

60-channel mode: Individual 4-channel RGBW control of each pixel

65-channel mode: Individual 4-channel RGBW control of each pixel +

Auto Programs Auto Program Speed Master Dimmer Strobe

Dimmer Curve Select

