

CSC 212: Data Structures and Abstractions

Big O Notation

Marco Alvarez

Department of Computer Science and Statistics
University of Rhode Island

Fall 2020



The story so far ...


- Can measure actual runtime to compare algorithms
 - ✓ however, runtime is noisy (highly sensitive to HW/SW and implementation details)
- Can count instructions to compare algorithms
 - ✓ can define $T(n)$, which depends on the input size
 - ✓ for large inputs, our focus should be on the dominant terms of $T(n)$
- ✓ we will now see formal ways for this approach

2

$$\sum_{i=1}^n i = 1 + 2 + 3 + \dots + (n-1) + n$$

3


$$\sum_{i=1}^{n-1} i = 1 + 2 + 3 + \dots + (n-2) + (n-1)$$



4


Should we consider these the same?

Comparing two algorithms with $T(n) = 2n$ and $T(n) = 25n$ respectively




5

What about now?



6


Now consider this example ...



7

Bottom line ...

- We are trying to compare $T(n)$ functions, but we also care about large values of n
- Can we properly define ' \leq ' for functions?
 - we can group functions into 'sets' and make our lives easier



8

Asymptotic Analysis

- Refers to the study of an algorithm as the input size “gets big” or reaches a limit (in the calculus sense)


- Growth rate**

- rate at which the cost of an algorithm grows as the size of its input grows

$$c_1n \quad c_2n^2$$

9

Common sets of functions



Faster
growth rate
... slower
algorithm

Algorithm A is better than algorithm B if for large values of n , $T_A(n)$ grows slower than $T_B(n)$

credit: COS 226, Princeton

10


A few examples ...

order of growth	name	typical code framework	description	example
1	constant	<code>a = b + c;</code>	statement	add two numbers
$\log n$	logarithmic	<code>while (n > 1) { n = n/2; ... }</code>	divide in half	binary search
n	linear	<code>for (int i = 0; i < n; i++) { ... }</code>	single loop	find the maximum
$n \log n$	linearithmic	<i>see mergesort lecture</i>	divide and conquer	mergesort
n^2	quadratic	<code>for (int i = 0; i < n; i++) for (int j = 0; j < n; j++) { ... }</code>	double loop	check all pairs
n^3	cubic	<code>for (int i = 0; i < n; i++) for (int j = 0; j < n; j++) for (int k = 0; k < n; k++) { ... }</code>	triple loop	check all triples
2^n	exponential	<i>see combinatorial search lecture</i>	exhaustive search	check all subsets

credit: COS 226, Princeton

11

Big O



$T(n)$ is $O(f(n)) \iff \exists$ positive $c, n_0 \mid 0 \leq T(n) \leq cf(n), \forall n \geq n_0$
set of functions

12

Examples

$$7n - 2 = O(n)$$

$$20n^3 + 10n \log n + 5 = O(n^3)$$


$$3 \log n + \log \log n = O(\log n)$$

$$2^{100} = O(1)$$

$$T(n) \text{ is } O(f(n)) \iff \exists \text{ positive } c, n_0 \mid 0 \leq T(n) \leq cf(n), \forall n \geq n_0$$

13

Big Omega




$$T(n) \text{ is } \Omega(f(n)) \iff \exists \text{ positive } c, n_0 \mid 0 \leq cf(n) \leq T(n), \forall n \geq n_0$$

set of functions

14

Big Theta



$$T(n) \text{ is } \Theta(f(n)) \iff T(n) \text{ is } O(f(n)) \text{ and } T(n) \text{ is } \Omega(f(n))$$

15

Prove that ...

$$3 \log n + \log \log n = \Omega(\log n)$$

$$3 \log n + \log \log n = \Theta(\log n)$$

$$T(n) \text{ is } O(f(n)) \iff \exists \text{ positive } c, n_0 \mid 0 \leq T(n) \leq cf(n), \forall n \geq n_0$$

$$T(n) \text{ is } \Omega(f(n)) \iff \exists \text{ positive } c, n_0 \mid 0 \leq cf(n) \leq T(n), \forall n \geq n_0$$

16

In practice you can ...

“ignore constants and drop lower order terms”

17

True or False?

$\{n^2, n^4, 2^n, \log n, \dots\}$

	Big O	Big Omega	Big Theta
$10^2 + 3000n + 10$			
$21 \log n$			
$500 \log n + n^4$			
$\sqrt{n} + \log n^{50}$			
$4^n + n^{5000}$			
$3000n^3 + n^{3.5}$			
$2^5 + n!$			

18

Asymptotic Performance

- For **large** values of n , a $\Theta(n^2)$ algorithm always beats a $\Theta(n^3)$ algorithm

However, we shouldn't completely ignore asymptotically slower algorithms

19