

» newrelic__alert__channel

Use this data source to get information about an specific alert channel in New Relic which already exists (e.g newrelic user).

» Example Usage

```
data "newrelic_alert_channel" "foo" {
  name = "foo@example.com"
}

resource "newrelic_alert_policy" "foo" {
  name = "foo"
}

resource "newrelic_alert_policy_channel" "foo" {
  policy_id = "${newrelic_alert_policy.foo.id}"
  channel_id = "${newrelic_alert_channel.foo.id}"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the alert channel in New Relic.

» Attributes Reference

- **id** - The ID of the alert channel.
- **type** - Alert channel type, either: `campfire`, `email`, `hipchat`, `opsgenie`, `pagerduty`, `slack`, `victorops`, or `webhook`..
- **policy_ids** - A list of policy IDs associated with the alert channel.

» newrelic__application

Use this data source to get information about a specific application in New Relic.

» Example Usage

```
data "newrelic_application" "app" {
  name = "my-app"
}

resource "newrelic_alert_policy" "foo" {
  name = "foo"
}

resource "newrelic_alert_condition" "foo" {
  policy_id = "${newrelic_alert_policy.foo.id}"

  name          = "foo"
  type          = "apm_app_metric"
  entities      = ["${data.newrelic_application.app.id}"]
  metric        = "apdex"
  runbook_url   = "https://www.example.com"

  term {
    duration      = 5
    operator       = "below"
    priority      = "critical"
    threshold     = "0.75"
    time_function = "all"
  }
}
```

» Argument Reference

The following arguments are supported:

- `name` - (Required) The name of the application in New Relic.

» Attributes Reference

- `id` - The ID of the application.
- `instance_ids` - A list of instance IDs associated with the application.
- `host_ids` - A list of host IDs associated with the application.

» newrelic_key_transaction

Use this data source to get information about a specific key transaction in New Relic.

» Example Usage

```
data "newrelic_key_transaction" "txn" {
  name = "txn"
}

resource "newrelic_alert_policy" "foo" {
  name = "foo"
}

resource "newrelic_alert_condition" "foo" {
  policy_id = "${newrelic_alert_policy.foo.id}"

  name          = "foo"
  type          = "apm_kt_metric"
  entities      = ["${data.newrelic_key_transaction.txn.id}"]
  metric        = "error_percentage"
  runbook_url   = "https://www.example.com"

  term {
    duration      = 5
    operator      = "below"
    priority      = "critical"
    threshold     = "0.75"
    time_function = "all"
  }
}
```

» Argument Reference

The following arguments are supported:

- `name` - (Required) The name of the application in New Relic.

» Attributes Reference

- `id` - The ID of the application.

» newrelic__synthetics__monitor

Use this data source to get information about a specific synthetics monitor in New Relic. This can then be used to set up a synthetics alert condition.

» Example Usage

```
data "newrelic_synthetics_monitor" "bar" {
  name = "bar"
}

resource "newrelic_synthetics_alert_condition" "baz" {
  policy_id = "${newrelic_alert_policy.foo.id}"

  name          = "baz"
  monitor_id    = "${data.newrelic_synthetics_monitor.bar.id}"
  runbook_url   = "https://www.example.com"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the synthetics monitor in New Relic.

» Attributes Reference

- **id** - The ID of the synthetics monitor.

» newrelic__alert__channel

Use this data source to get information about an specific alert policy in New Relic which already exists.

» Example Usage

```
data "newrelic_alert_channel" "foo" {
  name = "foo@example.com"
}

data "newrelic_alert_policy" "foo" {
```

```

    name = "foo policy"
  }

  resource "newrelic_alert_policy_channel" "foo" {
    policy_id = "${data.newrelic_alert_policy.foo.id}"
    channel_id = "${data.newrelic_alert_channel.foo.id}"
  }

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the alert policy in New Relic.

» Attributes Reference

- **id** - The ID of the alert policy.
- **incident_preference** - The rollup strategy for the policy. Options include: `PER_POLICY`, `PER_CONDITION`, or `PER_CONDITION_AND_TARGET`. The default is `PER_POLICY`.
- **created_at** - The time the policy was created.
- **updated_at** - The time the policy was last updated.

» newrelic__alert__channel

» Example Usage

```

resource "newrelic_alert_channel" "foo" {
  name = "foo"
  type = "email"

  configuration = {
    recipients          = "foo@example.com"
    include_json_attachment = "1"
  }
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the channel.

- **type** - (Required) The type of channel. One of: `campfire`, `email`, `hipchat`, `opsgenie`, `pagerduty`, `slack`, `victorops`, or `webhook`.
- **configuration** - (Required) A map of key / value pairs with channel type specific values.

» Attributes Reference

The following attributes are exported:

- **id** - The ID of the channel.

» Import

Alert channels can be imported using the `id`, e.g.

```
$ terraform import newrelic_alert_channel.main 12345
```

» newrelic_alert_condition

» Example Usage

```
data "newrelic_application" "app" {
  name = "my-app"
}

resource "newrelic_alert_policy" "foo" {
  name = "foo"
}

resource "newrelic_alert_condition" "foo" {
  policy_id = "${newrelic_alert_policy.foo.id}"

  name          = "foo"
  type          = "apm_app_metric"
  entities      = ["${data.newrelic_application.app.id}"]
  metric        = "apdex"
  runbook_url   = "https://www.example.com"

  term {
    duration      = 5
    operator      = "below"
    priority      = "critical"
    threshold     = "0.75"
  }
}
```

```

    time_function = "all"
  }
}

```

» Argument Reference

The following arguments are supported:

- **policy_id** - (Required) The ID of the policy where this condition should be used.
- **name** - (Required) The title of the condition. Must be between 1 and 64 characters, inclusive.
- **type** - (Required) The type of condition. One of: `apm_app_metric`, `apm_jvm_metric`, `apm_kt_metric`, `servers_metric`, `browser_metric`, `mobile_metric`
- **entities** - (Required) The instance IDS associated with this condition.
- **metric** - (Required) The metric field accepts parameters based on the type set.
- **gc_metric** - (Optional) A valid Garbage Collection metric e.g. `GC/G1 Young Generation`. This is required if you are using `apm_jvm_metric` with `gc_cpu_time` condition type.
- **violation_close_timer** - (Optional) Automatically close instance-based violations, including JVM health metric violations, after the number of hours specified. Must be: 1, 2, 4, 8, 12 or 24.
- **runbook_url** - (Optional) Runbook URL to display in notifications.
- **condition_scope** - (Optional) `instance` or `application`. This is required if you are using the JVM plugin in New Relic.
- **term** - (Required) A list of terms for this condition. See Terms below for details.
- **user_defined_metric** - (Optional) A custom metric to be evaluated.
- **user_defined_value_function** - (Optional) One of: `average`, `min`, `max`, `total`, or `sample_size`.

» Terms

The term mapping supports the following arguments:

- **duration** - (Required) In minutes, must be: 5, 10, 15, 30, 60, or 120.
- **operator** - (Optional) `above`, `below`, or `equal`. Defaults to `equal`.
- **priority** - (Optional) `critical` or `warning`. Defaults to `critical`.
- **threshold** - (Required) Must be 0 or greater.
- **time_function** - (Required) `all` or `any`.

» Attributes Reference

The following attributes are exported:

- `id` - The ID of the alert condition.

» Import

Alert conditions can be imported using the `id`, e.g.

```
$ terraform import newrelic_alert_condition.main 12345
```

» `newrelic_alert_policy`

» Example Usage

```
resource "newrelic_alert_policy" "foo" {  
  name = "foo"  
}
```

» Argument Reference

The following arguments are supported:

- `name` - (Required) The name of the policy.
- `incident_preference` - (Optional) The rollup strategy for the policy. Options include: `PER_POLICY`, `PER_CONDITION`, or `PER_CONDITION_AND_TARGET`. The default is `PER_POLICY`.

» Attributes Reference

The following attributes are exported:

- `id` - The ID of the policy.
- `created_at` - The time the policy was created.
- `updated_at` - The time the policy was last updated.

» Import

Alert policies can be imported using the `id`, e.g.

```
$ terraform import newrelic_alert_policy.main 12345
```


» newrelic__alert__policy__channel

» Example Usage

```
resource "newrelic_alert_policy" "foo" {
  name = "foo"
}

resource "newrelic_alert_channel" "foo" {
  name = "foo"
  type = "email"

  configuration = {
    recipients          = "foo@example.com"
    include_json_attachment = "1"
  }
}

resource "newrelic_alert_policy_channel" "foo" {
  policy_id = "${newrelic_alert_policy.foo.id}"
  channel_id = "${newrelic_alert_channel.foo.id}"
}
```

» Argument Reference

The following arguments are supported:

- `policy_id` - (Required) The ID of the policy.
- `channel_id` - (Required) The ID of the channel.

» newrelic__nrql__alert__condition

» Example Usage

```
resource "newrelic_alert_policy" "foo" {
  name = "foo"
}

resource "newrelic_nrql_alert_condition" "foo" {
  policy_id = "${newrelic_alert_policy.foo.id}"

  name          = "foo"
  runbook_url = "https://www.example.com"
```

```

enabled      = true

term {
  duration      = 5
  operator      = "below"
  priority      = "critical"
  threshold     = "1"
  time_function = "all"
}

nrql {
  query          = "SELECT count(*) FROM SyntheticCheck WHERE monitorId = '<monitorId>'"
  since_value    = "3"
}

value_function = "single_value"
}

```

» Argument Reference

The following arguments are supported:

- **policy_id** - (Required) The ID of the policy where this condition should be used.
- **name** - (Required) The title of the condition
- **runbook_url** - (Optional) Runbook URL to display in notifications.
- **enabled** - (Optional) Set whether to enable the alert condition. Defaults to **true**.
- **term** - (Required) A list of terms for this condition. See Terms below for details.
- **nrql** - (Required) A NRQL query. See NRQL below for details.
- **value_function** - (Optional) Possible values are **single_value**, **sum**.

» Terms

The **term** mapping supports the following arguments:

- **duration** - (Required) In minutes, must be: 1, 2, 3, 4, 5, 10, 15, 30, 60, or 120.
- **operator** - (Optional) **above**, **below**, or **equal**. Defaults to **equal**.
- **priority** - (Optional) **critical** or **warning**. Defaults to **critical**.
- **threshold** - (Required) Must be 0 or greater.
- **time_function** - (Required) **all** or **any**.

» NRQL

The `nrql` attribute supports the following arguments:

- `query` - (Required) The NRQL query to execute for the condition.
- `since_value` - (Required) The value to be used in the `SINCE <X> MINUTES AGO` clause for the NRQL query. Must be between 1 and 20.

» Attributes Reference

The following attributes are exported:

- `id` - The ID of the NRQL alert condition.

» Import

Alert conditions can be imported using the `id`, e.g.

```
$ terraform import newrelic_nrql_alert_condition.main 12345
```

» `newrelic__infra__alert__condition`

» Example Usage

```
resource "newrelic_alert_policy" "foo" {
  name = "foo"
}

resource "newrelic_infra_alert_condition" "foo" {
  policy_id = "${newrelic_alert_policy.foo.id}"

  name      = "High disk usage"
  type      = "infra_metric"
  event     = "StorageSample"
  select    = "diskUsedPercent"
  comparison = "above"
  where     = "(`hostname` LIKE '%frontend%')"

  critical {
    duration      = 25
    value         = 90
    time_function = "all"
  }
}
```

» Argument Reference

The following arguments are supported:

- **policy_id** - (Required) The ID of the alert policy where this condition should be used.
- **name** - (Required) The Infrastructure alert condition's name.
- **enabled** - (Optional) Set whether to enable the alert condition. Defaults to **true**.
- **type** - (Required) The type of Infrastructure alert condition: "infra_process_running", "infra_metric", or "infra_host_not_reporting".
- **event** - (Required) The metric event; for example, system metrics, process metrics, storage metrics, or network metrics.
- **select** - (Required) The attribute name to identify the type of metric condition; for example, "network", "process", "system", or "storage".
- **comparison** - (Required) The operator used to evaluate the threshold value; "above", "below", "equal".
- **critical** - (Required) Identifies the critical threshold parameters for triggering an alert notification. See Thresholds below for details.
- **warning** - (Optional) Identifies the warning threshold parameters. See Thresholds below for details.
- **where** - (Optional) Infrastructure host filter for the alert condition.
- **process_where** - (Optional) Any filters applied to processes; for example: "commandName = 'java'".
- **integration_provider** - (Optional) For alerts on integrations, use this instead of **event**.

» Thresholds

The **critical** and **warning** threshold mapping supports the following arguments:

- **duration** - (Required) Identifies the number of minutes the threshold must be passed or met for the alert to trigger. Threshold durations must be between 1 and 60 minutes (inclusive).
- **value** - (Optional) Threshold value, computed against the **comparison** operator. Supported by "infra_metric" and "infra_process_running" alert condition types.
- **time_function** - (Optional) Indicates if the condition needs to be sustained or to just break the threshold once; **all** or **any**. Supported by the "infra_metric" alert condition type.

» Attributes Reference

The following attributes are exported:

- `id` - The ID of the Infrastructure alert condition.

» `newrelic__synthetics__alert__condition`

» Example Usage

```
data "newrelic_synthetics_monitor" "foo" {
  name = "foo"
}

resource "newrelic_synthetics_alert_condition" "foo" {
  policy_id = "${newrelic_alert_policy.foo.id}"

  name          = "foo"
  monitor_id    = "${data.newrelic_synthetics_monitor.foo.id}"
  runbook_url   = "https://www.example.com"
}
```

» Argument Reference

The following arguments are supported:

- `policy_id` - (Required) The ID of the policy where this condition should be used.
- `name` - (Required) The title of this condition.
- `monitor_id` - (Required) The ID of the Synthetics monitor to be referenced in the alert condition.
- `runbook_url` - (Optional) Runbook URL to display in notifications.
- `enabled` - (Optional) Set whether to enable the alert condition. Defaults to `true`.

» Attributes Reference

The following attributes are exported:

- `id` - The ID of the Synthetics alert condition.

» `newrelic__synthetics__monitor`

Use this resource to create, update, and delete a synthetics monitor in New Relic.

» Example Usage

```
resource "newrelic_synthetics_monitor" "foo" {
  name = "foo"
  type = "SIMPLE"
  frequency = 5
  status = "ENABLED"
  locations = ["AWS_US_EAST_1"]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The title of this monitor.
- **type** - (Required) The monitor type.
- **frequency** - (Required) The interval (in minutes) at which this monitor should run.
- **status** - (Required) The monitor status (i.e. ENABLED, MUTED, DISABLED)
- **locations** - (Required) The locations in which this monitor should be run.
- **sla_threshold** - (Optional) The base threshold for the SLA report.

For SIMPLE and BROWSER monitor types, the following arguments are also supported:

- **uri** - (Required) The URI for the monitor to hit.
- **validation_string** - (Optional) The string to validate against in the response.
- **verify_ssl** - (Optional) Verify SSL.
- **bypass_head_request** - (Optional) Bypass HEAD request.
- **treat_redirect_as_failure** - (Optional) Fail the monitor check if redirected.

» Attributes Reference

The following attributes are exported:

- **id** - The ID of the Synthetics monitor.

» newrelic_synthetics_monitor_script

Use this resource to update a synthetics monitor script in New Relic.

» Example Usage

```
data "template_file" "foo_script" {
  template = "${file("${path.module}/foo_script.tpl")}"
}

resource "newrelic_synthetic_monitor_script" "foo_script" {
  monitor_id = "${newrelic_synthetic_monitor.foo.id}"
  text = "${data.template_file.foo_script.rendered}"
}
```

» Argument Reference

The following arguments are supported:

- `monitor_id` - (Required) The ID of the monitor to attach the script to.
- `text` - (Required) plaintext of the monitor script.

» Attributes Reference

The following attributes are exported:

- `id` - The ID of the Synthetics monitor that the script is attached to.

» newrelic__dashboard

» Example Usage

```
resource "newrelic_dashboard" "exampledash" {
  title = "New Relic Terraform Example"

  widget {
    title      = "Average Transaction Duration"
    row        = 1
    column     = 1
    width      = 2
    visualization = "faceted_line_chart"
    nrql       = "SELECT AVERAGE(duration) from Transaction FACET appName TIMESERIES auto"
  }

  widget {
    title      = "Page Views"
    row        = 1
  }
}
```

```

        column      = 3
        visualization = "billboard"
        nrql         = "SELECT count(*) FROM PageView SINCE 1 week ago"
    }
}

```

» Argument Reference

The following arguments are supported:

- **title** - (Required) The title of the dashboard.
- **icon** - (Optional) The icon for the dashboard. Defaults to **bar-chart**.
- **visibility** - (Optional) Who can see the dashboard in an account. Must be **owner** or **all**. Defaults to **all**.
- **widget** - (Optional) A widget that describes a visualization. See Widgets below for details.
- **editable** - (Optional) Who can edit the dashboard in an account. Must be **read_only**, **editable_by_owner**, **editable_by_all**, or **all**. Defaults to **editable_by_all**.

» Widgets

The widget mapping supports the following arguments:

- **title** - (Required) A title for the widget.
- **visualization** - (Required) How the widget visualizes data.
- **row** - (Required) Row position of widget from top left, starting at 1.
- **column** - (Required) Column position of widget from top left, starting at 1.
- **width** - (Optional) Width of the widget. Defaults to 1.
- **height** - (Optional) Height of the widget. Defaults to 1.
- **notes** - (Optional) Description of the widget.
- **nrql** - (Optional) Valid NRQL query string. See Writing NRQL Queries for help.

» Attributes Reference

The following attributes are exported:

- **id** - The ID of the dashboard.