

## » packet\_\_precreated\_\_ip\_\_block

Use this data source to get CIDR expression for precreated IPv6 and IPv4 blocks in Packet. You can then use the cidrsubnet TF builtin function to derive subnets.

### » Example Usage

```
# Create project, device in it, and then assign /64 subnet from precreated block
# to the new device

resource "packet_project" "test" {
  name = "testpro"
}

resource "packet_device" "web1" {
  hostname      = "tftest"
  plan          = "baremetal_0"
  facility      = "ewr1"
  operating_system = "ubuntu_16_04"
  billing_cycle  = "hourly"
  project_id    = "${packet_project.test.id}"
}

# we have to make the datasource depend on the device. Here I do it implicitly
# with the project_id param, because an explicit "depends_on" attribute in
# a datasource taints the state:
# https://github.com/hashicorp/terraform/issues/11806
data "packet_precreated_ip_block" "test" {
  facility      = "ewr1"
  project_id    = "${packet_device.test.project_id}"
  address_family = 6
  public        = true
}

# The precreated IPv6 blocks are /56, so to get /64, we specify 8 more bits for network.
# The cidrsubnet interpolation will pick second /64 subnet from the precreated block.

resource "packet_ip_attachment" "from_ipv6_block" {
  device_id = "${packet_device.web1.id}"
  cidr_notation = "${cidrsubnet(data.packet_precreated_ip_block.test.cidr_notation,8,2)}"
}
```

## » Argument Reference

- `project_id` - (Required) ID of the project where the searched block should be.
- `address_family` - (Required) 4 or 6, depending on which block you are looking for.
- `public` - (Required) Whether to look for public or private block.
- `facility` - (Required) Facility of the searched block.

## » Attributes Reference

- `cidr_notation` - CIDR notation of the looked up block.

## » `packet_device`

Provides a Packet device resource. This can be used to create, modify, and delete devices.

**Note:** All arguments including the `root_password` and `user_data` will be stored in the raw state as plain-text. Read more about sensitive data in state.

## » Example Usage

```
# Create a device and add it to cool_project
resource "packet_device" "web1" {
  hostname      = "tf.coreos2"
  plan          = "baremetal_1"
  facility      = "ewr1"
  operating_system = "coreos_stable"
  billing_cycle  = "hourly"
  project_id     = "${packet_project.cool_project.id}"
}

# Same as above, but boot via iPXE initially, using the Ignition Provider for provisioning
resource "packet_device" "pxe1" {
  hostname      = "tf.coreos2-pxe"
  plan          = "baremetal_1"
  facility      = "ewr1"
  operating_system = "custom_ipxe"
  billing_cycle  = "hourly"
  project_id     = "${packet_project.cool_project.id}"
  ipxe_script_url = "https://rawgit.com/cloudnativelabs/pxe/master/packet/coreos-stable-pa
  always_pxe     = "false"
```

```

    user_data          = "${data.ignition_config.example.rendered}"
  }

# Deploy device on next-available reserved hardware and do custom partitioning.
resource "packet_device" "web1" {
  hostname          = "tftest"
  plan              = "baremetal_0"
  facility          = "sjc1"
  operating_system  = "ubuntu_16_04"
  billing_cycle     = "hourly"
  project_id        = "${packet_project.cool_project.id}"
  hardware_reservation_id = "next-available"
  storage = <<EOS
{
  "disks": [
    {
      "device": "/dev/sda",
      "wipeTable": true,
      "partitions": [
        {
          "label": "BIOS",
          "number": 1,
          "size": 4096
        },
        {
          "label": "SWAP",
          "number": 2,
          "size": "3993600"
        },
        {
          "label": "ROOT",
          "number": 3,
          "size": 0
        }
      ]
    }
  ],
  "filesystems": [
    {
      "mount": {
        "device": "/dev/sda3",
        "format": "ext4",
        "point": "/",
        "create": {
          "options": [
            "-L",

```

```

        "ROOT"
      ]
    }
  },
  {
    "mount": {
      "device": "/dev/sda2",
      "format": "swap",
      "point": "none",
      "create": {
        "options": [
          "-L",
          "SWAP"
        ]
      }
    }
  }
]
}
EOS
}

```

## » Argument Reference

The following arguments are supported:

- **hostname** - (Required) The device name
- **project\_id** - (Required) The id of the project in which to create the device
- **operating\_system** - (Required) The operating system slug
- **facility** - (Required) The facility in which to create the device
- **plan** - (Required) The hardware config slug
- **billing\_cycle** - (Required) monthly or hourly
- **user\_data** (Optional) - A string of the desired User Data for the device.
- **public\_ipv4\_subnet\_size** (Optional) - Size of allocated subnet, more information is in the Custom Subnet Size doc.
- **ipxe\_script\_url** (Optional) - URL pointing to a hosted iPXE script. More information is in the Custom iPXE doc.
- **always\_pxe** (Optional) - If true, a device with OS `custom_ipxe` will continue to boot via iPXE on reboots.
- **hardware\_reservation\_id** (Optional) - The id of hardware reservation where you want this device deployed, or `next-available` if you want to pick your next available reservation automatically.
- **storage** (Optional) - JSON for custom partitioning. Only usable on re-

served hardware. More information in in the Custom Partitioning and RAID doc.

## » Attributes Reference

The following attributes are exported:

- `id` - The ID of the device
- `hostname` - The hostname of the device
- `project_id` - The ID of the project the device belongs to
- `facility` - The facility the device is in
- `plan` - The hardware config of the device
- `network` - The device's private and public IP (v4 and v6) network details
- `access_public_ipv6` - The ipv6 maintenance IP assigned to the device
- `access_public_ipv4` - The ipv4 maintenance IP assigned to the device
- `access_private_ipv4` - The ipv4 private IP assigned to the device
- `locked` - Whether the device is locked
- `billing_cycle` - The billing cycle of the device (monthly or hourly)
- `operating_system` - The operating system running on the device
- `state` - The status of the device
- `created` - The timestamp for when the device was created
- `updated` - The timestamp for the last time the device was updated
- `tags` - Tags attached to the device
- `hardware_reservation_id` - The id of hardware reservation which this device occupies
- `root_password` - Root password to the server (disabled after 24 hours)

## » `packet__project`

Provides a Packet Project resource to allow you manage devices in your projects.

## » Example Usage

```
# Create a new Project
resource "packet_project" "tf_project_1" {
  name          = "Terraform Fun"
  payment_method = "payment-method-id"
}
```

## » Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the Project on Packet.net
- **payment\_method** - (Optional) The unique ID of the payment method on file to use for services created in this project. If not given, the project will use the default payment method for your user.

## » Attributes Reference

The following attributes are exported:

- **id** - The unique ID of the project
- **payment\_method** - The unique ID of the payment method on file to use for services created in this project.
- **created** - The timestamp for when the Project was created
- **updated** - The timestamp for the last time the Project was updated

## » packet\_ssh\_key

Provides a Packet SSH key resource to allow you manage SSH keys on your account. All SSH keys on your account are loaded on all new devices, they do not have to be explicitly declared on device creation.

## » Example Usage

```
# Create a new SSH key
resource "packet_ssh_key" "key1" {
  name      = "terraform-1"
  public_key = "${file("/home/terraform/.ssh/id_rsa.pub")}"
}
```

## » Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the SSH key for identification
- **public\_key** - (Required) The public key. If this is a file, it can be read using the file interpolation function

## » Attributes Reference

The following attributes are exported:

- **id** - The unique ID of the key

- `name` - The name of the SSH key
- `public_key` - The text of the public key
- `fingerprint` - The fingerprint of the SSH key
- `created` - The timestamp for when the SSH key was created
- `updated` - The timestamp for the last time the SSH key was updated

## » `packet__volume`

Provides a Packet Block Storage Volume resource to allow you to manage block volumes on your account. Once created by Terraform, they must then be attached and mounted using the `api` and `packet_block_attach` and `packet_block_detach` scripts.

## » Example Usage

```
# Create a new block volume
resource "packet_volume" "volume1" {
  description    = "terraform-volume-1"
  facility       = "ewr1"
  project_id     = "${packet_project.cool_project.id}"
  plan           = "storage_1"
  size           = 100
  billing_cycle  = "hourly"

  snapshot_policies = {
    snapshot_frequency = "1day"

    snapshot_count = 7
  }

  snapshot_policies = {
    snapshot_frequency = "1month"

    snapshot_count = 6
  }
}
```

## » Argument Reference

The following arguments are supported:

- `plan` - (Required) The service plan slug of the volume
- `facility` - (Required) The facility to create the volume in

- `project_id` - (Required) The packet project ID to deploy the volume in
- `size` - (Required) The size in GB to make the volume
- `billing_cycle` - The billing cycle, defaults to "hourly"
- `description` - Optional description for the volume
- `snapshot_policies` - Optional list of snapshot policies

## » Attributes Reference

The following attributes are exported:

- `id` - The unique ID of the volume
- `name` - The name of the volume
- `description` - The description of the volume
- `size` - The size in GB of the volume
- `plan` - Performance plan the volume is on
- `billing_cycle` - The billing cycle, defaults to hourly
- `facility` - The facility slug the volume resides in
- `state` - The state of the volume
- `locked` - Whether the volume is locked or not
- `project_id` - The project id the volume is in
- `attachments` - A list of attachments, each with it's own `href` attribute
- `created` - The timestamp for when the volume was created
- `updated` - The timestamp for the last time the volume was updated

## » `packet__volume__attachment`

Provides attachment of Packet Block Storage Volume to Devices.

Device and volume must be in the same location (facility).

Once attached by Terraform, they must then be mounted using the `packet_block_attach` and `packet_block_detach` scripts.

## » Example Usage

```
resource "packet_project" "test_project" {
  name = "test-project"
}

resource "packet_device" "test_device_va" {
  hostname      = "terraform-test-device-va"
  plan          = "baremetal_0"
  facility      = "ewr1"
  operating_system = "ubuntu_16_04"
```



```

        billing_cycle    = "hourly"
        project_id       = "${packet_project.test_project.id}"
    }

    resource "packet_volume" "test_volume_va" {
        plan = "storage_1"
        billing_cycle = "hourly"
        size = 100
        project_id = "${packet_project.test_project.id}"
        facility = "ewr1"
        snapshot_policies = { snapshot_frequency = "1day", snapshot_count = 7 }
    }

    resource "packet_volume_attachment" "test_volume_attachment" {
        device_id = "${packet_device.test_device_va.id}"
        volume_id = "${packet_volume.test_volume_va.id}"
    }

```

## » Argument Reference

The following arguments are supported:

- `volume_id` - (Required) The ID of the volume to attach
- `device_id` - (Required) The ID of the device to which the volume should be attached

## » Attributes Reference

The following attributes are exported:

- `id` - The unique ID of the volume attachment