

» mailgun__domain

Provides a Mailgun App resource. This can be used to create and manage applications on Mailgun.

» Example Usage

```
# Create a new Mailgun domain
resource "mailgun_domain" "default" {
  name           = "test.example.com"
  spam_action    = "disabled"
  smtp_password  = "foobar"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The domain to add to Mailgun
- **smtp_password** - (Required) Password for SMTP authentication
- **spam_action** - (Optional) **disabled** or **tag** Disable, no spam filtering will occur for inbound messages. Tag, messages will be tagged with a spam header.
- **wildcard** - (Optional) Boolean that determines whether the domain will accept email for sub-domains.

» Attributes Reference

The following attributes are exported:

- **name** - The name of the domain.
- **smtp_login** - The login email for the SMTP server.
- **smtp_password** - The password to the SMTP server.
- **wildcard** - Whether or not the domain will accept email for sub-domains.
- **spam_action** - The spam filtering setting.
- **receiving_records** - A list of DNS records for receiving validation.
 - **priority** - The priority of the record.
 - **record_type** - The record type.
 - **valid** - "valid" if the record is valid.
 - **value** - The value of the record.
- **sending_records** - A list of DNS records for sending validation.
 - **name** - The name of the record.
 - **record_type** - The record type.
 - **valid** - "valid" if the record is valid.

– **value** - The value of the record.