

» packet__device

Provides a Packet device datasource.

Note: All arguments including the `root_password` and `user_data` will be stored in the raw state as plain-text. Read more about sensitive data in state.

» Example Usage

```
# Fetch a device data and show it's ID

data "packet_device" "test" {
  project_id      = "${local.project_id}"
  hostname        = "mydevice"
}

output "id" {
  value = "${data.packet_device.test.id}"
}
```

» Argument Reference

The following arguments are supported:

- `hostname` - (Required) The device name
- `project_id` - (Required) The id of the project in which the devices exists

» Attributes Reference

The following attributes are exported:

- `access_private_ipv4` - The ipv4 private IP assigned to the device
- `access_public_ipv4` - The ipv4 management IP assigned to the device
- `access_public_ipv6` - The ipv6 management IP assigned to the device
- `billing_cycle` - The billing cycle of the device (monthly or hourly)
- `facility` - The facility where the device is deployed.
- `description` - Description string for the device
- `hardware_reservation_id` - The id of hardware reservation which this device occupies
- `id` - The ID of the device
- `network` - The device's private and public IP (v4 and v6) network details. When a device is run without any special network configuration, it will have 3 networks:
 - Public IPv4 at `packet_device.name.network.0`

- IPv6 at `packet_device.name.network.1`
- Private IPv4 at `packet_device.name.network.2` Elastic addresses then stack by type - an assigned public IPv4 will go after the management public IPv4 (to index 1), and will then shift the indices of the IPv6 and private IPv4. Assigned private IPv4 will go after the management private IPv4 (to the end of the network list). The fields of the network attributes are:
 - `address` - IPv4 or IPv6 address string
 - `cidr` - Bit length of the network mask of the address
 - `gateway` - Address of router
 - `public` - Whether the address is routable from the Internet
 - `family` - IP version - "4" or "6"
- `network_type` - L2 network type of the device, one of "layer3", "layer2-bonded", "layer2-individual", "hybrid"
- `operating_system` - The operating system running on the device
- `plan` - The hardware config of the device
- `ports` - Ports assigned to the device
 - `name` - Name of the port (e.g. `eth0`, or `bond0`)
 - `id` - ID of the port
 - `type` - Type of the port (e.g. `NetworkPort` or `NetworkBondPort`)
 - `mac` - MAC address assigned to the port
 - `bonded` - Whether this port is part of a bond in bonded network setup
- `root_password` - Root password to the server (if still available)
- `ssh_key_ids` - List of IDs of SSH keys deployed in the device, can be both user or project SSH keys
- `state` - The state of the device
- `tags` - Tags attached to the device

» `packet_precreated_ip_block`

Use this data source to get CIDR expression for precreated IPv6 and IPv4 blocks in Packet. You can then use the `cidrsubnet` TF builtin function to derive subnets.

» Example Usage

```
# Create device in your project and then assign /64 subnet from precreated block
# to the new device

# Declare your project ID
locals {
  project_id = "<UUID_of_your_project>"
}
```

```

}

resource "packet_device" "web1" {
  hostname      = "web1"
  plan          = "t1.small.x86"
  facilities    = ["ewr1"]
  operating_system = "ubuntu_16_04"
  billing_cycle = "hourly"
  project_id    = "${local.project_id}"
}

data "packet_precreated_ip_block" "test" {
  facility      = "ewr1"
  project_id    = "${local.project_id}"
  address_family = 6
  public        = true
}

# The precreated IPv6 blocks are /56, so to get /64, we specify 8 more bits for network.
# The cidrsubnet interpolation will pick second /64 subnet from the precreated block.

resource "packet_ip_attachment" "from_ipv6_block" {
  device_id = "${packet_device.web1.id}"
  cidr_notation = "${cidrsubnet(data.packet_precreated_ip_block.test.cidr_notation,8,2)}"
}

```

» Argument Reference

- **project_id** - (Required) ID of the project where the searched block should be.
- **address_family** - (Required) 4 or 6, depending on which block you are looking for.
- **public** - (Required) Whether to look for public or private block.
- **global** - (Optional) Whether to look for global block. Default is false for backward compatibility.
- **facility** - (Optional) Facility of the searched block. (Optional) Only allowed for non-global blocks.

» Attributes Reference

- **cidr_notation** - CIDR notation of the looked up block.

» `packet__operating__system`

Use this data source to get Packet Operating System image.

» Example Usage

```
data "packet_operating_system" "example" {
  name           = "Container Linux"
  distro         = "coreos"
  version        = "alpha"
  provisionable_on = "c1.small.x86"
}

resource "packet_device" "server" {
  hostname      = "tf.coreos2"
  plan          = "c1.small.x86"
  facilities    = ["ewr1"]
  operating_system = "${data.packet_operating_system.example.id}"
  billing_cycle  = "hourly"
  project_id    = "${local.project_id}"
}
```

» Argument Reference

- `distro` - (Optional) Name of the OS distribution.
- `name` - (Optional) Name or part of the name of the distribution. Case insensitive.
- `provisionable_on` - (Optional) Plan name.
- `version` - (Optional) Version of the distribution

» Attributes Reference

- `id` - Operating system slug
- `slug` - Operating system slug (same as `id`)

» `packet__operating__system`

Use this data source to get Packet Spot Market Price.

» Example Usage

```
data "packet_spot_market_price" "example" {
  facility = "ewr1"
  plan     = "c1.small.x86"
}
```

» Argument Reference

- `facility` - (Required) Name of the facility.
- `plan` - (Required) Name of the plan.

» Attributes Reference

- `price` - Current spot market price for given plan in given facility.

» `packet__bgp_session`

Provides a resource to manage BGP sessions in Packet Host. Refer to Packet BGP documentation for more details.

You need to have BGP config enabled in your project.

BGP session must be linked to a device running BIRD or other BGP routing daemon which will control route advertisements via the session to Packet's upstream routers.

» Example Usage

Following HCL illustrates usage of the BGP features in Packet. It will

- spawn a device in a new BGP-enabled project
- reserve a floating IPv4 address in the project in the same location as the device
- configure the floating IPv4 statically in the device
- install and configure BIRD in the device, and make it announce the floating IPv4 locally

```
locals {
  bgp_password = "955dB0b81Ef"
  project_id   = "<UUID_of_your_project>"
}
```

```

# you need to enable BGP config for the project. If you decide to create new
# project, you can use the bgp_config section to enable BGP.
# resource "packet_project" "test" {
#   name = "testpro"
#   bgp_config {
#     deployment_type = "local"
#     md5 = "${local.bgp_password}"
#     asn = 65000
#   }
# }

resource "packet_reserved_ip_block" "addr" {
  project_id = "${local.project_id}"
  facility = "ewr1"
  quantity = 1
}

resource "packet_device" "test" {
  hostname      = "terraform-test-bgp-sesh"
  plan          = "t1.small.x86"
  facilities    = ["ewr1"]
  operating_system = "ubuntu_16_04"
  billing_cycle = "hourly"
  project_id    = "${local.project_id}"
}

resource "packet_bgp_session" "test" {
  device_id = "${packet_device.test.id}"
  address_family = "ipv4"
}

data "template_file" "interface_lo0" {
  template = <<EOF
auto lo:0
iface lo:0 inet static
    address ${floating_ip}
    netmask ${floating_netmask}
EOF

  vars = {
    floating_ip      = "${packet_reserved_ip_block.addr.address}"
    floating_netmask = "${packet_reserved_ip_block.addr.netmask}"
  }
}

```

```

data "template_file" "bird_conf_template" {

    template = <<EOF
filter packet_bgp {
    if net = ${floating_ip}/${floating_cidr} then accept;
}
router id ${private_ipv4};
protocol direct {
    interface "lo";
}
protocol kernel {
    scan time 10;
    persist;
    import all;
    export all;
}
protocol device {
    scan time 10;
}
protocol bgp {
    export filter packet_bgp;
    local as 65000;
    neighbor ${gateway_ip} as 65530;
    password "${bgp_password}";
}
EOF

    vars = {
        floating_ip      = "${packet_reserved_ip_block.addr.address}"
        floating_cidr    = "${packet_reserved_ip_block.addr.cidr}"
        private_ipv4     = "${packet_device.test.network.2.address}"
        gateway_ip       = "${packet_device.test.network.2.gateway}"
        bgp_password     = "${local.bgp_password}"
    }
}

resource "null_resource" "configure_bird" {

    connection {
        type = "ssh"
        host = "${packet_device.test.access_public_ipv4}"
        private_key = "${file("/home/tomk/keys/tkarasek_key.pem")}"
        agent = false
    }

    provisioner "remote-exec" {

```

```

    inline = [
        "apt-get install bird",
        "mv /etc/bird/bird.conf /etc/bird/bird.conf.old",
    ]
}

triggers = {
    template = "${data.template_file.bird_conf_template.rendered}"
    template = "${data.template_file.interface_lo0.rendered}"
}

provisioner "file" {
    content      = "${data.template_file.bird_conf_template.rendered}"
    destination = "/etc/bird/bird.conf"
}

provisioner "file" {
    content      = "${data.template_file.interface_lo0.rendered}"
    destination = "/etc/network/interfaces.d/lo0"
}

provisioner "remote-exec" {
    inline = [
        "sysctl net.ipv4.ip_forward=1",
        "grep /etc/network/interfaces.d /etc/network/interfaces || echo 'source /etc/network/3",
        "ifup lo:0",
        "service bird restart",
    ]
}
}

```

» Argument Reference

The following arguments are supported:

- **device_id** - (Required) ID of device
- **address_family** - (Required) ipv4 or ipv6
- **default_route** - (Optional) Boolean flag to set the default route policy.
False by default.

» Attributes Reference

The following attributes are exported:

- **status**: Status of the session - up or down

» packet__connect

Provides a resource for Packet Connect, a link between Packet VLANs and VLANs in other cloud providers.

» Example Usage

Create a new VLAN in ewr1 and connect it to Azure ExpressRoute

```
resource "packet_vlan" "vlan1" {
  description = "VLAN in New Jersey"
  facility    = "ewr1"
  project_id  = "${local.project_id}"
}

resource "packet_connect" "my_expressroute" {
  name          = "test"
  facility      = "ewr1"
  project_id    = "${local.project_id}"
  # provider ID for Azure ExpressRoute is ed5de8e0-77a9-4d3b-9de0-65281d3aa831
  provider_id   = "ed5de8e0-77a9-4d3b-9de0-65281d3aa831"
  # provider_payload for Azure ExpressRoute provider is your ExpressRoute
  # authorization key (in UUID format)
  provider_payload = "58b4ec12-af34-4435-5435-db3bde4a4b3a"
  port_speed    = 100
  vxlan         = "${packet_vlan.vlan1.vxlan}"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name for the Connect resource
- **facility** - (Required) Facility where to create the VLAN
- **project_id** - (Required) ID of parent project
- **provider_id** - (Required) ID of Connect Provider. Provider IDs are
 - Azure ExpressRoute - "ed5de8e0-77a9-4d3b-9de0-65281d3aa831"
- **provider_payload** - (Required) Authorization key for the Connect provider
- **port_speed** - (Required) Port speed in Mbps
- **vxlan** - (Required) VXLAN Network identifier of the linked Packet VLAN

» Attributes Reference

The following attributes are exported:

- **status** - Status of the Connect resource, one of PROVISIONING, PROVISIONED, DEPROVISIONING, DEPROVISIONED

» packet_device

Provides a Packet device resource. This can be used to create, modify, and delete devices.

Note: All arguments including the `root_password` and `user_data` will be stored in the raw state as plain-text. Read more about sensitive data in state.

» Example Usage

```
# Create a device and add it to cool_project
resource "packet_device" "web1" {
  hostname      = "tf.coreos2"
  plan          = "t1.small.x86"
  facilities    = ["ewr1"]
  operating_system = "coreos_stable"
  billing_cycle  = "hourly"
  project_id    = "${local.project_id}"
}

# Same as above, but boot via iPXE initially, using the Ignition Provider for provisioning
resource "packet_device" "pxe1" {
  hostname      = "tf.coreos2-pxe"
  plan          = "t1.small.x86"
  facilities    = ["ewr1"]
  operating_system = "custom_ipxe"
  billing_cycle  = "hourly"
  project_id    = "${local.project_id}"
  ipxe_script_url = "https://rawgit.com/cloudnativelabs/pxe/master/packet/coreos-stable-pa
  always_pxe    = "false"
  user_data     = "${data.ignition_config.example.rendered}"
}

# Deploy device on next-available reserved hardware and do custom partitioning.
resource "packet_device" "web1" {
  hostname      = "tftest"
  plan          = "t1.small.x86"
  facilities    = ["sjc1"]
}
```

```

operating_system = "ubuntu_16_04"
billing_cycle     = "hourly"
project_id       = "${local.project_id}"
hardware_reservation_id = "next-available"
storage = <<EOS
{
  "disks": [
    {
      "device": "/dev/sda",
      "wipeTable": true,
      "partitions": [
        {
          "label": "BIOS",
          "number": 1,
          "size": 4096
        },
        {
          "label": "SWAP",
          "number": 2,
          "size": "3993600"
        },
        {
          "label": "ROOT",
          "number": 3,
          "size": 0
        }
      ]
    }
  ],
  "filesystems": [
    {
      "mount": {
        "device": "/dev/sda3",
        "format": "ext4",
        "point": "/",
        "create": {
          "options": [
            "-L",
            "ROOT"
          ]
        }
      }
    }
  ],
  {
    "mount": {
      "device": "/dev/sda2",

```

```

        "format": "swap",
        "point": "none",
        "create": {
            "options": [
                "-L",
                "SWAP"
            ]
        }
    }
}
EOS
}

```

» Argument Reference

The following arguments are supported:

- **hostname** - (Required) The device name
- **project_id** - (Required) The id of the project in which to create the device
- **operating_system** - (Required) The operating system slug. To find the slug, or visit Operating Systems API docs, set your API auth token in the top of the page and see JSON from the API response.
- **facilities** - List of facility codes with deployment preferences. Packet API will go through the list and will deploy your device to first facility with free capacity. List items must be facility codes or **any** (a wildcard). To find the facility code, visit Facilities API docs, set your API auth token in the top of the page and see JSON from the API response.
- **plan** - (Required) The device plan slug. To find the plan slug, visit Device plans API docs, set your auth token in the top of the page and see JSON from the API response.
- **billing_cycle** - (Required) monthly or hourly
- **user_data** (Optional) - A string of the desired User Data for the device.
- **public_ipv4_subnet_size** (Optional) - Size of allocated subnet, more information is in the Custom Subnet Size doc.
- **ipxe_script_url** (Optional) - URL pointing to a hosted iPXE script. More information is in the Custom iPXE doc.
- **always_pxe** (Optional) - If true, a device with OS **custom_ipxe** will continue to boot via iPXE on reboots.
- **hardware_reservation_id** (Optional) - The id of hardware reservation where you want this device deployed, or **next-available** if you want to pick your next available reservation automatically.
- **storage** (Optional) - JSON for custom partitioning. Only usable on re-

served hardware. More information in in the Custom Partitioning and RAID doc.

- **tags** - Tags attached to the device
- **description** - Description string for the device
- **project_ssh_key_ids** - Array of IDs of the project SSH keys which should be added to the device. If you omit this, SSH keys of all the members of the parent project will be added to the device. If you specify this array, only the listed project SSH keys will be added. Project SSH keys can be created with the `[packet_project_ssh_key][packet_project_ssh_key.html]` resource.
- **network_type** (Optional) - Network type of device, used for Layer 2 networking. Allowed values are `layer3`, `hybrid`, `layer2-individual` and `layer2-bonded`. If you keep it empty, Terraform will not handle the network type of the device.
- **ip_address_types** (Optional) - A set containing one or more of `[private_ipv4, public_ipv4, public_ipv6]`. It specifies which IP address types a new device should obtain. If omitted, a created device will obtain all 3 addresses. If you only want private IPv4 address for the new device, pass `[private_ipv4]`.
- **wait_for_reservation_deprovision** (Optional) - Only used for devices in reserved hardware. If set, the deletion of this device will block until the hardware reservation is marked provisionable (about 4 minutes in August 2019).

» Attributes Reference

The following attributes are exported:

- **access_private_ipv4** - The ipv4 private IP assigned to the device
- **access_public_ipv4** - The ipv4 maintenance IP assigned to the device
- **access_public_ipv6** - The ipv6 maintenance IP assigned to the device
- **billing_cycle** - The billing cycle of the device (monthly or hourly)
- **created** - The timestamp for when the device was created
- **deployed_facility** - The facility where the device is deployed.
- **description** - Description string for the device
- **hardware_reservation_id** - The id of hardware reservation which this device occupies
- **hostname** - The hostname of the device
- **id** - The ID of the device
- **locked** - Whether the device is locked
- **network** - The device's private and public IP (v4 and v6) network details. When a device is run without any special network configuration, it will have 3 networks:
 - Public IPv4 at `packet_device.name.network.0`
 - IPv6 at `packet_device.name.network.1`

- Private IPv4 at `packet_device.name.network.2` Elastic addresses then stack by type - an assigned public IPv4 will go after the management public IPv4 (to index 1), and will then shift the indices of the IPv6 and private IPv4. Assigned private IPv4 will go after the management private IPv4 (to the end of the network list). The fields of the network attributes are:
 - `address` - IPv4 or IPv6 address string
 - `cidr` - bit length of the network mask of the address
 - `gateway` - address of router
 - `public` - whether the address is routable from the Internet
 - `family` - IP version - "4" or "6"
- `operating_system` - The operating system running on the device
- `plan` - The hardware config of the device
- `ports` - Ports assigned to the device
 - `name` - Name of the port (e.g. `eth0`, or `bond0`)
 - `id` - ID of the port
 - `type` - Type of the port (e.g. `NetworkPort` or `NetworkBondPort`)
 - `mac` - MAC address assigned to the port
 - `bonded` - Whether this port is part of a bond in bonded network setup
- `project_id` - The ID of the project the device belongs to
- `root_password` - Root password to the server (disabled after 24 hours)
- `ssh_key_ids` - List of IDs of SSH keys deployed in the device, can be both user and project SSH keys
- `state` - The status of the device
- `tags` - Tags attached to the device
- `updated` - The timestamp for the last time the device was updated

» `packet_ip_attachment`

Provides a resource to attach elastic IP subnets to devices.

To attach an IP subnet from a reserved block to a provisioned device, you must derive a subnet CIDR belonging to one of your reserved blocks in the same project and facility as the target device.

For example, you have reserved IPv4 address block 147.229.10.152/30, you can choose to assign either the whole block as one subnet to a device; or 2 subnets with CIDRs 147.229.10.152/31' and 147.229.10.154/31; or 4 subnets with mask prefix length 32. More about the elastic IP subnets is [here](#).

Device and reserved block must be in the same facility.

» Example Usage

```
# Reserve /30 block of max 2 public IPv4 addresses in Parsippany, NJ (ewr1) for myproject
resource "packet_reserved_ip_block" "myblock" {
  project_id = "${local.project_id}"
  facility   = "ewr1"
  quantity   = 2
}

# Assign /32 subnet (single address) from reserved block to a device
resource "packet_ip_attachment" "first_address_assignment" {
  device_id = "${packet_device.mydevice.id}"
  # following interpolation will result to sth like "147.229.10.152/32"
  cidr_notation = "${cidrhost(packet_reserved_ip_block.myblock.cidr_notation,0)}/32"
}
```

» Argument Reference

The following arguments are supported:

- `device_id` - (Required) ID of device to which to assign the subnet
- `cidr_notation` - (Required) CIDR notation of subnet from block reserved in the same project and facility as the device

» Attributes Reference

The following attributes are exported:

- `id` - The unique ID of the assignment
- `device_id` - ID of device to which subnet is assigned
- `cidr_notation` - Assigned subnet in CIDR notation, e.g. "147.229.15.30/31"
- `gateway` - IP address of gateway for the subnet
- `network` - Subnet network address
- `netmask` - Subnet mask in decimal notation, e.g. "255.255.255.0"
- `cidr` - length of CIDR prefix of the subnet as integer
- `address_family` - Address family as integer (4 or 6)
- `public` - boolean flag whether subnet is reachable from the Internet

» packet__organization

Provides a resource to manage organization resource in Packet.

» Example Usage

```
# Create a new Project
resource "packet_organization" "tf_organization_1" {
  name = "foobar"
  description = "quux"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the Organization.
- **description** - Description string.
- **website** - Website link.
- **twitter** - Twitter handle.
- **logo** - Logo URL.

» Attributes Reference

The following attributes are exported:

- **id** - The unique ID of the organization.
- **name** - The name of the Organization.
- **description** - Description string.
- **website** - Website link.
- **twitter** - Twitter handle.
- **logo** - Logo URL.

» packet__port__vlan__attachment

Provides a resource to attach device ports to VLANs.

Device and VLAN must be in the same facility.

If you need this resource to add the port back to bond on removal, set **force_bond = true**.

To learn more about Layer 2 networking in Packet, refer to * <https://support.packet.com/kb/articles/layer-2-configurations> * <https://support.packet.com/kb/articles/layer-2-overview>

» Example Usage

```
# Hybrid network type

resource "packet_vlan" "test" {
  description = "VLAN in New Jersey"
  facility    = "ewr1"
  project_id  = "${local.project_id}"
}

resource "packet_device" "test" {
  hostname      = "test"
  plan          = "m1.xlarge.x86"
  facilities    = ["ewr1"]
  operating_system = "ubuntu_16_04"
  billing_cycle = "hourly"
  project_id    = "${local.project_id}"
  network_type  = "hybrid"
}

resource "packet_port_vlan_attachment" "test" {
  device_id = "${packet_device.test.id}"
  port_name = "eth1"
  vlan_vnid = "${packet_vlan.test.vxlan}"
}

# Layer 2 network

resource "packet_device" "test" {
  hostname      = "test"
  plan          = "m1.xlarge.x86"
  facilities    = ["ewr1"]
  operating_system = "ubuntu_16_04"
  billing_cycle = "hourly"
  project_id    = "${local.project_id}"
  network_type  = "layer2-individual"
}

resource "packet_vlan" "test1" {
  description = "VLAN in New Jersey"
  facility    = "ewr1"
  project_id  = "${local.project_id}"
}
```

```

resource "packet_vlan" "test2" {
  description = "VLAN in New Jersey"
  facility    = "ewr1"
  project_id  = "${local.project_id}"
}

resource "packet_port_vlan_attachment" "test1" {
  device_id = "${packet_device.test.id}"
  vlan_vnid = "${packet_vlan.test1.vxlan}"
  port_name = "eth1"
}

resource "packet_port_vlan_attachment" "test2" {
  device_id  = "${packet_device.test.id}"
  vlan_vnid  = "${packet_vlan.test2.vxlan}"
  port_name  = "eth1"
  native     = true
  depends_on = ["packet_port_vlan_attachment.test1"]
}

```

» Argument Reference

The following arguments are supported:

- `device_id` - (Required) ID of device to be assigned to the VLAN
- `port_name` - (Required) Name of network port to be assigned to the VLAN
- `force_bond` - Add port back to the bond when this resource is removed. Default is false.
- `vlan_vnid` - VXLAN Network Identifier, integer
- `native` - (Optional) Mark this VLAN a native VLAN on the port. This can be used only if this assignment assigns second or further VLAN to the port. To ensure that this attachment is not first on a port, you can use `depends_on` pointing to another `packet_port_vlan_attachment`, just like in the `layer2-individual` example above.

» Attribute Referece

- `id` - UUID of device port used in the assignment
- `vlan_id` - UUID of VLAN API resource
- `port_id` - UUID of device port

» `packet__project`

Provides a Packet project resource to allow you manage devices in your projects.

» Example Usage

```
# Create a new project
resource "packet_project" "tf_project_1" {
  name          = "Terraform Fun"
}
```

Example with BGP config

```
# Create a new Project
resource "packet_project" "tf_project_1" {
  name          = "tftest"
  bgp_config {
    deployment_type = "local"
    md5             = "C179c28c41a85b"
    asn             = 65000
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the project
- **organization_id** - The UUID of organization under which you want to create the project. If you leave it out, the project will be create under your the default organization of your account.
- **payment_method_id** - The UUID of payment method for this project. The payment method and the project need to belong to the same organization (passed with **organization_id**, or default).
- **backend_transfer** - Enable or disable Backend Transfer, default is false
- **bgp_config** - Optional BGP settings. Refer to Packet guide for BGP.

Once you set the BGP config in a project, it can't be removed (due to a limitation in the Packet API). It can be updated.

The **bgp_config** block supports:

- **asn** - Autonomous System Numer for local BGP deployment
- **md5** - (Optional) Password for BGP session in plaintext (not a checksum)
- **deployment_type** - **private** or **public**, the **private** is likely to be usable immediately, the **public** will need to be review by Packet engineers

» Attributes Reference

The following attributes are exported:

- `id` - The unique ID of the project
- `payment_method_id` - The UUID of payment method for this project.
- `organization_id` - The UUID of this project's parent organization.
- `backend_transfer` - Whether Backend Transfer is enabled for this project.
- `created` - The timestamp for when the project was created
- `updated` - The timestamp for the last time the project was updated

The `bgp_config` block additionally exports:

- `status` - status of BGP configuration in the project
- `max_prefix` - The maximum number of route filters allowed per server

» `packet__project__ssh__key`

Provides a Packet project SSH key resource to manage project-specific SSH keys. On contrary to user SSH keys, project SSH keys are used to exclusively populate `authorized_keys` in new devices.

If you supply a list of project SSH keys when creating a new device, only the listed keys are used; user SSH keys are ignored.

» Example Usage

```
locals {
  project_id = "<UUID_of_your_project>"
}

resource "packet_project_ssh_key" "test" {
  name      = "test"
  public_key = "ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQDM/unxJeFqxsTJcu6mhqsMHSaVlpu+Jj/P+44Z"
  project_id = "${local.project_id}"
}

resource "packet_device" "test" {
  hostname      = "test"
  plan          = "baremetal_0"
  facilities    = ["ewr1"]
  operating_system = "ubuntu_16_04"
  billing_cycle = "hourly"
  project_ssh_key_ids = ["${packet_project_ssh_key.test.id}"]
}
```

```

    project_id      = "${local.project_id}"
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the SSH key for identification
- **public_key** - (Required) The public key. If this is a file, it can be read using the file interpolation function
- **project_id** - (Required) The ID of parent project

» Attributes Reference

The following attributes are exported:

- **id** - The unique ID of the key
- **name** - The name of the SSH key
- **public_key** - The text of the public key
- **project_id** - The ID of parent project
- **fingerprint** - The fingerprint of the SSH key
- **created** - The timestamp for when the SSH key was created
- **updated** - The timestamp for the last time the SSH key was updated

» packet__reserved__ip__block

Provides a resource to create and manage blocks of reserved IP addresses in a project.

When a user provisions first device in a facility, Packet API automatically allocates IPv6/56 and private IPv4/25 blocks. The new device then gets IPv6 and private IPv4 addresses from those block. It also gets a public IPv4/31 address. Every new device in the project and facility will automatically get IPv6 and private IPv4 addresses from these pre-allocated blocks. The IPv6 and private IPv4 blocks can't be created, only imported. With this resource, it's possible to create either public IPv4 blocks or global IPv4 blocks.

Public blocks are allocated in a facility. Addresses from public blocks can only be assigned to devices in the facility. Public blocks can have mask from /24 (256 addresses) to /32 (1 address). If you create public block with this resource, you must fill the facility argument.

Addresses from global blocks can be assigned in any facility. Global blocks can have mask from /30 (4 addresses), to /32 (1 address). If you create global block

with this resource, you must specify `type = "global_ipv4"` and you must omit the `facility` argument.

Once IP block is allocated or imported, an address from it can be assigned to device with the `packet_ip_attachment` resource.

» Example Usage

```
# Allocate /30 block of max 2 public IPv4 addresses in Parsippany, NJ (ewr1) for myproject

resource "packet_reserved_ip_block" "two_elastic_addresses" {
  project_id = "${local.project_id}"
  facility   = "ewr1"
  quantity   = 2
}

# Allocate 1 global floating IP, which can be assigned to device in any facility

resource "packet_reserved_ip_block" "test" {
  project_id = "${local.project_id}"
  type       = "global_ipv4"
  quantity   = 1
}
```

» Argument Reference

The following arguments are supported:

- `project_id` - (Required) The packet project ID where to allocate the address block
- `quantity` - (Required) The number of allocated /32 addresses, a power of 2
- `type` - (Optional) Either `"global_ipv4"` or `"public_ipv4"`, defaults to `"public_ipv4"` for backward compatibility
- `facility` - (Optional) Facility where to allocate the public IP address block, makes sense only for `type==public_ipv4`, must be empty for `type==global_ipv4`

» Attributes Reference

The following attributes are exported:

- `facility` - The facility where the block was allocated, empty for global blocks

- `project_id` - To which project the addresses belong
- `quantity` - Number of /32 addresses in the block
- `id` - The unique ID of the block
- `cidr_notation` - Address and mask in CIDR notation, e.g. "147.229.15.30/31"
- `network` - Network IP address portion of the block specification
- `netmask` - Mask in decimal notation, e.g. "255.255.255.0"
- `cidr` - length of CIDR prefix of the block as integer
- `address_family` - Address family as integer (4 or 6)
- `public` - boolean flag whether addresses from a block are public
- `global` - boolean flag whether addresses from a block are global (i.e. can be assigned in any facility)

Idempotent reference to a first /32 address from a reserved block might look like `"${cidrhost(packet_reserved_ip_block.test.cidr_notation,0)}/32"`.

» `packet_ssh_key`

Provides a resource to manage User SSH keys on your Packet user account. If you create a new device in a project, all the keys of the project's collaborators will be injected to the device.

The link between User SSH key and device is implicit. If you want to make sure that a key will be copied to a device, you must ensure that the device resource `depends_on` the key resource.

» Example Usage

```
# Create a new SSH key
resource "packet_ssh_key" "key1" {
  name      = "terraform-1"
  public_key = "${file("/home/terraform/.ssh/id_rsa.pub")}"
}

# Create new device with "key1" included. The device resource "depends_on" the
# key, in order to make sure the key is created before the device.
resource "packet_device" "test" {
  hostname      = "test-device"
  plan          = "t1.small.x86"
  facilities    = ["sjc1"]
  operating_system = "ubuntu_16_04"
  billing_cycle = "hourly"
  project_id    = "${local.project_id}"
  depends_on    = ["packet_ssh_key.key1"]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the SSH key for identification
- **public_key** - (Required) The public key. If this is a file, it can be read using the file interpolation function

» Attributes Reference

The following attributes are exported:

- **id** - The unique ID of the key
- **name** - The name of the SSH key
- **public_key** - The text of the public key
- **fingerprint** - The fingerprint of the SSH key
- **created** - The timestamp for when the SSH key was created
- **updated** - The timestamp for the last time the SSH key was updated

» packet_spot_market_request

Provides a Packet Spot Market Request resource to allow you to manage spot market requests on your account. <https://support.packet.com/kb/articles/spot-market>

» Example Usage

```
# Create a spot market request
resource "packet_spot_market_request" "req" {
  project_id      = "${local.project_id}"
  max_bid_price   = 0.03
  facilities      = ["ewr1"]
  devices_min     = 1
  devices_max     = 1

  instance_parameters {
    hostname       = "testspot"
    billing_cycle  = "hourly"
    operating_system = "coreos_stable"
    plan           = "t1.small.x86"
  }
}
```


» Argument Reference

The following arguments are supported:

- `devices_max` - (Required) Maximum number devices to be created
- `devices_min` - (Required) Minimum number devices to be created
- `max_bid_price` - (Required) Maximum price user is willing to pay per hour per device
- `facilities` - (Required) Facility IDs where devices should be created
- `instance_parameters` - (Required) Device parameters. See device resource for details
- `project_id` - (Required) Project ID
- `wait_for_devices` - (Optional) On resource creation - wait until all desired devices are active, on resource destruction - wait until devices are removed

» Timeouts

The `timeouts` block allows you to specify timeouts for certain actions:

- `create` - (Defaults to 60 mins) Used when creating the Spot Market Request and `wait_for_devices == true`
- `delete` - (Defaults to 60 mins) Used when destroying the Spot Market Request and `wait_for_devices == true`

» Attributes Reference

The following attributes are exported:

- `id` - The ID of the Spot Market Request

» `packet__vlan`

Provides a resource to allow users to manage Virtual Networks in their projects.

To learn more about Layer 2 networking in Packet, refer to * <https://support.packet.com/kb/articles/layer-2-configurations> * <https://support.packet.com/kb/articles/layer-2-overview>

» Example Usage

```
# Create a new VLAN in datacenter "ewr1"
```

```
resource "packet_vlan" "vlan1" {
  description = "VLAN in New Jersey"
  facility    = "ewr1"
  project_id  = "${local.project_id}"
}
```

» Argument Reference

The following arguments are supported:

- `project_id` - (Required) ID of parent project
- `facility` - (Required) Facility where to create the VLAN
- `description` - Description string

» Attributes Reference

The following attributes are exported:

- `vxlan` - VXLAN segment ID

» packet__volume

Provides a Packet Block Storage Volume resource to allow you to manage block volumes on your account. Once created by Terraform, they must then be attached and mounted using the `api` and `packet_block_attach` and `packet_block_detach` scripts.

» Example Usage

```
# Create a new block volume
resource "packet_volume" "volume1" {
  description = "terraform-volume-1"
  facility    = "ewr1"
  project_id  = "${local.project_id}"
  plan       = "storage_1"
  size       = 100
  billing_cycle = "hourly"

  snapshot_policies = {
    snapshot_frequency = "1day"

    snapshot_count = 7
  }
}
```

```

    }

    snapshot_policies = {
        snapshot_frequency = "1month"

        snapshot_count = 6
    }
}

```

» Argument Reference

The following arguments are supported:

- **plan** - (Required) The service plan slug of the volume
- **facility** - (Required) The facility to create the volume in
- **project_id** - (Required) The packet project ID to deploy the volume in
- **size** - (Required) The size in GB to make the volume
- **billing_cycle** - The billing cycle, defaults to "hourly"
- **description** - Optional description for the volume
- **snapshot_policies** - Optional list of snapshot policies
- **locked** - Lock or unlock the volume

» Attributes Reference

The following attributes are exported:

- **id** - The unique ID of the volume
- **name** - The name of the volume
- **description** - The description of the volume
- **size** - The size in GB of the volume
- **plan** - Performance plan the volume is on
- **billing_cycle** - The billing cycle, defaults to hourly
- **facility** - The facility slug the volume resides in
- **state** - The state of the volume
- **locked** - Whether the volume is locked or not
- **project_id** - The project id the volume is in
- **attachments** - A list of attachments, each with its own **href** attribute
- **created** - The timestamp for when the volume was created
- **updated** - The timestamp for the last time the volume was updated

» packet__volume__attachment

Provides attachment of Packet Block Storage Volume to Devices.

Device and volume must be in the same location (facility).

Once attached by Terraform, they must then be mounted using the `packet_block_attach` and `packet_block_detach` scripts.

» Example Usage

```
resource "packet_device" "test_device_va" {
  hostname      = "terraform-test-device-va"
  plan          = "t1.small.x86"
  facilities    = ["ewr1"]
  operating_system = "ubuntu_16_04"
  billing_cycle  = "hourly"
  project_id    = "${local.project_id}"
}

resource "packet_volume" "test_volume_va" {
  plan = "storage_1"
  billing_cycle = "hourly"
  size = 100
  project_id = "${local.project_id}"
  facility = "ewr1"
  snapshot_policies = { snapshot_frequency = "1day", snapshot_count = 7 }
}

resource "packet_volume_attachment" "test_volume_attachment" {
  device_id = "${packet_device.test_device_va.id}"
  volume_id = "${packet_volume.test_volume_va.id}"
}
```

» Argument Reference

The following arguments are supported:

- `volume_id` - (Required) The ID of the volume to attach
- `device_id` - (Required) The ID of the device to which the volume should be attached

» Attributes Reference

The following attributes are exported:

- `id` - The unique ID of the volume attachment