

» **tfe__organization**

Manages organizations.

» **Example Usage**

Basic usage:

```
resource "tfe_organization" "test" {  
  name = "my-org-name"  
  email = "admin@company.com"  
}
```

» **Argument Reference**

The following arguments are supported:

- **name** - (Required) Name of the organization.
- **email** - (Required) Admin email address.
- **session_timeout_minutes** - (Optional) Session timeout after inactivity. Defaults to 20160.
- **session_remember_minutes** - (Optional) Session expiration. Defaults to 20160.
- **collaborator_auth_policy** - (Optional) Authentication policy (password or two_factor_mandatory). Defaults to **password**.

» **Attributes Reference**

- **id** - The name of the organization.

» **Import**

Organizations can be imported; use <ORGANIZATION NAME> as the import ID. For example:

```
terraform import tfe_organization.test my-org-name
```

» **tfe__organization__token**

Generates a new organization token, replacing any existing token. This token can be used to act as the organization service account.

» Example Usage

Basic usage:

```
resource "tfe_organization_token" "test" {  
  organization = "my-org-name"  
}
```

» Argument Reference

The following arguments are supported:

- **organization** - (Required) Name of the organization.
- **force_regenerate** - (Optional) If set to **true**, a new token will be generated even if a token already exists. This will invalidate the existing token!

» Attributes Reference

- **id** - The ID of the token.
- **token** - The generated token.

» Import

Organization tokens can be imported; use `<ORGANIZATION NAME>` as the import ID. For example:

```
terraform import tfe_organization_token.test my-org-name
```

» tfe__policy__set

Sentinel Policy as Code is an embedded policy as code framework integrated with Terraform Enterprise.

Policy sets are configured on a per-organization level, and allow organization owners to choose which policies are enforced on which workspaces.

» Example Usage

Basic usage:

```
resource "tfe_policy_set" "test" {
  name = "my-policy-set"
  description = "A brand new policy set"
  organization = "my-org-name"
  policy_ids = ["${tfe_sentinel_policy.test.id}"]
  workspace_external_ids = ["${tfe_workspace.test.id}"]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the policy set.
- **description** - (Optional) A description of the policy set's purpose.
- **global** - (Optional) Whether or not policies in this set will apply to all workspaces. Defaults to **false**. This value *must not* be provided if **workspace_external_ids** are provided.
- **organization** - (Required) Name of the organization.
- **policy_ids** - (Required) A list of Sentinel policy IDs.
- **workspace_external_ids** - (Optional) A list of workspace external IDs. If the policy set is **global**, this value *must not* be provided.

» Attributes Reference

- **id** - The ID of the policy set.

» Import

Policy sets can be imported; use <POLICY SET ID> as the import ID. For example:

```
terraform import tfe_policy_set.test polset-wAs3zYmWAhYK7peR
```

» tfe__sentinel__policy

Sentinel Policy as Code is an embedded policy as code framework integrated with Terraform Enterprise.

Policies are configured on a per-organization level, and are enforced on all of an organization's workspaces during runs. Each plan's changes are validated against the policy prior to the apply step.

» Example Usage

Basic usage:

```
resource "tfe_sentinel_policy" "test" {
  name = "my-policy-name"
  description = "This policy always passes"
  organization = "my-org-name"
  policy = "main = rule { true }"
  enforce_mode = "hard-mandatory"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the policy.
- **description** - (Optional) A description of the policy's purpose.
- **organization** - (Required) Name of the organization.
- **policy** - (Required) The actual policy itself.
- **enforce_mode** - (Required) The enforcement level of the policy. Valid values are `advisory`, `hard-mandatory` and `soft-mandatory`. Defaults to `soft-mandatory`.

» Attributes Reference

- **id** - The ID of the policy.

» Import

Sentinel policies can be imported; use `<ORGANIZATION NAME>/<POLICY ID>` as the import ID. For example:

```
terraform import tfe_sentinel_policy.test my-org-name/pol-wAs3zYmWAhYK7peR
```

» tfe__ssh__key

This resource represents an SSH key which includes a name and the SSH private key. An organization can have multiple SSH keys available.

» Example Usage

Basic usage:

```
resource "tfe_ssh_key" "test" {  
  name = "my-ssh-key-name"  
  organization = "my-org-name"  
  key = "private-ssh-key"  
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name to identify the SSH key.
- **organization** - (Required) Name of the organization.
- **key** - (Required) The text of the SSH private key.

» Attributes Reference

- **id** The ID of the SSH key.

» Import

Because the Terraform Enterprise API does not return the private SSH key content, this resource cannot be imported.

» tfe__team

Manages teams.

» Example Usage

Basic usage:

```
resource "tfe_team" "test" {  
  name = "my-team-name"  
  organization = "my-org-name"  
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the team.
- **organization** - (Required) Name of the organization.

» Attributes Reference

- **id** The ID of the team.

» Import

Teams can be imported; use <ORGANIZATION NAME>/<TEAM ID> as the import ID. For example:

```
terraform import tfe_team.test my-org-name/team-uomQZysH9ou42ZYY
```

» tfe__team__access

Associate a team to permissions on a workspace.

» Example Usage

Basic usage:

```
resource "tfe_team" "test" {
  name = "my-team-name"
  organization = "my-org-name"
}

resource "tfe_workspace" "test" {
  name = "my-workspace-name"
  organization = "my-org-name"
}

resource "tfe_team_access" "test" {
  access = "read"
  team_id = "${tfe_team.test.id}"
  workspace_id = "${tfe_workspace.test.id}"
}
```

» Argument Reference

The following arguments are supported:

- **access** - (Required) Type of access to grant. Valid values are **admin**, **read** or **write**.
- **team_id** - (Required) ID of the team to add to the workspace.
- **workspace_id** - (Required) Workspace ID to which the team will be added.

» Attributes Reference

- **id** The team access ID.

» Import

Team accesses can be imported; use `<ORGANIZATION NAME>/<WORKSPACE NAME>/<TEAM ACCESS ID>` as the import ID. For example:

```
terraform import tfe_team_access.test my-org-name/my-workspace-name/tws-8S5wnRbRpogw6apb
```

» tfe__team__member

Add or remove a user from a team.

NOTE on managing team memberships: Terraform currently provides two resources for managing team memberships. The `tfe_team_member` resource can be used multiple times as it manages the team membership for a single user. The `tfe_team_members` resource, on the other hand, is used to manage all team memberships for a specific team and can only be used once. Both resources cannot be used for the same team simultaneously.

» Example Usage

Basic usage:

```
resource "tfe_team" "test" {
  name = "my-team-name"
  organization = "my-org-name"
}

resource "tfe_team_member" "test" {
  team_id = "${tfe_team.test.id}"
}
```

```
    username = "sander"
}
```

» Argument Reference

The following arguments are supported:

- `team_id` - (Required) ID of the team.
- `username` - (Required) Name of the user to add.

» Import

A team member can be imported; use `<TEAM ID>/<USERNAME>` as the import ID. For example:

```
terraform import tfe_team_member.test team-47qC3LmA47piVan7/sander
```

» `tfe__team__members`

Manages users in a team.

NOTE on managing team memberships: Terraform currently provides two resources for managing team memberships. The `tfe_team_member` resource can be used multiple times as it manages the team membership for a single user. The `tfe_team_members` resource, on the other hand, is used to manage all team memberships for a specific team and can only be used once. Both resources cannot be used for the same team simultaneously.

» Example Usage

Basic usage:

```
resource "tfe_team" "test" {
  name = "my-team-name"
  organization = "my-org-name"
}

resource "tfe_team_members" "test" {
  team_id = "${tfe_team.test.id}"
  usernames = ["admin", "sander"]
}
```


» Argument Reference

The following arguments are supported:

- `team_id` - (Required) ID of the team.
- `usernames` - (Required) Names of the users to add.

» Attributes Reference

- `id` - The ID of the team.

» Import

Team members can be imported; use `<TEAM ID>` as the import ID. For example:

```
terraform import tfe_team_members.test team-47qC3LmA47piVan7
```

» `tfe__team__token`

Generates a new team token and overrides existing token if one exists.

» Example Usage

Basic usage:

```
resource "tfe_team" "test" {
  name = "my-team-name"
  organization = "my-org-name"
}

resource "tfe_team_token" "test" {
  team_id = "${tfe_team.test.id}"
}
```

» Argument Reference

The following arguments are supported:

- `team_id` - (Required) ID of the team.
- `force_regenerate` - (Optional) If set to `true`, a new token will be generated even if a token already exists. This will invalidate the existing token!

» Attributes Reference

- `id` - The ID of the token.
- `token` - The generated token.

» Import

Team tokens can be imported; use `<TEAM ID>` as the import ID. For example:

```
terraform import tfe_team_token.test team-47qC3LmA47piVan7
```

» `tfe__variable`

Creates, updates and destroys variables.

» Example Usage

Basic usage:

```
resource "tfe_organization" "test" {
  name = "my-org-name"
  email = "admin@company.com"
}

resource "tfe_workspace" "test" {
  name = "my-workspace-name"
  organization = "${tfe_organization.test.id}"
}

resource "tfe_variable" "test" {
  key = "my_key_name"
  value = "my_value_name"
  category = "terraform"
  workspace_id = "${tfe_workspace.test.id}"
}
```

» Argument Reference

The following arguments are supported:

- `key` - (Required) Name of the variable.
- `value` - (Required) Value of the variable.

- **category** - (Required) Whether this is a Terraform or environment variable. Valid values are **terraform** or **env**.
- **hcl** - (Optional) Whether to evaluate the value of the variable as a string of HCL code. Has no effect for environment variables. Defaults to **false**.
- **sensitive** - (Optional) Whether the value is sensitive. If true then the variable is written once and not visible thereafter. Defaults to **false**.
- **workspace_id** - (Required) ID of the workspace that owns the variable.

» Attributes Reference

- **id** - The ID of the variable.

» Import

Variables can be imported; use `<ORGANIZATION NAME>/<WORKSPACE NAME>/<VARIABLE ID>` as the import ID. For example:

```
terraform import tfe_variable.test my-org-name/my-workspace-name/var-5rTwnSaR Pogw6apb
```

» tfe__workspace

Provides a workspace resource.

» Example Usage

Basic usage:

```
resource "tfe_workspace" "test" {
  name = "my-workspace-name"
  organization = "my-org-name"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the workspace.
- **organization** - (Required) Name of the organization.
- **auto_apply** - (Optional) Whether to automatically apply changes when a Terraform plan is successful. Defaults to **false**.
- **terraform_version** - (Optional) The version of Terraform to use for this workspace. Defaults to the latest available version.

- **working_directory** - (Optional) A relative path that Terraform will execute within. Defaults to the root of your repository.
- **vcs_repo** - (Optional) Settings for the workspace's VCS repository.

The **vcs_repo** block supports:

- **identifier** - (Required) A reference to your VCS repository in the format **:org/:repo** where **:org** and **:repo** refer to the organization and repository in your VCS provider.
- **branch** - (Optional) The repository branch that Terraform will execute from. Default to **master**.
- **ingress_submodules** - (Optional) Whether submodules should be fetched when cloning the VCS repository. Defaults to **false**.
- **oauth_token_id** - (Required) Token ID of the VCS Connection (OAuth Connection
– Token) to use.

» Attributes Reference

- **id** - The ID of the workspace within Terraform. This is a custom ID that is needed because the Terraform Enterprise workspace related API calls require the organization and workspace name instead of the actual workspace ID.
- **external_id** - The external ID of the workspace within Terraform Enterprise.

» Import

Workspaces can be imported; use **<ORGANIZATION NAME>/<WORKSPACE NAME>** as the import ID. For example:

```
terraform import tfe_workspace.test my-org-name/my-workspace-name
```