

## » Data Source: heroku\_\_addon

Use this data source to get information about a Heroku Addon.

### » Example Usage

```
data "heroku_addon" "from_another_app" {
  name = "addon-from-another-app"
}

output "heroku_addon_data_basic" {
  value = [
    "Addon from another app",
    "id: ${data.heroku_addon.from_another_app.id}",
    "name: ${data.heroku_addon.from_another_app.name}",
    "app: ${data.heroku_addon.from_another_app.app}",
    "plan: ${data.heroku_addon.from_another_app.plan}",
    "provider_id: ${data.heroku_addon.from_another_app.provider_id}",
    "config_vars: ${join(", ", data.heroku_addon.from_another_app.config_vars)}",
  ]
}
```

### » Argument Reference

The following arguments are supported:

- **name** - (Required) The add-on name

### » Attributes Reference

The following attributes are exported:

- **id** - The ID of the add-on
- **name** - The add-on name
- **plan** - The plan name
- **provider\_id** - The ID of the plan provider
- **config\_vars** - The Configuration variables of the add-on

## » Data Source: heroku\_\_app

Use this data source to get information about a Heroku App.

## » Example Usage

```
# Create a new Heroku app
data "heroku_app" "default" {
  name    = "my-cool-app"
}
```

## » Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the application. In Heroku, this is also the unique ID, so it must be unique and have a minimum of 3 characters.

## » Attributes Reference

The following attributes are exported:

- **name** - (Required) The name of the application. In Heroku, this is also the unique .
- **stack** - (Optional) The application stack is what platform to run the application in.
- **buildpacks** - (Optional) A list of buildpacks that this app uses.
- **space** - (Optional) The private space in which the app runs. Not present if this is a common runtime app.
- **region** - (Required) The region in which the app is deployed.
- **git\_url** - (Required) The Git URL for the application. This is used for deploying new versions of the app.
- **web\_url** - (Required) The web (HTTP) URL that the application can be accessed at by default.
- **heroku\_hostname** - (Required) A hostname for the Heroku application, suitable for pointing DNS records.
- **config\_vars** - (Optional) A map of all of the configuration variables for the app.
- **acm** - (Required) True if Heroku ACM is enabled for this app, false otherwise.
- **organization** - (Optional) The organization that owns this app, if the app is owned by an organization. The fields for this block are documented below.

The **organization** block supports:

- **name** (string) - The name of the organization.
- **locked** (boolean)
- **personal** (boolean)

## » Data Source: `heroku__space`

Use this data source to get information about a Heroku Private Space.

### » Example Usage

```
# Look up a Heroku Private Space
data "heroku_space" "default" {
  name = "my-secret-space"
}
```

### » Argument Reference

The following arguments are supported:

- `name` - (Required) The name of the Heroku Private Space.

### » Attributes Reference

The following attributes are exported:

- `name` - The name of the Heroku Private Space. In Heroku, this is also the unique .
- `id` - The unique ID of the Heroku Private Space.
- `region` - The region in which the Heroku Private Space is deployed.
- `state` - The state of the Heroku Private Space. Either `allocating` or `allocated`.
- `shield` - Whether or not the space has Shield turned on. One of `on` or `off`.
- `organization` - The organization that owns this space, if the space is owned by an organization. The fields for this block are documented below.
- `outbound_ips` - The space's stable outbound NAT IPs.

The `organization` block supports:

- `name` (string) - The name of the organization.

## » Data Source: `heroku__space__peering__info`

Use this data source to get peering information about a Heroku Private Space.

## » Example Usage

```
# Look up a Heroku Private Space's peering info.
data "heroku_space_peering_info" "default" {
  name = "my-secret-space"
}

# Initiate a VPC peering connection request.
resource "aws_vpc_peering_connection" "foo" {
  peer_owner_id = "${data.heroku_space_peering_info.default.aws_account_id}"
  peer_vpc_id   = "${data.heroku_space_peering_info.default.vpc_id}"
  vpc_id        = "${aws_vpc.foo.id}"
}
```

## » Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the Heroku Private Space.

## » Attributes Reference

The following attributes are exported:

- **aws\_account\_id** - The AWS account ID that the Heroku Private Space runs in.
- **aws\_region** - The AWS region that the Heroku Private Space runs in.
- **vpc\_id** - The VPC ID of the Heroku Private Space.
- **vpc\_cidr** - The CIDR block of the VPC ID.
- **dyno\_cidr\_blocks** - The CIDR blocks that the Dynos run on.
- **unavailable\_cidr\_blocks** - A list of unavailable CIDR blocks.

## » heroku\_\_addon

Provides a Heroku Add-On resource. These can be attach services to a Heroku app.

## » Example Usage

```
# Create a new Heroku app
resource "heroku_app" "default" {
  name = "test-app"
}
```

```

}

# Create a database, and configure the app to use it
resource "heroku_addon" "database" {
  app = "${heroku_app.default.name}"
  plan = "heroku-postgresql:hobby-basic"
}

# Add a web-hook addon for the app
resource "heroku_addon" "webhook" {
  app = "${heroku_app.default.name}"
  plan = "deployhooks:http"

  config {
    url = "http://google.com"
  }
}

```

## » Argument Reference

The following arguments are supported:

- **app** - (Required) The Heroku app to add to.
- **plan** - (Required) The addon to add.
- **config** - (Optional) Optional plan configuration.

## » Attributes Reference

The following attributes are exported:

- **id** - The ID of the add-on
- **name** - The add-on name
- **plan** - The plan name
- **provider\_id** - The ID of the plan provider
- **config\_vars** - The Configuration variables of the add-on

## » Import

Addons can be imported using the Addon id, e.g.

```
$ terraform import heroku_addon.foobar 12345678
```

## » heroku\_\_addon\_\_attachment

Attaches a Heroku Addon Resource to an additional Heroku App.

### » Example Usage

```
resource "heroku_addon_attachment" "database" {  
  app_id = "${heroku_app.default.id}"  
  addon_id = "${heroku_addon.database.id}"  
}
```

### » Argument Reference

The following arguments are supported:

- `app_id` - (Required) The ID of the Heroku App to attach to.
- `addon_id` - (Required) The ID of the existing Heroku Addon to attach.
- `name` - (Optional) A friendly name for the Heroku Addon Attachment.

### » Attributes Reference

The following attributes are exported:

- `id` - The unique ID of the add-on attachment

### » Import

Addons can be imported using the unique Addon Attachment `id`, e.g.

```
$ terraform import heroku_addon_attachment.foobar 01234567-89ab-cdef-0123-456789abcdef
```

## » heroku\_\_app

Provides a Heroku App resource. This can be used to create and manage applications on Heroku.

### » Example Usage

```
# Create a new Heroku app  
resource "heroku_app" "default" {  
  name = "my-cool-app"
```

```

region = "us"

config_vars {
  FOOBAR = "baz"
}

buildpacks = [
  "heroku/go"
]
}

```

## » Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the application. In Heroku, this is also the unique ID, so it must be unique and have a minimum of 3 characters.
- **region** - (Required) The region that the app should be deployed in.
- **stack** - (Optional) The application stack is what platform to run the application in.
- **buildpacks** - (Optional) Buildpack names or URLs for the application. Buildpacks configured externally won't be altered if this is not present.
- **config\_vars** - (Optional) Configuration variables for the application. The config variables in this map are not the final set of configuration variables, but rather variables you want present. That is, other configuration variables set externally won't be removed by Terraform if they aren't present in this list.
- **space** - (Optional) The name of a private space to create the app in.
- **internal\_routing** - (Optional) If true, the application will be routable only internally in a private space. This option is only available for apps that also specify **space**.
- **organization** - (Optional) A block that can be specified once to define organization settings for this app. The fields for this block are documented below.
- **acm** - (Optional) The flag representing Automated Certificate Management for the app.

The **organization** block supports:

- **name** (string) - The name of the organization.
- **locked** (boolean)
- **personal** (boolean)

## » Attributes Reference

The following attributes are exported:

- `id` - The ID of the app. This is also the name of the application.
- `name` - The name of the application. In Heroku, this is also the unique ID.
- `stack` - The application stack is what platform to run the application in.
- `space` - The private space the app should run in.
- `internal_routing` - Whether internal routing is enabled the private space app.
- `region` - The region that the app should be deployed in.
- `git_url` - The Git URL for the application. This is used for deploying new versions of the app.
- `web_url` - The web (HTTP) URL that the application can be accessed at by default.
- `heroku_hostname` - A hostname for the Heroku application, suitable for pointing DNS records.
- `all_config_vars` - A map of all of the configuration variables that exist for the app, containing both those set by Terraform and those set externally.
- `uuid` - The unique UUID of the Heroku app. **NOTE:** Use this for `null_resource` triggers.

## » Import

Apps can be imported using the App id, e.g.

```
$ terraform import heroku_app.foobar MyApp
```

## » heroku\_app\_feature

Provides a Heroku App Feature resource. This can be used to create and manage App Features on Heroku.

## » Example Usage

```
resource "heroku_app_feature" "log_runtime_metrics" {  
  app = "test-app"  
  name = "log-runtime-metrics"  
}
```



## » Argument Reference

The following arguments are supported:

- **app** - (Required) The Heroku app to link to.
- **name** - (Required) The name of the App Feature to manage.
- **enabled** - (Optional) Whether to enable or disable the App Feature. The default value is true.

## » heroku\_app\_release

Provides a Heroku App Release resource.

An app release represents a combination of code, config vars and add-ons for an app on Heroku.

**NOTE:** This resource requires the slug be uploaded to Heroku using `heroku_slug` or with external tooling prior to running terraform.

## » Example Usage

```
resource "heroku_app" "foobar" {
  name = "foobar"
  region = "us"
}

# Upload your slug

resource "heroku_app_release" "foobar-release" {
  app = "${heroku_app.foobar.name}"
  slug_id = "01234567-89ab-cdef-0123-456789abcdef"
}
```

## » Argument Reference

The following arguments are supported:

- **app** - (Required) The name of the application
- **slug\_id** - unique identifier of slug
- **description** - description of changes in this release

## » Attributes Reference

The following attributes are exported:

- `id` - The ID of the app release

## » Import

Existing app releases can be imported using the combination of the application name, a colon, and the formation's type.

For example: `$ terraform import heroku_app_release.foobar-release foobar`

## » `heroku__cert`

Provides a Heroku SSL certificate resource. It allows to set a given certificate for a Heroku app.

## » Example Usage

```
# Create a new Heroku app
resource "heroku_app" "default" {
  name = "test-app"
}

# Add-on SSL to application
resource "heroku_addon" "ssl" {
  app = "${heroku_app.default.name}"
  plan = "ssl"
}

# Establish certificate for a given application
resource "heroku_cert" "ssl_certificate" {
  app = "${heroku_app.default.name}"
  certificate_chain = "${file("server.crt")}"
  private_key = "${file("server.key")}"
  depends_on = ["heroku_addon.ssl"]
}
```

## » Argument Reference

The following arguments are supported:

- **app** - (Required) The Heroku app to add to.
- **certificate\_chain** - (Required) The certificate chain to add
- **private\_key** - (Required) The private key for a given certificate chain

## » Attributes Reference

The following attributes are exported:

- **id** - The ID of the add-on
- **cname** - The CNAME for the SSL endpoint
- **name** - The name of the SSL certificate

## » Importing

When importing a Heroku cert resource, the ID must be built using the app name colon the unique ID from the Heroku API. For an app named `production-api` with a certificate ID of `b85d9224-310b-409b-891e-c903f5a40568`, you would import it as: `$ terraform import heroku_cert.production_api production-api:b85d9224-310b-409b-891e-c903f5a40568`.

## » heroku\_\_domain

Provides a Heroku App resource. This can be used to create and manage applications on Heroku.

## » Example Usage

```
# Create a new Heroku app
resource "heroku_app" "default" {
  name = "test-app"
}

# Associate a custom domain
resource "heroku_domain" "default" {
  app      = "${heroku_app.default.name}"
  hostname = "terraform.example.com"
}
```

## » Argument Reference

The following arguments are supported:

- **hostname** - (Required) The hostname to serve requests from.
- **app** - (Required) The Heroku app to link to.

## » Attributes Reference

The following attributes are exported:

- **id** - The ID of the of the domain record.
- **hostname** - The hostname traffic will be served as.
- **cname** - The CNAME traffic should route to.

## » Importing

When importing a Heroku domain resource, the ID must be built using the app name colon the unique ID from the Heroku API. For an app named `production-api` with a domain ID of `b85d9224-310b-409b-891e-c903f5a40568`, you would import it as: `$ terraform import heroku_domain.production_api production-api:b85d9224-310b-409b-891e-c903f5a40568`.

## » heroku\_\_drain

Provides a Heroku Drain resource. This can be used to create and manage Log Drains on Heroku.

## » Example Usage

```
resource "heroku_drain" "default" {
  app = "test-app"
  url = "syslog://terraform.example.com:1234"
}
```

## » Argument Reference

The following arguments are supported:

- **url** - (Required) The URL for Heroku to drain your logs to.
- **app** - (Required) The Heroku app to link to.

## » Attributes Reference

The following attributes are exported:

- `token` - The unique token for your created drain.

## » Importing

When importing a Heroku drain resource, the ID must be built using the app name colon the unique ID from the Heroku API. For an app named `production-api` with a drain ID of `b85d9224-310b-409b-891e-c903f5a40568`, you would import it as: `$ terraform import heroku_drain.production_api production-api:b85d9224-310b-409b-891e-c903f5a40568`

## » heroku\_formation

Provides a Heroku Formation resource.

A formation represents the formation of processes that should be set for an application.

**NOTE:** - The application must have a dyno in order to update its formation.  
- If the heroku formation resource is removed and deleted, this will be a no-op action in Heroku. The Heroku Platform does not have a `DELETE` endpoint for `formation`. - This resource works well with the `heroku_app_release` resource, which allows you to deploy a slug/release to an application before the formation can be updated.

## » Example Usage

```
# Creates a new application called foobar
resource "heroku_app" "foobar" {
    name = "foobar"
    region = "us"
}

# Creates a new release for application foobar using a slug id
resource "heroku_app_release" "foobar-release" {
    app = "${heroku_app.foobar.name}"
    slug_id = "01234567-89ab-cdef-0123-456789abcdef"
}

# Update the web formation for the foobar application's web
resource "heroku_formation" "foobar-web" {
```

```

    app = "${heroku_app.foobar.name}"
    type = "web"
    quantity = 2
    size = "standard-2x"

    # Tells Terraform that this formation must be created/updated only after the app release
    depends_on = ["heroku_app_release.foobar-release"]
}

```

## » Argument Reference

- **app** - (Required) The name of the application
- **type** - (Required) type of process such as "web"
- **quantity** - (Required) number of processes to maintain
- **size** - (Required) dyno size (Example: "standard-1X"). Capitalization does not matter.

## » Attributes Reference

The following attributes are exported: \* **id** - The ID of the formation

## » Import

Existing formations can be imported using the combination of the application name, a colon, and the formation's type.

For example: `$ terraform import heroku_formation.foobar-web foobar:web`

## » heroku\_pipeline

Provides a Heroku Pipeline resource.

A pipeline is a group of Heroku apps that share the same codebase. Once a pipeline is created, and apps are added to different stages using `heroku_pipeline_coupling`, you can promote app slugs to the next stage.

## » Example Usage

```

# Create Heroku apps for staging and production
resource "heroku_app" "staging" {
  name = "test-app-staging"
}

```

```

}

resource "heroku_app" "production" {
  name = "test-app-production"
}

# Create a Heroku pipeline
resource "heroku_pipeline" "test-app" {
  name = "test-app"
}

# Couple apps to different pipeline stages
resource "heroku_pipeline_coupling" "staging" {
  app      = "${heroku_app.staging.name}"
  pipeline = "${heroku_pipeline.test-app.id}"
  stage    = "staging"
}

resource "heroku_pipeline_coupling" "production" {
  app      = "${heroku_app.production.name}"
  pipeline = "${heroku_pipeline.test-app.id}"
  stage    = "production"
}

```

## » Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the pipeline.

## » Attributes Reference

The following attributes are exported:

- **id** - The UUID of the pipeline.
- **name** - The name of the pipeline.

## » Import

Pipelines can be imported using the Pipeline id, e.g.

```
$ terraform import heroku_pipeline.foobar 12345678
```

## » heroku\_\_pipeline\_\_coupling

Provides a Heroku Pipeline Coupling resource.

A pipeline is a group of Heroku apps that share the same codebase. Once a pipeline is created using `heroku_pipeline`, and apps are added to different stages using `heroku_pipeline_coupling`, you can promote app slugs to the downstream stages.

### » Example Usage

```
# Create Heroku apps for staging and production
resource "heroku_app" "staging" {
  name = "test-app-staging"
}

resource "heroku_app" "production" {
  name = "test-app-production"
}

# Create a Heroku pipeline
resource "heroku_pipeline" "test-app" {
  name = "test-app"
}

# Couple apps to different pipeline stages
resource "heroku_pipeline_coupling" "staging" {
  app      = "${heroku_app.staging.name}"
  pipeline = "${heroku_pipeline.test-app.id}"
  stage    = "staging"
}

resource "heroku_pipeline_coupling" "production" {
  app      = "${heroku_app.production.name}"
  pipeline = "${heroku_pipeline.test-app.id}"
  stage    = "production"
}
```

### » Argument Reference

The following arguments are supported:

- `app` - (Required) The name of the app for this coupling.
- `pipeline` - (Required) The ID of the pipeline to add this app to.



- **stage** - (Required) The stage to couple this app to. Must be one of `review`, `development`, `staging`, or `production`.

## » Attributes Reference

The following attributes are exported:

- **id** - The UUID of this pipeline coupling.
- **app** - The name of the application.
- **app\_id** - The ID of the application.
- **pipeline** - The UUID of the pipeline.
- **stage** - The stage for this coupling.

## » Import

Pipeline couplings can be imported using the Pipeline coupling `id`, e.g.

```
$ terraform import heroku_pipeline_coupling.foobar 12345678
```

## » heroku\_slug

Provides a Heroku Slug resource.

This resource supports uploading a pre-generated archive file of executable code, making it possible to launch apps directly from a Terraform config. This resource does not itself generate the slug archive. A guide to creating slug archives is available in the Heroku Dev Center.

## » Minimal Example

Create a ready-to-release slug:

- **file\_url** or **file\_path** must reference a file containing a slug archive of executable code and must follow the prescribed layout from Create slug archive in the Heroku Dev Center (nested within an `./app` directory)
- The archive may be created by an external build system, downloaded from another Heroku app, or otherwise provided outside of the context of this Terraform resource
- If the content (SHA256) of **file\_path** changes, then a new resource will be forced on the next plan/apply; if the file does not exist, the difference is ignored.
- The **file\_url** is only fetched during resource creation. To trigger another fetch the **file\_url** should be changed, then a new resource will be forced on the next plan/apply.

```

resource "heroku_slug" "foobar" {
  app      = "${heroku_app.foobar.id}"
  file_url = "https://github.com/terraform-providers/terraform-provider-heroku/raw/master/heroku_slug.rb"

  process_types = {
    web = "ruby server.rb"
  }
}

```

## » Example Usage

Complete config to launch a Heroku app:

```

resource "heroku_app" "foobar" {
  name = "foobar"
  region = "us"
}

# Create a slug for the app with a local slug archive file
resource "heroku_slug" "foobar" {
  app      = "${heroku_app.foobar.id}"
  buildpack_provided_description = "Ruby"
  // The slug archive file must already exist
  file_path = "slug.tgz"

  process_types = {
    web = "ruby server.rb"
  }
}

# Deploy a release to the app with the slug
resource "heroku_app_release" "foobar" {
  app      = "${heroku_app.foobar.id}"
  slug_id = "${heroku_slug.foobar.id}"
}

# Launch the app's web process by scaling-up
resource "heroku_formation" "foobar" {
  app      = "${heroku_app.foobar.id}"
  type      = "web"
  quantity  = 1
  size      = "Standard-1x"
  depends_on = ["heroku_app_release.foobar"]
}

```

## » Argument Reference

The following arguments are supported:

- **app** - (Required) The ID of the Heroku app
- **buildpack\_provided\_description** - Description of language or app framework, "Ruby/Rack"; displayed as the app's language in the Heroku Dashboard
- **checksum** - Hash of the slug for verifying its integrity, auto-generated from contents of **file\_path** or **file\_url**, SHA256:e3b0c44298fc1c149afbf4c8996fb92427ae41e4649b934ca4
- **commit** - Identification of the code with your version control system (eg: SHA of the git HEAD), "60883d9e8947a57e04dc9124f25df004866a2051"
- **commit\_description** - Description of the provided commit
- **file\_path** - (Required unless **file\_url** is set) Local path to a slug archive, "slugs/current.tgz"
- **file\_url** - (Required unless **file\_path** is set) **https** URL to a slug archive, "https://example.com/slugs/app-v1.tgz"
- **process\_types** - (Required) Map of processes to launch on Heroku Dynos
- **stack** - Name or ID of the Heroku stack

## » Attributes Reference

The following attributes are exported:

- **id** - The ID of the slug
- **app** - The ID or unique name of the Heroku app
- **blob** - Slug archive (compressed tar of executable code)
  - **method** - HTTP method to upload the archive
  - **url** - Pre-signed, expiring URL to upload the archive
- **buildpack\_provided\_description** - Description of language or app framework, "Ruby/Rack"
- **checksum** - Hash of the slug for verifying its integrity, auto-generated from contents of **file\_path** or **file\_url**
- **commit** - Identification of the code with your version control system (eg: SHA of the git HEAD), "60883d9e8947a57e04dc9124f25df004866a2051"
- **commit\_description** - Description of the provided commit
- **process\_types** - Map of processes to launch on Heroku Dynos
- **size** - Slug archive filesize in bytes
- **stack** - Heroku stack name
- **stack\_id** - Heroku stack ID

## » Import

Existing slugs can be imported using the combination of the application name, a colon, and the slug ID.

For example: `$ terraform import heroku_slug.foobar bazbux:4f1db8ef-ed5c-4c42-a3d6-3c28262d5a`

- `foobar` is the **heroku\_slug** resource's name
- `bazbux` is the Heroku app name (or ID) that the slug belongs to
- `:` separates the app identifier & the slug identifier
- `4f1db8ef...` is the slug ID

## » heroku\_space

Provides a Heroku Space resource for running apps in isolated, highly available, secure app execution environments.

### » Example Usage

```
// Create a new Heroku space
resource "heroku_space" "default" {
  name = "test-space"
  organization = "my-company"
  region = "virginia"
}

// Create a new Heroku app in test-space
resource "heroku_app" "default" {
  name = "test-app"
  space = "${heroku_space.default.name}"
  organization = {
    name = "my-company"
  }
}
```

### » Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the space.
- **organization** - (Required) The name of the organization which will own the space.
- **region** - (Optional) The region that the space should be created in.
- **shield** - (Optional) Whether or not the private space should be shielded.

### » Attributes Reference

The following attributes are exported:

- `id` - The ID of the space.
- `name` - The space's name.
- `organization` - The space's organization.
- `region` - The space's region.
- `outbound_ips` - The space's stable outbound NAT IPs.

## » Import

Spaces can be imported using the space `id`, e.g.

```
$ terraform import heroku_space.foobar MySpace
```

## » `heroku_space_member`

Provides a Heroku Space resource for managing app permissions for the entire space. Members with the admin role will always have full permissions to a Heroku Space, so using this resource on an admin will have no affect. The provided member must already exist in your Heroku organization. Currently the only supported permission is `create_apps`.

## » Example Usage

```
// Create a new Heroku space
resource "heroku_space" "default" {
  name = "test-space"
  organization = "my-company"
  region = "virginia"
}

// Give an existing team member create_apps permissions to the space
resource "heroku_space_app_access" "member1" {
  space = "${heroku_space.default.name}"
  email = "member1@foobar.com"
  permissions = ["create_apps"]
}

// Remove all permissions from an existing team member
resource "heroku_space_app_access" "member1" {
  space = "${heroku_space.default.name}"
  email = "member1@foobar.com"
  permissions = []
}
```

## » Argument Reference

The following arguments are supported:

- **space** - (Required) The name of the space.
- **email** - (Required) The email of the team member to set permissions for.
- **permissions** - (Required) The permissions to grant the team member for the space. Currently **create\_apps** is the only supported permission. If not provided the member will have no permissions to the space. Members with admin role will always have **create\_apps** permissions, which cannot be removed.

## » heroku\_space\_inbound\_ruleset

Provides a resource for managing inbound rulesets for Heroku Private Spaces.

## » Example Usage

```
# Create a new Heroku space
resource "heroku_space" "default" {
  name           = "test-space"
  organization    = "my-company"
  region         = "virginia"
}

# Allow all traffic EXCEPT 8.8.4.4 to access the HPS.
resource "heroku_space_inbound_ruleset" "default" {
  space = "${heroku_space.default.name}"

  rule {
    action = "allow"
    source = "0.0.0.0/0"
  }

  rule {
    action = "deny"
    source = "8.8.4.4/32"
  }
}
```

## » Argument Reference

The following arguments are supported:

- **space** - (Required) The name of the space.
- **rule** - (Required) At least one **rule** block. Rules are documented below.

A **rule** block supports the following arguments:

- **action** - (Required) The action to apply this rule to. Must be one of **allow** or **deny**.
- **source** - (Required) A CIDR block source for the rule.

## » Attributes Reference

The following attributes are exported:

- **id** - The ID of the inbound ruleset.

## » heroku\_space\_peering\_connection\_accepter

Provides a resource for accepting VPC peering requests to Heroku Private Spaces.

## » Example Usage

```
# Fetch the peering information for the Heroku Private Space.
data "heroku_space_peering_info" "peer_space" {
  name = "my-fancy-space"
}

# Initiate the request.
resource "aws_vpc_peering_connection" "request" {
  peer_owner_id = "${data.heroku_space_peering_info.peer_space.aws_account_id}"
  peer_vpc_id   = "${data.heroku_space_peering_info.peer_space.vpc_id}"
  vpc_id        = "${aws_vpc.main.id}"
}

# Accept the request.
resource "heroku_space_peering_connection_accepter" "accept" {
  space = "${heroku_space.peer_space.name}"
  vpc_peering_connection_id = "${aws_vpc_peering_connection.request.id}"
}
```

## » Argument Reference

The following arguments are supported:

- **space** - (Required) The name of the space.
- **vpc\_peering\_connection\_id** - (Required) The peering connection request ID.

## » Attributes Reference

The following attributes are exported:

- **status** - The status of the peering connection request.
- **type** - The type of the peering connection.

## » heroku\_space\_vpn\_connection

Provides a resource for creating a VPN connection between a network and a Heroku Private Space. For more information, see Private Spaces VPN Connection in the Heroku DevCenter.

## » Example Usage

```
// Create a new Heroku space
resource "heroku_space" "default" {
  name           = "test-space"
  organization    = "my-company"
  region         = "virginia"
}

// Connect the Heroku space to another network with a VPN
resource "heroku_space_vpn_connection" "office" {
  name           = "office"
  space          = "${heroku_space.default.name}"
  public_ip      = "203.0.113.1"
  routable_cidrs = ["192.168.1.0/24"]
}
```

## » Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the VPN connection.
- **space** - (Required) The name of the Heroku Private Space where the VPN connection will be established.



- **public\_ip** - (Required) The public IP address of the VPN endpoint on the network where the VPN connection will be established.
- **routable\_cidrs** - (Required) A list of IPv4 CIDR blocks used by the network where the VPN connection will be established.

## » Attributes Reference

The following attributes are exported:

- **space\_cidr\_block** - The CIDR block for the Heroku Private Space. The network where the VPN will be established should be configured to route traffic destined for this CIDR block over the VPN link.
- **ike\_version** - The IKE version used to setup the IPsec tunnel.
- **tunnels** - Details about each VPN tunnel endpoint.
  - **ip** - The public IP address of the tunnel.
  - **pre\_shared\_key** - The pre-shared IPsec secret for the tunnel.

## » heroku\_team\_collaborator

Provides a Heroku Team Collaborator resource.

A team collaborator represents an account that has been given access to a team app on Heroku.

**NOTE:** Please only use this resource if you have team/organization apps

## » Example Usage

```
# Create a new team collaborator for the foobar application that has view, operate, manage p
resource "heroku_team_collaborator" "foobar-collaborator" {
  app = "${heroku_app.foobar.name}"
  email = "collaborator@foobar.com"
  permissions = ["view", "operate", "manage"]
}
```

## » Argument Reference

- **app** - (Required) The name of the team app that the team collaborator will be added to.
- **email** - (Required) Email address of the team collaborator
- **permissions** - (Required) List of permissions that will be granted to the team collaborator. The order in which individual permissions are set here

does not matter. Please visit [this link](#) for more information on available permissions.

## » Attributes Reference

The following attributes are exported:

- `id` - The ID of the team collaborator

## » Import

Team Collaborators can be imported using the combination of the team application name, a colon, and the collaborator's email address

For example:

```
$ terraform import heroku_team_collaborator.foobar-collaborator foobar_app:collaborator@foobar.com
```

## » `heroku_team_member`

Provides a Heroku Team Collaborator resource.

**NOTE:** Please only use this resource if you have team/organization apps

## » Example Usage

```
# Adds a Heroku user to a Heroku team as a viewer.
resource "heroku_team_member" "foobar-member" {
  team = "my-team"
  email = "some-user@example.com"
  role = "member"
}
```

## » Argument Reference

- `team` - (Required) The name of the Heroku team that the team member will be added to.
- `email` - (Required) Email address of the team collaborator
- `role` - (Required) The role to assign the team member. See the API docs for available options.

## » Import

Team members can be imported using the combination of the team application name, a colon, and the member's email address.

```
$ terraform import heroku_team_member.foobar-member my-team-foobar:some-user@example.com
```