

» **google__active__folder**

Get an active folder within GCP by `display_name` and `parent`.

» **Example Usage**

```
data "google_active_folder" "department1" {
  display_name = "Department 1"
  parent      = "organizations/1234567"
}
```

» **Argument Reference**

The following arguments are supported:

- `display_name` - (Required) The folder's display name.
- `parent` - (Required) The resource name of the parent Folder or Organization.

» **Attributes Reference**

In addition to the arguments listed above, the following attributes are exported:

- `name` - The resource name of the Folder. This uniquely identifies the folder.

» **google__billing__account**

Use this data source to get information about a Google Billing Account.

```
data "google_billing_account" "acct" {
  display_name = "My Billing Account"
  open        = true
}
```

```
resource "google_project" "my_project" {
  name          = "My Project"
  project_id    = "your-project-id"
  org_id        = "1234567"

  billing_account = "${data.google_billing_account.acct.id}"
}
```

» Argument Reference

The arguments of this data source act as filters for querying the available billing accounts. The given filters must match exactly one billing account whose data will be exported as attributes. The following arguments are supported:

- `billing_account` (Optional) - The name of the billing account in the form `{billing_account_id}` or `billingAccounts/{billing_account_id}`.
- `display_name` (Optional) - The display name of the billing account.
- `open` (Optional) - `true` if the billing account is open, `false` if the billing account is closed.

NOTE: One of `billing_account` or `display_name` must be specified.

» Attributes Reference

The following additional attributes are exported:

- `id` - The billing account ID.
- `name` - The resource name of the billing account in the form `billingAccounts/{billing_account_id}`.
- `project_ids` - The IDs of any projects associated with the billing account.

» `google_client_config`

Use this data source to access the configuration of the Google Cloud provider.

» Example Usage

```
data "google_client_config" "current" {}

output "project" {
  value = "${data.google_client_config.current.project}"
}
```

» Example Usage: Configure Kubernetes provider with OAuth2 access token

```
data "google_client_config" "default" {}

data "google_container_cluster" "my_cluster" {
  name     = "my-cluster"
  zone     = "us-east1-a"
```

```

}

provider "kubernetes" {
  load_config_file = false

  host = "https://${data.google_container_cluster.my_cluster.endpoint}"
  token = "${data.google_client_config.default.access_token}"
  cluster_ca_certificate = "${base64decode(data.google_container_cluster.my_cluster.master_certificate_data)}"
}

```

» Argument Reference

There are no arguments available for this data source.

» Attributes Reference

In addition to the arguments listed above, the following attributes are exported:

- `project` - The ID of the project to apply any resources to.
- `region` - The region to operate under.
- `access_token` - The OAuth2 access token used by the client to authenticate against the Google Cloud API.

» `google_cloudfunctions_function`

Get information about a Google Cloud Function. For more information see the official documentation and API.

» Example Usage

```

data "google_cloudfunctions_function" "my-function" {
  name = "function"
}

```

» Argument Reference

The following arguments are supported:

- `name` - (Required) The name of a Cloud Function.

- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
- **region** - (Optional) The region in which the resource belongs. If it is not provided, the provider region is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **name** - The name of the Cloud Function.
- **source_archive_bucket** - The GCS bucket containing the zip archive which contains the function.
- **source_archive_object** - The source archive object (file) in archive bucket.
- **description** - Description of the function.
- **available_memory_mb** - Available memory (in MB) to the function.
- **timeout** - Function execution timeout (in seconds).
- **entry_point** - Name of a JavaScript function that will be executed when the Google Cloud Function is triggered.
- **trigger_http** - If function is triggered by HTTP, this boolean is set.
- **trigger_bucket** - If function is triggered by bucket, bucket name is set here.
- **trigger_topic** - If function is triggered by Pub/Sub topic, name of topic is set here.
- **https_trigger_url** - If function is triggered by HTTP, trigger URL is set here.
- **labels** - A map of labels applied to this function.

» google_compute_address

Get the IP address from a static address. For more information see the official API documentation.

» Example Usage

```
data "google_compute_address" "my_address" {
  name = "foobar"
}

resource "google_dns_record_set" "frontend" {
  name = "frontend.${google_dns_managed_zone.prod.dns_name}"
}
```

```

type = "A"
ttl   = 300

managed_zone = "${google_dns_managed_zone.prod.name}"

rrdatas = ["${data.google_compute_address.my_address.address}"]
}

resource "google_dns_managed_zone" "prod" {
  name      = "prod-zone"
  dns_name = "prod.mydomain.com."
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the resource, required by GCE.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
 - **region** - (Optional) The Region in which the created address reside. If it is not provided, the provider region is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.
- **address** - The IP of the created resource.
- **status** - Indicates if the address is used. Possible values are: RESERVED or IN_USE.

» google__compute__backend__service

Provide acces to a Backend Service's attribute. For more information see the official documentation and the API.

» Example Usage

```
data "google_compute_backend_service" "baz" {  
  name = "foobar"  
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the Backend Service.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following attributes are exported:

- **connection_draining_timeout_sec** - Time for which instance will be drained (not accept new connections, but still work to finish started ones).
- **description** - Textual description for the Backend Service.
- **enable_cdn** - Whether or not Cloud CDN is enabled on the Backend Service.
- **fingerprint** - The fingerprint of the Backend Service.
- **port_name** - The name of a service that has been added to an instance group in this backend.
- **protocol** - The protocol for incoming requests.
- **self_link** - The URI of the Backend Service.
- **session_affinity** - The Backend Service session stickyness configuration.
- **timeout_sec** - The number of seconds to wait for a backend to respond to a request before considering the request failed.
- **backend** - The list of backends that serve this Backend Service.
- **health_checks** - The list of HTTP/HTTPS health checks used by the Backend Service.

» **google__compute__default__service__account**

Use this data source to retrieve default service account for this project

» **Example Usage**

```
data "google_compute_default_service_account" "default" { }
```

```
output "default_account" {  
  value = "${data.google_compute_default_service_account.default.email}"  
}
```

» **Argument Reference**

The following arguments are supported:

- **project** - (Optional) The project ID. If it is not provided, the provider project is used.

» **Attributes Reference**

The following attributes are exported:

- **email** - Email address of the default service account used by VMs running in this project

» **google__compute__forwarding__rule**

Get a forwarding rule within GCE from its name.

» **Example Usage**

```
data "google_compute_forwarding_rule" "my-forwarding-rule" {  
  name = "forwarding-rule-us-east1"  
}
```

» **Argument Reference**

The following arguments are supported:

- **name** - (Required) The name of the forwarding rule.

-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
 - **region** - (Optional) The region in which the resource belongs. If it is not provided, the project region is used.

» Attributes Reference

In addition to the arguments listed above, the following attributes are exported:

- **description** - Description of this forwarding rule.
- **network** - Network of this forwarding rule.
- **subnetwork** - Subnetwork of this forwarding rule.
- **ip_address** - IP address of this forwarding rule.
- **ip_protocol** - IP protocol of this forwarding rule.
- **ports** - List of ports to use for internal load balancing, if this forwarding rule has any.
- **port_range** - Port range, if this forwarding rule has one.
- **target** - URL of the target pool, if this forwarding rule has one.
- **backend_service** - Backend service, if this forwarding rule has one.
- **load_balancing_scheme** - Type of load balancing of this forwarding rule.
- **region** - Region of this forwarding rule.
- **self_link** - The URI of the resource.

» google_compute_global_address

Get the IP address from a static address reserved for a Global Forwarding Rule which are only used for HTTP load balancing. For more information see the official API documentation.

» Example Usage

```
data "google_compute_global_address" "my_address" {  
  name = "foobar"  
}
```



```

resource "google_dns_record_set" "frontend" {
  name = "lb.${google_dns_managed_zone.prod.dns_name}"
  type = "A"
  ttl  = 300

  managed_zone = "${google_dns_managed_zone.prod.name}"

  rrdatas = ["${data.google_compute_global_address.my_address.address}"]
}

resource "google_dns_managed_zone" "prod" {
  name      = "prod-zone"
  dns_name = "prod.mydomain.com."
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the resource, required by GCE.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.
- **address** - The IP of the created resource.
- **status** - Indicates if the address is used. Possible values are: RESERVED or IN_USE.

» google__compute__image

Get information about a Google Compute Image. Check that your service account has the `compute.imageUser` role if you want to share custom images from another project. If you want to use public images, do not forget to specify the dedicated project. For more information see the official documentation and its API.

» Example Usage

```
data "google_compute_image" "my_image" {
  name      = "debian-9"
  project   = "debian-cloud"
}

resource "google_compute_instance" "default" {
  # ...

  boot_disk {
    initialize_params {
      image = "${data.google_compute_image.my_image.self_link}"
    }
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** or **family** - (Required) The name of a specific image or a family. Exactly one of **name** or **family** must be specified. If **name** is specified, it will fetch the corresponding image. If **family** is specified, it will return the latest image that is part of an image family and is not deprecated.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used. If you are using a public base image, be sure to specify the correct Image Project.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the image.
- **name** - The name of the image.
- **family** - The family name of the image.
- **disk_size_gb** - The size of the image when restored onto a persistent disk in gigabytes.
- **archive_size_bytes** - The size of the image tar.gz archive stored in Google Cloud Storage in bytes.
- **image_id** - The unique identifier for the image.

- `image_encryption_key_sha256` - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this image.
- `source_image_id` - The ID value of the image used to create this image.
- `source_disk` - The URL of the source disk used to create this image.
- `source_disk_encryption_key_sha256` - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this image.
- `source_disk_id` - The ID value of the disk used to create this image.
- `creation_timestamp` - The creation timestamp in RFC3339 text format.
- `description` - An optional description of this image.
- `labels` - A map of labels applied to this image.
- `label_fingerprint` - A fingerprint for the labels being applied to this image.
- `licenses` - A list of applicable license URI.
- `status` - The status of the image. Possible values are **FAILED**, **PENDING**, or **READY**.

» `google_compute_instance_group`

Get a Compute Instance Group within GCE. For more information, see the [official documentation](#) and [API](#)

```
data "google_compute_instance_group" "all" {
  name = "instance-group-name"
  zone = "us-central1-a"
}
```

» Argument Reference

The following arguments are supported:

- `name` - (Optional) The name of the instance group. Either `name` or `self_link` must be provided.
- `project` - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- `self_link` - (Optional) The self link of the instance group. Either `name` or `self_link` must be provided.
- `zone` - (Optional) The zone of the instance group. If referencing the instance group by name and `zone` is not provided, the provider zone is used.

» Attributes Reference

The following arguments are exported:

- `description` - Textual description of the instance group.
- `instances` - List of instances in the group.
- `named_port` - List of named ports in the group.
- `network` - The URL of the network the instance group is in.
- `self_link` - The URI of the resource.
- `size` - The number of instances in the group.

» `google_compute_lb_ip_ranges`

Use this data source to access IP ranges in your firewall rules.

https://cloud.google.com/compute/docs/load-balancing/health-checks#health_check_source_ips_and_firewall_rules

» Example Usage

```
data "google_compute_lb_ip_ranges" "ranges" {}

resource "google_compute_firewall" "lb" {
  name      = "lb-firewall"
  network   = "${google_compute_network.main.name}"

  allow {
    protocol = "tcp"
    ports    = ["80"]
  }

  source_ranges = ["${data.google_compute_lb_ip_ranges.ranges.network}"]
  target_tags = [
    "InstanceBehindLoadBalancer"
  ]
}
```

» Argument Reference

There are no arguments available for this data source.

» Attributes Reference

In addition to the arguments listed above, the following attributes are exported:

- **network** - The IP ranges used for health checks when **Network load balancing** is used
- **http_ssl_tcp_internal** - The IP ranges used for health checks when **HTTP(S), SSL proxy, TCP proxy, and Internal load balancing** is used

» google_compute_network

Get a network within GCE from its name.

» Example Usage

```
data "google_compute_network" "my-network" {  
  name = "default-us-east1"  
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the network.
-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following attributes are exported:

- **network** - The network name or resource link to the parent network of this network.
- **description** - Description of this network.
- **gateway_ipv4** - The IP address of the gateway.
- **subnetworks_self_links** - the list of subnetworks which belong to the network

- `self_link` - The URI of the resource.

» `google_compute_region_instance_group`

Get a Compute Region Instance Group within GCE. For more information, see the official documentation and API.

```
data "google_compute_region_instance_group" "group" {
  name = "instance-group-name"
}
```

The most common use of this datasource will be to fetch information about the instances inside regional managed instance groups, for instance:

```
resource "google_compute_region_instance_group_manager" "foo" {
  name = "some_name"
  ...
  base_instance_name = "foo"
  ...
  instance_template = "${google_compute_instance_template.foo.self_link}"
  target_pools = ["${google_compute_target_pool.foo.self_link}"]
  ...
}

data "google_compute_region_instance_group" "data_source" {
  self_link = "${google_compute_region_instance_group_manager.foo.instance_group}"
}
```

» Argument Reference

The following arguments are supported:

- `name` - (Optional) The name of the instance group. One of `name` or `self_link` must be provided.
 - `self_link` - (Optional) The link to the instance group. One of `name` or `self_link` must be provided.
-
- `project` - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
 - `region` - (Optional) The region in which the resource belongs. If `self_link` is provided, this value is ignored. If neither `self_link` nor `region` are provided, the provider region is used.

» Attributes Reference

The following arguments are exported:

- **size** - The number of instances in the group.
- **instances** - List of instances in the group, as a list of resources, each containing:
 - **instance** - URL to the instance.
 - **named_ports** - List of named ports in the group, as a list of resources, each containing:
 - * **port** - Integer port number
 - * **name** - String port name
 - **status** - String description of current state of the instance.

» google__project__services

Use this data source to get details on the enabled project services.

For a list of services available, visit the [API library page](#) or run `gcloud services list`.

» Example Usage

```
data "google_project_services" "project" {
  project = "your-project-id"
}

output "project_services" {
  value = "${join(", ", data.google_project_services.project.services)}"
}
```

» Argument Reference

The following arguments are supported:

- **project** - (Required) The project ID.

» Attributes Reference

The following attributes are exported:

See `google__project__services` resource for details of the available attributes.

» google_compute_regions

Provides access to available Google Compute regions for a given project. See more about regions and regions in the upstream docs.

```
data "google_compute_regions" "available" {}

resource "google_compute_subnetwork" "cluster" {
  count = "${length(data.google_compute_regions.available.names)}"
  name   = "my-network"
  ip_cidr_range = "10.36.${count.index}.0/24"
  network = "my-network"
  region  = "${data.google_compute_regions.available.names[count.index]}"
}
```

» Argument Reference

The following arguments are supported:

- **project** (Optional) - Project from which to list available regions. Defaults to project declared in the provider.
- **status** (Optional) - Allows to filter list of regions based on their current status. Status can be either UP or DOWN. Defaults to no filtering (all available regions - both UP and DOWN).

» Attributes Reference

The following attribute is exported:

- **names** - A list of regions available in the given project

» google_compute_ssl_policy

Gets an SSL Policy within GCE from its name, for use with Target HTTPS and Target SSL Proxies. For more information see the official documentation.

» Example Usage

```
data "google_compute_ssl_policy" "my-ssl-policy" {
  name = "production-ssl-policy"
}
```


» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the SSL Policy.
-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following attributes are exported:

- **enabled_features** - The set of enabled encryption ciphers as a result of the policy config
- **description** - Description of this SSL Policy.
- **min_tls_version** - The minimum supported TLS version of this policy.
- **profile** - The Google-curated or custom profile used by this policy.
- **custom_features** - If the **profile** is **CUSTOM**, these are the custom encryption ciphers supported by the profile. If the **profile** is *not* **CUSTOM**, this attribute will be empty.
- **fingerprint** - Fingerprint of this resource.
- **self_link** - The URI of the created resource.

» google_compute_subnetwork

Get a subnetwork within GCE from its name and region.

» Example Usage

```
data "google_compute_subnetwork" "my-subnetwork" {  
  name     = "default-us-east1"  
  region = "us-east1"  
}
```

» Argument Reference

The following arguments are supported:

- **name** - The name of the subnetwork.
-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
 - **region** - (Optional) The region this subnetwork has been created in. If unspecified, this defaults to the region configured in the provider.

» Attributes Reference

In addition to the arguments listed above, the following attributes are exported:

- **network** - The network name or resource link to the parent network of this subnetwork.
- **description** - Description of this subnetwork.
- **ip_cidr_range** - The IP address range that machines in this network are assigned to, represented as a CIDR block.
- **gateway_address** - The IP address of the gateway.
- **private_ip_google_access** - Whether the VMs in this subnet can access Google services without assigned external IP addresses.
- **secondary_ip_range** - An array of configurations for secondary IP ranges for VM instances contained in this subnetwork. Structure is documented below.
- **self_link** - The URI of the created resource.

The **secondary_ip_range** block supports:

- **range_name** - The name associated with this subnetwork secondary range, used when adding an alias IP range to a VM instance.
- **ip_cidr_range** - The range of IP addresses belonging to this subnetwork secondary range.

» google__compute__vpn__gateway

Get a VPN gateway within GCE from its name.

» Example Usage

```
data "google_compute_vpn_gateway" "my-vpn-gateway" {
  name = "vpn-gateway-us-east1"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the VPN gateway.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
 - **region** - (Optional) The region in which the resource belongs. If it is not provided, the project region is used.

» Attributes Reference

In addition to the arguments listed above, the following attributes are exported:

- **network** - The network of this VPN gateway.
- **description** - Description of this VPN gateway.
- **region** - Region of this VPN gateway.
- **self_link** - The URI of the resource.

» google__compute__zones

Provides access to available Google Compute zones in a region for a given project. See more about regions and zones in the upstream docs.

```
data "google_compute_zones" "available" {}

resource "google_compute_instance_group_manager" "foo" {
  count = "${length(data.google_compute_zones.available.names)}"

  name                = "terraform-test-${count.index}"
  instance_template   = "${google_compute_instance_template.foobar.self_link}"
  base_instance_name  = "foobar-${count.index}"
  zone                = "${data.google_compute_zones.available.names[count.index]}"
  target_size         = 1
}
```

}

» Argument Reference

The following arguments are supported:

- **project** (Optional) - Project from which to list available zones. Defaults to project declared in the provider.
- **region** (Optional) - Region from which to list available zones. Defaults to region declared in the provider.
- **status** (Optional) - Allows to filter list of zones based on their current status. Status can be either **UP** or **DOWN**. Defaults to no filtering (all available zones - both **UP** and **DOWN**).

» Attributes Reference

The following attribute is exported:

- **names** - A list of zones available in the given region

» google__container__cluster

Get info about a cluster within GKE from its name and zone.

» Example Usage

```
data "google_container_cluster" "my_cluster" {
  name     = "my-cluster"
  zone     = "us-east1-a"
}

output "cluster_username" {
  value = "${data.google_container_cluster.my_cluster.master_auth.0.username}"
}

output "cluster_password" {
  value = "${data.google_container_cluster.my_cluster.master_auth.0.password}"
}

output "endpoint" {
  value = "${data.google_container_cluster.my_cluster.endpoint}"
}
```

```

output "instance_group_urls" {
  value = "${data.google_container_cluster.my_cluster.instance_group_urls}"
}

output "node_config" {
  value = "${data.google_container_cluster.my_cluster.node_config}"
}

output "node_pools" {
  value = "${data.google_container_cluster.my_cluster.node_pool}"
}

```

» Argument Reference

The following arguments are supported:

- **name** - The name of the cluster.
 - **zone** or **region** - The zone or region this cluster has been created in.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

See `google_container_cluster` resource for details of the available attributes.

» `google_container_engine_versions`

Provides access to available Google Container Engine versions in a zone for a given project.

```

data "google_container_engine_versions" "central1b" {
  zone = "us-central1-b"
}

resource "google_container_cluster" "foo" {
  name          = "terraform-test-cluster"
  zone          = "us-central1-b"
  node_version   = "${data.google_container_engine_versions.central1b.latest_node_version}"
  initial_node_count = 1
}

```

```

master_auth {
  username = "mr.yoda"
  password = "adoy.rm"
}
}

```

» Argument Reference

The following arguments are supported:

- **zone** (required) - Zone to list available cluster versions for. Should match the zone the cluster will be deployed in.
- **project** (optional) - ID of the project to list available cluster versions for. Should match the project the cluster will be deployed to. Defaults to the project that the provider is authenticated with.

» Attributes Reference

The following attributes are exported:

- **valid_master_versions** - A list of versions available in the given zone for use with master instances.
- **valid_node_versions** - A list of versions available in the given zone for use with node instances.
- **latest_master_version** - The latest version available in the given zone for use with master instances.
- **latest_node_version** - The latest version available in the given zone for use with node instances.
- **default_cluster_version** - Version of Kubernetes the service deploys by default.

» google__container__registry__image

This data source fetches the project name, and provides the appropriate URLs to use for container registry for this project.

The URLs are computed entirely offline - as long as the project exists, they will be valid, but this data source does not contact Google Container Registry (GCR) at any point.

» Example Usage

```

data "google_container_registry_image" "debian" {

```

```

    name = "debian"
}

output "gcr_location" {
    value = "${data.google_container_registry_image.debian.image_url}"
}

```

» Argument Reference

- **name:** (Required) The image name.
- **project:** (Optional) The project ID that this image is attached to. If not provider, provider project will be used instead.
- **region:** (Optional) The GCR region to use. As of this writing, one of `asia`, `eu`, and `us`. See the documentation for additional information.
- **tag:** (Optional) The tag to fetch, if any.
- **digest:** (Optional) The image digest to fetch, if any.

» Attributes Reference

In addition to the arguments listed above, this data source exports: * **image_url:** The URL at which the image can be accessed.

» google__container__registry__repository

This data source fetches the project name, and provides the appropriate URLs to use for container registry for this project.

The URLs are computed entirely offline - as long as the project exists, they will be valid, but this data source does not contact Google Container Registry (GCR) at any point.

» Example Usage

```

data "google_container_registry_repository" "foo" {}

output "gcr_location" {
    value = "${data.google_container_registry_repository.foo.repository_url}"
}

```

» Argument Reference

- **project**: (Optional) The project ID that this repository is attached to. If not provider, provider project will be used instead.
- **region**: (Optional) The GCR region to use. As of this writing, one of `asia`, `eu`, and `us`. See the documentation for additional information.

» Attributes Reference

In addition to the arguments listed above, this data source exports: *
repository_url: The URL at which the repository can be accessed.

» `google_dns_managed_zone`

Provides access to a zone's attributes within Google Cloud DNS. For more information see the official documentation and API.

```
data "google_dns_managed_zone" "env_dns_zone" {
  name = "qa-zone"
}

resource "google_dns_record_set" "dns" {
  name = "my-address.${data.google_dns_managed_zone.env_dns_zone.dns_name}"
  type = "TXT"
  ttl  = 300

  managed_zone = "${data.google_dns_managed_zone.env_dns_zone.name}"

  rrdatas = ["test"]
}
```

» Argument Reference

- **name** - (Required) A unique name for the resource.
- **project** - (Optional) The ID of the project for the Google Cloud DNS zone.

» Attributes Reference

The following attributes are exported:

- **dns_name** - The fully qualified DNS name of this zone, e.g. `terraform.io..`

- **description** - A textual description field.
- **name_servers** - The list of nameservers that will be authoritative for this domain. Use NS records to redirect from your DNS provider to these names, thus making Google Cloud DNS authoritative for this zone.

» **google__folder**

Use this data source to get information about a Google Cloud Folder.

```
# Get folder by id
data "google_folder" "my_folder_1" {
  folder = "folders/12345"
  lookup_organization = true
}

# Search by fields
data "google_folder" "my_folder_2" {
  folder = "folders/23456"
}

output "my_folder_1_organization" {
  value = "${data.google_folder.my_folder_1.organization}"
}

output "my_folder_2_parent" {
  value = "${data.google_folder.my_folder_2.parent}"
}
```

» **Argument Reference**

The following arguments are supported:

- **folder** (Required) - The name of the Folder in the form `{folder_id}` or `folders/{folder_id}`.
- **lookup_organization** (Optional) - `true` to find the organization that the folder belongs, `false` to avoid the lookup. It searches up the tree. (defaults to `false`)

» **Attributes Reference**

The following attributes are exported:

- **id** - The Folder ID.

- **name** - The resource name of the Folder in the form `folders/{organization_id}`.
- **parent** - The resource name of the parent Folder or Organization.
- **display_name** - The folder's display name.
- **create_time** - Timestamp when the Organization was created. A timestamp in RFC3339 UTC "Zulu" format, accurate to nanoseconds. Example: "2014-10-02T15:01:23.045123456Z".
- **lifecycle_state** - The Folder's current lifecycle state.
- **organization** - If `lookup_organization` is enable, the resource name of the Organization that the folder belongs.

» google_iam_policy

Generates an IAM policy document that may be referenced by and applied to other Google Cloud Platform resources, such as the `google_project` resource.

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/compute.instanceAdmin"

    members = [
      "serviceAccount:your-custom-sa@your-project.iam.gserviceaccount.com",
    ]
  }

  binding {
    role = "roles/storage.objectViewer"

    members = [
      "user:jane@example.com",
    ]
  }
}
```

This data source is used to define IAM policies to apply to other resources. Currently, defining a policy through a datasource and referencing that policy from another resource is the only way to apply an IAM policy to a resource.

Note: Several restrictions apply when setting IAM policies through this API. See the `setIamPolicy` docs for a list of these restrictions.

» Argument Reference

The following arguments are supported:

- **binding** (Required) - A nested configuration block (described below) defining a binding to be included in the policy document. Multiple **binding** arguments are supported.

Each document configuration must have one or more **binding** blocks, which each accept the following arguments:

- **role** (Required) - The role/permission that will be granted to the members. See the IAM Roles documentation for a complete list of roles. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **members** (Required) - An array of identities that will be granted the privilege in the **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account. It **can't** be used with the `google_project` resource.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account. It **can't** be used with the `google_project` resource.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.

» Attributes Reference

The following attribute is exported:

- **policy_data** - The above bindings serialized in a format suitable for referencing from a resource that supports IAM.

» `google__kms__secret`

This data source allows you to use data encrypted with Google Cloud KMS within your resource definitions.

For more information see the official documentation.

NOTE: Using this data provider will allow you to conceal secret data within your resource definitions, but it does not take care of protecting that data in the logging output, plan output, or state output. Please take care to secure your secret data outside of resource definitions.

» Example Usage

First, create a KMS KeyRing and CryptoKey using the resource definitions:

```
resource "google_kms_key_ring" "my_key_ring" {
  project = "my-project"
  name    = "my-key-ring"
  location = "us-central1"
}

resource "google_kms_crypto_key" "my_crypto_key" {
  name      = "my-crypto-key"
  key_ring = "${google_kms_key_ring.my_key_ring.id}"
}
```

Next, use the Cloud SDK to encrypt some sensitive information:

```
$ echo -n my-secret-password | gcloud kms encrypt \
> --project my-project \
> --location us-central1 \
> --keyring my-key-ring \
> --key my-crypto-key \
> --plaintext-file - \
> --ciphertext-file - \
> | base64
CiQAQD+xX4SX0SziF4a8JYvq4spfAuWhhYSNu133H85HnVtNQW4S0gDu2UZ46dQCRF15MF6ekabviN8xq+F+2035ZJ8
```

Finally, reference the encrypted ciphertext in your resource definitions:

```
data "google_kms_secret" "sql_user_password" {
  crypto_key = "${google_kms_crypto_key.my_crypto_key.id}"
  ciphertext = "CiQAQD+xX4SX0SziF4a8JYvq4spfAuWhhYSNu133H85HnVtNQW4S0gDu2UZ46dQCRF15MF6ekabviN8xq+F+2035ZJ8"
}

resource "google_sql_database_instance" "master" {
  name = "master-instance"

  settings {
    tier = "D0"
  }
}
```

```
resource "google_sql_user" "users" {
  name      = "me"
  instance = "${google_sql_database_instance.master.name}"
  host      = "me.com"
  password = "${data.google_kms_secret.sql_user_password.plaintext}"
}
```

This will result in a Cloud SQL user being created with password `my-secret-password`.

» Argument Reference

The following arguments are supported:

- `ciphertext` (Required) - The ciphertext to be decrypted, encoded in base64
- `crypto_key` (Required) - The id of the CryptoKey that will be used to decrypt the provided ciphertext. This is represented by the format `{projectId}/{location}/{keyRingName}/{cryptoKeyName}`.

» Attributes Reference

The following attribute is exported:

- `plaintext` - Contains the result of decrypting the provided ciphertext.

» google__netblock__ip__ranges

Use this data source to get the IP ranges from the sender policy framework (SPF) record of `_cloud-netblocks.googleusercontent`

https://cloud.google.com/compute/docs/faq#where_can_i_find_product_name_short_ip_ranges

» Example Usage

```
data "google_netblock_ip_ranges" "netblock" {}

output "cidr_blocks" {
  value = "${data.google_netblock_ip_ranges.netblock.cidr_blocks}"
}

output "cidr_blocks_ipv4" {
```

```

    value = "${data.google_netblock_ip_ranges.netblock.cidr_blocks_ipv4}"
  }

  output "cidr_blocks_ipv6" {
    value = "${data.google_netblock_ip_ranges.netblock.cidr_blocks_ipv6}"
  }

```

» Attributes Reference

- `cidr_blocks` - Retrieve list of all CIDR blocks.
- `cidr_blocks_ipv4` - Retrieve list of the IP4 CIDR blocks
- `cidr_blocks_ipv6` - Retrieve list of the IP6 CIDR blocks.

» google__organization

Use this data source to get information about a Google Cloud Organization.

```

data "google_organization" "org" {
  domain = "example.com"
}

resource "google_folder" "sales" {
  display_name = "Sales"
  parent       = "${data.google_organization.org.name}"
}

```

» Argument Reference

The arguments of this data source act as filters for querying the available Organizations. The given filters must match exactly one Organizations whose data will be exported as attributes. The following arguments are supported:

- `organization` (Optional) - The name of the Organization in the form `{organization_id}` or `organizations/{organization_id}`.
- `domain` (Optional) - The domain name of the Organization.

NOTE: One of `organization` or `domain` must be specified.

» Attributes Reference

The following additional attributes are exported:

- **id** - The Organization ID.
- **name** - The resource name of the Organization in the form **organizations/{organization_id}**.
- **directory_customer_id** - The Google for Work customer ID of the Organization.
- **create_time** - Timestamp when the Organization was created. A timestamp in RFC3339 UTC "Zulu" format, accurate to nanoseconds. Example: "2014-10-02T15:01:23.045123456Z".
- **lifecycle_state** - The Organization's current lifecycle state.

» **google__project**

Use this data source to get project details. For more information see API

» **Example Usage**

```
data "google_project" "project" {}

output "project_number" {
  value = "${data.google_project.project.number}"
}
```

» **Argument Reference**

The following arguments are supported:

- **project_id** - (Optional) The project ID. If it is not provided, the provider project is used.

» **Attributes Reference**

The following attributes are exported:

See `google_project` resource for details of the available attributes.

» **google__service__account**

Get the service account from a project. For more information see the official API documentation.

» Example Usage

```
data "google_service_account" "object_viewer" {
  account_id = "object-viewer"
}
```

» Example Usage, save key in Kubernetes secret

```
data "google_service_account" "myaccount" {
  account_id = "myaccount-id"
}

resource "google_service_account_key" "mykey" {
  service_account_id = "${data.google_service_account.myaccount.name}"
}

resource "kubernetes_secret" "google-application-credentials" {
  metadata {
    name = "google-application-credentials"
  }
  data {
    credentials.json = "${base64decode(google_service_account_key.mykey.private_key)}"
  }
}
```

» Argument Reference

The following arguments are supported:

- `account_id` - (Required) The Service account id.
- `project` - (Optional) The ID of the project that the service account will be created in. Defaults to the provider project configuration.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `email` - The e-mail address of the service account. This value should be referenced from any `google_iam_policy` data sources that would grant the service account privileges.
- `unique_id` - The unique id of the service account.
- `name` - The fully-qualified name of the service account.

- `display_name` - The display name for the service account.

» `google_service_account_key`

Get service account public key. For more information, see the official documentation and API.

» Example Usage

```
data "google_service_account" "myaccount" {
  account_id = "myaccount"
}

data "google_service_account_key" "mykey" {
  service_account_id = "${data.google_service_account.myaccount.name}"
  public_key_type = "TYPE_X509_PEM_FILE"
}

output "mykey_public_key" {
  value = "${data.google_service_account_key.mykey.public_key}"
}
```

» Argument Reference

The following arguments are supported:

- `service_account_id` - (Required) The Service account id of the Key Pair. This can be a string in the format `{ACCOUNT}` or `projects/{PROJECT_ID}/serviceAccounts/{ACCOUNT}`, where `{ACCOUNT}` is the email address or unique id of the service account. If the `{ACCOUNT}` syntax is used, the project will be inferred from the account.
- `project` - (Optional) The ID of the project that the service account will be created in. Defaults to the provider project configuration.
- `public_key_type` (Optional) The output format of the public key requested. `X509_PEM` is the default output format.

» Attributes Reference

The following attributes are exported in addition to the arguments listed above:

- `name` - The name used for this key pair

- `public_key` - The public key, base64 encoded

» `google_storage_object_signed_url`

The Google Cloud storage signed URL data source generates a signed URL for a given storage object. Signed URLs provide a way to give time-limited read or write access to anyone in possession of the URL, regardless of whether they have a Google account.

For more info about signed URL's is available [here](#).

» Example Usage

```
data "google_storage_object_signed_url" "artifact" {
  bucket = "install_binaries"
  path   = "path/to/install_file.bin"
}

resource "google_compute_instance" "vm" {
  name = "vm"
  ...

  provisioner "remote-exec" {
    inline = [
      "wget '${data.google_storage_object_signed_url.artifact.signed_url}' -O install_file.bin",
      "chmod +x install_file.bin",
      "./install_file.bin"
    ]
  }
}
```

» Full Example

```
data "google_storage_object_signed_url" "get_url" {
  bucket      = "fried_chicken"
  path        = "path/to/file"
  content_md5 = "pRviqwS4c40TJRTe03FD1w=="
  content_type = "text/plain"
  duration    = "2d"
  credentials = "${file("path/to/credentials.json")}"

  extension_headers {
```

```

    x-goog-if-generation-match = 1
  }
}

```

» Argument Reference

The following arguments are supported:

- **bucket** - (Required) The name of the bucket to read the object from
- **path** - (Required) The full path to the object inside the bucket
- **http_method** - (Optional) What HTTP Method will the signed URL allow (defaults to **GET**)
- **duration** - (Optional) For how long shall the signed URL be valid (defaults to 1 hour - i.e. **1h**). See here for info on valid duration formats.
- **credentials** - (Optional) What Google service account credentials json should be used to sign the URL. This data source checks the following locations for credentials, in order of preference: data source **credentials** attribute, provider **credentials** attribute and finally the **GOOGLE_APPLICATION_CREDENTIALS** environment variable.

NOTE the default google credentials configured by **gcloud** sdk or the service account associated with a compute instance cannot be used, because these do not include the private key required to sign the URL. A valid json service account credentials key file must be used, as generated via Google cloud console.

- **content_type** - (Optional) If you specify this in the datasource, the client must provide the **Content-Type** HTTP header with the same value in its request.
- **content_md5** - (Optional) The MD5 digest value in Base64. Typically retrieved from **google_storage_bucket_object.object.md5hash** attribute. If you provide this in the datasource, the client (e.g. browser, curl) must provide the **Content-MD5** HTTP header with this same value in its request.
- **extension_headers** - (Optional) As needed. The server checks to make sure that the client provides matching values in requests using the signed URL. Any header starting with **x-goog-** is accepted but see the Google Docs for list of headers that are supported by Google.

» Attributes Reference

The following attributes are exported:

- **signed_url** - The signed URL that can be used to access the storage object without authentication.

» `google_storage_project_service_account`

Get the email address of a project's unique Google Cloud Storage service account.

Each Google Cloud project has a unique service account for use with Google Cloud Storage. Only this special service account can be used to set up `google_storage_notification` resources.

For more information see the API reference.

» Example Usage

```
data "google_storage_project_service_account" "gcs_account" {}

resource "google_pubsub_topic_iam_binding" "binding" {
  topic      = "${google_pubsub_topic.topic.name}"
  role       = "roles/pubsub.publisher"

  members    = ["serviceAccount:${data.google_storage_project_service_account.gcs_account}"]
}
```

» Argument Reference

The following arguments are supported:

- `project` - (Optional) The project the unique service account was created for. If it is not provided, the provider project is used.
- `user_project` - (Optional) The project the lookup originates from. This field is used if you are making the request from a different account than the one you are finding the service account for.

» Attributes Reference

The following attributes are exported:

- `email_address` - The email address of the service account. This value is often used to refer to the service account in order to grant IAM permissions.

» google__bigquery__dataset

Creates a dataset resource for Google BigQuery. For more information see the official documentation and API.

» Example Usage

```
resource "google_bigquery_dataset" "default" {
  dataset_id          = "foo"
  friendly_name       = "test"
  description         = "This is a test description"
  location            = "EU"
  default_table_expiration_ms = 3600000

  labels {
    env = "default"
  }
}
```

» Argument Reference

The following arguments are supported:

- **dataset_id** - (Required) A unique ID for the resource. Changing this forces a new resource to be created.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **friendly_name** - (Optional) A descriptive name for the dataset.
- **description** - (Optional) A user-friendly description of the dataset.
- **location** - (Optional) The geographic location where the dataset should reside. See official docs.

There are two types of locations, regional or multi-regional. A regional location is a specific geographic place, such as Tokyo, and a multi-regional location is a large geographic area, such as the United States, that contains at least two geographic places

Possible regional values include: **asia-northeast1** Possible multi-regional values: **EU** and **US**.

The default value is multi-regional location **US**. Changing this forces a new resource to be created.

- **default_table_expiration_ms** - (Optional) The default lifetime of all tables in the dataset, in milliseconds. The minimum value is 3600000 milliseconds (one hour).

Once this property is set, all newly-created tables in the dataset will have an `expirationTime` property set to the creation time plus the value in this property, and changing the value will only affect new tables, not existing ones. When the `expirationTime` for a given table is reached, that table will be deleted automatically. If a table's `expirationTime` is modified or removed before the table expires, or if you provide an explicit `expirationTime` when creating a table, that value takes precedence over the default expiration time indicated by this property.

- **labels** - (Optional) A mapping of labels to assign to the resource.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.
- **etag** - A hash of the resource.
- **creation_time** - The time when this dataset was created, in milliseconds since the epoch.
- **last_modified_time** - The date when this dataset or any of its tables was last modified, in milliseconds since the epoch.

» Import

BigQuery datasets can be imported using the `project` and `dataset_id`, e.g.

```
$ terraform import google_bigquery_dataset.default gcp-project:foo
```

» google__bigquery__table

Creates a table resource in a dataset for Google BigQuery. For more information see the official documentation and API.

» Example Usage

```
resource "google_bigquery_dataset" "default" {
  dataset_id = "foo"
```

```

friendly_name          = "test"
description             = "This is a test description"
location               = "EU"
default_table_expiration_ms = 3600000

labels {
  env = "default"
}
}

resource "google_bigquery_table" "default" {
  dataset_id = "${google_bigquery_dataset.default.dataset_id}"
  table_id   = "bar"

  time_partitioning {
    type = "DAY"
  }

  labels {
    env = "default"
  }

  schema = "${file("schema.json")}"
}

```

» Argument Reference

The following arguments are supported:

- **dataset_id** - (Required) The dataset ID to create the table in. Changing this forces a new resource to be created.
- **table_id** - (Required) A unique ID for the resource. Changing this forces a new resource to be created.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **description** - (Optional) The field description.
- **expiration_time** - (Optional) The time when this table expires, in milliseconds since the epoch. If not present, the table will persist indefinitely. Expired tables will be deleted and their storage reclaimed.
- **friendly_name** - (Optional) A descriptive name for the table.
- **labels** - (Optional) A mapping of labels to assign to the resource.
- **schema** - (Optional) A JSON schema for the table.

- **time_partitioning** - (Optional) If specified, configures time-based partitioning for this table. Structure is documented below.
- **view** - (Optional) If specified, configures this table as a view. Structure is documented below.

The **time_partitioning** block supports:

- **expiration_ms** - (Optional) Number of milliseconds for which to keep the storage for a partition.
- **field** - (Optional) The field used to determine how to create a time-based partition. If time-based partitioning is enabled without this value, the table is partitioned based on the load time.
- **type** - (Required) The only type supported is DAY, which will generate one partition per day based on data loading time.

The **view** block supports:

- **query** - (Required) A query that BigQuery executes when the view is referenced.
- **use_legacy_sql** - (Optional) Specifies whether to use BigQuery's legacy SQL for this view. The default value is true. If set to false, the view will use BigQuery's standard SQL.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_time** - The time when this table was created, in milliseconds since the epoch.
- **etag** - A hash of the resource.
- **last_modified_time** - The time when this table was last modified, in milliseconds since the epoch.
- **location** - The geographic location where the table resides. This value is inherited from the dataset.
- **num_bytes** - The size of this table in bytes, excluding any data in the streaming buffer.
- **num_long_term_bytes** - The number of bytes in the table that are considered "long-term storage".
- **num_rows** - The number of rows of data in this table, excluding any data in the streaming buffer.
- **self_link** - The URI of the created resource.

- `type` - Describes the table type.

» Import

BigQuery tables can be imported using the `project`, `dataset_id`, and `table_id`, e.g.

```
$ terraform import google_bigquery_table.default gcp-project:foo.bar
```

» `google__bigtable__instance`

Creates a Google Bigtable instance. For more information see the official documentation and API.

» Example Usage

```
resource "google_bigtable_instance" "instance" {
  name          = "tf-instance"
  cluster_id    = "tf-instance-cluster"
  zone         = "us-central1-b"
  num_nodes    = 3
  storage_type = "HDD"
}
```

» Argument Reference

The following arguments are supported:

- `name` - (Required) The name of the Cloud Bigtable instance.
- `cluster_id` - (Required) The ID of the Cloud Bigtable cluster.
- `zone` - (Required) The zone to create the Cloud Bigtable cluster in. Zones that support Bigtable instances are noted on the Cloud Bigtable locations page.
- `num_nodes` - (Optional) The number of nodes in your Cloud Bigtable cluster. Minimum of 3 for a `PRODUCTION` instance. Cannot be set for a `DEVELOPMENT` instance.
- `instance_type` - (Optional) The instance type to create. One of `"DEVELOPMENT"` or `"PRODUCTION"`. Defaults to `"PRODUCTION"`.
- `storage_type` - (Optional) The storage type to use. One of `"SSD"` or `"HDD"`. Defaults to `"SSD"`.

- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **display_name** - (Optional) The human-readable display name of the Bigtable instance. Defaults to the instance **name**.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» google__bigtable__table

Creates a Google Bigtable table inside an instance. For more information see the official documentation and API.

» Example Usage

```
resource "google_bigtable_instance" "instance" {
  name          = "tf-instance"
  cluster_id    = "tf-instance-cluster"
  zone          = "us-central1-b"
  num_nodes     = 3
  storage_type  = "HDD"
}

resource "google_bigtable_table" "table" {
  name          = "tf-table"
  instance_name = "${google_bigtable_instance.instance.name}"
  split_keys    = ["a", "b", "c"]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the table.
- **instance_name** - (Required) The name of the Bigtable instance.
- **split_keys** - (Optional) A list of predefined keys to split the table on.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» google__binary__authorization__attestor

An attestor that attests to container image artifacts.

To get more information about Attestor, see:

- API documentation
- How-to Guides
 - Official Documentation

» Example Usage

```
resource "google_container_analysis_note" "note" {
  name = "test-attestor-note"
  attestation_authority {
    hint {
      human_readable_name = "Attestor Note"
    }
  }
}

resource "google_binary_authorization_attestor" "attestor" {
  name = "test-attestor"
  attestation_authority_note {
    note_reference = "${google_container_analysis_note.note.name}"
    public_keys {
      ascii_armored_pgp_public_key = <<EOF
mQENBFtP0doBCADF+joTiXWKVuP8kJt3fgpBSjT9h8ezMfKA4aXZctYLx5ws1WQ1
bB7Iu2ezkECNzoEeU7WxUe8a61pMCh9cisS9H5mB2K2uM4Jnf8tgFeXn3akJDVo0
oR1IC+Dp9mXbRSK3MAvKk0wWlG99sx3uEdvmeBRHB00+grchLx24EThXF0yP9Fk6
V39j6xMjw4agglD15B4V0v9JqBDdJiIYFzszZDL6pJwZrzcP0z8J04rTZd+f64bD
Mpj52j/pQfA81ZH0aAgb1OrthLdMrBAjoDjArV4Ek7vSbrcgYWcI6BhsQrFoxKdX
83TZKai55ZCfCLIskwUIzA1NLVwyzCS+fSN/ABEBAAG0KCJUZXNOIEF0dGVzdG9y
IiA8ZGFuYWVhZmZtYW5AZ29vZ2xlLmNvbT6JAU4EEwEiADgWIQRfWkqHt6hpTA1L
uY060eeM4dc66AUCW0/R2gIbLwULCQgHAgYVCgkICwIEFgIDAQIeAQIXgAAK CRA6
0eeM4dc66HdpCAC4ot3b00yxPb0Ip+WT2U0PbpTBPJklesuwpIrM4Lh0N+1nVRLC
51WsmVbM8BiAFhLbN9LpdHhds1kUrHF7+wWAjdR8sqAj9otc6HGRM/3qfa2qgh+U
WTEk/3us/rYSi7T7TkMuutRMia1IkR13uKiW56csEMnb0Qpn9rDqwIr5R8nlZP5h
MAU9vdm1DIv567meMqTaVZgR3w7bck2P49A08105ERFpVkErtu/98y+rUy9d789l
+OPuS1NGnxI1YKsNaWJF4uJVuvQuZ1twrhCbGntVor02U12+cEq+YtUxj7kmdOC1
EOF
    }
  }
}
```

```

qoIRW6y0+U1Ac+MbqfL0ziHD0Amcqz1GnR0g
=6Bvm
EOF
    }
  }
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The resource name.
- **attestation_authority_note** - (Required) A Container Analysis ATTESTATION_AUTHORITY Note, created by the user. Structure is documented below.

The **attestation_authority_note** block supports:

- **note_reference** - (Required) The resource name of a ATTESTATION_AUTHORITY Note, created by the user. If the Note is in a different project from the Attestor, it should be specified in the format **projects/*/notes/*** (or the legacy **providers/*/notes/***). This field may not be updated. An attestation by this attestor is stored as a Container Analysis ATTESTATION_AUTHORITY Occurrence that names a container image and that links to this Note.
- **public_keys** - (Optional) Public keys that verify attestations signed by this attestor. This field may be updated. If this field is non-empty, one of the specified public keys must verify that an attestation was signed by this attestor for the image specified in the admission request. If this field is empty, this attestor always returns that no valid attestations exist. Structure is documented below.
- **delegation_service_account_email** - This field will contain the service account email address that this Attestor will use as the principal when querying Container Analysis. Attestor administrators must grant this service account the IAM role needed to read attestations from the `noteReference` in Container Analysis (`containeranalysis.notes.occurrences.viewer`). This email address is fixed for the lifetime of the Attestor, but callers should not make any other assumptions about the service account email; future versions may use an email based on a different naming pattern.

The **public_keys** block supports:

- **comment** - (Optional) A descriptive comment. This field may be updated.
- **id** - This field will be overwritten with key ID information, for example, an identifier extracted from a PGP public key. This field may not be

updated.

- `ascii_armored_pgp_public_key` - (Required) ASCII-armored representation of a PGP public key, as the entire output by the command `gpg --export --armor foo@example.com` (either LF or CRLF line endings).

-
- `description` - (Optional) A descriptive comment. This field may be updated. The field may be displayed in chooser dialogs.
 - `project` - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Import

Attestor can be imported using any of these accepted formats:

```
$ terraform import google_binary_authorization_attestor.default projects/{{project}}/attestor/{{name}}
$ terraform import google_binary_authorization_attestor.default {{project}}/{{name}}
$ terraform import google_binary_authorization_attestor.default {{name}}
```

» google__binary__authorization__policy

A policy for container image binary authorization.

To get more information about Policy, see:

- API documentation
- How-to Guides
 - Official Documentation

» Example Usage

```
resource "google_container_analysis_note" "note" {
  name = "test-attestor-note"
  attestation_authority {
    hint {
      human_readable_name = "My attestor"
    }
  }
}

resource "google_binary_authorization_attestor" "attestor" {
  name = "test-attestor"
  attestation_authority_note {
```

```

    note_reference = "${google_container_analysis_note.note.name}"
  }
}

resource "google_binary_authorization_policy" "policy" {
  admission_whitelist_patterns {
    name_pattern= "gcr.io/google_containers/*"
  }

  default_admission_rule {
    evaluation_mode = "ALWAYS_ALLOW"
    enforcement_mode = "ENFORCED_BLOCK_AND_AUDIT_LOG"
  }

  cluster_admission_rules {
    cluster = "us-central1-a.prod-cluster"
    evaluation_mode = "REQUIRE_ATTESTATION"
    enforcement_mode = "ENFORCED_BLOCK_AND_AUDIT_LOG"
    require_attestations_by = ["${google_binary_authorization_attestor.attestor.name}"]
  }
}

```

» Argument Reference

The following arguments are supported:

- **default_admission_rule** - (Required) Default admission rule for a cluster without a per-cluster admission rule. Structure is documented below.

The **default_admission_rule** block supports:

- **evaluation_mode** - (Required) How this admission rule will be evaluated.
- **require_attestations_by** - (Optional) The resource names of the attestors that must attest to a container image. If the attestor is in a different project from the policy, it should be specified in the format **projects/*/attestors/***. Each attestor must exist before a policy can reference it. To add an attestor to a policy the principal issuing the policy change request must be able to read the attestor resource. Note: this field must be non-empty when the **evaluation_mode** field specifies **REQUIRE_ATTESTATION**, otherwise it must be empty.
- **enforcement_mode** - (Required) The action when a pod creation is denied by the admission rule.

-
- **description** - (Optional) A descriptive comment.

- **admission_whitelist_patterns** - (Optional) Admission policy whitelisting. A matching admission request will always be permitted. This feature is typically used to exclude Google or third-party infrastructure images from Binary Authorization policies. Structure is documented below.
- **cluster_admission_rules** - (Optional) Admission policy whitelisting. A matching admission request will always be permitted. This feature is typically used to exclude Google or third-party infrastructure images from Binary Authorization policies.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

The **admission_whitelist_patterns** block supports:

- **name_pattern** - (Optional) An image name pattern to whitelist, in the form **registry/path/to/image**. This supports a trailing ***** as a wildcard, but this is allowed only in text after the **registry/** part.

The **cluster_admission_rules** block supports:

- **evaluation_mode** - (Optional) How this admission rule will be evaluated.
- **require_attestations_by** - (Optional) The resource names of the attestors that must attest to a container image. If the attestor is in a different project from the policy, it should be specified in the format **projects/*/attestors/***. Each attestor must exist before a policy can reference it. To add an attestor to a policy the principal issuing the policy change request must be able to read the attestor resource. Note: this field must be non-empty when the **evaluation_mode** field specifies **REQUIRE_ATTESTATION**, otherwise it must be empty.
- **enforcement_mode** - (Optional) The action when a pod creation is denied by the admission rule.

» Import

Policy can be imported using any of these accepted formats:

```
$ terraform import google_binary_authorization_policy.default projects/{{project}}
$ terraform import google_binary_authorization_policy.default {{project}}
```

» google__cloudbuild__trigger

Creates a new build trigger within GCR. For more information, see the official documentation and API.

» Example Usage

```
resource "google_cloudbuild_trigger" "build_trigger" {
  project = "my-project"
  trigger_template {
    branch_name = "master"
    project     = "my-project"
    repo_name   = "some-repo"
  }
  build {
    images = ["gcr.io/$PROJECT_ID/$REPO_NAME:$COMMIT_SHA"]
    step {
      name = "gcr.io/cloud-builders/docker"
      args = ["build -t gcr.io/$PROJECT_ID/$REPO_NAME:$COMMIT_SHA -f Dockerfile ."]
    }
  }
}
```

OR

```
resource "google_cloudbuild_trigger" "build_trigger" {
  project = "my-project"
  trigger_template {
    branch_name = "master"
    project     = "my-project"
    repo_name   = "some-repo"
  }
  filename = "cloudbuild.yaml"
}
```

» Argument Reference

(Argument descriptions sourced from <https://godoc.org/google.golang.org/api/cloudbuild/v1#BuildTrigger>)

The following arguments are supported:

- **description** - (Optional) A brief description of this resource.
- **trigger_template** - (Optional) Location of the source in a Google Cloud Source Repository. Structure is documented below.
- **build** - (Optional) A build resource in the Container Builder API. Structure is documented below. At a high level, a **build** describes where to find source code, how to build it (for example, the builder image to run on the source), and where to store the built artifacts. Fields can include the following variables, which will be expanded when the build is created:

- `$PROJECT_ID`: the project ID of the build.
 - `$BUILD_ID`: the autogenerated ID of the build.
 - `$REPO_NAME`: the source repository name specified by RepoSource.
 - `$BRANCH_NAME`: the branch name specified by RepoSource.
 - `$TAG_NAME`: the tag name specified by RepoSource.
 - `$REVISION_ID` or `$COMMIT_SHA`: the commit SHA specified by RepoSource or resolved from the specified branch or tag.
 - `$SHORT_SHA`: first 7 characters of `$REVISION_ID` or `$COMMIT_SHA`.
- **filename** - (Optional) Specify the path to a Cloud Build configuration file in the Git repo. This is mutually exclusive with **build**. This is typically `cloudbuild.yaml` however it can be specified by the user.
 - **substitutions**: (Optional) User-defined substitutions. User-defined substitutions must conform to the following rules:
 - Substitutions must begin with an underscore (`_`) and use only uppercase-letters and numbers (respecting the regular expression `_[A-Z0-9_]+`). This prevents conflicts with built-in substitutions.
 - Unmatched keys in the template will cause an error (for example, if a build request includes `$_FOO` and the substitutions map doesn't define `_FOO`).
 - Unmatched keys in the parameters list will result in an error (for example, if a substitutions map defines `_FOO` but the build request doesn't include `$_FOO`).
 - To include a literal `$_VARIABLE` in the template, you must escape with `$$`.
 - You can explicitly denote variable expansion using the `${_VAR}` syntax. This prevents ambiguity in cases like `${_FOO}BAR`, where `$_FOO` is a variable.
 - The number of parameters is limited to 100 parameters.
 - The length of a parameter key and the length of a parameter value are limited to 100 characters.

The `trigger_template` block supports:

- **branch_name** - (Optional) Name of the branch to build.
- **commit_sha** - (Optional) Explicit commit SHA to build.
- **dir** - (Optional) Directory, relative to the source root, in which to run the build. This must be a relative path. If a step's **dir** is specified and is an absolute path, this value is ignored for that step's execution.
- **project** - (Optional) ID of the project that owns the Cloud Source Repository.
- **repo_name** - (Optional) Name of the Cloud Source Repository.

- `tag_name` - (Optional) Name of the tag to build.
-

The `build` block supports:

- `images` - (Optional) A list of images to be pushed upon the successful completion of all build steps.
 - `step` - (Optional) The operations to be performed on the workspace. Structure is documented below.
 - `tags` - (Optional) Tags for annotation of a build. **These are not docker tags**
-

The `step` block supports:

- `name` - (Optional) The name of the container image that will run this particular build step. If the image is available in the host's Docker daemon's cache, it will be run directly. If not, the host will attempt to pull the image first, using the builder service account's credentials if necessary. The Docker daemon's cache will already have the latest versions of all of the officially supported build steps (<https://github.com/GoogleCloudPlatform/cloud-builders>). The Docker daemon will also have cached many of the layers for some popular images, like "ubuntu", "debian", but they will be refreshed at the time you attempt to use them. If you built an image in a previous build step, it will be stored in the host's Docker daemon's cache and is available to use as the name for a later build step.
- `args` - (Optional) A list of arguments that will be presented to the step when it is started. If the image used to run the step's container has an entrypoint, the `args` are used as arguments to that entrypoint. If the image does not define an entrypoint, the first element in `args` is used as the entrypoint, and the remainder will be used as arguments.

» `google_cloudfunctions_function`

Creates a new Cloud Function. For more information see the official documentation and API.

» Example Usage

```
resource "google_storage_bucket" "bucket" {  
  name = "test-bucket"  
}
```

```

resource "google_storage_bucket_object" "archive" {
  name     = "index.zip"
  bucket   = "${google_storage_bucket.bucket.name}"
  source   = "./path/to/zip/file/which/contains/code"
}

resource "google_cloudfunctions_function" "function" {
  name                = "function-test"
  description         = "My function"
  available_memory_mb = 128
  source_archive_bucket = "${google_storage_bucket.bucket.name}"
  source_archive_object = "${google_storage_bucket_object.archive.name}"
  trigger_http        = true
  timeout             = 60
  entry_point         = "helloGET"
  labels {
    my-label = "my-label-value"
  }
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A user-defined name of the function. Function names must be unique globally.
 - **source_archive_bucket** - (Required) The GCS bucket containing the zip archive which contains the function.
 - **source_archive_object** - (Required) The source archive object (file) in archive bucket.
-
- **description** - (Optional) Description of the function.
 - **available_memory_mb** - (Optional) Memory (in MB), available to the function. Default value is 256MB. Allowed values are: 128MB, 256MB, 512MB, 1024MB, and 2048MB.
 - **timeout** - (Optional) Timeout (in seconds) for the function. Default value is 60 seconds. Cannot be more than 540 seconds.
 - **entry_point** - (Optional) Name of a JavaScript function that will be executed when the Google Cloud Function is triggered.
 - **trigger_http** - (Optional) Boolean variable. Any HTTP request (of a supported type) to the endpoint will trigger function execution. Sup-

ported HTTP request types are: POST, PUT, GET, DELETE, and OPTIONS. Endpoint is returned as `https_trigger_url`. Cannot be used with `trigger_bucket` and `trigger_topic`.

- `trigger_bucket` - (Optional) Google Cloud Storage bucket name. Every change in files in this bucket will trigger function execution. Cannot be used with `trigger_http` and `trigger_topic`.
- `trigger_topic` - (Optional) Name of Pub/Sub topic. Every message published in this topic will trigger function execution with message contents passed as input data. Cannot be used with `trigger_http` and `trigger_bucket`.
- `labels` - (Optional) A set of key/value label pairs to assign to the function.
- `retry_on_failure` - (Optional) Whether the function should be retried on failure. This only applies to bucket and topic triggers, not HTTPS triggers.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `https_trigger_url` - URL which triggers function execution. Returned only if `trigger_http` is used.
- `project` - Project of the function. If it is not provided, the provider project is used.
- `region` - Region of function. Currently can be only "us-central1". If it is not provided, the provider region is used.

» Import

Functions can be imported using the name, e.g.

```
$ terraform import google_cloudfunctions_function.default function-test
```

» google__folder

Allows management of a Google Cloud Platform folder. For more information see the official documentation and API.

A folder can contain projects, other folders, or a combination of both. You can use folders to group projects under an organization in a hierarchy. For example, your organization might contain multiple departments, each with its own set

of Cloud Platform resources. Folders allows you to group these resources on a per-department basis. Folders are used to group resources that share common IAM policies.

Folders created live inside an Organization. See the Organization documentation for more details.

The service account used to run Terraform when creating a `google_folder` resource must have `roles/resourcemanager.folderCreator`. See the Access Control for Folders Using IAM doc for more information.

» Example Usage

```
# Top-level folder under an organization.
resource "google_folder" "department1" {
  display_name = "Department 1"
  parent      = "organizations/1234567"
}

# Folder nested under another folder.
resource "google_folder" "team-abc" {
  display_name = "Team ABC"
  parent      = "${google_folder.department1.name}"
}
```

» Argument Reference

The following arguments are supported:

- `display_name` - (Required) The folder's display name. A folder's display name must be unique amongst its siblings, e.g. no two folders with the same parent can share the same display name. The display name must start and end with a letter or digit, may contain letters, digits, spaces, hyphens and underscores and can be no longer than 30 characters.
- `parent` - (Required) The resource name of the parent Folder or Organization. Must be of the form `folders/{folder_id}` or `organizations/{org_id}`.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `name` - The resource name of the Folder. Its format is `folders/{folder_id}`.

- `lifecycle_state` - The lifecycle state of the folder such as `ACTIVE` or `DELETE_REQUESTED`.
- `create_time` - Timestamp when the Folder was created. Assigned by the server. A timestamp in RFC3339 UTC "Zulu" format, accurate to nanoseconds. Example: "2014-10-02T15:01:23.045123456Z".

» Import

Folders can be imported using the folder autogenerated `name`, e.g.

```
# Both syntaxes are valid
$ terraform import google_folder.department1 1234567
$ terraform import google_folder.department1 folders/1234567
```

» `google_folder_iam_binding`

Allows creation and management of a single binding within IAM policy for an existing Google Cloud Platform folder.

Note: This resource *must not* be used in conjunction with `google_folder_iam_policy` or they will fight over what your policy should be.

» Example Usage

```
resource "google_folder" "department1" {
  display_name = "Department 1"
  parent      = "organizations/1234567"
}

resource "google_folder_iam_binding" "admin" {
  folder = "${google_folder.department1.name}"
  role   = "roles/editor"

  members = [
    "user:jane@example.com",
  ]
}
```

» Argument Reference

The following arguments are supported:

- **folder** - (Required) The resource name of the folder the policy is attached to. Its format is `folders/{folder_id}`.
- **members** (Required) - An array of identities that will be granted the privilege in the **role**. Each entry can have one of the following values:
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_folder_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the folder's IAM policy.

» Import

IAM binding imports use space-delimited identifiers; first the resource in question and then the role. These bindings can be imported using the **folder** and **role**, e.g.

```
$ terraform import google_folder_iam_binding.viewer "folder-name roles/viewer"
```

» google_folder_iam_member

Allows creation and management of a single member for a single binding within the IAM policy for an existing Google Cloud Platform folder.

Note: This resource *must not* be used in conjunction with `google_folder_iam_policy` or they will fight over what your policy should be. Similarly, roles controlled by `google_folder_iam_binding` should not be assigned to using `google_folder_iam_member`.

» Example Usage

```
resource "google_folder" "department1" {
  display_name = "Department 1"
  parent      = "organizations/1234567"
}

resource "google_folder_iam_member" "admin" {
  folder = "${google_folder.department1.name}"
  role   = "roles/editor"
  member = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **folder** - (Required) The resource name of the folder the policy is attached to. Its format is `folders/{folder_id}`.
- **member** - (Required) The identity that will be granted the privilege in the role. This field can have one of the following values:
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the folder's IAM policy.

» Import

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account. This member resource can be imported using the folder, role, and account e.g.

```
$ terraform import google_folder_iam_member.my_project "folder-name roles/viewer foo@example.com"
```

» google__folder__iam__policy

Allows creation and management of the IAM policy for an existing Google Cloud Platform folder.

» Example Usage

```
resource "google_folder_iam_policy" "folder_admin_policy" {
  folder      = "${google_folder.department1.name}"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}

resource "google_folder" "department1" {
  display_name = "Department 1"
  parent       = "organizations/1234567"
}

data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}
```

» Argument Reference

The following arguments are supported:

- **folder** - (Required) The resource name of the folder the policy is attached to. Its format is `folders/{folder_id}`.

- **policy_data** - (Required) The `google_iam_policy` data source that represents the IAM policy that will be applied to the folder. This policy overrides any existing policy applied to the folder.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the folder's IAM policy. `etag` is used for optimistic concurrency control as a way to help prevent simultaneous updates of a policy from overwriting each other.

» `google_folder_organization_policy`

Allows management of Organization policies for a Google Folder. For more information see the official documentation and API.

» Example Usage

To set policy with a boolean constraint:

```
resource "google_folder_organization_policy" "serial_port_policy" {
  folder      = "folders/123456789"
  constraint = "compute.disableSerialPortAccess"

  boolean_policy {
    enforced = true
  }
}
```

To set a policy with a list constraint:

```
resource "google_folder_organization_policy" "services_policy" {
  folder      = "folders/123456789"
  constraint = "serviceuser.services"

  list_policy {
    allow {
      all = true
    }
  }
}
```

Or to deny some services, use the following instead:

```
resource "google_folder_organization_policy" "services_policy" {
  folder      = "folders/123456789"
  constraint = "serviceuser.services"

  list_policy {
    suggested_values = "compute.googleapis.com"

    deny {
      values = ["cloudresourcemanager.googleapis.com"]
    }
  }
}
```

To restore the default folder organization policy, use the following instead:

```
resource "google_folder_organization_policy" "services_policy" {
  folder      = "folders/123456789"
  constraint = "serviceuser.services"

  restore_policy {
    default = true
  }
}
```

» Argument Reference

The following arguments are supported:

- **folder** - (Required) The resource name of the folder to set the policy for. Its format is `folders/{folder_id}`.
 - **constraint** - (Required) The name of the Constraint the Policy is configuring, for example, `serviceuser.services`. Check out the complete list of available constraints.
-
- **version** - (Optional) Version of the Policy. Default version is 0.
 - **boolean_policy** - (Optional) A boolean policy is a constraint that is either enforced or not. Structure is documented below.
 - **list_policy** - (Optional) A policy that can define specific values that are allowed or denied for the given constraint. It can also be used to allow or deny all values. Structure is documented below.
 - **restore_policy** - (Optional) A restore policy is a constraint to restore the default policy. Structure is documented below.
-

The `boolean_policy` block supports:

- **enforced** - (Required) If true, then the Policy is enforced. If false, then any configuration is acceptable.

The `list_policy` block supports:

- **allow** or **deny** - (Optional) One or the other must be set.
- **suggested_values** - (Optional) The Google Cloud Console will try to default to a configuration that matches the value specified in this field.

The **allow** or **deny** blocks support:

- **all** - (Optional) The policy allows or denies all values.
- **values** - (Optional) The policy can define specific values that are allowed or denied.

The `restore_policy` block supports:

- **default** - (Required) May only be set to true. If set, then the default Policy is restored.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the organization policy. **etag** is used for optimistic concurrency control as a way to help prevent simultaneous updates of a policy from overwriting each other.
- **update_time** - (Computed) The timestamp in RFC3339 UTC "Zulu" format, accurate to nanoseconds, representing when the variable was last updated. Example: "2016-10-09T12:33:37.578138407Z".

» `google__organization__policy`

Allows management of Organization policies for a Google Organization. For more information see the official documentation and API.

» Example Usage

To set policy with a boolean constraint:

```

resource "google_organization_policy" "serial_port_policy" {
  org_id      = "123456789"
  constraint = "compute.disableSerialPortAccess"

  boolean_policy {
    enforced = true
  }
}

```

To set a policy with a list constraint:

```

resource "google_organization_policy" "services_policy" {
  org_id      = "123456789"
  constraint = "serviceuser.services"

  list_policy {
    allow {
      all = true
    }
  }
}

```

Or to deny some services, use the following instead:

```

resource "google_organization_policy" "services_policy" {
  org_id      = "123456789"
  constraint = "serviceuser.services"

  list_policy {
    suggested_values = "compute.googleapis.com"

    deny {
      values = ["cloudresourcemanager.googleapis.com"]
    }
  }
}

```

To restore the default organization policy, use the following instead:

```

resource "google_organization_policy" "services_policy" {
  org_id      = "123456789"
  constraint = "serviceuser.services"

  restore_policy {
    default = true
  }
}

```

» Argument Reference

The following arguments are supported:

- **org_id** - (Required) The numeric ID of the organization to set the policy for.
 - **constraint** - (Required) The name of the Constraint the Policy is configuring, for example, `serviceuser.services`. Check out the complete list of available constraints.
-
- **version** - (Optional) Version of the Policy. Default version is 0.
 - **boolean_policy** - (Optional) A boolean policy is a constraint that is either enforced or not. Structure is documented below.
 - **list_policy** - (Optional) A policy that can define specific values that are allowed or denied for the given constraint. It can also be used to allow or deny all values. Structure is documented below.
 - **restore_policy** - (Optional) A restore policy is a constraint to restore the default policy. Structure is documented below.
-

The **boolean_policy** block supports:

- **enforced** - (Required) If true, then the Policy is enforced. If false, then any configuration is acceptable.

The **list_policy** block supports:

- **allow** or **deny** - (Optional) One or the other must be set.
- **suggested_values** - (Optional) The Google Cloud Console will try to default to a configuration that matches the value specified in this field.

The **allow** or **deny** blocks support:

- **all** - (Optional) The policy allows or denies all values.
- **values** - (Optional) The policy can define specific values that are allowed or denied.

The **restore_policy** block supports:

- **default** - (Required) May only be set to true. If set, then the default Policy is restored.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the organization policy. **etag** is used for optimistic concurrency control as a way to help prevent simultaneous updates of a policy from overwriting each other.
- **update_time** - (Computed) The timestamp in RFC3339 UTC "Zulu" format, accurate to nanoseconds, representing when the variable was last updated. Example: "2016-10-09T12:33:37.578138407Z".

» Import

Organization Policies can be imported using the `org_id` and the `constraint`, e.g.

```
$ terraform import google_organization_policy.services_policy 123456789:constraints/services_policy
```

» google_organization_iam_binding

Allows creation and management of a single binding within IAM policy for an existing Google Cloud Platform Organization.

Note: This resource **must not** be used in conjunction with `google_organization_iam_member` for the **same role** or they will fight over what your policy should be.

» Example Usage

```
resource "google_organization_iam_binding" "binding" {
  org_id = "123456789"
  role   = "roles/browser"

  members = [
    "user:jane@example.com",
  ]
}
```

» Argument Reference

The following arguments are supported:

- **org_id** - (Required) The numeric ID of the organization in which you want to create a custom role.
- **role** - (Required) The role that should be applied. Only one `google_organization_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **members** - (Required) A list of users that the role should apply to.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the organization's IAM policy.

» Import

IAM binding imports use space-delimited identifiers; first the resource in question and then the role. These bindings can be imported using the `org_id` and `role`, e.g.

```
$ terraform import google_organization_iam_binding.my_org "your-org-id roles/viewer"
```

» google_organization_iam_custom_role

Allows management of a customized Cloud IAM organization role. For more information see the official documentation and API.

» Example Usage

This snippet creates a customized IAM organization role.

```
resource "google_organization_iam_custom_role" "my-custom-role" {
  role_id      = "myCustomRole"
  org_id       = "123456789"
  title        = "My Custom Role"
  description   = "A description"
  permissions  = ["iam.roles.list", "iam.roles.create", "iam.roles.delete"]
}
```


» Argument Reference

The following arguments are supported:

- **role_id** - (Required) The role id to use for this role.
- **org_id** - (Required) The numeric ID of the organization in which you want to create a custom role.
- **title** - (Required) A human-readable title for the role.
- **permissions** (Required) The names of the permissions this role grants when bound in an IAM policy. At least one permission must be specified.
- **stage** - (Optional) The current launch stage of the role. Defaults to **GA**. List of possible stages is [here](#).
- **description** - (Optional) A human-readable description for the role.
- **deleted** - (Optional) The current deleted state of the role. Defaults to **false**.

» Import

Customized IAM organization role can be imported using their URI, e.g.

```
$ terraform import google_organization_iam_custom_role.my-custom-role organizations/12345678
```

» google_organization_iam_member

Allows creation and management of a single member for a single binding within the IAM policy for an existing Google Cloud Platform Organization.

Note: This resource **must not** be used in conjunction with `google_organization_iam_binding` for the **same role** or they will fight over what your policy should be.

» Example Usage

```
resource "google_organization_iam_member" "binding" {  
  org_id = "0123456789"  
  role   = "roles/editor"  
  member = "user:jane@example.com"  
}
```

» Argument Reference

The following arguments are supported:

- **org_id** - (Required) The numeric ID of the organization in which you want to create a custom role.
- **role** - (Required) The role that should be applied. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **member** - (Required) The user that the role should apply to.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the organization's IAM policy.

» Import

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account. This member resource can be imported using the `org_id`, `role`, and `account` e.g.

```
$ terraform import google_organization_iam_member.my_org "your-org-id roles/viewer foo@example.com"
```

» `google_organization_iam_policy`

Allows management of the entire IAM policy for an existing Google Cloud Platform Organization.

Warning: New organizations have several default policies which will, without extreme caution, be **overwritten** by use of this resource. The safest alternative is to use multiple `google_organization_iam_binding` resources. It is easy to use this resource to remove your own access to an organization, which will require a call to Google Support to have fixed, and can take multiple days to resolve. If you do use this resource, the best way to be sure that you are not making dangerous changes is to start by importing your existing policy, and examining the diff very closely.

Note: This resource **must not** be used in conjunction with `google_organization_iam_member` or `google_organization_iam_binding` or they will fight over what your policy should be.

» Example Usage

```
resource "google_organization_iam_policy" "policy" {
  org_id = "123456789"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}

data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}
```

» Argument Reference

The following arguments are supported:

- **org_id** - (Required) The numeric ID of the organization in which you want to create a custom role.
- **policy_data** - (Required) The `google_iam_policy` data source that represents the IAM policy that will be applied to the organization. This policy overrides any existing policy applied to the organization.

» Import

```
$ terraform import google_organization_iam_policy.my_org your-org-id
```

» google__project

Allows creation and management of a Google Cloud Platform project.

Projects created with this resource must be associated with an Organization. See the Organization documentation for more details.

The service account used to run Terraform when creating a `google_project` resource must have `roles/resourcemanager.projectCreator`. See the Access Control for Organizations Using IAM doc for more information.

Note that prior to 0.8.5, `google_project` functioned like a data source, meaning any project referenced by it had to be created and managed outside Terraform.

As of 0.8.5, `google_project` functions like any other Terraform resource, with Terraform creating and managing the project. To replicate the old behavior, either:

- Use the project ID directly in whatever is referencing the project, using the `google_project_iam_policy` to replace the old `policy_data` property.
- Use the import functionality to import your pre-existing project into Terraform, where it can be referenced and used just like always, keeping in mind that Terraform will attempt to undo any changes made outside Terraform.

It's important to note that any project resources that were added to your Terraform config prior to 0.8.5 will continue to function as they always have, and will not be managed by Terraform. Only newly added projects are affected.

» Example Usage

```
resource "google_project" "my_project" {
  name = "My Project"
  project_id = "your-project-id"
  org_id    = "1234567"
}
```

To create a project under a specific folder

```
resource "google_project" "my_project-in-a-folder" {
  name = "My Project"
  project_id = "your-project-id"
  folder_id = "${google_folder.department1.name}"
}
```

```
resource "google_folder" "department1" {
  display_name = "Department 1"
  parent      = "organizations/1234567"
}
```

To create a project with an App Engine app attached

```
resource "google_project" "my-app-engine-app" {
  name = "App Engine Project"
  project_id = "app-engine-project"
  org_id = "1234567"

  app_engine {
    location_id = "us-central"
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The display name of the project.
- **project_id** - (Required) The project ID. Changing this forces a new project to be created.
- **org_id** - (Optional) The numeric ID of the organization this project belongs to. Changing this forces a new project to be created. Only one of **org_id** or **folder_id** may be specified. If the **org_id** is specified then the project is created at the top level. Changing this forces the project to be migrated to the newly specified organization.
- **folder_id** - (Optional) The numeric ID of the folder this project should be created under. Only one of **org_id** or **folder_id** may be specified. If the **folder_id** is specified, then the project is created under the specified folder. Changing this forces the project to be migrated to the newly specified folder.
- **billing_account** - (Optional) The alphanumeric ID of the billing account this project belongs to. The user or service account performing this operation with Terraform must have Billing Account Administrator privileges (**roles/billing.admin**) in the organization. See Google Cloud Billing API Access Control for more details.
- **skip_delete** - (Optional) If true, the Terraform resource can be deleted without deleting the Project via the Google API.
- **policy_data** - (Deprecated) The IAM policy associated with the project. This argument is no longer supported, and will be removed in a future version of Terraform. It should be replaced with a **google_project_iam_policy** resource.
- **labels** - (Optional) A set of key/value label pairs to assign to the project.
- **auto_create_network** - (Optional) Create the 'default' network automatically. Default true. Note: this might be more accurately described as "Delete Default Network", since the network is created automatically then deleted before project creation returns, but we choose this name to match the GCP Console UI. Setting this field to false will enable the Compute Engine API which is required to delete the network.
- **app_engine** - (Optional) A block of configuration to enable an App Engine app. Setting this field will enable the App Engine Admin API, which is required to manage the app.

The **app_engine** block has the following configuration options:

- **location_id** - (Required) The location to serve the app from.

- **auth_domain** - (Optional) The domain to authenticate users with when using App Engine's User API.
- **serving_status** - (Optional) The serving status of the app. Note that this can't be updated at the moment.
- **feature_settings** - (Optional) A block of optional settings to configure specific App Engine features:
 - **split_health_checks** - (Optional) Set to false to use the legacy health check instead of the readiness and liveness checks.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **number** - The numeric identifier of the project.
- **policy_etag** - (Deprecated) The etag of the project's IAM policy, used to determine if the IAM policy has changed. Please use `google_project_iam_policy`'s `etag` property instead; future versions of Terraform will remove the `policy_etag` attribute
- **app_engine.0.name** - Unique name of the app, usually `apps/{PROJECT_ID}`
- **app_engine.0.url_dispatch_rule** - A list of dispatch rule blocks. Each block has a `domain`, `path`, and `service` field.
- **app_engine.0.code_bucket** - The GCS bucket code is being stored in for this app.
- **app_engine.0.default_hostname** - The default hostname for this app.
- **app_engine.0.default_bucket** - The GCS bucket content is being stored in for this app.
- **app_engine.0.gcr_domain** - The GCR domain used for storing managed Docker images for this app.

» Import

Projects can be imported using the `project_id`, e.g.

```
$ terraform import google_project.my_project your-project-id
```

» IAM policy for projects

Three different resources help you manage your IAM policy for a project. Each of these resources serves a different use case:

- `google_project_iam_policy`: Authoritative. Sets the IAM policy for the project and replaces any existing policy already attached.
- `google_project_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the project are preserved.
- `google_project_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the project are preserved.

Note: `google_project_iam_policy` **cannot** be used in conjunction with `google_project_iam_binding` and `google_project_iam_member` or they will fight over what your policy should be.

Note: `google_project_iam_binding` resources **can be** used in conjunction with `google_project_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_project_iam_policy`

Be careful! You can accidentally lock yourself out of your project using this resource. Proceed with caution.

```
resource "google_project_iam_policy" "project" {
  project      = "your-project-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}

data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}
```

» `google_project_iam_binding`

Note: If `role` is set to `roles/owner` and you don't specify a user or service account you have access to in `members`, you can lock yourself out of your project.

```
resource "google_project_iam_binding" "project" {
  project = "your-project-id"
  role    = "roles/editor"
```

```

members = [
    "user:jane@example.com",
]
}

```

» google_project_iam_member

```

resource "google_project_iam_member" "project" {
  project = "your-project-id"
  role    = "roles/editor"
  member  = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_project_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_project_iam_policy`) The `google_iam_policy` data source that represents the IAM policy that will be applied to the project. The policy will be merged with any existing policy applied to the project.

Changing this updates the policy.

Deleting this removes the policy, but leaves the original project policy intact. If there are overlapping **binding** entries between the original project policy and the data source policy, they will be removed.

- **project** - (Optional) The project ID. If not specified, uses the ID of the project configured with the provider.
- **authoritative** - (DEPRECATED) (Optional, only for `google_project_iam_policy`)
A boolean value indicating if this policy should overwrite any existing IAM policy on the project. When set to true, **any policies not in your config file will be removed**. This can **lock you out** of your project until an Organization Administrator grants you access again, so please exercise caution. If this argument is `true` and you want to delete the resource, you must set the `disable_project` argument to `true`, acknowledging that the project will be inaccessible to anyone but the Organization Admins, as it will no longer have an IAM policy. Rather than using this, you should use `google_project_iam_binding` and `google_project_iam_member`.
- **disable_project** - (DEPRECATED) (Optional, only for `google_project_iam_policy`)
A boolean value that must be set to `true` if you want to delete a `google_project_iam_policy` that is authoritative.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the project's IAM policy.
- **restore_policy** - (DEPRECATED) (Computed, only for `google_project_iam_policy`)
The IAM policy that will be restored when a non-authoritative policy resource is deleted.

» Import

IAM resources can be imported using the `project_id`, role, and account.

```
$ terraform import google_project_iam_policy.my_project your-project-id
```

```
$ terraform import google_project_iam_binding.my_project "your-project-id roles/viewer"
```

```
$ terraform import google_project_iam_member.my_project "your-project-id roles/viewer foo@example.com"
```

» IAM policy for projects

Three different resources help you manage your IAM policy for a project. Each of these resources serves a different use case:

- `google_project_iam_policy`: Authoritative. Sets the IAM policy for the project and replaces any existing policy already attached.
- `google_project_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the project are preserved.
- `google_project_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the project are preserved.

Note: `google_project_iam_policy` **cannot** be used in conjunction with `google_project_iam_binding` and `google_project_iam_member` or they will fight over what your policy should be.

Note: `google_project_iam_binding` resources **can be** used in conjunction with `google_project_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_project_iam_policy`

Be careful! You can accidentally lock yourself out of your project using this resource. Proceed with caution.

```
resource "google_project_iam_policy" "project" {
  project      = "your-project-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}

data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}
```

» `google_project_iam_binding`

Note: If `role` is set to `roles/owner` and you don't specify a user or service account you have access to in `members`, you can lock yourself out of your project.

```
resource "google_project_iam_binding" "project" {
  project = "your-project-id"
  role    = "roles/editor"
```

```

members = [
    "user:jane@example.com",
]
}

```

» google_project_iam_member

```

resource "google_project_iam_member" "project" {
  project = "your-project-id"
  role    = "roles/editor"
  member  = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_project_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_project_iam_policy`) The `google_iam_policy` data source that represents the IAM policy that will be applied to the project. The policy will be merged with any existing policy applied to the project.

Changing this updates the policy.

Deleting this removes the policy, but leaves the original project policy intact. If there are overlapping **binding** entries between the original project policy and the data source policy, they will be removed.

- **project** - (Optional) The project ID. If not specified, uses the ID of the project configured with the provider.
- **authoritative** - (DEPRECATED) (Optional, only for `google_project_iam_policy`)
A boolean value indicating if this policy should overwrite any existing IAM policy on the project. When set to true, **any policies not in your config file will be removed**. This can **lock you out** of your project until an Organization Administrator grants you access again, so please exercise caution. If this argument is `true` and you want to delete the resource, you must set the `disable_project` argument to `true`, acknowledging that the project will be inaccessible to anyone but the Organization Admins, as it will no longer have an IAM policy. Rather than using this, you should use `google_project_iam_binding` and `google_project_iam_member`.
- **disable_project** - (DEPRECATED) (Optional, only for `google_project_iam_policy`)
A boolean value that must be set to `true` if you want to delete a `google_project_iam_policy` that is authoritative.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the project's IAM policy.
- **restore_policy** - (DEPRECATED) (Computed, only for `google_project_iam_policy`)
The IAM policy that will be restored when a non-authoritative policy resource is deleted.

» Import

IAM resources can be imported using the `project_id`, role, and account.

```
$ terraform import google_project_iam_policy.my_project your-project-id
```

```
$ terraform import google_project_iam_binding.my_project "your-project-id roles/viewer"
```

```
$ terraform import google_project_iam_member.my_project "your-project-id roles/viewer foo@example.com"
```

» IAM policy for projects

Three different resources help you manage your IAM policy for a project. Each of these resources serves a different use case:

- `google_project_iam_policy`: Authoritative. Sets the IAM policy for the project and replaces any existing policy already attached.
- `google_project_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the project are preserved.
- `google_project_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the project are preserved.

Note: `google_project_iam_policy` **cannot** be used in conjunction with `google_project_iam_binding` and `google_project_iam_member` or they will fight over what your policy should be.

Note: `google_project_iam_binding` resources **can be** used in conjunction with `google_project_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_project_iam_policy`

Be careful! You can accidentally lock yourself out of your project using this resource. Proceed with caution.

```
resource "google_project_iam_policy" "project" {
  project      = "your-project-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}

data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}
```

» `google_project_iam_binding`

Note: If `role` is set to `roles/owner` and you don't specify a user or service account you have access to in `members`, you can lock yourself out of your project.

```
resource "google_project_iam_binding" "project" {
  project = "your-project-id"
  role    = "roles/editor"
```

```

members = [
    "user:jane@example.com",
]
}

```

» google_project_iam_member

```

resource "google_project_iam_member" "project" {
  project = "your-project-id"
  role    = "roles/editor"
  member  = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_project_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_project_iam_policy`) The `google_iam_policy` data source that represents the IAM policy that will be applied to the project. The policy will be merged with any existing policy applied to the project.

Changing this updates the policy.

Deleting this removes the policy, but leaves the original project policy intact. If there are overlapping **binding** entries between the original project policy and the data source policy, they will be removed.

- **project** - (Optional) The project ID. If not specified, uses the ID of the project configured with the provider.
- **authoritative** - (DEPRECATED) (Optional, only for `google_project_iam_policy`)
A boolean value indicating if this policy should overwrite any existing IAM policy on the project. When set to true, **any policies not in your config file will be removed**. This can **lock you out** of your project until an Organization Administrator grants you access again, so please exercise caution. If this argument is `true` and you want to delete the resource, you must set the `disable_project` argument to `true`, acknowledging that the project will be inaccessible to anyone but the Organization Admins, as it will no longer have an IAM policy. Rather than using this, you should use `google_project_iam_binding` and `google_project_iam_member`.
- **disable_project** - (DEPRECATED) (Optional, only for `google_project_iam_policy`)
A boolean value that must be set to `true` if you want to delete a `google_project_iam_policy` that is authoritative.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the project's IAM policy.
- **restore_policy** - (DEPRECATED) (Computed, only for `google_project_iam_policy`)
The IAM policy that will be restored when a non-authoritative policy resource is deleted.

» Import

IAM resources can be imported using the `project_id`, role, and account.

```
$ terraform import google_project_iam_policy.my_project your-project-id
```

```
$ terraform import google_project_iam_binding.my_project "your-project-id roles/viewer"
```

```
$ terraform import google_project_iam_member.my_project "your-project-id roles/viewer foo@example.com"
```

» `google_project_iam_custom_role`

Allows management of a customized Cloud IAM project role. For more information see the official documentation and API.

» Example Usage

This snippet creates a customized IAM role.

```
resource "google_project_iam_custom_role" "my-custom-role" {
  role_id      = "myCustomRole"
  title        = "My Custom Role"
  description  = "A description"
  permissions  = ["iam.roles.list", "iam.roles.create", "iam.roles.delete"]
}
```

» Argument Reference

The following arguments are supported:

- **role_id** - (Required) The role id to use for this role.
- **title** - (Required) A human-readable title for the role.
- **permissions** (Required) The names of the permissions this role grants when bound in an IAM policy. At least one permission must be specified.
- **project** - (Optional) The project that the service account will be created in. Defaults to the provider project configuration.
- **stage** - (Optional) The current launch stage of the role. Defaults to **GA**. List of possible stages is [here](#).
- **description** - (Optional) A human-readable description for the role.
- **deleted** - (Optional) The current deleted state of the role. Defaults to **false**.

» Import

Customized IAM project role can be imported using their URI, e.g.

```
$ terraform import google_project_iam_custom_role.my-custom-role projects/my-project/roles/n
```

» google__project__organization__policy

Allows management of Organization policies for a Google Project. For more information see the official documentation and API.

» Example Usage

To set policy with a boolean constraint:

```
resource "google_project_organization_policy" "serial_port_policy" {
  project      = "your-project-id"
  constraint   = "compute.disableSerialPortAccess"

  boolean_policy {
    enforced = true
  }
}
```

To set a policy with a list constraint:

```
resource "google_project_organization_policy" "services_policy" {
  project      = "your-project-id"
  constraint   = "serviceuser.services"

  list_policy {
    allow {
      all = true
    }
  }
}
```

Or to deny some services, use the following instead:

```
resource "google_project_organization_policy" "services_policy" {
  project      = "your-project-id"
  constraint   = "serviceuser.services"

  list_policy {
    suggested_values = "compute.googleapis.com"

    deny {
      values = ["cloudresourcemanager.googleapis.com"]
    }
  }
}
```

To restore the default project organization policy, use the following instead:

```
resource "google_project_organization_policy" "services_policy" {
  project      = "your-project-id"
  constraint   = "serviceuser.services"

  restore_policy {
    default = true
  }
}
```

```
}  
}
```

» Argument Reference

The following arguments are supported:

- **project** - (Required) The project id of the project to set the policy for.
 - **constraint** - (Required) The name of the Constraint the Policy is configuring, for example, `serviceuser.services`. Check out the complete list of available constraints.
-
- **version** - (Optional) Version of the Policy. Default version is 0.
 - **boolean_policy** - (Optional) A boolean policy is a constraint that is either enforced or not. Structure is documented below.
 - **list_policy** - (Optional) A policy that can define specific values that are allowed or denied for the given constraint. It can also be used to allow or deny all values. Structure is documented below.
 - **restore_policy** - (Optional) A restore policy is a constraint to restore the default policy. Structure is documented below.
-

The **boolean_policy** block supports:

- **enforced** - (Required) If true, then the Policy is enforced. If false, then any configuration is acceptable.

The **list_policy** block supports:

- **allow** or **deny** - (Optional) One or the other must be set.
- **suggested_values** - (Optional) The Google Cloud Console will try to default to a configuration that matches the value specified in this field.

The **allow** or **deny** blocks support:

- **all** - (Optional) The policy allows or denies all values.
- **values** - (Optional) The policy can define specific values that are allowed or denied.

The **restore_policy** block supports:

- **default** - (Required) May only be set to true. If set, then the default Policy is restored.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the organization policy. **etag** is used for optimistic concurrency control as a way to help prevent simultaneous updates of a policy from overwriting each other.
- **update_time** - (Computed) The timestamp in RFC3339 UTC "Zulu" format, accurate to nanoseconds, representing when the variable was last updated. Example: "2016-10-09T12:33:37.578138407Z".

» google_project_service

Allows management of a single API service for an existing Google Cloud Platform project.

For a list of services available, visit the API library page or run `gcloud services list`.

Note: This resource *must not* be used in conjunction with `google_project_services` or they will fight over which services should be enabled.

» Example Usage

```
resource "google_project_service" "project" {  
  project = "your-project-id"  
  service = "iam.googleapis.com"  
}
```

» Argument Reference

The following arguments are supported:

- **service** - (Required) The service to enable.
- **project** - (Optional) The project ID. If not provided, the provider project is used.
- **disable_on_destroy** - (Optional) If true, disable the service when the terraform resource is destroyed. Defaults to true. May be useful in the event that a project is long-lived but the infrastructure running in that project changes frequently.

» Import

Project services can be imported using the `project_id` and `service`, e.g.

```
$ terraform import google_project_service.my_project your-project-id/iam.googleapis.com
```

» google__project__services

Allows management of enabled API services for an existing Google Cloud Platform project. Services in an existing project that are not defined in the config will be removed.

For a list of services available, visit the [API library page](#) or run `gcloud services list`.

Note: This resource attempts to be the authoritative source on *all* enabled APIs, which often leads to conflicts when certain actions enable other APIs. If you do not need to ensure that *exclusively* a particular set of APIs are enabled, you should most likely use the `google_project_service` resource, one resource per API.

» Example Usage

```
resource "google_project_services" "project" {
  project = "your-project-id"
  services = ["iam.googleapis.com", "cloudresourcemanager.googleapis.com"]
}
```

» Argument Reference

The following arguments are supported:

- `project` - (Required) The project ID. Changing this forces Terraform to attempt to disable all previously managed API services in the previous project.
- `services` - (Required) The list of services that are enabled. Supports update.

» Import

Project services can be imported using the `project_id`, e.g.

```
$ terraform import google_project_services.my_project your-project-id
```

» google__project__usage__export__bucket

Sets up a usage export bucket for a particular project. A usage export bucket is a pre-configured GCS bucket which is set up to receive daily and monthly reports of the GCE resources used.

For more information see the Docs and for further details, the API Documentation.

» Example Usage

```
resource "google_project_usage_export_bucket" "export" {  
  project      = "foo"  
  bucket_name  = "bar"  
}
```

» Argument Reference

- **project:** (Required) The project to set the export bucket on.
- **bucket_name:** (Required) The bucket to store reports in.
- **prefix:** (Optional) A prefix for the reports, for instance, the project name.

» Note

You should specify only one of these per project. If there are two or more they will fight over which bucket the reports should be stored in. It is safe to have multiple resources with the same backing bucket.

» google__resource__manager__lien

A Lien represents an encumbrance on the actions that can be performed on a resource.

» Example Usage

```
resource "random_id" "r" {  
  byte_length = 8  
}  
  
resource "google_project" "project" {  
  project_id = "project-${random_id.r.hex}"  
}
```

```

    name = "A very important project!"
  }

  resource "google_resource_manager_lien" "lien" {
    parent = "projects/${google_project.project.number}"
    restrictions = ["resourcemanager.projects.delete"]
    origin = "machine-readable-explanation"
    reason = "This project is very important to me!"
  }

```

» Argument Reference

The following arguments are supported:

- **reason** - (Required) Concise user-visible strings indicating why an action cannot be performed on a resource. Maximum length of 200 characters.
- **origin** - (Required) A stable, user-visible/meaningful string identifying the origin of the Lien, intended to be inspected programmatically. Maximum length of 200 characters.
- **parent** - (Required) A reference to the resource this Lien is attached to. The server will validate the parent against those for which Liens are supported. Since a variety of objects can have Liens against them, you must provide the type prefix (e.g. "projects/my-project-name").
- **restrictions** - (Required) The types of operations which should be blocked as a result of this Lien. Each value should correspond to an IAM permission. The server will validate the permissions against those for which Liens are supported. An empty list is meaningless and will be rejected. e.g. ["resourcemanager.projects.delete"]

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **name** - A system-generated unique identifier for this Lien.
- **create_time** - Time of creation

» Import

Lien can be imported using any of these accepted formats:

```
$ terraform import google_resource_manager_lien.default {{parent}}/{{name}}
```

» **google__service__account**

Allows management of a Google Cloud Platform service account

» **Example Usage**

This snippet creates a service account, then gives it objectViewer permission in a project.

```
resource "google_service_account" "object_viewer" {  
  account_id = "object-viewer"  
  display_name = "Object viewer"  
}
```

» **Argument Reference**

The following arguments are supported:

- **account_id** - (Required) The service account ID. Changing this forces a new service account to be created.
- **display_name** - (Optional) The display name for the service account. Can be updated without creating a new resource.
- **project** - (Optional) The ID of the project that the service account will be created in. Defaults to the provider project configuration.
- **policy_data** - (DEPRECATED, Optional) The `google_iam_policy` data source that represents the IAM policy that will be applied to the service account. The policy will be merged with any existing policy.

This attribute has been deprecated. Use the `google_service_account_iam_*` resources instead.

Deleting this removes the policy declared in Terraform. Any policy bindings associated with the project before Terraform was used are not deleted.

» **Attributes Reference**

In addition to the arguments listed above, the following computed attributes are exported:

- **email** - The e-mail address of the service account. This value should be referenced from any `google_iam_policy` data sources that would grant the service account privileges.
- **name** - The fully-qualified name of the service account.
- **unique_id** - The unique id of the service account.

» Import

Service accounts can be imported using their URI, e.g.

```
$ terraform import google_service_account.my_sa projects/my-project/serviceAccounts/my-sa@my
```

» IAM policy for service account

When managing IAM roles, you can treat a service account either as a resource or as an identity. This resource is to add iam policy bindings to a service account resource to configure permissions for who can edit the service account. To configure permissions for a service account to act as an identity that can manage other GCP resources, use the `google_project_iam` set of resources.

Three different resources help you manage your IAM policy for a service account. Each of these resources serves a different use case:

- **google_service_account_iam_policy**: Authoritative. Sets the IAM policy for the service account and replaces any existing policy already attached.
- **google_service_account_iam_binding**: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the service account are preserved.
- **google_service_account_iam_member**: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the service account are preserved.

Note: `google_service_account_iam_policy` **cannot** be used in conjunction with `google_service_account_iam_binding` and `google_service_account_iam_member` or they will fight over what your policy should be.

Note: `google_service_account_iam_binding` resources **can be** used in conjunction with `google_service_account_iam_member` resources **only if** they do not grant privilege to the same role.

» google_service_account_iam_policy

```
data "google_iam_policy" "admin" {
```



```

binding {
  role = "roles/editor"

  members = [
    "user:jane@example.com",
  ]
}

resource "google_service_account_iam_policy" "admin-account-iam" {
  service_account_id = "your-service-account-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}

```

» google_service_account_iam_binding

```

resource "google_service_account_iam_binding" "admin-account-iam" {
  service_account_id = "your-service-account-id"
  role                = "roles/editor"

  members = [
    "user:jane@example.com",
  ]
}

```

» google_service_account_iam_member

```

resource "google_service_account_iam_member" "admin-account-iam" {
  service_account_id = "your-service-account-id"
  role                = "roles/editor"
  member              = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **service_account_id** - (Required) The service account id to apply policy to.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.

- **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, alice@gmail.com or joe@example.com.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, my-other-app@appspot.gserviceaccount.com.
 - **group:{emailid}**: An email address that represents a Google group. For example, admins@example.com.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Only one `google_service_account_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
 - **policy_data** - (Required only by `google_service_account_iam_policy`) The policy data generated by a `google_iam_policy` data source.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the service account IAM policy.

» Import

Service account IAM resources can be imported using the project, service account email, role and member.

```
$ terraform import google_service_account_iam_policy.admin-account-iam projects/{your-project-id}
```

```
$ terraform import google_service_account_iam_binding.admin-account-iam "projects/{your-project-id}/roles/{role-name}"
```

```
$ terraform import google_service_account_iam_member.admin-account-iam "projects/{your-project-id}/members/{member-email}"
```

» IAM policy for service account

When managing IAM roles, you can treat a service account either as a resource or as an identity. This resource is to add iam policy bindings to a service account resource to configure permissions for who can edit the service account.

To configure permissions for a service account to act as an identity that can manage other GCP resources, use the `google_project_iam` set of resources.

Three different resources help you manage your IAM policy for a service account. Each of these resources serves a different use case:

- `google_service_account_iam_policy`: Authoritative. Sets the IAM policy for the service account and replaces any existing policy already attached.
- `google_service_account_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the service account are preserved.
- `google_service_account_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the service account are preserved.

Note: `google_service_account_iam_policy` **cannot** be used in conjunction with `google_service_account_iam_binding` and `google_service_account_iam_member` or they will fight over what your policy should be.

Note: `google_service_account_iam_binding` resources **can be** used in conjunction with `google_service_account_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_service_account_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_service_account_iam_policy" "admin-account-iam" {
  service_account_id = "your-service-account-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» `google_service_account_iam_binding`

```
resource "google_service_account_iam_binding" "admin-account-iam" {
  service_account_id = "your-service-account-id"
  role               = "roles/editor"
}
```

```

members = [
    "user:jane@example.com",
]
}

```

» google_service_account_iam_member

```

resource "google_service_account_iam_member" "admin-account-iam" {
  service_account_id = "your-service-account-id"
  role                = "roles/editor"
  member              = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **service_account_id** - (Required) The service account id to apply policy to.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_service_account_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_service_account_iam_policy`) The policy data generated by a `google_iam_policy` data source.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `etag` - (Computed) The etag of the service account IAM policy.

» Import

Service account IAM resources can be imported using the project, service account email, role and member.

```
$ terraform import google_service_account_iam_policy.admin-account-iam projects/{your-project-id}
```

```
$ terraform import google_service_account_iam_binding.admin-account-iam "projects/{your-project-id}/roles/{role-id}"
```

```
$ terraform import google_service_account_iam_member.admin-account-iam "projects/{your-project-id}/roles/{role-id}/members/{member-id}"
```

» IAM policy for service account

When managing IAM roles, you can treat a service account either as a resource or as an identity. This resource is to add iam policy bindings to a service account resource to configure permissions for who can edit the service account. To configure permissions for a service account to act as an identity that can manage other GCP resources, use the `google_project_iam` set of resources.

Three different resources help you manage your IAM policy for a service account. Each of these resources serves a different use case:

- `google_service_account_iam_policy`: Authoritative. Sets the IAM policy for the service account and replaces any existing policy already attached.
- `google_service_account_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the service account are preserved.
- `google_service_account_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the service account are preserved.

Note: `google_service_account_iam_policy` **cannot** be used in conjunction with `google_service_account_iam_binding` and `google_service_account_iam_member` or they will fight over what your policy should be.

Note: `google_service_account_iam_binding` resources **can be** used in conjunction with `google_service_account_iam_member` resources **only if** they do not grant privilege to the same role.

» google_service_account_iam_policy

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_service_account_iam_policy" "admin-account-iam" {
  service_account_id = "your-service-account-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» google_service_account_iam_binding

```
resource "google_service_account_iam_binding" "admin-account-iam" {
  service_account_id = "your-service-account-id"
  role                = "roles/editor"

  members = [
    "user:jane@example.com",
  ]
}
```

» google_service_account_iam_member

```
resource "google_service_account_iam_member" "admin-account-iam" {
  service_account_id = "your-service-account-id"
  role                = "roles/editor"
  member              = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- `service_account_id` - (Required) The service account id to apply policy to.

- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, alice@gmail.com or joe@example.com.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, my-other-app@appspot.gserviceaccount.com.
 - **group:{emailid}**: An email address that represents a Google group. For example, admins@example.com.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Only one **google_service_account_iam_binding** can be used per role. Note that custom roles must be of the format **[projects|organizations]/{parent-name}/roles/{role-name}**.
- **policy_data** - (Required only by **google_service_account_iam_policy**) The policy data generated by a **google_iam_policy** data source.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the service account IAM policy.

» Import

Service account IAM resources can be imported using the project, service account email, role and member.

```
$ terraform import google_service_account_iam_policy.admin-account-iam projects/{your-project-id}
```

```
$ terraform import google_service_account_iam_binding.admin-account-iam "projects/{your-project-id}/roles/{role-name}"
```

```
$ terraform import google_service_account_iam_member.admin-account-iam "projects/{your-project-id}/roles/{role-name}:{member-email}"
```

» google__service__account__key

Creates and manages service account key-pairs, which allow the user to establish identity of a service account outside of GCP. For more information, see the official documentation and API.

» Example Usage, creating a new Key Pair

```
resource "google_service_account" "myaccount" {
  account_id = "myaccount"
  display_name = "My Service Account"
}

resource "google_service_account_key" "mykey" {
  service_account_id = "${google_service_account.myaccount.name}"
  public_key_type = "TYPE_X509_PEM_FILE"
}
```

» Example Usage, save key in Kubernetes secret

```
resource "google_service_account" "myaccount" {
  account_id = "myaccount"
  display_name = "My Service Account"
}

resource "google_service_account_key" "mykey" {
  service_account_id = "${google_service_account.myaccount.name}"
}

resource "kubernetes_secret" "google-application-credentials" {
  metadata {
    name = "google-application-credentials"
  }
  data {
    credentials.json = "${base64decode(google_service_account_key.mykey.private_key)}"
  }
}
```

» Create new Key Pair, encrypting the private key with a PGP Key

```
resource "google_service_account" "myaccount" {
```



```

    account_id = "myaccount"
    display_name = "My Service Account"
}

resource "google_service_account_key" "mykey" {
  service_account_id = "${google_service_account.myaccount.name}"
  pgp_key = "keybase:keybaseusername"
  public_key_type = "TYPE_X509_PEM_FILE"
}

```

» Argument Reference

The following arguments are supported:

- **service_account_id** - (Required) The Service account id of the Key Pair. This can be a string in the format `{ACCOUNT}` or `projects/{PROJECT_ID}/serviceAccounts/{ACCOUNT}`, where `{ACCOUNT}` is the email address or unique id of the service account. If the `{ACCOUNT}` syntax is used, the project will be inferred from the account.
- **key_algorithm** - (Optional) The algorithm used to generate the key. `KEY_ALG_RSA_2048` is the default algorithm. Valid values are listed at `ServiceAccountPrivateKeyType` (only used on create)
- **public_key_type** (Optional) The output format of the public key requested. `X509_PEM` is the default output format.
- **private_key_type** (Optional) The output format of the private key. `TYPE_GOOGLE_CREDENTIALS_FILE` is the default output format.
- **pgp_key** - (Optional) An optional PGP key to encrypt the resulting private key material. Only used when creating or importing a new key pair. May either be a base64-encoded public key or a `keybase:keybaseusername` string for looking up in Vault.

NOTE: a PGP key is not required, however it is strongly encouraged. Without a PGP key, the private key material will be stored in state unencrypted.

» Attributes Reference

The following attributes are exported in addition to the arguments listed above:

- **name** - The name used for this key pair
- **public_key** - The public key, base64 encoded
- **private_key** - The private key in JSON format, base64 encoded. This is what you normally get as a file when creating service account keys through

the CLI or web console. This is only populated when creating a new key, and when no `pgp_key` is provided.

- `private_key_encrypted` – The private key material, base 64 encoded and encrypted with the given `pgp_key`. This is only populated when creating a new key and `pgp_key` is supplied
- `private_key_fingerprint` - The MD5 public key fingerprint for the encrypted private key. This is only populated when creating a new key and `pgp_key` is supplied
- `valid_after` - The key can be used after this timestamp. A timestamp in RFC3339 UTC "Zulu" format, accurate to nanoseconds. Example: "2014-10-02T15:01:23.045123456Z".
- `valid_before` - The key can be used before this timestamp. A timestamp in RFC3339 UTC "Zulu" format, accurate to nanoseconds. Example: "2014-10-02T15:01:23.045123456Z".

» `google_compute_address`

Represents an Address resource.

Each virtual machine instance has an ephemeral internal IP address and, optionally, an external IP address. To communicate between instances on the same network, you can use an instance's internal IP address. To communicate with the Internet and instances outside of the same network, you must specify the instance's external IP address.

Internal IP addresses are ephemeral and only belong to an instance for the lifetime of the instance; if the instance is deleted and recreated, the instance is assigned a new internal IP address, either by Compute Engine or by you. External IP addresses can be either ephemeral or static.

To get more information about Address, see:

- API documentation
- How-to Guides
 - Reserving a Static External IP Address
 - Reserving a Static Internal IP Address

» Example Usage

```
resource "google_compute_address" "default" {  
  name = "my-address"  
}
```

```

resource "google_compute_network" "default" {
  name = "my-network"
}

resource "google_compute_subnetwork" "default" {
  name          = "my-subnet"
  ip_cidr_range = "10.0.0.0/16"
  region        = "us-central1"
  network       = "${google_compute_network.default.self_link}"
}

resource "google_compute_address" "internal_with_subnet_and_address" {
  name          = "my-internal-address"
  subnetwork    = "${google_compute_subnetwork.default.self_link}"
  address_type  = "INTERNAL"
  address       = "10.0.42.42"
  region        = "us-central1"
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
- **address** - (Optional) The static external IP address represented by this resource. Only IPv4 is supported. An address may only be specified for INTERNAL address types. The IP address must be inside the specified subnetwork, if any.
- **address_type** - (Optional) The type of address to reserve, either INTERNAL or EXTERNAL. If unspecified, defaults to EXTERNAL.
- **description** - (Optional) An optional description of this resource.
- **network_tier** - (Optional) The networking tier used for configuring this address. This field can take the following values: PREMIUM or STANDARD. If this field is not specified, it is assumed to be PREMIUM.
- **subnetwork** - (Optional) The URL of the subnetwork in which to reserve the address. If an IP address is specified, it must be within the subnet-

work's IP range. This field can only be used with INTERNAL type with GCE_ENDPOINT/DNS_RESOLVER purposes.

- **labels** - (Optional) Labels to apply to this address. A list of key->value pairs.
- **region** - (Optional) The Region in which the created address should reside. If it is not provided, the provider region is used.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **users** - The URLs of the resources that are using this address.
- **label_fingerprint** - The fingerprint used for optimistic locking of this resource. Used internally during updates.
- **self_link** - The URI of the created resource.
- **address** - The IP of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

Address can be imported using any of these accepted formats:

```
$ terraform import google_compute_address.default projects/{{project}}/regions/{{region}}/addresses/{{name}}
$ terraform import google_compute_address.default {{project}}/{{region}}/{{name}}
$ terraform import google_compute_address.default {{name}}
```

» google__compute__autoscaler

Represents an Autoscaler resource.

Autoscalers allow you to automatically scale virtual machine instances in managed instance groups according to an autoscaling policy that you define.

To get more information about Autoscaler, see:

- API documentation
- How-to Guides
 - Autoscaling Groups of Instances

» Example Usage

```
resource "google_compute_instance_template" "foobar" {
  name          = "foobar"
  machine_type   = "n1-standard-1"
  can_ip_forward = false

  tags = ["foo", "bar"]

  disk {
    source_image = "debian-cloud/debian-8"
  }

  network_interface {
    network = "default"
  }

  metadata {
    foo = "bar"
  }

  service_account {
    scopes = ["userinfo-email", "compute-ro", "storage-ro"]
  }
}

resource "google_compute_target_pool" "foobar" {
  name = "foobar"
}

resource "google_compute_instance_group_manager" "foobar" {
  name = "foobar"
  zone = "us-central1-f"
```

```

    instance_template = "${google_compute_instance_template.foobar.self_link}"
    target_pools      = ["${google_compute_target_pool.foobar.self_link}"]
    base_instance_name = "foobar"
  }

  resource "google_compute_autoscaler" "foobar" {
    name     = "scaler"
    zone     = "us-central1-f"
    target    = "${google_compute_instance_group_manager.foobar.self_link}"

    autoscaling_policy = {
      max_replicas    = 5
      min_replicas    = 1
      cooldown_period = 60

      cpu_utilization {
        target = 0.5
      }
    }
  }
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. The name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
- **autoscaling_policy** - (Required) The configuration parameters for the autoscaling algorithm. You can define one or more of the policies for an autoscaler: `CpuUtilization`, `CustomMetricUtilizations`, and `LoadBalancingUtilization`. If none of these are specified, the default will be to autoscale based on `CpuUtilization` to 0.6 or 60%. Structure is documented below.
- **target** - (Required) URL of the managed instance group that this autoscaler will scale.

The `autoscaling_policy` block supports:

- **min_replicas** - (Required) The minimum number of replicas that the autoscaler can scale down to. This cannot be less than 0. If not provided, autoscaler will choose a default value depending on maximum number of instances allowed.

- **max_replicas** - (Required) The maximum number of instances that the autoscaler can scale up to. This is required when creating or updating an autoscaler. The maximum number of replicas should not be lower than minimal number of replicas.
- **cooldown_period** - (Optional) The number of seconds that the autoscaler should wait before it starts collecting information from a new instance. This prevents the autoscaler from collecting information when the instance is initializing, during which the collected usage would not be reliable. The default time autoscaler waits is 60 seconds. Virtual machine initialization times might vary because of numerous factors. We recommend that you test how long an instance may take to initialize. To do this, create an instance and time the startup process.
- **cpu_utilization** - (Optional) Defines the CPU utilization policy that allows the autoscaler to scale based on the average CPU utilization of a managed instance group. Structure is documented below.
- **metric** - (Optional) Defines the CPU utilization policy that allows the autoscaler to scale based on the average CPU utilization of a managed instance group. Structure is documented below.
- **load_balancing_utilization** - (Optional) Configuration parameters of autoscaling based on a load balancer. Structure is documented below.

The **cpu_utilization** block supports:

- **target** - (Required) The target CPU utilization that the autoscaler should maintain. Must be a float value in the range (0, 1]. If not specified, the default is 0.6. If the CPU level is below the target utilization, the autoscaler scales down the number of instances until it reaches the minimum number of instances you specified or until the average CPU of your instances reaches the target utilization. If the average CPU is above the target utilization, the autoscaler scales up until it reaches the maximum number of instances you specified or until the average utilization reaches the target utilization.

The **metric** block supports:

- **name** - (Required) The identifier (type) of the Stackdriver Monitoring metric. The metric cannot have negative values. The metric must have a value type of INT64 or DOUBLE.
- **target** - (Required) The target value of the metric that autoscaler should maintain. This must be a positive value. A utilization metric scales number of virtual machines handling requests to increase or decrease proportionally to the metric. For example, a good metric to use as a utilization-Target is www.googleapis.com/compute/instance/network/received_bytes_count. The autoscaler will work to keep this value constant for each of the instances.

- **type** - (Required) Defines how target utilization value is expressed for a Stackdriver Monitoring metric. Either GAUGE, DELTA_PER_SECOND, or DELTA_PER_MINUTE.

The `load_balancing_utilization` block supports:

- **target** - (Required) Fraction of backend capacity utilization (set in HTTP(s) load balancing configuration) that autoscaler should maintain. Must be a positive float value. If not defined, the default is 0.8.

-
- **description** - (Optional) An optional description of this resource.
 - **zone** - (Optional) URL of the zone where the instance group resides.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

Autoscaler can be imported using any of these accepted formats:

```
$ terraform import google_compute_autoscaler.default projects/{{project}}/zones/{{zone}}/aut
$ terraform import google_compute_autoscaler.default {{zone}}/{{name}}
$ terraform import google_compute_autoscaler.default {{project}}/{{zone}}/{{name}}
$ terraform import google_compute_autoscaler.default {{name}}
```


» `google_compute_backend_bucket`

Backend buckets allow you to use Google Cloud Storage buckets with HTTP(S) load balancing.

An HTTP(S) load balancer can direct traffic to specified URLs to a backend bucket rather than a backend service. It can send requests for static content to a Cloud Storage bucket and requests for dynamic content a virtual machine instance.

To get more information about BackendBucket, see:

- API documentation
- How-to Guides
 - Using a Cloud Storage bucket as a load balancer backend

» Example Usage

```
resource "google_compute_backend_bucket" "image_backend" {
  name          = "image-backend-bucket"
  description    = "Contains beautiful images"
  bucket_name    = "${google_storage_bucket.image_bucket.name}"
  enable_cdn     = true
}

resource "google_storage_bucket" "image_bucket" {
  name        = "image-store-bucket"
  location    = "EU"
}
```

» Argument Reference

The following arguments are supported:

- `bucket_name` - (Required) Cloud Storage bucket name.
- `name` - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.

- **description** - (Optional) An optional textual description of the resource; provided by the client when the resource is created.
- **enable_cdn** - (Optional) If true, enable Cloud CDN for this Backend-Bucket.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

BackendBucket can be imported using any of these accepted formats:

```
$ terraform import google_compute_backend_bucket.default projects/{{project}}/global/backend_bucket/{{name}}
$ terraform import google_compute_backend_bucket.default {{project}}/{{name}}
$ terraform import google_compute_backend_bucket.default {{name}}
```

» google_compute_backend_service

A Backend Service defines a group of virtual machines that will serve traffic for load balancing. For more information see the official documentation and the API.

For internal load balancing, use a `google_compute_region_backend_service`.

» Example Usage

```
resource "google_compute_backend_service" "website" {
  name          = "my-backend"
  description   = "Our company website"
  port_name     = "http"
  protocol      = "HTTP"
  timeout_sec   = 10
  enable_cdn    = false

  backend {
    group = "${google_compute_instance_group_manager.webservers.instance_group}"
  }

  health_checks = ["${google_compute_http_health_check.default.self_link}"]
}

resource "google_compute_instance_group_manager" "webservers" {
  name          = "my-webservers"
  instance_template = "${google_compute_instance_template.webserver.self_link}"
  base_instance_name = "webserver"
  zone          = "us-central1-f"
  target_size    = 1
}

resource "google_compute_instance_template" "webserver" {
  name          = "standard-webserver"
  machine_type  = "n1-standard-1"

  network_interface {
    network = "default"
  }

  disk {
    source_image = "debian-cloud/debian-8"
    auto_delete = true
    boot        = true
  }
}

resource "google_compute_http_health_check" "default" {
  name          = "test"
  request_path   = "/"
  check_interval_sec = 1
  timeout_sec    = 1
}
```

}

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the backend service.
 - **health_checks** - (Required) Specifies a list of HTTP/HTTPS health checks for checking the health of the backend service. Currently at most one health check can be specified, and a health check is required.
-
- **backend** - (Optional) The list of backends that serve this BackendService. Structure is documented below.
 - **iap** - (Optional) Specification for the Identity-Aware proxy. Disabled if not specified. Structure is documented below.
 - **cdn_policy** - (Optional) Cloud CDN configuration for this BackendService. Structure is documented below.
 - **connection_draining_timeout_sec** - (Optional) Time for which instance will be drained (not accept new connections, but still work to finish started ones). Defaults to 300.
 - **custom_request_headers** - (Optional, Beta) Headers that the HTTP/S load balancer should add to proxied requests. See guide for details.
 - **description** - (Optional) The textual description for the backend service.
 - **enable_cdn** - (Optional) Whether or not to enable the Cloud CDN on the backend service.
 - **port_name** - (Optional) The name of a service that has been added to an instance group in this backend. See related docs for details. Defaults to http.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
 - **protocol** - (Optional) The protocol for incoming requests. Defaults to HTTP.
 - **security_policy** - (Optional, Beta) Name or URI of a security policy to add to the backend service.
 - **session_affinity** - (Optional) How to distribute load. Options are NONE (no affinity), CLIENT_IP (hash of the source/dest addresses / ports), and GENERATED_COOKIE (distribute load using a generated session cookie).

- **timeout_sec** - (Optional) The number of secs to wait for a backend to respond to a request before considering the request failed. Defaults to 30.

The **backend** block supports:

- **group** - (Required) The name or URI of a Compute Engine instance group (`google_compute_instance_group_manager.xyz.instance_group`) that can receive traffic.
- **balancing_mode** - (Optional) Defines the strategy for balancing load. Defaults to **UTILIZATION**
- **capacity_scaler** - (Optional) A float in the range [0, 1.0] that scales the maximum parameters for the group (e.g., max rate). A value of 0.0 will cause no requests to be sent to the group (i.e., it adds the group in a drained state). The default is 1.0.
- **description** - (Optional) Textual description for the backend.
- **max_rate** - (Optional) Maximum requests per second (RPS) that the group can handle.
- **max_rate_per_instance** - (Optional) The maximum per-instance requests per second (RPS).
- **max_connections** - (Optional) The max number of simultaneous connections for the group. Can be used with either **CONNECTION** or **UTILIZATION** balancing modes. For **CONNECTION** mode, either `maxConnections` or `maxConnectionsPerInstance` must be set.
- **max_connections_per_instance** - (Optional) The max number of simultaneous connections that a single backend instance can handle. This is used to calculate the capacity of the group. Can be used in either **CONNECTION** or **UTILIZATION** balancing modes. For **CONNECTION** mode, either `maxConnections` or `maxConnectionsPerInstance` must be set.
- **max_utilization** - (Optional) The target CPU utilization for the group as a float in the range [0.0, 1.0]. This flag can only be provided when the balancing mode is **UTILIZATION**. Defaults to 0.8.

The **cdn_policy** block supports:

- **cache_key_policy** - (Optional) The `CacheKeyPolicy` for this `CdnPolicy`. Structure is documented below.

The **cache_key_policy** block supports:

- **include_host** - (Optional) If true, requests to different hosts will be cached separately.
- **include_protocol** - (Optional) If true, http and https requests will be cached separately.

- **include_query_string** - (Optional) If true, include query string parameters in the cache key according to **query_string_whitelist** and **query_string_blacklist**. If neither is set, the entire query string will be included. If false, the query string will be excluded from the cache key entirely.
- **query_string_blacklist** - (Optional) Names of query string parameters to exclude in cache keys. All other parameters will be included. Either specify **query_string_whitelist** or **query_string_blacklist**, not both. '&' and '=' will be percent encoded and not treated as delimiters.
- **query_string_whitelist** - (Optional) Names of query string parameters to include in cache keys. All other parameters will be excluded. Either specify **query_string_whitelist** or **query_string_blacklist**, not both. '&' and '=' will be percent encoded and not treated as delimiters.

The **iap** block supports:

- **oauth2_client_id** - (Required) The client ID for use with OAuth 2.0.
- **oauth2_client_secret** - (Required) The client secret for use with OAuth 2.0.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **fingerprint** - The fingerprint of the backend service.
- **self_link** - The URI of the created resource.

» Import

Backend services can be imported using the **name**, e.g.

```
$ terraform import google_compute_backend_service.website my-backend
```

» google__compute__disk

Persistent disks are durable storage devices that function similarly to the physical disks in a desktop or a server. Compute Engine manages the hardware behind these devices to ensure data redundancy and optimize performance for you. Persistent disks are available as either standard hard disk drives (HDD) or solid-state drives (SSD).

Persistent disks are located independently from your virtual machine instances, so you can detach or move persistent disks to keep your data even after you delete your instances. Persistent disk performance scales automatically with size, so you can resize your existing persistent disks or add more persistent disks to an instance to meet your performance and storage space requirements.

Add a persistent disk to your instance when you need reliable and affordable storage with consistent performance characteristics.

To get more information about Disk, see:

- API documentation
- How-to Guides
 - Adding a persistent disk

Warning: All arguments including the disk encryption key will be stored in the raw state as plain-text. Read more about sensitive data in state.

» Example Usage

```
resource "google_compute_disk" "default" {
  name  = "test-disk"
  type  = "pd-ssd"
  zone  = "us-central1-a"
  image = "debian-8-jessie-v20170523"
  labels {
    environment = "dev"
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
-
- **description** - (Optional) An optional description of this resource. Provide this property when you create the resource.

- **labels** - (Optional) Labels to apply to this disk. A list of key->value pairs.
- **size** - (Optional) Size of the persistent disk, specified in GB. You can specify this field when creating a persistent disk using the `sourceImage` or `sourceSnapshot` parameter, or specify it alone to create an empty persistent disk. If you specify this field along with `sourceImage` or `sourceSnapshot`, the value of `sizeGb` must not be less than the size of the `sourceImage` or the size of the snapshot.
- **type** - (Optional) URL of the disk type resource describing which disk type to use to create the disk. Provide this when creating the disk.
- **image** - (Optional) The image from which to initialize this disk. This can be one of: the image's `self_link`, `projects/{project}/global/images/{image}`, `projects/{project}/global/images/family/{family}`, `global/images/{image}`, `global/images/family/{family}`, `family/{family}`, `{project}/{family}`, `{project}/{image}`, `{family}`, or `{image}`. If referred by family, the images names must include the family name. If they don't, use the `google_compute_image` data source. For instance, the image `centos-6-v20180104` includes its family name `centos-6`. These images can be referred by family name here.
- **zone** - (Optional) A reference to the zone where the disk resides.
- **source_image_encryption_key** - (Optional) The customer-supplied encryption key of the source image. Required if the source image is protected by a customer-supplied encryption key. Structure is documented below.
- **disk_encryption_key** - (Optional) Encrypts the disk using a customer-supplied encryption key. After you encrypt a disk with a customer-supplied key, you must provide the same key if you use the disk later (e.g. to create a disk snapshot or an image, or to attach the disk to a virtual machine). Customer-supplied encryption keys do not protect access to metadata of the disk. If you do not provide an encryption key when creating the disk, then the disk will be encrypted using an automatically generated key and you do not need to provide a key to use the disk later. Structure is documented below.
- **snapshot** - (Optional) The source snapshot used to create this disk. You can provide this as a partial or full URL to the resource. For example, the following are valid values:
 - `https://www.googleapis.com/compute/v1/projects/project/global/snapshots/snapshot`
 - `projects/project/global/snapshots/snapshot`
 - `global/snapshots/snapshot`
 - `snapshot`
- **source_snapshot_encryption_key** - (Optional) The customer-supplied encryption key of the source snapshot. Required if the source snapshot is

protected by a customer-supplied encryption key. Structure is documented below.

- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

The **source_image_encryption_key** block supports:

- **raw_key** - (Optional) Specifies a 256-bit customer-supplied encryption key, encoded in RFC 4648 base64 to either encrypt or decrypt this resource.
- **sha256** - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this resource.

The **disk_encryption_key** block supports:

- **raw_key** - (Optional) Specifies a 256-bit customer-supplied encryption key, encoded in RFC 4648 base64 to either encrypt or decrypt this resource.
- **sha256** - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this resource.

The **source_snapshot_encryption_key** block supports:

- **raw_key** - (Optional) Specifies a 256-bit customer-supplied encryption key, encoded in RFC 4648 base64 to either encrypt or decrypt this resource.
- **sha256** - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this resource.
- (Deprecated) **disk_encryption_key_raw**: This is an alias for **disk_encryption_key.raw_key**. It is deprecated to enhance consistency with **source_image_encryption_key** and **source_snapshot_encryption_key**.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **label_fingerprint** - The fingerprint used for optimistic locking of this resource. Used internally during updates.
- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **last_attach_timestamp** - Last attach timestamp in RFC3339 text format.
- **last_detach_timestamp** - Last detach timestamp in RFC3339 text format.
- **users** - Links to the users of the disk (attached instances) in form: `project/zones/zone/instances/instance`

- **source_image_id** - The ID value of the image used to create this disk. This value identifies the exact image that was used to create this persistent disk. For example, if you created the persistent disk from an image that was later deleted and recreated under the same name, the source image ID would identify the exact version of the image that was used.
- **source_snapshot_id** - The unique ID of the snapshot used to create this disk. This value identifies the exact snapshot that was used to create this persistent disk. For example, if you created the persistent disk from a snapshot that was later deleted and recreated under the same name, the source snapshot ID would identify the exact version of the snapshot that was used.
- **self_link** - The URI of the created resource.
- (Deprecated) **disk_encryption_key_sha256**: This is an alias for **disk_encryption_key.sha256**. It is deprecated to enhance consistency with **source_image_encryption_key** and **source_snapshot_encryption_key**.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 5 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

Disk can be imported using any of these accepted formats:

```
$ terraform import google_compute_disk.default projects/{{project}}/zones/{{zone}}/disks/{{name}}
$ terraform import google_compute_disk.default {{project}}/{{zone}}/{{name}}
$ terraform import google_compute_disk.default {{name}}
```

» google__compute__firewall

Each network has its own firewall controlling access to and from the instances.

All traffic to instances, even from other instances, is blocked by the firewall unless firewall rules are created to allow it.

The default network has automatically created firewall rules that are shown in default firewall rules. No manually created network has automatically created firewall rules except for a default "allow" rule for outgoing traffic and a default

"deny" for incoming traffic. For all networks except the default network, you must create any firewall rules you need.

To get more information about Firewall, see:

- API documentation
- How-to Guides
 - Official Documentation

» Example Usage

```
resource "google_compute_network" "default" {
  name = "test-network"
}

resource "google_compute_firewall" "default" {
  name      = "test-firewall"
  network   = "${google_compute_network.default.name}"

  allow {
    protocol = "icmp"
  }

  allow {
    protocol = "tcp"
    ports    = ["80", "8080", "1000-2000"]
  }

  source_tags = ["web"]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
- **network** - (Required) The name or `self_link` of the network to attach this firewall to.

-
- **allow** - (Optional) The list of ALLOW rules specified by this firewall. Each rule specifies a protocol and port-range tuple that describes a permitted connection. Structure is documented below.
 - **deny** - (Optional) The list of DENY rules specified by this firewall. Each rule specifies a protocol and port-range tuple that describes a denied connection. Structure is documented below.
 - **description** - (Optional) An optional description of this resource. Provide this property when you create the resource.
 - **destination_ranges** - (Optional) If destination ranges are specified, the firewall will apply only to traffic that has destination IP address in these ranges. These ranges must be expressed in CIDR format. Only IPv4 is supported.
 - **direction** - (Optional) Direction of traffic to which this firewall applies; default is INGRESS. Note: For INGRESS traffic, it is NOT supported to specify destinationRanges; For EGRESS traffic, it is NOT supported to specify sourceRanges OR sourceTags.
 - **disabled** - (Optional) Denotes whether the firewall rule is disabled, i.e not applied to the network it is associated with. When set to true, the firewall rule is not enforced and the network behaves as if it did not exist. If this is unspecified, the firewall rule will be enabled.
 - **priority** - (Optional) Priority for this rule. This is an integer between 0 and 65535, both inclusive. When not specified, the value assumed is 1000. Relative priorities determine precedence of conflicting rules. Lower value of priority implies higher precedence (eg, a rule with priority 0 has higher precedence than a rule with priority 1). DENY rules take precedence over ALLOW rules having equal priority.
 - **source_ranges** - (Optional) If source ranges are specified, the firewall will apply only to traffic that has source IP address in these ranges. These ranges must be expressed in CIDR format. One or both of sourceRanges and sourceTags may be set. If both properties are set, the firewall will apply to traffic that has source IP address within sourceRanges OR the source IP that belongs to a tag listed in the sourceTags property. The connection does not need to match both properties for the firewall to apply. Only IPv4 is supported.
 - **source_service_accounts** - (Optional) If source service accounts are specified, the firewall will apply only to traffic originating from an instance with a service account in this list. Source service accounts cannot be used to control traffic to an instance's external IP address because service accounts are associated with an instance, not an IP address. sourceRanges can be set at the same time as sourceServiceAccounts. If both are set, the

firewall will apply to traffic that has source IP address within sourceRanges OR the source IP belongs to an instance with service account listed in sourceServiceAccount. The connection does not need to match both properties for the firewall to apply. sourceServiceAccounts cannot be used at the same time as sourceTags or targetTags.

- **source_tags** - (Optional) If source tags are specified, the firewall will apply only to traffic with source IP that belongs to a tag listed in source tags. Source tags cannot be used to control traffic to an instance's external IP address. Because tags are associated with an instance, not an IP address. One or both of sourceRanges and sourceTags may be set. If both properties are set, the firewall will apply to traffic that has source IP address within sourceRanges OR the source IP that belongs to a tag listed in the sourceTags property. The connection does not need to match both properties for the firewall to apply.
- **target_service_accounts** - (Optional) A list of service accounts indicating sets of instances located in the network that may make network connections as specified in allowed[]. targetServiceAccounts cannot be used at the same time as targetTags or sourceTags. If neither targetServiceAccounts nor targetTags are specified, the firewall rule applies to all instances on the specified network.
- **target_tags** - (Optional) A list of instance tags indicating sets of instances located in the network that may make network connections as specified in allowed[]. If no targetTags are specified, the firewall rule applies to all instances on the specified network.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

The **allow** block supports:

- **protocol** - (Required) The IP protocol to which this rule applies. The protocol type is required when creating a firewall rule. This value can either be one of the following well known protocol strings (tcp, udp, icmp, esp, ah, sctp), or the IP protocol number.
- **ports** - (Optional) An optional list of ports to which this rule applies. This field is only applicable for UDP or TCP protocol. Each entry must be either an integer or a range. If not specified, this rule applies to connections through any port. Example inputs include: ["22"], ["80","443"], and ["12345-12349"].

The **deny** block supports:

- **protocol** - (Required) The IP protocol to which this rule applies. The protocol type is required when creating a firewall rule. This value can either be one of the following well known protocol strings (tcp, udp, icmp, esp, ah, sctp), or the IP protocol number.

- **ports** - (Optional) An optional list of ports to which this rule applies. This field is only applicable for UDP or TCP protocol. Each entry must be either an integer or a range. If not specified, this rule applies to connections through any port. Example inputs include: ["22"], ["80","443"], and ["12345-12349"].

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

Firewall can be imported using any of these accepted formats:

```
$ terraform import google_compute_firewall.default projects/{{project}}/global/firewalls/{{name}}
$ terraform import google_compute_firewall.default {{project}}/{{name}}
$ terraform import google_compute_firewall.default {{name}}
```

» google__compute__forwarding__rule

A ForwardingRule resource. A ForwardingRule resource specifies which pool of target virtual machines to forward a packet to if it matches the given [IPAddress, IPProtocol, portRange] tuple.

To get more information about ForwardingRule, see:

- API documentation
- How-to Guides
 - Official Documentation

» Example Usage

```
resource "google_compute_forwarding_rule" "default" {  
  name      = "website-forwarding-rule"  
  target    = "${google_compute_target_pool.default.self_link}"  
  port_range = "80"  
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource; provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.

-
- **description** - (Optional) An optional description of this resource. Provide this property when you create the resource.
 - **ip_address** - (Optional) The IP address that this forwarding rule is serving on behalf of. Addresses are restricted based on the forwarding rule's load balancing scheme (EXTERNAL or INTERNAL) and scope (global or regional). When the load balancing scheme is EXTERNAL, for global forwarding rules, the address must be a global IP, and for regional forwarding rules, the address must live in the same region as the forwarding rule. If this field is empty, an ephemeral IPv4 address from the same scope (global or regional) will be assigned. A regional forwarding rule supports IPv4 only. A global forwarding rule supports either IPv4 or IPv6. When the load balancing scheme is INTERNAL, this can only be an RFC 1918 IP address belonging to the network/subnet configured for the forwarding rule. By default, if this field is empty, an ephemeral internal IP address will be automatically allocated from the IP range of the subnet or network configured for this forwarding rule. An address can be specified either by a literal IP address or a URL reference to an existing Address resource. The following examples are all valid:

- 100.1.2.3
- <https://www.googleapis.com/compute/v1/projects/project/regions/region/addresses/address>
- [projects/project/regions/region/addresses/address](https://www.googleapis.com/compute/v1/projects/project/regions/region/addresses/address)
- [regions/region/addresses/address](https://www.googleapis.com/compute/v1/projects/project/regions/region/addresses/address)

- global/addresses/address
 - address
- **ip_protocol** - (Optional) The IP protocol to which this rule applies. Valid options are TCP, UDP, ESP, AH, SCTP or ICMP. When the load balancing scheme is INTERNAL, only TCP and UDP are valid.
- **backend_service** - (Optional) A reference to a BackendService to receive the matched traffic. This is used for internal load balancing. (not used for external load balancing)
- **ip_version** - (Optional) The IP Version that will be used by this forwarding rule. Valid options are IPV4 or IPV6. This can only be specified for a global forwarding rule.
- **load_balancing_scheme** - (Optional) This signifies what the ForwardingRule will be used for and can only take the following values: INTERNAL, EXTERNAL The value of INTERNAL means that this will be used for Internal Network Load Balancing (TCP, UDP). The value of EXTERNAL means that this will be used for External Load Balancing (HTTP(S) LB, External TCP/UDP LB, SSL Proxy)
- **network** - (Optional) For internal load balancing, this field identifies the network that the load balanced IP should belong to for this Forwarding Rule. If this field is not specified, the default network will be used. This field is not used for external load balancing.
- **port_range** - (Optional) This field is used along with the target field for TargetHttpProxy, TargetHttpsProxy, TargetSslProxy, TargetTcpProxy, TargetVpnGateway, TargetPool, TargetInstance. Applicable only when IPProtocol is TCP, UDP, or SCTP, only packets addressed to ports in the specified range will be forwarded to target. Forwarding rules with the same [IPAddress, IPProtocol] pair must have disjoint port ranges. Some types of forwarding target have constraints on the acceptable ports:
 - TargetHttpProxy: 80, 8080
 - TargetHttpsProxy: 443
 - TargetTcpProxy: 25, 43, 110, 143, 195, 443, 465, 587, 700, 993, 995, 1883, 5222
 - TargetSslProxy: 25, 43, 110, 143, 195, 443, 465, 587, 700, 993, 995, 1883, 5222
 - TargetVpnGateway: 500, 4500
- **ports** - (Optional) This field is used along with the backend_service field for internal load balancing. When the load balancing scheme is INTERNAL, a single port or a comma separated list of ports can be configured. Only packets addressed to these ports will be forwarded to the backends configured with this forwarding rule. You may specify a maximum of up to 5 ports.

- **subnetwork** - (Optional) A reference to a subnetwork. For internal load balancing, this field identifies the subnetwork that the load balanced IP should belong to for this Forwarding Rule. If the network specified is in auto subnet mode, this field is optional. However, if the network is in custom subnet mode, a subnetwork must be specified. This field is not used for external load balancing.
- **target** - (Optional) A reference to a TargetPool resource to receive the matched traffic. For regional forwarding rules, this target must live in the same region as the forwarding rule. For global forwarding rules, this target must be a global load balancing resource. The forwarded traffic must be of a type appropriate to the target object. This field is not used for internal load balancing.
- **labels** - (Optional) Labels to apply to this forwarding rule. A list of key->value pairs.
- **network_tier** - (Optional) The networking tier used for configuring this address. This field can take the following values: PREMIUM or STANDARD. If this field is not specified, it is assumed to be PREMIUM.
- **service_label** - (Optional) An optional prefix to the service name for this Forwarding Rule. If specified, will be the first label of the fully qualified service name. The label must be 1-63 characters long, and comply with RFC1035. Specifically, the label must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash. This field is only used for internal load balancing.
- **region** - (Optional) A reference to the region where the regional forwarding rule resides. This field is not applicable to global forwarding rules.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **label_fingerprint** - The fingerprint used for optimistic locking of this resource. Used internally during updates.
- **service_name** - The internal fully qualified service name for this Forwarding Rule. This field is only used for internal load balancing.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- `create` - Default is 4 minutes.
- `update` - Default is 4 minutes.
- `delete` - Default is 4 minutes.

» Import

ForwardingRule can be imported using any of these accepted formats:

```
$ terraform import google_compute_forwarding_rule.default projects/{{project}}/regions/{{region}}/forwarding_rules/{{name}}
$ terraform import google_compute_forwarding_rule.default {{project}}/{{region}}/{{name}}
$ terraform import google_compute_forwarding_rule.default {{name}}
```

» google_compute_global_address

Represents a Global Address resource. Global addresses are used for HTTP(S) load balancing.

To get more information about GlobalAddress, see:

- API documentation
- How-to Guides
 - Reserving a Static External IP Address

» Example Usage

```
resource "google_compute_global_address" "default" {
  name = "global-appserver-ip"
}
```

» Argument Reference

The following arguments are supported:

- `name` - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.

-
- **description** - (Optional) An optional description of this resource. Provide this property when you create the resource.
 - **labels** - (Optional) Labels to apply to this address. A list of key->value pairs.
 - **ip_version** - (Optional) The IP Version that will be used by this address. Valid options are IPV4 or IPV6. The default value is IPV4.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **address** - The static external IP address represented by this resource.
- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **label_fingerprint** - The fingerprint used for optimistic locking of this resource. Used internally during updates.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

GlobalAddress can be imported using any of these accepted formats:

```
$ terraform import google_compute_global_address.default projects/{{project}}/global/address/{{name}}
$ terraform import google_compute_global_address.default {{project}}/{{name}}
$ terraform import google_compute_global_address.default {{name}}
```

» google__compute__global__forwarding__rule

Manages a Global Forwarding Rule within GCE. This binds an ip and port to a target HTTP(s) proxy. For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_global_forwarding_rule" "default" {
  name          = "default-rule"
  target        = "${google_compute_target_http_proxy.default.self_link}"
  port_range    = "80"
}

resource "google_compute_target_http_proxy" "default" {
  name          = "test-proxy"
  description    = "a description"
  url_map       = "${google_compute_url_map.default.self_link}"
}

resource "google_compute_url_map" "default" {
  name          = "url-map"
  description    = "a description"
  default_service = "${google_compute_backend_service.default.self_link}"

  host_rule {
    hosts        = ["mysite.com"]
    path_matcher = "allpaths"
  }

  path_matcher {
    name          = "allpaths"
    default_service = "${google_compute_backend_service.default.self_link}"

    path_rule {
      paths      = ["/*"]
      service    = "${google_compute_backend_service.default.self_link}"
    }
  }
}

resource "google_compute_backend_service" "default" {
  name          = "default-backend"
  port_name     = "http"
}
```

```

protocol      = "HTTP"
timeout_sec   = 10

health_checks = ["${google_compute_http_health_check.default.self_link}"]
}

resource "google_compute_http_health_check" "default" {
  name           = "test"
  request_path    = "/"
  check_interval_sec = 1
  timeout_sec     = 1
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.
 - **target** - (Required) URL of target HTTP or HTTPS proxy.
-
- **description** - (Optional) Textual description field.
 - **ip_address** - (Optional) The static IP. (if not set, an ephemeral IP is used). This should be the literal IP address to be used, not the `self_link` to a `google_compute_global_address` resource. (If using a `google_compute_global_address` resource, use the `address` property instead of the `self_link` property.)
 - **ip_protocol** - (Optional) The IP protocol to route, one of "TCP" "UDP" "AH" "ESP" or "SCTP". (default "TCP").
 - **port_range** - (Optional) A range e.g. "1024-2048" or a single port "1024" (defaults to all ports!). Some types of forwarding targets have constraints on the acceptable ports:
 - Target HTTP proxy: 80, 8080
 - Target HTTPS proxy: 443
 - Target TCP proxy: 25, 43, 110, 143, 195, 443, 465, 587, 700, 993, 995, 1883, 5222
 - Target SSL proxy: 25, 43, 110, 143, 195, 443, 465, 587, 700, 993, 995, 1883, 5222
 - Target VPN gateway: 500, 4500
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

- `ip_version` - (Optional) The IP Version that will be used by this resource's address. One of "IPv4" or "IPv6". You cannot provide this and `ip_address`.
-
- `labels` - (Optional, Beta) A set of key/value label pairs to assign to the resource.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `self_link` - The URI of the created resource.
- `label_fingerprint` - (Beta) The current label fingerprint.

» Import

Global forwarding rules can be imported using the `name`, e.g.

```
$ terraform import google_compute_global_forwarding_rule.default default-rule
```

» google_compute_health_check

Manages a health check within GCE. This is used to monitor instances behind load balancers. Timeouts or HTTP errors cause the instance to be removed from the pool. For more information, see the official documentation and API.

» Example Usage

```
resource "google_compute_health_check" "default" {
  name = "internal-service-health-check"

  timeout_sec          = 1
  check_interval_sec   = 1

  tcp_health_check {
    port = "80"
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.

-
- **check_interval_sec** - (Optional) The number of seconds between each poll of the instance instance (default 5).
 - **description** - (Optional) Textual description field.
 - **healthy_threshold** - (Optional) Consecutive successes required (default 2).
 - **http_health_check** - (Optional) An HTTP Health Check. Only one kind of Health Check can be added. Structure is documented below.
 - **https_health_check** - (Optional) An HTTPS Health Check. Only one kind of Health Check can be added. Structure is documented below.
 - **ssl_health_check** - (Optional) An SSL Health Check. Only one kind of Health Check can be added. Structure is documented below.
 - **tcp_health_check** - (Optional) A TCP Health Check. Only one kind of Health Check can be added. Structure is documented below.
 - **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
 - **timeout_sec** - (Optional) The number of seconds to wait before declaring failure (default 5).
 - **unhealthy_threshold** - (Optional) Consecutive failures required (default 2).

The **http_health_check** block supports:

- **host** - (Optional) HTTP host header field (default instance's public ip).
- **port** - (Optional) TCP port to connect to (default 80).
- **proxy_header** - (Optional) Type of proxy header to append before sending data to the backend, either NONE or PROXY_V1 (default NONE).
- **request_path** - (Optional) URL path to query (default /).

The **https_health_check** block supports:

- **host** - (Optional) HTTPS host header field (default instance's public ip).
- **port** - (Optional) TCP port to connect to (default 443).

- **proxy_header** - (Optional) Type of proxy header to append before sending data to the backend, either NONE or PROXY_V1 (default NONE).
- **request_path** - (Optional) URL path to query (default /).

The **ssl_health_check** block supports:

- **port** - (Optional) TCP port to connect to (default 443).
- **proxy_header** - (Optional) Type of proxy header to append before sending data to the backend, either NONE or PROXY_V1 (default NONE).
- **request** - (Optional) Application data to send once the SSL connection has been established (default "").
- **response** - (Optional) The response that indicates health (default "")

The **tcp_health_check** block supports:

- **port** - (Optional) TCP port to connect to (default 80).
- **proxy_header** - (Optional) Type of proxy header to append before sending data to the backend, either NONE or PROXY_V1 (default NONE).
- **request** - (Optional) Application data to send once the TCP connection has been established (default "").
- **response** - (Optional) The response that indicates health (default "")

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.

» Import

Health checks can be imported using the **name**, e.g.

```
$ terraform import google_compute_health_check.default internal-service-health-check
```

» google_compute_http_health_check

An **HttpHealthCheck** resource. This resource defines a template for how individual VMs should be checked for health, via HTTP.

Note: `google_compute_http_health_check` is a legacy health check. The newer `google_compute_health_check` should be preferred for all uses except Network Load Balancers which still require the legacy version.

To get more information about `HttpHealthCheck`, see:

- API documentation
- How-to Guides
 - Adding Health Checks

» Example Usage

```
resource "google_compute_http_health_check" "default" {
  name          = "authentication-health-check"
  request_path  = "/health_check"

  timeout_sec      = 1
  check_interval_sec = 1
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
-
- **check_interval_sec** - (Optional) How often (in seconds) to send a health check. The default value is 5 seconds.
 - **description** - (Optional) An optional description of this resource. Provide this property when you create the resource.
 - **healthy_threshold** - (Optional) A so-far unhealthy instance will be marked healthy after this many consecutive successes. The default value is 2.
 - **host** - (Optional) The value of the host header in the HTTP health check request. If left empty (default value), the public IP on behalf of which this health check is performed will be used.

- **port** - (Optional) The TCP port number for the HTTP health check request. The default value is 80.
- **request_path** - (Optional) The request path of the HTTP health check request. The default value is `/`.
- **timeout_sec** - (Optional) How long (in seconds) to wait before claiming failure. The default value is 5 seconds. It is invalid for `timeoutSec` to have greater value than `checkIntervalSec`.
- **unhealthy_threshold** - (Optional) A so-far healthy instance will be marked unhealthy after this many consecutive failures. The default value is 2.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

`HttpHealthCheck` can be imported using any of these accepted formats:

```
$ terraform import google_compute_http_health_check.default projects/{{project}}/global/httpHealthCheck/{{name}}
$ terraform import google_compute_http_health_check.default {{project}}/{{name}}
$ terraform import google_compute_http_health_check.default {{name}}
```

» google_compute_https_health_check

An `HttpsHealthCheck` resource. This resource defines a template for how individual VMs should be checked for health, via HTTPS.

Note: `google_compute_https_health_check` is a legacy health check. The newer `google_compute_health_check` should be preferred for all uses except Network Load Balancers which still require the legacy version.

To get more information about `HttpsHealthCheck`, see:

- API documentation
- How-to Guides
 - Adding Health Checks

» Example Usage

```
resource "google_compute_https_health_check" "default" {
  name          = "test"
  request_path   = "/health_check"

  timeout_sec      = 1
  check_interval_sec = 1
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
-
- **check_interval_sec** - (Optional) How often (in seconds) to send a health check. The default value is 5 seconds.
 - **description** - (Optional) An optional description of this resource. Provide this property when you create the resource.
 - **healthy_threshold** - (Optional) A so-far unhealthy instance will be marked healthy after this many consecutive successes. The default value is 2.
 - **host** - (Optional) The value of the host header in the HTTPS health check request. If left empty (default value), the public IP on behalf of which this health check is performed will be used.

- **port** - (Optional) The TCP port number for the HTTPS health check request. The default value is 80.
- **request_path** - (Optional) The request path of the HTTPS health check request. The default value is `/`.
- **timeout_sec** - (Optional) How long (in seconds) to wait before claiming failure. The default value is 5 seconds. It is invalid for `timeoutSec` to have greater value than `checkIntervalSec`.
- **unhealthy_threshold** - (Optional) A so-far healthy instance will be marked unhealthy after this many consecutive failures. The default value is 2.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

`HttpsHealthCheck` can be imported using any of these accepted formats:

```
$ terraform import google_compute_https_health_check.default projects/{{project}}/global/httpsHealthCheck/{{name}}
$ terraform import google_compute_https_health_check.default {{project}}/{{name}}
$ terraform import google_compute_https_health_check.default {{name}}
```

» google_compute_image

Creates a bootable VM image resource for Google Compute Engine from an existing tarball. For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_image" "bootable-image" {
  name = "my-custom-image"

  raw_disk {
    source = "https://storage.googleapis.com/my-bucket/my-disk-image-tarball.tar.gz"
  }

  licenses = [
    "https://www.googleapis.com/compute/v1/projects/vm-options/global/licenses/enable-vmx",
  ]
}

resource "google_compute_instance" "vm" {
  name          = "vm-from-custom-image"
  machine_type  = "n1-standard-1"
  zone          = "us-east1-c"

  boot_disk {
    initialize_params {
      image = "${google_compute_image.bootable-image.self_link}"
    }
  }

  network_interface {
    network = "default"
  }
}
```

» Argument Reference

The following arguments are supported: (Note that one of either `source__disk` or `raw__disk` is required)

- **name** - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.
-
- **description** - (Optional) The description of the image to be created
 - **family** - (Optional) The name of the image family to which this image belongs.
 - **labels** - (Optional) A set of key/value label pairs to assign to the image.

- **source_disk** - (Optional) The URL of a disk that will be used as the source of the image. Changing this forces a new resource to be created.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **raw_disk** - (Optional) The raw disk that will be used as the source of the image. Changing this forces a new resource to be created. Structure is documented below.
- **licenses** - (Optional) A list of license URIs to apply to this image. Changing this forces a new resource to be created.
- **create_timeout** - (Deprecated) Configurable timeout in minutes for creating images. Default is 4 minutes.

The **raw_disk** block supports:

- **source** - (Required) The full Google Cloud Storage URL where the disk image is stored.
- **sha1** - (Optional) SHA1 checksum of the source tarball that will be used to verify the source before creating the image.
- **container_type** - (Optional) The format used to encode and transmit the block device. TAR is the only supported type and is the default.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.
- **label_fingerprint** - The fingerprint of the assigned labels.

» Timeouts

`google_compute_image` provides the following Timeouts configuration options:

- **create** - Default 4 minutes
- **update** - Default 4 minutes
- **delete** - Default 4 minutes

» Import

VM image can be imported using the **name**, e.g.

```
$ terraform import google_compute_image.web-image my-custom-image
```

» google__compute__instance

Manages a VM instance resource within GCE. For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_instance" "default" {
  name          = "test"
  machine_type  = "n1-standard-1"
  zone          = "us-central1-a"

  tags = ["foo", "bar"]

  boot_disk {
    initialize_params {
      image = "debian-cloud/debian-8"
    }
  }

  // Local SSD disk
  scratch_disk {
  }

  network_interface {
    network = "default"

    access_config {
      // Ephemeral IP
    }
  }

  metadata {
    foo = "bar"
  }

  metadata_startup_script = "echo hi > /test.txt"

  service_account {
    scopes = ["userinfo-email", "compute-ro", "storage-ro"]
  }
}
```

» Argument Reference

The following arguments are supported:

- **boot_disk** - (Required) The boot disk for the instance. Structure is documented below.
- **machine_type** - (Required) The machine type to create.

Note: If you want to update this value (resize the VM) after initial creation, you must set **allow_stopping_for_update** to **true**.

To create a machine with a custom type (such as extended memory), format the value like **custom-VCPUS-MEM_IN_MB** like **custom-6-20480** for 6 vCPU and 20GB of RAM.

- **name** - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.
- **zone** - (Required) The zone that the machine should be created in.
- **network_interface** - (Required) Networks to attach to the instance. This can be specified multiple times. Structure is documented below.

-
- **allow_stopping_for_update** - (Optional) If true, allows Terraform to stop the instance to update its properties. If you try to update a property that requires stopping the instance without setting this field, the update will fail.
 - **attached_disk** - (Optional) List of disks to attach to the instance. Structure is documented below.
 - **can_ip_forward** - (Optional) Whether to allow sending and receiving of packets with non-matching source or destination IPs. This defaults to false.
 - **create_timeout** - (Optional) Configurable timeout in minutes for creating instances. Default is 4 minutes. Changing this forces a new resource to be created.
 - **description** - (Optional) A brief description of this resource.
 - **deletion_protection** - (Optional) Enable deletion protection on this instance. Defaults to false. **Note:** you must disable deletion protection before removing the resource (e.g., via **terraform destroy**), or the instance cannot be deleted and the Terraform run will not complete successfully.
 - **guest_accelerator** - (Optional) List of the type and count of accelerator cards attached to the instance. Structure documented below. **Note:** GPU accelerators can only be used with **on_host_maintenance** option set to **TERMINATE**.

- **labels** - (Optional) A set of key/value label pairs to assign to the instance.
- **metadata** - (Optional) Metadata key/value pairs to make available from within the instance.
- **metadata_startup_script** - (Optional) An alternative to using the `startup-script` metadata key, except this one forces the instance to be recreated (thus re-running the script) if it is changed. This replaces the `startup-script` metadata key on the created instance and thus the two mechanisms are not allowed to be used simultaneously.
- **min_cpu_platform** - (Optional) Specifies a minimum CPU platform for the VM instance. Applicable values are the friendly names of CPU platforms, such as `Intel Haswell` or `Intel Skylake`. See the complete list [here](#). **Note:** `allow_stopping_for_update` must be set to true in order to update this field.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **scheduling** - (Optional) The scheduling strategy to use. More details about this configuration option are detailed below.
- **scratch_disk** - (Optional) Scratch disks to attach to the instance. This can be specified multiple times for multiple scratch disks. Structure is documented below.
- **service_account** - (Optional) Service account to attach to the instance. Structure is documented below. **Note:** `allow_stopping_for_update` must be set to true in order to update this field.
- **tags** - (Optional) A list of tags to attach to the instance.

The `boot_disk` block supports:

- **auto_delete** - (Optional) Whether the disk will be auto-deleted when the instance is deleted. Defaults to true.
- **device_name** - (Optional) Name with which attached disk will be accessible. On the instance, this device will be `/dev/disk/by-id/google-{{device_name}}`.
- **disk_encryption_key_raw** - (Optional) A 256-bit customer-supplied encryption key, encoded in RFC 4648 base64 to encrypt this disk.
- **initialize_params** - (Optional) Parameters for a new disk that will be created alongside the new instance. Either `initialize_params` or `source` must be set. Structure is documented below.
- **source** - (Optional) The name or `self_link` of the existing disk (such as those managed by `google_compute_disk`) to attach.

The `initialize_params` block supports:

- **size** - (Optional) The size of the image in gigabytes. If not specified, it will inherit the size of its base image.
- **type** - (Optional) The GCE disk type. May be set to `pd-standard` or `pd-ssd`.
- **image** - (Optional) The image from which to initialize this disk. This can be one of: the image's `self_link`, `projects/{project}/global/images/{image}`, `projects/{project}/global/images/family/{family}`, `global/images/{image}`, `global/images/family/{family}`, `family/{family}`, `{project}/{family}`, `{project}/{image}`, `{family}`, or `{image}`. If referred by family, the images names must include the family name. If they don't, use the `google_compute_image` data source. For instance, the image `centos-6-v20180104` includes its family name `centos-6`. These images can be referred by family name here.

The `scratch_disk` block supports:

- **interface** - (Optional) The disk interface to use for attaching this disk; either SCSI or NVME. Defaults to SCSI.

The `attached_disk` block supports:

- **source** - (Required) The name or `self_link` of the disk to attach to this instance.
- **device_name** - (Optional) Name with which the attached disk will be accessible under `/dev/disk/by-id/`
- **mode** - (Optional) Either "READ_ONLY" or "READ_WRITE", defaults to "READ_WRITE" If you have a persistent disk with data that you want to share between multiple instances, detach it from any read-write instances and attach it to one or more instances in read-only mode.
- **disk_encryption_key_raw** - (Optional) A 256-bit customer-supplied encryption key, encoded in RFC 4648 base64 to encrypt this disk.

The `network_interface` block supports:

- **network** - (Optional) The name or `self_link` of the network to attach this interface to. Either `network` or `subnetwork` must be provided.
- **subnetwork** - (Optional) The name or `self_link` of the subnetwork to attach this interface to. The subnetwork must exist in the same region this instance will be created in. Either `network` or `subnetwork` must be provided.
- **subnetwork_project** - (Optional) The project in which the subnetwork belongs. If the `subnetwork` is a `self_link`, this field is ignored in favor of the project defined in the subnetwork `self_link`. If the `subnetwork` is a name and this field is not provided, the provider project is used.

- **address** - (Optional) The private IP address to assign to the instance. If empty, the address will be automatically assigned.
- **access_config** - (Optional) Access configurations, i.e. IPs via which this instance can be accessed via the Internet. Omit to ensure that the instance is not accessible from the Internet (this means that ssh provisioners will not work unless you are running Terraform can send traffic to the instance's network (e.g. via tunnel or because it is running on another cloud instance on that network). This block can be repeated multiple times. Structure documented below.
- **alias_ip_range** - (Optional) An array of alias IP ranges for this network interface. Can only be specified for network interfaces on subnet-mode networks. Structure documented below.

The **access_config** block supports:

- **nat_ip** - (Optional) The IP address that will be 1:1 mapped to the instance's network ip. If not given, one will be generated.
- **public_ptr_domain_name** - (Optional) The DNS domain name for the public PTR record. To set this field on an instance, you must be verified as the owner of the domain. See the docs for how to become verified as a domain owner.
- **network_tier** - (Optional) The networking tier used for configuring this instance. This field can take the following values: PREMIUM or STANDARD. If this field is not specified, it is assumed to be PREMIUM.

The **alias_ip_range** block supports:

- **ip_cidr_range** - The IP CIDR range represented by this alias IP range. This IP CIDR range must belong to the specified subnetwork and cannot contain IP addresses reserved by system or used by other network interfaces. This range may be a single IP address (e.g. 10.2.3.4), a netmask (e.g. /24) or a CIDR format string (e.g. 10.1.2.0/24).
- **subnetwork_range_name** - (Optional) The subnetwork secondary range name specifying the secondary range from which to allocate the IP CIDR range for this alias IP range. If left unspecified, the primary range of the subnetwork will be used.

The **service_account** block supports:

- **email** - (Optional) The service account e-mail address. If not given, the default Google Compute Engine service account is used. **Note:** **allow_stopping_for_update** must be set to true in order to update this field.
- **scopes** - (Required) A list of service scopes. Both OAuth2 URLs and gcloud short names are supported. To allow full access to all Cloud APIs, use the **cloud-platform** scope. See a complete list of scopes here. **Note:**

`allow_stopping_for_update` must be set to true in order to update this field.

The `scheduling` block supports:

- `preemptible` - (Optional) Is the instance preemptible.
- `on_host_maintenance` - (Optional) Describes maintenance behavior for the instance. Can be `MIGRATE` or `TERMINATE`, for more info, read [here](#)
- `automatic_restart` - (Optional) Specifies if the instance should be restarted if it was terminated by Compute Engine (not a user).

The `guest_accelerator` block supports:

- `type` (Required) - The accelerator type resource to expose to this instance. E.g. `nvidia-tesla-k80`.
- `count` (Required) - The number of the guest accelerator cards exposed to this instance.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `instance_id` - The server-assigned unique identifier of this instance.
- `metadata_fingerprint` - The unique fingerprint of the metadata.
- `self_link` - The URI of the created resource.
- `tags_fingerprint` - The unique fingerprint of the tags.
- `label_fingerprint` - The unique fingerprint of the labels.
- `cpu_platform` - The CPU platform used by this instance.
- `network_interface.0.address` - The internal ip address of the instance, either manually or dynamically assigned.
- `network_interface.0.access_config.0.assigned_nat_ip` - If the instance has an access config, either the given external ip (in the `nat_ip` field) or the ephemeral (generated) ip (if you didn't provide one).
- `attached_disk.0.disk_encryption_key_sha256` - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this resource.
- `boot_disk.disk_encryption_key_sha256` - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this resource.

- `disk.0.disk_encryption_key_sha256` - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this resource.

» Import

Note: The fields `boot_disk.0.disk_entrpytion_raw` and `attached_disk.*.disk_encryption_key_raw` cannot be imported automatically. The API doesn't return this information. If you are setting one of these fields in your config, you will need to update your state manually after importing the resource.

Instances can be imported using the `project`, `zone` and `name`, e.g.

```
$ terraform import google_compute_instance.default gcp-project/us-central1-a/test
```

» `google_compute_instance_from_template`

Manages a VM instance resource within GCE. For more information see the official documentation and API.

This resource is specifically to create a compute instance from a given `source_instance_template`. To create an instance without a template, use the `google_compute_instance` resource.

» Example Usage

```
resource "google_compute_instance_template" "tpl" {
  name = "template"
  machine_type = "n1-standard-1"

  disk {
    source_image = "debian-cloud/debian-8"
    auto_delete = true
    disk_size_gb = 100
    boot = true
  }

  network_interface {
    network = "default"
  }

  metadata {
    foo = "bar"
  }
}
```

```

    can_ip_forward = true
  }

resource "google_compute_instance_from_template" "tpl" {
  name          = "instance-from-template"
  zone          = "us-central1-a"

  source_instance_template = "${google_compute_instance_template.tpl.self_link}"

  // Override fields from instance template
  can_ip_forward = false
  labels {
    my_key      = "my_value"
  }
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.
- **source_instance_template** - (Required) Name or self link of an instance template to create the instance based on.

-
- **zone** - (Optional) The zone that the machine should be created in. If not set, the provider zone is used.

In addition to these, all arguments from `google_compute_instance` are supported as a way to override the properties in the template. All exported attributes from `google_compute_instance` are likewise exported here.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 6 minutes.
- **update** - Default is 6 minutes.
- **delete** - Default is 6 minutes.

» `google_compute_instance_group`

Creates a group of dissimilar Compute Engine virtual machine instances. For more information, see the official documentation and API

» Example Usage

» Empty instance group

```
resource "google_compute_instance_group" "test" {
  name          = "terraform-test"
  description   = "Terraform test instance group"
  zone          = "us-central1-a"
  network       = "${google_compute_network.default.self_link}"
}
```

» With instances and named ports

```
resource "google_compute_instance_group" "webservers" {
  name          = "terraform-webservers"
  description   = "Terraform test instance group"

  instances = [
    "${google_compute_instance.test.self_link}",
    "${google_compute_instance.test2.self_link}",
  ]

  named_port {
    name = "http"
    port = "8080"
  }

  named_port {
    name = "https"
    port = "8443"
  }

  zone = "us-central1-a"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the instance group. Must be 1-63 characters long and comply with RFC1035. Supported characters include lowercase letters, numbers, and hyphens.
- **zone** - (Required) The zone that this instance group should be created in.

-
- **description** - (Optional) An optional textual description of the instance group.
 - **instances** - (Optional) List of instances in the group. They should be given as self_link URLs. When adding instances they must all be in the same network and zone as the instance group.
 - **named_port** - (Optional) The named port configuration. See the section below for details on configuration.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
 - **network** - (Optional) The URL of the network the instance group is in. If this is different from the network where the instances are in, the creation fails. Defaults to the network where the instances are in (if neither **network** nor **instances** is specified, this field will be blank).

The **named_port** block supports:

- **name** - (Required) The name which the port will be mapped to.
- **port** - (Required) The port number to map the name to.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.
- **size** - The number of instances in the group.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 6 minutes
- **update** - Default is 6 minutes
- **delete** - Default is 6 minutes

» Import

Instance group can be imported using the `zone` and `name`, e.g.

```
$ terraform import google_compute_instance_group.webservers us-central1-a/terraform-webservers
```

» `google_compute_instance_group_manager`

The Google Compute Engine Instance Group Manager API creates and manages pools of homogeneous Compute Engine virtual machine instances from a common instance template. For more information, see the official documentation and API

Note: Use `google_compute_region_instance_group_manager` to create a regional (multi-zone) instance group manager.

» Example Usage with top level instance template

```
resource "google_compute_health_check" "autohealing" {
  name                = "autohealing-health-check"
  check_interval_sec = 5
  timeout_sec         = 5
  healthy_threshold   = 2
  unhealthy_threshold = 10                                # 50 seconds

  http_health_check {
    request_path = "/healthz"
    port         = "8080"
  }
}

resource "google_compute_instance_group_manager" "appserver" {
  name = "appserver-igm"

  base_instance_name = "app"
  instance_template  = "${google_compute_instance_template.appserver.self_link}"
  update_strategy    = "NONE"
  zone               = "us-central1-a"

  target_pools = ["${google_compute_target_pool.appserver.self_link}"]
  target_size  = 2

  named_port {
    name = "customHTTP"
  }
}
```

```

    port = 8888
  }

  auto_healing_policies {
    health_check      = "${google_compute_health_check.autohealing.self_link}"
    initial_delay_sec = 300
  }
}

```

» Example Usage with multiple Versions

```

resource "google_compute_instance_group_manager" "appserver" {
  name = "appserver-igm"

  base_instance_name = "app"
  update_strategy     = "NONE"
  zone                = "us-central1-a"

  target_size = 5

  version {
    instance_template = "${google_compute_instance_template.appserver.self_link}"
  }

  version {
    instance_template = "${google_compute_instance_template.appserver-canary.self_link}"
    target_size {
      fixed = 1
    }
  }
}

```

» Argument Reference

The following arguments are supported:

- **base_instance_name** - (Required) The base instance name to use for instances in this group. The value must be a valid RFC1035 name. Supported characters are lowercase letters, numbers, and hyphens (-). Instances are named by appending a hyphen and a random four-character string to the base instance name.
- **instance_template** - (Optional) The full URL to an instance template from which all new instances will be created. Conflicts with **version** (see documentation)

- **version** - (Optional) Application versions managed by this instance group. Each version deals with a specific instance template, allowing canary release scenarios. Conflicts with **instance_template**. Structure is documented below. Beware that exactly one version must not specify a target size. It means that versions with a target size will respect the setting, and the one without target size will be applied to all remaining Instances (top level **target_size** - each version **target_size**).
 - **name** - (Required) The name of the instance group manager. Must be 1-63 characters long and comply with RFC1035. Supported characters include lowercase letters, numbers, and hyphens.
 - **zone** - (Required) The zone that instances in this group should be created in.
-
- **description** - (Optional) An optional textual description of the instance group manager.
 - **named_port** - (Optional) The named port configuration. See the section below for details on configuration.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
 - **update_strategy** - (Optional, Default "RESTART") If the **instance_template** resource is modified, a value of "NONE" will prevent any of the managed instances from being restarted by Terraform. A value of "RESTART" will restart all of the instances at once. "ROLLING_UPDATE" is supported as [Beta feature]. A value of "ROLLING_UPDATE" requires **rolling_update_policy** block to be set
 - **target_size** - (Optional) The target number of running instances for this managed instance group. This value should always be explicitly set unless this resource is attached to an autoscaler, in which case it should never be set. Defaults to 0.
 - **target_pools** - (Optional) The full URL of all target pools to which new instances in the group are added. Updating the target pools attribute does not affect existing instances.
 - **wait_for_instances** - (Optional) Whether to wait for all instances to be created/updated before returning. Note that if this is set to true and the operation does not succeed, Terraform will continue trying until it times out.
-
- **auto_healing_policies** - (Optional, Beta) The autohealing policies for this managed instance group. You can specify only one value. Structure is documented below. For more information, see the official documentation.

- **rolling_update_policy** - (Optional, Beta) The update policy for this managed instance group. Structure is documented below. For more information, see the official documentation and API

The **rolling_update_policy** block supports:

```
rolling_update_policy{
  type = "PROACTIVE"
  minimal_action = "REPLACE"
  max_surge_percent = 20
  max_unavailable_fixed = 2
  min_ready_sec = 50
}
```

- **minimal_action** - (Required) - Minimal action to be taken on an instance. Valid values are "RESTART", "REPLACE"
- **type** - (Required) - The type of update. Valid values are "OPPORTUNISTIC", "PROACTIVE"
- **max_surge_fixed** - (Optional), The maximum number of instances that can be created above the specified targetSize during the update process. Conflicts with **max_surge_percent**. If neither is set, defaults to 1
- **max_surge_percent** - (Optional), The maximum number of instances(calculated as percentage) that can be created above the specified targetSize during the update process. Conflicts with **max_surge_fixed**.
- **max_unavailable_fixed** - (Optional), The maximum number of instances that can be unavailable during the update process. Conflicts with **max_unavailable_percent**. If neither is set, defaults to 1
- **max_unavailable_percent** - (Optional), The maximum number of instances(calculated as percentage) that can be unavailable during the update process. Conflicts with **max_unavailable_fixed**.
- **min_ready_sec** - (Optional), Minimum number of seconds to wait for after a newly created instance becomes available. This value must be from range [0, 3600]

The **named_port** block supports: (Include a **named_port** block for each named-port required).

- **name** - (Required) The name of the port.
- **port** - (Required) The port number.

The **auto_healing_policies** block supports:

- **health_check** - (Required) The health check resource that signals auto-healing.
- **initial_delay_sec** - (Required) The number of seconds that the managed instance group waits before it applies autohealing policies to new instances or recently recreated instances. Between 0 and 3600.

The **version** block supports:

```
version {
  name = "appserver-canary"
  instance_template = "${google_compute_instance_template.appserver-canary.self_link}"
  target_size {
    fixed = 1
  }
}

version {
  name = "appserver-canary"
  instance_template = "${google_compute_instance_template.appserver-canary.self_link}"
  target_size {
    percent = 20
  }
}
```

- **name** - (Required) - Version name.
- **instance_template** - (Required) - The full URL to an instance template from which all new instances of this version will be created.
- **target_size** - (Optional) - The number of instances calculated as a fixed number or a percentage depending on the settings. Structure is documented below.

The **target_size** block supports:

- **fixed** - (Optional), The number of instances which are managed for this version. Conflicts with **percent**.
- **percent** - (Optional), The number of instances (calculated as percentage) which are managed for this version. Conflicts with **fixed**.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **fingerprint** - The fingerprint of the instance group manager.
- **instance_group** - The full URL of the instance group created by the manager.

- `self_link` - The URL of the created resource.

» Import

Instance group managers can be imported using the `name`, e.g.

```
$ terraform import google_compute_instance_group_manager.appserver appserver-igm
```

» `google_compute_instance_template`

Manages a VM instance template resource within GCE. For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_instance_template" "default" {
  name          = "appserver-template"
  description   = "This template is used to create app server instances."

  tags = ["foo", "bar"]

  labels = {
    environment = "dev"
  }

  instance_description = "description assigned to instances"
  machine_type         = "n1-standard-1"
  can_ip_forward       = false

  scheduling {
    automatic_restart    = true
    on_host_maintenance = "MIGRATE"
  }

  // Create a new boot disk from an image
  disk {
    source_image = "debian-cloud/debian-8"
    auto_delete = true
    boot        = true
  }

  // Use an existing disk resource
  disk {
```

```

        source      = "foo_existing_disk"
        auto_delete = false
        boot        = false
    }

    network_interface {
        network = "default"
    }

    metadata {
        foo = "bar"
    }

    service_account {
        scopes = ["userinfo-email", "compute-ro", "storage-ro"]
    }
}

```

» Using with Instance Group Manager

Instance Templates cannot be updated after creation with the Google Cloud Platform API. In order to update an Instance Template, Terraform will destroy the existing resource and create a replacement. In order to effectively use an Instance Template resource with an Instance Group Manager resource, it's recommended to specify `create_before_destroy` in a lifecycle block. Either omit the Instance Template `name` attribute, or specify a partial name with `name_prefix`. Example:

```

resource "google_compute_instance_template" "instance_template" {
    name_prefix = "instance-template-"
    machine_type = "n1-standard-1"
    region      = "us-central1"

    // boot disk
    disk {
        # ...
    }

    // networking
    network_interface {
        # ...
    }

    lifecycle {
        create_before_destroy = true
    }
}

```

```

    }
  }

  resource "google_compute_instance_group_manager" "instance_group_manager" {
    name           = "instance-group-manager"
    instance_template = "${google_compute_instance_template.instance_template.self_link}"
    base_instance_name = "instance-group-manager"
    zone           = "us-central1-f"
    target_size     = "1"
  }

```

With this setup Terraform generates a unique name for your Instance Template and can then update the Instance Group manager without conflict before destroying the previous Instance Template.

» Argument Reference

Note that changing any field for this resource forces a new resource to be created.

The following arguments are supported:

- **disk** - (Required) Disks to attach to instances created from this template. This can be specified multiple times for multiple disks. Structure is documented below.
- **machine_type** - (Required) The machine type to create.

Note: If you want to update this value (resize the VM) after initial creation, you must set **allow_stopping_for_update** to **true**.

To create a machine with a custom type (such as extended memory), format the value like **custom-VCPUS-MEM_IN_MB** like **custom-6-20480** for 6 vCPU and 20GB of RAM.

-
- **name** - (Optional) The name of the instance template. If you leave this blank, Terraform will auto-generate a unique name.
 - **name_prefix** - (Optional) Creates a unique name beginning with the specified prefix. Conflicts with **name**.
 - **can_ip_forward** - (Optional) Whether to allow sending and receiving of packets with non-matching source or destination IPs. This defaults to false.
 - **description** - (Optional) A brief description of this resource.
 - **instance_description** - (Optional) A brief description to use for instances created from this template.

- **labels** - (Optional) A set of key/value label pairs to assign to instances created from this template,
- **metadata** - (Optional) Metadata key/value pairs to make available from within instances created from this template.
- **metadata_startup_script** - (Optional) An alternative to using the startup-script metadata key, mostly to match the compute_instance resource. This replaces the startup-script metadata key on the created instance and thus the two mechanisms are not allowed to be used simultaneously.
- **network_interface** - (Required) Networks to attach to instances created from this template. This can be specified multiple times for multiple networks. Structure is documented below.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **region** - (Optional) An instance template is a global resource that is not bound to a zone or a region. However, you can still specify some regional resources in an instance template, which restricts the template to the region where that resource resides. For example, a custom **subnetwork** resource is tied to a specific region. Defaults to the region of the Provider if no value is given.
- **scheduling** - (Optional) The scheduling strategy to use. More details about this configuration option are detailed below.
- **service_account** - (Optional) Service account to attach to the instance. Structure is documented below.
- **tags** - (Optional) Tags to attach to the instance.
- **guest_accelerator** - (Optional) List of the type and count of accelerator cards attached to the instance. Structure documented below.
- **min_cpu_platform** - (Optional) Specifies a minimum CPU platform. Applicable values are the friendly names of CPU platforms, such as **Intel Haswell** or **Intel Skylake**. See the complete list [here](#).

The **disk** block supports:

- **auto_delete** - (Optional) Whether or not the disk should be auto-deleted. This defaults to true.
- **boot** - (Optional) Indicates that this is a boot disk.
- **device_name** - (Optional) A unique device name that is reflected into the `/dev/` tree of a Linux operating system running within the instance. If not specified, the server chooses a default device name to apply to this disk.

- **disk_name** - (Optional) Name of the disk. When not provided, this defaults to the name of the instance.
- **source_image** - (Required if source not set) The image from which to initialize this disk. This can be one of: the image's **self_link**, **projects/{project}/global/images/{image}**, **projects/{project}/global/images/family/{family}**, **global/images/{image}**, **global/images/family/{family}**, **family/{family}**, **{project}/{family}**, **{project}/{image}**, **{family}**, or **{image}**.
- **interface** - (Optional) Specifies the disk interface to use for attaching this disk.
- **mode** - (Optional) The mode in which to attach this disk, either **READ_WRITE** or **READ_ONLY**. If you are attaching or creating a boot disk, this must read-write mode.
- **source** - (Required if **source_image** not set) The name of the disk (such as those managed by **google_compute_disk**) to attach. This cannot be a regional disk.
- **disk_type** - (Optional) The GCE disk type. Can be either **"pd-ssd"**, **"local-ssd"**, or **"pd-standard"**.
- **disk_size_gb** - (Optional) The size of the image in gigabytes. If not specified, it will inherit the size of its base image.
- **type** - (Optional) The type of GCE disk, can be either **"SCRATCH"** or **"PERSISTENT"**.

The **network_interface** block supports:

- **network** - (Optional) The name or **self_link** of the network to attach this interface to. Use **network** attribute for Legacy or Auto subnetted networks and **subnetwork** for custom subnetted networks.
- **subnetwork** - (Optional) the name of the subnetwork to attach this interface to. The subnetwork must exist in the same **region** this instance will be created in. Either **network** or **subnetwork** must be provided.
- **subnetwork_project** - (Optional) The ID of the project in which the subnetwork belongs. If it is not provided, the provider project is used.
- **address** - (Optional) The private IP address to assign to the instance. If empty, the address will be automatically assigned.
- **access_config** - (Optional) Access configurations, i.e. IPs via which this instance can be accessed via the Internet. Omit to ensure that the instance is not accessible from the Internet (this means that ssh provisioners will not work unless you are running Terraform can send traffic to the instance's network (e.g. via tunnel or because it is running on another cloud instance on that network). This block can be repeated multiple times. Structure documented below.

- **alias_ip_range** - (Optional) An array of alias IP ranges for this network interface. Can only be specified for network interfaces on subnet-mode networks. Structure documented below.

The **access_config** block supports:

- **nat_ip** - (Optional) The IP address that will be 1:1 mapped to the instance's network ip. If not given, one will be generated.
- **network_tier** - (Optional) The networking tier used for configuring this instance template. This field can take the following values: PREMIUM or STANDARD. If this field is not specified, it is assumed to be PREMIUM.

The **alias_ip_range** block supports:

- **ip_cidr_range** - The IP CIDR range represented by this alias IP range. This IP CIDR range must belong to the specified subnetwork and cannot contain IP addresses reserved by system or used by other network interfaces. At the time of writing only a netmask (e.g. /24) may be supplied, with a CIDR format resulting in an API error.
- **subnetwork_range_name** - (Optional) The subnetwork secondary range name specifying the secondary range from which to allocate the IP CIDR range for this alias IP range. If left unspecified, the primary range of the subnetwork will be used.

The **service_account** block supports:

- **email** - (Optional) The service account e-mail address. If not given, the default Google Compute Engine service account is used.
- **scopes** - (Required) A list of service scopes. Both OAuth2 URLs and gcloud short names are supported. To allow full access to all Cloud APIs, use the **cloud-platform** scope. See a complete list of scopes [here](#).

The **scheduling** block supports:

- **automatic_restart** - (Optional) Specifies whether the instance should be automatically restarted if it is terminated by Compute Engine (not terminated by a user). This defaults to true.
- **on_host_maintenance** - (Optional) Defines the maintenance behavior for this instance.
- **preemptible** - (Optional) Allows instance to be preempted. This defaults to false. Read more on this [here](#).

The **guest_accelerator** block supports:

- **type** (Required) - The accelerator type resource to expose to this instance. E.g. **nvidia-tesla-k80**.
- **count** (Required) - The number of the guest accelerator cards exposed to this instance.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `metadata_fingerprint` - The unique fingerprint of the metadata.
- `self_link` - The URI of the created resource.
- `tags_fingerprint` - The unique fingerprint of the tags.

» Import

Instance templates can be imported using the `name`, e.g.

```
$ terraform import google_compute_instance_template.default appserver-template
```

» `google_compute_network`

Manages a network within GCE. For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_network" "default" {  
  name          = "foobar"  
  auto_create_subnetworks = "true"  
}
```

» Argument Reference

The following arguments are supported:

- `name` - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.
-
- `auto_create_subnetworks` - (Optional) If set to true, this network will be created in auto subnet mode, and Google will create a subnet for each region automatically. If set to false, a custom subnetted network will be created that can support `google_compute_subnetwork` resources. Defaults to true.

- `ipv4_range` - (Optional) If set to a CIDR block, uses the legacy VPC API with the specified range. This API is deprecated. If set, `auto_create_subnetworks` must be explicitly set to false.
- `routing_mode` - (Optional) Sets the network-wide routing mode for Cloud Routers to use. Accepted values are "GLOBAL" or "REGIONAL". Defaults to "REGIONAL". Refer to the Cloud Router documentation for more details.
- `description` - (Optional) A brief description of this resource.
- `project` - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `gateway_ipv4` - The IPv4 address of the gateway.
- `name` - The unique name of the network.
- `self_link` - The URI of the created resource.

» Import

Networks can be imported using the `name`, e.g.

```
$ terraform import google_compute_network.default foobar
```

» google_compute_network_peering

Manages a network peering within GCE. For more information see the official documentation and API.

Note: Both network must create a peering with each other for the peering to be functional.

Note: Subnets IP ranges across peered VPC networks cannot overlap.

» Example Usage

```
resource "google_compute_network_peering" "peering1" {
  name = "peering1"
  network = "${google_compute_network.default.self_link}"
  peer_network = "${google_compute_network.other.self_link}"
}
```

```

}

resource "google_compute_network_peering" "peering2" {
  name = "peering2"
  network = "${google_compute_network.other.self_link}"
  peer_network = "${google_compute_network.default.self_link}"
}

resource "google_compute_network" "default" {
  name = "foobar"
  auto_create_subnetworks = "false"
}

resource "google_compute_network" "other" {
  name = "other"
  auto_create_subnetworks = "false"
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the peering.
- **network** - (Required) Resource link of the network to add a peering to.
- **peer_network** - (Required) Resource link of the peer network.
- **auto_create_routes** - (Optional) If set to **true**, the routes between the two networks will be created and managed automatically. Defaults to **true**.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **state** - State for the peering.
- **state_details** - Details about the current state of the peering.

» google_compute_project_metadata

Manages metadata common to all instances for a project in GCE. For more information see the official documentation and API.

Note: If you want to manage only single key/value pairs within the project metadata rather than the entire set, then use `google_compute_project_metadata_item`.

» Example Usage

```
resource "google_compute_project_metadata" "default" {  
  metadata {  
    foo = "bar"  
    fizz = "buzz"  
    "13" = "42"  
  }  
}
```

» Argument Reference

The following arguments are supported:

- **metadata** - (Required) A series of key value pairs. Changing this resource updates the GCE state.
-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» `google_compute_project_metadata_item`

Manages a single key/value pair on metadata common to all instances for a project in GCE. Using `google_compute_project_metadata_item` lets you manage a single key/value setting in Terraform rather than the entire project metadata map.

» Example Usage

```
resource "google_compute_project_metadata_item" "default" {  
  key = "my_metadata"  
  value = "my_value"  
}
```

» Argument Reference

The following arguments are supported:

- **key** - (Required) The metadata key to set.
 - **value** - (Required) The value to set for the given metadata key.
-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» Import

Project metadata items can be imported using the **key**, e.g.

```
$ terraform import google_compute_project_metadata_item.default my_metadata
```

» google_compute_region_autoscaler

Represents an Autoscaler resource.

Autoscalers allow you to automatically scale virtual machine instances in managed instance groups according to an autoscaling policy that you define.

To get more information about RegionAutoscaler, see:

- API documentation
- How-to Guides
 - Autoscaling Groups of Instances

» Example Usage

```
resource "google_compute_instance_template" "foobar" {  
  name          = "foobar"  
  machine_type  = "n1-standard-1"  
  can_ip_forward = false  
  
  tags = ["foo", "bar"]  
}
```



```

disk {
  source_image = "debian-cloud/debian-8"
}

network_interface {
  network = "default"
}

metadata {
  foo = "bar"
}

service_account {
  scopes = ["userinfo-email", "compute-ro", "storage-ro"]
}

resource "google_compute_target_pool" "foobar" {
  name = "foobar"
}

resource "google_compute_region_instance_group_manager" "foobar" {
  name      = "foobar"
  region    = "us-central1"

  instance_template = "${google_compute_instance_template.foobar.self_link}"
  target_pools       = ["${google_compute_target_pool.foobar.self_link}"]
  base_instance_name = "foobar"
}

resource "google_compute_region_autoscaler" "foobar" {
  name      = "scaler"
  region    = "us-central1"
  target    = "${google_compute_region_instance_group_manager.foobar.self_link}"

  autoscaling_policy = {
    max_replicas    = 5
    min_replicas    = 1
    cooldown_period = 60

    cpu_utilization {
      target = 0.5
    }
  }
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. The name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
- **autoscaling_policy** - (Required) The configuration parameters for the autoscaling algorithm. You can define one or more of the policies for an autoscaler: `cpuUtilization`, `customMetricUtilizations`, and `loadBalancingUtilization`. If none of these are specified, the default will be to autoscale based on `cpuUtilization` to 0.6 or 60%. Structure is documented below.
- **target** - (Required) URL of the managed instance group that this autoscaler will scale.

The **autoscaling_policy** block supports:

- **min_replicas** - (Required) The minimum number of replicas that the autoscaler can scale down to. This cannot be less than 0. If not provided, autoscaler will choose a default value depending on maximum number of instances allowed.
- **max_replicas** - (Required) The maximum number of instances that the autoscaler can scale up to. This is required when creating or updating an autoscaler. The maximum number of replicas should not be lower than minimal number of replicas.
- **cooldown_period** - (Optional) The number of seconds that the autoscaler should wait before it starts collecting information from a new instance. This prevents the autoscaler from collecting information when the instance is initializing, during which the collected usage would not be reliable. The default time autoscaler waits is 60 seconds. Virtual machine initialization times might vary because of numerous factors. We recommend that you test how long an instance may take to initialize. To do this, create an instance and time the startup process.
- **cpu_utilization** - (Optional) Defines the CPU utilization policy that allows the autoscaler to scale based on the average CPU utilization of a managed instance group. Structure is documented below.
- **metric** - (Optional) Defines the CPU utilization policy that allows the autoscaler to scale based on the average CPU utilization of a managed instance group. Structure is documented below.
- **load_balancing_utilization** - (Optional) Configuration parameters of autoscaling based on a load balancer. Structure is documented below.

The `cpu_utilization` block supports:

- **target** - (Required) The target CPU utilization that the autoscaler should maintain. Must be a float value in the range (0, 1]. If not specified, the default is 0.6. If the CPU level is below the target utilization, the autoscaler scales down the number of instances until it reaches the minimum number of instances you specified or until the average CPU of your instances reaches the target utilization. If the average CPU is above the target utilization, the autoscaler scales up until it reaches the maximum number of instances you specified or until the average utilization reaches the target utilization.

The `metric` block supports:

- **name** - (Required) The identifier (type) of the Stackdriver Monitoring metric. The metric cannot have negative values. The metric must have a value type of INT64 or DOUBLE.
- **target** - (Required) The target value of the metric that autoscaler should maintain. This must be a positive value. A utilization metric scales number of virtual machines handling requests to increase or decrease proportionally to the metric. For example, a good metric to use as a utilization-Target is `www.googleapis.com/compute/instance/network/received_bytes_count`. The autoscaler will work to keep this value constant for each of the instances.
- **type** - (Required) Defines how target utilization value is expressed for a Stackdriver Monitoring metric. Either GAUGE, DELTA_PER_SECOND, or DELTA_PER_MINUTE.

The `load_balancing_utilization` block supports:

- **target** - (Required) Fraction of backend capacity utilization (set in HTTP(s) load balancing configuration) that autoscaler should maintain. Must be a positive float value. If not defined, the default is 0.8.

-
- **description** - (Optional) An optional description of this resource.
 - **region** - (Optional) URL of the region where the instance group resides.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.

- `self_link` - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- `create` - Default is 4 minutes.
- `update` - Default is 4 minutes.
- `delete` - Default is 4 minutes.

» Import

RegionAutoscaler can be imported using any of these accepted formats:

```
$ terraform import google_compute_region_autoscaler.default projects/{{project}}/regions/{{region}}/{{name}}
$ terraform import google_compute_region_autoscaler.default {{region}}/{{name}}
$ terraform import google_compute_region_autoscaler.default {{project}}/{{region}}/{{name}}
$ terraform import google_compute_region_autoscaler.default {{name}}
```

» google_compute_region_backend_service

A Region Backend Service defines a regionally-scoped group of virtual machines that will serve traffic for load balancing. For more information see the official documentation and API.

Note: Region backend services can only be used when using internal load balancing. For external load balancing, use `google_compute_backend_service` instead.

» Example Usage

```
resource "google_compute_region_backend_service" "foobar" {
  name           = "blablah"
  description    = "Hello World 1234"
  protocol       = "TCP"
  timeout_sec    = 10
  session_affinity = "CLIENT_IP"

  backend {
    group = "${google_compute_region_instance_group_manager.foo.instance_group}"
  }

  health_checks = ["${google_compute_health_check.default.self_link}"]
}
```

```

}

resource "google_compute_region_instance_group_manager" "foo" {
  name                = "terraform-test"
  instance_template   = "${google_compute_instance_template.foobar.self_link}"
  base_instance_name  = "foobar"
  region              = "us-central1"
  target_size         = 1
}

resource "google_compute_instance_template" "foobar" {
  name                = "terraform-test"
  machine_type        = "n1-standard-1"

  network_interface {
    network = "default"
  }

  disk {
    source_image = "debian-cloud/debian-8"
    auto_delete = true
    boot        = true
  }
}

resource "google_compute_health_check" "default" {
  name                = "test"
  check_interval_sec = 1
  timeout_sec         = 1

  tcp_health_check {
    port = "80"
  }
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the backend service.
- **health_checks** - (Required) Specifies a list of health checks for checking the health of the backend service. Currently at most one health check can be specified, and a health check is required.

- **backend** - (Optional) The list of backends that serve this BackendService. Structure is documented below.
- **description** - (Optional) The textual description for the backend service.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **protocol** - (Optional) The protocol for incoming requests. Defaults to TCP.
- **session_affinity** - (Optional) How to distribute load. Options are NONE (no affinity), CLIENT_IP, CLIENT_IP_PROTO, or CLIENT_IP_PORT_PROTO. Defaults to NONE.
- **region** - (Optional) The Region in which the created address should reside. If it is not provided, the provider region is used.
- **timeout_sec** - (Optional) The number of secs to wait for a backend to respond to a request before considering the request failed. Defaults to 30.
- **connection_draining_timeout_sec** - (Optional) Time for which instance will be drained (not accept new connections, but still work to finish started ones). Defaults to 0.

The **backend** block supports:

- **group** - (Required) The name or URI of a Compute Engine instance group (`google_compute_region_instance_group_manager.xyz.instance_group`) that can receive traffic. Instance groups must contain at least one instance.
- **description** - (Optional) Textual description for the backend.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **fingerprint** - The fingerprint of the backend service.
- **self_link** - The URI of the created resource.

» `google__compute__region__disk`

Persistent disks are durable storage devices that function similarly to the physical disks in a desktop or a server. Compute Engine manages the hardware behind these devices to ensure data redundancy and optimize performance for you. Persistent disks are available as either standard hard disk drives (HDD) or solid-state drives (SSD).

Persistent disks are located independently from your virtual machine instances, so you can detach or move persistent disks to keep your data even after you delete your instances. Persistent disk performance scales automatically with size, so you can resize your existing persistent disks or add more persistent disks to an instance to meet your performance and storage space requirements.

Add a persistent disk to your instance when you need reliable and affordable storage with consistent performance characteristics.

To get more information about `RegionDisk`, see:

- API documentation
- How-to Guides
 - Adding or Resizing Regional Persistent Disks

Warning: All arguments including the disk encryption key will be stored in the raw state as plain-text. Read more about sensitive data in state.

» Example Usage

```
resource "google_compute_disk" "disk" {
  name = "my-disk"
  image = "debian-cloud/debian-9"
  size = 50
  type = "pd-ssd"
  zone = "us-central1-a"
}

resource "google_compute_snapshot" "snapdisk" {
  name = "my-disk-snapshot"
  source_disk = "${google_compute_disk.disk.name}"
  zone = "us-central1-a"
}

resource "google_compute_region_disk" "regiondisk" {
  name = "my-regional-disk"
  snapshot = "${google_compute_snapshot.snapdisk.self_link}"
  type = "pd-ssd"
  region = "us-central1"

  replica_zones = ["us-central1-a", "us-central1-f"]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
- **replica_zones** - (Required) URLs of the zones where the disk should be replicated to.

-
- **description** - (Optional) An optional description of this resource. Provide this property when you create the resource.
 - **labels** - (Optional) Labels to apply to this disk. A list of key->value pairs.
 - **size** - (Optional) Size of the persistent disk, specified in GB. You can specify this field when creating a persistent disk using the `sourceImage` or `sourceSnapshot` parameter, or specify it alone to create an empty persistent disk. If you specify this field along with `sourceImage` or `sourceSnapshot`, the value of `sizeGb` must not be less than the size of the `sourceImage` or the size of the snapshot.
 - **type** - (Optional) URL of the disk type resource describing which disk type to use to create the disk. Provide this when creating the disk.
 - **region** - (Optional) A reference to the region where the disk resides.
 - **disk_encryption_key** - (Optional) Encrypts the disk using a customer-supplied encryption key. After you encrypt a disk with a customer-supplied key, you must provide the same key if you use the disk later (e.g. to create a disk snapshot or an image, or to attach the disk to a virtual machine). Customer-supplied encryption keys do not protect access to metadata of the disk. If you do not provide an encryption key when creating the disk, then the disk will be encrypted using an automatically generated key and you do not need to provide a key to use the disk later. Structure is documented below.
 - **snapshot** - (Optional) The source snapshot used to create this disk. You can provide this as a partial or full URL to the resource. For example, the following are valid values:

- `https://www.googleapis.com/compute/v1/projects/project/global/snapshots/snapshot`
- `projects/project/global/snapshots/snapshot`
- `global/snapshots/snapshot`
- `snapshot`

- **source_snapshot_encryption_key** - (Optional) The customer-supplied encryption key of the source snapshot. Required if the source snapshot is protected by a customer-supplied encryption key. Structure is documented below.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

The **disk_encryption_key** block supports:

- **raw_key** - (Optional) Specifies a 256-bit customer-supplied encryption key, encoded in RFC 4648 base64 to either encrypt or decrypt this resource.
- **sha256** - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this resource.

The **source_snapshot_encryption_key** block supports:

- **raw_key** - (Optional) Specifies a 256-bit customer-supplied encryption key, encoded in RFC 4648 base64 to either encrypt or decrypt this resource.
- **sha256** - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this resource.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **label_fingerprint** - The fingerprint used for optimistic locking of this resource. Used internally during updates.
- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **last_attach_timestamp** - Last attach timestamp in RFC3339 text format.
- **last_detach_timestamp** - Last detach timestamp in RFC3339 text format.
- **users** - Links to the users of the disk (attached instances) in form: `project/zones/zone/instances/instance`
- **source_snapshot_id** - The unique ID of the snapshot used to create this disk. This value identifies the exact snapshot that was used to create this persistent disk. For example, if you created the persistent disk from a snapshot that was later deleted and recreated under the same name, the source snapshot ID would identify the exact version of the snapshot that was used.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- `create` - Default is 5 minutes.
- `update` - Default is 4 minutes.
- `delete` - Default is 4 minutes.

» Import

RegionDisk can be imported using any of these accepted formats:

```
$ terraform import google_compute_region_disk.default projects/{{project}}/regions/{{region}}/disks/{{name}}
$ terraform import google_compute_region_disk.default {{project}}/{{region}}/{{name}}
$ terraform import google_compute_region_disk.default {{name}}
```

» google_compute_region_instance_group_manager

The Google Compute Engine Regional Instance Group Manager API creates and manages pools of homogeneous Compute Engine virtual machine instances from a common instance template. For more information, see the official documentation and API

Note: Use `google_compute_instance_group_manager` to create a single-zone instance group manager.

» Example Usage with top level instance template

```
resource "google_compute_health_check" "autohealing" {
  name                = "autohealing-health-check"
  check_interval_sec  = 5
  timeout_sec         = 5
  healthy_threshold    = 2
  unhealthy_threshold = 10                                # 50 seconds

  http_health_check {
    request_path = "/healthz"
    port         = "8080"
  }
}

resource "google_compute_region_instance_group_manager" "appserver" {
  name = "appserver-igm"
```

```

base_instance_name      = "app"
instance_template       = "${google_compute_instance_template.appserver.self_link}"
region                 = "us-central1"
distribution_policy_zones = ["us-central1-a", "us-central1-f"]

target_pools = ["${google_compute_target_pool.appserver.self_link}"]
target_size  = 2

named_port {
  name = "custom"
  port = 8888
}

auto_healing_policies {
  health_check      = "${google_compute_health_check.autohealing.self_link}"
  initial_delay_sec = 300
}
}

```

» Example Usage with multiple Versions

```

resource "google_compute_region_instance_group_manager" "appserver" {
  name = "appserver-igm"

  base_instance_name = "app"
  update_strategy     = "NONE"
  region              = "us-central1"

  target_size = 5

  version {
    instance_template = "${google_compute_instance_template.appserver.self_link}"
  }

  version {
    instance_template = "${google_compute_instance_template.appserver-canary.self_link}"
    target_size {
      fixed = 1
    }
  }
}

```

» Argument Reference

The following arguments are supported:

- **base_instance_name** - (Required) The base instance name to use for instances in this group. The value must be a valid RFC1035 name. Supported characters are lowercase letters, numbers, and hyphens (-). Instances are named by appending a hyphen and a random four-character string to the base instance name.
 - **instance_template** - (Optional) The full URL to an instance template from which all new instances will be created. Conflicts with **version** (see documentation)
 - **version** - (Optional) Application versions managed by this instance group. Each version deals with a specific instance template, allowing canary release scenarios. Conflicts with **instance_template**. Structure is documented below. Beware that exactly one version must not specify a target size. It means that versions with a target size will respect the setting, and the one without target size will be applied to all remaining Instances (top level **target_size** - each version **target_size**).
 - **name** - (Required) The name of the instance group manager. Must be 1-63 characters long and comply with RFC1035. Supported characters include lowercase letters, numbers, and hyphens.
 - **region** - (Required) The region where the managed instance group resides.
-
- **description** - (Optional) An optional textual description of the instance group manager.
 - **named_port** - (Optional) The named port configuration. See the section below for details on configuration.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
 - **update_strategy** - (Optional, Default "NONE") If the **instance_template** resource is modified, a value of "NONE" will prevent any of the managed instances from being restarted by Terraform. A value of "ROLLING_UPDATE" is supported as [Beta feature]. A value of "ROLLING_UPDATE" requires **rolling_update_policy** block to be set
 - **target_size** - (Optional) The target number of running instances for this managed instance group. This value should always be explicitly set unless this resource is attached to an autoscaler, in which case it should never be set. Defaults to 0.

- **target_pools** - (Optional) The full URL of all target pools to which new instances in the group are added. Updating the target pools attribute does not affect existing instances.
- **wait_for_instances** - (Optional) Whether to wait for all instances to be created/updated before returning. Note that if this is set to true and the operation does not succeed, Terraform will continue trying until it times out.

-
- **auto_healing_policies** - (Optional, Beta) The autohealing policies for this managed instance group. You can specify only one value. Structure is documented below. For more information, see the official documentation.
 - **rolling_update_policy** - (Optional, Beta) The update policy for this managed instance group. Structure is documented below. For more information, see the official documentation and API
 - **distribution_policy_zones** - (Optional, Beta) The distribution policy for this managed instance group. You can specify one or more values. For more information, see the official documentation.
-

The **rolling_update_policy** block supports:

```
rolling_update_policy{
  type = "PROACTIVE"
  minimal_action = "REPLACE"
  max_surge_percent = 20
  max_unavailable_fixed = 2
  min_ready_sec = 50
}
```

- **minimal_action** - (Required) - Minimal action to be taken on an instance. Valid values are "RESTART", "REPLACE"
- **type** - (Required) - The type of update. Valid values are "OPPORTUNISTIC", "PROACTIVE"
- **max_surge_fixed** - (Optional), The maximum number of instances that can be created above the specified targetSize during the update process. Conflicts with **max_surge_percent**. It has to be either 0 or at least equal to the number of zones. If fixed values are used, at least one of **max_unavailable_fixed** or **max_surge_fixed** must be greater than 0.
- **max_surge_percent** - (Optional), The maximum number of instances(calculated as percentage) that can be created above the specified targetSize during the update process. Conflicts with **max_surge_fixed**. Percent value is only allowed for regional managed instance groups with size at least 10.

- **max_unavailable_fixed** - (Optional), The maximum number of instances that can be unavailable during the update process. Conflicts with **max_unavailable_percent**. It has to be either 0 or at least equal to the number of zones. If fixed values are used, at least one of **max_unavailable_fixed** or **max_surge_fixed** must be greater than 0.
- **max_unavailable_percent** - (Optional), The maximum number of instances(calculated as percentage) that can be unavailable during the update process. Conflicts with **max_unavailable_fixed**. Percent value is only allowed for regional managed instance groups with size at least 10.
- **min_ready_sec** - (Optional), Minimum number of seconds to wait for after a newly created instance becomes available. This value must be from range [0, 3600]

The **named_port** block supports: (Include a **named_port** block for each named-port required).

- **name** - (Required) The name of the port.
- **port** - (Required) The port number.

The **auto_healing_policies** block supports:

- **health_check** - (Required) The health check resource that signals auto-healing.
- **initial_delay_sec** - (Required) The number of seconds that the managed instance group waits before it applies autohealing policies to new instances or recently recreated instances. Between 0 and 3600.

The **version** block supports:

```
version {
  name = "appserver-canary"
  instance_template = "${google_compute_instance_template.appserver-canary.self_link}"
  target_size {
    fixed = 1
  }
}

version {
  name = "appserver-canary"
  instance_template = "${google_compute_instance_template.appserver-canary.self_link}"
  target_size {
    percent = 20
  }
}
```

- **name** - (Required) - Version name.
- **instance_template** - (Required) - The full URL to an instance template from which all new instances of this version will be created.
- **target_size** - (Optional) - The number of instances calculated as a fixed number or a percentage depending on the settings. Structure is documented below.

The **target_size** block supports:

- **fixed** - (Optional), The number of instances which are managed for this version. Conflicts with **percent**.
- **percent** - (Optional), The number of instances (calculated as percentage) which are managed for this version. Conflicts with **fixed**.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **fingerprint** - The fingerprint of the instance group manager.
- **instance_group** - The full URL of the instance group created by the manager.
- **self_link** - The URL of the created resource.

» Import

Instance group managers can be imported using the **name**, e.g.

```
$ terraform import google_compute_region_instance_group_manager.appserver appserver-igm
```

» google__compute__route

Represents a Route resource.

A route is a rule that specifies how certain packets should be handled by the virtual network. Routes are associated with virtual machines by tag, and the set of routes for a particular virtual machine is called its routing table. For each packet leaving a virtual machine, the system searches that virtual machine's routing table for a single best matching route.

Routes match packets by destination IP address, preferring smaller or more specific ranges over larger ones. If there is a tie, the system selects the route with the smallest priority value. If there is still a tie, it uses the layer three and

four packet headers to select just one of the remaining matching routes. The packet is then forwarded as specified by the `next_hop` field of the winning route -- either to another virtual machine destination, a virtual machine gateway or a Compute Engine-operated gateway. Packets that do not match any route in the sending virtual machine's routing table will be dropped.

A Route resource must have exactly one specification of either `nextHopGateway`, `nextHopInstance`, `nextHopIp`, or `nextHopVpnTunnel`.

To get more information about Route, see:

- API documentation
- How-to Guides
 - Using Routes

» Example Usage

```
resource "google_compute_network" "default" {
  name = "compute-network"
}

resource "google_compute_subnetwork" "default" {
  name          = "compute-subnetwork"
  ip_cidr_range = "10.0.0.0/16"
  network       = "${google_compute_network.default.self_link}"
  region       = "us-central1"
}

resource "google_compute_route" "default" {
  name          = "network-route"
  dest_range    = "15.0.0.0/24"
  network       = "${google_compute_network.foobar.name}"
  next_hop_ip   = "10.0.1.5"
  priority      = 100
}
```

» Argument Reference

The following arguments are supported:

- **dest_range** - (Required) The destination range of outgoing packets that this route applies to. Only IPv4 is supported.
- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long

and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.

- **network** - (Required) The network that this route applies to.

-
- **description** - (Optional) An optional description of this resource. Provide this property when you create the resource.

- **priority** - (Optional) The priority of this route. Priority is used to break ties in cases where there is more than one matching route of equal prefix length. In the case of two routes with equal prefix length, the one with the lowest-numbered priority value wins. Default value is 1000. Valid range is 0 through 65535.

- **tags** - (Optional) A list of instance tags to which this route applies.

- **next_hop_gateway** - (Optional) URL to a gateway that should handle matching packets. Currently, you can only specify the internet gateway, using a full or partial valid URL:

- `https://www.googleapis.com/compute/v1/projects/project/global/gateways/default-internet-gateway`
- `projects/project/global/gateways/default-internet-gateway`
- `global/gateways/default-internet-gateway`
- The string `default-internet-gateway`.

- **next_hop_instance** - (Optional) URL to an instance that should handle matching packets. You can specify this as a full or partial URL. For example:

- `https://www.googleapis.com/compute/v1/projects/project/zones/zone/instances/instance`
- `projects/project/zones/zone/instances/instance`
- `zones/zone/instances/instance`
- Just the instance name, with the zone in `next_hop_instance_zone`.

- **next_hop_ip** - (Optional) Network IP address of an instance that should handle matching packets.

- **next_hop_vpn_tunnel** - (Optional) URL to a VpnTunnel that should handle matching packets.

- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

- **next_hop_instance_zone** - (Optional when `next_hop_instance` is specified) The zone of the instance specified in `next_hop_instance`. Omit if `next_hop_instance` is specified as a URL.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `next_hop_network` - URL to a Network that should handle matching packets.
- `self_link` - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- `create` - Default is 4 minutes.
- `delete` - Default is 4 minutes.

» Import

Route can be imported using any of these accepted formats:

```
$ terraform import google_compute_route.default projects/{{project}}/global/routes/{{name}}
$ terraform import google_compute_route.default {{project}}/{{name}}
$ terraform import google_compute_route.default {{name}}
```

» google_compute_router

Represents a Router resource.

To get more information about Router, see:

- API documentation
- How-to Guides
 - Google Cloud Router

» Example Usage

```
resource "google_compute_network" "foobar" {
  name                = "my-network"
  auto_create_subnetworks = false
}

resource "google_compute_router" "foobar" {
  name    = "my-router"
  network = "${google_compute_network.foobar.name}"
}
```

```

bgp {
  asn          = 64514
  advertise_mode = "CUSTOM"
  advertised_groups = ["ALL_SUBNETS"]
  advertised_ip_ranges {
    range = "1.2.3.4"
  }
  advertised_ip_ranges {
    range = "6.7.0.0/16"
  }
}
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
 - **network** - (Required) A reference to the network to which this router belongs.
-
- **description** - (Optional) An optional description of this resource.
 - **bgp** - (Optional) BGP information specific to this router. Structure is documented below.
 - **region** - (Optional) Region where the router resides.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

The **bgp** block supports:

- **asn** - (Required) Local BGP Autonomous System Number (ASN). Must be an RFC6996 private ASN, either 16-bit or 32-bit. The value will be fixed for this router resource. All VPN tunnels that link to this router will have the same local ASN.
- **advertise_mode** - (Optional) User-specified flag to indicate which mode to use for advertisement. Valid values of this enum field are: `DEFAULT`, `CUSTOM`

- **advertised_groups** - (Optional) User-specified list of prefix groups to advertise in custom mode. This field can only be populated if advertiseMode is CUSTOM and is advertised to all peers of the router. These groups will be advertised in addition to any specified prefixes. Leave this field blank to advertise no custom groups. This enum field has the one valid value: ALL_SUBNETS
- **advertised_ip_ranges** - (Optional) User-specified list of individual IP ranges to advertise in custom mode. This field can only be populated if advertiseMode is CUSTOM and is advertised to all peers of the router. These IP ranges will be advertised in addition to any specified groups. Leave this field blank to advertise no custom IP ranges. Structure is documented below.

The **advertised_ip_ranges** block supports:

- **range** - (Optional) The IP range to advertise. The value must be a CIDR-formatted string.
- **description** - (Optional) User-specified description for the IP range.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

Router can be imported using any of these accepted formats:

```
$ terraform import google_compute_router.default projects/{{project}}/regions/{{region}}/routers/{{name}}
$ terraform import google_compute_router.default {{region}}/{{name}}
$ terraform import google_compute_router.default {{project}}/{{region}}/{{name}}
$ terraform import google_compute_router.default {{name}}
```

» `google_compute_router_interface`

Manages a Cloud Router interface. For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_router_interface" "foobar" {  
  name      = "interface-1"  
  router    = "router-1"  
  region    = "us-central1"  
  ip_range  = "169.254.1.1/30"  
  vpn_tunnel = "tunnel-1"  
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the interface, required by GCE. Changing this forces a new interface to be created.
 - **router** - (Required) The name of the router this interface will be attached to. Changing this forces a new interface to be created.
 - **vpn_tunnel** - (Required) The name or resource link to the VPN tunnel this interface will be linked to. Changing this forces a new interface to be created.
-
- **ip_range** - (Optional) IP address and range of the interface. The IP range must be in the RFC3927 link-local IP space. Changing this forces a new interface to be created.
 - **project** - (Optional) The ID of the project in which this interface's router belongs. If it is not provided, the provider project is used. Changing this forces a new interface to be created.
 - **region** - (Optional) The region this interface's router sits in. If not specified, the project region will be used. Changing this forces a new interface to be created.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» Import

Router interfaces can be imported using the `region`, `router`, and `name`, e.g.

```
$ terraform import google_compute_router_interface.foobar us-central1/router-1/interface-1
```

» google_compute_router

Manages a Cloud Router BGP peer. For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_router_peer" "foobar" {
  name           = "peer-1"
  router         = "router-1"
  region         = "us-central1"
  peer_ip_address = "169.254.1.2"
  peer_asn       = 65513
  advertised_route_priority = 100
  interface      = "interface-1"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for BGP peer, required by GCE. Changing this forces a new peer to be created.
 - **router** - (Required) The name of the router in which this BGP peer will be configured. Changing this forces a new peer to be created.
 - **interface** - (Required) The name of the interface the BGP peer is associated with. Changing this forces a new peer to be created.
 - **peer_ip_address** - (Required) IP address of the BGP interface outside Google Cloud. Changing this forces a new peer to be created.
 - **peer_asn** - (Required) Peer BGP Autonomous System Number (ASN). Changing this forces a new peer to be created.
-
- **advertised_route_priority** - (Optional) The priority of routes advertised to this BGP peer. Changing this forces a new peer to be created.

- **project** - (Optional) The ID of the project in which this peer's router belongs. If it is not provided, the provider project is used. Changing this forces a new peer to be created.
- **region** - (Optional) The region this peer's router sits in. If not specified, the project region will be used. Changing this forces a new peer to be created.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **ip_address** - IP address of the interface inside Google Cloud Platform.

» Import

Router BGP peers can be imported using the **region**, **router**, and **name**, e.g.

```
$ terraform import google_compute_router_peer.foobar us-central1/router-1/peer-1
```

» google_compute_security_policy

A Security Policy defines an IP blacklist or whitelist that protects load balanced Google Cloud services by denying or permitting traffic from specified IP ranges. For more information see the official documentation and the API.

Note: This entire resource is in Beta

» Example Usage

```
resource "google_compute_security_policy" "policy" {
  name = "my-policy"

  rule {
    action    = "deny(403)"
    priority  = "1000"
    match {
      versioned_expr = "SRC_IPS_V1"
      config {
        src_ip_ranges = ["9.9.9.9/32"]
      }
    }
  }
}
```

```

    description = "Deny access to IPs in 9.9.9.0/24"
  }

  rule {
    action      = "allow"
    priority    = "2147483647"
    match {
      versioned_expr = "SRC_IPS_V1"
      config {
        src_ip_ranges = ["*"]
      }
    }
    description = "default rule"
  }
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the security policy.
-
- **description** - (Optional) An optional description of this security policy. Max size is 2048.
 - **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
 - **rule** - (Optional) The set of rules that belong to this policy. There must always be a default rule (rule with priority 2147483647 and match "*"). If no rules are provided when creating a security policy, a default rule with action "allow" will be added. Structure is documented below.

The **rule** block supports:

- **action** - (Required) Action to take when **match** matches the request. Valid values:
 - "allow" : allow access to target
 - "deny(status)" : deny access to target, returns the HTTP response code specified (valid values are 403, 404 and 502)
- **priority** - (Required) An unique positive integer indicating the priority of evaluation for a rule. Rules are evaluated from highest priority (lowest numerically) to lowest priority (highest numerically) in order.

- **match** - (Required) A match condition that incoming traffic is evaluated against. If it evaluates to true, the corresponding **action** is enforced. Structure is documented below.
- **description** - (Optional) An optional description of this rule. Max size is 64.
- **preview** - (Optional) When set to true, the **action** specified above is not enforced. Stackdriver logs for requests that trigger a preview action are annotated as such.

The **match** block supports:

- **config** - (Required) The configuration options available when specifying **versioned_expr**. Structure is documented below.
- **versioned_expr** - (Required) Predefined rule expression. Available options:
 - **SRC_IPS_V1**: Must specify the corresponding **src_ip_ranges** field in **config**.

The **config** block supports:

- **src_ip_ranges** - (Required) Set of IP addresses or ranges (IPV4 or IPV6) in CIDR notation to match against inbound traffic. There is a limit of 5 IP ranges per rule. A value of '*' matches all IPs (can be used to override the default behavior).

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **fingerprint** - Fingerprint of this resource.
- **self_link** - The URI of the created resource.

» Import

Security policies can be imported using the **name**, e.g.

```
$ terraform import google_compute_security_policy.policy my-policy
```

» google_compute_shared_vpc_host_project

Enables the Google Compute Engine Shared VPC feature for a project, assigning it as a Shared VPC host project.

For more information, see, the Project API documentation, where the Shared VPC feature is referred to by its former name "XPN".

» Example Usage

```
# A host project provides network resources to associated service projects.
resource "google_compute_shared_vpc_host_project" "host" {
  project = "host-project-id"
}

# A service project gains access to network resources provided by its
# associated host project.
resource "google_compute_shared_vpc_service_project" "service1" {
  host_project      = "${google_compute_shared_vpc_host_project.host.project}"
  service_project = "service-project-id-1"
}
resource "google_compute_shared_vpc_service_project" "service2" {
  host_project      = "${google_compute_shared_vpc_host_project.host.project}"
  service_project = "service-project-id-2"
}
```

» Argument Reference

The following arguments are expected:

- **project** - (Required) The ID of the project that will serve as a Shared VPC host project

» Import

Google Compute Engine Shared VPC host project feature can be imported using the `project`, e.g.

```
$ terraform import google_compute_shared_vpc_host_project.host host-project-id
```

» `google__compute__shared__vpc__service__project`

Enables the Google Compute Engine Shared VPC feature for a project, assigning it as a Shared VPC service project associated with a given host project.

For more information, see, the Project API documentation, where the Shared VPC feature is referred to by its former name "XPN".

» Example Usage

```
resource "google_compute_shared_vpc_service_project" "service1" {  
  host_project      = "host-project-id"  
  service_project = "service-project-id-1"  
}
```

For a complete Shared VPC example with both host and service projects, see `google_compute_shared_vpc_host_project`.

» Argument Reference

The following arguments are expected:

- `host_project` - (Required) The ID of a host project to associate.
- `service_project` - (Required) The ID of the project that will serve as a Shared VPC service project.

» Import

Google Compute Engine Shared VPC service project feature can be imported using the `host_project` and `service_project`, e.g.

```
$ terraform import google_compute_shared_vpc_service_project.service1 host-project-id/service-project-id
```

» google__compute__snapshot

Creates a new snapshot of a disk within GCE. For more information see the [official documentation](#) and [API](#).

» Example Usage

```
resource "google_compute_snapshot" "default" {  
  name          = "test-snapshot"  
  source_disk   = "test-disk"  
  zone          = "us-central1-a"  
  
  labels {  
    my-label = "my-label-value"  
  }  
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.
 - **zone** - (Required) The zone where the source disk is located.
 - **source_disk** - (Required) The disk which will be used as the source of the snapshot.
-
- **source_disk_encryption_key_raw** - (Optional) A 256-bit customer-supplied encryption key, encoded in RFC 4648 base64 to decrypt the source disk.
 - **snapshot_encryption_key_raw** - (Optional) A 256-bit customer-supplied encryption key, encoded in RFC 4648 base64 to encrypt this snapshot.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
 - **labels** - (Optional) A set of key/value label pairs to assign to the snapshot.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **snapshot_encryption_key_sha256** - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects this resource.
- **source_disk_encryption_key_sha256** - The RFC 4648 base64 encoded SHA-256 hash of the customer-supplied encryption key that protects the source disk.
- **source_disk_link** - The URI of the source disk.
- **self_link** - The URI of the created resource.
- **label_fingerprint** - The unique fingerprint of the labels.

» google_compute_ssl_certificate

Creates an SSL certificate resource necessary for HTTPS load balancing in GCE. For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_ssl_certificate" "default" {
  name_prefix = "my-certificate-"
  description = "a description"
  private_key = "${file("path/to/private.key")}"
  certificate = "${file("path/to/certificate.crt")}"

  lifecycle {
    create_before_destroy = true
  }
}

# You may also want to control name generation explicitly:

resource "random_id" "certificate" {
  byte_length = 4
  prefix      = "my-certificate-"

  # For security, do not expose raw certificate values in the output
  keepers {
    private_key = "${base64sha256(file("path/to/private.key"))}"
    certificate = "${base64sha256(file("path/to/certificate.crt"))}"
  }
}

resource "google_compute_ssl_certificate" "default" {
  # The name will contain 8 random hex digits,
  # e.g. "my-certificate-48ab27cd2a"
  name      = "${random_id.certificate.hex}"
  private_key = "${file("path/to/private.key")}"
  certificate = "${file("path/to/certificate.crt")}"

  lifecycle {
    create_before_destroy = true
  }
}
```

» Using with Target HTTPS Proxies

SSL certificates cannot be updated after creation. In order to apply the specified configuration, Terraform will destroy the existing resource and create a replacement. To effectively use an SSL certificate resource with a Target HTTPS Proxy resource, it's recommended to specify `create_before_destroy` in a lifecycle block. Either omit the Instance Template `name` attribute, specify a partial

name with `name_prefix`, or use `random_id` resource. Example:

```
resource "google_compute_ssl_certificate" "default" {
  name_prefix = "my-certificate-"
  description = "a description"
  private_key = "${file("path/to/private.key")}"
  certificate = "${file("path/to/certificate.crt")}"

  lifecycle {
    create_before_destroy = true
  }
}

resource "google_compute_target_https_proxy" "my_proxy" {
  name          = "public-proxy"
  url_map       = # ...
  ssl_certificates = ["${google_compute_ssl_certificate.default.self_link}"]
}
```

» Argument Reference

The following arguments are supported:

- **certificate** - (Required) A local certificate file in PEM format. The chain may be at most 5 certs long, and must include at least one intermediate cert. Changing this forces a new resource to be created.
 - **private_key** - (Required) Write only private key in PEM format. Changing this forces a new resource to be created.
-
- **name** - (Optional) A unique name for the SSL certificate. If you leave this blank, Terraform will auto-generate a unique name.
 - **name_prefix** - (Optional) Creates a unique name beginning with the specified prefix. Conflicts with **name**.
 - **description** - (Optional) An optional description of this resource. Changing this forces a new resource to be created.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `certificate_id` - A unique ID for the certificate, assigned by GCE.
- `self_link` - The URI of the created resource.

» Import

SSL certificate can be imported using the `name`, e.g.

```
$ terraform import compute_ssl_certificate.html.foobar foobar
```

» `google_compute_ssl_policy`

Represents a SSL policy. SSL policies give you the ability to control the features of SSL that your SSL proxy or HTTPS load balancer negotiates.

To get more information about `SslPolicy`, see:

- [API documentation](#)
- [How-to Guides](#)
 - [Using SSL Policies](#)

» Example Usage

```
resource "google_compute_ssl_policy" "prod-ssl-policy" {
  name      = "production-ssl-policy"
  profile   = "MODERN"
}
```

```
resource "google_compute_ssl_policy" "nonprod-ssl-policy" {
  name          = "nonprod-ssl-policy"
  profile       = "MODERN"
  min_tls_version = "TLS_1_2"
}
```

```
resource "google_compute_ssl_policy" "custom-ssl-policy" {
  name          = "custom-ssl-policy"
  min_tls_version = "TLS_1_2"
  profile       = "CUSTOM"
  custom_features = ["TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384", "TLS_ECDHE_RSA_WITH_AES_256_"]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.

-
- **description** - (Optional) An optional description of this resource.
 - **profile** - (Optional) Profile specifies the set of SSL features that can be used by the load balancer when negotiating SSL with clients. This can be one of `COMPATIBLE`, `MODERN`, `RESTRICTED`, or `CUSTOM`. If using `CUSTOM`, the set of SSL features to enable must be specified in the `customFeatures` field. See the official documentation for information on what cipher suites each profile provides. If `CUSTOM` is used, the `custom_features` attribute **must be set**. Default is `COMPATIBLE`.
 - **min_tls_version** - (Optional) The minimum version of SSL protocol that can be used by the clients to establish a connection with the load balancer. This can be one of `TLS_1_0`, `TLS_1_1`, `TLS_1_2`. Default is `TLS_1_0`.
 - **custom_features** - (Optional) Profile specifies the set of SSL features that can be used by the load balancer when negotiating SSL with clients. This can be one of `COMPATIBLE`, `MODERN`, `RESTRICTED`, or `CUSTOM`. If using `CUSTOM`, the set of SSL features to enable must be specified in the `customFeatures` field. See the official documentation for which ciphers are available to use. **Note:** this argument *must* be present when using the `CUSTOM` profile. This argument *must not* be present when using any other profile.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **enabled_features** - The list of features enabled in the SSL policy.
- **fingerprint** - Fingerprint of this resource. A hash of the contents stored in this object. This field is used in optimistic locking.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- `create` - Default is 4 minutes.
- `update` - Default is 4 minutes.
- `delete` - Default is 4 minutes.

» Import

SslPolicy can be imported using any of these accepted formats:

```
$ terraform import google_compute_ssl_policy.default projects/{{project}}/global/sslPolicies/{{name}}
$ terraform import google_compute_ssl_policy.default {{project}}/{{name}}
$ terraform import google_compute_ssl_policy.default {{name}}
```

» google_compute_subnetwork

A VPC network is a virtual version of the traditional physical networks that exist within and between physical data centers. A VPC network provides connectivity for your Compute Engine virtual machine (VM) instances, Container Engine containers, App Engine Flex services, and other network-related resources.

Each GCP project contains one or more VPC networks. Each VPC network is a global entity spanning all GCP regions. This global VPC network allows VM instances and other resources to communicate with each other via internal, private IP addresses.

Each VPC network is subdivided into subnets, and each subnet is contained within a single region. You can have more than one subnet in a region for a given VPC network. Each subnet has a contiguous private RFC1918 IP space. You create instances, containers, and the like in these subnets. When you create an instance, you must create it in a subnet, and the instance draws its internal IP address from that subnet.

Virtual machine (VM) instances in a VPC network can communicate with instances in all other subnets of the same VPC network, regardless of region, using their RFC1918 private IP addresses. You can isolate portions of the network, even entire subnets, using firewall rules.

To get more information about Subnetwork, see:

- API documentation
- How-to Guides
 - Private Google Access
 - Cloud Networking

» Example Usage

```
resource "google_compute_network" "custom-test" {
  name                = "test-network"
  auto_create_subnetworks = false
}

resource "google_compute_subnetwork" "network-with-private-secondary-ip-ranges" {
  name                = "test-subnetwork"
  ip_cidr_range       = "10.2.0.0/16"
  region              = "us-central1"
  network              = "${google_compute_network.custom-test.self_link}"
  secondary_ip_range {
    range_name         = "tf-test-secondary-range-update1"
    ip_cidr_range      = "192.168.10.0/24"
  }
}
```

» Argument Reference

The following arguments are supported:

- **ip_cidr_range** - (Required) The range of internal addresses that are owned by this subnetwork. Provide this property when you create the subnetwork. For example, 10.0.0.0/8 or 192.168.0.0/16. Ranges must be unique and non-overlapping within a network. Only IPv4 is supported.
 - **name** - (Required) The name of the resource, provided by the client when initially creating the resource. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
 - **network** - (Required) The network this subnet belongs to. Only networks that are in the distributed mode can have subnetworks.
-
- **description** - (Optional) An optional description of this resource. Provide this property when you create the resource. This field can be set only at resource creation time.
 - **enable_flow_logs** - (Optional) Whether to enable flow logging for this subnetwork.

- **secondary_ip_range** - (Optional) An array of configurations for secondary IP ranges for VM instances contained in this subnetwork. The primary IP of such VM must belong to the primary ipCidrRange of the subnetwork. The alias IPs may belong to either primary or secondary ranges. Structure is documented below.
- **private_ip_google_access** - (Optional) Whether the VMs in this subnet can access Google services without assigned external IP addresses.
- **region** - (Optional) URL of the GCP region for this subnetwork.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

The **secondary_ip_range** block supports:

- **range_name** - (Required) The name associated with this subnetwork secondary range, used when adding an alias IP range to a VM instance. The name must be 1-63 characters long, and comply with RFC1035. The name must be unique within the subnetwork.
- **ip_cidr_range** - (Required) The range of IP addresses belonging to this subnetwork secondary range. Provide this property when you create the subnetwork. Ranges must be unique and non-overlapping with all primary and secondary IP ranges within a network. Only IPv4 is supported.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **gateway_address** - The gateway address for default routes to reach destination addresses outside this subnetwork.
- **fingerprint** - Fingerprint of this resource. This field is used internally during updates of this resource.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 6 minutes.
- **update** - Default is 6 minutes.
- **delete** - Default is 6 minutes.

» Import

Subnetwork can be imported using any of these accepted formats:

```
$ terraform import google_compute_subnetwork.default projects/{{project}}/regions/{{region}}
$ terraform import google_compute_subnetwork.default {{region}}/{{name}}
$ terraform import google_compute_subnetwork.default {{project}}/{{region}}/{{name}}
$ terraform import google_compute_subnetwork.default {{name}}
```

» IAM policy for GCE subnetwork

Three different resources help you manage your IAM policy for GCE subnetwork. Each of these resources serves a different use case:

- `google_compute_subnetwork_iam_policy`: Authoritative. Sets the IAM policy for the subnetwork and replaces any existing policy already attached.
- `google_compute_subnetwork_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the subnetwork are preserved.
- `google_compute_subnetwork_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the subnetwork are preserved.

Note: `google_compute_subnetwork_iam_policy` **cannot** be used in conjunction with `google_compute_subnetwork_iam_binding` and `google_compute_subnetwork_iam_member` or they will fight over what your policy should be.

Note: `google_compute_subnetwork_iam_binding` resources **can be** used in conjunction with `google_compute_subnetwork_iam_member` resources **only if** they do not grant privilege to the same role.

Note: These entire resources are in Beta

» `google_compute_subnetwork_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}
```

```
resource "google_compute_subnetwork_iam_policy" "subnet" {
  subnetwork = "your-subnetwork-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» google_compute_subnetwork_iam_binding

```
resource "google_compute_subnetwork_iam_binding" "subnet" {
  subnetwork = "your-subnetwork-id"
  role       = "roles/compute.networkUser"

  members = [
    "user:jane@example.com",
  ]
}
```

» google_compute_subnetwork_iam_member

```
resource "google_compute_subnetwork_iam_member" "subnet" {
  subnetwork = "your-subnetwork-id"
  role       = "roles/compute.networkUser"
  member     = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **subnetwork** - (Required) The name of the subnetwork.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.

- **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Only one `google_compute_subnetwork_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_compute_subnetwork_iam_policy`) The policy data generated by a `google_iam_policy` data source.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **region** - (Optional) The region of the subnetwork. If unspecified, this defaults to the region configured in the provider.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the subnetwork's IAM policy.

» Import

For all import syntaxes, the "resource in question" can take any of the following forms:

- full self link or relative link (`projects/{{project}}/region/{{region}}/subnetworks/{{name}}`)
- `{{project}}/{{region}}/{{name}}`
- `{{region}}/{{name}}` (project is taken from provider project)
- `{{name}}` (project and region are taken from provider project)

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account, e.g.

```
$ terraform import google_compute_subnetwork_iam_member.subnet "project-name/region-name/subnet-name/role-name/account-name"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role, e.g.

```
$ terraform import google_compute_subnetwork_iam_binding.subnet "project-name/region-name/subnet-name/role-name"
```

IAM policy imports use the identifier of the resource in question, e.g.

```
$ terraform import google_compute_subnetwork_iam_policy.subnet project-name/region-name/subnet-name
```

» IAM policy for GCE subnetwork

Three different resources help you manage your IAM policy for GCE subnetwork. Each of these resources serves a different use case:

- `google_compute_subnetwork_iam_policy`: Authoritative. Sets the IAM policy for the subnetwork and replaces any existing policy already attached.
- `google_compute_subnetwork_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the subnetwork are preserved.
- `google_compute_subnetwork_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the subnetwork are preserved.

Note: `google_compute_subnetwork_iam_policy` **cannot** be used in conjunction with `google_compute_subnetwork_iam_binding` and `google_compute_subnetwork_iam_member` or they will fight over what your policy should be.

Note: `google_compute_subnetwork_iam_binding` resources **can be** used in conjunction with `google_compute_subnetwork_iam_member` resources **only if** they do not grant privilege to the same role.

Note: These entire resources are in Beta

» `google_compute_subnetwork_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_compute_subnetwork_iam_policy" "subnet" {
  subnetwork = "your-subnetwork-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» `google_compute_subnetwork_iam_binding`

```
resource "google_compute_subnetwork_iam_binding" "subnet" {
```

```

subnetwork = "your-subnetwork-id"
role       = "roles/compute.networkUser"

members = [
    "user:jane@example.com",
]
}

```

» google\compute_subnetwork_iam_member

```

resource "google_compute_subnetwork_iam_member" "subnet" {
  subnetwork = "your-subnetwork-id"
  role       = "roles/compute.networkUser"
  member     = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **subnetwork** - (Required) The name of the subnetwork.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_compute_subnetwork_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_compute_subnetwork_iam_policy`) The policy data generated by a `google_iam_policy` data source.

- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **region** - (Optional) The region of the subnetwork. If unspecified, this defaults to the region configured in the provider.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the subnetwork's IAM policy.

» Import

For all import syntaxes, the "resource in question" can take any of the following forms:

- full self link or relative link (`projects/{{project}}/region/{{region}}/subnetworks/{{name}}`)
- `{{project}}/{{region}}/{{name}}`
- `{{region}}/{{name}}` (project is taken from provider project)
- `{{name}}` (project and region are taken from provider project)

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account, e.g.

```
$ terraform import google_compute_subnetwork_iam_member.subnet "project-name/region-name/subnet-name:role:account"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role, e.g.

```
$ terraform import google_compute_subnetwork_iam_binding.subnet "project-name/region-name/subnet-name:role"
```

IAM policy imports use the identifier of the resource in question, e.g.

```
$ terraform import google_compute_subnetwork_iam_policy.subnet project-name/region-name/subnet-name
```

» IAM policy for GCE subnetwork

Three different resources help you manage your IAM policy for GCE subnetwork. Each of these resources serves a different use case:

- **google_compute_subnetwork_iam_policy**: Authoritative. Sets the IAM policy for the subnetwork and replaces any existing policy already attached.

- `google_compute_subnetwork_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the subnetwork are preserved.
- `google_compute_subnetwork_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the subnetwork are preserved.

Note: `google_compute_subnetwork_iam_policy` **cannot** be used in conjunction with `google_compute_subnetwork_iam_binding` and `google_compute_subnetwork_iam_member` or they will fight over what your policy should be.

Note: `google_compute_subnetwork_iam_binding` resources **can be** used in conjunction with `google_compute_subnetwork_iam_member` resources **only if** they do not grant privilege to the same role.

Note: These entire resources are in Beta

» `google_compute_subnetwork_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_compute_subnetwork_iam_policy" "subnet" {
  subnetwork = "your-subnetwork-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» `google_compute_subnetwork_iam_binding`

```
resource "google_compute_subnetwork_iam_binding" "subnet" {
  subnetwork = "your-subnetwork-id"
  role       = "roles/compute.networkUser"

  members = [
    "user:jane@example.com",
  ]
}
```

» google\compute_subnetwork_iam_member

```
resource "google_compute_subnetwork_iam_member" "subnet" {
  subnetwork = "your-subnetwork-id"
  role       = "roles/compute.networkUser"
  member     = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **subnetwork** - (Required) The name of the subnetwork.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_compute_subnetwork_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_compute_subnetwork_iam_policy`) The policy data generated by a `google_iam_policy` data source.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **region** - (Optional) The region of the subnetwork. If unspecified, this defaults to the region configured in the provider.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `etag` - (Computed) The etag of the subnetwork's IAM policy.

» Import

For all import syntaxes, the "resource in question" can take any of the following forms:

- full self link or relative link (`projects/{{project}}/region/{{region}}/subnetworks/{{name}}`)
- `{{project}}/{{region}}/{{name}}`
- `{{region}}/{{name}}` (project is taken from provider project)
- `{{name}}` (project and region are taken from provider project)

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account, e.g.

```
$ terraform import google_compute_subnetwork_iam_member.subnet "project-name/region-name/subnet-name/role/account"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role, e.g.

```
$ terraform import google_compute_subnetwork_iam_binding.subnet "project-name/region-name/subnet-name/role/account"
```

IAM policy imports use the identifier of the resource in question, e.g.

```
$ terraform import google_compute_subnetwork_iam_policy.subnet project-name/region-name/subnet-name
```

» `google_compute_target_http_proxy`

Represents a `TargetHttpProxy` resource, which is used by one or more global forwarding rule to route incoming HTTP requests to a URL map.

To get more information about `TargetHttpProxy`, see:

- API documentation
- How-to Guides
 - Official Documentation

» Example Usage

```
resource "google_compute_target_http_proxy" "default" {
  name          = "test-proxy"
  description   = "a description"
```

```

    url_map      = "${google_compute_url_map.default.self_link}"
  }

  resource "google_compute_url_map" "default" {
    name          = "url-map"
    description   = "a description"

    default_service = "${google_compute_backend_service.default.self_link}"

    host_rule {
      hosts      = ["mysite.com"]
      path_matcher = "allpaths"
    }

    path_matcher {
      name          = "allpaths"
      default_service = "${google_compute_backend_service.default.self_link}"

      path_rule {
        paths      = ["/*"]
        service    = "${google_compute_backend_service.default.self_link}"
      }
    }
  }

  resource "google_compute_backend_service" "default" {
    name          = "default-backend"
    port_name     = "http"
    protocol      = "HTTP"
    timeout_sec   = 10

    health_checks = ["${google_compute_http_health_check.default.self_link}"]
  }

  resource "google_compute_http_health_check" "default" {
    name          = "test"
    request_path   = "/"
    check_interval_sec = 1
    timeout_sec    = 1
  }

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
- **url_map** - (Required) A reference to the UrlMap resource that defines the mapping from URL to the BackendService.

-
- **description** - (Optional) An optional description of this resource.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **proxy_id** - The unique identifier for the resource.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

TargetHttpProxy can be imported using any of these accepted formats:

```
$ terraform import google_compute_target_http_proxy.default projects/{{project}}/global/targetHttpProxies/{{name}}
$ terraform import google_compute_target_http_proxy.default {{project}}/{{name}}
$ terraform import google_compute_target_http_proxy.default {{name}}
```

» google__compute__target__https__proxy

Represents a TargetHttpsProxy resource, which is used by one or more global forwarding rule to route incoming HTTPS requests to a URL map.

To get more information about TargetHttpsProxy, see:

- API documentation
- How-to Guides
 - Official Documentation

» Example Usage

```
resource "google_compute_target_https_proxy" "default" {
  name          = "test-proxy"
  description    = "a description"
  url_map        = "${google_compute_url_map.default.self_link}"
  ssl_certificates = ["${google_compute_ssl_certificate.default.self_link}"]
}
```

```
resource "google_compute_ssl_certificate" "default" {
  name          = "my-certificate"
  description    = "a description"
  private_key    = "${file("path/to/private.key")}"
  certificate     = "${file("path/to/certificate.crt")}"
}
```

```
resource "google_compute_url_map" "default" {
  name          = "url-map"
  description    = "a description"

  default_service = "${google_compute_backend_service.default.self_link}"

  host_rule {
    hosts          = ["mysite.com"]
    path_matcher    = "allpaths"
  }

  path_matcher {
    name          = "allpaths"
    default_service = "${google_compute_backend_service.default.self_link}"

    path_rule {
      paths        = ["/*"]
      service       = "${google_compute_backend_service.default.self_link}"
    }
  }
}
```

```

    }
  }
}

resource "google_compute_backend_service" "default" {
  name          = "default-backend"
  port_name     = "http"
  protocol      = "HTTP"
  timeout_sec   = 10

  health_checks = ["${google_compute_http_health_check.default.self_link}"]
}

resource "google_compute_http_health_check" "default" {
  name          = "test"
  request_path   = "/"
  check_interval_sec = 1
  timeout_sec    = 1
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
 - **ssl_certificates** - (Required) A list of SslCertificate resources that are used to authenticate connections between users and the load balancer. Currently, exactly one SSL certificate must be specified.
 - **url_map** - (Required) A reference to the UrlMap resource that defines the mapping from URL to the BackendService.
-
- **description** - (Optional) An optional description of this resource.
 - **quic_override** - (Optional) Specifies the QUIC override policy for this resource. This determines whether the load balancer will attempt to negotiate QUIC with clients or not. Can specify one of NONE, ENABLE, or DISABLE. If NONE is specified, uses the QUIC policy with no user

overrides, which is equivalent to DISABLE. Not specifying this field is equivalent to specifying NONE.

- **ssl_policy** - (Optional) A reference to the SslPolicy resource that will be associated with the TargetHttpsProxy resource. If not set, the TargetHttpsProxy resource will not have any SSL policy configured.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **proxy_id** - The unique identifier for the resource.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

TargetHttpsProxy can be imported using any of these accepted formats:

```
$ terraform import google_compute_target_https_proxy.default projects/{{project}}/global/targetHttpsProxies/{{name}}
$ terraform import google_compute_target_https_proxy.default {{project}}/{{name}}
$ terraform import google_compute_target_https_proxy.default {{name}}
```

» google_compute_target_ssl_proxy

Represents a TargetSslProxy resource, which is used by one or more global forwarding rule to route incoming SSL requests to a backend service.

To get more information about TargetSslProxy, see:

- [API documentation](#)
- [How-to Guides](#)

» Example Usage

```
resource "google_compute_target_ssl_proxy" "default" {
  name = "test"
  backend_service = "${google_compute_backend_service.default.self_link}"
  ssl_certificates = ["${google_compute_ssl_certificate.default.self_link}"]
}

resource "google_compute_ssl_certificate" "default" {
  name = "default-cert"
  private_key = "${file("path/to/test.key")}"
  certificate = "${file("path/to/test.crt")}"
}

resource "google_compute_backend_service" "default" {
  name = "default-backend"
  protocol = "SSL"
  health_checks = ["${google_compute_health_check.default.self_link}"]
}

resource "google_compute_health_check" "default" {
  name = "default-health-check"
  check_interval_sec = 1
  timeout_sec = 1
  tcp_health_check {
    port = "443"
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.
- **backend_service** - (Required) A reference to the BackendService resource.

- **ssl_certificates** - (Required) A list of SslCertificate resources that are used to authenticate connections between users and the load balancer. Currently, exactly one SSL certificate must be specified.

-
- **description** - (Optional) An optional description of this resource.
 - **proxy_header** - (Optional) Specifies the type of proxy header to append before sending data to the backend, either NONE or PROXY_V1. The default is NONE.
 - **ssl_policy** - (Optional) A reference to the SslPolicy resource that will be associated with the TargetSslProxy resource. If not set, the TargetSslProxy resource will not have any SSL policy configured.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **proxy_id** - The unique identifier for the resource.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

TargetSslProxy can be imported using any of these accepted formats:

```
$ terraform import google_compute_target_ssl_proxy.default projects/{{project}}/global/target_ssl_proxy/{{name}}
$ terraform import google_compute_target_ssl_proxy.default {{project}}/{{name}}
$ terraform import google_compute_target_ssl_proxy.default {{name}}
```

» google_compute_target_tcp_proxy

Represents a TargetTcpProxy resource, which is used by one or more global forwarding rule to route incoming TCP requests to a Backend service.

To get more information about TargetTcpProxy, see:

- API documentation
- How-to Guides
 - Setting Up TCP proxy for Google Cloud Load Balancing

» Example Usage

```
resource "google_compute_target_tcp_proxy" "default" {
  name = "test"
  description = "test"
  backend_service = "${google_compute_backend_service.default.self_link}"
}

resource "google_compute_backend_service" "default" {
  name          = "default-backend"
  protocol      = "TCP"
  timeout_sec   = 10

  health_checks = ["${google_compute_health_check.default.self_link}"]
}

resource "google_compute_health_check" "default" {
  name = "default"
  timeout_sec = 1
  check_interval_sec = 1

  tcp_health_check {
    port = "443"
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which

means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.

- **backend_service** - (Required) A reference to the BackendService resource.

-
- **description** - (Optional) An optional description of this resource.
 - **proxy_header** - (Optional) Specifies the type of proxy header to append before sending data to the backend, either NONE or PROXY_V1. The default is NONE.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **proxy_id** - The unique identifier for the resource.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

TargetTcpProxy can be imported using any of these accepted formats:

```
$ terraform import google_compute_target_tcp_proxy.default projects/{{project}}/global/target_tcp_proxies/{{name}}
$ terraform import google_compute_target_tcp_proxy.default {{project}}/{{name}}
$ terraform import google_compute_target_tcp_proxy.default {{name}}
```

» google_compute_target_pool

Manages a Target Pool within GCE. This is a collection of instances used as target of a network load balancer (Forwarding Rule). For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_target_pool" "default" {
  name = "instance-pool"

  instances = [
    "us-central1-a/myinstance1",
    "us-central1-b/myinstance2",
  ]

  health_checks = [
    "${google_compute_http_health_check.default.name}",
  ]
}

resource "google_compute_http_health_check" "default" {
  name           = "default"
  request_path   = "/"
  check_interval_sec = 1
  timeout_sec    = 1
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.
-
- **backup_pool** - (Optional) URL to the backup target pool. Must also set **failover_ratio**.
 - **description** - (Optional) Textual description field.
 - **failover_ratio** - (Optional) Ratio (0 to 1) of failed nodes before using the backup pool (which must also be set).

- **health_checks** - (Optional) List of zero or one health check name or `self_link`. Only legacy `google_compute_http_health_check` is supported.
- **instances** - (Optional) List of instances in the pool. They can be given as URLs, or in the form of "zone/name". Note that the instances need not exist at the time of target pool creation, so there is no need to use the Terraform interpolators to create a dependency on the instances from the target pool.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **region** - (Optional) Where the target pool resides. Defaults to project region.
- **session_affinity** - (Optional) How to distribute load. Options are "NONE" (no affinity), "CLIENT_IP" (hash of the source/dest addresses / ports), and "CLIENT_IP_PROTO" also includes the protocol (default "NONE").

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.

» Import

Target pools can be imported using the `name`, e.g.

```
$ terraform import google_compute_target_pool.default instance-pool
```

» google_compute_url_map

Manages a URL Map resource within GCE. For more information see the official documentation and API.

» Example Usage

```
resource "google_compute_url_map" "foobar" {
  name          = "urlmap"
  description = "a description"
```

```

default_service = "${google_compute_backend_service.home.self_link}"

host_rule {
  hosts      = ["mysite.com"]
  path_matcher = "allpaths"
}

path_matcher {
  name      = "allpaths"
  default_service = "${google_compute_backend_service.home.self_link}"

  path_rule {
    paths    = ["/home"]
    service = "${google_compute_backend_service.home.self_link}"
  }

  path_rule {
    paths    = ["/login"]
    service = "${google_compute_backend_service.login.self_link}"
  }

  path_rule {
    paths    = ["/static"]
    service = "${google_compute_backend_bucket.static.self_link}"
  }
}

test {
  service = "${google_compute_backend_service.home.self_link}"
  host    = "hi.com"
  path    = "/home"
}
}

resource "google_compute_backend_service" "login" {
  name      = "login-backend"
  port_name = "http"
  protocol  = "HTTP"
  timeout_sec = 10

  health_checks = ["${google_compute_http_health_check.default.self_link}"]
}

resource "google_compute_backend_service" "home" {
  name      = "home-backend"

```



```

    port_name    = "http"
    protocol     = "HTTP"
    timeout_sec  = 10

    health_checks = ["${google_compute_http_health_check.default.self_link}"]
}

resource "google_compute_http_health_check" "default" {
    name          = "test"
    request_path  = "/"
    check_interval_sec = 1
    timeout_sec   = 1
}

resource "google_compute_backend_bucket" "static" {
    name          = "static-asset-backend-bucket"
    bucket_name   = "${google_storage_bucket.static.name}"
    enable_cdn    = true
}

resource "google_storage_bucket" "static" {
    name          = "static-asset-bucket"
    location     = "US"
}

```

» Argument Reference

The following arguments are supported:

- **default_service** - (Required) The backend service or backend bucket to use when none of the given rules match.
 - **name** - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.
-
- **description** - (Optional) A brief description of this resource.
 - **host_rule** - (Optional) A list of host rules. Multiple blocks of this type are permitted. Structure is documented below.
 - **path_matcher** - (Optional) A list of paths to match. Structure is documented below.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

- **test** - (Optional) The test to perform. Multiple blocks of this type are permitted. Structure is documented below.

The **host_rule** block supports:

- **hosts** (Required) - The list of host patterns to match.
- **description** - (Optional) An optional description of the host rule.
- **path_matcher** - (Required) The name of the **path_matcher** to apply this host rule to.

The **path_matcher** block supports:

- **name** - (Required) The name of the **path_matcher** resource.
- **default_service** - (Required) The backend service or backend bucket to use if none of the given paths match.
- **description** - (Optional) An optional description of the host rule.
- **path_rule** - (Optional) A list of path rules. Multiple blocks of this type are permitted. Structure is documented below.

The **path_rule** block supports:

- **paths** - (Required) The list of paths to match against.
- **service** - (Required) The backend service or backend bucket to use if any of the given paths match.

The **test** block supports:

- **service** - (Required) The backend service or backend bucket link that should be matched by this test.
- **host** - (Required) The host component of the URL being tested.
- **path** - (Required) The path component of the URL being tested.
- **description** - (Optional) An optional description of this test.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **fingerprint** - The unique fingerprint for this resource.
- **map_id** - The GCE assigned ID of the resource.
- **self_link** - The URI of the created resource.

» Import

URL Map can be imported using the `name`, e.g.

```
$ terraform import google_compute_url_map.html.foobar foobar
```

Currently `host_rule`, `path_matcher` and `test` importing is not yet supported.

» google_compute_vpn_gateway

Represents a VPN gateway running in GCP. This virtual device is managed by Google, but used only by you.

To get more information about `VpnGateway`, see:

- [API documentation](#)

» Example Usage

```
resource "google_compute_network" "network1" {
  name      = "network1"
  ipv4_range = "10.120.0.0/16"
}

resource "google_compute_vpn_gateway" "target_gateway" {
  name      = "vpn1"
  network   = "${google_compute_network.network1.self_link}"
  region    = "${var.region}"
}

resource "google_compute_address" "vpn_static_ip" {
  name      = "vpn-static-ip"
  region    = "${var.region}"
}

resource "google_compute_forwarding_rule" "fr_esp" {
  name      = "fr-esp"
  region    = "${var.region}"
  ip_protocol = "ESP"
  ip_address  = "${google_compute_address.vpn_static_ip.address}"
  target     = "${google_compute_vpn_gateway.target_gateway.self_link}"
}

resource "google_compute_forwarding_rule" "fr_udp500" {
  name      = "fr-udp500"
}
```

```

    region      = "${var.region}"
    ip_protocol = "UDP"
    port_range  = "500"
    ip_address  = "${google_compute_address.vpn_static_ip.address}"
    target      = "${google_compute_vpn_gateway.target_gateway.self_link}"
  }

  resource "google_compute_forwarding_rule" "fr_udp4500" {
    name      = "fr-udp4500"
    region    = "${var.region}"
    ip_protocol = "UDP"
    port_range = "4500"
    ip_address = "${google_compute_address.vpn_static_ip.address}"
    target     = "${google_compute_vpn_gateway.target_gateway.self_link}"
  }

  resource "google_compute_vpn_tunnel" "tunnel1" {
    name      = "tunnel1"
    region    = "${var.region}"
    peer_ip   = "15.0.0.120"
    shared_secret = "a secret message"

    target_vpn_gateway = "${google_compute_vpn_gateway.target_gateway.self_link}"

    depends_on = [
      "google_compute_forwarding_rule.fr_esp",
      "google_compute_forwarding_rule.fr_udp500",
      "google_compute_forwarding_rule.fr_udp4500",
    ]
  }

  resource "google_compute_route" "route1" {
    name      = "route1"
    network   = "${google_compute_network.network1.name}"
    dest_range = "15.0.0.0/24"
    priority  = 1000

    next_hop_vpn_tunnel = "${google_compute_vpn_tunnel.tunnel1.self_link}"
  }

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. Provided by the client when the

resource is created. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.

- **network** - (Required) The network this VPN gateway is accepting traffic for.

-
- **description** - (Optional) An optional description of this resource.
 - **region** - (Optional) The region this gateway should sit in.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **self_link** - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

VpnGateway can be imported using any of these accepted formats:

```
$ terraform import google_compute_vpn_gateway.default projects/{{project}}/regions/{{region}}/gateways/{{name}}
$ terraform import google_compute_vpn_gateway.default {{project}}/{{region}}/{{name}}
$ terraform import google_compute_vpn_gateway.default {{name}}
```

» google_compute_vpn_tunnel

VPN tunnel resource.

To get more information about VpnTunnel, see:

- API documentation
- How-to Guides
 - Cloud VPN Overview
 - Networks and Tunnel Routing

Warning: All arguments including the shared secret will be stored in the raw state as plain-text. Read more about sensitive data in state.

» Example Usage

```
resource "google_compute_network" "network1" {
  name = "network1"
}

resource "google_compute_subnetwork" "subnet1" {
  name          = "subnet1"
  network       = "${google_compute_network.network1.self_link}"
  ip_cidr_range = "10.120.0.0/16"
  region       = "us-central1"
}

resource "google_compute_vpn_gateway" "target_gateway" {
  name     = "vpn1"
  network  = "${google_compute_network.network1.self_link}"
  region   = "${google_compute_subnetwork.subnet1.region}"
}

resource "google_compute_address" "vpn_static_ip" {
  name     = "vpn-static-ip"
  region   = "${google_compute_subnetwork.subnet1.region}"
}

resource "google_compute_forwarding_rule" "fr_esp" {
  name          = "fr-esp"
  ip_protocol    = "ESP"
  ip_address     = "${google_compute_address.vpn_static_ip.address}"
  target         = "${google_compute_vpn_gateway.target_gateway.self_link}"
}

resource "google_compute_forwarding_rule" "fr_udp500" {
  name          = "fr-udp500"
  ip_protocol    = "UDP"
  port_range     = "500-500"
  ip_address     = "${google_compute_address.vpn_static_ip.address}"
}
```

```

    target      = "${google_compute_vpn_gateway.target_gateway.self_link}"
  }

  resource "google_compute_forwarding_rule" "fr_udp4500" {
    name          = "fr-udp4500"
    ip_protocol   = "UDP"
    port_range    = "4500-4500"
    ip_address    = "${google_compute_address.vpn_static_ip.address}"
    target        = "${google_compute_vpn_gateway.target_gateway.self_link}"
  }

  resource "google_compute_vpn_tunnel" "tunnel1" {
    name          = "tunnel1"
    peer_ip       = "15.0.0.120"
    shared_secret = "a secret message"

    target_vpn_gateway = "${google_compute_vpn_gateway.target_gateway.self_link}"

    local_traffic_selector = ["${google_compute_subnetwork.subnet1.ip_cidr_range}"]
    remote_traffic_selector = ["172.16.0.0/12"]

    depends_on = [
      "google_compute_forwarding_rule.fr_esp",
      "google_compute_forwarding_rule.fr_udp500",
      "google_compute_forwarding_rule.fr_udp4500",
    ]
  }

  resource "google_compute_route" "route1" {
    name          = "route1"
    network       = "${google_compute_network.network1.name}"
    dest_range    = "15.0.0.0/24"
    priority      = 1000

    next_hop_vpn_tunnel = "${google_compute_vpn_tunnel.tunnel1.self_link}"
  }

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) Name of the resource. The name must be 1-63 characters long, and comply with RFC1035. Specifically, the name must be 1-63 characters long and match the regular expression `[a-z]([-a-z0-9]*[a-z0-9])?` which means the first character must be

a lowercase letter, and all following characters must be a dash, lowercase letter, or digit, except the last character, which cannot be a dash.

- **target_vpn_gateway** - (Required) URL of the Target VPN gateway with which this VPN tunnel is associated.
- **peer_ip** - (Required) IP address of the peer VPN gateway. Only IPv4 is supported.
- **shared_secret** - (Required) Shared secret used to set the secure session between the Cloud VPN gateway and the peer VPN gateway.

-
- **description** - (Optional) An optional description of this resource.
 - **router** - (Optional) URL of router resource to be used for dynamic routing.
 - **ike_version** - (Optional) IKE protocol version to use when establishing the VPN tunnel with peer VPN gateway. Acceptable IKE versions are 1 or 2. Default version is 2.
 - **local_traffic_selector** - (Optional) Local traffic selector to use when establishing the VPN tunnel with peer VPN gateway. The value should be a CIDR formatted string, for example `192.168.0.0/16`. The ranges should be disjoint. Only IPv4 is supported.
 - **remote_traffic_selector** - (Optional) Remote traffic selector to use when establishing the VPN tunnel with peer VPN gateway. The value should be a CIDR formatted string, for example `192.168.0.0/16`. The ranges should be disjoint. Only IPv4 is supported.
 - **labels** - (Optional) Labels to apply to this VpnTunnel.
 - **region** - (Optional) The region where the tunnel is located.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **creation_timestamp** - Creation timestamp in RFC3339 text format.
- **shared_secret_hash** - Hash of the shared secret.
- **label_fingerprint** - The fingerprint used for optimistic locking of this resource. Used internally during updates.
- **detailed_status** - Detailed status message for the VPN tunnel.

- `self_link` - The URI of the created resource.

» Timeouts

This resource provides the following Timeouts configuration options:

- `create` - Default is 4 minutes.
- `update` - Default is 4 minutes.
- `delete` - Default is 4 minutes.

» Import

VpnTunnel can be imported using any of these accepted formats:

```
$ terraform import google_compute_vpn_tunnel.default projects/{{project}}/regions/{{region}}/vpnTunnels/{{name}}
$ terraform import google_compute_vpn_tunnel.default {{project}}/{{region}}/{{name}}
$ terraform import google_compute_vpn_tunnel.default {{name}}
```

» google__container__analysis__note

Provides a detailed description of a Note.

To get more information about Note, see:

- [API documentation](#)
- [How-to Guides](#)
 - [Official Documentation](#)

» Example Usage

```
resource "google_container_analysis_note" "note" {
  name = "test-attestor-note"
  attestation_authority {
    hint {
      human_readable_name = "Attestor Note"
    }
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the note.
- **attestation_authority** - (Required) Note kind that represents a logical attestation "role" or "authority". For example, an organization might have one AttestationAuthority for "QA" and one for "build". This Note is intended to act strictly as a grouping mechanism for the attached Occurrences (Attestations). This grouping mechanism also provides a security boundary, since IAM ACLs gate the ability for a principle to attach an Occurrence to a given Note. It also provides a single point of lookup to find all attached Attestation Occurrences, even if they don't all live in the same project. Structure is documented below.

The **attestation_authority** block supports:

- **hint** - (Required) This submessage provides human-readable hints about the purpose of the AttestationAuthority. Because the name of a Note acts as its resource reference, it is important to disambiguate the canonical name of the Note (which might be a UUID for security purposes) from "readable" names more suitable for debug output. Note that these hints should NOT be used to look up AttestationAuthorities in security sensitive contexts, such as when looking up Attestations to verify. Structure is documented below.

The **hint** block supports:

- **human_readable_name** - (Required) The human readable name of this Attestation Authority, for example "qa".
-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Import

Note can be imported using any of these accepted formats:

```
$ terraform import google_container_analysis_note.default projects/{{project}}/notes/{{name}}
$ terraform import google_container_analysis_note.default {{project}}/{{name}}
$ terraform import google_container_analysis_note.default {{name}}
```

» google__container__cluster

Creates a Google Kubernetes Engine (GKE) cluster. For more information see the official documentation and API.

Note: All arguments including the username and password will be stored in the raw state as plain-text. Read more about sensitive data in state.

» Example usage

```
resource "google_container_cluster" "primary" {
  name          = "marcellus-wallace"
  zone          = "us-central1-a"
  initial_node_count = 3

  additional_zones = [
    "us-central1-b",
    "us-central1-c",
  ]

  master_auth {
    username = "mr.yoda"
    password = "adoy.rm"
  }

  node_config {
    oauth_scopes = [
      "https://www.googleapis.com/auth/compute",
      "https://www.googleapis.com/auth/devstorage.read_only",
      "https://www.googleapis.com/auth/logging.write",
      "https://www.googleapis.com/auth/monitoring",
    ]

    labels {
      foo = "bar"
    }

    tags = ["foo", "bar"]
  }
}

# The following outputs allow authentication and connectivity to the GKE Cluster.
output "client_certificate" {
  value = "${google_container_cluster.primary.master_auth.0.client_certificate}"
}

output "client_key" {
  value = "${google_container_cluster.primary.master_auth.0.client_key}"
}

output "cluster_ca_certificate" {
  value = "${google_container_cluster.primary.master_auth.0.cluster_ca_certificate}"
}
```

» Argument Reference

- **name** - (Required) The name of the cluster, unique within the project and zone.
-
- **zone** - (Optional) The zone that the master and the number of nodes specified in **initial_node_count** should be created in. Only one of **zone** and **region** may be set. If neither zone nor region are set, the provider zone is used.
 - **region** (Optional, Beta) The region to create the cluster in, for Regional Clusters.
 - **additional_zones** - (Optional) The list of additional Google Compute Engine locations in which the cluster's nodes should be located. If additional zones are configured, the number of nodes specified in **initial_node_count** is created in all specified zones.
 - **addons_config** - (Optional) The configuration for addons supported by GKE. Structure is documented below.
 - **cluster_ipv4_cidr** - (Optional) The IP address range of the kubernetes pods in this cluster. Default is an automatically assigned CIDR.
 - **description** - (Optional) Description of the cluster.
 - **enable_binary_authorization** - (Optional) Enable Binary Authorization for this cluster. If enabled, all container images will be validated by Google Binary Authorization.
 - **enable_kubernetes_alpha** - (Optional) Whether to enable Kubernetes Alpha features for this cluster. Note that when this option is enabled, the cluster cannot be upgraded and will be automatically deleted after 30 days.
 - **enable_legacy_abac** - (Optional) Whether the ABAC authorizer is enabled for this cluster. When enabled, identities in the system, including service accounts, nodes, and controllers, will have statically granted permissions beyond those provided by the RBAC configuration or IAM. Defaults to **false**
 - **initial_node_count** - (Optional) The number of nodes to create in this cluster (not including the Kubernetes master). Must be set if **node_pool** is not set.
 - **ip_allocation_policy** - (Optional) Configuration for cluster IP allocation. As of now, only pre-allocated subnetworks (custom type with secondary ranges) are supported. This will activate IP aliases. See the official documentation Structure is documented below.

- **logging_service** - (Optional) The logging service that the cluster should write logs to. Available options include `logging.googleapis.com`, `logging.googleapis.com/kubernetes` (beta), and `none`. Defaults to `logging.googleapis.com`
- **maintenance_policy** - (Optional) The maintenance policy to use for the cluster. Structure is documented below.
- **master_auth** - (Optional) The authentication information for accessing the Kubernetes master. Structure is documented below.
- **master_authorized_networks_config** - (Optional) The desired configuration options for master authorized networks. Omit the nested `cidr_blocks` attribute to disallow external access (except the cluster node IPs, which GKE automatically whitelists).
- **master_ipv4_cidr_block** - (Optional, Beta) Specifies a private RFC1918 block for the master's VPC. The master range must not overlap with any subnet in your cluster's VPC. The master and your cluster use VPC peering. Must be specified in CIDR notation and must be /28 subnet.
- **min_master_version** - (Optional) The minimum version of the master. GKE will auto-update the master to new versions, so this does not guarantee the current master version--use the read-only `master_version` field to obtain that. If unset, the cluster's version will be set by GKE to the version of the most recent official release (which is not necessarily the latest version).
- **monitoring_service** - (Optional) The monitoring service that the cluster should write metrics to. Automatically send metrics from pods in the cluster to the Google Cloud Monitoring API. VM metrics will be collected by Google Compute Engine regardless of this setting. Available options include `monitoring.googleapis.com`, `monitoring.googleapis.com/kubernetes` (beta) and `none`. Defaults to `monitoring.googleapis.com`
- **network** - (Optional) The name or `self_link` of the Google Compute Engine network to which the cluster is connected. For Shared VPC, set this to the self link of the shared network.
- **network_policy** - (Optional) Configuration options for the NetworkPolicy feature. Structure is documented below.
- **node_config** - (Optional) Parameters used in creating the cluster's nodes. Structure is documented below.
- **node_pool** - (Optional) List of node pools associated with this cluster. See `google_container_node_pool` for schema.
- **node_version** - (Optional) The Kubernetes version on the nodes. Must either be unset or set to the same value as `min_master_version` on create.

Defaults to the default version set by GKE which is not necessarily the latest version.

- **pod_security_policy_config** - (Optional, Beta) Configuration for the PodSecurityPolicy feature. Structure is documented below.
- **private_cluster** - (Optional, Beta) If true, a private cluster will be created, meaning nodes do not get public IP addresses. It is mandatory to specify **master_ipv4_cidr_block** and **ip_allocation_policy** with this option.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **remove_default_node_pool** - (Optional) If true, deletes the default node pool upon cluster creation.
- **resource_labels** - (Optional) The GCE resource labels (a map of key/value pairs) to be applied to the cluster.
- **subnetwork** - (Optional) The name or **self_link** of the Google Compute Engine subnetwork in which the cluster's instances are launched.

The **addons_config** block supports:

- **horizontal_pod_autoscaling** - (Optional) The status of the Horizontal Pod Autoscaling addon, which increases or decreases the number of replica pods a replication controller has based on the resource usage of the existing pods. It ensures that a Heapster pod is running in the cluster, which is also used by the Cloud Monitoring service. It is enabled by default; set **disabled = true** to disable.
- **http_load_balancing** - (Optional) The status of the HTTP (L7) load balancing controller addon, which makes it easy to set up HTTP load balancers for services in a cluster. It is enabled by default; set **disabled = true** to disable.
- **kubernetes_dashboard** - (Optional) The status of the Kubernetes Dashboard add-on, which controls whether the Kubernetes Dashboard is enabled for this cluster. It is enabled by default; set **disabled = true** to disable.
- **network_policy_config** - (Optional) Whether we should enable the network policy addon for the master. This must be enabled in order to enable network policy for the nodes. It can only be disabled if the nodes already do not have network policies enabled. Set **disabled = true** to disable.

This example **addons_config** disables two addons:

```
addons_config {
  http_load_balancing {
    disabled = true
  }
  horizontal_pod_autoscaling {
```

```

    disabled = true
  }
}

```

The `maintenance_policy` block supports:

- `daily_maintenance_window` - (Required) Time window specified for daily maintenance operations. Specify `start_time` in RFC3339 format "HH:MM", where HH : [00-23] and MM : [00-59] GMT. For example:

```

maintenance_policy {
  daily_maintenance_window {
    start_time = "03:00"
  }
}

```

The `ip_allocation_policy` block supports:

- `cluster_secondary_range_name` - (Optional) The name of the secondary range to be used as for the cluster CIDR block. The secondary range will be used for pod IP addresses. This must be an existing secondary range associated with the cluster subnetwork.
- `services_secondary_range_name` - (Optional) The name of the secondary range to be used as for the services CIDR block. The secondary range will be used for service ClusterIPs. This must be an existing secondary range associated with the cluster subnetwork.

The `master_auth` block supports:

- `password` - (Required) The password to use for HTTP basic authentication when accessing the Kubernetes master endpoint
- `username` - (Required) The username to use for HTTP basic authentication when accessing the Kubernetes master endpoint
- `client_certificate_config` - (Optional) Whether client certificate authorization is enabled for this cluster. For example:

```

master_auth {
  client_certificate_config {
    issue_client_certificate = false
  }
}

```

If this block is provided and both `username` and `password` are empty, basic authentication will be disabled. This block also contains several computed attributes, documented below. If this block is not provided, GKE will generate a password for you with the username `admin`.

The `master_authorized_networks_config` block supports:

- `cidr_blocks` - (Optional) Defines up to 20 external networks that can access Kubernetes master through HTTPS.

The `master_authorized_networks_config.cidr_blocks` block supports:

- `cidr_block` - (Optional) External network that can access Kubernetes master through HTTPS. Must be specified in CIDR notation.
- `display_name` - (Optional) Field for users to identify CIDR blocks.

The `network_policy` block supports:

- `provider` - (Optional) The selected network policy provider. Defaults to `PROVIDER_UNSPECIFIED`.
- `enabled` - (Optional) Whether network policy is enabled on the cluster. Defaults to false.

The `node_config` block supports:

- `disk_size_gb` - (Optional) Size of the disk attached to each node, specified in GB. The smallest allowed disk size is 10GB. Defaults to 100GB.
- `disk_type` - (Optional) Type of the disk attached to each node (e.g. 'pd-standard' or 'pd-ssd'). If unspecified, the default disk type is 'pd-standard'.
- `guest_accelerator` - (Optional) List of the type and count of accelerator cards attached to the instance. Structure documented below.
- `image_type` - (Optional) The image type to use for this node. Note that changing the image type will delete and recreate all nodes in the node pool.
- `labels` - (Optional) The Kubernetes labels (key/value pairs) to be applied to each node.
- `local_ssd_count` - (Optional) The amount of local SSD disks that will be attached to each cluster node. Defaults to 0.
- `machine_type` - (Optional) The name of a Google Compute Engine machine type. Defaults to `n1-standard-1`. To create a custom machine type, value should be set as specified here.
- `metadata` - (Optional) The metadata key/value pairs assigned to instances in the cluster.
- `min_cpu_platform` - (Optional) Minimum CPU platform to be used by this instance. The instance may be scheduled on the specified or newer CPU platform. Applicable values are the friendly names of CPU platforms, such as `Intel Haswell`. See the official documentation for more information.
- `oauth_scopes` - (Optional) The set of Google API scopes to be made available on all of the node VMs under the "default" service account. These

can be either FQDNs, or scope aliases. The following scopes are necessary to ensure the correct functioning of the cluster:

- `compute-rw` (<https://www.googleapis.com/auth/compute>)
 - `storage-ro` (https://www.googleapis.com/auth/devstorage.read_only)
 - `logging-write` (<https://www.googleapis.com/auth/logging.write>), if `logging_service` points to Google
 - `monitoring` (<https://www.googleapis.com/auth/monitoring>), if `monitoring_service` points to Google
- `preemptible` - (Optional) A boolean that represents whether or not the underlying node VMs are preemptible. See the official documentation for more information. Defaults to false.
 - `service_account` - (Optional) The service account to be used by the Node VMs. If not specified, the "default" service account is used.
 - `tags` - (Optional) The list of instance tags applied to all nodes. Tags are used to identify valid sources or targets for network firewalls.
 - `taint` - (Optional, Beta) List of kubernetes taints to apply to each node. Structure is documented below.
 - `workload_metadata_config` - (Optional) Metadata configuration to expose to workloads on the node pool. Structure is documented below.

The `guest_accelerator` block supports:

- `type` (Required) - The accelerator type resource to expose to this instance. E.g. `nvidia-tesla-k80`.
- `count` (Required) - The number of the guest accelerator cards exposed to this instance.

The `pod_security_policy_config` block supports:

- `enabled` (Required) - Enable the PodSecurityPolicy controller for this cluster. If enabled, pods must be valid under a PodSecurityPolicy to be created.

The `taint` block supports:

- `key` (Required) Key for taint.
- `value` (Required) Value for taint.
- `effect` (Required) Effect for taint. Accepted values are `NO_SCHEDULE`, `PREFER_NO_SCHEDULE`, and `NO_EXECUTE`.

The `workload_metadata_config` block supports:

- `node_metadata` (Required) How to expose the node metadata to the workload running on the node. Accepted values are:
 - `UNSPECIFIED`: Not Set

- **SECURE**: Prevent workloads not in `hostNetwork` from accessing certain VM metadata, specifically `kube-env`, which contains Kubelet credentials, and the instance identity token. See Metadata Concealment documentation.
- **EXPOSE**: Expose all VM metadata to pods.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **endpoint** - The IP address of this cluster's Kubernetes master.
- **instance_group_urls** - List of instance group URLs which have been assigned to the cluster.
- **maintenance_policy.0.daily_maintenance_window.0.duration** - Duration of the time window, automatically chosen to be smallest possible in the given scenario. Duration will be in RFC3339 format "PTnHnMnS".
- **master_auth.0.client_certificate** - Base64 encoded public certificate used by clients to authenticate to the cluster endpoint.
- **master_auth.0.client_key** - Base64 encoded private key used by clients to authenticate to the cluster endpoint.
- **master_auth.0.cluster_ca_certificate** - Base64 encoded public certificate that is the root of trust for the cluster.
- **master_version** - The current version of the master in the cluster. This may be different than the **min_master_version** set in the config if the master has been updated by GKE.

» Timeouts

`google_container_cluster` provides the following Timeouts configuration options:

- **create** - (Default 30 minutes) Used for clusters
- **update** - (Default 10 minutes) Used for updates to clusters
- **delete** - (Default 10 minutes) Used for destroying clusters.

» Import

GKE clusters can be imported using the `project`, `zone` or `region`, and `name`. If the project is omitted, the default provider value will be used. Examples:

```
$ terraform import google_container_cluster.mycluster my-gcp-project/us-east1-a/my-cluster
```

```
$ terraform import google_container_cluster.mycluster us-east1-a/my-cluster
```

» `google_container_node_pool`

Manages a Node Pool resource within GKE. For more information see the official documentation and API.

» Example usage

» Standard usage

```
resource "google_container_node_pool" "np" {
  name          = "my-node-pool"
  zone          = "us-central1-a"
  cluster       = "${google_container_cluster.primary.name}"
  node_count    = 3
}

resource "google_container_cluster" "primary" {
  name          = "marcellus-wallace"
  zone          = "us-central1-a"
  initial_node_count = 3

  additional_zones = [
    "us-central1-b",
    "us-central1-c",
  ]

  master_auth {
    username = "mr.yoda"
    password = "adoy.rm"
  }

  node_config {
    oauth_scopes = [
      "https://www.googleapis.com/auth/compute",
      "https://www.googleapis.com/auth/devstorage.read_only",
      "https://www.googleapis.com/auth/logging.write",
      "https://www.googleapis.com/auth/monitoring",
    ]
  }
}
```

```

    guest_accelerator {
      type = "nvidia-tesla-k80"
      count = 1
    }
  }
}

```

» Usage with an empty default pool.

```

resource "google_container_node_pool" "np" {
  name          = "my-node-pool"
  zone          = "us-central1-a"
  cluster       = "${google_container_cluster.primary.name}"
  node_count    = 1

  node_config {
    preemptible  = true
    machine_type = "n1-standard-1"

    oauth_scopes = [
      "compute-rw",
      "storage-ro",
      "logging-write",
      "monitoring",
    ]
  }
}

resource "google_container_cluster" "primary" {
  name     = "marcellus-wallace"
  zone     = "us-central1-a"

  lifecycle {
    ignore_changes = ["node_pool"]
  }

  node_pool {
    name = "default-pool"
  }
}

```

» Usage with a regional cluster

```

resource "google_container_cluster" "regional" {

```

```

    name    = "marcellus-wallace"
    region  = "us-central1"
  }

  resource "google_container_node_pool" "regional-np" {
    name      = "my-node-pool"
    region    = "us-central1"
    cluster   = "${google_container_cluster.primary.name}"
    node_count = 1
  }

```

» Argument Reference

- **zone** - (Optional) The zone in which the cluster resides.
- **region** - (Optional) The region in which the cluster resides (for regional clusters).
- **cluster** - (Required) The cluster to create the node pool for. Cluster must be present in **zone** provided for zonal clusters.

Note: You must provide region for regional clusters and zone for zonal clusters

-
- **autoscaling** - (Optional) Configuration required by cluster autoscaler to adjust the size of the node pool to the current cluster usage. Structure is documented below.
 - **initial_node_count** - (Optional) The initial node count for the pool. Changing this will force recreation of the resource.
 - **management** - (Optional) Node management configuration, wherein auto-repair and auto-upgrade is configured. Structure is documented below.
 - **name** - (Optional) The name of the node pool. If left blank, Terraform will auto-generate a unique name.
 - **name_prefix** - (Deprecated, Optional) Creates a unique name for the node pool beginning with the specified prefix. Conflicts with **name**.
 - **node_config** - (Optional) The node configuration of the pool. See `google_container_cluster` for schema.
 - **node_count** - (Optional) The number of nodes per instance group. This field can be used to update the number of nodes per instance group but should not be used alongside **autoscaling**.
 - **project** - (Optional) The ID of the project in which to create the node pool. If blank, the provider-configured project will be used.

- **version** - (Optional) The Kubernetes version for the nodes in this pool. Note that if this field and **auto_upgrade** are both specified, they will fight each other for what the node version should be, so setting both is highly discouraged.

The **autoscaling** block supports:

- **min_node_count** - (Required) Minimum number of nodes in the NodePool. Must be ≥ 1 and \leq **max_node_count**.
- **max_node_count** - (Required) Maximum number of nodes in the NodePool. Must be \geq **min_node_count**.

The **management** block supports:

- **auto_repair** - (Optional) Whether the nodes will be automatically repaired.
- **auto_upgrade** - (Optional) Whether the nodes will be automatically upgraded.

» Import

Node pools can be imported using the **project**, **zone**, **cluster** and **name**. If the project is omitted, the default provider value will be used. Examples:

```
$ terraform import google_container_node_pool.mainpool my-gcp-project/us-east1-a/my-cluster/
```

```
$ terraform import google_container_node_pool.mainpool us-east1-a/my-cluster/main-pool
```

» google__dataflow__job

Creates a job on Dataflow, which is an implementation of Apache Beam running on Google Compute Engine. For more information see the official documentation for Beam and Dataflow.

» Example Usage

```
resource "google_dataflow_job" "big_data_job" {
  name = "dataflow-job"
  template_gcs_path = "gs://my-bucket/templates/template_file"
  temp_gcs_location = "gs://my-bucket/tmp_dir"
  parameters {
    foo = "bar"
    baz = "qux"
  }
}
```

}

» Note on "destroy" / "apply"

There are many types of Dataflow jobs. Some Dataflow jobs run constantly, getting new data from (e.g.) a GCS bucket, and outputting data continuously. Some jobs process a set amount of data then terminate. All jobs can fail while running due to programming errors or other issues. In this way, Dataflow jobs are different from most other Terraform / Google resources.

The Dataflow resource is considered 'existing' while it is in a nonterminal state. If it reaches a terminal state (e.g. 'FAILED', 'COMPLETE', 'CANCELLED'), it will be recreated on the next 'apply'. This is as expected for jobs which run continuously, but may surprise users who use this resource for other kinds of Dataflow jobs.

A Dataflow job which is 'destroyed' may be "cancelled" or "drained". If "cancelled", the job terminates - any data written remains where it is, but no new data will be processed. If "drained", no new data will enter the pipeline, but any data currently in the pipeline will finish being processed. The default is "cancelled", but if a user sets `on_delete` to "drain" in the configuration, you may experience a long wait for your `terraform destroy` to complete.

» Argument Reference

The following arguments are supported:

- `name` - (Required) A unique name for the resource, required by Dataflow.
 - `template_gcs_path` - (Required) The GCS path to the Dataflow job template.
 - `temp_gcs_location` - (Required) A writeable location on GCS for the Dataflow job to dump its temporary data.
-
- `parameters` - (Optional) Key/Value pairs to be passed to the Dataflow job (as used in the template).
 - `max_workers` - (Optional) The number of workers permitted to work on the job. More workers may improve processing speed at additional cost.
 - `on_delete` - (Optional) One of "drain" or "cancel". Specifies behavior of deletion during `terraform destroy`. See above note.
 - `project` - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
 - `zone` - (Optional) The zone in which the created job should run. If it is not provided, the provider zone is used.

» Attributes Reference

- `state` - The current state of the resource, selected from the `JobState` enum

» `google_dataproc_cluster`

Manages a Cloud Dataproc cluster resource within GCP. For more information see the official [dataproc documentation](#).

Warning: Due to limitations of the API, all arguments except `labels`, `cluster_config.worker_config.num_instances` and `cluster_config.preemptible_worker_config.num_instances` are non-updateable. Changing others will cause recreation of the whole cluster!

» Example usage

```
resource "google_dataproc_cluster" "simplecluster" {
  name      = "simplecluster"
  region    = "us-central1"
}

resource "google_dataproc_cluster" "mycluster" {
  name      = "mycluster"
  region    = "us-central1"
  labels {
    foo = "bar"
  }

  cluster_config {
    staging_bucket = "dataproc-staging-bucket"

    master_config {
      num_instances = 1
      machine_type  = "n1-standard-1"
      disk_config {
        boot_disk_type = "pd-ssd"
        boot_disk_size_gb = 10
      }
    }

    worker_config {
      num_instances = 2
      machine_type  = "n1-standard-1"
      disk_config {
        boot_disk_size_gb = 10
      }
    }
  }
}
```



```

        num_local_ssds    = 1
    }
}

preemptible_worker_config {
    num_instances    = 0
}

# Override or set some custom properties
software_config {
    image_version      = "preview"
    override_properties = {
        "dataproc:dataproc.allow.zero.workers" = "true"
    }
}

gce_cluster_config {
    #network = "${google_compute_network.dataproc_network.name}"
    tags     = ["foo", "bar"]
}

# You can define multiple initialization_action blocks
initialization_action {
    script      = "gs://dataproc-initialization-actions/stackdriver/stackdriver.sh"
    timeout_sec = 500
}

}
}

```

» Argument Reference

- **name** - (Required) The name of the cluster, unique within the project and zone.
-
- **project** - (Optional) The ID of the project in which the **cluster** will exist. If it is not provided, the provider project is used.
 - **region** - (Optional) The region in which the cluster and associated nodes will be created in. Defaults to **global**.
 - **labels** - (Optional, Computed) The list of labels (key/value pairs) to be applied to instances in the cluster. GCP generates some itself including **goog-dataproc-cluster-name** which is the name of the cluster.

- **cluster_config** - (Optional) Allows you to configure various aspects of the cluster. Structure defined below.

The **cluster_config** block supports:

```
cluster_config {
  gce_cluster_config      { ... }
  master_config           { ... }
  worker_config           { ... }
  preemptible_worker_config { ... }
  software_config         { ... }

  # You can define multiple initialization_action blocks
  initialization_action    { ... }
}
```

- **staging_bucket** - (Optional) The Cloud Storage staging bucket used to stage files, such as Hadoop jars, between client machines and the cluster. Note: If you don't explicitly specify a **staging_bucket** then GCP will auto create / assign one for you. However, you are not guaranteed an auto generated bucket which is solely dedicated to your cluster; it may be shared with other clusters in the same region/zone also choosing to use the auto generation option.
- **delete_autogen_bucket** (Optional, Deprecated) If this is set to true, upon destroying the cluster, if no explicit **staging_bucket** was specified (i.e. an auto generated bucket was relied upon) then this auto generated bucket will also be deleted as part of the cluster destroy. By default this is set to false. This value is deprecated: autogenerated buckets are shared by all clusters in the same region, so deleting the bucket could adversely harm other dataproc clusters.
- **gce_cluster_config** (Optional) Common config settings for resources of Google Compute Engine cluster instances, applicable to all instances in the cluster. Structure defined below.
- **master_config** (Optional) The Google Compute Engine config settings for the master instances in a cluster.. Structure defined below.
- **worker_config** (Optional) The Google Compute Engine config settings for the worker instances in a cluster.. Structure defined below.
- **preemptible_worker_config** (Optional) The Google Compute Engine config settings for the additional (aka preemptible) instances in a cluster. Structure defined below.
- **software_config** (Optional) The config settings for software inside the cluster. Structure defined below.

- **initialization_action** (Optional) Commands to execute on each node after config is completed. You can specify multiple versions of these. Structure defined below.

The `cluster_config.gce_cluster_config` block supports:

```
cluster_config {
  gce_cluster_config {

    zone = "us-central1-a"

    # One of the below to hook into a custom network / subnetwork
    network    = "${google_compute_network.dataproc_network.name}"
    subnetwork = "${google_compute_network.dataproc_subnetwork.name}"

    tags      = ["foo", "bar"]
  }
}
```

- **zone** - (Optional, Computed) The GCP zone where your data is stored and used (i.e. where the master and the worker nodes will be created in). If **region** is set to 'global' (default) then **zone** is mandatory, otherwise GCP is able to make use of Auto Zone Placement to determine this automatically for you. Note: This setting additionally determines and restricts which computing resources are available for use with other configs such as `cluster_config.master_config.machine_type` and `cluster_config.worker_config.machine_type`.
- **network** - (Optional, Computed) The name or self_link of the Google Compute Engine network to the cluster will be part of. Conflicts with **subnetwork**. If neither is specified, this defaults to the "default" network.
- **subnetwork** - (Optional) The name or self_link of the Google Compute Engine subnetwork the cluster will be part of. Conflicts with **network**.
- **service_account** - (Optional) The service account to be used by the Node VMs. If not specified, the "default" service account is used.
- **service_account_scopes** - (Optional, Computed) The set of Google API scopes to be made available on all of the node VMs under the **service_account** specified. These can be either FQDNs, or scope aliases. The following scopes are necessary to ensure the correct functioning of the cluster:

- `useraccounts-ro` (<https://www.googleapis.com/auth/cloud.useraccounts.readonly>)
- `storage-rw` (https://www.googleapis.com/auth/devstorage.read_write)
- `logging-write` (<https://www.googleapis.com/auth/logging.write>)

- **tags** - (Optional) The list of instance tags applied to instances in the cluster. Tags are used to identify valid sources or targets for network firewalls.
- **internal_ip_only** - (Optional) By default, clusters are not restricted to internal IP addresses, and will have ephemeral external IP addresses assigned to each instance. If set to true, all instances in the cluster will only have internal IP addresses. Note: Private Google Access (also known as `privateIpGoogleAccess`) must be enabled on the subnetwork that the cluster will be launched in.

The `cluster_config.master_config` block supports:

```
cluster_config {
  master_config {
    num_instances      = 1
    machine_type       = "n1-standard-1"
    disk_config {
      boot_disk_type   = "pd-ssd"
      boot_disk_size_gb = 10
      num_local_ssds   = 1
    }
  }
}
```

- **num_instances** - (Optional, Computed) Specifies the number of master nodes to create. If not specified, GCP will default to a predetermined computed value (currently 1).
- **machine_type** - (Optional, Computed) The name of a Google Compute Engine machine type to create for the master. If not specified, GCP will default to a predetermined computed value (currently `n1-standard-4`).
- **disk_config** (Optional) Disk Config
 - **disk_config.boot_disk_type** - (Optional) The disk type of the primary disk attached to each node. One of `"pd-ssd"` or `"pd-standard"`. Defaults to `"pd-standard"`.
 - **disk_config.boot_disk_size_gb** - (Optional, Computed) Size of the primary disk attached to each node, specified in GB. The primary disk contains the boot volume and system libraries, and the smallest allowed disk size is 10GB. GCP will default to a predetermined computed value if not set (currently 500GB). Note: If SSDs are not attached, it also contains the HDFS data blocks and Hadoop working directories.
 - **disk_config.num_local_ssds** - (Optional) The amount of local SSD disks that will be attached to each master cluster node. Defaults to 0.

The `cluster_config.worker_config` block supports:

```
cluster_config {
  worker_config {
    num_instances      = 3
    machine_type       = "n1-standard-1"
    disk_config {
      boot_disk_type   = "pd-standard"
      boot_disk_size_gb = 10
      num_local_ssds   = 1
    }
  }
}
```

- `num_instances` - (Optional, Computed) Specifies the number of worker nodes to create. If not specified, GCP will default to a predetermined computed value (currently 2). There is currently a beta feature which allows you to run a Single Node Cluster. In order to take advantage of this you need to set `"dataproc:dataproc.allow.zero.workers" = "true"` in `cluster_config.software_config.properties`
- `machine_type` - (Optional, Computed) The name of a Google Compute Engine machine type to create for the worker nodes. If not specified, GCP will default to a predetermined computed value (currently `n1-standard-4`).
- `disk_config` (Optional) Disk Config
 - `disk_config.boot_disk_type` - (Optional) The disk type of the primary disk attached to each node. One of `"pd-ssd"` or `"pd-standard"`. Defaults to `"pd-standard"`.
 - `boot_disk_size_gb` - (Optional, Computed) Size of the primary disk attached to each worker node, specified in GB. The smallest allowed disk size is 10GB. GCP will default to a predetermined computed value if not set (currently 500GB). Note: If SSDs are not attached, it also contains the HDFS data blocks and Hadoop working directories.
 - `num_local_ssds` - (Optional) The amount of local SSD disks that will be attached to each worker cluster node. Defaults to 0.

The `cluster_config.preemptible_worker_config` block supports:

```
cluster_config {
  preemptible_worker_config {
    num_instances      = 1
    disk_config {
      boot_disk_size_gb = 10
    }
  }
}
```

```

    }
  }
}

```

Note: Unlike `worker_config`, you cannot set the `machine_type` value directly. This will be set for you based on whatever was set for the `worker_config.machine_type` value.

- `num_instances`- (Optional) Specifies the number of preemptible nodes to create. Defaults to 0.
- `disk_config` (Optional) Disk Config
 - `boot_disk_size_gb` - (Optional, Computed) Size of the primary disk attached to each preemptible worker node, specified in GB. The smallest allowed disk size is 10GB. GCP will default to a predetermined computed value if not set (currently 500GB). Note: If SSDs are not attached, it also contains the HDFS data blocks and Hadoop working directories.

The `cluster_config.software_config` block supports:

```

cluster_config {
  # Override or set some custom properties
  software_config {
    image_version      = "preview"
    override_properties = {
      "dataproc:dataproc.allow.zero.workers" = "true"
    }
  }
}

```

- `image_version` - (Optional, Computed) The Cloud Dataproc image version to use for the cluster - this controls the sets of software versions installed onto the nodes when you create clusters. If not specified, defaults to the latest version. For a list of valid versions see Cloud Dataproc versions
- `override_properties` - (Optional) A list of override and additional properties (key/value pairs) used to modify various aspects of the common configuration files used when creating a cluster. For a list of valid properties please see Cluster properties

The `initialization_action` block (Optional) can be specified multiple times and supports:

```

cluster_config {
  # You can define multiple initialization_action blocks

```

```

        initialization_action {
            script      = "gs://dataproc-initialization-actions/stackdriver/stackdriver.sh"
            timeout_sec = 500
        }
    }
}

```

- **script**- (Required) The script to be executed during initialization of the cluster. The script must be a GCS file with a `gs://` prefix.
- **timeout_sec** - (Optional, Computed) The maximum duration (in seconds) which **script** is allowed to take to execute its action. GCP will default to a predetermined computed value if not set (currently 300).

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **cluster_config.master_config.instance_names** - List of master instance names which have been assigned to the cluster.
- **cluster_config.worker_config.instance_names** - List of worker instance names which have been assigned to the cluster.
- **cluster_config.preemptible_worker_config.instance_names** - List of preemptible instance names which have been assigned to the cluster.
- **cluster_config.bucket** - The name of the cloud storage bucket ultimately used to house the staging data for the cluster. If **staging_bucket** is specified, it will contain this value, otherwise it will be the auto generated name.
- **cluster_config.software_config.properties** - A list of the properties used to set the daemon config files. This will include any values supplied by the user via **cluster_config.software_config.override_properties**

» Timeouts

`google_dataproc_cluster` provides the following Timeouts configuration options:

- **create** - (Default 10 minutes) Used for creating clusters.
- **update** - (Default 5 minutes) Used for updating clusters
- **delete** - (Default 5 minutes) Used for destroying clusters.

» google_dataproc_job

Manages a job resource within a Dataproc cluster within GCE. For more information see the official dataproc documentation.

Note: This resource does not support 'update' and changing any attributes will cause the resource to be recreated.

» Example usage

```
resource "google_dataproc_cluster" "mycluster" {
  name     = "dproc-cluster-unique-name"
  region   = "us-central1"
}

# Submit an example spark job to a dataproc cluster
resource "google_dataproc_job" "spark" {
  region           = "${google_dataproc_cluster.mycluster.region}"
  force_delete     = true
  placement {
    cluster_name = "${google_dataproc_cluster.mycluster.name}"
  }

  spark_config {
    main_class      = "org.apache.spark.examples.SparkPi"
    jar_file_uris   = ["file:///usr/lib/spark/examples/jars/spark-examples.jar"]
    args            = ["1000"]

    properties      = {
      "spark.logConf" = "true"
    }

    logging_config {
      driver_log_levels {
        "root" = "INFO"
      }
    }
  }
}

# Submit an example pyspark job to a dataproc cluster
resource "google_dataproc_job" "pyspark" {
  region           = "${google_dataproc_cluster.mycluster.region}"
  force_delete     = true
  placement {
```



```

        cluster_name = "${google_dataproc_cluster.mycluster.name}"
    }

    pyspark_config {
        main_python_file_uri = "gs://dataproc-examples-2f10d78d114f6aaec76462e3c310f31f/src/
        properties = {
            "spark.logConf" = "true"
        }
    }
}

# Check out current state of the jobs
output "spark_status" {
    value = "${google_dataproc_job.spark.status.0.state}"
}

output "pyspark_status" {
    value = "${google_dataproc_job.pyspark.status.0.state}"
}

```

» Argument Reference

- `placement.cluster_name` - (Required) The name of the cluster where the job will be submitted.
 - `xxx_config` - (Required) Exactly one of the specific job types to run on the cluster should be specified. If you want to submit multiple jobs, this will currently require the definition of multiple `google_dataproc_job` resources as shown in the example above, or by setting the `count` attribute. The following job configs are supported:
 - `pyspark_config` - Submits a PySpark job to the cluster
 - `spark_config` - Submits a Spark job to the cluster
 - `hadoop_config` - Submits a Hadoop job to the cluster
 - `hive_config` - Submits a Hive job to the cluster
 - `hpig_config` - Submits a Pig job to the cluster
 - `sparksql_config` - Submits a Spark SQL job to the cluster
-
- `project` - (Optional) The project in which the `cluster` can be found and jobs subsequently run against. If it is not provided, the provider project is used.
 - `region` - (Optional) The Cloud Dataproc region. This essentially determines which clusters are available for this job to be submitted to. If not specified, defaults to `global`.

- `force_delete` - (Optional) By default, you can only delete inactive jobs within Dataproc. Setting this to true, and calling destroy, will ensure that the job is first cancelled before issuing the delete.
- `labels` - (Optional) The list of labels (key/value pairs) to add to the job.
- `scheduling.max_failures_per_hour` - (Optional) Maximum number of times per hour a driver may be restarted as a result of driver terminating with non-zero code before job is reported failed.

The `pyspark_config` block supports:

Submitting a pyspark job to the cluster. Below is an example configuration:

```
# Submit a pyspark job to the cluster
resource "google_dataproc_job" "pyspark" {
  ...

  pyspark_config {
    main_python_file_uri = "gs://dataproc-examples-2f10d78d114f6aaec76462e3c310f31f/src/
    properties = {
      "spark.logConf" = "true"
    }
  }
}
```

For configurations requiring Hadoop Compatible File System (HCFS) references, the options below are generally applicable:

- GCS files with the ``gs://`` prefix
- HDFS files on the cluster with the ``hdfs://`` prefix
- Local files on the cluster with the ``file://`` prefix
- `main_python_file_uri`- (Required) The HCFS URI of the main Python file to use as the driver. Must be a .py file.
- `args` - (Optional) The arguments to pass to the driver.
- `python_file_uris` - (Optional) HCFS file URIs of Python files to pass to the PySpark framework. Supported file types: .py, .egg, and .zip.
- `jar_file_uris` - (Optional) HCFS URIs of jar files to add to the CLASSPATHs of the Python driver and tasks.
- `file_uris` - (Optional) HCFS URIs of files to be copied to the working directory of Python drivers and distributed tasks. Useful for naively parallel tasks.
- `archive_uris` - (Optional) HCFS URIs of archives to be extracted in the working directory of .jar, .tar, .tar.gz, .tgz, and .zip.
- `properties` - (Optional) A mapping of property names to values, used to configure PySpark. Properties that conflict with values set by the

Cloud Dataproc API may be overwritten. Can include properties set in `/etc/spark/conf/spark-defaults.conf` and classes in user code.

- **logging_config.driver_log_levels-** (Optional) The per-package log levels for the driver. This may include 'root' package name to configure rootLogger. Examples: 'com.google = FATAL', 'root = INFO', 'org.apache = DEBUG'

The `spark_config` block supports:

```
# Submit a spark job to the cluster
resource "google_dataproc_job" "spark" {
  ...

  spark_config {
    main_class      = "org.apache.spark.examples.SparkPi"
    jar_file_uris   = ["file:///usr/lib/spark/examples/jars/spark-examples.jar"]
    args            = ["1000"]

    properties      = {
      "spark.logConf" = "true"
    }

    logging_config {
      driver_log_levels {
        "root" = "INFO"
      }
    }
  }
}
```

- **main_class-** (Optional) The class containing the main method of the driver. Must be in a provided jar or jar that is already on the classpath. Conflicts with `main_jar_file_uri`
- **main_jar_file_uri** - (Optional) The HCFS URI of jar file containing the driver jar. Conflicts with `main_class`
- **args** - (Optional) The arguments to pass to the driver.
- **jar_file_uris** - (Optional) HCFS URIs of jar files to add to the CLASSPATHs of the Spark driver and tasks.
- **file_uris** - (Optional) HCFS URIs of files to be copied to the working directory of Spark drivers and distributed tasks. Useful for naively parallel tasks.
- **archive_uris** - (Optional) HCFS URIs of archives to be extracted in the working directory of .jar, .tar, .tar.gz, .tgz, and .zip.

- **properties** - (Optional) A mapping of property names to values, used to configure Spark. Properties that conflict with values set by the Cloud Dataproc API may be overwritten. Can include properties set in `/etc/spark/conf/spark-defaults.conf` and classes in user code.
- **logging_config.driver_log_levels**- (Optional) The per-package log levels for the driver. This may include 'root' package name to configure rootLogger. Examples: 'com.google = FATAL', 'root = INFO', 'org.apache = DEBUG'

The `hadoop_config` block supports:

```
# Submit a hadoop job to the cluster
resource "google_dataproc_job" "hadoop" {
  ...

  hadoop_config {
    main_jar_file_uri = "file:///usr/lib/hadoop-mapreduce/hadoop-mapreduce-examples.jar"
    args              = [
      "wordcount",
      "file:///usr/lib/spark/NOTICE",
      "gs://${google_dataproc_cluster.basic_cluster_config.0.bucket}/hadoopjob_output"
    ]
  }
}
```

- **main_class**- (Optional) The name of the driver's main class. The jar file containing the class must be in the default CLASSPATH or specified in `jar_file_uris`. Conflicts with `main_jar_file_uri`
- **main_jar_file_uri** - (Optional) The HCFS URI of the jar file containing the main class. Examples: 'gs://foo-bucket/analytics-binaries/extract-useful-metrics-mr.jar' 'hdfs://tmp/test-samples/custom-wordcount.jar' 'file:///home/usr/lib/hadoop-mapreduce/hadoop-mapreduce-examples.jar'. Conflicts with `main_class`
- **args** - (Optional) The arguments to pass to the driver. Do not include arguments, such as `-libjars` or `-Dfoo=bar`, that can be set as job properties, since a collision may occur that causes an incorrect job submission.
- **jar_file_uris** - (Optional) HCFS URIs of jar files to add to the CLASSPATHs of the Spark driver and tasks.
- **file_uris** - (Optional) HCFS URIs of files to be copied to the working directory of Hadoop drivers and distributed tasks. Useful for naively parallel tasks.
- **archive_uris** - (Optional) HCFS URIs of archives to be extracted in the working directory of `.jar`, `.tar`, `.tar.gz`, `.tgz`, and `.zip`.

- **properties** - (Optional) A mapping of property names to values, used to configure Hadoop. Properties that conflict with values set by the Cloud Dataproc API may be overwritten. Can include properties set in `/etc/hadoop/conf/*-site` and classes in user code..
- **logging_config.driver_log_levels**- (Optional) The per-package log levels for the driver. This may include 'root' package name to configure rootLogger. Examples: 'com.google = FATAL', 'root = INFO', 'org.apache = DEBUG'

The `hive_config` block supports:

```
# Submit a hive job to the cluster
resource "google_dataproc_job" "hive" {
  ...

  hive_config {
    query_list = [
      "DROP TABLE IF EXISTS dprocjob_test",
      "CREATE EXTERNAL TABLE dprocjob_test(bar int) LOCATION 'gs://${google_dataproc_...}',
      "SELECT * FROM dprocjob_test WHERE bar > 2",
    ]
  }
}
```

- **query_list**- (Optional) The list of Hive queries or statements to execute as part of the job. Conflicts with `query_file_uri`
- **query_file_uri** - (Optional) HCFS URI of file containing Hive script to execute as the job. Conflicts with `query_list`
- **continue_on_failure** - (Optional) Whether to continue executing queries if a query fails. The default value is false. Setting to true can be useful when executing independent parallel queries. Defaults to false.
- **script_variables** - (Optional) Mapping of query variable names to values (equivalent to the Hive command: `SET name="value";`).
- **properties** - (Optional) A mapping of property names and values, used to configure Hive. Properties that conflict with values set by the Cloud Dataproc API may be overwritten. Can include properties set in `/etc/hadoop/conf/*-site.xml`, `/etc/hive/conf/hive-site.xml`, and classes in user code..
- **jar_file_uris** - (Optional) HCFS URIs of jar files to add to the CLASSPATH of the Hive server and Hadoop MapReduce (MR) tasks. Can contain Hive SerDes and UDFs.

The `pig_config` block supports:

```
# Submit a pig job to the cluster
```

```

resource "google_dataproc_job" "pig" {
  ...

  pig_config {
    query_list = [
      "LNS = LOAD 'file:///usr/lib/pig/LICENSE.txt ' AS (line)",
      "WORDS = FOREACH LNS GENERATE FLATTEN(TOKENIZE(line)) AS word",
      "GROUPS = GROUP WORDS BY word",
      "WORD_COUNTS = FOREACH GROUPS GENERATE group, COUNT(WORDS)",
      "DUMP WORD_COUNTS"
    ]
  }
}

```

- **query_list**- (Optional) The list of Hive queries or statements to execute as part of the job. Conflicts with **query_file_uri**
- **query_file_uri** - (Optional) HCFS URI of file containing Hive script to execute as the job. Conflicts with **query_list**
- **continue_on_failure** - (Optional) Whether to continue executing queries if a query fails. The default value is false. Setting to true can be useful when executing independent parallel queries. Defaults to false.
- **script_variables** - (Optional) Mapping of query variable names to values (equivalent to the Pig command: **name=[value]**).
- **properties** - (Optional) A mapping of property names to values, used to configure Pig. Properties that conflict with values set by the Cloud Dataproc API may be overwritten. Can include properties set in `/etc/hadoop/conf/*-site.xml`, `/etc/pig/conf/pig.properties`, and classes in user code.
- **jar_file_uris** - (Optional) HCFS URIs of jar files to add to the CLASSPATH of the Pig Client and Hadoop MapReduce (MR) tasks. Can contain Pig UDFs.
- **logging_config.driver_log_levels**- (Optional) The per-package log levels for the driver. This may include 'root' package name to configure rootLogger. Examples: 'com.google = FATAL', 'root = INFO', 'org.apache = DEBUG'

The **sparksql_config** block supports:

```

# Submit a spark SQL job to the cluster
resource "google_dataproc_job" "sparksql" {
  ...

  sparksql_config {
    query_list = [

```

```

        "DROP TABLE IF EXISTS dprocjob_test",
        "CREATE TABLE dprocjob_test(bar int)",
        "SELECT * FROM dprocjob_test WHERE bar > 2",
    ]
}
}

```

- **query_list**- (Optional) The list of SQL queries or statements to execute as part of the job. Conflicts with **query_file_uri**
- **query_file_uri** - (Optional) The HCFS URI of the script that contains SQL queries. Conflicts with **query_list**
- **script_variables** - (Optional) Mapping of query variable names to values (equivalent to the Spark SQL command: **SET name="value";**).
- **properties** - (Optional) A mapping of property names to values, used to configure Spark SQL's SparkConf. Properties that conflict with values set by the Cloud Dataproc API may be overwritten.
- **jar_file_uris** - (Optional) HCFS URIs of jar files to be added to the Spark CLASSPATH.
- **logging_config.driver_log_levels**- (Optional) The per-package log levels for the driver. This may include 'root' package name to configure rootLogger. Examples: 'com.google = FATAL', 'root = INFO', 'org.apache = DEBUG'

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **reference.0.cluster_uuid** - A cluster UUID generated by the Cloud Dataproc service when the job is submitted.
- **status.0.state** - A state message specifying the overall job state.
- **status.0.details** - Optional job state details, such as an error description if the state is ERROR.
- **status.0.state_start_time** - The time when this state was entered.
- **status.0.substate** - Additional state information, which includes status reported by the agent.
- **driver_output_resource_uri** - A URI pointing to the location of the stdout of the job's driver program.
- **driver_controls_files_uri** - If present, the location of miscellaneous control files which may be used as part of job setup and handling.

If not present, control files may be placed in the same location as `driver_output_uri`.

» Timeouts

`google_dataproc_cluster` provides the following Timeouts configuration options:

- **create** - (Default 10 minutes) Used for submitting a job to a dataproc cluster.
- **delete** - (Default 10 minutes) Used for deleting a job from a dataproc cluster.

» google_dns_managed_zone

Manages a zone within Google Cloud DNS. For more information see the official documentation and API.

» Example Usage

```
resource "google_dns_managed_zone" "prod" {
  name          = "prod-zone"
  dns_name      = "prod.mydomain.com."
  description    = "Production DNS zone"
}
```

» Argument Reference

The following arguments are supported:

- **dns_name** - (Required) The fully qualified DNS name of this zone, e.g. `terraform.io..`
 - **name** - (Required) A unique name for the resource, required by GCE. Changing this forces a new resource to be created.
-
- **description** - (Optional) A textual description field. Defaults to 'Managed by Terraform'.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **name_servers** - The list of nameservers that will be authoritative for this domain. Use NS records to redirect from your DNS provider to these names, thus making Google Cloud DNS authoritative for this zone.

» Import

DNS managed zones can be imported using the **name**, e.g.

```
$ terraform import google_dns_managed_zone.prod prod-zone
```

» google_dns_record_set

Manages a set of DNS records within Google Cloud DNS. For more information see the official documentation and API.

Note: The Google Cloud DNS API requires NS records be present at all times. To accommodate this, when creating NS records, the default records Google automatically creates will be silently overwritten. Also, when destroying NS records, Terraform will not actually remove NS records, but will report that it did.

» Example Usage

» Binding a DNS name to the ephemeral IP of a new instance:

```
resource "google_dns_record_set" "frontend" {
  name = "frontend.${google_dns_managed_zone.prod.dns_name}"
  type = "A"
  ttl  = 300

  managed_zone = "${google_dns_managed_zone.prod.name}"

  rrdatas = ["${google_compute_instance.frontend.network_interface.0.access_config.0.assigne
}

resource "google_compute_instance" "frontend" {
  name          = "frontend"
  machine_type  = "g1-small"
  zone         = "us-central1-b"
```

```

boot_disk {
  initialize_params {
    image = "debian-cloud/debian-8"
  }
}

network_interface {
  network      = "default"
  access_config = {}
}
}

resource "google_dns_managed_zone" "prod" {
  name      = "prod-zone"
  dns_name = "prod.mydomain.com."
}

```

» Adding an A record

```

resource "google_dns_record_set" "a" {
  name      = "backend.${google_dns_managed_zone.prod.dns_name}"
  managed_zone = "${google_dns_managed_zone.prod.name}"
  type      = "A"
  ttl       = 300

  rrdatas = ["8.8.8.8"]
}

resource "google_dns_managed_zone" "prod" {
  name      = "prod-zone"
  dns_name = "prod.mydomain.com."
}

```

» Adding an MX record

```

resource "google_dns_record_set" "mx" {
  name      = "${google_dns_managed_zone.prod.dns_name}"
  managed_zone = "${google_dns_managed_zone.prod.name}"
  type      = "MX"
  ttl       = 3600

  rrdatas = [
    "1 aspmx.l.google.com.",

```

```

        "5 alt1.aspmx.1.google.com.",
        "5 alt2.aspmx.1.google.com.",
        "10 alt3.aspmx.1.google.com.",
        "10 alt4.aspmx.1.google.com."
    ]
}

resource "google_dns_managed_zone" "prod" {
    name      = "prod-zone"
    dns_name = "prod.mydomain.com."
}

```

» Adding an SPF record

Quotes (") must be added around your `rrdatas` for a SPF record. Otherwise `rrdatas` string gets split on spaces.

```

resource "google_dns_record_set" "spf" {
    name      = "frontend.${google_dns_managed_zone.prod.dns_name}"
    managed_zone = "${google_dns_managed_zone.prod.name}"
    type      = "TXT"
    ttl       = 300

    rrdatas = ["\"v=spf1 ip4:111.111.111.111 include:backoff.email-example.com -all\""]
}

resource "google_dns_managed_zone" "prod" {
    name      = "prod-zone"
    dns_name = "prod.mydomain.com."
}

```

» Argument Reference

The following arguments are supported:

- **managed_zone** - (Required) The name of the zone in which this record set will reside.
- **name** - (Required) The DNS name this record set will apply to.
- **rrdatas** - (Required) The string data for the records in this record set whose meaning depends on the DNS type. For TXT record, if the string data contains spaces, add surrounding \" if you don't want your string to get split on spaces.
- **ttl** - (Required) The time-to-live of this record set (seconds).

- **type** - (Required) The DNS record set type.

-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» Import

DNS record set can be imported using the `zone name`, `record name` and `record type`, e.g.

```
$ terraform import google_dns_record_set.frontend prod-zone/frontend.prod.mydomain.com./A
```

Note: The record name must include the trailing dot at the end.

» google__endpoints__service

This resource creates and rolls out a Cloud Endpoints service using OpenAPI or gRPC. View the relevant docs for OpenAPI and gRPC.

» Example Usage

```
resource "google_endpoints_service" "openapi_service" {
  service_name = "api-name.endpoints.project-id.cloud.goog"
  project      = "project-id"
  openapi_config = "${file("openapi_spec.yml")}"
}
```

```
resource "google_endpoints_service" "grpc_service" {
  service_name = "api-name.endpoints.project-id.cloud.goog"
  project      = "project-id"
  grpc_config  = "${file("service_spec.yml")}"
  protoc_output = "${file("compiled_descriptor_file.pb")}"
}
```

The example in `examples/endpoints_on_compute_engine` shows the API from the quickstart running on a Compute Engine VM and reachable through Cloud Endpoints, which may also be useful.

» Argument Reference

The following arguments are supported: * **service_name**: (Required) The name of the service. Usually of the form `$apiname.endpoints.$projectid.cloud.goog`. * **openapi_config**: (Optional) The full text of the OpenAPI YAML configuration as described here. Either this, or *both* of **grpc_config** and **protoc_output** must be specified. * **grpc_config**: (Optional) The full text of the Service Config YAML file (Example located here). If provided, must also provide **protoc_output**. **open_api** config must *not* be provided. * **protoc_output_base64**: (Optional) The full contents of the Service Descriptor File generated by protoc. This should be a compiled .pb file, base64-encoded. * **protoc_output**: (Deprecated) The full contents of the Service Descriptor File generated by protoc. This should be a compiled .pb file. Use **protoc_output_base64** instead to prevent a permanent diff from the statefile's munging of non-UTF8 bytes. * **project**: (Optional) The project ID that the service belongs to. If not provided, provider project is used.

» Attributes Reference

In addition to the arguments, the following attributes are available: * **config_id**: The autogenerated ID for the configuration that is rolled out as part of the creation of this resource. Must be provided to compute engine instances as a tag. * **dns_address**: The address at which the service can be found - usually the same as the service name. * **apis**: A list of API objects; structure is documented below. * **endpoints**: A list of Endpoint objects; structure is documented below.

» API Object Structure

- **name**: The FQDN of the API as described in the provided config.
- **syntax**: SYNTAX_PROTO2 or SYNTAX_PROTO3.
- **version**: A version string for this api. If specified, will have the form major-version.minor-version, e.g. 1.10.
- **methods**: A list of Method objects; structure is documented below.

» Method Object Structure

- **name**: The simple name of this method as described in the provided config.
- **syntax**: SYNTAX_PROTO2 or SYNTAX_PROTO3.
- **request_type**: The type URL for the request to this API.
- **response_type**: The type URL for the response from this API.

» Endpoint Object Structure

- **name:** The simple name of the endpoint as described in the config.
- **address:** The FQDN of the endpoint as described in the config.

» google__pubsub__subscription

Creates a subscription in Google's pubsub queueing system. For more information see the official documentation and API.

» Example Usage

```
resource "google_pubsub_topic" "default-topic" {
  name = "default-topic"
}

resource "google_pubsub_subscription" "default" {
  name     = "default-subscription"
  topic    = "${google_pubsub_topic.default-topic.name}"

  ack_deadline_seconds = 20

  push_config {
    push_endpoint = "https://example.com/push"

    attributes {
      x-goog-version = "v1"
    }
  }
}
```

If the subscription has a topic in a different project:

```
resource "google_pubsub_topic" "topic-different-project" {
  project = "another-project"
  name    = "topic-different-project"
}

resource "google_pubsub_subscription" "default" {
  name     = "default-subscription"
  topic    = "${google_pubsub_topic.topic-different-project.id}"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the resource, required by pubsub. Changing this forces a new resource to be created.
 - **topic** - (Required) The topic name or id to bind this subscription to, required by pubsub. Changing this forces a new resource to be created.
-
- **ack_deadline_seconds** - (Optional) The maximum number of seconds a subscriber has to acknowledge a received message, otherwise the message is redelivered. Changing this forces a new resource to be created.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
 - **push_config** - (Optional) Block configuration for push options. More configuration options are detailed below.

The optional **push_config** block supports:

- **push_endpoint** - (Required) The URL of the endpoint to which messages should be pushed. Changing this forces a new resource to be created.
- **attributes** - (Optional) Key-value pairs of API supported attributes used to control aspects of the message delivery. Currently, only **x-goog-version** is supported, which controls the format of the data delivery. For more information, read the API docs [here](#). Changing this forces a new resource to be created.

» Attributes Reference

- **path** - Path of the subscription in the format `projects/{project}/subscriptions/{sub}`

» Import

Pubsub subscription can be imported using the **name**, e.g.

```
$ terraform import google_pubsub_subscription.default default-subscription
```

» IAM policy for Pubsub Subscription

Three different resources help you manage your IAM policy for pubsub subscription. Each of these resources serves a different use case:

- `google_pubsub_subscription_iam_policy`: Authoritative. Sets the IAM policy for the subscription and replaces any existing policy already attached.
- `google_pubsub_subscription_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the subscription are preserved.
- `google_pubsub_subscription_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the subscription are preserved.

Note: `google_pubsub_subscription_iam_policy` **cannot** be used in conjunction with `google_pubsub_subscription_iam_binding` and `google_pubsub_subscription_iam_member` or they will fight over what your policy should be.

Note: `google_pubsub_subscription_iam_binding` resources **can be** used in conjunction with `google_pubsub_subscription_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_pubsub_subscription_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role    = "roles/editor"
    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_pubsub_subscription_iam_policy" "editor" {
  subscription = "your-subscription-name"
  policy_data  = "${data.google_iam_policy.admin.policy_data}"
}
```

» `google_pubsub_subscription_iam_binding`

```
resource "google_pubsub_subscription_iam_binding" "editor" {
  subscription = "your-subscription-name"
  role         = "roles/editor"
  members      = [
    "user:jane@example.com",
  ]
}
```


» `google_pubsub_subscription_iam_member`

```
resource "google_pubsub_subscription_iam_member" "editor" {
  subscription = "your-subscription-name"
  role         = "roles/editor"
  member       = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **subscription** - (Required) The subscription name or id to bind to attach IAM policy to.
 - **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
 - **role** - (Required) The role that should be applied. Only one `google_pubsub_subscription_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
 - **policy_data** - (Required only by `google_pubsub_subscription_iam_policy`) The policy data generated by a `google_iam_policy` data source.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `etag` - (Computed) The etag of the subscription's IAM policy.

» Import

Pubsub subscription IAM resources can be imported using the project, subscription name, role and member.

```
$ terraform import google_pubsub_subscription_iam_policy.editor projects/{your-project-id}/s
```

```
$ terraform import google_pubsub_subscription_iam_binding.editor "projects/{your-project-id}/s
```

```
$ terraform import google_pubsub_subscription_iam_member.editor "projects/{your-project-id}/s
```

» IAM policy for Pubsub Subscription

Three different resources help you manage your IAM policy for pubsub subscription. Each of these resources serves a different use case:

- `google_pubsub_subscription_iam_policy`: Authoritative. Sets the IAM policy for the subscription and replaces any existing policy already attached.
- `google_pubsub_subscription_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the subscription are preserved.
- `google_pubsub_subscription_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the subscription are preserved.

Note: `google_pubsub_subscription_iam_policy` **cannot** be used in conjunction with `google_pubsub_subscription_iam_binding` and `google_pubsub_subscription_iam_member` or they will fight over what your policy should be.

Note: `google_pubsub_subscription_iam_binding` resources **can be** used in conjunction with `google_pubsub_subscription_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_pubsub_subscription_iam_policy`

```
data "google_iam_policy" "admin" {
```

```

binding {
  role    = "roles/editor"
  members = [
    "user:jane@example.com",
  ]
}

resource "google_pubsub_subscription_iam_policy" "editor" {
  subscription = "your-subscription-name"
  policy_data  = "${data.google_iam_policy.admin.policy_data}"
}

```

» google_pubsub_subscription_iam_binding

```

resource "google_pubsub_subscription_iam_binding" "editor" {
  subscription = "your-subscription-name"
  role         = "roles/editor"
  members      = [
    "user:jane@example.com",
  ]
}

```

» google_pubsub_subscription_iam_member

```

resource "google_pubsub_subscription_iam_member" "editor" {
  subscription = "your-subscription-name"
  role         = "roles/editor"
  member       = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **subscription** - (Required) The subscription name or id to bind to attach IAM policy to.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.

- **user:{emailid}**: An email address that represents a specific Google account. For example, alice@gmail.com or joe@example.com.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, my-other-app@appspot.gserviceaccount.com.
 - **group:{emailid}**: An email address that represents a Google group. For example, admins@example.com.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Only one `google_pubsub_subscription_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
 - **policy_data** - (Required only by `google_pubsub_subscription_iam_policy`) The policy data generated by a `google_iam_policy` data source.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the subscription's IAM policy.

» Import

Pubsub subscription IAM resources can be imported using the project, subscription name, role and member.

```
$ terraform import google_pubsub_subscription_iam_policy.editor projects/{your-project-id}/s
```

```
$ terraform import google_pubsub_subscription_iam_binding.editor "projects/{your-project-id}/s
```

```
$ terraform import google_pubsub_subscription_iam_member.editor "projects/{your-project-id}/s
```

» IAM policy for Pubsub Subscription

Three different resources help you manage your IAM policy for pubsub subscription. Each of these resources serves a different use case:

- `google_pubsub_subscription_iam_policy`: Authoritative. Sets the IAM policy for the subscription and replaces any existing policy already attached.
- `google_pubsub_subscription_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the subscription are preserved.
- `google_pubsub_subscription_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the subscription are preserved.

Note: `google_pubsub_subscription_iam_policy` **cannot** be used in conjunction with `google_pubsub_subscription_iam_binding` and `google_pubsub_subscription_iam_member` or they will fight over what your policy should be.

Note: `google_pubsub_subscription_iam_binding` resources **can be** used in conjunction with `google_pubsub_subscription_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_pubsub_subscription_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role    = "roles/editor"
    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_pubsub_subscription_iam_policy" "editor" {
  subscription = "your-subscription-name"
  policy_data  = "${data.google_iam_policy.admin.policy_data}"
}
```

» `google_pubsub_subscription_iam_binding`

```
resource "google_pubsub_subscription_iam_binding" "editor" {
  subscription = "your-subscription-name"
  role         = "roles/editor"
  members      = [
    "user:jane@example.com",
  ]
}
```

» `google_pubsub_subscription_iam_member`

```
resource "google_pubsub_subscription_iam_member" "editor" {
  subscription = "your-subscription-name"
  role         = "roles/editor"
  member       = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **subscription** - (Required) The subscription name or id to bind to attach IAM policy to.
 - **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
 - **role** - (Required) The role that should be applied. Only one `google_pubsub_subscription_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
 - **policy_data** - (Required only by `google_pubsub_subscription_iam_policy`) The policy data generated by a `google_iam_policy` data source.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the subscription's IAM policy.

» Import

Pubsub subscription IAM resources can be imported using the project, subscription name, role and member.

```
$ terraform import google_pubsub_subscription_iam_policy.editor projects/{your-project-id}/s
```

```
$ terraform import google_pubsub_subscription_iam_binding.editor "projects/{your-project-id}
```

```
$ terraform import google_pubsub_subscription_iam_member.editor "projects/{your-project-id}/
```

» google__pubsub__topic

Creates a topic in Google's pubsub queueing system. For more information see the official documentation and API.

» Example Usage

```
resource "google_pubsub_topic" "mytopic" {  
  name = "default-topic"  
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the pubsub topic. Changing this forces a new resource to be created.
-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» Import

Pubsub topics can be imported using the `name` or full topic id, e.g.

```
$ terraform import google_pubsub_topic.mytopic default-topic
```

```
$ terraform import google_pubsub_topic.mytopic projects/my-gcp-project/topics/default-topic
```

When importing using only the name, the provider project must be set.

» IAM policy for Pubsub Topic

Three different resources help you manage your IAM policy for pubsub topic. Each of these resources serves a different use case:

- `google_pubsub_topic_iam_policy`: Authoritative. Sets the IAM policy for the topic and replaces any existing policy already attached.
- `google_pubsub_topic_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the topic are preserved.
- `google_pubsub_topic_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the topic are preserved.

Note: `google_pubsub_topic_iam_policy` **cannot** be used in conjunction with `google_pubsub_topic_iam_binding` and `google_pubsub_topic_iam_member` or they will fight over what your policy should be.

Note: `google_pubsub_topic_iam_binding` resources **can be** used in conjunction with `google_pubsub_topic_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_pubsub_topic_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role    = "roles/editor"
    members = [
      "user:jane@example.com",
    ]
  }
}
```



```

}

resource "google_pubsub_topic_iam_policy" "editor" {
  topic      = "your-topic-name"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}

```

» google_pubsub_topic_iam_binding

```

resource "google_pubsub_topic_iam_binding" "editor" {
  topic  = "your-topic-name"
  role   = "roles/editor"
  members = [
    "user:jane@example.com",
  ]
}

```

» google_pubsub_topic_iam_member

```

resource "google_pubsub_topic_iam_member" "editor" {
  topic  = "your-topic-name"
  role   = "roles/editor"
  member = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **topic** - (Required) The topic name or id to bind to attach IAM policy to.
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.

- **serviceAccount:{emailid}**: An email address that represents a service account. For example, my-other-app@appspot.gserviceaccount.com.
 - **group:{emailid}**: An email address that represents a Google group. For example, admins@example.com.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Only one `google_pubsub_topic_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
 - **policy_data** - (Required only by `google_pubsub_topic_iam_policy`) The policy data generated by a `google_iam_policy` data source.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the topic's IAM policy.

» Import

Pubsub topic IAM resources can be imported using the project, topic name, role and member.

```
$ terraform import google_pubsub_topic_iam_policy.editor projects/{your-project-id}/topics/{topic-name}
```

```
$ terraform import google_pubsub_topic_iam_binding.editor "projects/{your-project-id}/topics/{topic-name}:{role-name}"
```

```
$ terraform import google_pubsub_topic_iam_member.editor "projects/{your-project-id}/topics/{topic-name}:{role-name}:{member-email-address}"
```

» IAM policy for Pubsub Topic

Three different resources help you manage your IAM policy for pubsub topic. Each of these resources serves a different use case:

- **google_pubsub_topic_iam_policy**: Authoritative. Sets the IAM policy for the topic and replaces any existing policy already attached.
- **google_pubsub_topic_iam_binding**: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the topic are preserved.

- `google_pubsub_topic_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the topic are preserved.

Note: `google_pubsub_topic_iam_policy` **cannot** be used in conjunction with `google_pubsub_topic_iam_binding` and `google_pubsub_topic_iam_member` or they will fight over what your policy should be.

Note: `google_pubsub_topic_iam_binding` resources **can be** used in conjunction with `google_pubsub_topic_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_pubsub_topic_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role   = "roles/editor"
    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_pubsub_topic_iam_policy" "editor" {
  topic      = "your-topic-name"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» `google_pubsub_topic_iam_binding`

```
resource "google_pubsub_topic_iam_binding" "editor" {
  topic   = "your-topic-name"
  role    = "roles/editor"
  members = [
    "user:jane@example.com",
  ]
}
```

» `google_pubsub_topic_iam_member`

```
resource "google_pubsub_topic_iam_member" "editor" {
  topic   = "your-topic-name"
  role    = "roles/editor"
  member  = "user:jane@example.com"
}
```

}

» Argument Reference

The following arguments are supported:

- **topic** - (Required) The topic name or id to bind to attach IAM policy to.
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_pubsub_topic_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_pubsub_topic_iam_policy`) The policy data generated by a `google_iam_policy` data source.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the topic's IAM policy.

» Import

Pubsub topic IAM resources can be imported using the project, topic name, role and member.

```
$ terraform import google_pubsub_topic_iam_policy.editor projects/{your-project-id}/topics/{your-topic-name}

$ terraform import google_pubsub_topic_iam_binding.editor "projects/{your-project-id}/topics/{your-topic-name}/bindings/{role}"

$ terraform import google_pubsub_topic_iam_member.editor "projects/{your-project-id}/topics/{your-topic-name}/members/{member}"
```

» IAM policy for Pubsub Topic

Three different resources help you manage your IAM policy for pubsub topic. Each of these resources serves a different use case:

- `google_pubsub_topic_iam_policy`: Authoritative. Sets the IAM policy for the topic and replaces any existing policy already attached.
- `google_pubsub_topic_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the topic are preserved.
- `google_pubsub_topic_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the topic are preserved.

Note: `google_pubsub_topic_iam_policy` **cannot** be used in conjunction with `google_pubsub_topic_iam_binding` and `google_pubsub_topic_iam_member` or they will fight over what your policy should be.

Note: `google_pubsub_topic_iam_binding` resources **can be** used in conjunction with `google_pubsub_topic_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_pubsub_topic_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role    = "roles/editor"
    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_pubsub_topic_iam_policy" "editor" {
  topic      = "your-topic-name"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» google_pubsub_topic_iam_binding

```
resource "google_pubsub_topic_iam_binding" "editor" {
  topic    = "your-topic-name"
  role     = "roles/editor"
  members = [
    "user:jane@example.com",
  ]
}
```

» google_pubsub_topic_iam_member

```
resource "google_pubsub_topic_iam_member" "editor" {
  topic    = "your-topic-name"
  role     = "roles/editor"
  member   = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **topic** - (Required) The topic name or id to bind to attach IAM policy to.
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.

- **role** - (Required) The role that should be applied. Only one `google_pubsub_topic_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_pubsub_topic_iam_policy`) The policy data generated by a `google_iam_policy` data source.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the topic's IAM policy.

» Import

Pubsub topic IAM resources can be imported using the project, topic name, role and member.

```
$ terraform import google_pubsub_topic_iam_policy.editor projects/{your-project-id}/topics/{topic-name}
```

```
$ terraform import google_pubsub_topic_iam_binding.editor "projects/{your-project-id}/topics/{topic-name}:{role-name}:{member-name}"
```

```
$ terraform import google_pubsub_topic_iam_member.editor "projects/{your-project-id}/topics/{topic-name}:{role-name}:{member-name}"
```

» google__redis__instance

A Google Cloud Redis instance.

To get more information about Instance, see:

- API documentation
- How-to Guides
 - Official Documentation

» Example Usage

» Basic Usage

```
resource "google_redis_instance" "test" {
  name          = "%s"
  memory_size_gb = 1
}
```

» Full Usage

```
resource "google_compute_network" "test" {
  name = "%s"
}

resource "google_redis_instance" "test" {
  name          = "%s"
  tier           = "STANDARD_HA"
  memory_size_gb = 1

  region          = "us-central1"
  location_id     = "us-central1-a"
  alternative_location_id = "us-central1-f"

  authorized_network = "${google_compute_network.test.self_link}"

  redis_version      = "REDIS_3_2"
  display_name       = "Terraform Test Instance"
  reserved_ip_range = "192.168.0.0/29"

  labels {
    my_key    = "my_val"
    other_key = "other_val"
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The ID of the instance or a fully qualified identifier for the instance.
 - **memory_size_gb** - (Required) Redis memory size in GiB.
-
- **alternative_location_id** - (Optional) Only applicable to STANDARD_HA tier which protects the instance against zonal failures by provisioning it across two zones. If provided, it must be a different zone from the one provided in [locationId].
 - **authorized_network** - (Optional) The full name of the Google Compute Engine network to which the instance is connected. If left unspecified, the default network will be used.

- **display_name** - (Optional) An arbitrary and optional user-provided name for the instance.
- **labels** - (Optional) Resource labels to represent user provided metadata.
- **redis_configs** - (Optional) Redis configuration parameters, according to <http://redis.io/topics/config>.
- **location_id** - (Optional) The zone where the instance will be provisioned. If not provided, the service will choose a zone for the instance. For STANDARD_HA tier, instances will be created across two zones for protection against zonal failures. If [alternativeLocationId] is also provided, it must be different from [locationId].
- **redis_version** - (Optional) The version of Redis software. If not provided, latest supported version will be used. Updating the version will perform an upgrade/downgrade to the new version. Currently, the supported values are REDIS_3_2 for Redis 3.2.
- **reserved_ip_range** - (Optional) The CIDR range of internal addresses that are reserved for this instance. If not provided, the service will choose an unused /29 block, for example, 10.0.0.0/29 or 192.168.0.0/29. Ranges must be unique and non-overlapping with existing subnets in an authorized network.
- **tier** - (Optional) The service tier of the instance. Must be one of these values:
 - BASIC: standalone instance
 - STANDARD_HA: highly available primary/replica instances
- **region** - (Optional) The name of the Redis region of the instance.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **create_time** - The time the instance was created in RFC3339 UTC "Zulu" format, accurate to nanoseconds.
- **current_location_id** - The current zone where the Redis endpoint is placed. For Basic Tier instances, this will always be the same as the [locationId] provided by the user at creation time. For Standard Tier instances, this can be either [locationId] or [alternativeLocationId] and can change after a failover event.

- **host** - Hostname or IP address of the exposed Redis endpoint used by clients to connect to the service.
- **port** - The port number of the exposed Redis endpoint.

» Timeouts

This resource provides the following Timeouts configuration options:

- **create** - Default is 6 minutes.
- **update** - Default is 4 minutes.
- **delete** - Default is 4 minutes.

» Import

Instance can be imported using any of these accepted formats:

```
$ terraform import google_redis_instance.default projects/{{project}}/locations/{{region}}/instances/{{name}}
$ terraform import google_redis_instance.default {{project}}/{{region}}/{{name}}
$ terraform import google_redis_instance.default {{name}}
```

» google__runtimeconfig__config

Manages a RuntimeConfig resource in Google Cloud. For more information, see the official documentation, or the JSON API.

» Example Usage

Example creating a RuntimeConfig resource.

```
resource "google_runtimeconfig_config" "my-runtime-config" {
  name = "my-service-runtime-config"
  description = "Runtime configuration values for my service"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the runtime config.

- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **description** - (Optional) The description to associate with the runtime config.

» **google_runtimeconfig_variable**

Manages a RuntimeConfig variable in Google Cloud. For more information, see the official documentation, or the JSON API.

» **Example Usage**

Example creating a RuntimeConfig variable.

```
resource "google_runtimeconfig_config" "my-runtime-config" {
  name = "my-service-runtime-config"
  description = "Runtime configuration values for my service"
}

resource "google_runtimeconfig_variable" "environment" {
  parent = "${google_runtimeconfig_config.my-runtime-config.name}"
  name = "prod-variables/hostname"
  text = "example.com"
}
```

You can also encode binary content using the **value** argument instead. The value must be base64 encoded.

Example of using the **value** argument.

```
resource "google_runtimeconfig_config" "my-runtime-config" {
  name = "my-service-runtime-config"
  description = "Runtime configuration values for my service"
}

resource "google_runtimeconfig_variable" "my-secret" {
  parent = "${google_runtimeconfig_config.my-runtime-config.name}"
  name = "secret"
  value = "${base64encode(file("my-encrypted-secret.dat"))}"
}
```

» **Argument Reference**

The following arguments are supported:

- **name** - (Required) The name of the variable to manage. Note that variable names can be hierarchical using slashes (e.g. "prod-variables/hostname").
 - **parent** - (Required) The name of the RuntimeConfig resource containing this variable.
 - **text** or **value** - (Required) The content to associate with the variable. Exactly one of **text** or **variable** must be specified. If **text** is specified, it must be a valid UTF-8 string and less than 4096 bytes in length. If **value** is specified, it must be base64 encoded and less than 4096 bytes in length.
-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **update_time** - (Computed) The timestamp in RFC3339 UTC "Zulu" format, accurate to nanoseconds, representing when the variable was last updated. Example: "2016-10-09T12:33:37.578138407Z".

» google_sourcerepo_repository

For more information, see the official documentation and API

» Example Usage

This example is the common case of creating a repository within Google Cloud Source Repositories:

```
resource "google_sourcerepo_repository" "frontend" {
  name = "frontend"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the repository that will be created.
-

- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

The following attributes are exported:

- **size** - The size of the repository.
- **url** - The url to clone the repository.

» google_spanner_instance

Creates a Google Spanner Database within a Spanner Instance. For more information, see the official documentation, or the JSON API.

» Example Usage

Example creating a Spanner database.

```
resource "google_spanner_instance" "main" {
  config      = "regional-europe-west1"
  display_name = "main-instance"
}

resource "google_spanner_database" "db" {
  instance = "${google_spanner_instance.main.name}"
  name     = "main-instance"
  ddl     = [
    "CREATE TABLE t1 (t1 INT64 NOT NULL,) PRIMARY KEY(t1)",
    "CREATE TABLE t2 (t2 INT64 NOT NULL,) PRIMARY KEY(t2)"
  ]
}
```

» Argument Reference

The following arguments are supported:

- **instance** - (Required) The name of the instance that will serve the new database.
- **name** - (Required) The name of the database.

- **project** - (Optional) The ID of the project in which to look for the **instance** specified. If it is not provided, the provider project is used.
- **ddl** - (Optional) An optional list of DDL statements to run inside the newly created database. Statements can create tables, indexes, etc. These statements execute atomically with the creation of the database: if there is an error in any statement, the database is not created.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **state** - The current state of the database.

» Import

Databases can be imported via their **instance** and **name** values, and optionally the **project** in which the instance is defined (Often used when the project is different to that defined in the provider). The format is thus either `{instanceName}/{dbName}` or `{projectId}/{instanceName}/{dbName}`. e.g.

```
$ terraform import google_spanner_database.db1 instance456/db789
```

```
$ terraform import google_spanner_database.db1 project123/instance456/db789
```

» IAM policy for Spanner databases

Three different resources help you manage your IAM policy for a Spanner database. Each of these resources serves a different use case:

- **google_spanner_database_iam_policy**: Authoritative. Sets the IAM policy for the database and replaces any existing policy already attached.

Warning: It's entirely possible to lock yourself out of your database using **google_spanner_database_iam_policy**. Any permissions granted by default will be removed unless you include them in your config.

- **google_spanner_database_iam_binding**: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the database are preserved.
- **google_spanner_database_iam_member**: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the database are preserved.

Note: `google_spanner_database_iam_policy` **cannot** be used in conjunction with `google_spanner_database_iam_binding` and `google_spanner_database_iam_member` or they will fight over what your policy should be.

Note: `google_spanner_database_iam_binding` resources **can be** used in conjunction with `google_spanner_database_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_spanner_database_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_spanner_database_iam_policy" "database" {
  instance      = "your-instance-name"
  database      = "your-database-name"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» `google_spanner_database_iam_binding`

```
resource "google_spanner_database_iam_binding" "database" {
  instance      = "your-instance-name"
  database      = "your-database-name"
  role          = "roles/compute.networkUser"

  members = [
    "user:jane@example.com",
  ]
}
```

» `google_spanner_database_iam_member`

```
resource "google_spanner_database_iam_member" "database" {
  instance      = "your-instance-name"
  database      = "your-database-name"
```

```

    role      = "roles/compute.networkUser"
    member    = "user:jane@example.com"
  }

```

» Argument Reference

The following arguments are supported:

- **database** - (Required) The name of the Spanner database.
- **instance** - (Required) The name of the Spanner instance the database belongs to.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_spanner_database_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_spanner_database_iam_policy`) The policy data generated by a `google_iam_policy` data source.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the database's IAM policy.

» Import

For all import syntaxes, the "resource in question" can take any of the following forms:

- `{{project}}/{{instance}}/{{database}}`
- `{{instance}}/{{database}}` (project is taken from provider project)

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account, e.g.

```
$ terraform import google_spanner_database_iam_member.database "project-name/instance-name/role-name/account-name"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role, e.g.

```
$ terraform import google_spanner_database_iam_binding.database "project-name/instance-name/role-name"
```

IAM policy imports use the identifier of the resource in question, e.g.

```
$ terraform import google_spanner_database_iam_policy.database project-name/instance-name/database-name
```

» IAM policy for Spanner databases

Three different resources help you manage your IAM policy for a Spanner database. Each of these resources serves a different use case:

- `google_spanner_database_iam_policy`: Authoritative. Sets the IAM policy for the database and replaces any existing policy already attached.

Warning: It's entirely possible to lock yourself out of your database using `google_spanner_database_iam_policy`. Any permissions granted by default will be removed unless you include them in your config.

- `google_spanner_database_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the database are preserved.
- `google_spanner_database_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the database are preserved.

Note: `google_spanner_database_iam_policy` **cannot** be used in conjunction with `google_spanner_database_iam_binding` and `google_spanner_database_iam_member` or they will fight over what your policy should be.

Note: `google_spanner_database_iam_binding` resources **can be** used in conjunction with `google_spanner_database_iam_member` resources **only if** they do not grant privilege to the same role.

» google_spanner_database_iam_policy

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_spanner_database_iam_policy" "database" {
  instance      = "your-instance-name"
  database      = "your-database-name"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» google_spanner_database_iam_binding

```
resource "google_spanner_database_iam_binding" "database" {
  instance      = "your-instance-name"
  database      = "your-database-name"
  role          = "roles/compute.networkUser"

  members = [
    "user:jane@example.com",
  ]
}
```

» google_spanner_database_iam_member

```
resource "google_spanner_database_iam_member" "database" {
  instance      = "your-instance-name"
  database      = "your-database-name"
  role          = "roles/compute.networkUser"
  member        = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **database** - (Required) The name of the Spanner database.
- **instance** - (Required) The name of the Spanner instance the database belongs to.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, alice@gmail.com or joe@example.com.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, my-other-app@appspot.gserviceaccount.com.
 - **group:{emailid}**: An email address that represents a Google group. For example, admins@example.com.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Only one `google_spanner_database_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_spanner_database_iam_policy`) The policy data generated by a `google_iam_policy` data source.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the database's IAM policy.

» Import

For all import syntaxes, the "resource in question" can take any of the following forms:

- `{{project}}/{{instance}}/{{database}}`
- `{{instance}}/{{database}}` (project is taken from provider project)

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account, e.g.

```
$ terraform import google_spanner_database_iam_member.database "project-name/instance-name/da
```

IAM binding imports use space-delimited identifiers; the resource in question and the role, e.g.

```
$ terraform import google_spanner_database_iam_binding.database "project-name/instance-name/da
```

IAM policy imports use the identifier of the resource in question, e.g.

```
$ terraform import google_spanner_database_iam_policy.database project-name/instance-name/da
```

» IAM policy for Spanner databases

Three different resources help you manage your IAM policy for a Spanner database. Each of these resources serves a different use case:

- `google_spanner_database_iam_policy`: Authoritative. Sets the IAM policy for the database and replaces any existing policy already attached.

Warning: It's entirely possible to lock yourself out of your database using `google_spanner_database_iam_policy`. Any permissions granted by default will be removed unless you include them in your config.

- `google_spanner_database_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the database are preserved.
- `google_spanner_database_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the database are preserved.

Note: `google_spanner_database_iam_policy` **cannot** be used in conjunction with `google_spanner_database_iam_binding` and `google_spanner_database_iam_member` or they will fight over what your policy should be.

Note: `google_spanner_database_iam_binding` resources **can be** used in conjunction with `google_spanner_database_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_spanner_database_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
```

```

        "user:jane@example.com",
    ]
}
}

resource "google_spanner_database_iam_policy" "database" {
  instance      = "your-instance-name"
  database      = "your-database-name"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}

```

» google_spanner_database_iam_binding

```

resource "google_spanner_database_iam_binding" "database" {
  instance      = "your-instance-name"
  database      = "your-database-name"
  role          = "roles/compute.networkUser"

  members = [
    "user:jane@example.com",
  ]
}

```

» google_spanner_database_iam_member

```

resource "google_spanner_database_iam_member" "database" {
  instance      = "your-instance-name"
  database      = "your-database-name"
  role          = "roles/compute.networkUser"
  member        = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **database** - (Required) The name of the Spanner database.
- **instance** - (Required) The name of the Spanner instance the database belongs to.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:

- **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, alice@gmail.com or joe@example.com.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, my-other-app@appspot.gserviceaccount.com.
 - **group:{emailid}**: An email address that represents a Google group. For example, admins@example.com.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Only one `google_spanner_database_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
 - **policy_data** - (Required only by `google_spanner_database_iam_policy`) The policy data generated by a `google_iam_policy` data source.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the database's IAM policy.

» Import

For all import syntaxes, the "resource in question" can take any of the following forms:

- `{{project}}/{{instance}}/{{database}}`
- `{{instance}}/{{database}}` (project is taken from provider project)

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account, e.g.

```
$ terraform import google_spanner_database_iam_member.database "project-name/instance-name/role-name/account-name"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role, e.g.

```
$ terraform import google_spanner_database_iam_binding.database "project-name/instance-name/da
```

IAM policy imports use the identifier of the resource in question, e.g.

```
$ terraform import google_spanner_database_iam_policy.database project-name/instance-name/da
```

» google_spanner_instance

Creates and manages a Google Spanner Instance. For more information, see the [official documentation](#), or the [JSON API](#).

» Example Usage

Example creating a Spanner instance.

```
resource "google_spanner_instance" "main" {
  config      = "regional-europe-west1"
  display_name = "main-instance"
  name        = "main-instance"
  num_nodes   = 1
}
```

» Argument Reference

The following arguments are supported:

- **config** - (Required) The name of the instance's configuration (similar but not quite the same as a region) which defines the geographic placement and replication of your databases in this instance. It determines where your data is stored. Values are typically of the form **regional-europe-west1** , **us-central** etc. In order to obtain a valid list please consult the Configuration section of the docs.
 - **display_name** - (Required) The descriptive name for this instance as it appears in UIs. Can be updated, however should be kept globally unique to avoid confusion.
-
- **name** - (Optional, Computed) The unique name (ID) of the instance. If the name is left blank, Terraform will randomly generate one when the instance is first created.
 - **num_nodes** - (Optional, Computed) The number of nodes allocated to this instance. Defaults to 1. This can be updated after creation.

- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **labels** - (Optional) A mapping (key/value pairs) of labels to assign to the instance.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **state** - The current state of the instance.

» Import

Instances can be imported using their **name** and optionally the **project** in which it is defined (Often used when the project is different to that defined in the provider), The format is thus either `{instanceId}` or `{projectId}/{instanceId}`. e.g.

```
$ terraform import google_spanner_instance.master instance123
```

```
$ terraform import google_spanner_instance.master project123/instance456
```

» IAM policy for Spanner Instances

Three different resources help you manage your IAM policy for a Spanner instance. Each of these resources serves a different use case:

- **google_spanner_instance_iam_policy**: Authoritative. Sets the IAM policy for the instance and replaces any existing policy already attached.

Warning: It's entirely possible to lock yourself out of your instance using **google_spanner_instance_iam_policy**. Any permissions granted by default will be removed unless you include them in your config.

- **google_spanner_instance_iam_binding**: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the instance are preserved.
- **google_spanner_instance_iam_member**: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the instance are preserved.

Note: **google_spanner_instance_iam_policy** **cannot** be used in conjunction with **google_spanner_instance_iam_binding** and **google_spanner_instance_iam_member** or they will fight over what your policy should be.

Note: `google_spanner_instance_iam_binding` resources **can be** used in conjunction with `google_spanner_instance_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_spanner_instance_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_spanner_instance_iam_policy" "instance" {
  instance      = "your-instance-name"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» `google_spanner_instance_iam_binding`

```
resource "google_spanner_instance_iam_binding" "instance" {
  instance = "your-instance-name"
  role     = "roles/compute.networkUser"

  members = [
    "user:jane@example.com",
  ]
}
```

» `google_spanner_instance_iam_member`

```
resource "google_spanner_instance_iam_member" "instance" {
  instance = "your-instance-name"
  role     = "roles/compute.networkUser"
  member   = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **instance** - (Required) The name of the instance.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_spanner_instance_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_spanner_instance_iam_policy`) The policy data generated by a `google_iam_policy` data source.
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the instance's IAM policy.

» Import

For all import syntaxes, the "resource in question" can take any of the following forms:

- `{{project}}/{{name}}`
- `{{name}}` (project is taken from provider project)

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account, e.g.

```
$ terraform import google_spanner_instance_iam_member.instance "project-name/instance-name r
```

IAM binding imports use space-delimited identifiers; the resource in question and the role, e.g.

```
$ terraform import google_spanner_instance_iam_binding.instance "project-name/instance-name
```

IAM policy imports use the identifier of the resource in question, e.g.

```
$ terraform import google_spanner_instance_iam_policy.instance project-name/instance-name
```

» IAM policy for Spanner Instances

Three different resources help you manage your IAM policy for a Spanner instance. Each of these resources serves a different use case:

- `google_spanner_instance_iam_policy`: Authoritative. Sets the IAM policy for the instance and replaces any existing policy already attached.

Warning: It's entirely possible to lock yourself out of your instance using `google_spanner_instance_iam_policy`. Any permissions granted by default will be removed unless you include them in your config.

- `google_spanner_instance_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the instance are preserved.
- `google_spanner_instance_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the instance are preserved.

Note: `google_spanner_instance_iam_policy` **cannot** be used in conjunction with `google_spanner_instance_iam_binding` and `google_spanner_instance_iam_member` or they will fight over what your policy should be.

Note: `google_spanner_instance_iam_binding` resources **can be** used in conjunction with `google_spanner_instance_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_spanner_instance_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
```

```

        "user:jane@example.com",
    ]
}
}

resource "google_spanner_instance_iam_policy" "instance" {
  instance      = "your-instance-name"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}

```

» google_spanner_instance_iam_binding

```

resource "google_spanner_instance_iam_binding" "instance" {
  instance = "your-instance-name"
  role     = "roles/compute.networkUser"

  members = [
    "user:jane@example.com",
  ]
}

```

» google_spanner_instance_iam_member

```

resource "google_spanner_instance_iam_member" "instance" {
  instance = "your-instance-name"
  role     = "roles/compute.networkUser"
  member   = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **instance** - (Required) The name of the instance.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.

- **serviceAccount:{emailid}**: An email address that represents a service account. For example, my-other-app@appspot.gserviceaccount.com.
 - **group:{emailid}**: An email address that represents a Google group. For example, admins@example.com.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Only one `google_spanner_instance_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
 - **policy_data** - (Required only by `google_spanner_instance_iam_policy`) The policy data generated by a `google_iam_policy` data source.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the instance's IAM policy.

» Import

For all import syntaxes, the "resource in question" can take any of the following forms:

- `{{project}}/{{name}}`
- `{{name}}` (project is taken from provider project)

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account, e.g.

```
$ terraform import google_spanner_instance_iam_member.instance "project-name/instance-name role account"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role, e.g.

```
$ terraform import google_spanner_instance_iam_binding.instance "project-name/instance-name role"
```

IAM policy imports use the identifier of the resource in question, e.g.

```
$ terraform import google_spanner_instance_iam_policy.instance project-name/instance-name
```

» IAM policy for Spanner Instances

Three different resources help you manage your IAM policy for a Spanner instance. Each of these resources serves a different use case:

- `google_spanner_instance_iam_policy`: Authoritative. Sets the IAM policy for the instance and replaces any existing policy already attached.

Warning: It's entirely possible to lock yourself out of your instance using `google_spanner_instance_iam_policy`. Any permissions granted by default will be removed unless you include them in your config.

- `google_spanner_instance_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the instance are preserved.
- `google_spanner_instance_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the instance are preserved.

Note: `google_spanner_instance_iam_policy` **cannot** be used in conjunction with `google_spanner_instance_iam_binding` and `google_spanner_instance_iam_member` or they will fight over what your policy should be.

Note: `google_spanner_instance_iam_binding` resources **can be** used in conjunction with `google_spanner_instance_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_spanner_instance_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_spanner_instance_iam_policy" "instance" {
  instance      = "your-instance-name"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» google_spanner_instance_iam_binding

```
resource "google_spanner_instance_iam_binding" "instance" {
  instance = "your-instance-name"
  role     = "roles/compute.networkUser"

  members = [
    "user:jane@example.com",
  ]
}
```

» google_spanner_instance_iam_member

```
resource "google_spanner_instance_iam_member" "instance" {
  instance = "your-instance-name"
  role     = "roles/compute.networkUser"
  member   = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **instance** - (Required) The name of the instance.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_spanner_instance_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.

- **policy_data** - (Required only by `google_spanner_instance_iam_policy`)
The policy data generated by a `google_iam_policy` data source.
- **project** - (Optional) The ID of the project in which the resource belongs.
If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the instance's IAM policy.

» Import

For all import syntaxes, the "resource in question" can take any of the following forms:

- `{{project}}/{{name}}`
- `{{name}}` (project is taken from provider project)

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account, e.g.

```
$ terraform import google_spanner_instance_iam_member.instance "project-name/instance-name role account"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role, e.g.

```
$ terraform import google_spanner_instance_iam_binding.instance "project-name/instance-name role"
```

IAM policy imports use the identifier of the resource in question, e.g.

```
$ terraform import google_spanner_instance_iam_policy.instance project-name/instance-name
```

» google__sql__database

Creates a new Google SQL Database on a Google SQL Database Instance. For more information, see the official documentation, or the JSON API.

» Example Usage

Example creating a SQL Database.


```

resource "google_sql_database_instance" "master" {
  name = "master-instance"

  settings {
    tier = "D0"
  }
}

resource "google_sql_database" "users" {
  name      = "users-db"
  instance  = "${google_sql_database_instance.master.name}"
  charset   = "latin1"
  collation = "latin1_swedish_ci"
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the database.
 - **instance** - (Required) The name of containing instance.
-
- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
 - **charset** - (Optional) The charset value. See MySQL's Supported Character Sets and Collations and Postgres' Character Set Support for more details and supported values. Postgres databases are in Beta, and have limited **charset** support; they only support a value of **UTF8** at creation time.
 - **collation** - (Optional) The collation value. See MySQL's Supported Character Sets and Collations and Postgres' Collation Support for more details and supported values. Postgres databases are in Beta, and have limited **collation** support; they only support a value of **en_US.UTF8** at creation time.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.

» Import

SQL databases can be imported using the `instance` and `name`, e.g.

```
$ terraform import google_sql_database.database master-instance:users-db
```

» google_sql_database_instance

Creates a new Google SQL Database Instance. For more information, see the [official documentation](#), or the [JSON API](#).

NOTE on google_sql_database_instance: - Second-generation instances include a default 'root'@'%' user with no password. This user will be deleted by Terraform on instance creation. You should use `google_sql_user` to define a custom user with a restricted host and strong password.

» Example Usage

» SQL First Generation

```
resource "google_sql_database_instance" "master" {
  name = "master-instance"
  database_version = "MYSQL_5_6"
  # First-generation instance regions are not the conventional
  # Google Compute Engine regions. See argument reference below.
  region = "us-central"

  settings {
    tier = "D0"
  }
}
```

» SQL Second generation

```
resource "google_sql_database_instance" "master" {
  name = "master-instance"
  database_version = "POSTGRES_9_6"
  region = "us-central1"

  settings {
    # Second-generation instance tiers are based on the machine
    # type. See argument reference below.
    tier = "db-f1-micro"
  }
}
```

```

    }
}

```

» Granular restriction of network access

```

resource "google_compute_instance" "apps" {
  count          = 8
  name           = "apps-${count.index + 1}"
  machine_type   = "f1-micro"

  boot_disk {
    initialize_params {
      image = "ubuntu-os-cloud/ubuntu-1804-lts"
    }
  }
}

network_interface {
  network = "default"

  access_config {
    // Ephemeral IP
  }
}

data "null_data_source" "auth_netw_postgres_allowed_1" {
  count = "${length(google_compute_instance.apps).*self_link}"

  inputs = {
    name  = "apps-${count.index + 1}"
    value = "${element(google_compute_instance.apps.*.network_interface.0.access_config.0.as
  }
}

data "null_data_source" "auth_netw_postgres_allowed_2" {
  count = 2

  inputs = {
    name  = "onprem-${count.index + 1}"
    value = "${element(list("192.168.1.2", "192.168.2.3"), count.index)}"
  }
}

resource "google_sql_database_instance" "postgres" {
  name = "postgres-instance"

```

```

database_version = "POSTGRES_9_6"

settings {
  tier = "db-f1-micro"

  ip_configuration {
    authorized_networks = [
      "${data.null_data_source.auth_netw_postgres_allowed_1.*.outputs}",
      "${data.null_data_source.auth_netw_postgres_allowed_2.*.outputs}",
    ]
  }
}
}

```

» Argument Reference

The following arguments are supported:

- **region** - (Required) The region the instance will sit in. Note, first-generation Cloud SQL instance regions do not line up with the Google Compute Engine (GCE) regions, and Cloud SQL is not available in all regions - choose from one of the options listed here. A valid region must be provided to use this resource. If a region is not provided in the resource definition, the provider region will be used instead, but this will be an apply-time error for all first-generation instances *and* for second-generation instances if the provider region is not supported with Cloud SQL. If you choose not to provide the **region** argument for this resource, make sure you understand this.
 - **settings** - (Required) The settings to use for the database. The configuration is detailed below.
-
- **database_version** - (Optional, Default: `MYSQL_5_6`) The MySQL version to use. Can be `MYSQL_5_6`, `MYSQL_5_7` or `POSTGRES_9_6` for second-generation instances, or `MYSQL_5_5` or `MYSQL_5_6` for first-generation instances. See [Second Generation Capabilities](#) for more information. `POSTGRES_9_6` support is in Beta.
 - **name** - (Optional, Computed) The name of the instance. If the name is left blank, Terraform will randomly generate one when the instance is first created. This is done because after a name is used, it cannot be reused for up to one week.
 - **master_instance_name** - (Optional) The name of the instance that will act as the master in the replication setup. Note, this requires the master to have `binary_log_enabled` set, as well as existing backups.

- **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
- **replica_configuration** - (Optional) The configuration for replication. The configuration is detailed below.

The required **settings** block supports:

- **tier** - (Required) The machine tier (First Generation) or type (Second Generation) to use. See tiers for more details and supported versions. Postgres supports only shared-core machine types such as **db-f1-micro**, and custom machine types such as **db-custom-2-13312**. See the Custom Machine Type Documentation to learn about specifying custom machine types.
- **activation_policy** - (Optional) This specifies when the instance should be active. Can be either **ALWAYS**, **NEVER** or **ON_DEMAND**.
- **authorized_gae_applications** - (Optional) A list of Google App Engine (GAE) project names that are allowed to access this instance.
- **availability_type** - (Optional) This specifies whether a PostgreSQL instance should be set up for high availability (**REGIONAL**) or single zone (**ZONAL**).
- **crash_safe_replication** - (Optional) Specific to read instances, indicates when crash-safe replication flags are enabled.
- **disk_autoresize** - (Optional, Second Generation, Default: **true**) Configuration to increase storage size automatically.
- **disk_size** - (Optional, Second Generation, Default: 10) The size of data disk, in GB. Size of a running instance cannot be reduced but can be increased.
- **disk_type** - (Optional, Second Generation, Default: **PD_SSD**) The type of data disk: **PD_SSD** or **PD_HDD**.
- **pricing_plan** - (Optional, First Generation) Pricing plan for this instance, can be one of **PER_USE** or **PACKAGE**.
- **replication_type** - (Optional) Replication type for this instance, can be one of **ASYNCHRONOUS** or **SYNCHRONOUS**.
- **user_labels** - (Optional) A set of key/value user label pairs to assign to the instance.

The optional **settings.database_flags** sublist supports:

- **name** - (Optional) Name of the flag.
- **value** - (Optional) Value of the flag.

The optional **settings.backup_configuration** subblock supports:

- **binary_log_enabled** - (Optional) True if binary logging is enabled. If **logging** is false, this must be as well.
- **enabled** - (Optional) True if backup configuration is enabled.
- **start_time** - (Optional) HH:MM format time indicating when backup configuration starts.

The optional **settings.ip_configuration** subblock supports:

- **ipv4_enabled** - (Optional) True if the instance should be assigned an IP address. The IPv4 address cannot be disabled for Second Generation instances.
- **require_ssl** - (Optional) True if mysqld should default to **REQUIRE X509** for users connecting over IP.

The optional **settings.ip_configuration.authorized_networks[]** sublist supports:

- **expiration_time** - (Optional) The RFC 3339 formatted date time string indicating when this whitelist expires.
- **name** - (Optional) A name for this whitelist entry.
- **value** - (Optional) A CIDR notation IPv4 or IPv6 address that is allowed to access this instance. Must be set even if other two attributes are not for the whitelist to become active.

The optional **settings.location_preference** subblock supports:

- **follow_gae_application** - (Optional) A GAE application whose zone to remain in. Must be in the same region as this instance.
- **zone** - (Optional) The preferred compute engine zone.

The optional **settings.maintenance_window** subblock for Second Generation instances declares a one-hour maintenance window when an Instance can automatically restart to apply updates. The maintenance window is specified in UTC time. It supports:

- **day** - (Optional) Day of week (1-7), starting on Monday
- **hour** - (Optional) Hour of day (0-23), ignored if **day** not set
- **update_track** - (Optional) Receive updates earlier (**canary**) or later (**stable**)

The optional **replica_configuration** block must have **master_instance_name** set to work, cannot be updated, and supports:

- **ca_certificate** - (Optional) PEM representation of the trusted CA's x509 certificate.

- **client_certificate** - (Optional) PEM representation of the slave's x509 certificate.
- **client_key** - (Optional) PEM representation of the slave's private key. The corresponding public key is encoded in the **client_certificate**.
- **connect_retry_interval** - (Optional, Default: 60) The number of seconds between connect retries.
- **dump_file_path** - (Optional) Path to a SQL file in GCS from which slave instances are created. Format is **gs://bucket/filename**.
- **failover_target** - (Optional) Specifies if the replica is the failover target. If the field is set to true the replica will be designated as a failover replica. If the master instance fails, the replica instance will be promoted as the new master instance.
- **master_heartbeat_period** - (Optional) Time in ms between replication heartbeats.
- **password** - (Optional) Password for the replication connection.
- **sslCipher** - (Optional) Permissible ciphers for use in SSL encryption.
- **username** - (Optional) Username for replication connection.
- **verify_server_certificate** - (Optional) True if the master's common name value is checked during the SSL handshake.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **first_ip_address** - The first IPv4 address of the addresses assigned. This is to support accessing the first address in the list in a terraform output when the resource is configured with a **count**.
- **connection_name** - The connection name of the instance to be used in connection strings.
- **ip_address.0.ip_address** - The IPv4 address assigned.
- **ip_address.0.time_to_retire** - The time this IP address will be retired, in RFC 3339 format.
- **self_link** - The URI of the created resource.
- **settings.version** - Used to make sure changes to the **settings** block are atomic.
- **server_ca_cert.0.cert** - The CA Certificate used to connect to the SQL Instance via SSL.

- `server_ca_cert.0.common_name` - The CN valid for the CA Cert.
- `server_ca_cert.0.create_time` - Creation time of the CA Cert.
- `server_ca_cert.0.expiration_time` - Expiration time of the CA Cert.
- `server_ca_cert.0.sha1_fingerprint` - SHA Fingerprint of the CA Cert.

» Timeouts

`google_sql_database_instance` provides the following Timeouts configuration options:

- `create` - Default is 10 minutes.
- `update` - Default is 10 minutes.
- `delete` - Default is 10 minutes.

» Import

Database instances can be imported using the `name`, e.g.

```
$ terraform import google_sql_database_instance.master master-instance
```

» google__sql__user

Creates a new Google SQL User on a Google SQL User Instance. For more information, see the official documentation, or the JSON API.

Note: All arguments including the username and password will be stored in the raw state as plain-text. Read more about sensitive data in state. Passwords will not be retrieved when running "terraform import".

» Example Usage

Example creating a SQL User.

```
resource "google_sql_database_instance" "master" {
  name = "master-instance"

  settings {
    tier = "D0"
  }
}
```



```
resource "google_sql_user" "users" {
  name      = "me"
  instance = "${google_sql_database_instance.master.name}"
  host      = "me.com"
  password  = "changeme"
}
```

» Argument Reference

The following arguments are supported:

- **instance** - (Required) The name of the Cloud SQL instance. Changing this forces a new resource to be created.
 - **name** - (Required) The name of the user. Changing this forces a new resource to be created.
 - **password** - (Optional) The password for the user. Can be updated.
-
- **host** - (Optional) The host the user can connect from. This is only supported for MySQL instances. Don't set this field for PostgreSQL instances. Can be an IP address. Changing this forces a new resource to be created.
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» Import

SQL users for MySQL databases can be imported using the **instance**, **host** and **name**, e.g.

```
$ terraform import google_sql_user.users master-instance/my-domain.com/me
```

SQL users for PostgreSQL databases can be imported using the **instance** and **name**, e.g.

```
$ terraform import google_sql_user.users master-instance/me
```

» `google_logging_billing_account_exclusion`

Manages a billing account logging exclusion. For more information see the official documentation and Excluding Logs.

Note that you must have the "Logs Configuration Writer" IAM role (`roles/logging.configWriter`) granted to the credentials used with Terraform.

» Example Usage

```
resource "google_logging_billing_account_exclusion" "my-exclusion" {
  name          = "my-instance-debug-exclusion"
  billing_account = "ABCDEF-012345-GHIJKL"

  description = "Exclude GCE instance debug logs"

  # Exclude all DEBUG or lower severity messages relating to instances
  filter = "resource.type = gce_instance AND severity <= DEBUG"
}
```

» Argument Reference

The following arguments are supported:

- `billing_account` - (Required) The billing account to create the exclusion for.
- `name` - (Required) The name of the logging exclusion.
- `description` - (Optional) A human-readable description.
- `disabled` - (Optional) Whether this exclusion rule should be disabled or not. This defaults to false.
- `filter` - (Required) The filter to apply when excluding logs. Only log entries that match the filter are excluded. See Advanced Log Filters for information on how to write a filter.

» Import

Billing account logging exclusions can be imported using their URI, e.g.

```
$ terraform import google_logging_billing_account_exclusion.my_exclusion billingAccounts/my-
```

» google__logging__billing__account__sink

Manages a billing account logging sink. For more information see the official documentation and Exporting Logs in the API.

Note that you must have the "Logs Configuration Writer" IAM role (roles/logging.configWriter) granted to the credentials used with terraform.

» Example Usage

```
resource "google_logging_billing_account_sink" "my-sink" {
  name = "my-sink"
  billing_account = "ABCDEF-012345-GHIJKL"

  # Can export to pubsub, cloud storage, or bigtable
  destination = "storage.googleapis.com/${google_storage_bucket.log-bucket.name}"
}

resource "google_storage_bucket" "log-bucket" {
  name = "billing-logging-bucket"
}

resource "google_project_iam_binding" "log-writer" {
  role = "roles/storage.objectCreator"

  members = [
    "${google_logging_billing_account_sink.my-sink.writer_identity}",
  ]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the logging sink.
- **billing_account** - (Required) The billing account exported to the sink.
- **destination** - (Required) The destination of the sink (or, in other words, where logs are written to). Can be a Cloud Storage bucket, a PubSub topic, or a BigQuery dataset. Examples:
"storage.googleapis.com/[GCS_BUCKET]" "bigquery.googleapis.com/projects/[PROJECT_ID]/datasets/[DATASET_ID]"
"pubsub.googleapis.com/projects/[PROJECT_ID]/topics/[TOPIC_ID]"
The writer associated with the sink must have access to write to the above resource.

- **filter** - (Optional) The filter to apply when exporting logs. Only log entries that match the filter are exported. See Advanced Log Filters for information on how to write a filter.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **writer_identity** - The identity associated with this sink. This identity must be granted write access to the configured **destination**.

» google_logging_folder_exclusion

Manages a folder-level logging exclusion. For more information see the official documentation and Excluding Logs.

Note that you must have the "Logs Configuration Writer" IAM role (`roles/logging.configWriter`) granted to the credentials used with Terraform.

» Example Usage

```
resource "google_logging_folder_exclusion" "my-exclusion" {
  name      = "my-instance-debug-exclusion"
  folder    = "${google_folder.my-folder.name}"

  description = "Exclude GCE instance debug logs"

  # Exclude all DEBUG or lower severity messages relating to instances
  filter      = "resource.type = gce_instance AND severity <= DEBUG"
}

resource "google_folder" "my-folder" {
  display_name = "My folder"
  parent      = "organizations/123456"
}
```

» Argument Reference

The following arguments are supported:

- **folder** - (Required) The folder to be exported to the sink. Note that either [FOLDER_ID] or "folders/[FOLDER_ID]" is accepted.
- **name** - (Required) The name of the logging exclusion.
- **description** - (Optional) A human-readable description.
- **disabled** - (Optional) Whether this exclusion rule should be disabled or not. This defaults to false.
- **filter** - (Required) The filter to apply when excluding logs. Only log entries that match the filter are excluded. See Advanced Log Filters for information on how to write a filter.

» Import

Folder-level logging exclusions can be imported using their URI, e.g.

```
$ terraform import google_logging_folder_exclusion.my_exclusion folders/my-folder/exclusions
```

» google_logging_folder_sink

Manages a folder-level logging sink. For more information see the official documentation and Exporting Logs in the API.

Note that you must have the "Logs Configuration Writer" IAM role (roles/logging.configWriter) granted to the credentials used with terraform.

» Example Usage

```
resource "google_logging_folder_sink" "my-sink" {
  name      = "my-sink"
  folder    = "${google_folder.my-folder.name}"

  # Can export to pubsub, cloud storage, or bigtable
  destination = "storage.googleapis.com/${google_storage_bucket.log-bucket.name}"

  # Log all WARN or higher severity messages relating to instances
  filter      = "resource.type = gce_instance AND severity >= WARN"
}

resource "google_storage_bucket" "log-bucket" {
  name = "folder-logging-bucket"
}
```

```

resource "google_project_iam_binding" "log-writer" {
  role      = "roles/storage.objectCreator"

  members = [
    "${google_logging_folder_sink.my-sink.writer_identity}",
  ]
}

resource "google_folder" "my-folder" {
  display_name = "My folder"
  parent       = "organizations/123456"
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the logging sink.
- **folder** - (Required) The folder to be exported to the sink. Note that either `[FOLDER_ID]` or `"folders/[FOLDER_ID]"` is accepted.
- **destination** - (Required) The destination of the sink (or, in other words, where logs are written to). Can be a Cloud Storage bucket, a PubSub topic, or a BigQuery dataset. Examples: `"storage.googleapis.com/[GCS_BUCKET]"` `"bigquery.googleapis.com/projects/[PROJECT_ID]/datasets/[DATASET]"` `"pubsub.googleapis.com/projects/[PROJECT_ID]/topics/[TOPIC_ID]"` The writer associated with the sink must have access to write to the above resource.
- **filter** - (Optional) The filter to apply when exporting logs. Only log entries that match the filter are exported. See Advanced Log Filters for information on how to write a filter.
- **include_children** - (Optional) Whether or not to include children folders in the sink export. If true, logs associated with child projects are also exported; otherwise only logs relating to the provided folder are included.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **writer_identity** - The identity associated with this sink. This identity must be granted write access to the configured **destination**.

» google_logging_organization_exclusion

Manages an organization-level logging exclusion. For more information see the official documentation and Excluding Logs.

Note that you must have the "Logs Configuration Writer" IAM role (roles/logging.configWriter) granted to the credentials used with Terraform.

» Example Usage

```
resource "google_logging_organization_exclusion" "my-exclusion" {
  name      = "my-instance-debug-exclusion"
  org_id    = "123456789"

  description = "Exclude GCE instance debug logs"

  # Exclude all DEBUG or lower severity messages relating to instances
  filter      = "resource.type = gce_instance AND severity <= DEBUG"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the logging exclusion.
- **org_id** - (Required) The organization to create the exclusion in.
- **description** - (Optional) A human-readable description.
- **disabled** - (Optional) Whether this exclusion rule should be disabled or not. This defaults to false.
- **filter** - (Required) The filter to apply when excluding logs. Only log entries that match the filter are excluded. See Advanced Log Filters for information on how to write a filter.

» Import

Organization-level logging exclusions can be imported using their URI, e.g.

```
$ terraform import google_logging_organization_exclusion.my_exclusion organizations/my-organ
```

» google_logging_organization_sink

Manages a organization-level logging sink. For more information see the official documentation and Exporting Logs in the API.

Note that you must have the "Logs Configuration Writer" IAM role (roles/logging.configWriter) granted to the credentials used with terraform.

» Example Usage

```
resource "google_logging_organization_sink" "my-sink" {
  name      = "my-sink"
  org_id    = "123456789"

  # Can export to pubsub, cloud storage, or bigtable
  destination = "storage.googleapis.com/${google_storage_bucket.log-bucket.name}"

  # Log all WARN or higher severity messages relating to instances
  filter      = "resource.type = gce_instance AND severity >= WARN"
}

resource "google_storage_bucket" "log-bucket" {
  name = "organization-logging-bucket"
}

resource "google_project_iam_binding" "log-writer" {
  role    = "roles/storage.objectCreator"

  members = [
    "${google_logging_organization_sink.my-sink.writer_identity}",
  ]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the logging sink.
- **org_id** - (Required) The numeric ID of the organization to be exported to the sink.
- **destination** - (Required) The destination of the sink (or, in other words, where logs are written to). Can be a Cloud Storage bucket, a PubSub topic, or a BigQuery dataset. Examples:


```
"storage.googleapis.com/[GCS_BUCKET]" "bigquery.googleapis.com/projects/[PROJECT_ID]/datasets/[PROJECT_ID].table/[TOPIC_ID]"
"pubsub.googleapis.com/projects/[PROJECT_ID]/topics/[TOPIC_ID]"
```

The writer associated with the sink must have access to write to the above resource.

- **filter** - (Optional) The filter to apply when exporting logs. Only log entries that match the filter are exported. See Advanced Log Filters for information on how to write a filter.
- **include_children** - (Optional) Whether or not to include children organizations in the sink export. If true, logs associated with child projects are also exported; otherwise only logs relating to the provided organization are included.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **writer_identity** - The identity associated with this sink. This identity must be granted write access to the configured **destination**.

» google_logging_project_exclusion

Manages a project-level logging exclusion. For more information see the official documentation and Excluding Logs.

Note that you must have the "Logs Configuration Writer" IAM role (`roles/logging.configWriter`) granted to the credentials used with Terraform.

» Example Usage

```
resource "google_logging_project_exclusion" "my-exclusion" {
  name = "my-instance-debug-exclusion"

  description = "Exclude GCE instance debug logs"

  # Exclude all DEBUG or lower severity messages relating to instances
  filter = "resource.type = gce_instance AND severity <= DEBUG"
}
```

» Argument Reference

The following arguments are supported:

- **filter** - (Required) The filter to apply when excluding logs. Only log entries that match the filter are excluded. See Advanced Log Filters for information on how to write a filter.
- **name** - (Required) The name of the logging exclusion.
- **description** - (Optional) A human-readable description.
- **disabled** - (Optional) Whether this exclusion rule should be disabled or not. This defaults to false.
- **project** - (Optional) The project to create the exclusion in. If omitted, the project associated with the provider is used.

» Import

Project-level logging exclusions can be imported using their URI, e.g.

```
$ terraform import google_logging_project_exclusion.my_exclusion projects/my-project/exclusion/
```

» google_logging_project_sink

Manages a project-level logging sink. For more information see the official documentation, Exporting Logs in the API and API.

Note that you must have the "Logs Configuration Writer" IAM role (`roles/logging.configWriter`) granted to the credentials used with terraform.

» Example Usage

```
resource "google_logging_project_sink" "my-sink" {
  name = "my-pubsub-instance-sink"

  # Can export to pubsub, cloud storage, or bigtable
  destination = "pubsub.googleapis.com/projects/my-project/topics/instance-activity"

  # Log all WARN or higher severity messages relating to instances
  filter = "resource.type = gce_instance AND severity >= WARN"

  # Use a unique writer (creates a unique service account used for writing)
  unique_writer_identity = true
}
```

```
}
```

A more complete example follows: this creates a compute instance, as well as a log sink that logs all activity to a cloud storage bucket. Because we are using `unique_writer_identity`, we must grant it access to the bucket. Note that this grant requires the "Project IAM Admin" IAM role (`roles/resourcemanager.projectIamAdmin`) granted to the credentials used with terraform.

```
# Our logged compute instance
resource "google_compute_instance" "my-logged-instance" {
  name          = "my-instance"
  machine_type  = "n1-standard-1"
  zone          = "us-central1-a"

  boot_disk {
    initialize_params {
      image = "debian-cloud/debian-8"
    }
  }

  network_interface {
    network = "default"

    access_config {}
  }
}

# A bucket to store logs in
resource "google_storage_bucket" "log-bucket" {
  name = "my-unique-logging-bucket"
}

# Our sink; this logs all activity related to our "my-logged-instance" instance
resource "google_logging_project_sink" "instance-sink" {
  name = "my-instance-sink"
  destination = "storage.googleapis.com/${google_storage_bucket.log-bucket.name}"
  filter = "resource.type = gce_instance AND resource.labels.instance_id = \"${google_compute_instance.name}\""

  unique_writer_identity = true
}

# Because our sink uses a unique_writer, we must grant that writer access to the bucket.
resource "google_project_iam_binding" "log-writer" {
  role = "roles/storage.objectCreator"

  members = [
```

```

    "${google_logging_project_sink.instance-sink.writer_identity}",
  ]
}

```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the logging sink.
- **destination** - (Required) The destination of the sink (or, in other words, where logs are written to). Can be a Cloud Storage bucket, a PubSub topic, or a BigQuery dataset. Examples:
`"storage.googleapis.com/[GCS_BUCKET]"` `"bigquery.googleapis.com/projects/[PROJECT_ID]/datasets/[DATASET_ID]"`
`"pubsub.googleapis.com/projects/[PROJECT_ID]/topics/[TOPIC_ID]"`
 The writer associated with the sink must have access to write to the above resource.
- **filter** - (Optional) The filter to apply when exporting logs. Only log entries that match the filter are exported. See Advanced Log Filters for information on how to write a filter.
- **project** - (Optional) The ID of the project to create the sink in. If omitted, the project associated with the provider is used.
- **unique_writer_identity** - (Optional) Whether or not to create a unique identity associated with this sink. If **false** (the default), then the **writer_identity** used is `serviceAccount:cloud-logs@system.gserviceaccount.com`. If **true**, then a unique service account is created and used for this sink. If you wish to publish logs across projects, you must set **unique_writer_identity** to **true**.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **writer_identity** - The identity associated with this sink. This identity must be granted write access to the configured **destination**.

» Import

Project-level logging sinks can be imported using their URI, e.g.

```
$ terraform import google_logging_project_sink.my_sink projects/my-project/sinks/my-sink
```

» google__storage__bucket

Creates a new bucket in Google cloud storage service (GCS). Once a bucket has been created, its location can't be changed. ACLs can be applied using the `google_storage_bucket_acl` resource. For more information see the official documentation and API.

» Example Usage

Example creating a private bucket in standard storage, in the EU region.

```
resource "google_storage_bucket" "image-store" {
  name      = "image-store-bucket"
  location  = "EU"

  website {
    main_page_suffix = "index.html"
    not_found_page    = "404.html"
  }
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The name of the bucket.
-
- **force_destroy** - (Optional, Default: false) When deleting a bucket, this boolean option will delete all contained objects. If you try to delete a bucket that contains objects, Terraform will fail that run.
 - **location** - (Optional, Default: 'US') The GCS location
 - **project** - (Optional) The ID of the project in which the resource belongs. If it is not provided, the provider project is used.
 - **storage_class** - (Optional) The Storage Class of the new bucket. Supported values include: `MULTI_REGIONAL`, `REGIONAL`, `NEARLINE`, `COLDLINE`.
 - **lifecycle_rule** - (Optional) The bucket's Lifecycle Rules configuration. Multiple blocks of this type are permitted. Structure is documented below.
 - **versioning** - (Optional) The bucket's Versioning configuration.
 - **website** - (Optional) Configuration if the bucket acts as a website. Structure is documented below.

- **cors** - (Optional) The bucket's Cross-Origin Resource Sharing (CORS) configuration. Multiple blocks of this type are permitted. Structure is documented below.
- **labels** - (Optional) A set of key/value label pairs to assign to the bucket.
- **logging** - (Optional) The bucket's Access & Storage Logs configuration.
- **encryption** - (Optional) The bucket's encryption configuration.

The **lifecycle_rule** block supports:

- **action** - (Required) The Lifecycle Rule's action configuration. A single block of this type is supported. Structure is documented below.
- **condition** - (Required) The Lifecycle Rule's condition configuration. A single block of this type is supported. Structure is documented below.

The **action** block supports:

- **type** - The type of the action of this Lifecycle Rule. Supported values include: **Delete** and **SetStorageClass**.
- **storage_class** - (Required if action type is **SetStorageClass**) The target Storage Class of objects affected by this Lifecycle Rule. Supported values include: **MULTI_REGIONAL**, **REGIONAL**, **NEARLINE**, **COLDLINE**.

The **condition** block supports the following elements, and requires at least one to be defined:

- **age** - (Optional) Minimum age of an object in days to satisfy this condition.
- **created_before** - (Optional) Creation date of an object in RFC 3339 (e.g. 2017-06-13) to satisfy this condition.
- **is_live** - (Optional) Defaults to **false** to match archived objects. If **true**, this condition matches live objects. Unversioned buckets have only live objects.
- **matches_storage_class** - (Optional) Storage Class of objects to satisfy this condition. Supported values include: **MULTI_REGIONAL**, **REGIONAL**, **NEARLINE**, **COLDLINE**, **STANDARD**, **DURABLE_REDUCED_AVAILABILITY**.
- **num_newer_versions** - (Optional) Relevant only for versioned objects. The number of newer versions of an object to satisfy this condition.

The **versioning** block supports:

- **enabled** - (Optional) While set to **true**, versioning is fully enabled for this bucket.

The **website** block supports:

- **main_page_suffix** - (Optional) Behaves as the bucket's directory index where missing objects are treated as potential directories.
- **not_found_page** - (Optional) The custom object to return when a requested resource is not found.

The **cors** block supports:

- **origin** - (Optional) The list of Origins eligible to receive CORS response headers. Note: "*" is permitted in the list of origins, and means "any Origin".
- **method** - (Optional) The list of HTTP methods on which to include CORS response headers, (GET, OPTIONS, POST, etc) Note: "*" is permitted in the list of methods, and means "any method".
- **response_header** - (Optional) The list of HTTP headers other than the simple response headers to give permission for the user-agent to share across domains.
- **max_age_seconds** - (Optional) The value, in seconds, to return in the Access-Control-Max-Age header used in preflight responses.

The **logging** block supports:

- **log_bucket** - (Required) The bucket that will receive log objects.
- **log_object_prefix** - (Optional, Computed) The object prefix for log objects. If it's not provided, by default GCS sets this to this bucket's name.

The **encryption** block supports:

- **default_kms_key_name**: A Cloud KMS key that will be used to encrypt objects inserted into this bucket, if no encryption method is specified. You must pay attention to whether the crypto key is available in the location that this bucket is created in. See the docs for more details.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.
- **url** - The base URL of the bucket, in the format `gs://<bucket-name>`.

» Import

Storage buckets can be imported using the **name**, e.g.

```
$ terraform import google_storage_bucket.image-store image-store-bucket
```

Note that when importing a bucket (and only when importing), the Compute API needs to be enabled - you'll see an error with a link to the enablement page if it is not.

» google_storage_bucket_acl

Creates a new bucket ACL in Google cloud storage service (GCS). For more information see the official documentation and API.

» Example Usage

Example creating an ACL on a bucket with one owner, and one reader.

```
resource "google_storage_bucket" "image-store" {
  name      = "image-store-bucket"
  location = "EU"
}

resource "google_storage_bucket_acl" "image-store-acl" {
  bucket = "${google_storage_bucket.image-store.name}"

  role_entity = [
    "OWNER:user-my.email@gmail.com",
    "READER:group-mygroup",
  ]
}
```

» Argument Reference

- `bucket` - (Required) The name of the bucket it applies to.
-
- `predefined_acl` - (Optional) The canned GCS ACL to apply. Must be set if `role_entity` is not.
 - `role_entity` - (Optional) List of role/entity pairs in the form `ROLE:entity`. See GCS Bucket ACL documentation for more details. Must be set if `predefined_acl` is not.
 - `default_acl` - (Optional) Configure this ACL to be the default ACL.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» IAM policy for Google storage bucket

Three different resources help you manage your IAM policy for storage bucket. Each of these resources serves a different use case:

- `google_storage_bucket_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the storage bucket are preserved.
- `google_storage_bucket_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the storage bucket are preserved.
- `google_storage_bucket_iam_policy`: Setting a policy removes all other permissions on the bucket, and if done incorrectly, there's a real chance you will lock yourself out of the bucket. If possible for your use case, using multiple `google_storage_bucket_iam_binding` resources will be much safer. See the usage example on how to work with policy correctly.

Note: `google_storage_bucket_iam_binding` resources **can be** used in conjunction with `google_storage_bucket_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_storage_bucket_iam_binding`

```
resource "google_storage_bucket_iam_binding" "binding" {
  bucket = "your-bucket-name"
  role   = "roles/storage.objectViewer"

  members = [
    "user:jane@example.com",
  ]
}
```

» `google_storage_bucket_iam_member`

```
resource "google_storage_bucket_iam_member" "member" {
  bucket = "your-bucket-name"
  role   = "roles/storage.objectViewer"
  member = "user:jane@example.com"
}
```

» google_storage_bucket_iam_policy

When applying a policy that does not include the roles listed below, you lose the default permissions which google adds to your bucket: `*roles/storage.legacyBucketOwner * roles/storage.legacyBucketReader`

If this happens only an entity with `roles/storage.admin` privileges can repair this bucket's policies. It is recommended to include the above roles in policies to get the same behaviour as with the other two options.

```
data "google_iam_policy" "foo-policy" {
  binding {
    role = "roles/your-role"

    members = [ "group:yourgroup@example.com" ]
  }
}

resource "google_storage_bucket_iam_policy" "member" {
  bucket = "your-bucket-name"
  policy_data = "${data.google_iam_policy.foo-policy.policy_data}"
}
```

» Argument Reference

The following arguments are supported:

- **bucket** - (Required) The name of the bucket it applies to.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.

- **role** - (Required) The role that should be applied. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the storage bucket's IAM policy.

» IAM policy for Google storage bucket

Three different resources help you manage your IAM policy for storage bucket. Each of these resources serves a different use case:

- **google_storage_bucket_iam_binding**: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the storage bucket are preserved.
- **google_storage_bucket_iam_member**: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the storage bucket are preserved.
- **google_storage_bucket_iam_policy**: Setting a policy removes all other permissions on the bucket, and if done incorrectly, there's a real chance you will lock yourself out of the bucket. If possible for your use case, using multiple `google_storage_bucket_iam_binding` resources will be much safer. See the usage example on how to work with policy correctly.

Note: `google_storage_bucket_iam_binding` resources **can be** used in conjunction with `google_storage_bucket_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_storage_bucket_iam_binding`

```
resource "google_storage_bucket_iam_binding" "binding" {
  bucket = "your-bucket-name"
  role   = "roles/storage.objectViewer"

  members = [
    "user:jane@example.com",
  ]
}
```

» google_storage_bucket_iam_member

```
resource "google_storage_bucket_iam_member" "member" {  
  bucket = "your-bucket-name"  
  role   = "roles/storage.objectViewer"  
  member = "user:jane@example.com"  
}
```

» google_storage_bucket_iam_policy

When applying a policy that does not include the roles listed below, you lose the default permissions which google adds to your bucket: `*roles/storage.legacyBucketOwner * roles/storage.legacyBucketReader`

If this happens only an entity with `roles/storage.admin` privileges can repair this bucket's policies. It is recommended to include the above roles in policies to get the same behaviour as with the other two options.

```
data "google_iam_policy" "foo-policy" {  
  binding {  
    role = "roles/your-role"  
  
    members = [ "group:yourgroup@example.com" ]  
  }  
}  
  
resource "google_storage_bucket_iam_policy" "member" {  
  bucket = "your-bucket-name"  
  policy_data = "${data.google_iam_policy.foo-policy.policy_data}"  
}
```

» Argument Reference

The following arguments are supported:

- **bucket** - (Required) The name of the bucket it applies to.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.

- **serviceAccount:{emailid}**: An email address that represents a service account. For example, my-other-app@appspot.gserviceaccount.com.
- **group:{emailid}**: An email address that represents a Google group. For example, admins@example.com.
- **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the storage bucket's IAM policy.

» google_storage_bucket_object

Creates a new object inside an existing bucket in Google cloud storage service (GCS). ACLs can be applied using the `google_storage_object_acl` resource. For more information see the official documentation and API.

» Example Usage

Example creating a public object in an existing `image-store` bucket.

```
resource "google_storage_bucket_object" "picture" {
  name     = "butterfly01"
  source   = "/images/nature/garden-tiger-moth.jpg"
  bucket   = "image-store"
}
```

» Argument Reference

The following arguments are supported:

- **bucket** - (Required) The name of the containing bucket.
- **name** - (Required) The name of the object.

One of the following is required:

- **content** - (Optional) Data as **string** to be uploaded. Must be defined if **source** is not.
- **source** - (Optional) A path to the data you want to upload. Must be defined if **content** is not.

-
- **cache_control** - (Optional) Cache-Control directive to specify caching behavior of object data. If omitted and object is accessible to all anonymous users, the default will be public, max-age=3600
 - **content_disposition** - (Optional) Content-Disposition of the object data.
 - **content_encoding** - (Optional) Content-Encoding of the object data.
 - **content_language** - (Optional) Content-Language of the object data.
 - **content_type** - (Optional) Content-Type of the object data. Defaults to "application/octet-stream" or "text/plain; charset=utf-8".
 - **storage_class** - (Optional) The StorageClass of the new bucket object. Supported values include: **MULTI_REGIONAL**, **REGIONAL**, **NEARLINE**, **COLDLINE**. If not provided, this defaults to the bucket's default storage class or to a standard class.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **crc32c** - (Computed) Base 64 CRC32 hash of the uploaded data.
- **md5hash** - (Computed) Base 64 MD5 hash of the uploaded data.

» **google__storage__default__object__acl**

Creates a new default object ACL in Google Cloud Storage service (GCS). For more information see the official documentation and API.

» Example Usage

Example creating a default object ACL on a bucket with one owner, and one reader.

```

resource "google_storage_bucket" "image-store" {
  name      = "image-store-bucket"
  location  = "EU"
}

resource "google_storage_default_object_acl" "image-store-default-acl" {
  bucket = "${google_storage_bucket.image-store.name}"
  role_entity = [
    "OWNER:user-my.email@gmail.com",
    "READER:group-mysgroup",
  ]
}

```

» Argument Reference

- `bucket` - (Required) The name of the bucket it applies to.
- `role_entity` - (Required) List of role/entity pairs in the form `ROLE:entity`. See GCS Object ACL documentation for more details.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» `google_storage_notification`

Creates a new notification configuration on a specified bucket, establishing a flow of event notifications from GCS to a Cloud Pub/Sub topic. For more information see the official documentation and API.

In order to enable notifications, a special Google Cloud Storage service account unique to the project must have the IAM permission `projects.topics.publish` for a Cloud Pub/Sub topic in the project. To get the service account's email address, use the `google_storage_project_service_account` datasource's `email_address` value, and see below for an example of enabling notifications by granting the correct IAM permission. See the notifications documentation for more details.

» Example Usage

```

resource "google_storage_notification" "notification" {
  bucket = "${google_storage_bucket.bucket.name}"

```

```

    payload_format    = "JSON_API_V1"
    topic             = "${google_pubsub_topic.topic.id}"
    event_types       = ["OBJECT_FINALIZE", "OBJECT_METADATA_UPDATE"]
    custom_attributes {
        new-attribute = "new-attribute-value"
    }
    depends_on        = ["google_pubsub_topic_iam_binding.binding"]
}

// Enable notifications by giving the correct IAM permission to the unique service account.

data "google_storage_project_service_account" "gcs_account" {}

resource "google_pubsub_topic_iam_binding" "binding" {
    topic      = "${google_pubsub_topic.topic.name}"
    role       = "roles/pubsub.publisher"
    members    = ["serviceAccount:${data.google_storage_project_service_account.gcs_account}"]
}

// End enabling notifications

resource "google_storage_bucket" "bucket" {
    name = "default_bucket"
}

resource "google_pubsub_topic" "topic" {
    name = "default_topic"
}

```

» Argument Reference

The following arguments are supported:

- **bucket** - (Required) The name of the bucket.
 - **payload_format** - (Required) The desired content of the Payload. One of "JSON_API_V1" or "NONE".
 - **topic** - (Required) The Cloud PubSub topic to which this subscription publishes. Expects either the topic name, assumed to belong to the default GCP provider project, or the project-level name, i.e. `projects/my-gcp-project/topics/my-topic` or `my-topic`.
-
- **custom_attributes** - (Optional) A set of key/value attribute pairs to

attach to each Cloud PubSub message published for this notification subscription

- **event_types** - (Optional) List of event type filters for this notification config. If not specified, Cloud Storage will send notifications for all event types. The valid types are: "OBJECT_FINALIZE", "OBJECT_METADATA_UPDATE", "OBJECT_DELETE", "OBJECT_ARCHIVE"
- **object_name_prefix** - (Optional) Specifies a prefix path filter for this notification config. Cloud Storage will only send notifications for objects in this bucket whose names begin with the specified prefix.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The URI of the created resource.

» Import

Storage notifications can be imported using the notification id in the format <bucket_name>/notificationConfigs/<id> e.g.

```
$ terraform import google_storage_notification.notification default_bucket/notificationConfigs/<id>
```

» google_storage_object_acl

Creates a new object ACL in Google cloud storage service (GCS). For more information see the official documentation and API.

» Example Usage

Create an object ACL with one owner and one reader.

```
resource "google_storage_bucket" "image-store" {
  name     = "image-store-bucket"
  location = "EU"
}

resource "google_storage_bucket_object" "image" {
  name     = "image1"
  bucket   = "${google_storage_bucket.image-store.name}"
  source   = "image1.jpg"
}
```

```

}

resource "google_storage_object_acl" "image-store-acl" {
  bucket = "${google_storage_bucket.image-store.name}"
  object = "${google_storage_bucket_object.image.name}"

  role_entity = [
    "OWNER:user-my.email@gmail.com",
    "READER:group-mygroup",
  ]
}

```

» Argument Reference

- `bucket` - (Required) The name of the bucket it applies to.
 - `object` - (Required) The name of the object it applies to.
-
- `predefined_acl` - (Optional) The canned GCS ACL to apply. Must be set if `role_entity` is not.
 - `role_entity` - (Optional) List of role/entity pairs in the form `ROLE:entity`. See GCS Object ACL documentation for more details. Must be set if `predefined_acl` is not.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» `google_kms_crypto_key`

Allows creation of a Google Cloud Platform KMS CryptoKey. For more information see the official documentation and API.

A CryptoKey is an interface to key material which can be used to encrypt and decrypt data. A CryptoKey belongs to a Google Cloud KMS KeyRing.

Note: CryptoKeys cannot be deleted from Google Cloud Platform. Destroying a Terraform-managed CryptoKey will remove it from state and delete all CryptoKeyVersions, rendering the key unusable, but **will not delete the resource on the server**.

» Example Usage

```
resource "google_kms_key_ring" "my_key_ring" {
  name      = "my-key-ring"
  project   = "my-project"
  location  = "us-central1"
}

resource "google_kms_crypto_key" "my_crypto_key" {
  name          = "my-crypto-key"
  key_ring      = "${google_kms_key_ring.my_key_ring.self_link}"
  rotation_period = "100000s"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The CryptoKey's name. A CryptoKey's name must be unique within a location and match the regular expression `[a-zA-Z0-9_-]{1,63}`
 - **key_ring** - (Required) The id of the Google Cloud Platform KeyRing to which the key shall belong.
-
- **rotation_period** - (Optional) Every time this period passes, generate a new CryptoKeyVersion and set it as the primary. The first rotation will take place after the specified period. The rotation period has the format of a decimal number with up to 9 fractional digits, followed by the letter `s` (seconds). It must be greater than a day (ie, 86400).

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **self_link** - The self link of the created CryptoKey. Its format is `projects/{projectId}/locations/{location}/keyRings/{keyRingName}/cryptoKeys/{cryptoKeyName}`

» Import

CryptoKeys can be imported using the CryptoKey autogenerated id, e.g.

```
$ terraform import google_kms_crypto_key.my_crypto_key my-gcp-project/us-central1/my-key-ring/my-crypto-key
$ terraform import google_kms_crypto_key.my_crypto_key us-central1/my-key-ring/my-crypto-key
```

» `google_kms_crypto_key_iam_binding`

Allows creation and management of a single binding within IAM policy for an existing Google Cloud KMS crypto key.

» Example Usage

```
resource "google_kms_crypto_key_iam_binding" "crypto_key" {
  crypto_key_id = "my-gcp-project/us-central1/my-key-ring/my-crypto-key"
  role          = "roles/editor"

  members = [
    "user:jane@example.com",
  ]
}
```

» Argument Reference

The following arguments are supported:

- `members` - (Required) A list of users that the role should apply to.
- `role` - (Required) The role that should be applied. Only one `google_kms_crypto_key_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- `crypto_key_id` - (Required) The crypto key ID, in the form `{project_id}/{location_name}/{key_ring_name}/{crypto_key_name}` or `{location_name}/{key_ring_name}/{crypto_key_name}`. In the second form, the provider's project setting will be used as a fallback.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `etag` - (Computed) The etag of the crypto key's IAM policy.

» Import

IAM binding imports use space-delimited identifiers; first the resource in question and then the role. These bindings can be imported using the `crypto_key_id` and `role`, e.g.

```
$ terraform import google_kms_crypto_key_iam_binding.crypto_key "my-gcp-project/us-central1/
```

» google_kms_crypto_key_iam_member

Allows creation and management of a single member for a single binding within the IAM policy for an existing Google Cloud KMS crypto key.

Note: This resource *must not* be used in conjunction with `google_kms_crypto_key_iam_policy` or they will fight over what your policy should be. Similarly, roles controlled by `google_kms_crypto_key_iam_binding` should not be assigned to using `google_kms_crypto_key_iam_member`.

» Example Usage

```
resource "google_kms_crypto_key_iam_member" "crypto_key" {
  crypto_key_id = "your-crypto-key-id"
  role          = "roles/editor"
  member        = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- `member` - (Required) The user that the role should apply to.
- `role` - (Required) The role that should be applied. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- `crypto_key_id` - (Required) The key ring ID, in the form `{project_id}/{location_name}/{key_ring_name}` or `{location_name}/{key_ring_name}/{crypto_key_name}`. In the second form, the provider's project setting will be used as a fallback.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the project's IAM policy.

» Import

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account. This member resource can be imported using the `crypto_key_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_crypto_key_iam_member.member "your-project-id/location-name/k
```

» google_kms_key_ring

Allows creation of a Google Cloud Platform KMS KeyRing. For more information see the official documentation and API.

A KeyRing is a grouping of CryptoKeys for organizational purposes. A KeyRing belongs to a Google Cloud Platform Project and resides in a specific location.

Note: KeyRings cannot be deleted from Google Cloud Platform. Destroying a Terraform-managed KeyRing will remove it from state but **will not delete the resource on the server**.

» Example Usage

```
resource "google_kms_key_ring" "my_key_ring" {
  name      = "my-key-ring"
  location = "us-central1"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) The KeyRing's name. A KeyRing's name must be unique within a location and match the regular expression `[a-zA-Z0-9_-]{1,63}`
- **location** - (Required) The Google Cloud Platform location for the KeyRing. A full list of valid locations can be found by running `gcloud kms locations list`.

-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `self_link` - The self link of the created KeyRing. Its format is `projects/{projectId}/locations/{location}/keyRings/{keyRingName}`.

» Import

KeyRings can be imported using the KeyRing autogenerated id, e.g.

```
$ terraform import google_kms_key_ring.my_key_ring my-gcp-project/us-central1/my-key-ring
```

```
$ terraform import google_kms_key_ring.my_key_ring us-central1/my-key-ring
```

» IAM policy for Google Cloud KMS key ring

Three different resources help you manage your IAM policy for KMS key ring. Each of these resources serves a different use case:

- `google_kms_key_ring_iam_policy`: Authoritative. Sets the IAM policy for the key ring and replaces any existing policy already attached.
- `google_kms_key_ring_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the key ring are preserved.
- `google_kms_key_ring_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the key ring are preserved.

Note: `google_kms_key_ring_iam_policy` **cannot** be used in conjunction with `google_kms_key_ring_iam_binding` and `google_kms_key_ring_iam_member` or they will fight over what your policy should be.

Note: `google_kms_key_ring_iam_binding` resources **can be** used in conjunction with `google_kms_key_ring_iam_member` resources **only if** they do not grant privilege to the same role.

» `google_kms_key_ring_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
```

```

        "user:jane@example.com",
    ]
}
}

resource "google_kms_key_ring_iam_policy" "key_ring" {
    key_ring_id = "your-key-ring-id"
    policy_data = "${data.google_iam_policy.admin.policy_data}"
}

```

» google_kms_key_ring_iam_binding

```

resource "google_kms_key_ring_iam_binding" "key_ring" {
    key_ring_id = "your-key-ring-id"
    role        = "roles/editor"

    members = [
        "user:jane@example.com",
    ]
}

```

» google_kms_key_ring_iam_member

```

resource "google_kms_key_ring_iam_member" "key_ring" {
    key_ring_id = "your-key-ring-id"
    role        = "roles/editor"
    member      = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **key_ring_id** - (Required) The key ring ID, in the form `{project_id}/{location_name}/{key_ring_name}` or `{location_name}/{key_ring_name}`. In the second form, the provider's project setting will be used as a fallback.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.

- **user:{emailid}**: An email address that represents a specific Google account. For example, alice@gmail.com or joe@example.com.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, my-other-app@appspot.gserviceaccount.com.
 - **group:{emailid}**: An email address that represents a Google group. For example, admins@example.com.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, google.com or example.com.
- **role** - (Required) The role that should be applied. Only one `google_kms_key_ring_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
 - **policy_data** - (Required only by `google_kms_key_ring_iam_policy`) The policy data generated by a `google_iam_policy` data source.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the key ring's IAM policy.

» Import

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account. This member resource can be imported using the `key_ring_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_key_ring_iam_member.key_ring_iam "your-project-id/location-name"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role. This binding resource can be imported using the `key_ring_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_key_ring_iam_binding.key_ring_iam "your-project-id/location-name"
```

IAM policy imports use the identifier of the resource in question. This policy resource can be imported using the `key_ring_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_key_ring_iam_policy.key_ring_iam your-project-id/location-name"
```

» IAM policy for Google Cloud KMS key ring

Three different resources help you manage your IAM policy for KMS key ring. Each of these resources serves a different use case:

- `google_kms_key_ring_iam_policy`: Authoritative. Sets the IAM policy for the key ring and replaces any existing policy already attached.
- `google_kms_key_ring_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the key ring are preserved.
- `google_kms_key_ring_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the key ring are preserved.

Note: `google_kms_key_ring_iam_policy` **cannot** be used in conjunction with `google_kms_key_ring_iam_binding` and `google_kms_key_ring_iam_member` or they will fight over what your policy should be.

Note: `google_kms_key_ring_iam_binding` resources **can be** used in conjunction with `google_kms_key_ring_iam_member` resources **only** if they do not grant privilege to the same role.

» `google_kms_key_ring_iam_policy`

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_kms_key_ring_iam_policy" "key_ring" {
  key_ring_id = "your-key-ring-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» `google_kms_key_ring_iam_binding`

```
resource "google_kms_key_ring_iam_binding" "key_ring" {
  key_ring_id = "your-key-ring-id"
  role        = "roles/editor"
```

```

members = [
    "user:jane@example.com",
]
}

```

» google_kms_key_ring_iam_member

```

resource "google_kms_key_ring_iam_member" "key_ring" {
  key_ring_id = "your-key-ring-id"
  role        = "roles/editor"
  member      = "user:jane@example.com"
}

```

» Argument Reference

The following arguments are supported:

- **key_ring_id** - (Required) The key ring ID, in the form `{project_id}/{location_name}/{key_ring_name}` or `{location_name}/{key_ring_name}`. In the second form, the provider's project setting will be used as a fallback.
- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_kms_key_ring_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_kms_key_ring_iam_policy`) The policy data generated by a `google_iam_policy` data source.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- `etag` - (Computed) The etag of the key ring's IAM policy.

» Import

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account. This member resource can be imported using the `key_ring_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_key_ring_iam_member.key_ring_iam "your-project-id/location-name/key-ring-id/role/account"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role. This binding resource can be imported using the `key_ring_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_key_ring_iam_binding.key_ring_iam "your-project-id/location-name/key-ring-id/role/account"
```

IAM policy imports use the identifier of the resource in question. This policy resource can be imported using the `key_ring_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_key_ring_iam_policy.key_ring_iam "your-project-id/location-name/key-ring-id/role/account"
```

» IAM policy for Google Cloud KMS key ring

Three different resources help you manage your IAM policy for KMS key ring. Each of these resources serves a different use case:

- `google_kms_key_ring_iam_policy`: Authoritative. Sets the IAM policy for the key ring and replaces any existing policy already attached.
- `google_kms_key_ring_iam_binding`: Authoritative for a given role. Updates the IAM policy to grant a role to a list of members. Other roles within the IAM policy for the key ring are preserved.
- `google_kms_key_ring_iam_member`: Non-authoritative. Updates the IAM policy to grant a role to a new member. Other members for the role for the key ring are preserved.

Note: `google_kms_key_ring_iam_policy` **cannot** be used in conjunction with `google_kms_key_ring_iam_binding` and `google_kms_key_ring_iam_member` or they will fight over what your policy should be.

Note: `google_kms_key_ring_iam_binding` resources **can be** used in conjunction with `google_kms_key_ring_iam_member` resources **only** if they do not grant privilege to the same role.

» google_kms_key_ring_iam_policy

```
data "google_iam_policy" "admin" {
  binding {
    role = "roles/editor"

    members = [
      "user:jane@example.com",
    ]
  }
}

resource "google_kms_key_ring_iam_policy" "key_ring" {
  key_ring_id = "your-key-ring-id"
  policy_data = "${data.google_iam_policy.admin.policy_data}"
}
```

» google_kms_key_ring_iam_binding

```
resource "google_kms_key_ring_iam_binding" "key_ring" {
  key_ring_id = "your-key-ring-id"
  role        = "roles/editor"

  members = [
    "user:jane@example.com",
  ]
}
```

» google_kms_key_ring_iam_member

```
resource "google_kms_key_ring_iam_member" "key_ring" {
  key_ring_id = "your-key-ring-id"
  role        = "roles/editor"
  member      = "user:jane@example.com"
}
```

» Argument Reference

The following arguments are supported:

- **key_ring_id** - (Required) The key ring ID, in the form {project_id}/{location_name}/{key_ring_name} or {location_name}/{key_ring_name}. In the second form, the provider's project setting will be used as a fallback.

- **member/members** - (Required) Identities that will be granted the privilege in **role**. Each entry can have one of the following values:
 - **allUsers**: A special identifier that represents anyone who is on the internet; with or without a Google account.
 - **allAuthenticatedUsers**: A special identifier that represents anyone who is authenticated with a Google account or a service account.
 - **user:{emailid}**: An email address that represents a specific Google account. For example, `alice@gmail.com` or `joe@example.com`.
 - **serviceAccount:{emailid}**: An email address that represents a service account. For example, `my-other-app@appspot.gserviceaccount.com`.
 - **group:{emailid}**: An email address that represents a Google group. For example, `admins@example.com`.
 - **domain:{domain}**: A Google Apps domain name that represents all the users of that domain. For example, `google.com` or `example.com`.
- **role** - (Required) The role that should be applied. Only one `google_kms_key_ring_iam_binding` can be used per role. Note that custom roles must be of the format `[projects|organizations]/{parent-name}/roles/{role-name}`.
- **policy_data** - (Required only by `google_kms_key_ring_iam_policy`) The policy data generated by a `google_iam_policy` data source.

» Attributes Reference

In addition to the arguments listed above, the following computed attributes are exported:

- **etag** - (Computed) The etag of the key ring's IAM policy.

» Import

IAM member imports use space-delimited identifiers; the resource in question, the role, and the account. This member resource can be imported using the `key_ring_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_key_ring_iam_member.key_ring_iam "your-project-id/location-name/key-ring-id/role/account"
```

IAM binding imports use space-delimited identifiers; the resource in question and the role. This binding resource can be imported using the `key_ring_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_key_ring_iam_binding.key_ring_iam "your-project-id/location-name/key-ring-id/role/account"
```

IAM policy imports use the identifier of the resource in question. This policy resource can be imported using the `key_ring_id`, `role`, and `account` e.g.

```
$ terraform import google_kms_key_ring_iam_policy.key_ring_iam your-project-id/location-name
```

» google__cloudiot__registry

Creates a device registry in Google's Cloud IoT Core platform. For more information see the official documentation and API.

» Example Usage

```
resource "google_pubsub_topic" "default-devicestatus" {
  name = "default-devicestatus"
}

resource "google_pubsub_topic" "default-telemetry" {
  name = "default-telemetry"
}

resource "google_cloudiot_registry" "default-registry" {
  name = "default-registry"

  event_notification_config = {
    pubsub_topic_name = "${google_pubsub_topic.default-telemetry.id}"
  }

  state_notification_config = {
    pubsub_topic_name = "${google_pubsub_topic.default-devicestatus.id}"
  }

  http_config = {
    http_enabled_state = "HTTP_ENABLED"
  }

  mqtt_config = {
    mqtt_enabled_state = "MQTT_ENABLED"
  }

  credentials = [
    {
      public_key_certificate = {
        format      = "X509_CERTIFICATE_PEM"
        certificate = "${file("rsa_cert.pem")}"
      }
    },
  ],
}
```

```
]
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required) A unique name for the resource, required by device registry. Changing this forces a new resource to be created.
-
- **project** - (Optional) The project in which the resource belongs. If it is not provided, the provider project is used.
 - **region** - (Optional) The Region in which the created address should reside. If it is not provided, the provider region is used.
 - **event_notification_config** - (Optional) A PubSub topics to publish device events. Structure is documented below.
 - **state_notification_config** - (Optional) A PubSub topic to publish device state updates. Structure is documented below.
 - **mqtt_config** - (Optional) Activate or deactivate MQTT. Structure is documented below.
 - **http_config** - (Optional) Activate or deactivate HTTP. Structure is documented below.
 - **credentials** - (Optional) List of public key certificates to authenticate devices. Structure is documented below.

The **event_notification_config** block supports:

- **pubsub_topic_name** - (Required) PubSub topic name to publish device events.

The **state_notification_config** block supports:

- **pubsub_topic_name** - (Required) PubSub topic name to publish device state updates.

The **mqtt_config** block supports:

- **mqtt_enabled_state** - (Required) The field allows **MQTT_ENABLED** or **MQTT_DISABLED**.

The **http_config** block supports:

- **http_enabled_state** - (Required) The field allows **HTTP_ENABLED** or **HTTP_DISABLED**.

The **credentials** block supports:

- `public_key_certificate` - (Required) The certificate format and data.

The `public_key_certificate` block supports:

- `format` - (Required) The field allows only `X509_CERTIFICATE_PEM`.
- `certificate` - (Required) The certificate data.

» Attributes Reference

Only the arguments listed above are exposed as attributes.

» Import

A device registry can be imported using the `name`, e.g.

```
$ terraform import google_cloudiot_registry.default-registry projects/{project}/locations/{location}/registries/{registry-name}
```