

» Data Source: `hcloud_floating_ip`

Provides details about a Hetzner Cloud Floating IP.

This resource can be useful when you need to determine a Floating IP ID based on the IP address.

» Example Usage

» Data Source: `hcloud_floating_ip`

Provides details about a Hetzner Cloud Floating IP. This resource can be useful when you need to determine a Floating IP ID based on the IP address.

» Example Usage

```
data "hcloud_floating_ip" "ip_1" {
  ip_address = "1.2.3.4"
}
data "hcloud_floating_ip" "image_2" {
  selector = "key=value"
}
resource "hcloud_floating_ip_assignment" "main" {
  count          = "${var.counter}"
  floating_ip_id = "${data.hcloud_floating_ip.ip_1.id}"
  server_id      = "${hcloud_server.main.id}"
}
```

» Argument Reference

- `ip_address` - (Optional, string) IP address of the Floating IP.
- `selector` - (Optional, string) Label selector

» Attributes Reference

- `id` - (int) Unique ID of the Floating IP.
- `ip_address` - (string) IP address of the Floating IP.

» Data Source: `hcloud_image`

Provides details about a Hetzner Cloud Image. This resource is useful if you want to use a non-terraform managed image.

» Example Usage

```
data "hcloud_image" "image_1" {
  id = "1234"
}
data "hcloud_image" "image_2" {
  name = "ubuntu-18.04"
}
data "hcloud_image" "image_3" {
  selector = "key=value"
}

resource "hcloud_server" "main" {
  image = "${data.hcloud_image.image_1.name}"
}
```

» Argument Reference

- `id` - (Optional, string) ID of the Image.
- `name` - (Optional, string) Name of the Image.
- `selector` - (Optional, string) Label selector

» Attributes Reference

- `id` - (int) Unique ID of the Image.
- `name` - (string) Name of the Image.
- `type` - (string) Type of the Image, could be `system`, `backup` or `snapshot`.
- `status` - (string) Status of the Image.
- `description` - (string) Description of the Image.
- `created` - (string) Date when the Image was created (in ISO-8601 format).
- `os_flavor` - (string) Flavor of operating system contained in the image, could be `ubuntu`, `centos`, `debian`, `fedora` or `unknown`.
- `os_version` - (string) Operating system version.
- `rapid_deploy` - (bool) Indicates that rapid deploy of the image is available.
- `deprecated` - (string) Point in time when the image is considered to be deprecated (in ISO-8601 format).

» Data Source: `hcloud__sshkey`

Provides details about a Hetzner Cloud SSH Key. This resource is useful if you want to use a non-terraform managed SSH Key.

» Example Usage

```
data "hcloud_ssh_key" "ssh_key_1" {
  id = "1234"
}
data "hcloud_ssh_key" "ssh_key_2" {
  name = "my-ssh-key"
}
data "hcloud_ssh_key" "ssh_key_3" {
  fingerprint = "43:51:43:a1:b5:fc:8b:b7:0a:3a:a9:b1:0f:66:73:a8"
}
data "hcloud_ssh_key" "ssh_key_4" {
  selector = "key=value"
}
resource "hcloud_server" "main" {
  ssh_keys = ["${data.hcloud_ssh_key.ssh_key_1.id}", "${data.hcloud_ssh_key.ssh_key_2.id}", "${data.hcloud_ssh_key.ssh_key_3.id}", "${data.hcloud_ssh_key.ssh_key_4.id}"]
}
```

» Argument Reference

- `id` - (Optional, string) ID of the SSH Key.
- `name` - (Optional, string) Name of the SSH Key.
- `fingerprint` - (Optional, string) Fingerprint of the SSH Key.
- `selector` - (Optional, string) Label selector

» Attributes Reference

- `id` - (int) Unique ID of the SSH Key.
- `name` - (string) Name of the SSH Key.
- `fingerprint` - (string) Fingerprint of the SSH Key.
- `public_key` - (string) Public Key of the SSH Key.

» Data Source: `hcloud__volume`

Provides details about a Hetzner Cloud volume. This resource is useful if you want to use a non-terraform managed volume.

» Example Usage

```
data "hcloud_volume" "volume_1" {
  id = "1234"
}
data "hcloud_volume" "volume_2" {
  name = "my-volume"
}
data "hcloud_volume" "volume_3" {
  selector = "key=value"
}
```

» Argument Reference

- `id` - ID of the volume.
- `name` - Name of the volume.
- `selector` - Label Selector. For more information about possible values, visit the [Hetzner Cloud Documentation](#).

» Attributes Reference

- `id` - Unique ID of the volume.
- `name` - Name of the volume.
- `size` - Size of the volume.

» `hcloud_server`

Provides an Hetzner Cloud server resource. This can be used to create, modify, and delete servers. Servers also support provisioning.

» Example Usage

```
# Create a new server running debian
resource "hcloud_server" "node1" {
  name = "node1"
  image = "debian-9"
  server_type = "cx11"
}
```

» Argument Reference

The following arguments are supported:

- **name** - (Required, string) Name of the server to create (must be unique per project and a valid hostname as per RFC 1123).
- **server_type** - (Required, string) Name of the server type this server should be created with.
- **image** - (Required, string) Name or ID of the image the server is created from.
- **location** - (Optional, string) The location name to create the server in.
- **datacenter** - (Optional, string) The datacenter name to create the server in.
- **user_data** - (Optional, string) Cloud-Init user data to use during server creation
- **ssh_keys** - (Optional, list) SSH key IDs or names which should be injected into the server at creation time
- **keep_disk** - (Optional, bool) If true, do not upgrade the disk. This allows downgrading the server type later.
- **iso** - (Optional, string) Name of an ISO image to mount.
- **rescue** - (Optional, string) Enable and boot in to the specified rescue system. This enables simple installation of custom operating systems. `linux64 linux32` or `freebsd64`
- **labels** - (Optional, map) User-defined labels (key-value pairs) should be created with.
- **backups** - (Optional, boolean) Enable or disable backups.

» Attributes Reference

The following attributes are exported:

- **id** - (int) Unique ID of the server.
- **name** - (string) Name of the server.
- **server_type** - (string) Name of the server type.
- **image** - (string) Name or ID of the image the server was created from.
- **location** - (string) The location name.
- **datacenter** - (string) The datacenter name.
- **backup_window** - (string) The backup window of the server, if enabled.
- **backups** - (boolean) Whether backups are enabled.
- **iso** - (string) Name of the mounted ISO image.
- **ipv4_address** - (string) The IPv4 address.
- **ipv6_address** - (string) The first IPv6 address of the assigned network.
- **ipv6_network** - (string) The IPv6 network.
- **status** - (string) The status of the server.
- **labels** - (map) User-defined labels (key-value pairs)

» Import

Servers can be imported using the server id:

```
terraform import hcloud_server.myserver <id>
```

» hcloud_volume

Provides a Hetzner Cloud volume resource to manage volumes.

» Example Usage

```
resource "hcloud_server" "node1" {
  name = "node1"
  image = "debian-9"
  server_type = "cx11"
}

resource "hcloud_volume" "master" {
  name = "volume1"
  size = 50
  server_id = "${hcloud_server.node1.id}"
}
```

» Argument Reference

- **name** - (Required, string) Name of the volume to create (must be unique per project).
- **size** - (Required, int) Size of the volume (in GB).
- **server** - (Optional, int) Server to attach the Volume to, optional if location argument is passed.
- **location** - (Optional, string) Location of the volume to create, optional if server_id argument is passed.

» Attributes Reference

- **id** - Unique ID of the volume.
- **name** - Name of the volume.
- **size** - Size of the volume.
- **labels** - User-defined labels (key-value pairs).
- **linux_device** - Device path on the file system for the Volume.

» Import

Volumes can be imported using their id:

```
terraform import hcloud_volume.myvolume <id>
```

» hcloud_volume_attachment

Provides a Hetzner Cloud Volume attachment to attach a Volume to a Hetzner Cloud Server. Deleting a Volume Attachment will detach the Volume from the Server.

» Example Usage

```
resource "hcloud_volume_attachment" "main" {
  volume_id = "${hcloud_volume.master.id}"
  server_id = "${hcloud_server.node1.id}"
}

resource "hcloud_server" "node1" {
  name = "node1"
  image = "debian-9"
  server_type = "cx11"
  datacenter = "nbg1-dc3"
}

resource "hcloud_volume" "master" {
  location = "nbg1"
  size     = 10
}
```

» Argument Reference

- `volume_id` - (Required, int) ID of the Volume.
- `server_id` - (Required, int) Server to attach the Volume to.

» Attributes Reference

- `id` - (int) Unique ID of the Volume Attachment.
- `volume_id` - (int) ID of the Volume.
- `server_id` - (int) Server the Volume was attached to.

» **hcloud_ssh_key**

Provides a Hetzner Cloud SSH key resource to manage SSH keys for server access.

» **Example Usage**

```
# Create a new SSH key
resource "hcloud_ssh_key" "default" {
  name = "Terraform Example"
  public_key = "${file("~/ssh/id_rsa.pub")}"
}
```

» **Argument Reference**

The following arguments are supported:

- **name** - (Required, string) Name of the SSH key.
- **public_key** - (Required, string) The public key. If this is a file, it can be read using the file interpolation function

» **Attributes Reference**

The following attributes are exported:

- **id** - (int) The unique ID of the key.
- **name** - (string) The name of the SSH key
- **public_key** - (string) The text of the public key
- **fingerprint** - (string) The fingerprint of the SSH key
- **labels** - (map) User-defined labels (key-value pairs)

» **Import**

SSH keys can be imported using the SSH key id:

```
terraform import hcloud_ssh_key.mykey <id>
```

» **hcloud_floating_ip**

Provides a Hetzner Cloud Floating IP to represent a publicly-accessible static IP address that can be mapped to one of your servers.

» Example Usage

```
resource "hcloud_server" "node1" {
  name = "node1"
  image = "debian-9"
  server_type = "cx11"
}

resource "hcloud_floating_ip" "master" {
  type = "ipv4"
  server_id = "${hcloud_server.node1.id}"
}
```

» Argument Reference

- **type** - (Required, string) Type of the Floating IP. `ipv4` `ipv6`
- **server_id** - (Optional, int) Server to assign the Floating IP to.
- **home_location** - (Optional, string) Home location (routing is optimized for that location). Optional if `server_id` argument is passed.
- **description** - (Optional, string) Description of the Floating IP.

» Attributes Reference

- **id** - (int) Unique ID of the Floating IP.
- **type** - (string) Type of the Floating IP.
- **server_id** - (int) Server to assign the Floating IP is assigned to.
- **home_location** - (string) Home location.
- **description** - (string) Description of the Floating IP.
- **ip_address** - (string) IP Address of the Floating IP.
- **ip_network** - (string) IPv6 subnet. (Only set if **type** is `ipv6`)
- **labels** - (map) User-defined labels (key-value pairs)

» Import

Floating IPs can be imported using its id:

```
terraform import hcloud_floating_ip.myip <id>
```

» `hcloud_floating_ip_assignment`

Provides a Hetzner Cloud Floating IP Assignment to assign a Floating IP to a Hetzner Cloud Server. Deleting a Floating IP Assignment will unassign the

Floating IP from the Server.

» Example Usage

```
resource "hcloud_floating_ip_assignment" "main" {
  floating_ip_id = "${hcloud_floating_ip.master.id}"
  server_id = "${hcloud_server.node1.id}"
}

resource "hcloud_server" "node1" {
  name = "node1"
  image = "debian-9"
  server_type = "cx11"
  datacenter = "fsn1-dc8"
}

resource "hcloud_floating_ip" "master" {
  type = "ipv4"
  home_location = "nbg1"
}
```

» Argument Reference

- `floating_ip_id` - (Required, int) ID of the Floating IP.
- `server_id` - (Required, int) Server to assign the Floating IP to.

» Attributes Reference

- `id` - (int) Unique ID of the Floating IP Assignment.
- `floating_ip_id` - (int) ID of the Floating IP.
- `server_id` - (int) Server the Floating IP was assigned to.

» `hcloud_rdns`

Provides a Hetzner Cloud Reverse DNS Entry to create, modify and reset reverse dns entries for Hetzner Cloud Floating IPs or servers.

» Example Usage

For servers:

```

resource "hcloud_server" "node1" {
  name = "node1"
  image = "debian-9"
  server_type = "cx11"
}

resource "hcloud_rdns" "master" {
  server_id = "${hcloud_server.node1.id}"
  ip_address = "${hcloud_server.node1.ipv4_address}"
  dns_ptr = "example.com"
}

```

For Floating IPs:

```

resource "hcloud_floating_ip" "floating1" {
  home_location = "ngb1"
  type = "ipv4"
}

resource "hcloud_rdns" "floating_master" {
  floating_ip_id = "${hcloud_floating_ip.floating1.id}"
  ip_address = "${hcloud_floating_ip.floating1.ipv4_address}"
  dns_ptr = "example.com"
}

```

» Argument Reference

- `dns_ptr` - (Required, string) The DNS address the `ip_address` should resolve to.
- `ip_address` - (Required, string) The IP address that should point to `dns_ptr`.
- `server_id` - (Required, int) The server the `ip_address` belongs to.
- `floating_ip_id` - (Required, int) The Floating IP the `ip_address` belongs to.

» Attributes Reference

- `id` - (int) Unique ID of the Reverse DNS Entry.
- `dns_ptr` - (string) DNS pointer for the IP address.
- `ip_address` - (string) IP address.
- `server_id` - (int) The server the IP address belongs to.
- `floating_ip_id` - (int) The Floating IP the IP address belongs to.

» Import

Reverse DNS entries can be imported using a compound ID with the following format: <prefix (s for server/ f for floating ip)>-<server or floating ip ID>-<IP address>

```
# import reverse dns entry on server with id 123, ip 192.168.100.1
terraform import hcloud_rdns.myrdns s-123-192.168.100.1
```

```
# import reverse dns entry on floating ip with id 123, ip 2001:db8::1
terraform import hcloud_rdns.myrdns f-123-2001:db8::1
```