

Tiny Lisp Interpreter

Brent Seidel
Phoenix, AZ

January 19, 2021

This document is ©2021 Brent Seidel. All rights reserved.

Note that this is a draft version and not the final version for publication.

Contents

1	Introduction	1
1.1	What is This?	1
1.2	Why is This?	1
1.2.1	Why Lisp?	1
1.2.2	Why Ada?	2
2	The Language	3
2.1	User Interface	3
2.2	Optimization	3
2.3	Syntax	3
2.3.1	Special Characters	3
2.3.2	Reserved Words	4
2.3.3	Examples	4
2.4	Symbols and Variables	4
2.5	Operations	5
2.5.1	Normal Forms vs Special Forms	5
2.5.2	Arithmetic Operations	6
2.5.3	Boolean Operations	6
2.5.4	Character Operations	6
2.5.5	Comparison Operations	7
2.5.6	Control Flow	7
2.5.7	Debugging	7
2.5.8	Functions	8
2.5.9	Input/Output	8
2.5.10	List Operations	8
2.5.11	Memory Access	9
2.5.12	Predicates	9
2.5.13	String Related Operations	10
2.5.14	Symbol Related Operations	11
2.5.15	Variables	11
2.5.16	Other	12
2.6	Data Types	12
2.6.1	Integer	12
2.6.2	Characters	12

2.6.3	String	13
2.6.4	Boolean	13
2.6.5	List	13
3	Operation Reference	14
3.1	Template	14
3.1.1	Inputs	14
3.1.2	Output	14
3.1.3	Example	14
3.1.4	Description	14
3.1.5	Common Lisp Compatibility	14
3.2	+	14
3.2.1	Inputs	15
3.2.2	Output	15
3.2.3	Example	15
3.2.4	Description	15
3.2.5	Common Lisp Compatibility	15
3.3	-	15
3.3.1	Inputs	15
3.3.2	Output	15
3.3.3	Example	15
3.3.4	Description	15
3.3.5	Common Lisp Compatibility	15
3.4	*	16
3.4.1	Inputs	16
3.4.2	Output	16
3.4.3	Example	16
3.4.4	Description	16
3.4.5	Common Lisp Compatibility	16
3.5	/	16
3.5.1	Inputs	16
3.5.2	Output	16
3.5.3	Example	16
3.5.4	Description	16
3.5.5	Common Lisp Compatibility	17
3.6	=	17
3.6.1	Inputs	17
3.6.2	Output	17
3.6.3	Example	17
3.6.4	Description	17
3.6.5	Common Lisp Compatibility	17
3.7	/=	17
3.7.1	Inputs	17
3.7.2	Output	17
3.7.3	Example	18
3.7.4	Description	18

3.7.5	Common Lisp Compatibility	18
3.8	<	18
3.8.1	Inputs	18
3.8.2	Output	18
3.8.3	Example	18
3.8.4	Description	18
3.8.5	Common Lisp Compatibility	18
3.9	>	18
3.9.1	Inputs	18
3.9.2	Output	19
3.9.3	Example	19
3.9.4	Description	19
3.9.5	Common Lisp Compatibility	19
3.10	and	19
3.10.1	Inputs	19
3.10.2	Output	19
3.10.3	Example	19
3.10.4	Description	19
3.10.5	Common Lisp Compatibility	19
3.11	arrayp	20
3.11.1	Inputs	20
3.11.2	Output	20
3.11.3	Example	20
3.11.4	Description	20
3.11.5	Common Lisp Compatibility	20
3.12	atomp	20
3.12.1	Inputs	20
3.12.2	Output	20
3.12.3	Example	20
3.12.4	Description	20
3.12.5	Common Lisp Compatibility	21
3.13	bit-vector-p	21
3.13.1	Inputs	21
3.13.2	Output	21
3.13.3	Example	21
3.13.4	Description	21
3.13.5	Common Lisp Compatibility	21
3.14	car	21
3.14.1	Inputs	21
3.14.2	Output	21
3.14.3	Example	22
3.14.4	Description	22
3.14.5	Common Lisp Compatibility	22
3.15	cdr	22
3.15.1	Inputs	22
3.15.2	Output	22

3.15.3	Example	22
3.15.4	Description	22
3.15.5	Common Lisp Compatibility	22
3.16	char	22
3.16.1	Inputs	23
3.16.2	Output	23
3.16.3	Example	23
3.16.4	Description	23
3.16.5	Common Lisp Compatibility	23
3.17	char-downcase	23
3.17.1	Inputs	23
3.17.2	Output	23
3.17.3	Example	23
3.17.4	Description	23
3.17.5	Common Lisp Compatibility	23
3.18	char-int	24
3.18.1	Inputs	24
3.18.2	Output	24
3.18.3	Example	24
3.18.4	Description	24
3.18.5	Common Lisp Compatibility	24
3.19	char-upcase	24
3.19.1	Inputs	24
3.19.2	Output	24
3.19.3	Example	24
3.19.4	Description	24
3.19.5	Common Lisp Compatibility	25
3.20	characterp	25
3.20.1	Inputs	25
3.20.2	Output	25
3.20.3	Example	25
3.20.4	Description	25
3.20.5	Common Lisp Compatibility	25
3.21	coerce	25
3.21.1	Inputs	25
3.21.2	Output	25
3.21.3	Example	26
3.21.4	Description	26
3.21.5	Common Lisp Compatibility	26
3.22	compiled-function-p	26
3.22.1	Inputs	26
3.22.2	Output	26
3.22.3	Example	26
3.22.4	Description	26
3.22.5	Common Lisp Compatibility	26
3.23	complexp	27

3.23.1	Inputs	27
3.23.2	Output	27
3.23.3	Example	27
3.23.4	Description	27
3.23.5	Common Lisp Compatibility	27
3.24	concatenate	27
3.24.1	Inputs	27
3.24.2	Output	27
3.24.3	Example	27
3.24.4	Description	27
3.24.5	Common Lisp Compatibility	28
3.25	cons	28
3.25.1	Inputs	28
3.25.2	Output	28
3.25.3	Example	28
3.25.4	Description	28
3.25.5	Common Lisp Compatibility	28
3.26	consp	28
3.26.1	Inputs	28
3.26.2	Output	28
3.26.3	Example	29
3.26.4	Description	29
3.26.5	Common Lisp Compatibility	29
3.27	defun	29
3.27.1	Inputs	29
3.27.2	Output	29
3.27.3	Example	29
3.27.4	Description	29
3.27.5	Common Lisp Compatibility	29
3.28	dowhile	29
3.28.1	Inputs	30
3.28.2	Output	30
3.28.3	Example	30
3.28.4	Description	30
3.28.5	Common Lisp Compatibility	30
3.29	dotimes	30
3.29.1	Inputs	30
3.29.2	Output	30
3.29.3	Example	31
3.29.4	Description	31
3.29.5	Common Lisp Compatibility	31
3.30	dump	31
3.30.1	Inputs	31
3.30.2	Output	31
3.30.3	Example	31
3.30.4	Description	31

3.30.5	Common Lisp Compatibility	31
3.31	exit	32
3.31.1	Inputs	32
3.31.2	Output	32
3.31.3	Example	32
3.31.4	Description	32
3.31.5	Common Lisp Compatibility	32
3.32	floatp	32
3.32.1	Inputs	32
3.32.2	Output	32
3.32.3	Example	32
3.32.4	Description	32
3.32.5	Common Lisp Compatibility	33
3.33	fresh-line	33
3.33.1	Inputs	33
3.33.2	Output	33
3.33.3	Example	33
3.33.4	Description	33
3.33.5	Common Lisp Compatibility	33
3.34	functionp	33
3.34.1	Inputs	33
3.34.2	Output	33
3.34.3	Example	34
3.34.4	Description	34
3.34.5	Common Lisp Compatibility	34
3.35	if	34
3.35.1	Inputs	34
3.35.2	Output	34
3.35.3	Example	34
3.35.4	Description	34
3.35.5	Common Lisp Compatibility	34
3.36	int-char	35
3.36.1	Inputs	35
3.36.2	Output	35
3.36.3	Example	35
3.36.4	Description	35
3.36.5	Common Lisp Compatibility	35
3.37	integerp	35
3.37.1	Inputs	35
3.37.2	Output	35
3.37.3	Example	35
3.37.4	Description	36
3.37.5	Common Lisp Compatibility	36
3.38	lambda	36
3.38.1	Inputs	36
3.38.2	Output	36

3.38.3	Example	36
3.38.4	Description	36
3.38.5	Common Lisp Compatibility	36
3.39	length	36
3.39.1	Inputs	36
3.39.2	Output	37
3.39.3	Example	37
3.39.4	Description	37
3.39.5	Common Lisp Compatibility	37
3.40	let	37
3.40.1	Inputs	37
3.40.2	Output	37
3.40.3	Example	37
3.40.4	Description	37
3.40.5	Common Lisp Compatibility	37
3.41	list	37
3.42	listp	37
3.43	msg	37
3.44	not	37
3.45	nullp	37
3.46	numberp	37
3.46.1	Inputs	38
3.46.2	Output	38
3.46.3	Example	38
3.46.4	Description	38
3.46.5	Common Lisp Compatibility	38
3.47	or	38
3.47.1	Inputs	38
3.47.2	Output	38
3.47.3	Example	38
3.47.4	Description	38
3.47.5	Common Lisp Compatibility	39
3.48	packagep	39
3.48.1	Inputs	39
3.48.2	Output	39
3.48.3	Example	39
3.48.4	Description	39
3.48.5	Common Lisp Compatibility	39
3.49	parse-integer	40
3.50	peek8	40
3.51	peek16	40
3.52	peek32	40
3.53	poke8	40
3.54	poke16	40
3.55	poke32	40
3.56	print	40

3.57	quote	40
3.58	rationalp	40
3.58.1	Inputs	40
3.58.2	Output	40
3.58.3	Example	40
3.58.4	Description	40
3.58.5	Common Lisp Compatibility	40
3.59	read-line	41
3.60	realp	41
3.60.1	Inputs	41
3.60.2	Output	41
3.60.3	Example	41
3.60.4	Description	41
3.60.5	Common Lisp Compatibility	41
3.61	reset	41
3.62	setq	41
3.63	simple-bit-vector-p	41
3.63.1	Inputs	41
3.63.2	Output	41
3.63.3	Example	42
3.63.4	Description	42
3.63.5	Common Lisp Compatibility	42
3.64	simple-string-p	42
3.65	simple-vector-p	42
3.65.1	Inputs	42
3.65.2	Output	42
3.65.3	Example	42
3.65.4	Description	42
3.65.5	Common Lisp Compatibility	42
3.66	sleep	43
3.67	string-downcase	43
3.68	string-upcase	43
3.69	stringp	43
3.70	subseq	43
3.71	symbolp	43
3.72	terpri	43
3.72.1	Inputs	43
3.72.2	Output	43
3.72.3	Example	43
3.72.4	Description	43
3.72.5	Common Lisp Compatibility	43
3.73	vectorp	43
3.73.1	Inputs	43
3.73.2	Output	44
3.73.3	Example	44
3.73.4	Description	44

3.73.5	Common Lisp Compatibility	44
4	Internals	45
4.1	Operation	45
4.1.1	Read	45
4.1.2	Parse	45
4.1.3	Evaluate	45
4.1.4	Print	45
4.2	Data Structures	46
4.2.1	Elements	46
4.2.2	Cons	47
4.2.3	Symbols	47
4.2.4	Values	48
4.2.5	Strings	49
4.2.6	Functions	50
4.2.7	The Stack	50
4.2.8	Global Data	50
4.2.9	Memory Management	50
4.3	Utility Functions	50
4.4	Embedding	50
4.5	Opportunities for Optimizing	51
4.5.1	Memory Management	51
4.5.2	Constant expressions	51

Chapter 1

Introduction

This document provides a definition of a Tiny-Lisp interpreter written in Ada. Without such a definition, it is difficult to determine if the language is actually doing what it should be doing. This makes debugging more complicated.

1.1 What is This?

This is a Tiny-Lisp interpreter written in Ada. It is designed to provide a language that can be embedded into other programs, including running on embedded systems without an operating system. As a result, effort has been made to remove dependencies on Ada packages that may not be available. A primary example is `Ada.Text_IO`. Another feature that may be missing is dynamic memory allocation.

1.2 Why is This?

As a young lad, I learned to program on 8-bit computers with minimal BASIC interpreters and 4-16K of RAM. With these simple systems, one had a hope of being able to understand the complete system at a fairly low level. Now, one can buy small computers like the Arduino Due with 32-bit processors, 96K of RAM, and 512K of flash memory (I'm ignoring systems like the Raspberry PI as they are full up Linux computer and thus are more complicated). This seemed like a reasonable platform for recreating the early experience.

1.2.1 Why Lisp?

Why not? My first thought was to use some flavor of Tiny BASIC which would have more in common with those early systems. I then realized that Lisp is much easier to parse. Being somewhat lazy and interested in various computer languages, I decided that some form of a “Tiny-Lisp” would be a good idea.

Tiny-Lisp can be thought of as a small subset of Common Lisp, with some extensions of use to embedded systems. Most of the more complex features of Common Lisp are not and probably

never will be available in this Tiny-Lisp. However, one should be able to write code in Tiny-Lisp and have it actually run on a Common Lisp system.

1.2.2 Why Ada?

Again, why not? I have developed an interest in Ada, especially for programming embedded systems. It has features, such as strong typing, which can help to catch errors early, thus saving time debugging. I would not claim to be the world's greatest programmer, so I need all the help that I can get.

Chapter 2

The Language

As a “Tiny-Lisp”, some (many) of the features of Common Lisp are not available. Some of the lacks may be temporary while others will be permanent, and some may be added by the host program.

2.1 User Interface

The interpreter reads text from an input device, parses it, and and executes it. The function used to read the input must match the signature for `Ada.Text_IO.Get_Line()` and this will probably be used if that is available. On an embedded system without `Ada.Text_IO`, the user must provide a suitable function.

Comments

A comment starts with a semicolon character, “;”, and extends to the end of the line. Any text in a comment is ignore by the interpreter.

Continuation

If a list isn’t closed (number of open parentheses matches the number of close parentheses) by the end of the line, the interpreter will ask for more text. This will continue until the list is closed.

2.2 Optimization

None. Some could possibly be added, but right now the focus has been on getting things to work correctly.

2.3 Syntax

2.3.1 Special Characters

There are only a few characters with special significance. Parenthesis, “(” and “)”, are used for delimiting lists. Quotation marks, “”” are used for delimiting strings. The apostrophe “ ’ ” is used

for quoting symbols or lists. The semicolon, “;”, indicates a comment. The pound sign (octothorp) “#” is used to indicate certain special processing. Spaces are used to separate elements in a list. That’s about it. However, it’s probably best to avoid most symbol characters since some more special characters may be added. A good rule of thumb would be to avoid any special characters that are used by Common Lisp.

The language is case insensitive thus, `CAR`, `car`, `cAr`, etc all are considered identical by the language.

2.3.2 Reserved Words

There are almost none. `T` and `NIL` refer to the boolean true and false values, and you can’t define a symbol that it already used for a builtin or special operation. However, even the builtin and special operations are not, strictly speaking, reserved words. Their names are strings that are added to the symbol table during program initialization. They can easily be changed (say to translate into a different language) and the interpreter recompiled.

2.3.3 Examples

The basic syntax for languages in the Lisp family is very simple. Everything is a list of elements, where each element may also be a list. Elements are separated by spaces and the list is contained in parentheses. Here is a simple list:

```
(+ 1 2 3)
```

The first element in the list is the symbol “+”. The following elements are “1”, “2”, and “3”. The “+” symbol is the addition operation and adds the following integers together. Thus, the example would return the integer “6”.

A more complicated example:

```
(+ (* 2 3) (* 4 5))
```

This is equivalent to $2 * 3 + 4 * 5$. Breaking this down, the first element of the outside list is “+”. The second element is the list `(* 2 3)` and the third element is the list `(* 4 5)`. Since “*” is the symbol for the multiplication operation, this returns a value of 26.

A final example:

```
(print "Hello _World!")
```

This list consists of only two elements. The first is the symbol `print`. The second is the string “Hello World!”. With strings, everything from the starting quotation mark to the next quotation mark is part of the string. This means that you can’t have a string that contains a quotation mark (at some point, a work-around may be available).

2.4 Symbols and Variables

Elements that are not numbers, strings, or lists are symbols or variables. In determining what the element represents, the search order is:

1. Boolean literals are checked first.

2. Builtin or Special symbols are checked next.
3. Variables in the most recent stack frame.
4. Variables in older stack frames.
5. Variable symbols are checked last. These can be considered to be global variables.

All symbols share the same namespace. This makes this Tiny-Lisp a LISP-1 (for those who are interested in such things). It is possible that this will change at some point.

Another thing to be aware of is that if a function is defined within a function definition or local block, the inner definition may reference locals or parameters in the outer blocks. In Common Lisp, this creates a closure where the variables remain accessible. This does not work in Tiny-Lisp and may cause an error when the function is called. It is best to define functions at the top level for now. For example, consider the following:

```
(let ((a 10)) (defun test (b) (print "Sum is " (+ a b)) (terpri))
  (test 5))
(test 6)
(let ((a 20)) (test 7))
(let ((b 30)) (test 8))
```

The first call (test 5) produces "Sum is 15". The second (test 6) and fourth (test 8) calls produce an error. The third call (test 7) produces "Sum is 27".

2.5 Operations

A limited number of operations are defined. Note that this list will probably be expanded.

2.5.1 Normal Forms vs Special Forms

A number of normal forms are defined. The main difference between normal forms and special forms is that all active arguments for a normal form are evaluated. Thus:

```
(* (+ 1 2) (+ 3 4))
;
; Versus
;
; (if (> 1 2) (+ 1 2) (+ 3 4))
```

"*" is a normal operation and both (+ 1 2) and (+ 3 4) are evaluated before "*" is evaluated. If is a special form so first (> 1 2) is evaluated, then depending on whether the result is T or NIL, either (+ 1 2) or (+ 3 4) is evaluated. For a simple example like this, it doesn't really matter, but if the operations have other effects, such as:

```
(if (> 1 2) (print "Greater") (print "Not greater"))
```

will only print "Not greater".

2.5.2 Arithmetic Operations

Four arithmetic operations are defined for operation on integers. The operations are addition, subtraction, multiplication, and division. For example:

```
(+ 1 2 3 4)
(- 1 2 3 4)
(* 1 2 3 4)
(/ 1 2 3 4)
```

These operations work on a list of one or more parameters, with the operation inserted between the parameters. Thus `(+ 1 2 3 4)` computes as $1 + 2 + 3 + 4$. The return value for each of these operations is an integer value.

Note that division by zero is not checked. If this occurs, an Ada exception will be thrown. In some cases, this might be useful.

2.5.3 Boolean Operations

Three basic boolean operations are provided. These work on either boolean or integer variables.

```
(not NIL)
(and 1 5 7)
(or 1 2 4)
```

The **not** operation operates on a single parameter. If the parameter is boolean, the return value is the inverse of the parameter ($NIL \rightarrow T$, $T \rightarrow NIL$). If the parameter is integer, the individual bits of the integer are inverted and the resulting value returned.

The **and** and **or** operations operate on either booleans or integers as long as they are not mixed. These perform the logical **and** and **or** operations. Both of these operations short circuit. As soon as the result is T or -1 or **or** NIL or 0 for **and**, processing additional parameters will not change the result so evaluation of parameters stops and the result is returned.

2.5.4 Character Operations

The normal comparison operations work on characters. There are also some operations defined to operate on characters.

```
(char-downcase #\A)
(char-int #\B)
(char-upcase #\c)
(int-char 65)
```

The **char-int** and **int-char** operations convert between characters and their integer codes. Given an integer in the range 0-255, **int-char** returns the corresponding character value. Given a character value, the function **char-int** returns the corresponding integer (usually the ASCII code).

The **char-downcase** and **char-upcase** operations convert characters between upper and lower case. Non-alphabetic characters are not changed.

2.5.5 Comparison Operations

Four comparison operations are defined for integers, strings, and booleans. Note that this is different from Common Lisp which has separate operations defined for different types. The operations are equals, not equals, greater than, and less than. Equality and not equality is also defined for quoted symbols. For example:

```
(= 1 2)
(/= 1 2)
(< 1 2)
(> 1 2)
```

These operations work on two parameters of the same type. The return value of each of these operations is a boolean.

2.5.6 Control Flow

A couple of control flow special forms are available. More will probably be added.

```
(if (> 1 2) (print "True") (print "False"))
(dowhile (> 1 2) (print "Forever") (terpri))
(dotimes (n 5 10) (print "This is printed 5 times") (terpri))
```

The **if** form has two or three parameters. The first parameter is a condition. If the condition evaluates to **T**, then the second parameter is evaluated. If the condition evaluates to **NIL**, then the third parameter, if present, is evaluated.

The **dowhile** form has two parameters. The first is a condition. The second is a list of operations to be evaluated. The second parameter is evaluated as long as the condition evaluates to **T**.

The **dotimes** form also has two parameters. The first is a list with two or three elements. The first element is the name of the local variable used as a loop counter. The second element is a positive integer giving the number of times to loop. The third is a value to return at the end of the loop. If the return value is not provided, **NIL** is returned. The second parameter is a list of operations to be evaluated.

2.5.7 Debugging

Some additional operations are provided for debugging purposes. These control the display of some debugging information.

```
(dump)
(msg T)
(msg NIL)
(reset)
```

The **dump** operation prints the contents of the cons, symbol, and string tables. The **msg** operation turns the display of debugging information on and off. These are helpful when trying to debug the interpreter and should not be necessary during normal operation.

The **reset** operation is intended to reset the interpreter to an initial state. Currently, it just calls the **init()** function. It needs to go through the symbol table and remove everything that's not a **builtin** and clear out the cons table. Do not use until this is fixed.

2.5.8 Functions

```
(defun fib (n)
  (if (< n 2)
      1
      (+ (fib (- n 2)) (fib (- n 1)))))
(lambda (a b) (+ a b))
```

the **defun** form is used to create a user defined function. The first parameter is a symbol for the function name. The second parameter is a list of the parameters for the function. If the function has no parameters, the empty list “()” is used. Following this is a list of statements for the function. The function returns the value from the last statement to return a value.

The **lambda** form returns a user defined function. This function can be assigned to a variable or passed as a parameter to another function.

2.5.9 Input/Output

As this Lisp may run on systems without filesystems, only a few operations are provided for input and output. These are:

```
(print "Strings_" 1 2 N)
(fresh-line)
(read-line)
(terpri)
```

The **print** form prints the list of objects to the standard output. No newline is added to the end. It returns *NIL_ELEM*.

The **fresh-line** prints a newline to the standard output if the output is not already at the start of a line. It returns *NIL_ELEM*.

The **read-line** reads a line of text from the standard input, terminated by a newline. It returns the text as a string without the newline.

The **terpri** prints a newline to the standard output. It returns *NIL_ELEM*.

2.5.10 List Operations

Basic list operations are provided.

```
(car (1 2 3 4))
(cdr (1 2 3 4))
(cons 1 (cons 2 ()))
(quote (+ 1 2) 3 4 (* 5 6 7 8))
(list (+ 1 2) 3 4 (* 5 6 7 8))
```

Each of **car** and **cdr** take one parameter that should be a list. **Car** returns the first item in the list. This item may be a single element or it may be a list. **Cdr** returns the remainder of the list.

The **cons** operation creates a *cons* cell and sets the *car* field to the first parameter and the *cdr* to the second parameter. This exposes a subtle difference between Tiny-Lisp and Common Lisp. In Tiny-Lisp, *NIL* is a constant of boolean type, while in Common Lisp, it also represents an empty list. Thus **(cons 1 NIL)** produce slightly different results, **(1 . NIL)** for Tiny-Lisp or

(1) for Common Lisp. If you wish to produce the Common Lisp results, where the *car* points to a value and the *cdr* is an empty pointer, you can use `(cons 1 ())` or `(cons 1)`. The former is preferred as it is compatible with Common Lisp.

The `list` operation returns its parameters as a list after evaluating each of them. This is similar to `quote` except that `quote` does not evaluate the parameters. Thus `(quote (+ 1 2) 3 4 (* 5 6 7 8))` returns `((+ 1 2) 3 4 (* 5 6 7 8))`, while `(list (+ 1 2) 3 4 (* 5 6 7 8))` returns `(3 3 4 1680)`.

The `quote` operation returns its parameters as a list without evaluating any of them. In many cases this is not needed since if the first item in a list is not a symbol representing an operation or user defined function, the list simply evaluates to itself. At some point, this may change to be more compatible with Common Lisp.

2.5.11 Memory Access

Here be dragons! Use at your own risk. These operations are intended for use on embedded systems to access memory mapped peripheral devices. Access to a memory map is essential so that you know which locations to access.

```
(peek8 #x400E0940)
(peek16 #x400E0940)
(peek32 #x400E0940)
(poke8 #x100 5)
(poke16 #x110 10)
(poke32 #x1000 32)
```

The `peek` operations read 8, 16, or 32 bits from the specified memory location. Depending on the hardware, there may be memory alignment requirements, or certain operations will only work on some addresses. For example, the bytes of the Chip ID (CHIPID_CIDR) register on the SAM3X8E works using `peek8`, but hangs when using `peek16` or `peek32`. The returned value is the contents of memory at the specified location.

The `poke` operations write a 8, 16, or 32 bit value to the specified memory location. This is even more dangerous than the `peek` operations. ***You have been warned!*** The return value is the value written to the memory location.

2.5.12 Predicates

A wide variety of predicates are provided. These mostly match the ones in Common Lisp. Note that some of these will always return *NIL* due to missing features. There may also be some differences in corner cases due to implementation differences between Common Lisp and Tiny-Lisp.

```
;
; The following will always return NIL as the data types or features
; are not implemented.
;
(arrayp (1 3 5))
(bit-vector-p (1 2 3))
(complexp +)
(floatp 3)
```

```

(vectorp (1 2 3))
(rationalp "Hello")
(realp 4)
(simple-vector-p print)
(simple-bit-vector-p #xF0F0F0F)
(packagep "package")
(vectorp (1 2 3))
;
;  The following will return NIL or T depending on the parameter.
;
(atomp 1)
(characterp #\A)
(compiled-function-p print)
(consp (1 2 3))
(functionp functionp)
(integerp 3)
(listp (2 4 6))
(numberp 4)
(nullp ())
(simple-string-p "Hello")
(stringp "Hello")
(symbolp car)

```

Some corner cases to watch out for are:

1. Tiny-Lisp does not treat `()` and `NIL` exactly the same so `nullp` may not always do what it does in Common Lisp.
2. Tiny-Lisp does not have arrays or vectors. Strings are managed as linked lists in a separate allocation pool. Thus `stringp` and `simple-string-p` are treated the same and return `T` for any string and `NIL` for anything else.
3. Some of these operations evaluate the parameter to get a value to check and some do not. It's best not to get too creative with them.

2.5.13 String Related Operations

These operations are related to strings, but may have wider scope.

```

(length "Hello, this is a test")
(length (list 1 2 3 4 5))
(char "This is a test string" 5)
(parse-integer "42")
(string-downcase "HELLO")
(string-upcase "hello")
(subseq "This is a test of a subsequence" 5 10)

```

The `length` operation works on all types. For strings, it returns the number of characters in the string. For lists, it returns the number of elements in a list. For integers, characters, and booleans, it returns 1. For an empty list, it returns 0.

The **char** operation returns a specific character in a string, where the first character is character number 0.

The **parse-integer** operation parses the passed string as an integer. Positive and negative decimal integers are supported. Parsing ends when a non-decimal character is encountered.

The **string-downcase** and **string-upcase** operations make a copy of the passed string and convert it to all upper or all lower case. The original string is unchanged.

The **subseq** operation returns a substring of the original string. The first parameter is the string. The second parameter is the starting character (0 based). The third parameter is optional. If present, it is the index (not length of the substring) of the first character not part of the substring. If absent, the substring extends to the end of the original string.

2.5.14 Symbol Related Operations

Some operations use a quoted symbol to indicate what type of operation should be performed or what type of date should be returned. These thus require a bit more description than some of the other operations.

```
(coerce t 'integer)
(concatenate 'string "First_string," "second_string,"
  "and_finally_the_third_string.")
```

The **coerce** operation is used to convert data of one type to another. The current supported conversions are:

- Boolean \rightarrow Integer
- Boolean \rightarrow String
- Character \rightarrow String
- Integer \rightarrow Boolean

Converting a type to itself is supported, but probably isn't very useful. Also of note is that coercing a string to a string returns a string object that points to the original string data structure, not a copy.

The **concatenate** operation works on both strings and lists. It constructs a new list or string that is the concatenation of the parameters. Note that in the case of a list, elements that are lists or strings are not copied. Only the references are copied.

2.5.15 Variables

Both global and local variables are supported.

```
(setq variable 1)
(let (var1 (var2 2) (var3))
  (print "var1_is_" var1 "_var2_is_" var2 "var3_is_" var3)
  (terpri))
```

The **setq** form sets a value for a symbol or stack variable. If a symbol and an active stack variable have the same name, the stack variable will be used. The first parameter is the symbol

and the second parameter is the value. If the symbol does not yet exist, it is created. Symbols that already exist as builtin or special can't be used for values. The second parameter is evaluated to return the value.

The **let** form creates local variables on the stack and an environment for other statements that use them. Variables can have an optional initial value. If no initial value is provided, the variable is set to *NIL*. The value returned from the **let** form is the value of the last statement executed.

2.5.16 Other

There are a few operations that do things that can't be easily categorized.

```
(exit)  
(sleep 1000)
```

The **exit** operation just exits the interpreter. It should mainly be used from the command line. It may cause problems in some cases if used in a function.

The **sleep** operation suspends program execution for the specified number of milliseconds. This is different from Common Lisp, where the parameter is a float in units of seconds. Since Tiny-Lisp is integer only, this doesn't work well, thus the difference.

2.6 Data Types

A limited selection of data types is provided. Think of the old Applesoft Integer BASIC.

2.6.1 Integer

This is a 32 bit signed integer. Integer literals can be given as either signed decimal integers, with a minus sign, “-”, indicating negative numbers. This is just as one would expect, however don't use a plus sign, “+”, to indicate positive numbers. Integers can also be expressed as unsigned hexadecimal numbers by preceding the number by “#x”.

2.6.2 Characters

Character literals are introduced by preceding the literal by “#\”. The following character is the character used, with some exceptions. The end of a line is always the end of a line, so this cannot be used to create a character containing a newline. If the first character is alphabetic and is followed by further alphabetic characters, it is interpreted as a character name. The defined character names are:

- Space
- Newline
- Tab
- Page
- Rubout

- Linefeed
- Return
- Backspace

Thus, the correct way to create a character containing a newline is “#\newline”. Note that the character names are case insensitive.

2.6.3 String

Strings are stored in linked lists of 8-bit characters/bytes. Each node in the list can hold 16 (adjustable by a parameter) bytes. Unicode is not currently supported.

2.6.4 Boolean

The Boolean values *NIL* and *T* correspond to *True* and *False*. An empty list “()” is also interpreted as *NIL*.

2.6.5 List

The list is the basic complex data type. A list element has two slots (historically called *car* and *cdr*). Typically the *car* slot contains a data value and the *cdr* slot contains a pointer to the next list element. The end of a list is indicated by a *NIL* value in the *cdr* slot.

Chapter 3

Operation Reference

This is an alphabetical list of all the operations.

3.1 Template

This is the template for each operation.

3.1.1 Inputs

The inputs are listed here.

3.1.2 Output

Any output is listed here.

3.1.3 Example

An example of the operation is listed here.

3.1.4 Description

This describes the operation. In many cases, it will be fairly simple.

3.1.5 Common Lisp Compatibility

This subsection discusses compatibility with Common Lisp. Usually, this will be a subset of Common Lisp. In some cases, it may be a superset. For example the comparison operators work on more types than Common Lisp supports.

3.2 +

Addition

3.2.1 Inputs

Any number of `integers`.

3.2.2 Output

An `integer` representing the sum of the inputs.

3.2.3 Example

```
(+ 1 2 3)
```

Returns the value 6.

3.2.4 Description

This operation adds a series of `integers`. Note that there is a possibility for integer overflow.

3.2.5 Common Lisp Compatibility

This is a subset of Common Lisp in that it only works on `integers`.

3.3 -

Subtraction

3.3.1 Inputs

Any number of `integers`.

3.3.2 Output

An `integer` representing the difference of the inputs. Note that there is a possibility for integer overflow.

3.3.3 Example

```
(- 1 2 3)
```

Returns the value -4.

3.3.4 Description

This operation subtracts a series of `integers`. This is done by starting with the first value, then subtracting the second value (if any). The next value is subtracted from the result.

3.3.5 Common Lisp Compatibility

This is a subset of Common Lisp in that it only works on `integers`.

3.4 *

Multiplication

3.4.1 Inputs

Any number of `integers`.

3.4.2 Output

An `integer` representing the product of the inputs. Note that there is a possibility for integer overflow.

3.4.3 Example

```
(* 1 2 3)
```

Returns the value 6.

3.4.4 Description

This operation multiplies a series of `integers`.

3.4.5 Common Lisp Compatibility

This is a subset of Common Lisp in that it only works on `integers`.

3.5 /

Division

3.5.1 Inputs

Any number of `integers`.

3.5.2 Output

An `integer` representing the quotient of the inputs. Division by zero is not checked and will cause an exception.

3.5.3 Example

```
(/ 1 2 3)
```

Returns the value 0.

3.5.4 Description

This operation divides a series of `integers`. This is done by starting with the first value, then dividing by the second value (if any). The result is then divided by the next value, and so on.

3.5.5 Common Lisp Compatibility

This is a subset of Common Lisp in that it only works on `integers`.

3.6 =

Equals

3.6.1 Inputs

Compares two values of the same type.

3.6.2 Output

T if the values are equal, otherwise *NIL*.

3.6.3 Example

```
(= 1 2)
```

Returns the value *NIL*.

3.6.4 Description

This operation compares two values of the same type for equality.

3.6.5 Common Lisp Compatibility

This operation works on `integers`, `booleans`, `strings`, and quoted symbols.

3.7 /=

Not-equals

3.7.1 Inputs

Compares two values of the same type.

3.7.2 Output

T if the values are not equal, otherwise *NIL*.

3.7.3 Example

(= 1 2)

Returns the value *NIL*.

3.7.4 Description

This operation compares two values of the same type for not equality.

3.7.5 Common Lisp Compatibility

This operation works on **integers**, **booleans**, **strings**, and quoted **symbols**.

3.8 <

Less Than

3.8.1 Inputs

Compares two values of the same type.

3.8.2 Output

T if the first value is less than the second value, otherwise *NIL*.

3.8.3 Example

(< 1 2)

Returns the value *T*.

3.8.4 Description

This operation compares two values of the same type for less than.

3.8.5 Common Lisp Compatibility

This operation works on **integers**, **booleans**, and **strings**.

3.9 >

Greater Than

3.9.1 Inputs

Compares two values of the same type.

3.9.2 Output

T if the first value is greater than the second value, otherwise *NIL*.

3.9.3 Example

```
(> 1 2)
```

Returns the value *NIL*.

3.9.4 Description

This operation compares two values of the same type for greater than.

3.9.5 Common Lisp Compatibility

This operation works on *integers*, *booleans*, and *strings*.

3.10 and

Logical or bitwise *and*.

3.10.1 Inputs

Performs the logical or bitwise *and* on values of the same type.

3.10.2 Output

If the input parameters are *boolean* then the output is *boolean*. If the input parameters are *integer*, the output is *integer*.

3.10.3 Example

```
(and 1 3 4)
```

Returns the value 1.

3.10.4 Description

If the two parameters are *boolean*, the result is the logical and of the parameters. If the two parameters are *integer*, then the result is the bitwise and of the parameters. Processing of parameters stop when the result is either *NIL* of *boolean* values, or 0 (zero) for *integer* values.

3.10.5 Common Lisp Compatibility

This operation performs a bitwise *and* for integers. This is probably more useful for embedded systems.

3.11 arrayp

Is parameter an **array**?

3.11.1 Inputs

A single value. Any additional values are ignored..

3.11.2 Output

NIL.

3.11.3 Example

```
(arrayp 1 2 3)
```

Returns the value *NIL*.

3.11.4 Description

Since **arrays** are not a supported datatype, this always returns *NIL*.

3.11.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.12 atomp

Is parameter an atom?

3.12.1 Inputs

A single value. Any additional values are ignored..

3.12.2 Output

T or *NIL*

3.12.3 Example

```
(atomp 1 2 3)
```

Returns the value *T*.

3.12.4 Description

Returns *T* if the first value is an atom. Returns *NIL* otherwise. Since the only non-atom datatype supported is a list, this really just checks if the value is a list.

3.12.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.13 bit-vector-p

Is parameter a `bit vector`?

3.13.1 Inputs

A single value. Any additional values are ignored.

3.13.2 Output

NIL.

3.13.3 Example

```
(bit-vector-p 1 2 3)
```

Returns the value *NIL*.

3.13.4 Description

Since `bit vectors` are not a supported datatype, this always returns *NIL*.

3.13.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.14 car

Returns the first element of a list

3.14.1 Inputs

If the first value is a list, return the first value of that. Otherwise return the first value.

3.14.2 Output

The first value of a list.

3.14.3 Example

```
(car 1 2 3)
```

Returns the value 1.

3.14.4 Description

Returns the first value of a list. If the first value passed is a list, then return the first value of that. Otherwise the list of parameters is treated as a list and the first value is returned.

3.14.5 Common Lisp Compatibility

If multiple parameters are passed, the first one is returned. Compatible with Common Lisp if only one parameter is passed.

3.15 cdr

Returns all but the first element of a list

3.15.1 Inputs

If the first value is a list, return all but the first value of that. Otherwise return all but the first value.

3.15.2 Output

All but the first value of a list.

3.15.3 Example

```
(cdr 1 2 3)
```

Returns the value (2 3).

3.15.4 Description

Returns all but the first value of a list. If the first value passed is a list, then return all but the first value of that. Otherwise the list of parameters is treated as a list and all but the first value is returned.

3.15.5 Common Lisp Compatibility

If multiple parameters are passed, all but the first one is returned. Compatible with Common Lisp if only one parameter is passed.

3.16 char

Returns a specified character in a string.

3.16.1 Inputs

A string and an integer.

3.16.2 Output

A character.

3.16.3 Example

```
(char "This is a string" 5)
```

Returns the character “i”.

3.16.4 Description

Returns the specified character in a string where the first character is number 0.

3.16.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.17 char-downcase

Converts a character to lower case.

3.17.1 Inputs

A character.

3.17.2 Output

A character.

3.17.3 Example

```
(char-downcase #\A)
```

Returns the character “a”.

3.17.4 Description

If the character passed is uppercase, convert it to lowercase and return it. Otherwise return the character unchanged.

3.17.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.18 char-int

Returns the integer ASCII value of a character.

3.18.1 Inputs

A character.

3.18.2 Output

A character.

3.18.3 Example

```
(char-int #\A)
```

Returns the integer 65.

3.18.4 Description

This returns the integer ASCII (you might be able to find some odd systems where this is not true) code for the provided character. Unicode is not currently supported.

3.18.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.19 char-upcase

Converts a character to upper case.

3.19.1 Inputs

A character.

3.19.2 Output

A character.

3.19.3 Example

```
(char-upcase #\a)
```

Returns the character “A”.

3.19.4 Description

If the character passed is lowercase, convert it to uppercase and return it. Otherwise return the character unchanged.

3.19.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.20 characterp

Is parameter a `character`?

3.20.1 Inputs

A single value. Any additional values are ignored.

3.20.2 Output

A boolean value

3.20.3 Example

```
(characterp 1)
```

Returns the value *NIL*.

3.20.4 Description

Returns *T* if the first value is a character. Otherwise it returns *NIL*. Note that a string containing a single character is not the same as a character.

3.20.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.21 coerce

Converts a value of one type to another type

3.21.1 Inputs

Two values. The first value is the item to be converted. The second value is a quoted symbol representing the result type.

3.21.2 Output

A value of the desired type.

3.21.3 Example

`(coerce NIL 'integer)`

Returns the integer value 0.

3.21.4 Description

The result is a representation of the first value in the desired type.

3.21.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

Only the following coercions are supported:

- character \rightarrow string
- boolean \rightarrow string
- boolean \rightarrow integer ($NIL \rightarrow 0$, $T \rightarrow 1$).
- integer \rightarrow boolean ($0 \rightarrow NIL$, $\neq 0 \rightarrow T$)

3.22 compiled-function-p

Is parameter a compiled function?

3.22.1 Inputs

A single value. Any additional values are ignored.

3.22.2 Output

A boolean value

3.22.3 Example

`(compiled-function-p print)`

Returns the value T .

3.22.4 Description

Returns T if the first value is a compiled function. Otherwise it returns NIL . Tiny-Lisp() considers the builtin intrinsic functions to be compiled. User defined functions are not compiled..

3.22.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.23 complexp

Is parameter a `complex` number?

3.23.1 Inputs

A single value. Any additional values are ignored.

3.23.2 Output

NIL.

3.23.3 Example

```
(complexp 1 2 3)
```

Returns the value *NIL*.

3.23.4 Description

Since `complex` numbers are not a supported datatype, this always returns *NIL*.

3.23.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.24 concatenate

Concatenates strings or lists.

3.24.1 Inputs

A quoted symbol (either *LIST* or *STRING*) followed by either lists or strings.

3.24.2 Output

A list or string consisting of the concatenation of the lists or strings

3.24.3 Example

```
(concatenate 'string "One_" "Two")
```

Returns the string "One Two".

3.24.4 Description

Concatenates either string or lists. The first parameter is a symbol that specifies what to concatenate. The following parameters must be of the appropriate type.

3.24.5 Common Lisp Compatibility

This is probably a subset of the Common Lisp function. Normal cases will operate the same, but error handling is different.

3.25 cons

Combines elements into a list.

3.25.1 Inputs

One or two values

3.25.2 Output

A list consisting of the provided inputs.

3.25.3 Example

```
(cons 1 2)
```

Returns the list (1 . 2).

3.25.4 Description

The `cons` operation creates a *cons* cell and sets the *car* field to the first parameter and the *cdr* to the second parameter..

3.25.5 Common Lisp Compatibility

There is a subtle difference between Tiny-Lisp and Common Lisp. In Tiny-Lisp, *NIL* is a constant of boolean type, while in Common Lisp, it also represents an empty list. Thus `(cons 1 NIL)` produce slightly different results, (1 . NIL) for Tiny-Lisp or (1) for Common Lisp. If you wish to produce the Common Lisp results, where the *car* points to a value and the *cdr* is an empty pointer, you can use `(cons 1 ())` or `(cons 1)`. The former is preferred as it is compatible with Common Lisp.

3.26 consp

Is parameter a cons?

3.26.1 Inputs

A single value. Any additional values are ignored.

3.26.2 Output

A boolean.

3.26.3 Example

```
(consp (1 2 3))
```

Returns the value *T*.

3.26.4 Description

If the supplied parameter is a **cons** (a list), return *T*, otherwise return *NIL*.

3.26.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.27 defun

Defines a function.

3.27.1 Inputs

Three or more values. The first is a symbol that becomes the function's name. The second is a list of parameters for the function. The remaining values are the code for the function

3.27.2 Output

NIL.

3.27.3 Example

```
(defun hello (name) (print "Hello_" name))
```

Returns the value *NIL*.

3.27.4 Description

This creates a user defined function.

3.27.5 Common Lisp Compatibility

This is more or less a subset of Common Lisp, except that there are probably many corner cases where things don't quite match..

3.28 dowhile

Repeats a series of statements while a condition is *T*.

3.28.1 Inputs

Two or more values. The first value is evaluated as the condition, the remaining values are the statements to be executed while the condition is true.

3.28.2 Output

A value.

3.28.3 Example

```
(dowhile (> (- max min) 1)
  (setq mid (/ (+ min max) 2))
  (if (> mid (/ n mid))
    (setq max mid)
    (setq min mid))
  (+ 0 min))
```

Returns the value of the last statement in the loop, `min`

3.28.4 Description

The condition is evaluated on each pass through the loop. If the condition evaluates to *T*, the rest of the statements are executed. If the condition evaluates to *NIL*, the loop is exited. Thus, if the first time the condition is evaluated it returns *NIL*, the statements in the loop are never executed.

3.28.5 Common Lisp Compatibility

This doesn't appear to exist in Common Lisp. It is similar to the Common Lisp `do` loop, except that the condition comes first.

3.29 dotimes

Repeats a series of statements a specific number of times.

3.29.1 Inputs

Two or more values. The first value is a list containing a local variable and the numb, the remaining values are the statements to be executed the specified number of times.

3.29.2 Output

A constant *NIL*.

3.29.3 Example

```
(setq sum 0)
(dotimes (x 10)
  (print "The sum is " sum)
  (terpri)
  (setq sum (+ sum x)))
```

Returns the constant *NIL*.

3.29.4 Description

On each pass through the loop, the local variable is set to the next value in the range 0 to the loop limit. The supplied statements are evaluated. It is not recommended to change the value of the local variable in the body of the loop.

3.29.5 Common Lisp Compatibility

The result-form, declarations, and tags are not supported.

3.30 dump

Prints out some internal tables.

3.30.1 Inputs

None.

3.30.2 Output

A value.

3.30.3 Example

```
(dump)
```

Returns the constant *NIL*.

3.30.4 Description

This is intended for debugging purposes. It prints the contents of the cons, symbol, and string tables.

3.30.5 Common Lisp Compatibility

This operation does not exist in Common Lisp.

3.31 `exit`

Exits the Tiny-Lisp interpreter.

3.31.1 Inputs

None.

3.31.2 Output

A value.

3.31.3 Example

```
(exit)
```

No value can be returned as the interpreter exits..

3.31.4 Description

This is a way to exit the Tiny-Lisp interpreter.

3.31.5 Common Lisp Compatibility

This operation does not exist in Common Lisp, but some implementations (i.e. SBCL) do have it.

3.32 `floatp`

Is parameter a `floating point number`?

3.32.1 Inputs

A single value. Any additional values are ignored.

3.32.2 Output

NIL.

3.32.3 Example

```
(floatp 1 2 3)
```

Returns the value *NIL*.

3.32.4 Description

Since `floating point numbers` are not a supported datatype, this always returns *NIL*.

3.32.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.33 *fresh-line*

Prints a newline if not already at the start of a line.

3.33.1 Inputs

None, any values are ignored.

3.33.2 Output

NIL.

3.33.3 Example

(*fresh-line*)

Returns the value *NIL*.

3.33.4 Description

Checks if the internal first character flag is set. If not, prints a newline, otherwise does nothing.

3.33.5 Common Lisp Compatibility

There is no optional output-stream parameter as Tiny-Lisp only has one output stream. It also always returns *NIL*.

3.34 *functionp*

Is parameter a function?

3.34.1 Inputs

A single value. Any additional values are ignored.

3.34.2 Output

NIL.

3.34.3 Example

```
(functionp 1 2 3)
```

Returns the value *NIL*.

3.34.4 Description

Returns *T* if the value is a builtin function, a user defined function, or a lambda function.

3.34.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.35 if

Conditionally executes a statement.

3.35.1 Inputs

Two or three parameters. The first is a condition. If the condition evaluates to *T*, the second parameter is evaluated. If the condition evaluates to *NIL*, the third parameter, if present, is evaluated.

3.35.2 Output

Returns the value of the parameter evaluated.

3.35.3 Example

```
(if (> 1 2)
    (print "Greater")
    (print "Not_greater"))
```

Prints the string "Not greater".

3.35.4 Description

Evaluates the condition and then depending on the condition, evaluates one of the other parameters. If the third parameter is omitted, this is approximately equivalent to an **IF-THEN** statement in other languages. If the third parameter is present, this is similar to an **IF-THEN-ELSE** statement. The value of the evaluated parameter is returned. If no parameter is evaluated (only two parameters passed and the condition evaluates to *NIL*), then *NIL* is returned.

3.35.5 Common Lisp Compatibility

This seems to be mostly compatible with Common Lisp.

3.36 int-char

Converts an integer to a character where the integer is the ASCII representation of the character. The integer is limited to the range 0-255.

3.36.1 Inputs

A single integer. Any other parameters are ignored.

3.36.2 Output

The character represented by the ASCII code input.

3.36.3 Example

```
(int-char 65)
```

Returns the character 'A'.

3.36.4 Description

This can be used to generate any 8 bit ASCII character.

3.36.5 Common Lisp Compatibility

The operation (int-char) has been removed from Common Lisp. The proper operation to use is `code-char`. Note that Common Lisp also allows a larger range than 0-255 since Unicode is supported.

3.37 integerp

Is the parameter an integer?

3.37.1 Inputs

A single value. Any additional values are ignored.

3.37.2 Output

The value *T* if the parameter is an integer, otherwise *NIL*.

3.37.3 Example

```
(integerp 1 2 3)
```

Returns the value *T*.

3.37.4 Description

This is used to check if a parameter is of integer type or not. Currently the only number type supported is integer so this is equivalent to `numberp` in Tiny-Lisp.

3.37.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.38 `lambda`

Creates a variable record that can be assigned to a variable or passed as a parameter to a function.

3.38.1 Inputs

The first parameter is a list of the parameters for the function. The remaining parameters are the operation for the function.

3.38.2 Output

A variable record pointing to the created function.

3.38.3 Example

```
(setq hello (lambda (name) (print "Hello_" name)))
```

Sets the symbol (or variable depending on context) `hello` to point to the created function.

3.38.4 Description

Creates a function that can be assigned to a variable or passed as a parameter. Note that `(setq var (lambda ...))` is slightly different from `(defun var ...)`. The first creates a variable record and assigns it to `var` while the second directly sets `var` to point to the function. This difference may be removed in future versions.

3.38.5 Common Lisp Compatibility

This is mostly a subset of Common Lisp.

3.39 `length`

Returns the length of an object.

3.39.1 Inputs

The first parameter is a list of the object to measure.

3.39.2 Output

An integer.

3.39.3 Example

```
(length "Hello")
```

Returns the value 5.

3.39.4 Description

Returns the length of an object. For **strings** this is the number of characters in a string. For **lists** this is the number of items in a list not descending into sublists. All other datatypes return a value of 1.

3.39.5 Common Lisp Compatibility

This is mostly compatible with Common Lisp, except that errors are not thrown if the parameter is not a sequence.

3.40 **let**

3.40.1 Inputs

3.40.2 Output

3.40.3 Example

3.40.4 Description

3.40.5 Common Lisp Compatibility

3.41 **list**

3.42 **listp**

3.43 **msg**

3.44 **not**

3.45 **nullp**

3.46 **numberp**

Is the parameter a number?

3.46.1 Inputs

A single value. Any additional values are ignored.

3.46.2 Output

The value *T* if the parameter is a number, otherwise *NIL*.

3.46.3 Example

```
(numberp 1 2 3)
```

Returns the value *T*.

3.46.4 Description

This is used to check if a parameter is of number type or not. Currently the only number type supported is integer so this is equivalent to `integerp` in Tiny-Lisp.

3.46.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.47 or

Logical or bitwise `or`.

3.47.1 Inputs

Performs the logical or bitwise `and` on values of the same type.

3.47.2 Output

If the input parameters are `boolean` then the output is `boolean`. If the input parameters are `integer`, the output is `integer`.

3.47.3 Example

```
(or 1 3 4)
```

Returns the value 7.

3.47.4 Description

If the two parameters are `boolean`, the result is the logical and of the parameters. If the two parameters are `integer`, then the result is the bitwise and of the parameters. Processing of parameters stop when the result is either *NIL* of `boolean` values, or 0 (zero) for `integer` values.

3.47.5 Common Lisp Compatibility

This operation performs a bitwise `or` for integers. This is probably more useful for embedded systems.

3.48 `packagep`

Is parameter a `package`?

3.48.1 Inputs

A single value. Any additional values are ignored.

3.48.2 Output

NIL.

3.48.3 Example

```
(packagep 1 2 3)
```

Returns the value *NIL*.

3.48.4 Description

Since `packages` are not a supported datatype, this always returns *NIL*.

3.48.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.49 `parse-integer`

3.50 `peek8`

3.51 `peek16`

3.52 `peek32`

3.53 `poke8`

3.54 `poke16`

3.55 `poke32`

3.56 `print`

3.57 `quote`

3.58 `rationalp`

Is parameter a `rational` number?

3.58.1 Inputs

A single value. Any additional values are ignored.

3.58.2 Output

NIL.

3.58.3 Example

```
(rationalp 1 2 3)
```

Returns the value *NIL*.

3.58.4 Description

Since `rational` numbers are not a supported datatype, this always returns *NIL*.

3.58.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.59 read-line

3.60 realp

Is parameter a `real number`?

3.60.1 Inputs

A single value. Any additional values are ignored.

3.60.2 Output

NIL.

3.60.3 Example

```
(realp 1 2 3)
```

Returns the value *NIL*.

3.60.4 Description

Since `real numbers` are not a supported datatype, this always returns *NIL*.

3.60.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.61 reset

3.62 setq

3.63 simple-bit-vector-p

Is parameter a `simple bit vector`?

3.63.1 Inputs

A single value. Any additional values are ignored.

3.63.2 Output

NIL.

3.63.3 Example

(`simple-bit-vector-p` 1 2 3)

Returns the value *NIL*.

3.63.4 Description

Since `bit vectors` (simple or otherwise) are not a supported datatype, this always returns *NIL*.

3.63.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.64 `simple-string-p`

3.65 `simple-vector-p`

Is parameter a `simple vector`?

3.65.1 Inputs

A single value. Any additional values are ignored.

3.65.2 Output

NIL.

3.65.3 Example

(`simple-vector-p` 1 2 3)

Returns the value *NIL*.

3.65.4 Description

Since `vectors` (simple or otherwise) are not a supported datatype, this always returns *NIL*.

3.65.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.66 sleep**3.67 string-downcase****3.68 string-upcase****3.69 stringp****3.70 subseq****3.71 symbolp**

Is the parameter a symbol?

3.71.1 Inputs

A single value. Any additional values are ignored.

3.71.2 Output

The value *T* if the parameter is a symbol, otherwise *NIL*.

3.71.3 Example

```
(symbolp 1 2 3)
```

Returns the value *NIL*.

3.71.4 Description

This is used to check if a parameter is a symbol or not.

3.71.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

3.72 terpri

Prints a newline.

3.72.1 Inputs

None

3.72.2 Output

A newline.

3.72.3 Example

```
(terpri)
```

Returns the value *NIL*.

3.72.4 Description

Prints a newline to the output stream.

3.72.5 Common Lisp Compatibility

Tiny-Lisp() has only one output stream so the optional output stream designator is ignored.

3.73 vectorp

Is parameter a **vector**?

3.73.1 Inputs

A single value. Any additional values are ignored.

3.73.2 Output

NIL.

3.73.3 Example

```
(vectorp 1 2 3)
```

Returns the value *NIL*.

3.73.4 Description

Since **vectors** are not a supported datatype, this always returns *NIL*.

3.73.5 Common Lisp Compatibility

This is compatible with Common Lisp, except that no error is thrown with extra parameters. They are just silently ignored.

Chapter 4

Internals

As the interpreter is under active development, this section is subject to change without notice.

4.1 Operation

Processing consists of four phases.

4.1.1 Read

Text is read from the input stream and passed to the parser.

4.1.2 Parse

The parse phase examines the text and converts it into the internal representation of a list. If the list is not complete (parentheses are unbalanced), more text is requested until the list can be completed. Parsing of sub-lists is done by recursively calling the parser.

4.1.3 Evaluate

The list from the parse phase is evaluated. If the first in the list is not a symbol that represents a function, the list is simply returned as is. Otherwise the function is evaluated and the returned value is passed to the print phase. Evaluation of sub-lists is done recursively. Note that, depending on the function, not all sub-lists are evaluated.

4.1.4 Print

The value returned from the evaluation is printed. Once this is done, the read phase is reentered and more text requested.

4.2 Data Structures

4.2.1 Elements

The basic data type is the element. It is defined as follows:

```

max_cons : constant Integer := 300;
max_symb : constant Integer := 200;
max_string : constant Integer := 500;
type cons_index is range 0 .. max_cons;
type symb_index is range 0 .. max_symb;
type string_index is range 0 .. max_string;
type ptr_type is (E_CONS, E_ERROR, E_NIL, E_STACK, E_SYMBOL,
                  E_TEMPSYM, E_VALUE);
type element_type(kind : ptr_type := E_NIL) is
  record
    case kind is
      when E_CONS =>
        ps : cons_index;
      when E_ERROR =>
        null;
      when E_NIL =>
        null;
      when E_TEMPSYM =>
        tempsym : string_index;
      when E_SYMBOL =>
        sym : symb_index;
      when E_STACK =>
        st_name : string_index;
        st_offset : stack_index;
      when E_VALUE =>
        v : value;
    end case;
  end record;

```

The different types of elements are:

E_CONS Contains an index into the array of cons cells as described in section 4.2.2. This may eventually go away.

E_ERROR This indicates that some operation has encountered an error of some sort.

E_NIL This represents an empty element.

E_TEMPSYM This contains an index into the *string* table for representing a temporary symbol name. This is used during parsing to represent an item where the type has not yet been determined. It should never appear once parsing is complete.

E_STACK This represents a stack variable. It contains an index into the *string* table for the variable's name and a stack frame offset.

E_SYMBOL This contains an index into the *symbol* table thus representing a symbol as described in section 4.2.3.

E_VALUE This represents a value as described in section 4.2.4. It can contain any of the defined data types. Note that for *V_STRING* or *V_LIST* data types, the value actually contains an index into the *string* or *cons* array.

There is a bit of ambiguity right now about lists. Since recursively defined records aren't possible, elements of type *E_STACK* can't contain an *element_type*. So in order for them to be able to have lists, the *value* type also contains a list pointer. This means that right now, an *element_type* can point to a list either directly by having a kind of *E_CONS*, or by having a kind that contains a *value* with a kind of *V_LIST*. This really should be fixed at some point. On the other hand, one could make the distinction that the kind *E_CONS* represents a list that can be evaluated, while a *value* of kind *V_LIST* is just data.

4.2.2 Cons

Cons elements are used to make lists. A cons cell is defined as

```

type cons is
  record
    ref : Natural;
    car : element_type;
    cdr : element_type;
  end record;

```

4.2.3 Symbols

Symbols are defined as:

```

type symbol_type is (SY_SPECIAL, — A special form that needs
                        — support during parsing
                        SY_BUILTIN, — A normal builtin function
                        SY_LAMBDA, — A user defined function
                        SY_VARIABLE, — A value, not a function
                        SY_EMPTY); — No contents
type execute_function is access function(e : element_type)
  return element_type;
type special_function is access function(e : element_type;
                                           p : phase)
  return element_type;
type symbol(kind : symbol_type := SY_EMPTY) is
  record
    ref : Natural;
    str : string_index;
    case kind is
      when SY_SPECIAL =>
        s : special_function;

```

```

    when SY_BUILTIN =>
        f : execute_function;
    when SY_LAMBDA =>
        ps : cons_index;
    when SY_VARIABLE =>
        pv : element_type;
    when SY_EMPTY =>
        null;
    end case;
end record;

```

SY_BUILTIN vs SY_SPECIAL

Some functions need to be able to access some of their parameters during parsing so that the rest of the parameters can be properly parsed. Usually, but not always, this involves building a stack frame with the parameters so that they will be properly identified during further processing. These functions are passed an extra parameter *p* for phase. The possible values are:

```
type phase is (PH_QUERY, PH_PARSE_BEGIN, PH_PARSE_END, PH_EXECUTE);
```

The phases are:

PH_QUERY Initial call to the function to query the function when it wants to be called again. The function returns an integer value indicating the parameter after which it should be called.

PH_PARSE_BEGIN This is the call after the desired parameter has been parsed. The function can then examine this parameter and make any needed changes.

PH_PARSE_END This is the call at the end of parsing for the function. Usually this just clears the stack frame. It could also be used for things like preprocessing the parameter list.

PH_EXECUTE This is the call for execution where the function performs its normal operation.

4.2.4 Values

The value type represent a (surprise) value. It can be either an atomic type such as integer or boolean, or a more complex type such as a list or a string.

```

type value_type is (V_INTEGER, V_STRING, V_CHARACTER, V_BOOLEAN,
                    V_LIST, V_LAMBDA, V_SYMBOL, V_QSYMBOL, V_NONE);
type int32 is range -(2**31) .. 2**31 - 1
with Size => 32;
type value(kind : value_type := V_INTEGER) is
    record
        case kind is
            when V_INTEGER =>
                i : int32;
            when V_CHARACTER =>
                c : Character;

```

```

when V_STRING =>
    s : string_index;
when V_BOOLEAN =>
    b : Boolean;
when V_LIST =>
    l : cons_index;
when V_LAMBDA =>
    lam : cons_index;
when V_SYMBOL =>
    sym : symb_index;
when V_QSYMBOL =>
    qsym : symb_index;
when V_NONE =>
    null;
end case;
end record;

```

The data types available are:

V_INTEGER is the basic integer numeric type. It is defined as a 32 bit signed integer. Basic math operations can be performed on it and integers can be compared.

V_STRING is the string type. These are unbounded strings. The value structure contains an index into the string fragment array. Details of strings are described in section 4.2.5.

V_CHARACTER will represent a character data type when implemented. It is currently not implemented.

V_BOOLEAN is a boolean data type that can represent false or true. Comparison operations return boolean values and certain functions expect boolean values.

V_LIST is a list data type. It is approximately equal to an element type of *E_CONS* (see section 4.2.2). The value structure contains an index into the cons cell array.

V_LAMBDA is a list data type that is used to represent a user defined function. It is approximately equivalent to the symbol type of *SY_LAMBDA*, except that it can be assigned to stack variables.

V_QSYMBOL is a quoted symbol.

V_SYMBOL is a symbol. This is currently not used and may be deleted.

4.2.5 Strings

Strings are stored as a set of string fragments in a linked list. Thus, the length of a string is limited only by the number of fragments available. Strings are defined as:

```

fragment_len : constant Integer := 16;
type fragment is
    record

```

```

    ref : Natural;
    next : Integer range -1 .. Integer(string_index 'Last);
    len : Integer range 0..fragment_len;
    str : String (1..fragment_len);
end record;

```

4.2.6 Functions

A function is a list that contains two elements. The first element is a list of the function parameters. The second element is a list of the function's statements.

4.2.7 The Stack

A stack is defined for storing function parameters and local variables. The function parameters are used only for user defined functions. Builtin and Special functions are handled within the Ada code directly from the *cons* cells of the function parameter list.

4.2.8 Global Data

4.2.9 Memory Management

Memory management is done by reference counting. When the number of references goes to zero, the item is deallocated. Items in the cons table and the strings table are reference counted.

4.3 Utility Functions

4.4 Embedding

This section covers how to embed the list interpreter in another program. Here is a minimal host program:

```

with Ada.Text_IO;
with bbs.lisp;
with new_line;
—
—  This is a simple shell routine to call the embedded lisp
—  interpreter.
—
procedure Lisp is
begin
  Ada.Text_IO.Put_Line("Tiny_lisp_interpreter_written_in_Ada.");
  bbs.lisp.init(Ada.Text_IO.Put_Line'Access, Ada.Text_IO.Put'Access,
               new_line.New_Line'Access, Ada.Text_IO.Get_Line'Access);
  bbs.lisp.repl;
end Lisp;

```

With `new_line` defined as:

```

—
— The text_io version of newline contains an optional parameter
— indicating the number of lines to skip. The type of this parameter
— is defined in Ada.Text_IO. This makes it awkward to define a
— function prototype that can be used both when Ada.Text_IO is
— available and when it isn't. This is a crude hack to define
— locally a new_line that has no parameters and uses the
— Ada.Text_IO new_line with the default value.
—
package new_line is
    procedure new_line;
end new_line;

with Ada.Text_IO;
package body new_line is

    procedure new_line is
    begin
        Ada.Text_IO.New_Line;
    end;

end new_line;

```

It's fairly simple. Initialize the interpreter and call it. The only wrinkle is the need to define `new_line`. The Ada version has an optional parameter of a type defined in `Ada.Text_IO`. This is a problem when trying to eliminate dependencies on `Ada.Text_IO`. A more complex example of embedding is found in the <https://github.com/BrentSeidel/Ada-Arduino-Due> repository. This repository contains code that runs on an Arduino Due and includes the definition of several Tiny-Lisp operations to access attached hardware.

4.5 Opportunities for Optimizing

No big effort has gone into optimizing the interpreter. Should the need arise, there are a few places where things could be optimized.

4.5.1 Memory Management

If allocation becomes a bottleneck, the free items could be linked together in a list. That way a new item could be picked off the head of the list instead of searching through all the items. This would also require the list to be created at initialization.

4.5.2 Constant expressions

During parsing, it may be possible to recognize some constant expressions and replace them by their result. For example:

`(+ 1 2 3) → 6`