No.
Thứ ngày . .

```
interface Mail {
    void sendMail()
    void log();
}
class mailImple implements Mail {
    @Override
    public void sendMail {
        system.out.println("Pay")

class log implements Mail
    @override
```

Bài 2

```
public interface Shape {
    ~~void draw();~~
}
    double getArea();
    double getPerimeter();
    void draw();

class Rectangle implements Shape {
    private double width
    private double height

    public rectangle(double width, double
    height) {
        this.width = width;
        this.height = height;
```

ClassMate

Được quét bằng CamScanner

No.
Thứ ngày . .

```
    }
    public void setSize(double width, double
    height){
        this.width = width
        this.height = hight;
    }

    @Override
    public double getArea(){
        return width * height;
    }

    @ Override
    public double getPerimeter(){
        Return 2 * (width + height);
    }

    public boolean isSquare(){
        return width = hight;
    }
    @ Override
    public void draw(){
        system.out.print("Drawing Rectangle:
    width" + width + ", height" + height);
    }
}
class circle implements Shape {
    private double radius;

    // Constructor
    public circle(double ~~rad~~ radius)
```


ClassMate
Được quét bằng CamScanner

No.
Thứ ngày . .

```
        this.radius = radius;

        public Circle(double radius) {
            This.radius = radius;
        }
        @Override
        public double getArea() {
            return Math.PI * radius * radius;
        }
        @Override
        public double getPerimeter() {
            return 2* Math.PI * radius;
        }
        @Override
        public void draw() {
            System.out.println("Drawing circle
        }
    }
    public class Main {
        public static void main(String[] args)
        IShape[] shapes = {
            new Rectangle(5, 3),
            new Rectangle(4, 4),
            new Circle(7)
        };
```

ClassMate

Được quét bằng CamScanner

No.
Thứ ngày . .

```
Class Main {
    public static void main (String [] args );
        obj = new C();
        obj : methods A ;
        obj : methods B ;
}

interface Line {
    void draw line ();
}

interface Polygon extends

Ví dụ

public interface Shape {
    void draw ();
}
public interface color {
    String get color ();
}
public class Rectangle implements Shape, color
    @ override
    public void draw () {
        sy
```

ClassMate

Được quét bằng CamScanner

No.

Thứ ngày . .

```
interface Mail {
    void sendMail()
    void log();
}

class mailimple implements Mail {
    @ Override
    public void sendMail() {
        system.out.println("Pay")

class log implements Mail
    @ override
```

Bài 2

```
public interface Shape {
    ~~void draw();~~
}
    double getArea();
    double getPerimeter();
    void draw();

class Rectangle implements Shape {
    private double width
    private double height

    public Rectangle(double width, dou
    height) {
        this.width = width;
        this.height = height;
```

ClassMate

Được quét bằng CamScanner

No.
Thứ ngày . .

Bài 3

```
class MaySanXuat {
    private String tenMaySanXuat;
    private String tenQuocGia;

    public MaySanXuat (String tenMaySanXuat, String
tenQuocGia ){
        this.tenMaySanXuat = tenSanXuat;
        this.tenQuocGia = tenQuocGia;
    }
    publi String getTenMaySanXuat () {
        Return tenMaySanXuat;
    }
    public String getTenQuocGia () {
        return tenQuocGia;
    }

interface PhuongTienDiChuyen {
    String layTenMaySanXuat ();

    default void batDau() {
        System.out.println( layTenMaySanXuat())
    }

    default void tangToc() {
        System.out.println( layTenMaySanXuat
```

ClassMate
Được quét bằng CamScanner