

Product datasheet

Specifications



Single Socket Outlet, Standard Series, 32V, 10A, 2 PIN Polarised, Surface Mount

402/32-WE

Main

Product or component type	Socket-outlet
Product brand	Clipsal
Quantity per set	Set of 1
Cover type	Complete housing

Complementary

Marking	Extra low voltage
Local signalling	Without light indicator
Device mounting	Surface
fixing mode	By screws
Material	Plastic
[In] rated current	15 A
[Ue] rated operational voltage	32 V DC
Network frequency	50 Hz
Depth	28 mm
Diameter	47 mm
fixing center	35...38 mm
Number of poles	1
Colour code	WE

Environment

Standards	AS/NZS 3112 AS 3100 AS 3109 AS/NZS 3122:approval number S/1
-----------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.7 cm
Package 1 Width	4.8 cm
Package 1 Length	4.8 cm
Package 1 Weight	33.0 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.3 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Again



Repack and remanufacture

Recyclability potential, in %	27
End of life manual availability	No need of specific recycling operations
Take-back	No