

The kautools bundle*

Stefan Berthold
stefan.berthold@kau.se

January 24, 2018

Abstract

The kautools bundle provides tools (L^AT_EX style files) for the kauthesis bundle.

Contents

1	Introduction	2
1.1	The kautitle package	2
1.2	The kaumeta package	2
1.3	The kaulist package	2
1.4	The kauclear package	2
1.5	The kauenvironments package	3
1.6	The kauparts package	3
1.7	The kaupaper package	3
1.8	The kaustudies package	3
1.9	The kaulanguage package	3
1.10	The pgfcropmarks package	3
2	Implementation	3
2.1	The kautitle package	3
2.2	The kaumeta package	5
2.3	The kaulist package	6
2.4	The kauclear package	7
2.5	The kauenvironments package	7
2.6	The kauparts package	8
2.7	The kaupaper package	10
2.8	The kaustudies package	13
2.9	The kaulanguage package	14
2.10	The pgfcropmarks package	14

*This document corresponds to kautools v1.15, dated 2014/10/22.

1 Introduction

1.1 The kautitle package

The kautitle package defines an alternative title page using the logo of Karlstad University. Note that this is not an implementation of the Karlstad University Studies title page, i. e., this alternative title page won't be used for your thesis. The logo is available from

<http://www.kau.se/sites/default/files/image/press/kau-logo-tryck.pdf>

and must be available in L^AT_EX's search path before using this package.

At the moment, this package uses a manually installed font called **aun** and it's bold version **aub**. It might not be available on your system, though, and since the font is licensed, I may not distribute it. If you do not possess the font, you have to switch to another one.

Load the package without options. The title page can be created using `\maketitle`. Note that the previous definition of `\maketitle` is not destroyed, but preserved in the macro `\kut@maketitle`. You can use it in your document as follows:

`\maketitle`
`\kut@maketitle`

```
\makeatletter
\kut@maketitle
\makeatother
```

Two fonts are used on the title page and can be changed using the macro `\setkautitlefont`. The argument `\setkautitlefont{}` accepts key-value pairs where keys are **normalfont** and **titlefont** and values are any sequence of L^AT_EX's font commands. For switching to your standard sans-serif font, you should add these lines to your preamble:

```
\setkautitle%
{ normalfont=\sffamily\LARGE
, titlefont=\sffamily\bfseries\Huge }
```

1.2 The kaumeta package

The kaumeta package defines three macros, `\subject`, `\institute`, and `\place`, for providing additional meta data about the document and it's author. This meta data can be used, e. g., on the title page of the document.

1.3 The kaulist package

The kaulist package defines pretty printing macros for lists. For instance, a list "1,2,3" is transformed to "1, 2, and 3".

1.4 The kauclear package

This package replaces the macro `\cleardoublepage`. Empty pages with odd page numbers will not print the page number. Also, the macro `\pagestyle` is redefined. The new behaviour is to store the page style for being able to restore it later on.

1.5 The `kauenvironments` package

This package defines the environments `researchquestions` and `contributions`.

1.6 The `kauparts` package

This package defines a new `\part` macro, `\kaupart`. It is independent of `\part`, but you should decide yourself for one alternative only. The `\kaupart` macro adds a cover page for the new part.

Use the package options `vshift` and `vstep` to adjust the placement of the thumb indices on the cover pages.

`\kaupart` Use `\kaupart[⟨meta⟩]{⟨title⟩}` to create a numbered part with the given `⟨title⟩`. You may use the optional argument `⟨arg⟩` for adding meta data. This includes `body` for typing additional material on the cover page and `label` for creating a label such as usually created by `\label`. In addition, the switch `tocentry` may be set to false, if the macro should not add an entry to the table of contents.

`\kaupart*` The starred version of `\kaupart` works exactly like the unstarred version, but creates an unnumbered part.

1.7 The `kaupaper` package

Yet no description.

1.8 The `kaustudies` package

This package sets the page dimensions so that your document does not need to be scaled for printing. It also chooses Garamond as the standard font.

You can use the package option `tinyfontswitch=false` in order to avoid the switch to sans-serif fonts when using `\tiny`. The switch is recommended by Karlstad University Studies, though, it is rather debatable whether this is necessary when using L^AT_EX and the correct page dimensions.

1.9 The `kaulanguage` package

This package defines a macro for supporting names in English and Swedish depending on the chosen language in `babel`.

1.10 The `pgfcropmarks` package

The package `pgfcropmarks` draws crop marks on A4 paper. This is supposed to be the last step after creating all tables, indices, and glosseries. When the package is loaded, L^AT_EX will not create or update any auxiliary files.

2 Implementation

2.1 The `kautitle` package

No package options are accepted.

```
1 ⟨*title⟩
2 \ProcessOptions\relax
```

Load dependencies.

```
3 \RequirePackage{xkeyval}
4 \RequirePackage{tikz}
5 \RequirePackage{hyphenat}
6 \RequirePackage{kaumeta}
```

\setkautitlefont The macro `\setkautitlefont` allows to choose another than the default font for the title page. The title page has only two different font settings, `titlefont` which is used for the title text and `normalfont` which is used otherwise.

```
7 \definecmdkeys[kut]{pkg}[kut@]{normalfont,titlefont}
8 \setkeys[kut]{pkg}%
9 { normalfont=\fontfamily{aun}\fontsize{18}{21.6}\selectfont\bfseries
10 , titlefont=\fontfamily{aub}\fontsize{28}{33.6}\selectfont }
11 \newcommand\setkautitlefont[1]{\setkeys[kut]{pkg}{#1}}
```

\kut@maketitle Preserve the previous version of `\maketitle`.

```
12 \let\kut@maketitle\maketitle
```

\maketitle The title page will consist of two background images (the Karlstad University logo), title, subject, author, and author's institute. Everything will be shaded except the title.

```
13 \renewcommand\maketitle{%
14   \thispagestyle{empty}
15   \begin{tikzpicture}[remember picture, overlay]%
```

Clipping the title page to the dimensions of the logical page. This is interesting when the physical and the logical page do not have the same dimensions.

```
16   \path (current page.north west) +(-4pt,4pt) node (NW) {};
17   \path (current page.south east) +(4pt,-4pt) node (SE) {};
18   \path (current page.north west) +(-3pt,3pt) node (NWC) {};
19   \path (current page.south east) +(3pt,-3pt) node (SEC) {};
20   \path[clip] (NWC) rectangle (SEC);
```

Background images.

```
21   \path (current page.south west) node[rotate=243.5] {\pgfimage{kau-logo-tryck}};%
22   \path (current page.north east) node[rotate=175] {\pgfimage{kau-logo-tryck}};%
```

Subject in the upper left corner of the page.

```
23   \path (current page.north west) node
24     [shift={{(10pt,-12pt)},anchor=south west,rotate=270
25     ,font=\kut@normalfont\phantom{Xy}}]
26     {\@subject};
```

Institute in the lower right corner of the page.

```
27   \path (current page.south east) node
28     [shift={{(-8pt,6pt)},anchor=north east,rotate=270
29     ,rounded corners,fill=black,text=white,inner sep=8pt
30     ,font=\kut@normalfont\phantom{Xy}}]
31     {\@shortinstitute};
```

Title bar on vertically centered on the left side of the page.

```
32   \path
33     (current page.east) node[shift={{(-10,0)}}] (A) {}
34     (current page.east) node[shift={{(0,-2.5)}}] (B) {}
35     [shading=axis,left color=white,right color=black] (A) rectangle (B.south east)
36   ;
```

Author below the title bar.

```

37 \path (B) node
38 [anchor=north east
39 ,inner sep=8pt
40 ,text=black
41 ,font=\kut@normalfont\phantom{Xy}
42 ,text width=14cm,text ragged left]
43 {\@author};

```

Shading over the entire page (slightly bigger than the clipping).

```

44 \path[fill=white,opacity=0.90,transparency group] (NW) rectangle (SE);

```

Title text on the title bar. No hyphens are allowed in the title text.

```

45 \path (B) node
46 [anchor=south east,shift={(-3pt,0)}
47 ,text=yellow!75!red
48 ,font=\kut@titlefont\phantom{Xy}
49 ,text width=14cm,text ragged left]
50 {\nohyphens{\@title}};
51 \end{tikzpicture}%
52 \clearpage%
53 }
54 </title>

```

2.2 The kaumeta package

No package options are parsed.

```

55 <*meta>
56 \ProcessOptions\relax

```

Dependencies are loaded.

```

57 \usepackage{ifthen}

```

\subject The macro `\subject{<subject>}` can be used to set the subject of the document.
\@subject The last `<subject>` set will be available in the macro `\@subject`.

```

58 \newcommand*\@subject{}
59 \newcommand\subject[1]{\renewcommand*\@subject{#1}}

```

\institute The macro `\institute[<short>]{<institute>}` can be used to set the institute of the document's author. It is possible to provide a shorter version of the institute in the optional argument `<short>`. If not explicitly set, the short version is the same as the long version `<institute>`. The values are available in the macros `\@institute` and `\@shortinstitute`.

```

60 \newcommand*\@institute{}
61 \newcommand*\@shortinstitute{}
62 \newcommand\institute[2][]{%
63 \renewcommand*\@institute{#2}%
64 \ifthenelse{\equal{#1}{}}{ }{%
65 \renewcommand*\@shortinstitute{#2}%
66 }%
67 \renewcommand*\@shortinstitute{#1}%
68 }%
69 }

```

`\place` The macro `\place{<place>}` can be used to set the place of the document's author.

`\@place` The last `<place>` set will be available in the macro `\@place`.

```

70 \newcommand*\@place{}
71 \newcommand\place[1]{\renewcommand*\@place{#1}}

```

`\supervisor` `{<name>}` sets the supervisor's name for the kaumasters class.

```

72 \newcommand\@supervisor{}
73 \newcommand\supervisor[1]{\renewcommand*\@supervisor{#1}}

```

`\examiner` `{<name>}` sets the examiner's name for the kaumasters class.

```

74 \newcommand\@examiner{}
75 \newcommand\examiner[1]{\renewcommand*\@examiner{#1}}
76 </meta>

```

2.3 The kaulist package

No options are parsed.

```

77 <*list>
78 \ProcessOptions\relax
79 \RequirePackage{kaulanguage}

```

For `\prettylist`, the packages `pgffor`, `pgfmath`, and `pgfkeys` are required.

```

80 \RequirePackage{tikz}

```

`\commasign` defines a comma (","), if one is to be used before "and".

```

81 \AtBeginDocument{%
82   \setname{commasign}{},{,}%
83 }

```

`\andname` defines the word used as "and".

```

84 \AtBeginDocument{%
85   \setname{andname}{and}{och}%
86 }

```

`\prettylist` `{<list>}` transforms a comma separated list into a list in natural language.

```

87 \newcommand\prettylist[1]{%

```

The number of list elements is stored in `\num`.

```

88   \foreach[count=\xi] \x in #1 {%
89     \let\num=\xi%

```

The first element is just printed without any changes.

```

90   \foreach[count=\xi] \x in #1 {%
91     \ifnum \xi=1%
92       \x%

```

The last element is printed with preceding `\commasign`, if there are more than two elements in the list, and otherwise without.

```

93     \else%
94       \ifnum \xi=\num%
95         \ifnum \num=2%
96           {} \andname{} \x%
97         \else%
98           \commasign{} \andname{} \x%
99         \fi%

```

Elements in between the first and the last one are printed with a preceding hard-coded comma sign (not `\commasign`).

```

100     \else%
101     , \x%
102     \fi%
103     \fi%
104   }%
105 }%
106 </list>

```

2.4 The `kauclear` package

No options are parsed.

```

107 <{*clear>
108 \ProcessOptions\relax

```

`\kuc@currentpagestyle` The page style is stored in `\kuc@currentpagestyle`. Default: `plain`

```

109 \newcommand\kuc@currentpagestyle{plain}

```

`\pagestyle` The macro `\pagestyle` is redefined to update the page style in `\kuc@currentpagestyle`.

```

110 \let\pagestyle@orig\pagestyle
111 \renewcommand\pagestyle[1]{%
112   \renewcommand\kuc@currentpagestyle{#1}%
113   \pagestyle@orig{#1}%
114 }

```

`\kuc@restorepagestyle` The page style can be restored with `\kuc@restorepagestyle` after (temporarily) switching to another one using `\pagestyle@orig`.

```

115 \newcommand\kuc@restorepagestyle{%
116   \pagestyle@orig{\kuc@currentpagestyle}%
117 }

```

`\cleardoubpage@orig` The previous definition of `\cleardoublepage` is preserved in `\cleardoublepage@orig`.

```

118 \let\cleardoubpage@orig\cleardoublepage

```

`\cleardoublepage` The macro `\cleardoublepage` is redefined. The new definition switches temporarily to the page style `empty`.

```

119 \renewcommand\cleardoublepage{%
120   \clearpage%
121   \pagestyle@orig{empty}%
122   \cleardoubpage@orig%
123   \kuc@restorepagestyle%
124 }
125 </clear>

```

2.5 The `kauenvironments` package

No package options are parsed.

```

126 <{*environments>
127 \ProcessOptions\relax

```

```

Load dependencies.
128 \RequirePackage{xspace}
129 \RequirePackage{xcolor}

researchquestions The environment is an enumeration derived from enumerate. The argument of
\item[question] is used to formulate the research question.
130 \newenvironment{researchquestions}%
131 {\begin{enumerate}%
132 \let\kue@item\item%
133 \renewcommand\item[1][Research question]%
134 {\kue@item\emph{##1}\nopagebreak\par}%
135 }%
136 {\end{enumerate}}%

contributions The environment is an enumeration derived from enumerate. The argument of
\item[contrib] is used to formulate the contribution.
137 \newenvironment{contributions}%
138 {\begin{enumerate}%
139 \let\kue@item\item%
140 \renewcommand\item[1][%
141 \textcolor{red}{\emph{write your contribution between brackets
142 as optional argument of \texttt{\string\item}.}}}%
143 {\kue@item\emph{##1}\xspace}%
144 }%
145 {\end{enumerate}}%
146 \end{environments}

```

2.6 The kauparts package

```

147 \*parts
148 \RequirePackage{xkeyval}
149
150 \define@cmdkeys[kup]{pkg}[kup@]{vshift,vstep}
151 \setkeys[kup]{pkg}{vshift=2,vstep=0.8}
152
153 \ProcessOptionsX[kup]<pkg>
154
155 \RequirePackage{calc}
156 \RequirePackage{ifthen}
157 \RequirePackage{suffix}
158 \RequirePackage{tikz}
159 \usetikzlibrary{positioning}
160
161 \define@cmdkeys[kup]{part}[kup@]{body,label}
162 \define@boolkeys[kup]{part}[kup@]{tocentry}
163
164 \newcounter{kup@part}
165 \newcounter{kup@vertical}
166 \setcounter{kup@vertical}{0}
167
168 \newcommand*\@titlepagestyle{empty}
169 \newcommand\titlepagestyle[1]{\renewcommand*\@titlepagestyle{##1}}
170

```



```

171 \newcommand\kup@parheadline[2]{%
172   \path[node distance=1ex] (current page.north east) +(3pt,\kup@vshift+\kup@vstep*\arabic{kup
173     node%
174     [ anchor=north east%
175       , minimum width=2cm+3pt%
176       %, minimum height=7mm%
177       %, draw=black%
178       %, fill=black%
179       , left color=white%
180       , right color=black%
181       , text=white%
182       , font=\LARGE\bfseries%
183       ] (bar) {#1}%
184     node[base left=of bar,font=\LARGE\bfseries] {#2};%
185 }

\kupart

186 \newcommand\kupart[2][]{%
187   \cleardoublepage%
188   \thispagestyle{\@titlepagestyle}%
189   \stepcounter{kup@part}%
190   \setkeys[kup]{part}{body=\relax,label=,tocentry=true,#1}%
191   \providecommand\phantomsection{}%
192   \phantomsection%
193   \ifkup@tocentry%
194     \addcontentsline{toc}{part}{\numberline{\Roman{kup@part}}\textsc{#2}}%
195   \fi%
196   \renewcommand\@currentlabel{\Roman{kup@part}}%
197   \ifthenelse{\equal{\kup@label}{}}{\label{\kup@label}}%
198   \begin{tikzpicture}[remember picture,overlay,yscale=-1]%
199     \kup@parheadline{\Roman{kup@part}}{#2}%
200   \end{tikzpicture}%
201   \kup@body
202   \stepcounter{kup@vertical}%
203   \cleardoublepage%
204 }

\kupart*

205 \WithSuffix\newcommand\kupart*[2][]{%
206   \cleardoublepage%
207   \thispagestyle{\@titlepagestyle}%
208   \setkeys[kup]{part}{body=\relax,tocentry=true,#1}%
209   \providecommand\phantomsection{}%
210   \phantomsection%
211   \ifkup@tocentry%
212     \addcontentsline{toc}{part}{\textsc{#2}}%
213   \fi%
214   \begin{tikzpicture}[remember picture,overlay,yscale=-1]%
215     \kup@parheadline{\vphantom{X}}{#2}%
216   \end{tikzpicture}%
217   \kup@body
218   \stepcounter{kup@vertical}%
219   \cleardoublepage%
220 }
221 </parts>

```

2.7 The kaupaper package

```

222 <*paper>
223 \RequirePackage{xkeyval}
224
225 \define@cmdkeys[kua]{paper}[kua@]{author,title,subtitle,refprefix,reference,refnote,email,ref}
226 \define@cmdkeys[kua]{paperlist}[kua@]{printparticipation,tocline}
227 \setkeys[kua]{paper}{refstr=\reprintedname}
228
229 \ProcessOptionsX[kua]<paper>
230
231 \RequirePackage{kauparts}
232 \RequirePackage{ifthen}
233 \RequirePackage{tikz}
234
235 \RequirePackage{ragged2e}
236 \RequirePackage{hyphenat}
237
238 \RequirePackage{kaulanguage}
239
240 \AtBeginDocument{%
241   \setname{reprintedname}{Reprinted from}{Ursprungligen publicertad i}%
242   \setname{appendedpapersname}{List of Appended Papers}{Bifogade publiceringar}%
243   \setname{participationname}{Comments on my Participation}{Kommentarer p\aa{} min medverka}%
244   \setname{papername}{Paper}{Publicering}%
245 }
246
247 \newcounter{kua@section}
248 \newcounter{kua@equation}
249 \newcounter{kua@figure}
250 \newcounter{kua@table}
251
252 \newcounter{kua@paper}
253
254 \providecommand\thepaper{}
255 \providecommand\thepapertitle{}
256
257 \newcommand\kua@warning\relax
258 \newcommand\kua@dowarn{\gdef\kua@warning{\@latex@warning@no@line{List data created from the k
259 \AtEndDocument{\kua@warning}
260
261 \newcommand\kua@listof[4]{%
262   \IfFileExists{\jobname.#1}%
263     {% check whether empty file
264       \newread\reader%
265       \openin\reader\jobname.#1%
266       \read\reader to \readmacro%
267       \ifeof\reader%
268         \textcolor{red}{\ldots} will be available after the next \LaTeX{} run.}%
269       \@starttoc{#1}%
270       \%AtEndDocument{\@latex@warning@no@line{Rerun to get the list of #2 right}}%
271       \kua@dowarn%
272     }% file not empty -> create list
273     #3\@starttoc{#1}#4%

```

```

274     \fi%
275 }%
276 {% file does not exist
277   \textcolor{red}{\ldots{}} will be available after the next \LaTeX{} run.}%
278   \@starttoc{#1}%
279   %\AtEndDocument{\@latex@warning@no@line{Rerun to get the list of #2 right}}%
280   \kua@dowarn%
281 }%
282 }

```

\listofpapers

```

283 \newcommand\listofpapers[1]{%
284   \setkeys[kua]{paperlist}{printparticipation=yes,tocline=yes,#1}
285   \section*{\appendedpapersname}%
286   \ifthenelse{\equal{\kua@tocline}{yes}}{%
287     \addcontentsline{toc}{section}{\appendedpapersname}%
288   }{}%
289   \kua@listof{pap}{appended papers}{%
290     \begin{enumerate}%
291       \renewcommand\theenumi{\textbf{\Roman{enumi}}}%
292     }\end{enumerate}}%
293   \ifthenelse{\equal{\kua@printparticipation}{yes}}{%
294     \subsection*{\participationname}%
295     \kua@listof{pcp}{participation in appended papers}{}{}%
296   }{}%
297 }

298
299 \newcommand\l@paper[2]{%
300   \item #1%
301 }
302
303 \newcommand\listofsummaries{%
304   \kua@listof{sum}{paper summaries}{}{}%
305 }
306
307 \newcommand\l@summary[2]{%
308   #1%
309 }
310
311 \newcommand\l@limit[2]{%
312   %\paragraph{Limitations.}
313   #1%
314 }
315
316 \newcommand\l@participation[2]{%
317   #1%
318 }
319
320 \newcommand\papercover{%
321   \begin{tikzpicture}[remember picture,overlay]%
322     \path (current page.center)%
323       node%
324         [ node distance=\baselineskip%
325           , text width=\textwidth%

```

```

326     , text centered%
327   ] (refstr) {\kua@refstr};%
328 \ifthenelse{\equal{\kua@subtitle}{}}{%
329   \node%
330     [ node distance=1.5\baselineskip%
331     , above=of refstr%
332     , text width=\textwidth%
333     , text centered%
334     , font=\LARGE\bfseries%
335     ] {\nohyphens{\kua@title}};%
336 }{%
337   \node%
338     [ node distance=1.5\baselineskip%
339     , above=of refstr%
340     , text width=\textwidth%
341     , text centered%
342     , font=\large\bfseries%
343     ] (sub) {\nohyphens{\kua@subtitle}};%
344   \node%
345     [ node distance=1pt%
346     , above=of sub%
347     , text width=\textwidth%
348     , text centered%
349     , font=\LARGE\bfseries%
350     ] {\nohyphens{\kua@title}};%
351 }%
352 \node%
353   [ node distance=\baselineskip%
354   , below=of refstr%
355   , text width=\textwidth%
356   , text centered%
357   , font=\large%
358   ] {\nohyphens{\kua@reference}}\ifthenelse{\equal{\kua@refnote}{}}{\mbox{}\\medskip\n
359 ;%
360 \end{tikzpicture}%
361 }
362
363 \newenvironment{kaupaper}[1] []{%
364   \setcounter{kua@section}{\value{section}}%
365   \setcounter{kua@equation}{\value{equation}}%
366   \setcounter{kua@figure}{\value{figure}}%
367   \setcounter{kua@table}{\value{table}}%
368   \setcounter{section}{0}%
369   \setcounter{equation}{0}%
370   \setcounter{figure}{0}%
371   \setcounter{table}{0}%
372   \setkeys{kua}{paper}{subtitle=,vanity=,subdelimiter={---},refprefix=,refnote=,label=,summary=,
373   \setcounter{kua@paper}{\value{kup@part}}\stepcounter{kua@paper}%
374   \kaupart[tocentry=false,label=\kua@label,body=\papercover\kua@vanity]{\papername}%
375   \ifthenelse{\equal{\kua@subtitle}{}}%
376     {\ifthenelse{\equal{\kua@refnote}{}}%
377       {\addcontentsline{pap}{paper}{\kua@author. \kua@title. \kua@refprefix\kua@reference.}}%
378       {\addcontentsline{pap}{paper}{\kua@author. \kua@title. \kua@refprefix\kua@reference.\sm
379     \addcontentsline{toc}{part}{\textsc{\papername} \Roman{kua@paper}: \kua@title}}%

```

```

380     {\ifthenelse{\equal{\kua@refnote}{}}}%
381     {\addcontentsline{pap}{paper}{\kua@author. \kua@title\kua@subdelimiter\kua@subtitle. \k
382     {\addcontentsline{pap}{paper}{\kua@author. \kua@title\kua@subdelimiter\kua@subtitle. \k
383     \addcontentsline{toc}{part}{\textsc{\papername} \Roman{\kua@paper}: \\\kua@title\kua@subde
384     \addcontentsline{sum}{summary}{\string\subsubsection*\papername~\Roman{\kua@paper} -- \kua@
385     \ifthenelse{\equal{\kua@limitations}{}}{\}%
386     \addcontentsline{sum}{limit}{\kua@limitations}}%
387     \addcontentsline{pcp}{participation}{\string\paragraph{\papername~\Roman{\kua@paper}}\kua@par
388     \renewcommand*{\thepaper}{\papername~\Roman{\kua@paper}}%
389     \renewcommand*{\thepapertitle}{\kua@title}%
390     \renewcommand\maketitle{%
391     \thispagestyle{plain}%
392     \centering%
393     \Large\bfseries%
394     \vspace*{0.15\textheight}%
395     \kua@title\par%
396     \addvspace{1ex}%
397     \ifthenelse{\equal{\kua@subtitle}{}}{\}\{\large\kua@subtitle}%
398     \par\addvspace{\baselineskip}%
399     \normalsize%
400     \kua@author\\[0.25\baselineskip]%
401     \normalfont%
402     \kua@email%
403     \par\addvspace{2\baselineskip}\justifying%
404     }%
405 }{%
406     \setcounter{section}{\value{\kua@section}}%
407     \setcounter{equation}{\value{\kua@equation}}%
408     \setcounter{figure}{\value{\kua@figure}}%
409     \setcounter{table}{\value{\kua@table}}%
410     \clearpage%
411 }
412 </paper>

```

2.8 The kaustudies package

```

413 <*studies>
414 \RequirePackage{xkeyval}
415
416 \define@boolkey[kus]{pkg}[kus@]{tinyfontswitch}[true]{}
417
418 \presetkeys[kus]{pkg}{tinyfontswitch}{}
419 \ProcessOptionsX[kus]<pkg>
420
421 \RequirePackage[twoside]{geometry}
422 \RequirePackage{garamondx}
423 \RequirePackage{garamondx,cmbraces}{newtxmath}
424
425 \geometry
426 { paperwidth=165mm
427   , paperheight=242mm
428   , inner=27mm
429   , outer=27mm
430   , top=24mm

```

```

431   , bottom=22mm
432 }
433
434 \ifkus@tinyfontswitch
435   \let\kus@tiny@orig\tiny
436   \renewcommand*\tiny{\sffamily\kus@tiny@orig}
437 \fi
438 </studies>

```

2.9 The kaulanguage package

```

439 <*language>
440 \ProcessOptions\relax
441 \newif\ifbabel
442 \babelfalse
443 \AtBeginDocument{%
444   \ifpackageloaded{babel}%
445     {\babeltrue}%
446     {\babelfalse}%
447 }
\setname   {\<macro name>}{\<english>}{\<swedish>}}
448 \newcommand\setname[3]{%
449   \IfFileExists{swedish.ldf}{%
450     \ifbabel%
451       \expandafter\edef\csname #1\endcsname{\noexpand\iflanguage{swedish}{#3}{#2}}%
452     \else%
453       \expandafter\edef\csname #1\endcsname{#2}%
454     \fi%
455   }%
456   {\expandafter\edef\csname #1\endcsname{#2}}%
457 }
458 </language>

```

2.10 The pgfcropmarks package

No options are parsed.

```

459 <*crop>
460 \ProcessOptions\relax
461 \RequirePackage{pgfpages}%

```

No files are created or updated.

```

462 \nofiles%
  Boolean, true on odd pages.
463 \newif\if@kus@isodd%
464 \@kus@isoddtrue%

```

`\cropmarklen` The length of the crop mark lines.

```

465 \newlength{\cropmarklen}\setlength{\cropmarklen}{40pt}%

```

`\cropmarksep` The space between cropmark and paper edge.

```

466 \newlength{\cropmarksep}\setlength{\cropmarksep}{15pt}%

```

The cropmark page layout.

```

467 \pgfpagesdeclarelayout{cropmarks}%
468 {%
469 }%
470 {%
471   \pgfpagesphysicalpageoptions%
472   {%
473     logical pages=1,%
474     physical height=297mm,%
475     physical width=210mm%
476   }%
477   \pgfpageslogicalpageoptions{1}%
478   {%
479     border code=%
480     \if@kus@isodd
481       \global\@kus@isoddfalse
482       \pgfsetlinewidth{0.6pt}%
483       \pgfusepath{discard}%
484       \pgfmoveto{\pgfpoint{-\cropmarksep}{0pt}}%
485       \pgflineto{\pgfpoint{-\cropmarklen}{0pt}}%
486       \pgfmoveto{\pgfpoint{0pt}{-\cropmarksep}}%
487       \pgflineto{\pgfpoint{0pt}{-\cropmarklen}}%
488       \pgfmoveto{\pgfpoint{\paperwidth+\cropmarksep}{0pt}}%
489       \pgflineto{\pgfpoint{\paperwidth+\cropmarklen}{0pt}}%
490       \pgfmoveto{\pgfpoint{\paperwidth}{-\cropmarksep}}%
491       \pgflineto{\pgfpoint{\paperwidth}{-\cropmarklen}}%
492       \pgfmoveto{\pgfpoint{-\cropmarksep}{\paperheight}}%
493       \pgflineto{\pgfpoint{-\cropmarklen}{\paperheight}}%
494       \pgfmoveto{\pgfpoint{0pt}{\paperheight+\cropmarksep}}%
495       \pgflineto{\pgfpoint{0pt}{\paperheight+\cropmarklen}}%
496       \pgfmoveto{\pgfpoint{\paperwidth}{\paperheight+\cropmarksep}}%
497       \pgflineto{\pgfpoint{\paperwidth}{\paperheight+\cropmarklen}}%
498       \pgfmoveto{\pgfpoint{\paperwidth+\cropmarksep}{\paperheight}}%
499       \pgflineto{\pgfpoint{\paperwidth+\cropmarklen}{\paperheight}}%
500       \pgfusepath{stroke}%
501     \else
502       \global\@kus@isoddtrue
503       \fi,%
504     center=\pgfpoint{.5\pgfphysicalwidth}{.5\pgfphysicalheight}%
505   }%
506 }%

```

Activate the cropmark page layout.

```

507 \pgfpagesuselayout{cropmarks}%
508 \end{crop}

```

Change History

v1.0		v1.10	
General: SBe's licentiate version . . .	1		
v1.1		General: Version bump without	
General: Initial public release	1	changes	1

v1.11	General: Fixed missing file in babel support 1	v1.5	General: Added templates for kau-collection and kaureport 1
v1.14	General: Added refnote 1	v1.6	General: Merged the styles' dtx files 1
v1.15	General: Added refprefix 1	v1.7	General: Added macros for supervisor and examiner in kaumeta . . 1
v1.2	General: Support for babel.sty, Documentation added 1	v1.8	General: Added macros pretty printing lists in kaulist 1
v1.3	General: Merged the classes' dtx files 1	v1.9	General: Version bump without changes 1
v1.4	General: Fixed babel.sty support . . 1		

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	\appendedpapersname	\cropmarklen <u>465</u> , 485, 487, 489, 491, 493, 495, 497, 499
\@author 43 285, 287	
\@currentlabel 196	\arabic 172	\cropmarksep <u>466</u> , 484, 486, 488, 490, 492, 494, 496, 498
\@examiner 74, 75	\AtBeginDocument 81, 84, 240, 443	\csname . . . 451, 453, 456
\@ifpackageloaded . 444	\AtEndDocument 259, 270, 279	
\@institute . . . 5, 60, 63		
\@kus@isoddfalse . . 481		
\@kus@isoddtrue 464, 502		
\@latex@warning@no@line 258, 270, 279	B	D
\@place 6, 70, 71	\babe>false . . . 442, 446	\define@boolkey . . . 416
\@shortinstitute 5, 31, 61, 65, 67	\babeltrue 445	\define@boolkeys . . 162
\@starttoc 269, 273, 278	\baselineskip 324, 330, 338, 353, 398, 400, 403	\define@cmdkeys . 7, 150, 161, 225, 226
\@subject . 5, 26, 58, 59	\begin . 15, 131, 138, 198, 214, 290, 321	E
\@supervisor 72, 73	\bfseries 9, 182, 184, 334, 342, 349, 393	\edef 451, 453, 456
\@title 50		\else 93, 97, 100, 272, 452, 501
\@titlepagestyle . . . 168, 169, 188, 207	C	\emph 134, 141, 143
\@ 358, 378, 379, 382, 383, 400	\centering 392	\end . . . 51, 136, 145, 200, 216, 292, 360
	\cleardoublepage 118, <u>119</u> , 187, 203, 206, 219	\endcsname 451, 453, 456
A	\cleardoubpage@orig <u>118</u> , 122	environments:
\aa 243	\clearpage 52, 120, 410	contributions . . <u>137</u>
\addcontentsline 194, 212, 287, 377–379, 381–384, 386, 387	\commasign <u>81</u> , 98	researchquestions <u>130</u>
\addvspace 396, 398, 403	contributions (environment) . . . <u>137</u>	\equal 64, 197, 286, 293, 328, 358, 375, 376, 380, 385, 397
\andname <u>84</u> , 96, 98		\examiner <u>74</u>

<code>\expandafter</code>	<code>\kua@refnote</code> . . 358,	N
. . . . 451, 453, 456	376, 378, 380, 382	<code>\newcounter</code> . . . 164,
F	<code>\kua@refprefix</code>	165, 247–250, 252
<code>\fi</code> 99, 102,	. 377, 378, 381, 382	<code>\newif</code> 441, 463
103, 195, 213,	<code>\kua@refstr</code> 327	<code>\newlength</code> . . . 465, 466
274, 437, 454, 503	<code>\kua@subdelimiter</code> .	<code>\newread</code> 264
<code>\fontfamily</code> 9, 10 381–383	<code>\node</code> . 329, 337, 344, 352
<code>\fontsize</code> 9, 10	<code>\kua@subtitle</code>	<code>\noexpand</code> 451
<code>\foreach</code> 88, 90 328, 343,	<code>\nofiles</code> 462
G	375, 381–383, 397	<code>\nohyphens</code> 50,
<code>\gdef</code> 258	<code>\kua@summary</code> 384	335, 343, 350, 358
<code>\geometry</code> 425	<code>\kua@title</code> . . . 335,	<code>\nopagebreak</code> 134
<code>\global</code> 481, 502	350, 377–379,	<code>\normalfont</code> 401
I	381–384, 389, 395	<code>\normalsize</code> 399
<code>\if@kus@isodd</code> . 463, 480	<code>\kua@tocline</code> 286	<code>\num</code> 89, 94, 95
<code>\ifbabel</code> 441, 450	<code>\kua@vanity</code> 374	<code>\numberline</code> 194
<code>\ifeof</code> 267	<code>\kua@warning</code> . . 257–259	O
<code>\ifFileExists</code> . 262, 449	<code>\kuc@currentpagestyle</code>	<code>\openin</code> 265
<code>\ifkup@tocentry</code> 193, 211 109, 112, 116	P
<code>\ifkus@tinyfontswitch</code>	<code>\kuc@restorepagestyle</code>	<code>\pagestyle</code> 110
. 434 115, 123	<code>\pagestyle@orig</code> . .
<code>\iflanguage</code> 451	<code>\kue@item</code> 110, 113, 116, 121
<code>\ifnum</code> 91, 94, 95	. 132, 134, 139, 143	<code>\papercover</code> . . . 320, 374
<code>\ifthenelse</code> 64,	<code>\kup@body</code> 201, 217	<code>\paperheight</code> . . 492–499
197, 286, 293,	<code>\kup@label</code> 197	<code>\papername</code> 374, 379,
328, 358, 375,	<code>\kup@parheadline</code> .	383, 384, 387, 388
376, 380, 385, 397 171, 199, 215	<code>\paperwidth</code>
<code>\institute</code> 60	<code>\kup@vshift</code> 172	. 488–491, 496–499
<code>\item</code> 132, 133,	<code>\kup@vstep</code> 172	<code>\par</code> . . 134, 395, 398, 403
139, 140, 142, 300	<code>\kus@tiny@orig</code> 435, 436	<code>\paragraph</code> . . . 312, 387
J	<code>\kut@maketitle</code> . . . 2, 12	<code>\participationname</code> . 294
<code>\jobname</code> 262, 265	<code>\kut@normalfont</code> . . .	<code>\path</code> . 16–23, 27, 32,
<code>\justifying</code> 403 25, 30, 41	37, 44, 45, 172, 322
K	<code>\kut@titlefont</code> 48	<code>\pgfimage</code> 21, 22
<code>\kaupart</code> 3, 186, 205, 374	L	<code>\pgflineto</code> . . . 485,
<code>\kaupart*</code> 3, 205	<code>\l@limit</code> 311	487, 489, 491,
<code>\kua@author</code> . . . 377,	<code>\l@paper</code> 299	493, 495, 497, 499
378, 381, 382, 400	<code>\l@participation</code> . . 316	<code>\pgfmoveto</code> . . . 484,
<code>\kua@dowarn</code> 258, 271, 280	<code>\l@summary</code> 307	486, 488, 490,
<code>\kua@email</code> 402	<code>\label</code> 197	492, 494, 496, 498
<code>\kua@label</code> 374	<code>\LARGE</code> 182, 184, 334, 349	<code>\pgfpagesdeclarelayout</code>
<code>\kua@limitations</code> . .	<code>\Large</code> 393 467
. 385, 386	<code>\large</code> 342, 357, 397	<code>\pgfpageslogicalpageoptions</code>
<code>\kua@listof</code>	<code>\LaTeX</code> 268, 277 477
. 261, 289, 295, 304	<code>\ldots</code> 268, 277	<code>\pgfpagesphysicalpageoptions</code>
<code>\kua@participation</code> . 387	<code>\listofpapers</code> 283 471
<code>\kua@printparticipation</code>	<code>\listofsummaries</code> . . 303	<code>\pgfpagesuselayout</code> . 507
. 293	M	<code>\pgfphysicalheight</code> . 504
<code>\kua@reference</code> 358,	<code>\maketitle</code> 2, 12, 13, 390	<code>\pgfphysicalwidth</code> . 504
377, 378, 381, 382	<code>\mbox</code> 358	<code>\pgfpoint</code> . 484–499, 504
	<code>\medskip</code> 358	<code>\pgfsetlinewidth</code> . . 482
		<code>\pgfusepath</code> . . . 483, 500

<code>\phantomsection</code> 191, 192, 209, 210	<code>\Roman</code> 194, 196, 199, 291, 379, 383, 384, 387, 388	<code>\textsc</code> 194, 212, 379, 383 <code>\texttt</code> 142, 372 <code>\textwidth</code> ... 325, 332, 340, 347, 355
<code>\place</code> 70	S	<code>\theenumi</code> 291
<code>\presetkeys</code> 418	<code>\section</code> 285	<code>\thepaper</code> 254, 388
<code>\prettylist</code> 87	<code>\selectfont</code> 9, 10	<code>\thepapertitle</code> 255, 389
<code>\ProcessOptions</code> 2, 56, 78, 108, 127, 440, 460	<code>\setcounter</code> 166, 364– 371, 373, 406–409	<code>\thispagestyle</code> 14, 188, 207, 391
<code>\ProcessOptionsX</code> 153, 229, 419	<code>\setkautitlefont</code> . 2 , 7	<code>\tiny</code> 435, 436
<code>\providecommand</code> 191, 209, 254, 255	<code>\setkeys</code> 8, 11, 151, 190, 208, 227, 284, 372	<code>\titlepagestyle</code> ... 169
R	<code>\setlength</code> ... 465, 466	U
<code>\read</code> 266	<code>\setname</code> 82, 85, 241–244, 448	<code>\usepackage</code> 57
<code>\reader</code> 264–267	<code>\sffamily</code> 436	<code>\usetikzlibrary</code> ... 159
<code>\readmacro</code> 266	<code>\smallskip</code> ... 378, 382	V
<code>\relax</code> 2, 56, 78, 108, 127, 190, 208, 257, 440, 460	<code>\stepcounter</code> 189, 202, 218, 373	<code>\value</code> 364– 367, 373, 406–409
<code>\reprintedname</code> 227	<code>\string</code> 142, 372, 384, 387	<code>\vphantom</code> 25, 30, 41, 48, 215
<code>\RequirePackage</code> 3–6, 79, 80, 128, 129, 148, 155–158, 223, 231–233, 235, 236, 238, 414, 421–423, 461	<code>\subject</code> 58	<code>\vspace</code> 394
<code>researchquestions</code> (environment) 130	<code>\subsection</code> 294	W
	<code>\subsubsection</code> 384	<code>\WithSuffix</code> 205
	<code>\supervisor</code> 72	X
	T	<code>\x</code> 88, 90, 92, 96, 98, 101
	<code>\textbf</code> 291	<code>\xi</code> 88–91, 94
	<code>\textcolor</code> 141, 268, 277, 372	<code>\xspace</code> 143
	<code>\textheight</code> 394	