The kauthesis package*

Stefan Berthold stefan.berthold@kau.se

May 28, 2013

1 Introduction

The kauthesis package provides LATEX classes for master's theses (kaumasters class), collection theses (kaucollection class), and monographs (kaureport class). The latest version can be obtained from

http://github.com/ZjMNZHgG5jMXw/kauthesis

The user's manual is found in kauguide.pdf. This file provides the source code documentation to all three classes.

2 Usage

2.1 Master's thesis

This template can be found in kaumasterstemplate.tex. The kaumasters class is quite similar to LATEX's article class. After loading the class, title, author, and institute have to be declared. Different authors in author lists can be separated by commata (","). The formatting will be done by LATEX.

- 1 (*masterstemplate)
- 2 \documentclass{kaumasters}
- 3 \title{Title}
- 4 \author{Author}
- 5 \supervisor{Super}
- 6 \examiner{Exam}
- 7 \institute{Department of Mathematics and Computer Science}
- 8 \place{Place}

The thesis starts with the front matter \frontmatter. It will (re)print the title. The macro \maketitle does not exist, since the title will be created by Karlstad University Studies.

- 9 \begin{document}
- 10 \frontmatter

The two mandatory inhabitants of the front matter are the abstract (abstract environment) and the \tableofcontents. If you like to write acknowledgements, put it between the abstract and the table of contents.

^{*}This document corresponds to kauthesis v1.10, dated 2013/05/28.

```
11 \begin{abstract}
12 Abstract.
13 \keywords keywords
14 \end{abstract}
15 \approvalpage%
16 \begin{acknowledgements}
17 Thanks.
18 \end{acknowledgements}
```

19 \tableofcontents

The main matter starts with \mainmatter for adjusting the page numbering. The content in the main matter is your work. Any macro or environment known from LaTeX's article class can be used here.

```
20 \mainmatter  
21 \section{Introduction}  
22 \end{document}  
23 \langle \text{/masterstemplate} \rangle
```

2.2 Report

This template can be found in kaureporttemplate.tex. Like the master's thesis class, the report class is derived from the LATEX article class.

```
24 \langle *reporttemplate \rangle 25 \land documentclass\{kaureport\}
```

After loading the class, title, author, and institute have to be declared. Different authors in author lists can be separated by commata (","). The formatting will be done by LATEX.

```
26 \title{Title}
27 \author{Author}
28 \institute{Department of Mathematics and Computer Science}
29 \place{Place}
30 \begin{document}
```

The two mandatory inhabitants of the front matter are the abstract (abstract environment) and the \tableofcontents. If you like to write acknowledgements, put it between the abstract and the table of contents.

```
31 \frontmatter
32 \begin{abstract}
33    Brief abstract.
34    \keywords keywords
35 \end{abstract}
36 \begin{acknowledgements}
37    Thanks.
38 \end{acknowledgements}
39 \tableofcontents
```

The main matter starts with \mainmatter for adjusting the page numbering. The content in the main matter is your work. Any macro or environment known from LaTeX's article class can be used here.

```
40 \mainmatter
41 \part{Introduction}
42 \section{Related work}
43 \part{Conclusions and Future Work}
```

```
44 \end{document} 45 \langle \text{reporttemplate} \rangle
```

2.3 Collection thesis

This template can be found in kaucollectiontemplate.tex. Like the master's thesis class, the report class is derived from the \LaTeX article class.

```
46 46 47 \documentclass{kaucollection}
```

52 \lohead{\thepapertitle}

Page headings and can be created using the scrheadings packages.

```
48 \usepackage{scrpage2}
49 \pagestyle{scrheadings}
50 \renewcommand*\headfont{\normalfont\small}
51 \rehead{\thepaper}
```

After loading the class, title, author, and institute have to be declared. Different authors in author lists can be separated by commata (","). The formatting will be done by LATEX.

```
53 \title{Title}
54 \author{Author}
55 \institute{Department of Mathematics and Computer Science}
56 \place{Place}
57 \begin{document}
```

The two mandatory inhabitants of the front matter are the abstract (abstract environment) and the \tableofcontents. If you like to write acknowledgements, put it between the abstract and the table of contents.

```
58 \frontmatter
59 \begin{abstract}
60 Brief abstract.
61 \keywords keywords
62 \end{abstract}
63 \begin{acknowledgements}
64 Thanks.
65 \end{acknowledgements}
66 \tableofcontents
```

The table of contents is followed by the list of papers.

 $67 \setminus listofpapers$

The main matter starts with \mainmatter for adjusting the page numbering.

```
68 \mainmatter
```

69 \section{Introduction}

Create a list of summaries of all appended papers with \listofsummaries.

```
70 \section{Summary of Appended Papers} 71 \listofsummaries
```

72 \section{Conclusions and Future Work}

Append papers, each in an own kaupaper environment.

```
73 \begin{kaupaper}[ author=Author
74 , title=Paper Title
75 , reference=reference text.
76 , email=author@kau.se
```

```
77
                   , summary=Abstract in the intro.
                   , participation=I am the main author.
78
79
                     label=paper:shorttitle
80
Appended papers may have their own titles and abstracts.
    \maketitle
82
    \begin{abstract}
83
      Paper abstract.
    \end{abstract}
84
    Paper content.
85
86 \end{kaupaper}
87 \end{document}
88 (/collectiontemplate)
```

3 Implementation

3.1 Class options and dependencies

Class options are neither parsed nor passed to the underlying article class. All macros are derived from the standard article class.

```
89 (*collection | report | masters)
90 \ProcessOptions\relax
91 \LoadClass{article}
```

kauclear provides page style switches in \cleardoublepage, kaumeta defines the macros relevant for creating title information, e.g., \institute.

```
92 \RequirePackage{kauclear}
93 \RequirePackage{kaumeta}
94 \RequirePackage{kaulist}
```

kaustudies sets the page dimension to the format required by Karlstad University Studies, kauenvironments defines environments such as researchquestions and contributions, tikz allows to place content material with absolute coordinates (required by \vanityquote).

```
(required by \vanityquote).
95 \*collection | report\)
96 \RequirePackage{kaustudies}
97 \RequirePackage{kauenvironments}
98 \RequirePackage{tikz}
99 \( / \collection | \text{report} \)
kaupaper defines the macros for appending papers to the collection thesis.
100 \( * \collection \)
101 \RequirePackage{kaupaper}
102 \( / \collection \)
kauparts defines \kaupart, a replacement for \part.
103 \( * \text{report} \)
104 \RequirePackage{kauparts}
105 \( / \text{report} \)
Garamond becomes the default font on A4 page layout.
106 \( * \text{masters} \)
```

107 \RequirePackage[urw-garamond]{mathdesign}

109 (/masters)

108 \RequirePackage[paper=a4,pagesize,twoside=semi]{typearea}

3.2 Language support

\acknowledgementname

By default, the acknowledgements environment will create an unnumbered section with the title "Acknowledgements" (or "Tacksägelser", if Swedish is chosen as default language). The section headline can be changed to any other language by redefining the macro \acknowledgementname.

```
110 \AtBeginDocument{%
111 \@ifpackageloaded{babel}%
112 {\newcommand*\acknowledgementname{%
113 \iflanguage{swedish}{Tacks\"agelser}{Acknowledgements}}%
114 }%
115 {\newcommand*\acknowledgementname{Acknowledgements}}%
116}
```

\keywordname

The abstract is followed by the list of keywords. By default, the list is introduced by the word "Keywords" (and "Nyckelord" if the default language is set to Swedish). The list introduction can be changed to any other language by redefining the macro \keywordname.

```
117 \AtBeginDocument{%
118 \@ifpackageloaded{babel}%
119 {\newcommand*\keywordname{%
120 \iflanguage{swedish}{Nyckelord}{Keywords}}%
121 }%
122 {\newcommand*\keywordname{Keywords}}%
123 }
```

\introname

In collection thesis, the main matter starts automatically with an Introductory Summary. The name of the Introductory Summary ("Inledande sammanfattning" in Swedish) can be changed to any other language by redefining the macro \introname.

```
124 (*collection)
125 \AtBeginDocument{%
     \@ifpackageloaded{babel}%
127
        {\newcommand*\introname{%
          \verb|\iflamguage{swedish}| %
128
            {Inledande sammanfattning}%
129
            {Introductory Summary}}%
130
       }%
131
132
        {\newcommand*\introname{Introductory Summary}}%
133 }
134 (/collection)
```

A master's thesis needs to be approved by the supervisor and the examiner.

 $135 \langle *masters \rangle$

\approvalname This macro contains the word "approved".

```
136 \AtBeginDocument{%
137 \@ifpackageloaded{babel}%
138 {\newcommand*\approvalname{%
139 \iflanguage{swedish}%
140 {Godk\"and}%
141 {Approved}}%
```

```
7%
                  142
                         {\newcommand*\approvalname{Approved}}%
                  143
                  144 }
                  This macro contains the name of the examination.
\examinationname
                  145 \AtBeginDocument{%
                       \@ifpackageloaded{babel}%
                  146
                         {\newcommand*\examinationname{%
                  147
                           \iflanguage{swedish}%
                  148
                             {magisterexamen}%
                  149
                  150
                             {Master's degree}}%
                  151
                         }%
                         {\newcommand*\examinationname{Master's degree}}%
                  152
                  153 }
   \approvaltext The approval text.
                  154 \AtBeginDocument{%
                       \@ifpackageloaded{babel}%
                  156
                         {\newcommand*\approvaltext{%
                           \iflanguage{swedish}%
                  157
                             {Denna uppsats \"ar skriven som en del av det arbete som kr\"avs %
                  158
                               f\"or att erh\aa lla en \examinationname{} i datavetenskap. Allt %
                  159
                               material i denna rapport, vilket inte \"ar mitt eget, har blivit %
                  160
                               tydligt identifierat och inget material \"ar inkluderat som %
                  161
                               tidigare anv\"ants f\"or erh\aa llande av annan examen.}%
                  162
                             {This thesis is submitted in partial fulfillment of the \%
                  163
                               requirements for the \examinationname{} in Computer Science. %
                  164
                               All material in this thesis which is not my own work has been %
                  165
                               identified and no material is included for which a degree has \%
                  166
                               previously been conferred.}}%
                  167
                  168
                         {\newcommand*\approvaltext{This thesis is submitted in partial %
                  169
                           fulfillment of the requirements for the \examinationname{} in %
                  170
                           Computer Science. All material in this thesis which is not my own %
                  171
                           work has been identified and no material is included for which a %
                  172
                           degree has previously been conferred.}}%
                  173
                  174 }
 \supervisorname
                  This macro contains the word "supervisor".
                  175 \AtBeginDocument{%
                       \@ifpackageloaded{babel}%
                  177
                         {\newcommand*\supervisorname{%
                  178
                           \iflanguage{swedish}%
                             {Handledare}%
                  179
                              {Supervisor}}%
                  180
                         7%
                  181
                         {\newcommand*\supervisorname{Supervisor}}%
                  182
                  183 }
   \examinername This macro contains the word "examiner".
                  184 \AtBeginDocument{%
                       \@ifpackageloaded{babel}%
                  185
                         {\newcommand*\examinername{%
                  186
                           \iflanguage{swedish}%
                  187
```

3.3 Title page

Karlstad University Studies will create the title page for the thesis, thus, creating an own title page is not necessary.

\kauths@maketitle

The definition of \maketitle in the article class creates a title without creating a separate page. The original definition is preserved in \kauths@maketitle.

194 \let\kauths@maketitle\maketitle

\maketitle \maketitle does not serve any purpose. When invoked, it produces a warning, referring the user to the abstract environment.

```
195 \renewcommand\maketitle{%

196 \PackageWarning{maketitle does not serve any purpose in this class.

197 The abstract environment reproduces the title instead.}%

198 }
```

3.4 Front matter

The front matter starts after the title on page iii. It contains the abstract of the thesis, followed by an optional acknowledgements section and the table of contents. In collection theses and reports, the keywords are defined in the front matter.

\kauths@abstract

The abstract environment of the article class provides a perfect layout for article abstracts in collection theses. It will be used for the abstracts of appended papers and preserved in the macro \kauths@abstract.

```
199 \let\kauths@abstract\abstract%
200 \let\kauths@endabstract\endabstract%
```

\frontmatter

The front matter is started with \frontmatter. It is assumed that this macro directly runs after the optional \maketitle.

```
201 \newcommand*\frontmatter{%
202 \clearpage%
```

The front matter starts on page iii, i.e., two pages are reserved for the title.

```
203 \setcounter{page}{3}%
204 \renewcommand\thepage{\roman{page}}%
```

abstract The abstract environment in the front matter creates a title and an unnumbered abstract section.

```
205 \renewenvironment{abstract}{%
```

\keywords The abstract's last line in collection theses and reports is supposed to be a list of keywords preceded by \keywords.

```
206 \newcommand\keywords{\paragraph{\keywordname:}}%
```

```
english It is common to append an English translation of the abstract, if the thesis or
                        report is not written in English.
                               \newenvironment{english}{%
                       207
                                \renewcommand\keywords{\paragraph{Keywords:}}%
                       208
                                 \section*{Abstract}%
                       209
                              }{%
                       210
                       211
                        The abstract starts by repeating the title, author, and the institue.
                               \cleardoublepage%
                               \section*{\@title}%
                       213
                               \textsc{\prettylist{\@author}}\par%
                       214
                              \noindent\textit{\@institute}%
                       215
                               \section*{\abstractname}%
                       216
                       217
                        The thesis continues after the abstract on an odd page.
                               \cleardoublepage%
                       218
                       219
                            }%
                       220 }
         \approvalpage The macro \approvalpage creates an approval page for Master's theses.
                       221 \langle *masters \rangle
                       222 \newcommand\approvalpage{%
                       223
                            \cleardoublepage%
                             224
                             225
                             \noindent\approvaltext\\\mbox{}\bigskip%
                       226
                       227
                             \foreach \x in \@author {\signer{\x}}%
                             \\\mbox{}\bigskip\\\mbox{}\bigskip%
                       228
                             \approvalname,\\\mbox{}\bigskip%
                       229
                             \begin{quote}%
                       230
                       231
                               \sig\supervisorname: \@supervisor\\\mbox{}\bigskip\\%
                       232
                               \sig\examinername: \@examiner
                       233
                             \end{quote}%
                       234 }
                       235 (/masters)
      acknowledgements
                       The environment acknowledgements creates an unnumbered section.
                        236 \newenvironment{acknowledgements}{%
                       237
                            \cleardoublepage%
                       238
                            \section*{\acknowledgementname}%
                       239 }{%
                        The author's name is reused to create an attribution line at the end of the ac-
                        knowledgements section.
                            \par\bigskip\bigskip\noindent\@place, \@date\hfill \prettylist{\@author}%
                             \cleardoublepage%
                       241
                       242 }
                        The \tableofcontents definition from the article class is preserved. It is not
\kauths@tableofcontents
                        reused in this class.
```

243 \let\kauths@tableofcontents\tableofcontents

\tableofcontents The redefined macro makes the table of contents start on an odd page.

```
244 \renewcommand\tableofcontents{%
245 \cleardoublepage%
246 \kauths@tableofcontents%
247 }
```

3.5 Main matter

The main matter is started with \mainmatter. The macro resets the page counter to page 1 and, for collection theses, it immediately creates the part Introductory Summary.

\mainmatter

The optional argument of $\mbox{\mbox{$\mbox{mainmatter}[$\langle body\ material$\rangle$]}}$ can be used to get access to the part's title page, e.g., for adding a quote with $\mbox{\mbox{$\mbox{$\mbox{$\mbox{$\mbox{$\mbox{$\mbox{$}\mbox{$\mbox{$}\mbox{$}\mbox{$\mbox{$}\mbox{$}\mbox{$\mbox{$}\mb$

```
248 \newcommand\mainmatter[1][]{% 249 \cleardoublepage%
```

The original definition of the abstract environment is restored.

250 \renewenvironment{abstract}{\kauths@abstract}{\kauths@endabstract}

The page counter is set to page 1.

```
251 \setcounter{page}{1}%
252 \pagenumbering{arabic}%
```

The Introductory Summary title page is created with \introname and $\langle body \ material \rangle$.

```
253 \langle *collection \rangle
254 \langle *collection \rangle
255 \langle /collection \rangle
256 }
```

\vanityquote

```
257 (*collection | report)
258 \newcommand\vanityquote[2]{%
```

The quote is placed relative to the borders of the page. TikZ is doing the actual placing.

259 \begin{tikzpicture}[remember picture,overlay]%

The placing reference is the lower right corner of the page.

```
260 \path (current page.south east) +(-3,3.5)%

261 node%

262 [ anchor=south east%

263 , font=\large%

264 , text width=25em%
```

The closing quotation marks are placed outside the quote's right margin.

```
265 ] {\raggedleft''#1\rlap{''}\%
266 \normalfont\par\medskip\itshape #2\par};%
267 \end{tikzpicture}%
268 }
269 \( /collection | report \)
```

```
\part In the kaureport class, the \part{\lambda headline}} is replaced by \kaupart. 
 \[ \frac{270}{*report} \] \[ \frac{271}{let\part\kaupart} \] \[ \frac{272}{/report} \] \[ \frac{272}{/collection} | report | masters \rangle \]
```

Change History

v1.0	collection and kaureport 1
General: SBe's licentiate version 1	v1.6
v1.1 General: Initial public release 1 v1.10 General: Version bump without	General: Merged the styles' dtx files
changes	General: Added approval page to kaumasters 1 v1.8
v1.3 General: Merged the classes' dtx files	General: Improved author's signatures on the approval page of kaumasters
General: Fixed babel.sty support . 1 v1.5 General: Added templates for kau-	General: Added keywords to kaumasters, added an environment for English abstracts 1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

${f Symbols}$	abstract (environ-	\bigskip 226,
\" 113, 140, 158–162	ment) 205	228, 229, 231, 240
\@author 214, 227, 240	\abstractname 216	
\@date 240	\acknowledgementname	${f C}$
\@examiner 232	$110, 238$	\cleardoublepage
\@ifpackageloaded .	acknowledgements (en-	. 212, 218, 223,
111,	vironment) $\underline{236}$	237, 241, 245, 249
118, 126, 137,	\approvalname . $\underline{136}$, 229	\clearpage 202
146, 155, 176, 185	\approvalpage $15, \underline{221}$	
\@institute 215	\approvaltext . <u>154</u> , 226	D
\@place 240	\AtBeginDocument 110,	\documentclass $2, 25, 47$
\@supervisor $\dots 231$	117, 125, 136,	
\@title 213	145, 154, 175, 184	${f E}$
\\ 224, 226, 228, 229, 231	\author 4, 27, 54	\end $14, 18, 22, 35, 38,$
	В	44, 62, 65, 84,
${f A}$	\begin 9, 11, 16, 30, 32,	86, 87, 225, 233, 267
\aa 159, 162	36, 57, 59, 63,	$\verb \endabstract \dots \dots 200$
\abstract 199	73, 82, 225, 230, 259	english (environment) 207

environments: abstract	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	\renewcommand 50, 195, 204, 208, 244 \renewenvironment 205, 250 \RequirePackage
F \foreach 227 \frontmatter 10, 31, 58, <u>201</u> H	$\begin{array}{c} \mathbf{M} \\ \texttt{\mbox{\mbox{\sim}}} & 20,40,68,\underline{248} \\ \texttt{\mbox{\mbox{\sim}}} & 224 \\ \texttt{\mbox{\mbox{\sim}}} & 81,194,\underline{195} \end{array}$	S \section 21, 42, 69, 70, 72, 209, 213, 216, 238 \setcounter 203, 251
\headfont 50 \hfill 240 \hrulefill 224	\mbox	\sig . 224, 225, 231, 232 \signer 225, 227 \small 50 \supervisor 5
I \iflanguage 113, 120, 128, 139,	N \noindent . 215, 226, 240 \normalfont 50, 266	\supervisorname \frac{175}{231}
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccc} \mathbf{P} \\ \texttt{\packageWarning} & \dots & 196 \\ \texttt{\pagenumbering} & \dots & 252 \\ \texttt{\pagestyle} & \dots & & 49 \\ \end{array}$	\tableofcontents
K \kaupart 254, 271 \kauths@abstract 199, 250 \kauths@endabstract	\par 214, 240, 266 \paragraph 206, 208 \part 41, 43, <u>270</u> \path 260 \place 8, 29, 56	\thepaper
$ 200, 250 \\ \label{eq:contents} $$ \lambda = 194 \\ \lambda = 100 \\ \lambda =$	\prettylist 214, 240 \ProcessOptions 90	$f U$ \usepackage 48 $f V$
$\begin{array}{cccc} & \dots & \underline{243}, \ 246 \\ \texttt{keywordname} & \underline{117}, \ 206 \\ \texttt{keywords} & \dots & \dots \\ & 13, \ 34, \ 61, \ \underline{206}, \ 208 \\ \end{array}$	R \raggedleft 265 \rehead 51 \relax 90	\vanityquote 257 X \x 227